

Description

The invention relates to dental articulators for use with dental model casts, and methods associated therewith.

Correlators or articulators for use with casts of a dental model to develop prosthetic dentures or denture elements have been used for a number of years. These articulators range from a very simple device affording only fixed pivotal movement between a pair of casts to highly sophisticated and mechanically complex devices which are capable of simulating the full range of occlusal and masticatory registration unique to any patient. The relatively simple devices are generally inadequate to provide sufficiently accurately registered prosthetic restoration to avoid extensive visits with a dentist to obtain adjustments thereof while the very complex devices are time consuming to operate and require extensive training to use properly. In either situation, the costs incurred to the patient are substantial. Moreover, none of the prior art articulators permit disengagement of the casts from registration with one another without extensive realignment upon reengagement. Thus, a technician is usually forced to perform his work while the casts are mounted on the articulator. Such an environment is difficult to work in with speed and accuracy.

Each of the following listed U.S. Patents are directed to dental articulators which incorporate lockable ball and socket elements to afford pivotal movement and extensible members to afford translational movement: U.S. Patent Nos. 175,046, 530,524, 537,812, 565,326, 981,430, 1,736,006, 1,841,729, 2,571,280, 2,600,899, 2,608,762, 2,621,407, 2,765,533, 4,169,314, 4,196,518 and Belgian Patent No. 572,850.

An articulator which provides structure to effect a simple hinged movement without provision of mechanical structure for defining translatory movement or multi-axis pivotal movement is disclosed in U.S. Patent No. 2,430,177. Simulation of the full range of occlusal and masticatory registration is obtained by resiliently flexing the articulator. Such resiliency is afforded by the coil spring like configuration of a wire element defining each leg of two pairs of legs. For a well trained and experienced technician, the freedom of movement afforded by this articulator is sufficient to permit the formation and adjustments of most prosthetic dentures. Accurate use of the device is predicated upon the formation of elongated sockets within each cast of a dental model for receiving, capturing and retaining each of the four wire legs. The casts usually vary in overall physical size, depending upon the size of the patient's teeth to be simulated and the size and configuration of the base formed. To employ the articulator described in this patent, uniformity of spacing during formation of the casts is time consuming and requires an experienced

technician. No adjustment capability exists within the articulator itself to accommodate differences in spacing, as would be expected, as the size of a pair of casts vary in proportion to the physical size of the patient's jaws and the usually uniquely sized bases therefor. Other U.S. Patents describing articulators include U.S. Patents Nos. 824,096, 3,429,045 and 3,466,750.

All of the articulators described in the various patents enumerated above are primarily intended to be reused. Such reuse requires dismantling of the model dental casts therefrom, clean up of the articulators in preparation for reuse and periodic maintenance and repair; all of which activities are time consuming and contribute to overhead costs. Moreover, a substantial investment in articulators must be made in order to have sufficient stock of articulators to accommodate the rate of use, turnaround time and loss/damage rate.

US 4548581 discloses a disposable articulator for dental models. This articulator, however, does not provide sufficient flexibility to accommodate all required movements of the casts.

A primary object of the present invention is to provide a method of and an apparatus for operatively simulating the occlusal and masticatory relationships to be reintegrated in a dental model.

The invention also includes a method of mounting casts of a dental model to afford correlation of the casts throughout a full range of occlusal and masticatory registration.

According to the present invention there is provided an articulator for correlating the casts of a dental model, each of the casts including a mounting, said articulator having a pair of resiliently flexible brackets, each of said pair of brackets including a base member having opposed ends and a pair of arms, each arm of said pair of arms depending from one of said opposed ends to form a junction therebetween, each arm having an end, said articulator also having pivot means for pivoting one bracket with the other bracket at said end of each arm about a common pivot axis and also having means for interconnecting each of the casts with each of said pair of brackets respectively, each of said interconnecting means including a ball and socket joint wherein one member of said ball and socket joint is defined by said mounting and wherein the other member of said ball and socket joint is defined by said bracket and webs are disposed at each of said junctions for interconnecting the respective ones of said opposed ends and said arms, characterised in that:

(a) each of said opposed ends comprises a varying cross section that is reduced as it tapers from a central section of said base member toward the respective one of said junctions;

(b) each of said arms also comprises a varying cross section that is increased from the respec-

tive one of said junctions toward the respective one of said pivot means ;

(c) each of said webs has a thickness that increases from the respective one of said junctions towards said ends of said arm for encouraging flexing at the reduced cross sections of said arms and said opposed ends and discouraging flexing in the plane of said webs ; and

(d) whereby, flexing of the brackets at each of said junctions is encouraged after the angular relationship between each cast and the interconnected one of said pair of brackets has been fixed after registration of the casts relative to one another and during correlation of the casts.

Thus, the invention is directed to an inexpensive throw away articulator for dental models. The articulator includes a pair of brackets of flexible resilient material interconnected by snap fit hinges. A sphere is disposed at opposed ends of each pair of brackets. One of these spheres is locatable in a cavity formed in a mounting attached to each cast. Upon alignment of the casts with one another and development of the respective cavities, each sphere is adhesively attached within its respective cavity and the casts become hingedly attached to one another through the pair of brackets. To ensure flow of the adhesive adjacent a substantial part of the common surface area between each sphere and its cavity, a partially circumferential groove may be formed in each sphere. The groove aids in distributing the adhesive by promoting flow through capillary and wicking action. Simulating the full range of natural occlusal and masticatory registration is effected by a combination of pivotal movement about the hinge line and flexing of the respective brackets. Use of the snap fit hinge embodiment permits rapid disassembly and reassembly without the need of realignment to effect proper registration between the casts ; accordingly, a technician can readily perform his work on each of the casts or dental restoration in comfort by placing the cast to be worked upon a work surface or a holder.

The reduced cross section of each bracket of the pair of brackets proximate the junction between the base member and each of the arms, in combination with the web therebetween and the greater depth than width of the remaining portions of the base member and the arms, assists in focusing the major flex of the brackets at such junctions to assist and render more facile the simulation of the full range of occlusal and masticatory registration unique to the articulated dental model without modification or change of the alignment between the casts.

The present invention may be described with greater specificity and clarity with reference to the following drawings, in which :

Fig. 1 is a perspective view illustrating the articulator supporting a pair of full base casts of a dental model ;

Fig. 2 is a perspective view illustrating the articulator supporting a pair of quadrant base casts of a dental model ;

Fig. 3 is a partial cross sectional view illustrating the articulator attached to the casts of a dental model ;

Fig. 4 is a rear view of the interconnected brackets of the articulator ;

Fig. 5 illustrates the mountings securable to the articulator ;

Fig. 6 is a front view of one of the brackets ;

Fig. 7 is a top view of one of the brackets ;

Fig. 8 is a left side view of one of the brackets ;

Fig. 9 is a right side view of one of the brackets ; and

Fig. 10 illustrates simulation of the full range of occlusal and masticatory registration of the dental model by flexing of the articulator.

In the practice of prosthetic dentistry, one very important technical problem is the shaping and fitting of the restoration occlusal surfaces to register, meet and operatively cooperate with opposed surfaces in conformity with the established habits, idiosyncrasies and tooth facet inclinations of the user. These many factors peculiar to the individual have heretofore made proper operative correlation of the restoration with the associated dental elements almost invariably a matter susceptible of satisfactory resolution only through repetitious adjustments and modifications had in the dental chair after installation of the restoration. This occurs despite the use of fixed, even though adjustable, mechanically simulated axes of articulation, planes and arcs of occlusion, lines, planes and axes of symmetry and the like which fail to provide the full orbital range necessary for reconstitution of the natural dental relationships determinable from the traces and indices upon and established through use of the original dentures. To facilitate attainment of the desired operative registration between restorations and their associated dental elements and corrections in the dental chair, the present invention provides a device for laboratory use wherein the relationships to be reintegrated can be fully and accurately portrayed and operatively duplicated as a check mounting for the restoration.

The present invention is a device which hingedly, yieldably and separable associates for registration a pair of casts of a dental model in spaced opposition and throughout a full spherical orbit wherein every phase and condition of dental occlusive attitude may be exemplified.

In practice, the casts of both the upper and lower natural dentures along with the conditions thereof requiring restoration or correction are made by well known techniques. The casts are secured to the present invention to register in simulation of the natural relationships they portray when positioned in a substantially parallel relationship at one limit of the range

of relative movement, which position is determinable by the structure of the invention. Through the novel features, structure and characteristics of the invention correlating restoration or correction and the facet disposition and inclination thereof with the operative range and pattern of movement of the original dentures becomes possible.

Referring to Fig. 1, there is shown a complete full base dental model 10 having a pair of mating dental model casts 12 and 14 simulative of the original dentures and the condition requiring restoration or correction. Fig. 2 illustrates a complete quadrant base dental model 10' having a pair of mating dental model casts 12' and 14' simulative of the original dentures and the condition requiring restoration or correction. An articulator 16 is attached to the casts of either or each of dental models 10 and 10' as illustrated. The articulator maintains the casts positionally simulative of the natural relationships portrayed when substantially in parallel relationship at one limit of the range of relative movement. The articulator includes a pair of interconnecting elements or brackets 18 and 20 pivotally attached to one another and of resilient flexible material sufficient to accommodate relative movement about all axes and within all planes between the casts in either and each dental model in simulation of the operative range and pattern of the original dentures.

Referring jointly to Figs. 3, 4 and 5, further details of articulator 16 will be described. Each of brackets 18 and 20 includes a base member (22, 24), each of which base members supports a ball or sphere (26, 28). Each sphere may extend directly from its respective bracket or one or both of the spheres may be supported upon a straight or angled stalk (30, 32) extending from the respective bracket. Brackets 18 and 20 are pivotally joined to one another by pivot means 34, 36; preferably, the pivot means is of the snap fit type, as illustrated.

To mount articulator 16, mounting means 38 and 40 are attached to the rear faces of the respective casts. Each mounting means includes a semi-spherical or partially spherical depression disposed at the respective extremity. In example, mounting means 38 includes depression 42 and mounting means 40 includes depression 44, which depressions are sized to mate with spheres 26, 28. Spheres 26 and 28 are located within their respective depressions 42, 44 upon angular adjustment of the respective brackets to obtain the requisite spatial relationship therebetween; nominally, the brackets when joined, define an interior obtuse angle. To maintain the casts in the predetermined fixed spatial relationship to one another at one limit of the range of relative movement, an adhesive is applied intermediate the spheres and their respective depressions to fixedly secure the respective bracket in fixed angular orientation with respect to the mounting means. Pivotal movement of the casts is

effected by relative angular displacement between the joined brackets about the respect pivot means or hinged line. Translational movement in any plane and rotational movement about any axis of the casts with respect to one another is accommodated by the flexibility of brackets 16 and 18.

With the above general understanding of the basic function and structure of the invention, it may be beneficial to review and analyze certain nuances of the invention which render it of great practical benefit in the field of dental correction and restoration.

Each of mounting means 38 and 40 may be generally triangular in one plane to provide an apex (46, 48) within which a depression (42, 44) is formed. Base 50 of mounting means 38 may include a ridge or tab 52 for mechanical engagement with a slot 54 formed in the rear surface of cast 12. Base 56 of mounting means 40 includes tab 58 for engagement with slot 60 of cast 14. The resulting mechanical engagement, in combination with mastic or adhesive disposed therebetween, rigidly secures each mounting means to its respective cast.

During initial alignment and attachment of the brackets to the mounting means, maintenance of the casts in a predetermined relationship is critical. To simplify the manipulation during attachment, retaining fingers 62 extend from apex 46. These fingers are of resilient material and in the quiescent state, cant toward one another to provide snap retention for sphere 26 inserted within depression 42. Similar fingers 62 extend from apex 48 of mounting means 40 to engage sphere 28. With the use of such fingers, articulator 16 is retained in place during positioning of casts 12 and 14 and the need for manually retaining the articulator in place during such orientation of the casts is obviated. Upon achievement of the orientation of the casts, an adhesive, such as any one of the commercially available fast setting cyanoacrylate, aerobic or anaerobic adhesives, may be employed to secure each sphere within its respective depression.

To facilitate and promote flow of adhesive intermediate the common surfaces of each sphere and its receiving depression, a groove (64, 66) extending partially circumferentially about each sphere (26, 28) is formed. For best results, the groove in each sphere extends sufficiently about the sphere to have an end exposed irrespective of the angular orientation of the partially sphere enclosing mounting means. Upon application of a drop of the adhesive upon the sphere, the adhesive will flow along the edge of the depression and, by capillary or wicking action, will flow intermediate the adjacent opposing surfaces of the sphere and depression. The extent of flow is a function of the spacing therebetween provided and the viscosity of the adhesive. The groove promotes flow of adhesive from either and both ends along its full covered length due to capillary action. Moreover, flow of adhesive lateral of the groove intermediate the opposing sur-

face of the depression and sphere will also occur due to capillary action and wicking. The resulting bond formed upon curing of the adhesive extends essentially circumferentially about the opening of the depression and essentially along an arc into the depression, which arc may subtend an angle of approximately 180 degrees. Furthermore, some or all of the opposing spherical surface area common to both the depression and the sphere may become bonded to one another. The strength of the resulting bond has been found by testing to be greater than the fracture strength of the articulator and mounting means when they are made of plastic.

Alternatively, a mounting may be defined by a cylindrical cavity (not shown), such as may be formed by a conventional drill bit, or a partial spherical cavity, such as may be formed by a ball burr developed in the rear faces 68, 70 of casts 12, 14 respectively. Spheres 26 and 28 may be located within their respective cavities upon angular adjustment about the pivot axis of the respective brackets to obtain the requisite spatial relationship therebetween. To maintain the casts in the predetermined fixed spatial relationship to one another at one limit of the range of relative movement, an adhesive is applied intermediate the spheres and their respective cavities to fixedly secure the respective bracket in fixed angular orientation with respect to the casts. By having the spheres grooved, as described above, the adhesive bond formed is essentially commensurate with the opposed surface areas of the sphere and cavity for reasons stated above.

Articulator 16, as illustrated primarily in Fig. 4, is formed of a pair of mirror image brackets, each of which includes a base member (22, 24) and a pair of arms (72, 74 and 76, 78). Each base member supports a sphere (26, 28), which sphere may be, but is not necessarily, located laterally off set of the longitudinal axis of its respective base member and off center along the longitudinal axis such that upon mating of the brackets, a line drawn through the center of the spheres is orthogonal to a line representative of the pivot axis of the articulator. The extent of longitudinal offset of the spheres (26, 28) is a function of the dimensions attendant the pivot means (34, 36). That is, upon mating of the brackets at the pivot means, one bracket is offset from the other and the extent of offset is a function of the width of the arms (72, 74, 76, 78) at the pivot means. More particularly, sphere 26 is offset along base member 22 toward arm 72 by an amount equivalent to the width of arm 72 and sphere 28 is offset along base member 24 toward arm 78 by an amount equivalent to the width of arm 78. As arms 72 and 78 are duplicative of one another, the offset of each of spheres 26 and 28 is the same and both spheres lie upon a common line orthogonal to a line extending through the pivot axis upon attachment of the brackets to one another. As illustrated, the lateral offset and/or displacement from the base member of

each sphere may be effected by a supporting stalk (30, 32). Such stalk also has the further benefit of increasing the distance between the respective base member and the rear face of the attached cast to prevent interference therebetween on attachment and use of the articulator.

Figs. 6, 7, 8 and 9 illustrate one bracket (18), which bracket is duplicative of the other bracket (20) and the brackets are mirror images of one another. The arms of each bracket may be formed to include complementary elements to establish the pivot means. In example, one arm may include a slot 80 having a circular bearing surface 82 disposed along the slot. The other arm may include a pin 84 extending therefrom for retentative engagement with a corresponding slot and bearing surface. The pin, molded or otherwise formed upon fabrication of each of brackets, may be a simple shaft extending therefrom and terminated by an end plate 86. The space intermediate the arm and end plate is generally equivalent to the width of the arm to be disposed therebetween in slotted retention upon the shaft. Alternatively, each arm may include an aperture penetrably engagable by ancillary pin means or the like. Webs 88, 90 or other strengthening means may be employed at the interconnection between the base member and the extending arms to provide the requisite strength, yet minimize the mass and size of the articulator.

Preferably, the pivot means is of the snap fit type such that disengagement and reengagement of the brackets (and the supported casts) may be readily effected. Upon reengagement, the casts will be in registration with one another as no adjustments or parameters affecting registration are disturbed by disengagement/reengagement of the pivot means.

In a variant of articulator 16, the pivot means interconnecting the brackets is a flexible resilient membrane formed as part of the joined arms of the brackets. As noted above, each of the brackets are of flexible resilient material to permit manipulation of the casts through every phase and condition of dental occlusive attitude. And, the integrally formed joining membranes, being of substantially reduced thickness than the interconnected arms, serve in the nature of a hinge to permit pivotal movement of the brackets and attached casts relative to one another.

To focus the flexing of the brackets (18, 20) upon predetermined portions of the base members and the arms, the cross sections of the base members and the arms are non uniform along their respective lengths. The varying cross sections will be described with particular reference to Figs. 6, 7, 8 and 9. Base member 22 is of approximately equal height and depth at its center section 92, which center section supports sphere 26 directly or via stalk 30. The height of the center section tapers toward the opposed ends with a uniform or nonuniform taper. In one embodiment, the depth of the base member is substantially reduced

by the employment of curved surfaces 94, 96 to a depth at opposed end portions 98, 100 to half of that attendant center section 92. Surfaces 102, 104 of webs 88, 90, respectively, are essentially coincident with an extension of the surfaces of opposed end portions 98, 100. The opposite surfaces of the webs are recessed from the corresponding lateral sides of the base member and the arms, as illustrated in Fig. 4.

Arms 72, 74 have a width throughout their length of approximately that of the depth of opposed end portions 98, 100 of the base member. The depth of the arms attendant therein respective junctions with the base member is approximately the same as the width of the arms. However, the depth of the arms is increased by a factor of approximately two toward the pivot means and the change in depth is coincident with and formed by curved surfaces 106, 108. It may be noted that the thickness of webs 88, 90 toward the ends of the respective arms may increase coincident with the increasing depth of the arms as defined by surfaces 106, 108, respectively.

With the construction of brackets 18, 20 as depicted in Figs. 6, 7, 8 and 9, flexing of each of the brackets tends to be localized to the segments or locations of the brackets having reduced cross sections. Several benefits are achieved thereby. The ease of manipulating an articulated dental model is enhanced, particularly protrusive movement. Flexing of the ends of the arms attendant the pivot means (34, 36) is reduced which ends to minimize inadvertent disengagement of the pivot means. Flexing of center section 92 is reduced and distortion of the sphere/base member junction is reduced. Webs 88, 90 still serve their primary purpose of reducing the load concentration attendant the junctions between the base member and the respective arms and yet readily accommodate flexing of the respective reduced cross section segments of the base member and attached arms.

In operation, as illustrated by arrows 110, 112, 114, in Fig. 10, the mounted casts may be relatively approached, separated, traversed, protruded, retracted, included and rotated through every possible condition and position of occlusal and masticatory registration by simple manipulation to flex the brackets of the articulator. The resiliently yieldable brackets accommodate all deviation from the initial position of the casts to the extent necessary to fully manifest the operative variations of position inherent in the natural dentures.

After fabrication of a restoration and fitting of same to the appropriate cast, the casts may be manipulated to trace the normal occlusal registration of the dentures as determined by the facet inclinations of the natural teeth and the operative correlation of the restoration with the condition to be reintegrated may be checked for correction and precise fitting. The restoration may be removed from the respective cast with

or without physical severance of the casts from one another. By severing the brackets from one another at the pivot means, the casts readily become physically separated from one another and work on the restoration may become more facile. On completion of the work, the casts are rejoined to one another by rejoining the brackets at the pivot means. The severance capability, without an accompanying obligation or requirement to realign or even check the alignment of the casts, is of immense importance to the dental technician's efficiency. After severance, each cast may be worked on physically independent of the other and positioned upon or retained by a work surface which surface can support the cast at an orientation most favorable for the type and nature of the work to be done. And, a check of the accuracy of the work can be made in a matter of seconds by simply snapping the elements of the pivot means together to engage the two brackets with one another and then simulate and trace the paths of natural and masticatory registration.

While the principles of the invention have now been made clear in an illustrative embodiment, there will be immediately obvious to those skilled in the art many modifications of structure, arrangement, proportions, elements, materials and components, used in the practice of the invention which are particularly adapted for specific environments and operating requirements without departing from those principles.

Claims

1. An articulator (16) for correlating the casts (12, 14) of a dental model, each of the casts (12, 14) including a mounting (38, 40), said articulator (16) having a pair of resiliently flexible brackets (18, 20), each of said pair of brackets (18, 20) including a base member (22, 24) having opposed ends (98, 100) and a pair of arms (72, 74 and 76, 78), each arm of said pair of arms (72, 74 and 76, 78) depending from one of said opposed ends (98, 100) to form a junction therebetween, each arm having an end, said articulator also having pivot means (34, 36) for pivoting one bracket (18) with the other bracket (20) at said end of each arm about a common pivot axis and also having means for interconnecting each of the casts (12, 14) with each of said pair of brackets (18, 20) respectively, each of said interconnecting means including a ball and socket joint wherein one member of said ball and socket joint is defined by said mounting (38, 40) and wherein the other member of said ball and socket joint is defined by said bracket and webs (88, 90) are disposed at each of said junctions for interconnecting the respective ones of said opposed ends (98, 100) and said arms (72, 74 and 76, 78), characterised in that :

(a) each of said opposed ends (98, 100) com-



by the employment of curved surfaces 94, 96 to a depth at opposed end portions 98, 100 to half of that attendant center section 92. Surfaces 102, 104 of webs 88, 90, respectively, are essentially coincident with an extension of the surfaces of opposed end portions 98, 100. The opposite surfaces of the webs are recessed from the corresponding lateral sides of the base member and the arms, as illustrated in Fig. 4.

Arms 72, 74 have a width throughout their length of approximately that of the depth of opposed end portions 98, 100 of the base member. The depth of the arms attendant therein respective junctions with the base member is approximately the same as the width of the arms. However, the depth of the arms is increased by a factor of approximately two toward the pivot means and the change in depth is coincident with and formed by curved surfaces 106, 108. It may be noted that the thickness of webs 88, 90 toward the ends of the respective arms may increase coincident with the increasing depth of the arms as defined by surfaces 106, 108, respectively.

With the construction of brackets 18, 20 as depicted in Figs. 6, 7, 8 and 9, flexing of each of the brackets tends to be localized to the segments or locations of the brackets having reduced cross sections. Several benefits are achieved thereby. The ease of manipulating an articulated dental model is enhanced, particularly protrusive movement. Flexing of the ends of the arms attendant the pivot means (34, 36) is reduced which ends to minimize inadvertent disengagement of the pivot means. Flexing of center section 92 is reduced and distortion of the sphere/base member junction is reduced. Webs 88, 90 still serve their primary purpose of reducing the load concentration attendant the junctions between the base member and the respective arms and yet readily accommodate flexing of the respective reduced cross section segments of the base member and attached arms.

In operation, as illustrated by arrows 110, 112, 114, in Fig. 10, the mounted casts may be relatively approached, separated, traversed, protruded, retracted, included and rotated through every possible condition and position of occlusal and masticatory registration by simple manipulation to flex the brackets of the articulator. The resiliently yieldable brackets accommodate all deviation from the initial position of the casts to the extent necessary to fully manifest the operative variations of position inherent in the natural dentures.

After fabrication of a restoration and fitting of same to the appropriate cast, the casts may be manipulated to trace the normal occlusal registration of the dentures as determined by the facet inclinations of the natural teeth and the operative correlation of the restoration with the condition to be reintegrated may be checked for correction and precise fitting. The restoration may be removed from the respective cast with

or without physical severance of the casts from one another. By severing the brackets from one another at the pivot means, the casts readily become physically separated from one another and work on the restoration may become more facile. On completion of the work, the casts are rejoined to one another by rejoining the brackets at the pivot means. The severance capability, without an accompanying obligation or requirement to realign or even check the alignment of the casts, is of immense importance to the dental technician's efficiency. After severance, each cast may be worked on physically independent of the other and positioned upon or retained by a work surface which surface can support the cast at an orientation most favorable for the type and nature of the work to be done. And, a check of the accuracy of the work can be made in a matter of seconds by simply snapping the elements of the pivot means together to engage the two brackets with one another and then simulate and trace the paths of natural and masticatory registration.

While the principles of the invention have now been made clear in an illustrative embodiment, there will be immediately obvious to those skilled in the art many modifications of structure, arrangement, proportions, elements, materials and components, used in the practice of the invention which are particularly adapted for specific environments and operating requirements without departing from those principles.

Claims

1. An articulator (16) for correlating the casts (12, 14) of a dental model, each of the casts (12, 14) including a mounting (38, 40), said articulator (16) having a pair of resiliently flexible brackets (18, 20), each of said pair of brackets (18, 20) including a base member (22, 24) having opposed ends (98, 100) and a pair of arms (72, 74 and 76, 78), each arm of said pair of arms (72, 74 and 76, 78) depending from one of said opposed ends (98, 100) to form a junction therebetween, each arm having an end, said articulator also having pivot means (34, 36) for pivoting one bracket (18) with the other bracket (20) at said end of each arm about a common pivot axis and also having means for interconnecting each of the casts (12, 14) with each of said pair of brackets (18, 20) respectively, each of said interconnecting means including a ball and socket joint wherein one member of said ball and socket joint is defined by said mounting (38, 40) and wherein the other member of said ball and socket joint is defined by said bracket and webs (88, 90) are disposed at each of said junctions for interconnecting the respective ones of said opposed ends (98, 100) and said arms (72, 74 and 76, 78), characterised in that :

(a) each of said opposed ends (98, 100) com-



prises a varying cross section that is reduced as it tapers from a central section (92) of said base member (22, 24) toward the respective one of said junctions ;

(b) each of said arms (72, 74 and 76, 78) also comprises a varying cross section that is increased from the respective one of said junctions toward the respective one of said pivot means (34, 36) ;

(c) each of said webs has a thickness that increases from the respective one of said junctions towards said ends of said arm for encouraging flexing at the reduced cross sections of said arms (72, 74 and 76, 78) and said opposed ends (98, 100) and discouraging flexing in the plane of said webs (88, 90) ; and

(d) whereby, flexing of the brackets (18, 20) at each of said junctions is encouraged after the angular relationship between each cast (12, 14) and the interconnected one of said pair of brackets (18, 20) has been fixed after registration of the casts relative to one another and during correlation of the casts.

2. An articulator (16) as claimed in claim 1, characterised in that a central portion (92) of each of said base members (22, 24) intermediate said opposed ends (98, 100) is approximately square in cross section, and wherein each of said webs (88, 90) is flush with another side of said arms and said base member at surfaces (102, 104) at the respective one of the junctions.

3. An articulator (16) as claimed in claim 1 or claim 2, characterised in that said reduced cross section of each of said arms (72, 74 and 76, 78) is approximately square and wherein each of said webs (88, 90) is recessed from one side of said arms (72, 74 and 76, 78) and said base member (22, 24) at the respective one of said junctions.

4. A method for mounting casts of a dental model to afford correlation of the casts throughout a full range of occlusal and masticatory registration comprising : providing an articulator (16) for correlating the casts (12, 14) of a dental model, said articulator (16) having a pair of resiliently flexible brackets (18, 20), each of said pair of brackets (18, 20) including a base member (22, 24) having opposed ends (98, 100) and a pair of arms (72, 74 and 76, 78), each arm of said pair of arms depending from one of said opposed ends (98, 100) to form a junction therebetween, positioning and fixing the angular relationship between each cast (12, 14) and its respective brackets (18, 20), characterised in that

(a) each of said opposed ends (98, 100) has a varying cross section that is reduced as it tapers from a central section (92) of said base member (22, 24) toward the respective one of said junctions, each of said arms (72, 74 and 76, 78) also having a varying cross section that is increased

from the respective one of said junctions toward the respective one of pivot means (34, 36) interconnecting said brackets (18, 20) to one another, and in that webs (88, 90) are disposed at each of said junctions for interconnecting the respective ones of said opposed ends (98, 100) and said arms (72, 74 and 76, 78), each of said webs having a thickness that increases from the respective one of said junctions towards said ends of said arms for encouraging flexing at the reduced cross sections of said arms (72, 74 and 76, 78) and said opposed ends (98, 100) and discouraging flexing in a plane defined by said webs (88, 90) ;

(b) encouraging flexing of each of the brackets (18, 20) primarily at said junctions of each of the brackets (18, 20) having said reduced cross section to assist in the correlation of the casts (12, 14) throughout the full range of occlusal and masticatory registration ; and

(c) restraining flexing at said pivot means (34, 36) interconnecting said brackets (18, 20) to one another due to each of said webs (88, 90) having a thickness that increases from the respective one of said junctions towards said ends of said arms and restraining flexing in said plane defined by said webs (88, 90) also to assist in the correlation of the casts (12, 14) throughout the full range of occlusal and masticatory registration.

5. A method for reintegrating the casts of a dental model through a full range of occlusal and masticatory registration to develop a dental prosthetic device mounted on the casts, comprising : providing an articulator (16) for correlating the casts (12, 14) of a dental model, said articulator (16) having a pair of resiliently flexible brackets (18, 20), positioning the casts relative to one another at one end of the range of occlusal and masticatory registration to be reintegrated by adjusting the angular relationship between each mounting (38, 40) and its engaged bracket (18, 20) and adjusting the angular relationship about pivot means (34, 36) interconnecting said brackets (18, 20) to one another, fixing the angular relationship between each cast (12, 14) and its respective brackets (18, 20) ; flexing the brackets (18, 20) to translate and rotate the casts (12, 14) relative to one another to determine adjustments necessary to the model teeth or prosthetic devices or restorations formed thereon, each of said pair of brackets (18, 20) including a base member (22, 24) having opposed ends (98, 100) and a pair of arms (72, 74 and 76, 78), each arm of said pair of arms depending from one of said opposed ends (98, 100) to form junctions therebetween, characterised in that

(a) each of said opposed ends (98, 100) has a varying cross section that is reduced as it tapers from a central section (92) of said base member (22, 24) toward the respective one of said junctions, each of said arms (72, 74 and 76, 78) also



having a varying cross section that is increased from the respective one of said junctions toward the respective ones of pivot means (34, 36), and webs (88, 90) disposed at each of said junctions for interconnecting the respective ones of said opposed ends (98, 100) and said arms (72, 74 and 76, 78), each of said webs having a thickness that increases from the respective one of said junctions towards said ends of said arm for encouraging flexing at the reduced cross sections of said arms (72, 74 and 76, 78) and said opposed ends (98, 100) and discouraging flexing in a plane defined by said webs (88, 90) ;

(b) encouraging flexing of each of the brackets (18, 20) primarily at said junctions of each of the brackets (18, 20) having said reduced cross section to assist in the correlation of the casts (12, 14) throughout the full range of occlusal and masticatory registration ;

(c) restraining flexing at said pivot means (34, 36) interconnecting said brackets (18, 20) to one another due to each of said webs (88, 90) having a thickness that increases from the respective one of said junctions towards said ends of said arm, and restraining flexing in said plane defined by said web (88, 90) also to assist in the correlation of the casts (12, 14) throughout the full range of occlusal and masticatory registration ;

(d) alternatively to steps (b) and (c) pivoting the casts (12, 14) about pivot means (34, 36) through an obtuse angle or disengaging the brackets (18, 20) one from the other to permit unrestricted access to the cast (12, 14) for making the adjustments determined in said flexing step ;

(e) alternatively repivoting the casts (12, 14) into registration with one another or reengaging the brackets (18, 20) with one another depending upon whether said pivoting or disengaging step, respectively, were undertaken in step (d) ; and

(f) repeating said steps of flexing the brackets (18, 20) to translate and rotate the casts (12, 14) relative to one another to determine adjustments necessary to the model teeth or prosthetic devices or restorations formed thereon ; and either of the following : step (b) and step (c) ; or step (d) and step (e) ; until the model teeth prosthetic device or restorations are developed.

Patentansprüche

1. Artikulator (16) zum Korrelieren der Abgüsse (12, 14) eines Dentalmodells, wobei jeder Abgüsse (12, 14) eine Halterung (38, 40) umfaßt, der Artikulator (16) ein Paar von federn flexiblen Bügeln (18, 20) aufweist, jeder der beiden Bügeln (18, 20) einen Basisteil (22, 24) mit entgegengesetzten Enden (98, 100) und ein Paar von Armen (72, 74 und 76, 78) umfaßt,

jeder Arm des Paares von Armen (72, 74 und 76, 78) von einem der entgegengesetzten Enden (98, 100) absteht, um dazwischen einen Übergang zu bilden, jeder Arm ein Ende aufweist, der Artikulator auch mit Gelenkmitteln (34, 36) zum gelenkigen Verbinden eines Bügels (18) mit dem anderen Bügel (20) an dem besagten Ende eines jedes Armes um eine gemeinsame Gelenkachse versehen ist und auch Mittel zum Verbinden eines jeden der Abgüsse (12, 14) jeweils mit einem der beiden Bügel (18, 20) aufweist, jedes der Verbindungsmittel ein Kugelgelenk mit Kugel und Pfanne beinhaltet, wobei ein Teil des Kugelgelenks durch die Halterung (38, 40) definiert ist und der andere Teil des Kugelgelenks durch den Bügle (3) definiert ist und an jedem der Übergänge Aussteifungen (88, 90) zum Verbinden der jeweiligen entgegengesetzten Enden (98, 100) und Arme (72, 74 und 76, 78) angeordnet sind, dadurch gekennzeichnet, daß

(a) jedes der entgegengesetzten Enden (98, 100) einen veränderlichen Querschnitt aufweist, der abnimmt, während es sich von einem Mittelabschnitt (92) des Basisteiles (22, 24) zu dem betreffenden Übergang hin verjüngt,

(b) jeder der Arme (72, 74 und 76, 78) ebenfalls einen veränderlichen Querschnitt aufweist, der von dem jeweiligen Übergang zu dem jeweiligen Gelenkmittel (34, 36) zunimmt,

(c) jede der Aussteifungen eine Dicke hat, die von dem jeweiligen Übergang zu dem Ende des Armes zunimmt, um ein Biegen an den verminderten Querschnitten der Arme (72, 74 und 76, 78) und der entgegengesetzten Enden (98, 100) zu begünstigen und ein Biegen in der Ebene der Aussteifungen (88, 90) zu erschweren, und

(d) wodurch ein Biegen der Bügel (18, 20) an jedem der Übergänge, nachdem die Winkelbeziehung zwischen jedem Abguß (12, 14) und dem angeschlossenen Bügel des Bügelpaares (18, 20) nach dem gegenseitigen Anordnen der Abgüsse einander gegenüber fixiert worden ist und während des Korrelierens der Abgüsse, erleichtert wird.

2. Artikulator (16) nach Anspruch 1, dadurch gekennzeichnet, daß der Mittelteil (92) eines jeden Basisteiles (22, 24) zwischen den entgegengesetzten Enden (98, 100) einen etwa quadratischen Querschnitt aufweist und jede der Aussteifungen (88, 90) mit einer anderen Seite der Arme und des Basisteiles an Flächen (102, 104) an dem jeweiligen Übergang abschließt.

3. Artikulator (16) nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß der verminderte Querschnitt eines jeden Armes (72, 74 und 76, 78) etwa quadratisch ist und jede der Aussteifungen (88, 90) an dem jeweiligen Übergang von einer Seite der Arme (72, 74 und 76, 78) und des Basisteiles (22, 24) zurückgesetzt ist.

4. Verfahren zum Montieren von Abgüssen eines



Dentalmodells zwecks Ermöglichung des Korrelierens der Abgüsse über einen vollen Bereich der gegenseitigen Schließ- und Kaupositionen, wobei ein Artikulator (16) zum Korrelieren der Abgüsse (12, 14) eines Dentalmodells vorgesehen wird, der ein Paar von federnd flexiblen Bügeln (18, 20) aufweist, von denen jeder einen Basisteil (22, 24) mit entgegengesetzten Enden (98, 100) und ein Paar von Armen (72, 74 und 76, 78) umfaßt, von denen jeder von einem der entgegengesetzten Enden (98, 100) absteht, um dazwischen einen Übergang zu bilden, und wobei die Winkelbeziehung zwischen jedem Abguß (12, 40) und seinem jeweiligen Bügel (18, 20) eingerichtet und fixiert wird, dadurch gekennzeichnet, daß

(a) jedes der entgegengesetzten Enden (98, 100) einen veränderlichen Querschnitt aufweist, der abnimmt, während es sich von einem Mittelabschnitt (92) des Basisteils (22, 24) zu dem jeweiligen Übergang hin verjüngt, jeder der Arme (72, 74 und 76, 78) ebenfalls einen veränderlichen Querschnitt aufweist, der von dem jeweiligen Übergang zu dem ihm zugeordneten Gelenkmittel von die Bügel (18, 20) miteinander verbindenden Gelenkmitteln (34, 36) zunimmt, und an jedem der Übergänge Aussteifungen (88, 90) zum Verbinden der jeweiligen entgegengesetzten Enden (98, 100) und Arme (72, 74 und 76, 78) angeordnet sind, wobei jede der Aussteifungen eine Dicke aufweist, die von dem zugehörigen Übergang zu den Enden der Arme zunimmt, um ein Biegen an den verminderten Querschnitten der Arme (72, 74 und 76, 78) und der entgegengesetzten Enden (98, 100) zu begünstigen und ein Biegen in der durch die Aussteifungen (88, 90) definierten Ebene zu erschweren,

(b) ein Biegen eines jeden der Bügel (18, 20) hauptsächlich an den den verminderten Querschnitt aufweisenden Übergängen eines jeden der Bügel (18, 20) begünstigt wird, um das Korrelieren der Abgüsse (12, 14) über den vollen Bereich der gegenseitigen Schließ- und Kaupositionen zu unterstützen, und

(c) ein Biegen an den die Bügel (18, 20) miteinander verbindenden Gelenkmitteln (34, 36) dadurch beschränkt wird, daß eine jede der Aussteifungen (88, 90) eine von dem jeweiligen Übergang zu den Enden der Arme hin zunehmende Dicke aufweist, und ein Biegen in der durch die Aussteifungen (88, 90) bestimmten Ebene beschränkt wird, um ebenfalls das Korrelieren der Abgüsse über den vollen Bereich der gegenseitigen Schließ- und Kaupositionen zu unterstützen.

5. Verfahren zum Anpassen der Abgüsse eines Dentalmodells über einen vollen Bereich der gegenseitigen Schließ- und Kaupositionen zur Entwicklung einer auf den Abgüssen montierten zahnprothetischen Einrichtung, wobei ein Artikulator (16) zum Korrelieren der Abgüsse (12, 14) des Dentalmodells

vorgesehen wird, der ein Paar von federnd flexiblen Bügeln (18, 20) aufweist, die Abgüsse in bezug aufeinander durch Einstellen der Winkelbeziehung zwischen jeder Halterung (38, 40) und ihrem angeschlossenen Bügel (18, 20) und Einstellen der Winkelbeziehung um die Bügel (18, 20) miteinander verbindende Gelenkmittel (34, 36) an einem Ende des Bereichs der anzupassenden gegenseitigen Schließ- und Kaupositionen angeordnet werden, die Winkelbeziehung zwischen jedem Abguß (12, 14) und seinem jeweiligen Bügel (18, 20) fixiert wird, die Bügel (18, 20) zum geradlinigen Bewegen und zum Drehen der Abgüsse (12, 14) in Bezug aufeinander gebogen werden, um für die darauf gebildeten Modellzähne oder prothetischen Einrichtungen oder Rekonstruktionen nötige Anpassungen festzutellen, wobei jeder der beiden Bügel (18, 20) einen Basisteil (22, 24) mit entgegengesetzten Enden (98, 100) und ein Paar von Armen (72, 74 und 76, 78) umfaßt und jeder Arm des Armpaares von einem der entgegengesetzten Enden (98, 100) absteht, um dazwischen Übergänge zu bilden, dadurch gekennzeichnet, daß

(a) jedes der entgegengesetzten Enden (98, 100) einen veränderlichen Querschnitt hat, der abnimmt, während es sich von einem Mittelabschnitt (92) des Basisteils (22, 24) zu dem jeweiligen Übergang hin verjüngt, wobei jeder der Arme (72, 74 und 76, 78) ebenfalls einen veränderlichen Querschnitt hat, der von dem jeweiligen Übergang zu dem jeweiligen Gelenkmittel (34, 36) hin zunimmt, und an jedem der Übergänge Aussteifungen (88, 90) zum Verbinden der jeweiligen entgegengesetzten Enden (98, 100) und Arme (72, 74 und 76, 78) angeordnet sind, wobei jede der Aussteifungen eine Dicke hat, die von dem jeweiligen Übergang zu dem Ende des Armes zunimmt, um ein Biegen an den reduzierten Querschnitten der Arme (72, 74 und 76, 78) und der entgegengesetzten Enden (98, 100) zu begünstigen und ein Biegen in einer durch die Aussteifungen (88, 90) bestimmten Ebene zu erschweren ;

(b) ein Biegen eines jeden der Bügel (18, 20) hauptsächlich an den den verminderten Querschnitt aufweisenden Übergängen eines jeden Bügels (18, 20) begünstigt wird, um die Korrelierung der Abgüsse (12, 14) über den vollen Bereich der gegenseitigen Schließ- und Kaupositionen zu unterstützen,

(c) ein Biegen an den die Bügel (18, 20) miteinander verbindenden Gelenkmitteln (34, 36) dadurch erschwert wird, daß jede der Aussteifungen (88, 90) eine Dicke aufweist, die von dem jeweiligen Übergang zum Ende des Armes zunimmt, und ein Biegen in der durch die Aussteifung (88, 90) bestimmten Ebene erschwert wird, um das Korrelieren der Abgüsse (12, 14) über den vollen Bereich der gegenseitigen Schließ-



und Kaupositionen ebenfalls zu unterstützen ;
 (d) alternativ zu den Schritten (b) und (c) die Abgüsse (12, 14) über einen stumpfen Winkel um die Gelenkmittel geschwenkt werden oder die Bügel (18, 20) voneinander gelöst werden, um einen unbehinderten Zugang zu den Abgüssen (12, 14) für die Durchführung der im Biegeschritt festgestellten Anpassungen zu schaffen ;
 (e) alternativ abhängig davon, ob im Verfahrensschritt (d) jeweils der Schritt des Verschwenkens oder der Schritt des Lösens durchgeführt worden ist, die Abgüsse (12, 14) in einander gegenüberstehende Position zurück- geschwenkt oder die Bügel (18, 20) wieder miteinander in Eingriff gebracht werden ; und
 (f) die Schritte des Biegens der Bügel (18, 20) zum geradlinigen Bewegen und zum Drehen der Abgüsse (12, 14) in bezug aufeinander zwecks Feststellung von für die darauf gebildeten Modellzähne oder prothetischen Einrichtungen oder Rekonstruktionen nötigen Anpassungen und eine der Maßnahmen : Schritt (b) und Schritt (c) ; oder Schritt (d) und Schritt (e) ; wiederholt werden, bis die Modellzähne oder die prothetische Einrichtung oder die Rekonstruktionen entwickelt sind.

Revendications

1. Articulateur (16) pour faire correspondre les empreintes (12, 14) d'un modèle dentaire, chaque empreinte (12, 14) comprenant une ferrure (38, 40), ledit articulateur (16) comportant une paire de brides (18, 20) élastiquement flexibles, chacune desdites brides (18, 20) comportant une base (22, 24) aux deux extrémités opposées (98, 100) de laquelle est solidarisée une paire de bras (72, 74 et 76, 78), ledit articulateur (16) comportant en outre des moyens de pivotement (34, 36) pour faire pivoter une bride (18) avec l'autre bride (20) à l'extrémités de chaque bras autour d'un axe de pivotement commun et comportant également des moyens pour interconnecter chacune des empreintes (12, 14) avec chacune des brides (18, 20), chacun desdits moyens d'interconnexion comportant un joint à bille dont un élément est défini par ladite ferrure (38, 40) et l'autre élément par ladite bride, et des nervures (88, 90) sont disposées à chacune desdites jonctions pour interconnecter les extrémités respectives desdites extrémités (98, 100) avec lesdits bras (72, 74 et 76, 78), caractérisé en ce que :

a) chacune desdites extrémités opposées (98, 100) comporte une section transversale variable qui est réduite, allant diminuant à partir d'une section centrale (92) de ladite base (22, 24) vers chacune desdites jonctions ;

b) chacun desdits bras (72, 74 et 76, 78) comprend également une section transversale

variable qui va augmentant à partir de chacune desdites jonctions vers le moyen de pivotement (34, 36) correspondant ;

c) chacune desdites nervures (88, 90) a une épaisseur qui augmente à partir de la jonction correspondante vers lesdites extrémités desdits arbres pour faciliter la flexion au niveau des sections réduites desdits bras (72, 74 et 76, 78) et desdites extrémités opposées (98, 100) et pour empêcher la flexion dans le plan desdites nervures (88, 90) ; la flexion des brides (18, 20) à chacune desdites jonctions étant facilitée après que la relation angulaire entre chaque empreinte (12, 14) et la bride (18, 20) qui lui est interconnectée ait été fixée après enregistrement des empreintes l'une par rapport à l'autre et pendant qu'elles correspondent.

2. Articulateur (16) selon la revendication 1, caractérisé en ce qu'une partie centrale (92) de ladite base (22, 24) entre lesdites extrémités opposées (98, 100) présente une section transversale approximativement carrée, chacune desdites nervures (88, 90) étant située dans le même plan qu'un autre côté desdits bras et de ladite base à des surfaces (102, 104) situées à l'endroit de chaque jonction correspondante.

3. Articulateur selon la revendication 1 ou la revendication 2, caractérisé en ce que ladite section transversale réduite de chacun desdits bras (72, 74 et 76, 78) est approximativement carrée et chacune desdites nervures (88, 90) est en retrait par rapport à un côté desdits bras (72, 74 et 76, 78) et de la base (22, 24) à l'endroit de chacune desdites jonctions.

4. Procédé de montage d'empreintes pour modèle dentaire, en vue d'obtenir une corrélation entre les empreintes sur toute la gamme des emboîtements et des conditions masticatoires, comprenant les phases qui consistent à mettre en oeuvre un articulateur (16) pour faire correspondre les empreintes (12, 14) d'un modèle dentaire, ledit articulateur (16) comprenant deux brides (18, 20) élastiquement souples, chacune desdites brides (18, 20) comportant une base (22, 24) aux deux extrémités opposées (98, 100) de laquelle est solidarisée une paire de bras (72, 74 et 76, 78) ; à positionner et fixer la position angulaire relative entre chaque empreinte (12, 14) et sa bride correspondante (18, 20) ; caractérisé en ce que :

a) chacune desdites extrémités opposées (98, 100) présente une section transversale variable qui va diminuant à partir d'une section centrale (92) de ladite base (22, 24) vers chacune desdites jonctions, chacun desdits bras (72, 74 et 76, 78) présentant également une section transversale variable qui va augmentant de chacune desdites jonctions vers le moyen de pivotement correspondant (34, 36) reliant lesdites brides (18, 20) l'une à l'autre, et en ce que les nervures (88, 90) sont disposées à chacune desdites jonctions



pour interconnecter lesdites extrémités correspondantes (98, 100) et lesdits bras (72, 74 et 76, 78), chacune desdites nervures ayant une épaisseur qui augmente de la jonction correspondante vers l'extrémité dudit bras pour faciliter la flexion au niveau des sections transversales réduites desdits bras (72, 74 et 76, 78) et desdites extrémités opposées (98, 100) et pour empêcher la flexion dans le plan défini par lesdites nervures (88, 90) ;

b) on encourage la flexion de chacune des brides (18, 20) prioritairement auxdites jonctions de chacune des brides (18, 20) ayant une section transversale réduite de manière à faciliter la correspondance des empreintes (12, 14) sur toute la gamme des emboîtements et des conditions masticatoires, et

c) on limite la flexion au niveau desdits moyens de pivotement (34, 36) pour interconnecter lesdites brides (18, 20) l'une à l'autre à l'aide desdites nervures (88, 90) dont l'épaisseur augmente de la jonction correspondante vers les extrémités desdits bras, et on limite la flexion dans le plan défini par lesdites nervures (88, 90) également pour faciliter la corrélation des empreintes (12, 14) sur toute la gamme des emboîtements et des conditions masticatoires.

5. Procédé de réintégration des empreintes d'un modèle dentaire à travers une gamme complète d'emboîtements et de conditions masticatoires en vue de mettre au point un dispositif de prothèse dentaire monté sur les empreintes, comprenant les étapes qui consistent à : mettre en oeuvre un articulateur (16) pour faire correspondre les empreintes (12, 14) d'un modèle dentaire, ledit articulateur (16) ayant une paire de brides élastiquement souples (18, 20) ; positionner les empreintes l'une par rapport à l'autre à une extrémité de la gamme d'emboîtements et de conditions masticatoires à réintégrer en ajustant la position angulaire relative entre chaque ferrure (38, 40) et la bride correspondante (18, 20) qui y est engagée, et en ajustant la position angulaire relative au niveau des moyens de pivotement (34, 36) reliant lesdites brides (18, 20) l'une à l'autre ; fixer la position angulaire relative entre chaque empreinte (12, 14) et ses brides respectives (18, 20) ; courber les brides (18, 20) de manière à faire translater et pivoter les empreintes (12, 14) l'une par rapport à l'autre en vue de déterminer les ajustements nécessaires pour les dents modèles ou les dispositifs prothétiques ou les restaurations réalisées dessus ; chacune desdites paires de brides (18, 20) comportant une base (22, 24) aux deux extrémités opposées (98, 100) de laquelle est solidarisée une paire de bras (72, 74 et 76, 78) ; caractérisé en ce que :

a) chacune desdites extrémités opposées, (98, 100) présente une section transversale variable qui va diminuant à partir d'une section centrale

(92) de ladite base (22, 24) vers chacune desdites jonctions, chacun desdits bras (72, 74 et 76, 78) présentant également une section transversale variable qui va augmentant de chacune desdites jonctions vers le moyen de pivotement correspondant (34, 36) reliant lesdites brides (18, 20) l'une à l'autre, et en ce que les nervures (88, 90) sont disposées à chacune desdites jonctions pour interconnecter lesdites extrémités correspondantes (98, 100) et lesdits bras (72, 74 et 76, 78), chacune desdites nervures ayant une épaisseur qui augmente de la jonction correspondante vers l'extrémité dudit bras pour faciliter la flexion au niveau des sections transversales réduites desdits bras (72, 74 et 76, 78) et desdites extrémités opposées (98, 100) et pour empêcher la flexion dans le plan défini par lesdites nervures (88, 90) ;

b) on encourage la flexion de chacune des brides (18, 20) prioritairement auxdites jonctions de chacune des brides (18, 20) ayant une section transversale réduite de manière à faciliter la correspondance des empreintes (12, 14) sur toute la gamme des emboîtements et des conditions masticatoires ; et

c) on limite la flexion au niveau desdits moyens de pivotement (34, 36) pour interconnecter lesdites brides (18, 20) l'une à l'autre à l'aide desdites nervures (88, 90) dont l'épaisseur augmente de la jonction correspondante vers les extrémités desdits bras, et on limite la flexion dans le plan défini par lesdites nervures (88, 90) également pour faciliter la corrélation des empreintes (12, 14) sur toute la gamme des emboîtements et des conditions masticatoires.

d) en alternative aux étapes b) et c) on fait pivoter les empreintes (12, 14) au niveau des moyens de pivotement (34, 36) selon un angle obtus ou on désengage les brides (18, 20) l'une de l'autre pour permettre un accès non limité à l'empreinte (12, 14) en vue de faire les ajustements déterminés dans ladite étape de flexion ;

e) en alternative on fait pivoter à nouveau les empreintes (12, 14) de manière à les faire correspondre l'une à l'autre ou on réengage les brides (18, 20) l'une avec l'autre selon que l'une ou l'autre desdites étapes de pivotement ou de désengagement ont été accomplies à l'étape d) ;

f) on répète lesdites étapes de flexion des brides (18, 20) de manière à faire translater et pivoter les empreintes (12, 14) l'une par rapport à l'autre en vue de déterminer les ajustements nécessaires pour les dents modèles ou les dispositifs prothétiques ou les restaurations réalisées dessus ; et l'une des étapes b) et c) ; ou d) et e) ; jusqu'à ce que les dents modèles ou le dispositif prothétique ou les restaurations soient mis au point.