

INTRAMODAL SYNCHRONIZATION OF SURGICAL DATA

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to U.S. Provisional Application No.

- 5 61/801,282, titled “**SYSTEMS AND METHODS FOR PATHOLOGY TRACKING**” and filed on March 15, 2013, the entire contents of which is incorporated herein by reference.

This application also claims priority to U.S. Provisional Application No.

- 61/800,911, titled “**HYPERSPPECTRAL IMAGING DEVICE**” and filed on
10 March 15, 2013, the entire contents of which is incorporated herein by reference.

This application also claims priority to U.S. Provisional Application No.

61/801,746, titled “**INSERT IMAGING DEVICE**” and filed on March 15, 2013, the entire contents of which is incorporated herein by reference.

- 15 This application also claims priority to U.S. Provisional Application No. 61/818,255, titled “**INSERT IMAGING DEVICE**” and filed on May 1, 2013, the entire contents of which is incorporated herein by reference.

This application also claims priority to U.S. Provisional Application No.

- 61/800,155, titled “**PLANNING, NAVIGATION AND SIMULATION SYSTEMS AND METHODS FOR MINIMALLY INVASIVE THERAPY**” and filed on
20 March 15, 2013, the entire contents of which is incorporated herein by reference.

This application also claims priority to U.S. Provisional Application No.

- 61/924,993, titled “**PLANNING, NAVIGATION AND SIMULATION SYSTEMS AND METHODS FOR MINIMALLY INVASIVE THERAPY**” and filed on
25

January 8, 2014, the entire contents of which is incorporated herein by reference.

This application also claims priority to U.S. Provisional Application No. 61/798,867, titled **“SYSTEM AND METHOD FOR RECORDING THE TIME**
5 **COURSE OF TOOLS THROUGH A PROCEDURE”** and filed on March 15, 2013, the entire contents of which is incorporated herein by reference.

FIELD

The present disclosure relates to image guided medical procedures.
10 The present disclosure also relates to medical procedures involving tissue excision, identification and/or pathology analysis.

BACKGROUND

Imaging and imaging guidance is becoming a more significant
15 component of surgical care, from diagnosis of disease, monitoring of the disease, planning of the surgical approach, guidance during the procedure and follow-up after the procedure is complete, or as part of a multi-faceted treatment approach.

In many medical procedures tissue samples are excised or examined,
20 for example, during the surgical removal of a tumor. Currently in the fields of medical imaging and surgical diagnostics, taking a tissue sample and performing histopathology examination of it using a microscope, often with staining of that tissue, remains the gold standard for tissue diagnosis. This involves resection in a surgical suite and transfer of the sample to a pathology
25 laboratory.

However, this approach is fraught with problems and issues. For example, current methods of tissue analysis are unable to accurately and painlessly access tissue and can result in the possibility of seeding tumor cells through the biopsy process. It is also typically impractical to perform multiple
5 biopsies to enable proper examination of heterogeneous tumors.

Tissue samples are also often mislabeling during the process, which can result due to sample mix-up or labelling errors resulting in faulty diagnosis. Furthermore, pathology results may be discordant with the imaging results. Current workflow also often has a poor feedback loop to radiologists,
10 hindering them from improving their diagnostic accuracy for future cases. This also can result in an unnecessary delay between biopsy and pathology results, resulting in a reduction in positive patient outcomes.

SUMMARY

15 Systems and methods are provided in which local tissue diagnostic measurements are correlated with archival local tissue diagnostic data from prior tissue analyses to supplement diagnostic measurements with tissue analysis data from prior tissue analyses having similar local tissue diagnostic data. The tissue analysis data may include information such as pathology
20 data, outcome data, and diagnostic data. The archived local tissue diagnostic data and the tissue analysis data may be stored in a database, and employed for a wide variety of methods, involving preoperative, intraoperative, and/or postoperative phases of a medical procedure. Methods and systems are also provided for displaying, on a medical image shown in a user interface,
25 hyperlinked reference markers associated with tissue analyses, where the

reference markers are shown at locations corresponding to local tissue analyses, and where associated diagnostic data and/or tissue analysis may be viewed by selecting a given reference marker.

Accordingly, in one aspect, there is provided a computer implemented
5 method of correlating a local tissue diagnostic measurement with archival tissue analysis data, the method comprising:

obtaining local tissue diagnostic data associated with one or more local tissue diagnostic measurements performed on a subject;

accessing archival local tissue diagnostic data and tissue analysis
10 data associated with one or more prior local tissue analyses;

comparing, according to pre-selected similarity criteria, the local tissue diagnostic data associated with the one or more local tissue diagnostic measurements and the archival local tissue diagnostic data associated with the one or more prior local tissue analyses;

15 identifying one or more similar prior local tissue analyses having archival local tissue diagnostic data satisfying the pre-selected similarity criteria; and

providing tissue analysis data associated with the one or more similar prior local tissue analyses.

20 In another aspect, there is provided a system for correlating a local tissue diagnostic measurement with archival tissue analysis data, comprising:

a control and processing system comprising one or more processors and memory coupled to said one or more processors, said memory storing instructions, which, when executed by said one or more processors, causes

25 said one or more processors to perform operations comprising:

obtaining local tissue diagnostic data associated with one or more local tissue diagnostic measurements performed on a subject;

accessing archival local tissue diagnostic data and tissue analysis data associated with one or more prior local tissue analyses;

5 comparing, according to pre-selected similarity criteria, the local tissue diagnostic data associated with the one or more local tissue diagnostic measurements and the archival local tissue diagnostic data associated with the one or more prior local tissue analyses;

 identifying one or more similar prior local tissue analyses having
10 archival local tissue diagnostic data satisfying the pre-selected similarity criteria; and

 providing tissue analysis data associated with the one or more similar prior local tissue analyses.

 In another aspect, there is provided a computer implemented method
15 of displaying tissue analysis information on a user interface, the method comprising:

 obtaining a medical image of at least a portion of a subject and displaying the medical image on the user interface;

 obtaining local tissue information corresponding to one or more local
20 tissue analyses performed on the subject;

 obtaining location data identifying a location corresponding to each local tissue analysis, wherein the location data is spatially registered to the medical image;

 displaying one or more reference markers in the medical image,
25 wherein:

each reference marker is associated with one of the local tissue analyses; and

each reference marker is displayed, in the medical image, at the location at which its associated local tissue analysis was performed;

5 receiving input from an operator identifying a selected reference marker associated with a selected local tissue analysis, thereby identifying selected local tissue information; and

presenting at least a portion of the selected local tissue information associated with the selected local tissue analysis.

10 In another aspect, there is provided a system for displaying tissue analysis information on a user interface, comprising:

a control and processing system interfaced with a display device, said control and processing system comprising one or more processors and memory coupled to said one or more processors, said memory storing

15 instructions, which, when executed by said one or more processors, causes said one or more processors to perform operations comprising:

obtaining a medical image of at least a portion of a subject and displaying the medical image on the user interface;

obtaining local tissue information corresponding to one or more local
20 tissue analyses performed on the subject;

obtaining location data identifying a location corresponding to each local tissue analysis, wherein the location data is spatially registered to the medical image;

displaying one or more reference markers in the medical image,
25 wherein:

each reference marker is associated with one of the local tissue analyses; and

each reference marker is displayed, in the medical image, at the location at which its associated local tissue analysis was performed;

5 receiving input from an operator identifying a selected reference marker associated with a selected local tissue analysis, thereby identifying selected local tissue information; and

presenting at least a portion of the selected local tissue information associated with the selected local tissue analysis.

10 In another aspect, there is provided a computer implemented method of correlating preoperative tissue analysis data with archival tissue analysis data from one or more prior medical procedures, the method comprising:

obtaining preoperative tissue analysis data associated with a subject;

15 accessing archival tissue analysis data associated with one or more prior medical procedures;

accessing time-dependent medical procedure data recorded during the one or more prior medical procedures;

20 comparing, according to pre-selected similarity criteria, the preoperative tissue analysis data and the archival tissue analysis data associated with the one or more prior medical procedures;

identifying one or more similar prior medical procedures having archival tissue analysis data satisfying the pre-selected similarity criteria; and

25 processing the time-dependent medical procedure data associated with the one or more similar prior medical procedures to replay at least a

portion of the medical procedure.

In another aspect, there is provided a system for correlating preoperative tissue analysis data with archival tissue analysis data from one or more prior medical procedures, comprising:

5 a control and processing system comprising one or more processors and memory coupled to said one or more processors, said memory storing instructions, which, when executed by said one or more processors, causes said one or more processors to perform operations comprising:

 obtaining preoperative tissue analysis data associated with a
10 subject;
 accessing archival tissue analysis data associated with one or more prior medical procedures;

 accessing time-dependent medical procedure data recorded during the one or more prior medical procedures;

15 comparing, according to pre-selected similarity criteria, the preoperative tissue analysis data and the archival tissue analysis data associated with the one or more prior medical procedures;

 identifying one or more similar prior medical procedures having archival tissue analysis data satisfying the pre-selected similarity criteria; and
20 processing the time-dependent medical procedure data associated with the one or more similar prior medical procedures to replay at least a portion of the medical procedure.

In another aspect, there is provided a computer implemented method of suggesting one or more steps of a surgical plan based on archival surgical
25 plan data from one or more prior medical procedures, the method comprising:

obtaining tissue analysis data associated with a subject;
accessing archival tissue analysis data associated with one or more
prior medical procedures;
accessing surgical plan data associated with the one or more prior
5 medical procedures;
comparing, according to pre-selected similarity criteria, the tissue
identification data and the archival tissue analysis data associated with the
one or more prior medical procedures;
identifying one or more similar prior medical procedures having
10 archival tissue analysis data satisfying the pre-selected similarity criteria; and
processing the surgical plan data associated with the one or more
similar prior medical procedures to generate one or more steps of a
suggested surgical plan; and
communicating the one or more steps of the suggested surgical
15 plan.

In another aspect, there is provided a system for suggesting one or
more steps of a surgical plan based on archival surgical plan data from one or
more prior medical procedures, comprising:

a control and processing system comprising one or more processors
20 and memory coupled to said one or more processors, said memory storing
instructions, which, when executed by said one or more processors, causes
said one or more processors to perform operations comprising:
obtaining tissue analysis data associated with a subject;
accessing archival tissue analysis data associated with one or more
25 prior medical procedures;

accessing surgical plan data associated with the one or more prior medical procedures;

comparing, according to pre-selected similarity criteria, the tissue identification data and the archival tissue analysis data associated with the
5 one or more prior medical procedures;

identifying one or more similar prior medical procedures having archival tissue analysis data satisfying the pre-selected similarity criteria; and

processing the surgical plan data associated with the one or more similar prior medical procedures to generate one or more steps of a
10 suggested surgical plan; and

communicating the one or more steps of the suggested surgical plan.

In another aspect, there is provided a computer implemented method of correlating a preoperative surgical plan with archival surgical plan data from
15 one or more prior medical procedures, the method comprising:

obtaining preoperative surgical plan data associated with a medical procedure to be performed on a subject;

accessing outcome data associated with one or more prior medical procedures;

20 accessing archival surgical plan data employed during the one or more prior medical procedures;

comparing, according to pre-selected similarity criteria, the preoperative surgical plan data and the archival surgical plan data associated with the one or more prior medical procedures;

25 identifying one or more similar prior medical procedures having

archival surgical plan data satisfying the pre-selected similarity criteria; and
providing outcome data associated with the one or more similar prior
medical procedures.

In another aspect, there is provided a system for correlating a
5 preoperative surgical plan with archival surgical plan data from one or more
prior medical procedures, comprising:

a control and processing system comprising one or more processors
and memory coupled to said one or more processors, said memory storing
instructions, which, when executed by said one or more processors, causes
10 said one or more processors to perform operations comprising:

obtaining preoperative surgical plan data associated with a medical
procedure to be performed on a subject;

accessing outcome data associated with one or more prior medical
procedures;

15 accessing archival surgical plan data employed during the one or
more prior medical procedures;

comparing, according to pre-selected similarity criteria, the
preoperative surgical plan data and the archival surgical plan data associated
with the one or more prior medical procedures;

20 identifying one or more similar prior medical procedures having
archival surgical plan data satisfying the pre-selected similarity criteria; and
providing outcome data associated with the one or more similar prior
medical procedures.

method of performing tissue analyses while performing a tissue
25 resection procedure on a subject, the method comprising:

during a tissue resection procedure, performing, with a spatially tracked local tissue analysis device, a plurality of local tissue analyses, such that different local tissue analyses correspond to different tissue locations that are exposed during the resection procedure;

5 employing tracking data associated with the spatially tracked local tissue analysis device to determine, in a reference frame spatially registered to a medical image of the subject, the location data corresponding to each local tissue analysis;

 recording local tissue diagnostic data from each local tissue analysis
10 in association with its corresponding location data;

 constructing a spatial profile of the resected tissue by correlating the local tissue diagnostic data with the location data.

 In another aspect, there is provided a method of performing intraoperative tissue analysis while performing a tissue resection procedure
15 on a subject, the method comprising:

 during a tissue resection procedure:

 performing a local ex-vivo diagnostic measurement on a biopsy sample of a tumor, thereby obtaining a reference measurement associated with tumor tissue; and

20 during subsequent tissue resection:

 intermittently performing local in-vivo diagnostic measurements on exposed tissue; and

 comparing the reference measurement to each in-vivo measurement to identify the presence or absence of tumor tissue in the
25 exposed tissue.

A further understanding of the functional and advantageous aspects of the disclosure can be realized by reference to the following detailed description and drawings.

5

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments will now be described, by way of example only, with reference to the drawings, in which: **FIG. 1** shows an exemplary navigation system to support minimally invasive access port-based surgery.

FIG. 2 is an illustration showing various components of system for performing image-guided port based medical procedures.

FIG. 2 shows a human brain into which an access port has been inserted, establishing an open conduit for providing access to tissue within the brain.

FIG. 4A is a flow chart illustrating the processing steps involved in a port-based surgical procedure using a navigation system.

FIG. 4B is a flow chart illustrating the processing steps involved registering a patient to an intraoperative reference frame.

FIG. 5 shows an example implementation of computer control system for implementing the various methods disclosed herein.

FIG. 6A is an illustration showing an axial view of the brain in which a tumor is present.

FIGS. 6B-6D illustrate an example user interface, in which a regional image has reference markers shown at the locations corresponding to tissue analyses.

FIG. 7 is a flow chart illustrating an example method of displaying

location-specific and hyperlinked tissue analysis information in a user interface.

FIGS. 8A and 8B illustrate the selectable display, in a user interface, of tissue analysis information identified by searching a tissue analysis database.

5 **FIG. 9** is a diagram showing an example embodiment involving four aspects of patient care.

FIG. 10 is a flow chart demonstrating an example method of identifying similar prior tissue analyses by performing a similarity analysis between local diagnostic data and archival local tissue diagnostic data stored in a tissue
10 analysis database.

FIG. 11 is a flow chart illustrating a method of selecting suitable diagnostic modalities for use during a medical procedure.

FIG. 12 is a flow chart illustrating an example method of determining similarity among different tissue regions based on spectroscopic
15 measurements.

FIG. 13 is flow chart illustrating an example method of obtaining outcome data associated with a prior medical procedures having a similar surgical plan to a proposed medical procedure.

FIG 14A and 14B are example search algorithms that may be
20 employed to search archival data sets.

FIG. 15 is a diagram showing an example embodiment involving specific utilization of regional imaging, point imaging, and pathology data to link imaging and pathology results in a single patient, and linking results across subjects.

25 **FIG. 16** is a diagram showing an example embodiment involving

specific utilization of preoperative imaging, pathology, and point source imaging data to facilitate decision making for treatment and surgical planning.

FIG. 17 is a diagram showing an example embodiment involving specific utilization of preoperative imaging to facilitate decision making for tissue differentiation and treatment.

FIGS. 18A and 18B illustrate views of tissue, from the perspective of looking through an access port.

FIG. 18C is an illustration of a probe interrogating an island of tissue through an access port.

FIG. 19 is a diagram demonstrating how multiple tissue metrics are utilized to characterize tissue of interest.

FIG. 20 is a diagram showing an example embodiment involving specific utilization of postoperative imaging in the context of expected outcomes.

DETAILED DESCRIPTION

Various embodiments and aspects of the disclosure will be described with reference to details discussed below. The following description and drawings are illustrative of the disclosure and are not to be construed as limiting the disclosure. Numerous specific details are described to provide a thorough understanding of various embodiments of the present disclosure. However, in certain instances, well-known or conventional details are not described in order to provide a concise discussion of embodiments of the present disclosure.

As used herein, the terms, “comprises” and “comprising” are to be

construed as being inclusive and open ended, and not exclusive. Specifically, when used in the specification and claims, the terms, “comprises” and “comprising” and variations thereof mean the specified features, steps or components are included. These terms are not to be interpreted to exclude
5 the presence of other features, steps or components.

As used herein, the term “exemplary” means “serving as an example, instance, or illustration,” and should not be construed as preferred or advantageous over other configurations disclosed herein.

As used herein, the terms “about” and “approximately” are meant to
10 cover variations that may exist in the upper and lower limits of the ranges of values, such as variations in properties, parameters, and dimensions. In one non-limiting example, the terms “about” and “approximately” mean plus or minus 10 percent or less.

Unless defined otherwise, all technical and scientific terms used herein
15 are intended to have the same meaning as commonly understood to one of ordinary skill in the art. Unless otherwise indicated, such as through context, as used herein, the following terms are intended to have the following meanings:

As used herein, the phrase “medical instrument” refers to a tool,
20 instrument, or other implement employed during a medical procedure. A medical instrument may be provided in various forms, such as, but not limited to, a handheld or robotically positioned tool, or a component that is attached to, or inserted into, a subject during a surgical or medical procedure. Non-limiting examples of medical instruments include, but are not limited to,
25 scalpels, bi-polar devices, suction devices, cutting devices, clamping devices,

access ports, and forceps.

As used herein, the phrase "operator" refers to a user, medical practitioner, surgeon, imaging technician, or other individual or group of individuals involved in operating medical instruments, devices and equipment
5 during a medical procedure.

As used herein, the phrase "tracking system" refers to a system configured to track the position and/or orientation of one or more objects, such as locations of a subject and/or surgical instruments. In some embodiments, the tracking system may be configured to track the position and/or orientation
10 of an imaging device (such as an optical camera). A tracking system may also be employed to track the position and/or orientation of an access port or other component that is attached to, or inserted into, a subject or subject. In one example, a tracking system may employ a pair of infrared cameras to track the position and orientation of active or passive infrared spheres (fiducials)
15 attached to one or more objects, such as the Polaris[®] system from NDI.

As used herein, the phrase "navigation system" refers to a system that processes and spatially registers preoperative image data to an intraoperative reference frame, and displays the position and orientation of one or more tracked items relative to the preoperative image data. A navigation system
20 may interface with, or include, a tracking system, in order to track the items. In some example implementations, hardware associated with the navigation system may include a computer system, a display, and a tracking system.

As used herein, the phrase "phase of the medical procedure" refers to a given step, or set of sequential steps, within a medical procedure. In another
25 example, a phase of a medical procedure need not be a given step or set of

sequential steps in a procedure, but may relate to the use of a specific tool or set of tools within a given step of a medical procedure.

As used herein, the phrase “intraoperative” refers to an action, process, method, event or step that occurs or is carried out during at least a portion of a medical procedure. Intraoperative, as defined herein, is not limited to
5 surgical procedures, and may refer to other types of medical procedures, such as diagnostic and therapeutic procedures.

As used herein, the phrase “access port” refers to a cannula, conduit, sheath, port, tube, or other structure that may be inserted into a subject in
10 order to provide access to internal tissue, organs, or other biological substances. In some embodiments an access port may directly expose internal tissue, for example via an opening or aperture at a distal end thereof, and/or via an opening or aperture at an intermediate location along a length thereof. In other embodiments an access port may provide indirect access, via
15 one or more surfaces that are transparent, or partially transparent, to one or more forms of energy or radiation, such as, but not limited to, electromagnetic waves and acoustic waves.

As used herein, the phrase “local tissue analysis” refers to an action taken to, or event associated with, the local analysis of tissue during, and
20 optionally after, a medical procedure. In one example, a local tissue analysis may involve obtaining a biopsy sample during a medical procedure, and performing an analysis on the biopsy sample either intraoperatively or postoperatively. In another example, a local tissue analysis may involve obtaining a diagnostic measurement of a local region (e.g. a subset of a
25 region associated with a medical image, or a subset of an anatomic region

within a subject). It will be understood that a local tissue analysis involving a diagnostic measurement may be performed to obtain one or more spot or point measurements (optionally combining a plurality of local spot or point measurements to construct an image) or an image of a local tissue region.

5 As used herein, the phrase “tissue analysis data” refers to data obtained after having performed a local tissue analysis. For example, in the case in which a local tissue analysis is performed as a biopsy with postoperative analysis, the tissue analysis data may be measurements (e.g. cell morphology, cell type, microscopy images, etc.) obtained when
10 performing the analysis of the biopsy sample. In the case in which a local tissue analysis is performed to obtain a local diagnostic image, the tissue analysis data may include the local image data. Non-limiting examples of local diagnostic images include, for example, a white light image, a hyperspectral image, a polarization-sensitive image, an optical coherence tomography
15 image, an ultrasound image, and a magnetic resonance imaging image. In another non-limiting example, in the case when a local tissue analysis is performed to obtain a spot or point measurement within a region of interest, the local tissue analysis data may be a spectrum, such as a Raman spectrum or an optical spectrum.

20 As used herein, the phrase “local”, when used in association with a diagnostic measurement, refers to a diagnostic measurement obtained at or near a tissue or region of interest. For example, a local diagnostic measurement may be made with a local diagnostic non-imaging device, such as a Raman probe, or with a local diagnostic imaging device, such as an
25 exoscope or magnetic resonance imaging probe. A local diagnostic

measurement has a location associated therewith, where the location may be shown in a regional or global image of a subject. The phrase “regional”, when used in association with a diagnostic image, refers to an image including both a tissue region of interest, and other surrounding tissue structure.

5 As used herein, the phrase “diagnosis data” refers to data or information associated with the diagnosis of a medical condition, such as a type of tumor or a stage of a tumor. Diagnosis data may be based on, or include, pathology data.

 As used herein, the phrase “pathology data” refers to information
10 associated with pathology testing of a tissue sample. Pathology data may include a pathology report. In another non-limiting example, pathology data may include information associated with one or more pathological tissue types identified from the local tissue analysis such as, but not limited to, tumor type, tumor stage, tumor size, and tumor cell information.

15 As used herein, the phrase “subject” refers to human or non-human subjects or patients.

 Some example embodiments of the present disclosure provide methods and systems that involve the integration of imaging and tissue analysis. In some example embodiments a combination of regional, and local
20 imaging, and tissue biopsy or local analysis, may be employed to inform decision making and treatment selection during or after a medical procedure. Some example embodiments described below provide systems and methods for integrating and updating preoperative and intraoperative plans based on prior medical procedures having, for example, similar local tissue analysis
25 data, similar pathology data, and/or similar surgical plans.

In some example embodiments described below, systems and methods are provided in which three-dimensional positions (between or within subjects) associated with local tissue analyses (e.g. biopsy or in-vivo measurements) are associated with preoperative or intraoperative images, and/or with information associated with prior tissue analyses, such as prior outcomes (e.g. subject outcomes and/or economic outcomes), archival tissue analysis, and/or pathology data (which may be stored in an electronic data base including subject information). Furthermore, in some embodiments information recorded during previous medical procedures may be employed to assist with the performing or planning of a medical procedure.

While many of the examples and illustrations provided in the present disclosure relate to minimally invasive neurological procedures, such as procedures involve resection of brain tumors, it will be understood that the scope of the present disclosure is intended to include and be applicable to, a wide range of medical procedures as further described below.

Example Minimally Invasive System for Performing Image-Guided Medical Procedure

FIGS. 1 and 2 illustrate an example automated system for performing various embodiments of the present disclosure, providing a non-limiting example pertaining to a computer-assisted minimally-invasive neurological surgical procedure employing an access port. **FIG. 1** illustrates a perspective view of a minimally invasive port based surgical procedure. Surgeon **101** conducts a minimally invasive access port-based surgery on a subject **102** in an operating room (OR) environment. An automated system including an

equipment tower, cameras, displays, and tracked instruments assists surgeon **101** during the medical procedure. One or more operators **103** may also present to operate, control and provide assistance for the one or more aspects of the system.

5 **FIG. 2** illustrates various example components of an automated system for assisting a medical procedure involving an access port. The system includes one or more imaging devices (for example, volumetric, whole organ, regional, point, or tool based), surgical guidance devices, software systems, databases, tissue specimen handling devices, and tracked medical
10 instruments (e.g. surgical tools) as an integrated system. As described in various example embodiments below, the system may be configured to correlate three-dimensional positions on or within subjects with pathology samples, preoperative or intraoperative images (volumetric, regional, point or tool based), and patient and economic outcomes, and an electronic data base
15 of patient information.

The example automated system includes an automated robotic arm **105**, which supports an optical video scope **110** (and associated illumination), video display **115** for displaying a video image from optical video scope **110**, navigation display **116** for providing a navigation user interface, a tracking
20 device **120** for tracking various medical instruments within the surgical field, and a control and processing unit **400** for controlling various devices (such as the robotic arm **105**) and providing surgical navigation. A secondary display may provide output of the tracking device **120**. The output may be shown in axial, sagittal and coronal views as part of a multi-view display.

25 The example embodiment shown illustrates control and processing

system **400** as residing in an equipment tower in a single tower configuration, connected to dual displays **115** and **116**. However, it will be understood that other configurations may alternatively be employed (for example, a dual tower configuration and/or a single display configuration). Furthermore, an
5 equipment tower may also configured with a UPS (universal power supply) to provide for emergency power, in addition to a regular AC adapter power supply.

As described in detail below, in some embodiments, control and processing system **400** may include, or may be interfaced with, one or more
10 recording devices or software modules that provide real-time recording of one or more aspects of the medical procedure. For example, the system may be configured to capture one or more of audio, video, sensory and multi-modal (e.g. CT, MR, US, etc.) inputs from different sources. All relevant data may be received via one or more recording devices (for example, stored in the
15 equipment tower) and stored in memory by a recording module. The one or more aspects of the medical procedure may be automatically recorded from the outset of the procedure, or may be controlled by an operator and/or administrator. In other embodiments, the procedure may be automatically recorded (by default), but there may be an option to override or delete the
20 recording during the medical procedure or after the medical procedure has been completed.

Referring again to **FIG. 2**, a subject's head is held in place by a head holder **125**, and inserted into the head is an access port **130** and introducer **135** (having fiducial markers attached thereto). Introducer **135** is shown
25 received within access port **130** in the figure, and is tracked using tracking

system **120**. A guide clamp **133** for holding access port **130** may be provided. Guide clamp **133** can optionally engage and disengage with access port **130** without needing to remove the access port from the subject. In some embodiments, access port **130** can slide up and down within clamp **133** while
5 in the closed position. A locking mechanism may be attached to or integrated with guide clamp **133**, and can optionally be actuated with one hand, as described further below.

Articulated arm **134** may be provided with an attachment point to hold guide clamp **133**. Articulated arm **134** may have up to six degrees of freedom
10 to position guide clamp **133**. Articulated arm **134** may be attached or attachable to a point based on subject head holder **125**, or another suitable subject support, to ensure when locked in place, guide clamp **133** cannot move relative to the subject's head. The interface between guide clamp **133** and articulated arm **134** may be flexible, or optionally locked into place.
15 Flexibility is desired so the access port can be moved into various positions within the brain, but still rotate about a fixed point.

An example of such a linkage that can achieve this function is a slender bar or rod. When access port **130** is moved to various positions, the bar or rod will oppose such a bend, and move the access port **130** back to the
20 centered position. Furthermore, an optional collar may be attached to the linkage between the articulated arm, and the access port guide, such that when engaged, the linkage becomes rigid. Currently, no such mechanisms exist to enable positioning access port **130** in such a manner.

The position of the subject may be initially determined and/or
25 continuously tracked intraoperatively by tracking system **120**. A set of

preoperative images associated with the anatomy of interest of the subject may be obtained prior to surgery. These images may be intraoperatively registered to the subject, for example, by way of surface matching, sets of known touch points (e.g., tip of nose, temple, and ears) and/or fiduciary
5 markings that can be identified on the subject and in the associated images. These points or surfaces are registered to the tracking coordinate frame through a defined registration process. Once registered, medical instruments, and the associated subject images can be tracked in real-time, and shown in various manners on a computer monitor.

10 The example automated system illustrated in **FIG. 2** is configured for the application of minimally invasive brain surgery, using an access port to provide a conduit within the head, allowing access to internal brain tissue for surgical, therapeutic, or diagnostic applications. The figure shows an intracranial access port which may be employed in neurological procedures in
15 order to provide access to internal tissue pathologies, such as tumors. One example of an intracranial access port is the BrainPath™ surgical access port provided by NICO, which may be inserted into the brain via an obturator (introducer) with an atraumatic tip. Such an access port may be employed during a surgical procedure, by inserting the access port via the obturator that
20 is received within the access port to access an internal surgical site.

FIG. 3 illustrates the use of an access port, showing a human brain **140** into which an access port **130** has been inserted, thereby establishing an open conduit providing access to tissue deep within the brain. Surgical instruments may then be inserted within the lumen of the access port in order
25 to perform surgical, diagnostic or therapeutic procedures, such as resecting

tumors as necessary. This approach allows a surgeon, or robotic surgical system, to perform a surgical procedure involving tumor resection in which the residual tumor remaining after is minimized, while also minimizing the trauma to the intact white and grey matter of the brain. In such procedures, trauma
5 may occur, for example, due to contact with the access port, stress to the brain matter, unintentional impact with surgical devices, and/or accidental resection of healthy tissue. For example, access port based procedures may be employed for other surgical interventions for other anatomical regions such as, but not limited to, spine, knee, and any other region of the body that will
10 benefit from the use of an access port or small orifice to access the interior of the human body.

Referring again to **FIG. 2**, in order to introduce the access port **130** into the brain, introducer **135** with an atraumatic tip may be positioned within the access port and employed to position the access portion within the head. As
15 noted above, introducer **135** (or access port **130**) may include fiducials for tracking. These fiducials may be passive or active fiducials, such as reflective spheres for passive infrared detection via an optical camera, or, for example, pick-up coils in the case of an electromagnetic tracking system. The fiducials are detected by tracking system **120** and their respective positions are
20 inferred by tracking software (which may reside within tracking system **120**, or may reside, for example, within control and processing unit **400**).

Once access port **130** is inserted into the brain, introducer **135** may be removed to allow for access to the tissue through the central opening of access port **130**. However, once introducer **135** is removed, access port **130**
25 can no longer be directly tracked in real time (according to the example

embodiment shown in **FIG. 2** in which no fiducials are attached to access port **130**). In order to track the position and orientation of access port 130, it may be indirectly and intermittently tracked by a pointer tool having fiducials that are detectable by tracking system **120**.

5 Although the example system described in **FIGS. 1** and **2** relates to a neurosurgical procedure, it will be understood that the systems and methods described herein are not intended to be limited to neurosurgical procedures or port-based procedures, and may be employed for a wide range of medical procedures. Examples of other types of medical procedures including
10 orthopedic, trauma, gastrological, cardiac, gynecological, abdominal, otolaryngology (or ENT – ear, nose, throat conditions), spinal, thoracic, oral and maxillofacial, urological, dental, and other surgical, diagnostic or therapeutic medical procedures. It is further noted that while many of the example embodiments described herein employ external imaging, such as
15 imaging with an external video scope, it will be understood that various internal imaging devices, such as endoscopic or catheter imaging devices, may additionally or alternatively be employed. It is further noted that embodiments of the present disclosure may be employed within or adapted to procedures employing telesurgical or shared-control systems.

20 In many of the example embodiments described below, each medical instrument that is to be tracked may have a fiducial attached thereto (e.g. passive or active fiducial markers, such as reflective spheres or active LED lighting emitted from at least 3 points on a device) so that the position and orientation of the instrument can be determined. In one example
25 implementation, the fiducial markers may be employed to determine a

reference position on medical instrument (such as a central point), and an axis of the medical instrument (such as a longitudinal axis of a tool).

Example Methods of Performing Access Port based Medical Procedure

FIG. 4A is a flow chart illustrating the processing steps involved in an example port-based surgical procedure using a navigation system. The first step involves importing the port-based surgical plan (**step 302**). A detailed description of the process to create and select a surgical plan is outlined in the disclosure "PLANNING, NAVIGATION AND SIMULATION SYSTEMS AND METHODS FOR MINIMALLY INVASIVE THERAPY", a United States Patent Publication based on a United States Patent Application, which claims priority to United States Provisional Patent Application Serial Nos. 61/800,155 and 61/924,993, which are both hereby incorporated by reference in their entirety.

As outlined above, an example surgical plan may include preoperative 3D imaging data (e.g., MRI, ultrasound, etc.) overlaid with inputs (e.g., sulcal entry points, target locations, surgical outcome criteria, and additional 3D image data information) and displaying one or more trajectory paths based on the calculated score for a projected surgical path. It will be understood that the present example embodiment is provided merely as an illustrative example plan, and that other surgical plans and/or methods may also be employed without departing from the scope of the present disclosure.

Once the plan has been imported into the navigation system in step **302**, the subject is affixed into position using a head or body holding mechanism. The head position is also confirmed with the subject plan using the navigation software, as shown in step **304**.

Registration of the subject is then initiated in step **306**. The phrase

"registration" or "image registration" refers to the process of transforming sets of data into a common coordinate system. Registered data may be provided in the form of multiple images, data from different sensors, times, depths, or viewpoints. The process of registration is employed in the present application
5 for medical imaging in which images from different imaging modalities are co-registered.

It will be appreciated that there are numerous registration techniques available and one or more of them may be employed according to the embodiments of the present disclosure. Non-limiting examples of registration
10 methods include intensity-based methods which compare intensity patterns in images via correlation metrics, while feature-based methods find correspondence between image features such as points, lines, and contours. Image registration algorithms may also be classified according to the transformation models they use to relate the target image space to the
15 reference image space. Another classification can be made between single-modality and multi-modality methods. Single-modality methods typically register images in the same modality acquired by the same scanner/sensor type, for example, a series of CT images can be co-registered, while multi-modality registration methods are used to register images acquired by
20 different scanner/sensor types or pulse sequences, for example in MRI and PET. Multi-modality registration methods are often used in medical imaging of the head/brain, as images of a subject are frequently obtained from different scanners. Examples include registration of brain CT/MRI images or PET/CT images for tumor localization, registration of contrast-enhanced CT images
25 against non-contrast-enhanced CT images, and registration of ultrasound and

CT.

FIG. 4B is a flow chart illustrating the further processing steps involved in registration as outlined in **FIG. 4A**. In one example implementation, the method may employ fiducial touchpoints as shown at **340**. In such a case, the process involves first identifying fiducials on images at step **342**, then touching the touchpoints with a tracked instrument (step **344**). Next, the navigation system computes the registration to reference markers (step **346**).

In another example implementation, registration can be performed by conducting a surface scan procedure, as shown at **350**. The first step involves scanning a portion of the body (e.g., the face) using a 3D scanner (step **352**). The face surface is then extracted from the MR/CT data (step **354**). Finally, surfaces are matched to determine registration datapoints. Upon completion of either the fiducial touchpoint **340** or surface scan **350** procedures, the data extracted is computed and used to confirm registration, as shown in step **308**.

In another example implementation, recovery of loss of registration may be provided. For example, during a medical procedure, a handheld medical instrument may be tracked using a tracking system, and a representation of the instrument's position and orientation may be provided and displayed as an overlay on a previously acquired or current image (such as a three-dimensional scan) of a subject's anatomy obtained with an imaging device or system (such as ultrasound, CT or MRI).

To achieve such an image overlay, a registration is needed between the coordinate frame of a tracking system, the physical location of the subject in space, and the coordinate frame of the corresponding image of the subject. This registration is typically obtained relative to a tracked reference marker,

which is placed in a fixed position relative to the patient anatomy of interest and thus can be used as a fixed reference for the anatomy. Generally this can be accomplished by attaching the reference to a patient immobilization frame (such as a clamp for skull fixation in neurosurgery), which itself is rigidly
5 attached to the subject (for example, as shown in **FIG. 2**).

However, the reference may be held to the frame, for example, through an arm, which can be bumped and accidentally moved, which creates a loss of registration. Additionally, since the reference marker must be positioned so that it is visible by the navigation hardware (typically requiring line-of-sight for
10 optical tracking, or otherwise within the observation or communication field of the tracking system), this tends to position the reference such that it is in the open thus more susceptible to accidental interaction and loss of registration. In situations of lost registration, a surgical procedure tends to be stopped while a new registration is computed, although this may not always be
15 possible if, for example, the registration fiducial points or patient skin surface are no longer accessible due to the progression of the surgical procedure, and thus creating a need for a full re-registration or, in some cases even disabling navigation for the remainder of the procedure.

Referring again to **FIG. 4A**, once registration is confirmed in step **308**,
20 the subject is draped (step **310**). Typically, draping involves covering the subject and surrounding areas with a sterile barrier to create and maintain a sterile field during the surgical procedure. The purpose of draping is to eliminate the passage of microorganisms between non-sterile and sterile areas. Upon completion of draping (step **310**), the patient engagement points
25 are confirmed at step **312**, and craniotomy is then prepared and planned (step

314).

Upon completion of the prep and planning of the craniotomy (step **312**), the craniotomy is then cut, where a bone flap is temporarily removed from the skull to access the brain (step **316**). Registration data is updated with the
5 navigation system at this point (step **322**).

The engagement within craniotomy and the motion range is then confirmed in step **318**. Once this data is confirmed, the procedure advances to the next step of cutting the dura at the engagement points and identifying the sulcus (step **320**). Registration data is also updated with the navigation
10 system at this point (step **322**).

In one example embodiment, by focusing the camera's gaze on the surgical area of interest, this registration update can be manipulated to ensure the best match for that region, while ignoring any non-uniform tissue deformation affecting areas outside of the surgical field (of interest).
15 Additionally, by matching overlay representations of tissue with an actual view of the tissue of interest, the particular tissue representation can be matched to the video image, and thus tending to ensure registration of the tissue of interest.

For example, in one example implementation, a video image may be
20 provided in which a post-craniotomy real-time intraoperative optical image of the brain surface (i.e. exposed brain) is provided with an overlay of the preoperative (and registered) sulcal map, and the registration may be corrected by providing input manipulating aligning the preoperative sulcal map with the sulcal profile that is observable in the real-time intraoperative image.

In another example implementation, a video image may be provided in which a post-craniotomy real-time intraoperative optical image of the exposed vessels on the brain surface (i.e. exposed brain) is provided with an overlay of preoperative image of vessels (obtained via image segmentation of

5 preoperative image data, co-registered with intraoperative position), and the registration may be corrected by providing input manipulating aligning the preoperative vessels with the exposed vessels that are observable in the real-time intraoperative image.

In another example implementation, a video image may be provided in

10 which a post-craniotomy real-time intraoperative optical image of an exposed tumor (i.e. exposed brain) is provided with an overlay of a preoperative (and registered) image of the tumor (obtained via image segmentation of preoperative image data), and the registration may be corrected by providing input manipulating aligning the preoperative tumor image with the exposed

15 tumor that are observable in the real-time intraoperative image.

In another example implementation, a video image may be provided in which a real-time intraoperative optical image of a nasal cavity is provided with an overlay of a preoperative (and registered) image of bone rendering of the bone surface (obtained via image segmentation of preoperative image

20 data), and the registration may be corrected by providing input manipulating aligning the preoperative bone image with the bone surface that is observable in the real-time intraoperative image.

In other embodiments, multiple cameras can be used and overlaid with tracked instrument(s) views, and thus allowing multiple views of the data and

overlays to be presented at the same time, which can provide even greater confidence in a registration, or correction in more than dimensions / views.

Thereafter, the cannulation process is initiated, as shown at step **324**. Cannulation involves inserting a port into the brain, typically along a sulcal path as identified in step **320**, along a trajectory plan. Cannulation is an iterative process that involves repeating the steps of aligning the port on engagement and setting the planned trajectory (step **332**) and then cannulating to the target depth (step **334**) until the complete trajectory plan is executed (step **324**).

The surgeon then performs resection (step **326**) to remove part of the brain and/or tumor of interest. The surgeon then decannulates (step **328**) by removing the port and any tracking instruments from the brain. Finally, the surgeon closes the dura and completes the craniotomy (step **330**).

Example Implementation of Control and Processing Unit

Referring now to **FIG. 5**, a block diagram of an example system configuration is shown. The example system includes control and processing unit **400** and a number of external components, shown below.

As shown in the **FIG. 5**, in one embodiment, control and processing unit **400** may include one or more processors **402**, a memory **404**, a system bus **406**, one or more input/output interfaces **408**, and a communications interface **410**, and storage device **412**. Storage device **412** may be employed to store information associated with a medical procedure, such as, but not limited to, local tissue analysis data, surgical plan data, pathology data, and recorded time-dependent medical procedure data.

Control and processing unit **400** is interfaced with other external

devices, such as tracking system **120**, data storage **442**, and external user input and output devices **444**, which may include, for example, one or more of a display, keyboard, mouse, foot pedal, microphone and speaker. Data storage **442** may be any suitable data storage device, such as a local or
5 remote computing device (e.g. a computer, hard drive, digital media device, or server) having a database stored thereon.

In the example shown in **FIG. 5**, data storage device **442** may include archival information associated with prior tissue analyses, and control and processing unit **400** may be programmed to process such information to
10 perform one or more of the methods described below. As shown in the example implementation illustrated in **FIG. 8**, data storage device **442** may include the following examples of information associated with a prior tissue analyses: pathology data **450**, outcome data **451**, archival local tissue analysis data **452**, recorded time-dependent medical procedure data **454**,
15 planning data **456** (e.g. a surgical plan having been followed during a medical procedure including a local tissue analysis), and additional information associated with subjects associated with the prior tissue analyses, such as, but not limited to, demographic, prognostic, prior history, and/or genetic information. Although data storage device **442** is shown as a single device in
20 **FIG. 5**, it will be understood that in other embodiments, data storage device **442** may be provided as multiple storage devices.

Medical instruments **460**, such as a tissue resection device (for example, the Myriad tissue resection device manufactured by NICO), a biopsy device, or a local diagnostic measurement device (e.g. point-based or imaging
25 based), are identifiable by control and processing unit **400**. Medical

instruments **460** may be connected to, and controlled by, control and processing unit **400**, or may be operated or otherwise employed independent of control and processing unit **400**. Tracking system **120** may be employed to track one or more of medical instruments **460** and spatially register the one or
5 more tracked medical instruments to an intraoperative reference frame.

Control and processing unit **400** is also interfaced with a number of configurable devices that may be tracked by tracking system. Examples of devices **420**, as shown in the figure, include one or more imaging devices **422**, one or more illumination devices **424**, robotic arm **105**, one or more
10 projection devices **428**, and one or more displays **115**. The one or more imaging devices **422** may include one or more local diagnostic measurement devices (e.g. point-based or imaging based). Tracking system **120** may be employed to track one or more of devices **422** and spatially register them to an intraoperative reference frame.

15 Embodiments of the disclosure can be implemented via processor(s) **402** and/or memory **404**. For example, the functionalities described herein can be partially implemented via hardware logic in processor **402** and partially using the instructions stored in memory **404**, as one or more processing engines **470**. Example processing engines include, but are not limited to, user
20 interface engine **472**, tracking engine **474**, motor controller **476**, image processing engine **478**, image registration engine **480**, procedure planning engine **482**, navigation engine **484**.

As described in detail below, one or more processing engines may be provided for process information associated with prior tissue analyses, and
25 such engines are represented by analysis engine **486**. For example, in some

embodiments, an analysis engine is provided to evaluate similarity criteria between of one or more local tissue analyses performed on a subject, and prior local tissue analyses stored in data storage device **442**, or otherwise accessible, such as through an external network. Examples of such methods

5 are described in the forthcoming description and accompanying flow charts. As described in detail below, similarity criteria may involve the evaluation of one or more metrics associated with one or more local tissue analyses performed on a subject, and one or more prior local tissue analyses, where the prior local tissue analyses may be associated with the medical history of

10 the subject and/or a collection of other subjects.

In some example embodiments, the processing engines may be employed to perform methods including, but not limited to, tracking 3D position and orientation data for the purpose of spatially registering diagnostic devices capable of performing local diagnostic measurements (e.g. point

15 based or imaging measurements); tracking locations of biopsy specimens to maintain 3D position and imaging information; recording biopsy sampling locations relative to the timing of the biopsy; recording surgical tool, and imaging device positions and actuation throughout a medical procedure; determining and recording margin boundaries in a tissue of interest in a virtual

20 manner; locating regions on a 3D image and correlating pathology information to such regions; and characterizing tissue based on one or more tissue metrics, and employing such metrics to search a database including prior tissue analysis data, and ranking results based on a variable weighted metric based algorithm.

25 It is to be understood that the system is not intended to be limited to

the components shown in the **FIG. 5**. One or more components control and processing **400** may be provided as an external component or device. In one alternative embodiment, navigation module **484** may be provided as an external navigation system that is integrated with control and processing unit

5 **400**.

Some embodiments may be implemented using processor **402** without additional instructions stored in memory **404**. Some embodiments may be implemented using the instructions stored in memory **404** for execution by one or more general purpose microprocessors. Thus, the disclosure is not

10 limited to a specific configuration of hardware and/or software.

While some embodiments can be implemented in fully functioning computers and computer systems, various embodiments are capable of being distributed as a computing product in a variety of forms and are capable of being applied regardless of the particular type of machine or computer

15 readable media used to actually effect the distribution.

At least some aspects disclosed can be embodied, at least in part, in software. That is, the techniques may be carried out in a computer system or other data processing system in response to its processor, such as a microprocessor, executing sequences of instructions contained in a memory,

20 such as ROM, volatile RAM, non-volatile memory, cache or a remote storage device.

A computer readable storage medium can be used to store software and data which when executed by a data processing system causes the system to perform various methods. The executable software and data may

25 be stored in various places including for example ROM, volatile RAM,

nonvolatile memory and/or cache. Portions of this software and/or data may be stored in any one of these storage devices.

Recording Time-Dependent Information Associated with a Medical Procedure

5 In some embodiments, the one or more events during a medical procedure may be temporally and spatially tracked, and this information can be logged. For example, if a tissue specimen is captured, the time at which is it captured can be recorded. This time can be correlated with location through the use of tracked tools in a navigation system (tracked using an optical
10 approach, or an EM-based tracking system). The location information will correspond to intraoperative MRI or CT (or PET or SPECT). The pathology information (microscope images, local imaging) can be associated with the time-stamp to allow that information to be stored in an appropriate database. This database can be searchable by patient (to see how the same
15 tissue looked under different modalities) or by disease type (to see how the same disease (validated by pathology) looks under different modalities), or by modality (to see what diseases are possibilities given a certain result (i.e. what possible tissues could have a given Raman spectra).

 By tracking the movements and locations of all tools throughout the
20 procedure, it is also possible to determine efficiencies in the operation – for example that the surgeon uses a particular tool for a very short or very long time, or that certain steps are less efficient than they could be. This information can be used by the surgeons and hospital administrators to properly estimate surgical times for optimum scheduling.

As noted in **FIG. 5**, one or more medical instruments **460** and devices **420** may be tracked using tracking system **120**. Such instruments and/or devices may be tracked, for example, using fiducials markers. Fiducial markers may be passive or active fiducials, such as reflective spheres for passive infrared detection via an optical camera, or, for example, pick-up coils in the case of an electromagnetic tracking system. The fiducials are detected by tracking system **120** and their respective positions are inferred by tracking software (which may reside within tracking system **120**, or may reside, for example, within control and processing unit **400**. Such tracking allows the position and orientation of the instruments and/or devices to be determined and recorded. In one example implementation, the fiducial markers may be employed to determine a reference position on medical instrument or device, (such as a central point), and an axis of the medical instrument or device (such as a longitudinal axis of a tool).

In some embodiments, tracked position and orientation data associated with one or more instruments and/or devices is recorded during a medical procedure. For example, in one example embodiment, the time-dependent position and orientation, and optionally other state information or configuration parameters associated one or more instruments or devices is recorded. For example, information that may be recorded may include, but is not limited to, tip offset, tip deflection, the state of control buttons and status, accuracy of measurement, visibility to a tracking system, the identity of a tool that is being used as a registration reference, and/or a registration reference transform may be recorded and/or processed.

In one example implementation, any or all of the recorded information may be recorded, along with time data (e.g. transmitted to a recording device), at sequential time points, at particular time points, or only at time points for which the information to be recorded has changed relative to its
5 previously recorded value.

In some example embodiments, a timestamp is associated with one or more, or all, of recorded information. Each timestamp may be matched to a global timestamp associated with other events recorded during the medical procedure, such as a global timestamp associated with video captures (such
10 as during a surgery, or sub-procedures such as when a cauterizer was on, when cutting, when tissue pathology samples were obtained, or other procedures). Further data can be integrated from any source from which a timestamp can be matched, including audio streams, video streams, state information of any imaging displays (e.g. data set, hanging protocol, window
15 level, position, orientation, etc.) or other events of interest (e.g. registration of biopsy samples, containers, results, etc.).

In one example embodiment, the time-dependent position and orientation of a medical instrument or device may be recorded as a vector relative to a fixed reference position (such as a patient fixed reference tool or
20 a tracking camera centered on a coordinated frame). An orientation can be recorded, for example, as a quaternion or axes vectors, and deflection can be recorded as an offset, or another parameterized geometric representation (such as spline parameters).

In various embodiments, several parameters may be tracked and recorded at each time for an instrument, depending on the data of relevance and any assumptions made (or variables held constant).

In one example implementation, seven parameters may be recorded to
5 represent the time-dependent position and orientation of a device or instrument. The six parameters are x, y, z, roll, pitch and yaw. The 7th parameter being the time instance at which specific orientation information is recorded. In other example implementations, fewer parameters may be used, if one or more assumptions are made (if, for example, there is no desire to
10 track or record a direction of rotation, such as an elongated instrument rotating around a longitudinal axis). More parameters can be used if the data is represented in other convenient ways, such as a 4x4 (16 parameter) transformation matrix in homogeneous coordinates, or a quaternion representation of rotations as an example. In other embodiments, fewer or
15 more parameters may be tracked, as required or desired by the configuration for use.

The representation, transmission, receiving, recording, storing, and processing of information pertaining to a medical procedure as described herein may allow for efficient storage, communication, and processing of the
20 state of tools and instruments involved in a procedure. For example, by storing such data as discrete data points pertaining to specific points in time, less storage space may be required than, for example, a video capture of a screen display of a navigation system and the storage of this information may enable other features and functions, as described below.

As noted above, in some example embodiments, one or more other time-stamped data streams, in addition or in alternative to a data stream recorded for a tracked instrument, may be recorded for subsequent playback and/or analysis.

5 In an example embodiment, once at least a portion of the time course of a procedure has been recorded as described herein, the spatial (position and orientation) data points and associated timestamps may be processed for subsequent analysis. For example an analysis may be performed to determine, based on the retrospective data, one or more metrics associated
10 with a procedure (such as surgical metrics). Examples of such metric include, but are not limited to, an amount of time that a tool or instrument was used, an amount of time that a tool or instrument spent at each depth of insertion, an amount of time that a tool or instrument spent near a certain feature (such as a vessel, nerve or lesion), and/or an extent of coverage of the various tools
15 and instruments available during the procedure.

As noted above various aspects of a medical procedure may be recorded (e.g. in a database) in a seamless manner so that the surgeon or an operator can utilize the volume of data for future care of the same subject, other subjects, or training purposes. Data streams may include, but are not
20 limited to, any or more of the following (or additional data streams): video streams; audio streams; location and position of all tracked instruments and items; the state of any imaging displays (data set, hanging protocol, window level, position, orientation, etc.; other events of interest (registration of biopsy samples, containers, results). This would enable the local or distributed
25 playback, at some point in the future, the entire operative procedure in part or

in whole. As noted above, one example implementation would be to allow the surgeon to "pause" the playback and then take control of the "paused" imaging displays and execute what-if scenarios for post-mortem analysis, audit, education, or training. One would be able to assess how the surgical procedure would have proceeded if the approach was slightly different approach than was actually used during the recorded session. The playback could even proceed using a different display angle, different data sets, or other differences from the originally recorded procedure.

Alternatively, a paused playback point could be used as the starting point for a new simulation, where the current position and orientations of tracked items and states of displays become the starting point for virtual manipulation of both the instruments and the imaging displays. One could even record the progress of the simulation in the same way as a live procedure so that it can also be used for time shifted audit, analysis, and training. Finally, several recorded simulations of different parts of one procedure could be made in different physical locations by different people, can be reviewed and analyzed at another location by a different team, and then the "best" parts of each simulation could be stitched together to provide a final "best" solution.

In some embodiments, a common source of time stamps for samples is provided at high enough resolution and low enough latency so that recording of samples of various stream can be effectively distributed during real time, and then later amalgamated.

In some example embodiments the data points and timestamps may be further processed to simulate intraoperative instrument/device motion. This

simulation may be provided as a controllable replay. Unlike a video feed that is only viewable from the angle of recording, the present example embodiment permits the recreation and playback, of instrument/device motion through other angles by way of the recorded data points and timestamps. In
5 other words, the viewpoint from which a simulation is rendered may be controllable by an operator.

Additionally, such an embodiment may be implemented to provide controls during playback, as if the instruments/devices were being manipulated live, which, when the system is associated with other imaging
10 devices and systems, and/or spatially registered data from imaging devices and systems, permits slices and/or views of the image data to be visualized and manipulated in ways that are different than the ones used during the procedure. This embodiment may be employed to provide a more flexible, dynamic and/or controllable review of a procedure, rather than a straight static
15 playback of a video recording of the procedure, which is limited to displaying only the image data that was recorded, from pre-set views, at the time of the procedure.

In one example implementation positions may be played back in real-time and also, for example, sped up, slowed down, paused, and searched.
20 Additionally, an operator may recall some or all activities performed near a particular location in a spatially-constrained search function. Such an embodiment provides a "location aware" search function. For example, a 3D brain structure may be reconstructed using preoperative medical images such as MRI or CT. A user can then position a pointing device or a cursor at a
25 specific anatomical position (e.g. the paracentral sulcus) and initiate a search.

The search routine may query a database with previously recorded position and time information of each surgical tool and identify all instances where tip of a surgical tool was present in a predefined (and configurable) vicinity of the identified location. The location may be also identified using 3 orthogonal
5 planar projections of the preoperative medical image, such as the multiplanar reconstruction image layout typically used by a radiologist. The position and associated time stamp information of the surgical tools may be alternatively stored as a sequential data structure. The query information (position information in this case) may be then used to search the list after sorting the
10 data by position using any of the commonly known searching algorithm for sequential data.

In some embodiments, the positions and orientations of tracked intraoperative imaging devices and systems (such as, but not limited to, ultrasound probes, optical coherence tomography (OCT) probes,
15 spectroscopy probes, intraoperative MRI coils, intraoperative CT, or fluoroscopy devices, and the like) can be correlated with the acquired images and analyzed in relation to other imaging data positioned and oriented to match the tools and instruments data points. If timestamps are available on the imaging devices/systems data, such timestamps can also be matched to
20 the timestamps associated with the data points pertaining to the recorded position and orientation data for the instrument(s), so as to provide time-synchronized images and/or videos.

For example a hand-held ultrasound probe may be used shortly after craniotomy during brain tumor resection to identify presence of vasculature
25 immediately below the dura. The position relative to the brain where the

ultrasound image (typically, a B-mode scan) is obtained and time instance when the image is recorded may be captured. This recording, when synchronized with the time component of the 7 parameter time-dependent position and orientation information recording described previously, allows for
5 exact association of intraoperative images with specific time points in the surgical procedure.

Such synchronized recording requires synchronization of a reference clock the time that is utilized by all recording systems in the room (OR). This can be achieved, for example, by configuring the recording devices to record
10 the present time (e.g. a time referenced to UTC). Alternatively, if the recording devices are not recording standard time, they may be synchronized using a common server that provides time information to multiple clients, where one client may be a computer-based data acquisition systems used to record the position of surgical tools and another client may be a computer-based image
15 acquisition system used to acquire ultrasonic images. Another client may be a computer-based system used to acquire intraoperative MRI. Similarly, other separate computer-based image and patient's physiological system monitoring systems may act as clients to a common time server. The server may be contacted by the clients at regular intervals to update the internal
20 clock of each client. Hence, any drift in individual clocks of the clients can be adjusted. The end result is time synchronized recording of surgical tools, intraoperative physiological state of the patient (e.g. dissolved oxygen level) and intraoperative images.

This synchronized data may be valuable as a training tool, as well as to
25 assess efficient use of surgical workflows and associated instrumentation.

Such information associated with utilization of various tools and techniques in a particular surgical procedure may be analysed by health institutions to identify cost associated with surgical procedures and substantiate the charges communicated to insurance companies and other payers.

- 5 The preceding example embodiments may be employed for a variety of purposes. For example, the recorded information may be employed for review of a medical procedure, for a variety of purposes, including, not limited to, clinical, educational, legal, self-assessment, performance assessment, audit, retrospective determination of exact location of points of interest for
- 10 subsequent imaging and follow-up assessment, and/or in-situ review of previous step(s) of a procedure during the conduct of the procedure, among others.

- Furthermore, the preceding embodiments may be modified to allow an operator to "pause" the playback of a recorded procedure, and then take
- 15 control of the "paused" imaging displays, and perform what-if scenarios for post-mortem analysis, audit, education, or training. A paused playback point could thus be used as the starting point for a new simulation, where the current position and orientations of tracked items and states of displays become the starting point for virtual manipulation of both instruments and
- 20 imaging displays. The progress of such a simulation can also be recorded in the same way as a live procedure so that it can also be used, for example, for time shifted audit, analysis, and training.

- After having paused the playback of a recorded medical procedure, an operator may provide input specifying another angle, or may provide input
- 25 such that the playback proceeds with different information displayed than was

actually used during the recorded session. The playback may proceed using a different display angle, different data sets, or other differences from the original recorded session.

In one example embodiment, both recordings and /or simulated video
5 or visualization data from different parts of a medical procedure could be obtained or created in different physical locations by different people and in different sessions. These parts can be reviewed and analyzed at another location by a different team and the "best" parts of each simulation, as identified by a human, stitched together to provide a final "best solution" for
10 future training purposes.

For example, in the case of brain tumor resection one surgeon may perform a real craniotomy and then acquire images using an ultrasound probe to identify the presence of sulcal folds or vasculature beneath the dura. The position of surgical tools and ultrasound scans will be recorded as the first
15 data set, first comprised of the position of surgical tools at regular time instances along with the ultrasonic data acquired at specific time instances. The time instances act as a common parameter that help synchronize the position information of the surgical tools with the ultrasonic data acquired during the same procedure.

20 While the first surgeon would have proceeded with the complete surgical procedure, a second surgeon may use the recorded first data set as a simulated surgical scenario. The second surgeon may pause the playback of the same surgical procedure at a time point. For illustration purpose, this time point may be shortly after completion of craniotomy. The second surgeon may
25 then choose another simulated dural opening or a different simulated sulcal

opening based on the presence of high-risk vasculature immediately below the dura – as observed from previously described ultrasound image. This action will generate a second data set. The second data set will have a pointer at the start of the data series to indicate the exact time point in the first data set where second data set begins. New data sets can be created so that that one can view a combination real surgical recordings and simulated surgical recordings and chose to observe different approaches to the same initial disease condition. All such alternative data set corresponding to the same initial disease condition may be simultaneously stored and retrieved on demand and alternative intervention methods compared by a human. If metrics are associated with alternative clinical approaches described above, surgical steps with highest metrics or scores may be combined sequentially to arrive at an overall optimal procedure.

The information recorded according to the preceding embodiments may be stored in an information store or database of procedures, optionally along with other data such as data obtained from a local tissue analysis, or from an imaging system, and can be used as an intraoperative surgical data source, pathology correlation, and/or for future surgery/procedure planning and training. Several examples of such methods are described below.

20 Methods involving Correlation of Diagnostic Data for Tissue Analysis

The following example embodiments provide methods involving the use of tissue analysis to supplement preoperative, intraoperative, or postoperative analysis and guidance. Such methods are provided to address a fundamental problem of surgery, namely the problem of needing, but not obtaining, sufficient information pertaining to tissue identification.

For example, during a neurosurgical resection procedure, a surgeon typically needs to decide, at various stages during the procedure, whether or not an exposed tissue region should be excised. There are several diagnostic modalities that the surgeon can use to attempt to make such a

5 determination. However, no single intraoperative modality can generally give a definitive conclusion. Indeed, there are several types of brain tumors that appear similar to each other on MRI, however are different in pathology. Hence, MRI alone is not sufficient to identify the tumor. Examining the cells under a microscope is the gold standard in tumor

10 identification, but it is not feasible to perform on every excised piece of tissue and often cannot be performed intraoperatively. An approach to arrive at a definitive conclusion may involve the interrogation of a tissue region with one modality, in order to initially narrow down the possible tissue types. Then a second modality could then be used that would supply more information and

15 further narrow the tree of possibilities. Eventually, it may be possible to definitively identify the tissue. Such a method is therefore complex and uncertain in its effectiveness.

Traditionally, there has been little integration between diagnostic imaging, surgery, and pathology in existing solutions. Imaging offers an

20 opportunity to seamlessly present information between the disciplines of radiology (diagnosis), surgery (treatment), neurology (outcomes) and pathology (tissue analysis). Imaging, and pathology analysis targeting a specific region of interest can be correlated on the scale of the tissue sample size that is resected. Procedure outcomes are often dependent on the

25 percentage of total diseased tissue that is removed, compared to the amount

of healthy tissue that is accidentally resected.

For achieving a more accurate pathology sample to imaging correlation, a more accurate method of registering a volume of interest of a tissue-sampling device, and delivering the tissue-sampling device to a region
5 of interest within a subject, may be employed, as described below.

Furthermore, in order to locate a smaller volume of interest in a larger surgically excised volume of tissue of interest, a system that can perform diagnostic measurements on the tissue in an ex-vivo manner, using the appropriate contrast mechanism, may be employed.

10 In some example embodiments, the ability to perform local tissue analysis on the scale of the volume of tissue to be resected, and to track the resulting local tissue analysis data relative to excised tissue, and to register to a more regional image of the tissue, may be employed to obtain a correlation between local, regional, full volume, and pathology results. This information
15 can be tracked relative to the outcome of the medical procedure, or progression of the disease locally, as tracked by imaging on subsequent imaging procedures.

Accordingly, in some embodiments, an integrated system is provided that enables imaging on a full volume, regional, or local basis, in the context
20 of a medical procedure, and provides the appropriate imaging with the appropriate tissue contrast to provide for diagnostic, surgical extent and outcome prediction.

Such a system may be employed, for example, when larger regions are resected for the purpose of more certainly resecting a small target of
25 interest inside a larger volume (for instance 10 cubic centimeter volume),

where the system provides the capability of performing imaging of the resected surgical specimen in such a manner that the smaller region of interest can be analyzed at a higher resolution for pathological analysis.

These and other systems, and associated methods, are described in detail
5 below.

The following example embodiments illustrate various aspects of the present disclosure, in the context of an access port based neurosurgical tumor resection procedure. As noted above, it will be understood that such example embodiments are not intended to limit the scope of the present
10 disclosure to neurological procedures, and it will be understood that the systems and methods disclosed herein may be readily adapted to, and employed for, various other types of medical procedures.

In some embodiments, a system is provided to enable tracking of individual locations within a patient's anatomy, provide local imaging data at
15 the location, provide external imaging data when tissue is removed (hand-shake image). External imaging may be performed as a volumetric or a surface scan.

In one embodiment, a sample is transferred to pathology in a labeled container. The labeled container is uniquely identified in the system, and the
20 system can locate the sample to a specific location in the imaging volume, through tool tracking, and to a set of in-vivo and ex-vivo imaging sets. Any larger scans of the tissue of interest can be used to target specific regions of interest.

The system may comprise i) a navigation system that registers a set of
25 volumetric imaging scans, to a patient frame of reference, ii) intraoperative

imaging in a targeted region of interest, iii) software system to register preoperative imaging, intraoperative imaging, and imaging of pathology samples, iv) a database to store relevant information, including, but not limited to, patient data, or Electronic Medical Records (EMR), Picture Archiving and
5 Communication System(PACS), Treatment Plans, Lab Testing Reports, Pathology Reports and Imaging, Patient Outcomes (reports and lab tests), v) software system to search, weight metrics, calculate similarity or metrics, and rank based on said metrics. vi) a software system to present said results in the context of the decision making process (diagnostic scan, surgery,
10 pathology diagnosis, outcome evaluation), vii) means of sorting and imaging biopsy samples.

The system may be employed to track and measure comparable tissue sample metrics throughout the process of diagnostic imaging, biopsy, treatment planning, surgery, and follow-up imaging. Thus the system may
15 provide comparable case information for patient(s) with similar metrics. These comparisons can better inform the clinical specialist of similar imaging, pathology, or outcomes for a given imaging, pathology or outcome condition for a specific patient.

In some embodiments, the system may utilize patient data already
20 available, by way of current diagnostic imaging scans, lab results, patient information (EMR), to better inform surgery, pathology and outcomes for the case in progress. The information associated with the case in progress would likewise be recorded, tracked, and submitted to same informatics systems (EMR, image databases, lab results,), in a manner that they will contribute
25 additional information for the next case In this way, the system may acts as an

adaptive decision making system such that more patients treated, and the more often information is entered into a system for a patient, the more powerful the ability of the system to present more data to the physician for more effective decision making.

5 Referring now to **FIG. 6A**, an axial view of a brain **530** is illustrated, with a tumor **532** originating in the ventricle of the brain, and growing to the surface of the brain. The tumor is shown as three different textures, representing three different types of tumor cells. This is representative of tumors, which can be heterogeneous in their biology, and thus their
10 appearance on imaging, pathology, and their response to treatments.

 A tracked medical instrument **534** is shown relative to the tumor and pointing to a location in the tumor. When used in conjunction with a tracking system for tracking the instrument tip (a tip tracking strategy may be employed for flexible instruments, e.g. greater than 1 mm flex at the tip inside
15 the tissue of interest, or the resolution of interest for that procedure), the position of the tracked medical instrument **534** is known relative to the local tissue region of interest.

 In one example embodiment, if medical instrument **534** is a biopsy sampling device, or includes a biopsy device, and the biopsy instrument
20 actuation is measured in coordination with the sample removal, and the sample is may be stored or tracked in a manner that it can be uniquely identified relative to this local tissue region. Tissue analysis, such as pathology results, can then be recorded and displayed relative to the location for which the sample was retrieved.

25 In another example embodiment, if medical instrument **534** is (or

includes) a local diagnostic measurement device the local tissue diagnostic data obtained from a local diagnostic measurement may be stored or tracked in a manner that such that the data can be uniquely identified relative to this local tissue region. The local tissue diagnostic data, such as a local image or
5 a Raman spectrum, can then be recorded and displayed relative to the local tissue region at which the diagnostic measurement was made.

In one embodiment, the location associated with one or more tissue analyses (e.g. a biopsy or a local diagnostic measurement) may be shown on a regional medical image that includes the local tissue region. In order to
10 show the location of a given tissue analysis, the location data associated with the tissue analysis is spatially registered to the medical image data. This may be performed using known registration methods, such as obtaining a preoperative medical image and spatially registering the preoperative image data to an intraoperative reference frame to which the location data
15 associated with the tissue analysis is registered.

Referring now to **FIG. 6B**, an example implementation of such an embodiment is illustrated, in which the location of three tissue analyses are shown by reference markers **540**, **541** and **542** are shown, in a user interface, overlaid on medical image data.

20 As shown in **FIGS. 6C** and **6D**, reference markers **540**, **541** and **542** may additionally serve as selectable graphical hyperlinks to information associated with the tissue analyses. For example, in **FIG. 6C**, the selection, via input from an operator (e.g. a mouse click or the touch of a finger or stylus on a touch screen display) results in the display of a pathology report **550**
25 associated with a tissue sample obtained from location **540**. In another

example implementation, shown in **FIG. 6D**, the selection, via input from an operator, of reference marker **540**, results in the display of local tissue diagnostic data **555**, including an MR image **556** and a Raman spectrum **557** that were locally measured.

5 For example, if in-vivo image data is acquired concurrently with biopsy samples then the in-vivo imaging can be presented in the same context, and location, as the reference marker for the pathology results. If there are no corresponding pathology results, the in-vivo data may be provided in place of pathology results, as shown in **FIG. 6D**. Examples of local imaging modalities
10 include OCT, high-frequency ultrasound, Spectroscopy, MRI, MR Spectroscopy, tissue conductivity, electromagnetic imaging, etc.

It is noted that the present example provides method of reviewing local tissue diagnostic data and tissue analysis results in a manner that is very different from conventional methods. For example, some existing pathology
15 software systems associate diagnostic image data based on hyperlinked text in a pathology report. In other words, the access to local diagnostic image data, or other diagnostic data, is provided through the pathology report. In contrast, the present embodiment allows for the graphical navigation to relevant location-specific diagnostic or tissue analysis data through a user
20 interface, via the selection of a hyperlinked reference marker (e.g. a label, icon, text, or tag), on a regional medical image, where the position of the reference marker corresponds to the location at which a biopsy sample was acquired or a local tissue diagnostic measurement was performed.

In some embodiments, illustrating in **FIGS. 6B-6D**, there may be
25 multiple locations for which hyperlinked data is available. In such a case, the

user may select one or more of the reference markers in order to view, or otherwise obtain (e.g. print, download, or email) the relevant data.

In some example embodiments, a single location may have multiple forms of associated local data. For example, as shown in **FIGS. 6C** and **6D**,
5 reference marker **540** has three different forms of associated data, including a pathology report (a form of tissue analysis data) and two forms of diagnostic data (a local MR image and a Raman spectrum). **FIG. 6E** illustrates one example in which a menu **560** may be provided to display a list of selectable items to display.

10 **FIG. 7** provides a flow chart illustrating the present example embodiment. At **570**, a medical image is obtained of at least a portion of a subject and displayed on user interface. The medical image may be obtained, for example, preoperatively, using fiducial markers that enable subsequent registration to an intraoperative reference frame associated with a medical
15 procedure during which the tissue analysis is performed. In another example, the medical image, and the local tissue information associated with at least one local tissue analyses, may be intraoperatively obtained during a common medical procedure.

Local tissue information, corresponding to one or more local tissue
20 analyses, is then obtained at **572**. Location data identifying the location corresponding to each local tissue analysis is obtained at **574**, where the location data is spatially registered to the medical image. At **574**, reference markers corresponding to each tissue analysis are displayed in the medical image, at the locations corresponding to their spatially registered location
25 data. Input is then received from an operator at **576**, the input identifying a

selected marker, and therefore, a selected tissue analysis. At least a portion of the local tissue analysis information associated with selected tissue analysis is then presented, or is otherwise provided, to the operator.

It will be understood that the variations of the embodiments shown in

5 **FIGS. 6B-6E** may be performed without departing from the scope of the present disclosure. For example, the selected local tissue information may be displayed in a separate window of the user interface. In one example implementation, at least a portion of the selected local tissue information associated with the selected reference marker is displayed intraoperatively
10 during a medical procedure, and wherein at least one said one or more local tissue analyses are performed during the medical procedure.

In one example implementation, at least one local tissue analysis may pertain to a previously medical procedure performed on the subject. The local tissue diagnostic data associated with at least one local tissue analysis may
15 include additional tissue analysis information associated with a previous local tissue analysis that was performed at approximately the same location.

It will be understood that a tracking system typically has a positional error associated therewith. For example, there will generally be an error associated with tip position, at the particular time when a biopsy sample or a
20 local diagnostic measurement is obtained, for instance, due to registration error and imaging related distortions. The estimated spatial error associated with the location corresponding to a given tissue analysis can be estimated, and displayed as a visual representation associated with the corresponding reference marker. For example, the visual representation can be provided as
25 a circle, sphere, error bars, or other suitable representation.

In additional embodiments, the method may be adapted to track specific locations that are registered across various modalities and resolutions enables the user to “drop points” virtually throughout the surgical cavity as tissue is resected. This allows a virtual margin to be created. These points
5 that are defined in a local area, are linked to a local imaging frame. The region of interest is located in larger volume by tracking of the imaging device, and imaging is recorded in synchrony with that tracking. If imaging at a larger scale is performed without significant tissue deformation, an image with a larger field of view can be defined. In such a way, the larger fields of view can
10 link to the entire imaging field. If the larger field of view can be imaged using contrast common to the preoperative, or intraoperative imaging, these points can be registered between the various clinical utilizations of the system.

FIG. 8A illustrates another embodiment in which information pertaining to one or more similar tissue analyses may additionally or alternatively
15 displayed in response to the selection of a given reference marker. Methods for identifying similar tissue analyses are described in detail below. As shown in the figure at 585, various form of tissue information pertaining to one or more similar tissue analyses may be presented via a user interface, such as, but not limited to pathology data associated with similar prior tissue analyses,
20 outcome data associated with similar prior tissue analyses, and/or diagnosis data associated with similar prior tissue analyses. Furthermore, as shown in FIG. 8B, local tissue diagnostic data 590 associated with similar prior tissue analyses may be presented to the operator. These example embodiments, and related methods, are described in detail below.

25 As noted above, in some embodiments, tissue information pertaining to

prior tissue analyses may be provided, based on a determination of similarity. In some embodiments, the determination of similarity may be made based on a comparison between local tissue diagnostic data associated with the subject, and archival local tissue diagnostic data obtained from a tissue analysis database. Such embodiments, involving the use of a tissue analysis database, may be employed according to a wide variety of methods, and in a wide variety of medical procedures, and stages of a given medical procedure. The information stored in the database may be tracked, updated and utilized as an adaptive evaluation tool, to search for similar results (pathology, imaging and outcomes) in the history of the patient, patients with similar imaging/clinical presentations, and/or database with all patients' information and their medical history.

An example illustration of different stages of a surgical procedure, and their association to one or more tissue analysis databases, is shown in **FIG. 9**. The figure shows an example embodiment involving four stages of decision-making, namely diagnostic evaluation **505**, surgical planning **510**, intraoperative surgery, diagnosis or treatment **515**, and postoperative analysis **520**. These stages are shown in their relation to each other, and with regard to one or more tissue identification databases **500**, which can be searched during one or more stages of a medical procedure. In this example, four aspects of patient care, where the use of a database linking registered imaging, pathology and outcomes can be utilized to improve diagnosis, surgical planning, surgical tissue differentiation and treatment and postoperative decision-making.

In the example workflow shown in **FIG. 9**, the diagnostic modalities

listed, include, but are not limited to, a set of whole organ, regional, or local diagnostic modalities, which may include imaging modalities such as, magnetic resonance Imaging (MRI), computerized tomography (CT), positron emission tomography (PET), SPECT, ultrasound (US), x-ray, optical (visible
5 light or sections of full EM spectrum), optical coherence tomography (OCT), photo-acoustic (PA) or regional imaging modalities. These modalities can be acquired and shown as 1D, 2D, 3D, or 4D (3D+time), data sets, any may be registered to the patient in a dimensional and positional accurate manner. Biopsy methods include core or endoscopic biopsy, surgical biopsy (large
10 section), aspiration, or other methods of removing tissue of interest for further pathology analysis.

It is noted that the phrase “outcome”, as used herein, refers to quantifiable methods to measure mortality and morbidity of the subject. This includes, but is not limited to, measurement of actual patient function,
15 including direct measures of tissue viability, or higher-level function, as well as in-direct measurements, tests and observations. An outcome may also refer to the economic outcome of a procedure (in a specific or broad sense), and may include the time for the procedure, the equipment and personal utilization, drug and disposable utilization, length of stay, and indications of
20 complications and/or comorbidities.

In some example embodiments that are described in detail below, tissue analysis may be performed by comparing local tissue diagnostic measurements (obtained with one or more diagnostic modalities) with archived local tissue diagnostic data. The archived local tissue diagnostic data
25 is associated with prior tissue analyses for which tissue analysis data, such as

outcomes, pathology data, and diagnoses, are available. The tissue analysis data is stored in a tissue analysis database (or two or more databases) with the associated archived local tissue diagnostic data. The local tissue analysis data (pertaining to a subject) may be employed to search the tissue analysis database to identify one or more similar prior tissue analyses, and the tissue analysis data associated with the similar prior tissue analyses may be provided to the surgeon, practitioner, or operator, or processed and employed for various uses and applications, examples of which are described further below.

For example, referring now to **FIG. 10**, a flow chart is provided that illustrates an example method for correlating a local tissue diagnostic measurement with archival tissue analysis data. At step **600**, local tissue diagnostic data is obtained, where the local tissue diagnostic data is associated with one or more local tissue diagnostic measurements performed on a subject.

For example, as described below, the local tissue diagnostic data may be local imaging data, such as a MR image obtained via an insertable MR probe, or local non-imaging data, such as locally measured Raman spectrum. Although this local tissue diagnostic data may not be sufficient to perform tissue analysis, it may be correlated with archival local tissue diagnostic data from prior tissue analyses from the same or other subjects, as described below. In cases in which the local tissue diagnostic data pertains to more local tissue diagnostic measurements made with more than one diagnostic modality, the location at which each local tissue analysis is made may be recorded, optionally along with a time stamp, as described above. The

location may be employed to correlate local tissue diagnostic data obtained for a common tissue location, but with different diagnostic modalities.

At step **605**, archival local tissue diagnostic data and tissue analysis data associated with one or more prior local tissue analyses is accessed or
5 otherwise obtained. As noted above, tissue analysis data may include information including, but not limited to, one or more of pathology data, outcome data, tissue identification data, and/or diagnosis data. The archival local tissue diagnostic data, and the associated tissue analysis data, pertain to previous local tissue analyses, and may be provided in a tissue analysis
10 database, as explained further below.

At step **610**, the local tissue diagnostic data associated with the one or more local tissue diagnostic measurements, and the archival local tissue diagnostic data associated with the one or more prior local tissue analyses, are then compared, according to pre-selected similarity criteria.

15 The local tissue diagnostic data pertaining to the subject may be employed to search the tissue analysis database for similar prior tissue analyses. Non-limited example of diagnostic modalities include MRI (T1, T2, DWI, ADC, FA, SWI, MRS), CT, Ultrasound, SPECT, PET, Raman spectroscopy, OCT, histological staining and high resolution optical imaging
20 (microscopy and otherwise). For example, if the local tissue diagnostic data obtained for the subject includes a Raman spectrum, a tissue analysis database may be searched to find archival local tissue diagnostic data that was also measured via Raman spectroscopy (where the archived Raman spectra are stored correlated with tissue analysis data), and the measured
25 Raman spectrum for the subject may be compared with the archival Raman

spectrum to find a prior tissue analysis having a similar Raman spectrum.

At step **615**, one or more similar prior local tissue analyses having archival local tissue diagnostic data satisfying the pre-selected similarity criteria are identified, thereby identifying a prior tissue analysis that may be
5 representative of the local tissue region of the subject. The tissue analysis data associated with the one or more similar prior local tissue analyses may then be provided, displayed, or otherwise processed for further uses, as described below.

As described above, the tissue analysis database may be generated
10 by performing multiple tissue analyses (e.g. for the same subject, or for different subjects), and storing, in a database, or suitable data structure, the local tissue diagnostic data obtained from local tissue diagnostic measurements, and tissue analysis data.

For example, one entry in a tissue analysis database may be
15 constructed as follows, in which multiple diagnostic modalities are employed to interrogate a local tissue region of a subject (although it will be understood that an entry or data element may include diagnostic data from a single diagnostic modality). In the present example, three different diagnostic modalities are employed. A tracked Raman spectroscopy probe is employed
20 to correlate the location the local tissue region with its Raman spectrum. Intraoperative MRI is also be employed to obtain MRI diagnostic data, where the use of a tracking and/or navigation system will allow the obtained MRI data to be correlated with the Raman spectrum. Finally, a tracked optical imaging device is be employed to optically interrogate the local tissue region,
25 allowing the visual appearance of the tissue to be correlated with the Raman

and MR data.

The local tissue diagnostic data associated with these measurements is stored, in the database (or other suitable data structure), along with, or correlated with, tissue analysis data pertaining to the local region. The tissue analysis data may include pathology data. For example, if a tissue sample from the local tissue region is excised and sent to a pathology laboratory, the pathology results (which may include cell type, microscope image, tissue imaging (for example, X-ray, MRI)) may be correlated, as tissue analysis data, with the local tissue diagnostic data that was intraoperatively obtained, and stored as an entry in the tissue database.

As described below, other types of tissue analysis data may additionally or alternatively be correlated with the local tissue diagnostic data to form the entry (e.g. database element) of the tissue analysis database. Examples of other tissue analysis data include, but are not limited to, outcome data (e.g. pertaining to the outcome of a medical procedure during which the local tissue diagnostic data was obtained), diagnosis data (e.g. pertaining to the diagnosis of a given pathology), and additional data pertaining to the subject (such as, but not limited to, demographic data, genetic data, and/or medical history data).

In some example embodiments, the diagnostic data from two or more different diagnostic modalities may be employed allow for improved tissue analysis, as the same tissue region can be measured using multiple tissue analyses.

The tissue analysis database, which, as noted above, includes tissue analysis data from prior tissue analyses, may be used to guide, or suggest,

which diagnostic modalities should or could be employed when performing medical procedures (e.g. surgical tissue resection procedures) involving known types of tissue. For example, if tissue resection of a known tissue type (e.g. a known tumor type) is to be performed, then the tissue analysis

5 database can be searched to identify prior tissue analyses corresponding to the particular tissue type of interest, in order to identify diagnostic modalities that have been shown to have local tissue diagnostic data that is correlated with a given tissue type. The identified diagnostic modalities may then be employed during the tissue resection procedure, and the local tissue

10 diagnostic data that is intraoperatively obtained may be compared with the archival local tissue diagnostic data to intraoperatively identify exposed tissue. In such an embodiment, it may be beneficial to filter the tissue identification database such that any local tissue diagnostic data that is included in the tissue identification database exhibits diagnostic data that is correlated with

15 the tissue analysis data (e.g. such that local tissue diagnostic data that did not show features or a signature associated with the tissue type is excluded).

In one example embodiment, a tissue resection procedure may be planned for a known, or suspected tissue type. **FIG. 11** is a flow chart illustrating a method of selecting suitable diagnostic modalities for use during

20 a medical procedure, and using the suitable diagnostic modalities to perform a similarity analysis between local diagnostic data and archival local tissue diagnostic data stored in a tissue analysis database. For example, a tissue resection procedure may be planned for a clinical case in which the tissue type is known to be, or suspected to be, a glioblastoma tumor. As shown at

25 step **620**, the tissue analysis database then be searched for diagnostic data

pertaining to the known or suspected tissue type, in order to identify one or more suitable diagnostic modalities at step **625**.

In the present example of **FIG. 11**, the tissue identification database would be searched for database entries pertaining to glioblastoma tumors, in order to identify diagnostic modalities associated with such database entries. For example, the search of the tissue analysis database may identify suitable diagnostic modalities as Raman spectroscopy, T2 MRI imaging, and ADC MRI imaging. The tissue analysis database may include entries whereby glioblastoma tumors have been associated with: Raman spectra having a specific spectral signature, T2 MRI image data in which the tissue appears dark, and bright ADC MRI data.

Accordingly, based on the knowledge of these diagnostic modalities as being suitable for intraoperative diagnostic measurements of this tissue type, a subsequent medical procedure involving tumor resection of a glioblastoma tumor (e.g. based on a suspected pathology, or based on a previously performed biopsy) may be performed diagnostic devices employing these diagnostic modalities, as shown at step **630**.

During the medical procedure, tumor tissue may be intraoperatively detected by associating local tissue regions of dark T2 MRI, bright ADC, and also having the specific Raman spectra, with the glioblastoma tumor. Such an embodiment may enable greater and more precise margin delineation and simultaneously more complete tumor excision with more healthy brain sparing.

Another example embodiment is shown in **FIG. 12**. **FIG. 12** is a flow chart illustrating an example method of determining similarity among different

tissue regions based on spectroscopic measurements. During a medical procedure, a biopsy sample may be obtained, as shown at step **640**. This sample may be measured using a spectroscopic diagnostic modality, such as a Raman spectroscopy, or hyperspectral imaging, in order to obtain a
5 characteristic spectral signature associated with the tissue. For example, it may be known that the tissue type is tumor tissue. This knowledge of the tissue being tumor tissue may result from obtaining a tissue sample within the central region of a tumor. The spectroscopic measurement that is obtained from the tissue sample may be performed ex-vivo, using a suitable ex-vivo
10 imaging device.

The local tissue diagnostic data obtained from the diagnostic measurement of the biopsy sample, having a characteristic spectral signature, may be subsequently compared with intraoperative measurements from an intraoperative, in-vivo, spectroscopic diagnostic device (such as a Raman
15 probe, or a hyperspectral probe) in order to determine whether or not a local tissue region (e.g. a layer of exposed tissue remaining after tumor resection) is of the same type as the tissue sample, as shown at step **650**. This determination may be made by performing an assessment of the similarity between the measured spectral signature from the tissue sample, and the in-
20 vivo spectrum (or spectra) intraoperatively obtained by measuring the tissue, as shown at step **655**. Such an embodiment may be employed to obtain an indication of when a tumor margin has been reached, and/or to confirm an alternative basis for determining that a tumor margin has been reached (such as an estimate based on a surgical plan).

25 As noted above and described in the flow chart shown in **FIG. 10**, the

tissue analysis database may be intraoperatively accessed and searched during a medical procedure in order to obtain tissue analysis information pertaining to unidentified tissue. During such a medical procedure, a local region may be measured in-vivo by performing one or more local tissue diagnostic measurements. For example, when performing a medical procedure in which one or more local tissue diagnostic measurements are made on an unidentified tissue region, the local tissue diagnostic data obtained from such diagnostic measurements may be compared with the archival local tissue analysis data in the database, in order to search for a prior tissue analysis having similar local tissue diagnostic data.

In the event that a prior local tissue analysis is identified, the tissue analysis data associated with the similar prior local tissue analysis may be provided and optionally processed such that it may be employed for various purposes and applications. For example, in embodiments, in which the pathology of tissue is unknown, pathology results from one or more similar prior tissue analyses can be presented when identified based on a search of the tissue database (e.g. as shown in **FIG. 8A**).

In order to avoid the system to be considered a fully automated computer based diagnosis system, the system can present one or more similar confirmed pathology cases that can be examined by the operator. This data can be reviewed, and the associated imaging examined in visual comparison.

Referring again to **FIG. 8B**, in some example embodiments, archived local tissue diagnostic data that is deemed to satisfy similarity criteria may be presented to an operator using a graphical user interface. In one example

implementation, in which the similar archived local tissue diagnostic data is imaging data, the region in the imaging set with the confirmed pathology may be scaled and presented in a similar size, orientation, and/or configuration as the active case (the case which the physician is comparing against), in a
5 compare mode. It is noted that this may not provide a definitive determination of tumor pathology based on imaging – and instead may provide an informative and suggestive search and retrieve functionality that presents the appropriate data based on search results.

In one example embodiment, the local tissue analysis database may
10 also include time-dependent medical procedure data recorded during a medical procedure in which one or more prior local tissue analysis were performed. This may allow a surgeon or operator to replay one or more portions of a similar prior tissue analysis identified according to the aforementioned methods. The time-dependent medical procedure data may
15 include time-dependent positional information associated with the position and the orientation of one or more medical instruments employed during the medical procedure, which may be processed to render and display a time-dependent simulation of one or more of the medical instruments during at least a portion of the medical procedure.

20 In one example embodiment, the method may be adapted to provide a computer recommended surgical plan, or an evaluation of a user selected surgical plan. For example, the tissue analysis database may include surgical plan data for at least one similar prior local tissue analysis. This may enable an operator, having identified a similar tissue analysis according to one of the
25 methods described above, to review, or simulate, one or more steps of the

surgical plan that was employed for the previous tissue analysis.

In another example implementation, a proposed surgical plan, outlining a planned medical procedure for a subject, may be compared with surgical plan data stored in the tissue analysis database. This may allow a clinician to
5 observe or review outcomes of similar surgical plans stored in the database. In some example embodiments, the method may be adapted to provide a computer recommended surgical plan, or an evaluation of a user selected surgical plan. For example, the database may be searched for similar approaches that were taken for similar tumors, tissues and critical tissue
10 structures. The search can be done in a similar manner as described as above, but instead of searching for the optimal outcome, the search is performed to best match the user selected approach.

FIG. 13 provides a flow chart illustrating an example method employing a tissue analysis database, where in the present example embodiment, the
15 tissue analysis database includes to identify prior tissue analysis having a similar surgical plan that was performed. At step **660**, preoperative surgical plan data associated with medical procedure to be performed on a subject is obtained. The tissue analysis database is then accessed at steps **662** and **664** to obtain outcome data and archival surgical plan data associated with
20 one or more prior medical procedures. The Preoperative surgical plan data and archival surgical plan data are then compared according to pre-selected similarity criteria at step **666**, and one or more similar prior medical procedures having archival surgical plan data satisfying pre-selected similarity criteria are identified at step **668**. If one or more prior medical procedures are
25 identified having similar surgical plan data, outcome data associated with the

similar medical procedures may be provided. The outcome data may be used, for example, to infer to potential effectiveness of a given choice of surgical plan.

5 **Methods of Performing Similarity Analysis with Prior Tissue Analyses**

Many of the embodiments described in the present disclosure involve the assessment of similarity between local tissue diagnostic data pertaining to tissue analysis performed on a subject, and archival local tissue diagnostic data stored in a database, in order to identify one or more similar prior local
10 tissue analyses. Performing such similarity assessment first requires the selection of appropriate metrics or criteria that differentiate the data set in the clinical context. In the specific case where local diagnostic measurement is composed of images, a common approach in computer vision is to detect and describe local features in images. Such features are known as keypoints. A
15 method such as Scale-Invariant Feature Transform (SIFT, U.S. Patent No. 6,711,293) is an example of algorithm that is used for the purpose of detecting and describing local features that aid in searching image data sets. Second step of the search involves judicious reduction of the size of the data set based on additional context associated with the data set. First, selection and
20 measurement of appropriate criteria is explained.

In some non-limiting examples, the clinical data set may include imaging contrast dynamics (contrast in-flow, contrast out-flow), diffusion information (e.g. FA or ADC mapping), quantitative T1 and T2, CT contrast flow, PET tracer dynamics. In all of these cases, the resulting data is a set of
25 images, the images can be decomposed into essential criteria using feature

extraction algorithms such as SIFT, SURF (Herbert Bay, Andreas Ess, Tinne Tuytelaars, Luc Van Gool, "SURF: Speeded Up Robust Features", Computer Vision and Image Understanding (CVIU), Vol. 110, No. 3, pp. 346--359, 2008) and Principal Component Analysis. Once the data is reduced to essential
5 criteria, searching can be done in a lower dimensional space that comprises the essential criteria instead of the entire image data points.

The process of matching a new clinical image data with an archival data set is illustrated in **FIG. 14A** and **FIG. 14B**. In one non-limiting example (shown in **FIG. 14A**), the process starts with decomposition of the newly
10 acquired image data (step **680**) into essential criteria (step **682**) and comparison of the newly estimated essential criteria values against essential criteria values already stored in a database (step **684**.) (e.g. calculating a vector distance). Examples of searching algorithms include nearest neighbor classifier (step **686**), Bayesian classifier and the general class of clustering
15 algorithms.

FIG. 14B illustrates another method for comparing patient-specific data with those in the archival data set. Here, the criteria are estimated from the data in the archival data set (step **690**) and these criteria are grouped into clusters (step **692**) described by multi-dimensional Gaussian distributions
20 (reference: "Findings Groups in Data: An Introduction to Cluster Analysis," L. Kaufman and P. J. Rousseeuw, Wiley Series in Probability and Statistics). Preoperative and intraoperative data from a specific patient are then obtained (step **694**) and criteria are estimated for this data (step **696**). Conditional probabilities are finally estimated (step **698**) to identify the most likely
25 Gaussian distribution where the newly acquired data belongs. Clinical

information (step 699), such as surgical outcomes, survival rate, postoperative complications, quality of life (QOL) measures, from archival data set can then be used to anticipate and appropriately prepare for the care of the patient.

Even though these tools are readily available, above described approach

- 5 does not utilize clinically relevant criteria; instead, abstract criteria are extracted and compared. This approach can be biased by spurious noise in the data and rationale for identifying a match cannot often be easily discerned.

- Additional criteria such as tumor size, tumor location in brain anatomy
- 10 tumor histology and pathology results may be used in combination with the imaging results to add clinically relevant criteria to the dataset. Thus, the range of data set that is searched (also known as search space) is comprised of two sets: (i) essential criteria obtained by decomposing images and (ii) above described additional clinically relevant criteria. In one non-limiting
- 15 example, tumor size is estimated by segmenting clinical image data (such as MR and CT) to isolate the tumor and then computing its surface area or volume. Segmentation of the image data to isolate the tumor may be done in 2D space in each of the original image slices that are commonly used to construct the 3D volume data (e.g. MRI 2D image slices). Segmentation of 2D
- 20 image may be accomplished using region-based segmentation methods (e.g. region growing, region splitting and merging, unsupervised segmentation), data clustering methods (e.g. hierarchical clustering, partitional clustering) or edge-based segmentation methods (e.g. watershed segmentation, markers based approach). These methods are known in the computer vision industry
- 25 and explained in the context of generic image data and clinical images in

“Tutorial: Image Segmentation,” Yu-Hsiang Wang, Graduate Institute of Communication Engineering, National Taiwan University, Taipei, Taiwan, ROC. Natively 3D segmentation approaches may also be used.

Tumor location relative to the brain anatomy may be deduced first
5 based on the identified location of the tumor relative to the brain. This may be achieved by identifying the centroid of a tumor region described previously. Then, this centroid location may be expressed relative to the patient’s brain. Finally, translating this location to a general brain atlas such as that described in The Cerefy Brain Atlases (“Continuous Enhancement of the Electronic
10 Talairach-Tournoux Brain Atlas,” Neuroinformatics, Vol. 3, 2005) will enable the association of anatomical location of the specific tumor. This identification of location can be achieved by applying standard image co-registration techniques between the patient imaging and atlas exemplars.

Tumor histology may be quantified using imaging techniques such as
15 Apparent Diffusion Coefficient (ADC) measured from diffusion weighted resonance (MR) imaging methodologies. Past publications have illustrated correlation between ADC and cellularity (reference: “Diffusion-weighted MR imaging of the brain: value of differentiating between extraaxial cysts and epidermoid tumors,” J S Tsuruda, W M Chew, M E Moseley and D Norman,
20 American Journal of Roentgenology, Nov. 1990, Vol. 155, No. 5). Hence, the correlation can be used to build a mathematical model that transforms measured ADC values to cellularity measures. In summary, all of the above clinically relevant criteria may be quantified and associated with clinical images to arrive at a data set that is searchable based on clinically relevant
25 criteria.

Finally, pathology information may be also added as a clinically relevant search criteria as follows. Biopsy is often performed prior to surgical resection of the tumor. The removed tissue sample may be analyzed using biochemical processing or monoclonal anti-bodies at a pathology laboratory to
5 identify the type of tumor (reference: "Identification of proliferating cells in human gliomas using the monoclonal antibody Ki-67," Zuber et. al., NeuroSurgery, 1988, Vol. 22, Issue 2). Similarly, some of the tissue samples resected during surgical procedures are set aside for such pathology analysis. The information from such pathology analyses may be added to the data set
10 collected during the surgical procedure by associating the results of pathology analysis with the exact location and time point where the analyzed tissue sample was removed. Thus, the pathology analysis results can be considered as metadata associated with the original position and time information captured during the recording of surgical procedure.

15 The metadata may be searched independent of position and time information to identify past surgical procedures (in the archival data) that are similar to a particular surgical procedure. In this case, the search algorithm may be a text-based searching algorithm that is commonly used in searching text strings in large volumes of text data (reference: "A fast string searching
20 algorithm," Comm. Association for Computing Machinery, 20(10): 762-772). Identification of the pathology of the particular patient with those in the archival data set may aid in the evaluation of clinical outcome that may be anticipated for the particular patient based on what was observed for patients with similar pathology in the past.

25 A similar means of searching through established databases is

possible using specific metrics from the local non-imaging diagnostic modalities. For example, metrics such as, but non-limited to, metabolite concentrations or ratios, local scattering or absorption, tissue stiffness (elasticity), anisotropy, etc., can be used.

- 5 In other cases, local imaging modalities may be employed which may provide enhanced imaging quality, resolution, and/or the ability to measure contrast mechanisms that cannot otherwise be imaged with external imaging probes. Imaging in this manner provides a unique opportunity to correlate quantitative metrics to the tissue sample of interest, and can facilitate
- 10 diagnosis, registration between regional and local imaging, and provide a means to track the biopsy sample through detection to diagnosis through pathologic examination.

- Additional information that may be analyzed to assess similarity may include specific patient information such as age, weight, the presence of
- 15 certain genetic mutations, exposure or presence of viruses, or disease prevalence information. For example, in each of these more qualitative metrics an appropriate quantitative ranking may be provided and associated with the features to enable a similarity calculation.

- A non-limiting example of associating scores with patient information is
- 20 the association of cancer recurrence score with tumor size and tumor grade (reference: "A population-based study of tumor gene expression and risk of breast cancer death among lymph node-negative patients," Habel et. al., Breast Cancer Research 2006, Vol. 8, No. 3). Hence, previously described tumor size estimates may be associated with disease prevalence information.
- 25 The latter information is another metadata that can be used as search criteria

to identify other patients in the archival data set. Such identified information can be used to infer possible outcome of the current surgical procedure, such as survival period and quality of life after surgery. This information, in turn, can aid in choosing suitable post-surgical care for the particular patient. For
5 example, if the tumor size indicates a high possibility (high score) for cancer recurrence then the patient can be watched more carefully with frequent imaging to monitor possible recurrence.

In some embodiments, the search of the tissue analysis database, and the associated similarity analysis, can be modified to include weighting
10 factors, such that one or more criteria are assessed as having a greater weighting in the similarity analysis. In one example implementation, one or more weighting factors can be pre-selected. In another example implementation, one or more weighting factors can be associated with a decision tree. In yet another example implementation, one or more weighting
15 factors may be selected by an operator (e.g. dynamically selected during a medical procedure). For instance, for a medical procedure involving a tumor that has been identified, or is suspected to be, a Stage 4 Glioblastoma multiforme (GBM), the weighting of the MRI contrast may be weighted as a higher number, for instance 2, verses all other factors weighted as one. As a
20 contrasting example, in the case of a Stage 2 GBM, the weighting of the DWI ADC value may be weighted higher, for instance 3, verses all other factors weighted as one. In another embodiment, the features weighting can be determined based on a global calculation across multiple data points for a patient, or across a large patient population.

25 In one embodiment, a weighting can be applied based on the

operator's interpretation of the results. For instance, if the surgeon determines the local Raman signal to be of high-quality, and clearly delineating a difference in tissue within that subject, they may choose to weight that factor higher than other factors such as CT perfusion of the area. They may also
5 choose to exclude regions, or down-weight specific parameters – such as ADC values from a region of interest, if it appears the registration accuracy between the image sets is poor, or the imaging quality is not sufficient. In addition, local intraoperative imaging can be registered back to the radiology presentation of the data. In the future this can better inform diagnosis as
10 discussed in the context of diagnostic (radiologic) utilization of the system. In this way, higher quality imaging can be used as an internal surrogate to tissue sampling and pathology analysis, and may in-fact be more accurate than the current accepted gold standard of tissue characterization.

EXAMPLES

15 The following examples illustrate non-limiting example implementations of various aspects of the present disclosure, within the context of preoperative, intraoperative, and postoperative neurosurgical procedures involving the resection of brain tumors. The examples presented herein are provided to enable those skilled in the art to understand and to practice
20 embodiments of the present disclosure. They should not be considered as a limitation on the scope of the disclosure, but merely as being illustrative and representative thereof.

Example 1: Preoperative Analysis and Search of Tissue Analysis

Database

25 In a first example, shown in **FIG. 15**, various aspects of the present

disclosure may be employed in the context of preoperative procedures involving preoperative imaging and a tissue biopsy. **FIG. 15** is a diagram illustrating the interrelationship between various aspects of an example implementation of the methods described above, showing how various

5 diagnostic measurements and inputs are employed in order present search results based on a search of a tissue identification database 500. The present example implementation involves specific utilization of regional image data **700**, local diagnostic measurements **702**, and tissue analysis data **704** to link imaging and pathology results in a single patient, and linking results across

10 subjects.

Shown in the middle of the figure, is an axial view of a brain **760**, with a tumor **532** originating in the ventricle of the brain, and growing to the surface of the brain. The tumor is shown as three different textures, representing three different types of tumor cells. This is representative of tumors, which can be

15 heterogeneous in their biology, and thus their appearance on imaging, pathology, and their response to treatments.

A tracked instrument **534** is shown relative to the tumor and pointing to a location in the tumor. When used in conjunction with a tracking system, and a tip tracking strategy (as is needed for flexible instruments, i.e. greater than

20 1mm flex at the tip inside the tissue of interest, or the resolution of interest for that procedure), the exact position of the surgical device is known relative to the tissue of interest with great certainty.

If this instrument **534** is used in conjunction with a biopsy sampling device, and the biopsy instrument actuation is measured in coordination with

25 the sample removal, and the sample is stored or tracked in a manner that it

can be uniquely identified relative to this location at pathologic analysis, then this pathology results can be recorded and displayed relative to the location for which the sample was retrieved.

As noted above, the location can be represented on an image viewing system, identifying a reference marker (e.g. a label, or tag) on a regional image 700, that corresponds to the location at which the sample was acquired. Upon selection of that label, the system may present the corresponding pathology report on the screen for viewing. If there were multiple locations from which multiple samples are selected, each would have an associated report. This was explained previously in relation to **FIG. 8A**.

The navigation system would have associated tip position accuracy at the particular time when the sample was taken, for instance due to registration error and imaging related distortions, total accuracy for the tip could be estimated, and displayed as a visual representation around the center of that estimated tracked needle tip location (as a circle, or a sphere or like representation).

In one embodiment, if the user selected the point for which the pathology results were linked, a search of database 500 could be performed to look for other studies, which had similar metrics. In some non-limiting examples, the metrics 730 could include quantitative imaging metrics such as imaging contrast dynamics (contrast in-flow, contrast out-flow), Diffusion information (ADC mapping), quantitative T1 and T2, CT contrast flow, PET tracer dynamics. Additional metrics such as tumor size, tumor morphology or histology, and pathology results may be used in combination with the imaging results to characterize the location and enable a search. Even further metrics

includes specific patient information such as age, weight, or the presence of certain genetic mutations. In each of these more qualitative features, an appropriate quantitative ranking must associate with the features.

As shown at 740, the database search can be weighted towards some metrics 730 having a greater weighting in the search. The weightings can be pre-set, or associated with a decision tree, or user selected. For instance, for a tumor that demonstrates a Stage 4 Glioblastoma multiforme (GBM), the weighting of the MRI contrast may be weighted as a higher number, for instance 2, verses all other factors weighted as one. As a contrasting example, a Stage 2 GBM, the weighting of the DWI ADC value may be weighted higher, for instance 3, verses all other factors weighted as one. In another embodiment, the features weighting can be determined based on a global calculation across multiple data points for a patient, or across a large patient population.

In the case of diagnostic imaging, where the pathology is unknown, a set of comparable pathology results can be presented based on a similar search method previously presented. In order to avoid the system to be considered a fully automated computer based diagnosis system, the system can present to the user a set of similar confirmed pathology cases that can be examined by the user, as shown at **742**. These sets can be reviewed, and the associated imaging examined in visual comparison.

In order to make the viewing efficient, the region in the imaging set with the confirmed pathology would be scaled and presented in a similar configuration as the active case (the case which the physician is comparing against), in a compare mode. This is not a definitive determination of tumor

pathology based on imaging – but a search and retrieve function that presents the appropriate data based on search results.

If local in-vivo imaging **702** is acquired at the same time that the biopsy sample is acquired, then the in-vivo imaging can be presented in the same context, and location as the tag for the pathology results, or if there are no corresponding pathology results, in place of those results. Examples of local imaging modalities **702** include OCT, high-frequency ultrasound, Spectroscopy, MRI, MR Spectroscopy, tissue conductivity, electromagnetic imaging, etc.

10 A similar means of searching through established databases **740** is possible using specific metrics from the local imaging. Metrics such as metabolite concentrations or ratios, local scattering or absorption, tissue stiffness (elasticity), anisotropy, etc., can be used. In most cases the local imaging will provide significantly enhanced imaging quality, resolution, or the
15 ability to measure contrast mechanisms that cannot otherwise be imaged with external imaging probes. Imaging in this manner provides a unique opportunity to correlate quantitative metrics to the tissue sample of interest, and can facilitate diagnosis, registration between regional and local imaging, and provide a means to track the biopsy sample through detection to
20 diagnosis through pathologic examination.

Shown on **FIG. 15** are the various inputs (regional imaging **706**, local imaging or other diagnostic measurements **702**, and pathology data **704**) to a software engine **740** that determines various metrics **730** (imaging metrics, tumor morphology, tumor size/location, point imaging metrics, and pathology
25 results). These metrics **730** can contribute to associated database for that

subject, as well as be used in a search of the specific subject database, or other databases to locate similar imaging, pathology, or anticipated outcomes for that subject, as shown at **500**.

In one example implementation, the search may be performed using a search algorithms as previously described, with a weighting of the features used determined by, for example: pre-set weightings, contextually selected weightings, user selected, or modified weightings, weightings selected or modified based on data quality measures (e.g. if it appears that the fidelity of that measure is poor, it is rejected), and weightings selected in an adaptive, or trained manner.

The results may be presented, as shown at **742**, in a manner that is pre-selected, contextually, or user selected, for instance always presented as a top ten ranking of subjects from the local institution database. It may be desired that these large datasets be accessible in a fast manner, therefore pre-loading of the typically viewed number of sets could be accomplished during processing of the search results.

Example 2: Preoperative Analysis and Search of Tissue Analysis

Database

Another example implementation demonstrating of the clinical utility of the system is the use of an example embodiment of the system in context surgical and treatment planning for the subject, as illustrated in **FIG. 16**. **FIG. 16** is a diagram showing an example embodiment involving specific utilization of preoperative imaging, pathology, and point source imaging data to facilitate decision making for treatment and surgical planning. Data from the results of

previous surgical treatments performed on that subject, or subjects with similar imaging and/or pathology are presented based on an algorithmic search.

In this case, based on preoperative imaging **706**, pathology results **708**, and knowledge of the devices or system used in treatment (i.e. device physical properties, treatment modality properties), an expected outcome for the subject may be suggested based on subjects with similar imaging, pathology and medical condition. The optimal approach may be selected for the subject while using this information in the context of treatment or surgical planning.

Shown in the center of the figure, is an axial view of a same brain **770** as in **FIG. 15**, however this time with a surgical implement **772** represented in the same coordinate frame. In this case, the implement is illustrated as a surgical access port, with an introducer device.

In the present example embodiment, the model of the associated device, structures and tumor from the preoperative images, can then be used, for example, to provide a computer recommended treatment plan, or an evaluation of a user selected treatment plan.

For the selection of a computer recommended treatment plan, the software system can search (as shown at **744**) the database **500** for tumors that having various metrics or criteria **732**, such as tumors of similar pathology, similar size, and located in a similar location in the brain, with corresponding nerve fascicle and critical structure locations undergone a similar surgical approach, i.e. with a similar device (for example access port). Corresponding nerve fascicles can be identified by associating tumor location

with a brain atlas. Further, DTI atlas (such as that available at www.dtiatlas.org) may be used to identify nerve fascicles in the region.

Various properties associated with a tissue region of interest may be obtained from preoperative imaging **706**. For instance, a tumor volume may be determined from the images from multiple modalities. Tumor metrics **732** such as stiffness can be determined or inferred using the external imaging (DWI, T2, MR Elastography), internal imaging if performed in conjunction with biopsy (OCT measured stiffness, tissue anisotropy, biosensors, i.e. direct pressure measurement), or pathology would contribute to the model of the tumor (vascularity, tissue fibrosis). Finally, preoperative diagnostic information may be used to rank the various search criteria. For example, if the patient has been already diagnosed with Glioblastoma, the search criteria may add higher weight to past surgical data in the archival data set or database (**500**) that correspond to tumors located in the frontal and temporal lobes since Glioblastoma are typically confined to these regions.

The end result **746** could be a ranked set of cases with a selected surgical approach, the associated patient outcome and postoperative imaging set. The patient outcomes could be quantified and an optimal value would be calculated based on weighted rankings.

In an additional example embodiment, if the positions of the tools are tracked for those procedures, the surgeon can watch the position of the devices, and the tools that were selected for that case. In this way, the surgeon can be informed of similar cases, their approaches, and their outcomes, in a way that can inform for their approach.

In a second method of using the model, the surgeon may select a

surgical path for resecting the selected tumor, with or without using the model in a predictive manner that searches a database, where the model could inform upon the expected outcome.

In one non-limiting example of using surgical path as a search criteria
5 the path of the tools and the volume of tumor predicted to be surgically resected, can be used to search a database for similar approaches that were taken for similar tumors, tissues and critical tissue structures. The search can be done in a similar manner as described as above, and the search is performed to best match the user selected approach.

10 For example, the search, in this case will may consist of first matching the planned surgical path to previously stored surgical paths in the archival data set. The surgical paths can be represented as a set of vectors that sequentially represent the entire path with each vector representing one segment of a piecewise surgical path. Congruence between thus described
15 directed vector path and those previously stored in the archival data set can be estimated using such mathematical techniques as Hamming distance or Levenshtein distance (reference: "Error detecting and error correcting code," Bell System Technical Journal, 1950, 29(2):147-160). These mathematical constructs provide a measure of similarity between pairs of directed vector
20 paths and, hence, can be used as a search criteria. The search can be further constrained to those cases where estimated volume of the planned surgical procedure matches those in the archival data set. Hence, previous surgical procedures that closely match surgical path and tumor size can be presented to the surgeon to review prior to embarking on the actual surgical procedure.

25 The system may present a set of procedures **746** that had a particular

surgical approach in that region, that the user may be informed by viewing the imaging, and actual case (a recorded movement of the surgical tools and imaging used in that region). In a similar manner, where surgical outcomes have been searched to mean patient outcomes, the economic impact of surgical approaches may be considered.

In one non-limiting example, the exact surgical tools used during various stages of a surgical procedure may be recorded since each surgical tool may be uniquely identified and tracked by a navigation system. Each surgical tool, in addition, may have additional parameters such as capital cost of the tool, cost associated with each use (e.g. cost of disposable or consumable components associated with the tool) and cost associated with technical staff using the tool. In this manner, the total cost of using all the tools or specific tools in a surgical procedure may be computed and stored along with position and time information of all the tools. This information may aid the surgical team and hospital administration to accurately track the cost of various surgical procedures.

Example 3: Intraoperative Analysis and Search of Tissue Analysis

Database

FIG. 17 illustrates an example embodiment involving specific utilization of preoperative imaging (in the context of the surgical plan **712**), intraoperative imaging **710** (full volume, regional, and point based), intraoperative pathology **716**, and intraoperative procedure testing **714** (electrophysiology for example), to facilitate decision making for tissue differentiation and treatment. Database **500** is searched based on metrics **734**, such that the results of previous surgeries performed on the subject, or subjects with similar imaging

and/or pathology are presented **750** based on an algorithmic search **748**. **FIG. 17** illustrates an example implementation, in which an embodiment of the system is considered in the context of surgical or treatment guidance. Shown in the middle of the figure, in the center of the image, is an axial view of a brain **780**, with the overlay of an access port **782**, and a tracked surgical tool **784** (biopsy device, surgical resection device or point imaging probe).

In **FIG. 17**, much of the tumor that was originally shown in **FIG. 15** is removed, and a small margin of tumor remains. It is in this context that the described system is most impactful. One of the biggest challenges in surgery is careful resection of the tumor at the boundaries of the tumor. By tracking the surgical tools, and registering imaging and pathology in the manner presented, the full informative and predictive power of all associated imaging and pathology results can be used to better differentiate between tumor locations within various regions of a subjects tumor and brain.

In **FIG. 17**, much of the tumor that was originally shown in **FIG. 15** is removed, and a small margin of tumor remains. This is always a challenge in tumor resection, balancing the goals of complete resection and minimizing damage to healthy tissue. By tracking the surgical approach, tools used, pathology, and any other relevant criteria, the system can offer correlated retrospective information on resection performance (e.g. as narrowly as for a particular surgical team or procedure, or broadly through all available records) to aid in informing surgical decisions. For instance, for a particular tumor size, tumor location, nerve fiber locations, pathology, patient specific information (age, virus status, genetic background), there would be an associated set of prior cases with similar metrics. From these cases there would be instances

where margin of tumor was left behind from taking too conservative of a tumor margin resulting in tumor being left behind, and visible (for instance under MRI). Whereas other case where there was too aggressive of a margin causing cognitive loss. In each case pre-operative imaging, such as MRI

5 tumor volume as related to surgical resection margin by way of overlapping volumetric measurement, or intraoperative imaging results such as Raman Spectroscopic signature of the tissue status at the margin, could be related to the boundary. Additional information such as the proximity of the margin to major fiber tracts could also be measured relative to the margin to determine

10 what proximity may lead to being too close causing nerve damage. This information would be presented to show the surgeon so they can use this data to guide the margin to fall between too aggressive, and insufficient surgical margin resection, as guided by prior case similarity search in the manner presented. In a similar manner, the use of pressure sensors along surgical

15 instrumentation, such as the edge of the port, or the edge of surgical retractors, could provide an average, or peak measurement of pressure on the surrounding tissue. A search of clinical outcomes associated with similar instances of port positioning, or tissue retraction extent and location, would guide thresholds for acceptable peak pressure for that specific surgical

20 procedure.

FIGS. 18A and 18B illustrate an example implementation in the context of a view looking down the access port. Shown in this figure on the top left is a view **800** of multiple types of tissues as seen by a video scan from a device such as an exo-scope. Here various colors, and textures create the

25 appearance of multiple tissue types. Shown are five separate islands of

tissue, with differing appearance, and lines that may represent planes between tissues, vessels or nerve fibers. With only the optical view of the tissue, it is not possible to differentiate between the tissue types with certainty.

In **FIG. 18C**, a probe **810** is shown interrogating an island of tissue 815 through access port **782**. In one example implementation, this probe may be a Raman probe. The associated tissue spectra obtained from the Raman probe is represented in the frequency spectra shown at **850** in **FIG. 19**, under the title "In-vivo Imaging Data". This specific location in the port, and on the video image, can be located by tracking the position of the tip of the Raman imaging probe **810**. This specific location may have, associated with it, additional local imaging data, either collected in that surgical procedure, or from prior diagnostic imaging exams (this information would be could registered through various registration methods). This specific location may also have associated regional, or volumetric imaging data, for example, which may have been obtained in this surgical procedure, or in prior pre-surgical scans.

If spatial registration can be adequately performed, then additional metrics associated with the other imaging data, such as contrast uptake, DWI ADC values, or other metrics useful in helping to differentiate or characterize the tissue, can be associated with this particular sampled point (or region outlined by a probe). In one non-limiting example, a reformatted image, such as **FIG. 18B**, may be created by specifically highlighting all regions of the DWI ADC image that correspond to the particular ADC value measured at the same location where the Raman data was acquired. Image highlighting described here may be realized through selective coloring of DWI ADC image pixels with specific values described above.

Referring now to **FIG. 18B**, a view **805** is shown down access port 782 from the video scan, providing the above described reformatted and registered view of an image down the same port trajectory. Registration will be required because the DWI ADC image needs to be transformed to match the view down the port. In this representation of the tissues of interest, it can be seen that the islands of tissue have a similar appearance and classification.

FIG. 19 is a diagram demonstrating how multiple tissue metrics are utilized to characterize tissue of interest, and how that information is used to search a database for similar tissue types characterized on a similar metrics. The ranked similar tissue types are then associated with their respective full-imaging set, pathology, and subject information, which are presented to the physician. As shown in **FIG. 19**, these features can be used to help differentiate the tissue of interest that is being interrogated. This is represented at **850** by the box with the label "In-vivo Imaging Data". The point of interest can be associated with different metrics or criteria, such as i) local quantitative data (such as ratios between peaks on the Raman spectra, or absolute point quantities such as tissue anisotropy, or tissue density can be determined based on ADC measurements, as described before), ii) local imaging combined feature set, (such as tissue morphology on a local scale), iii) intraoperative combined feature set (such as DWI, contrast flow, etc.), iv) preoperative imaging combined feature set (registered data including DWI, contrast flow, etc.). These metrics can then be used to search a database for similar tissue, based on a similarity analysis or algorithm, shown as "comparison" **860** in the figure. The actual mechanism for comparison may be

as described in **FIG. 14A** and **14B**.

The database search could be performed in a similar manner of weighting, and ranking described previously. In some embodiments, the search may be performed based on diagnostic data obtained through
5 measurements of other regions that were done within the same subject. In the context of imaging through a small surgical window to address a larger area of interest surgically, the ability to piece together a full view of the regions of interest can be lost as the surgeon traverses through areas of tissue.

As specific regions are interrogated in above described manner against
10 previously stored data in archival data set, some of the interrogated regions may be stored for easy recall during the same procedure. In other words, the database or archival data set that is searched is now composed of the original archival data set and any new tissues regions that were interrogated recently. The same search algorithm may be employed to search any new data against
15 this expanded data set. Hence, the surgeon may explore the possibility of comparing a new tissue regions against previously analyzed tissue region. For example, the Raman spectroscopy data from a new tissue region may be compared with Raman spectroscopy data from a previously analyzed tissue region in the same patient.

20 The surgeon may use this information simply to inquire whether the tissue under local interrogation is simply similar to tissue adjacent or more similar to tissue that was seen previously, and clearly differentiable based on other imaging metrics. Accordingly, the surgeon is provided with the ability to reference information that was previously available, and interrogate tissue
25 using various tissue metrics.

In a further example of what has been described, intraoperative imaging and preoperative imaging can be combined to better define set of pathology types based on similarity metrics.

Example 4: Intraoperative Analysis and Search of Tissue Analysis

5 Database

FIG. 20 illustrates another example embodiment involving specific utilization of postoperative imaging **720**, postoperative pathology data **724**, and postoperative therapy outcomes **722**, to facilitate decision making for next stage care, in the context of expected outcomes. As shown in **FIG. 20**,
10 multiple tissue metrics may be utilized to characterize tissue of interest, and how that information is used to search a database for similar tissue types characterized on a similar metrics database **500** is searched **752** using one or more metrics **736**, such that the results of previous surgeries performed on the subject, or subjects with similar imaging and/or pathology and or treatment
15 response **754** are presented based on an algorithmic search **752**.

Shown centrally in the figure, is an axial view of a brain **790**, with the overlay of the residual tumor **792**, and the nerve fascicles. In this example context, the tumor, and brain tissue is evaluated after the surgical procedure either using a full-volume scan, or a regional scan. The evaluation may be
20 done immediately after the surgery, or done at various intervals at any times after the surgery is done, and may be informed based on patient response, or metrics from the database discussed in this disclosure (for instance a specific follow-up imaging regiment may be suggested for a certain tumor size, location and subject age). The postoperative imaging **720** is used to evaluate
25 the tumor, and tissue metrics such as tumor volume, total fiber volume locally,

regionally and throughout the brain. In addition postoperative pathology data **724** may be obtained, and registered to the imaging set.

Further still, post-surgery outcomes **722** may be used to define quantifiable metrics such as neurological deficits (motor response, visual field
5 coverage, cognitive testing results, etc.). Each of these metrics can be calculated in part, or whole by the software system, and can be compared to a database in manners previously discussed. For instance, a specific residual tumor volume, with specific imaging metrics (DWI ADC, Contrast uptake), located in a specific region of the brain, and subject age, may be searched
10 against similar metrics in the data base, or find the best long-term outcomes. The search, and presentation of the data would be done in a manner similar to that presented in the second context of use – surgical planning. It is essentially the same process, as the next clinical decision for the treatment of the subject is based on a similar process of searching for similar conditions,
15 and considering those outcomes in comparison to the current subject, and specific context of their disease and subject history thus far.

Another unique feature of the present disclosure may involve the knowledge that tumors are inherently heterogeneous, and that tumor biology has a fundamental impact on treatment – therefore point-wise pathological
20 analysis should be linked to regional treatment selections. The pathology linked to a specific region of interest can instruct secondary local imaging (in same procedure), treatments (in same procedure) or secondary imaging (secondary procedure), or treatments (secondary procedure). Specific bio-markers can be selected for, for which specific imaging targets may be
25 selected, or specific therapies. These bio-markers may instruct selection from

a set of “off-the-shelf” therapies or contrast agents, or specific targets may be developed for that subject/tumor combination. Therefore, the response of the particular subject to the therapy (surgical, radiation, chemotherapy), can guide further therapies in the context of the imaging, pathology, and a larger subject
5 outcome database.

In summary, according to various embodiments of the present disclosure, tracking of preoperative imaging, intraoperative imaging, and pathology results in a system that can link the information back to the original diagnosis, and allow the information to be accessible in the operating room to
10 be integrated between pathology, surgery and radiology. In this way the actual results can be used to support better-informed diagnostic decision making in the future. There does not exist an integrated system in this manner today, as typically radiologists are separated from the actual outcomes and any intraoperative imaging that can be used to support pathology, or radiology is
15 not integrated in any manner. Likewise, in the pathology lab, the imaging information can be provided to with respect to the location of interest from which the sample is obtained, and any imaging information associated with it. Pathology diagnosis can be made more accurate if the context in which the sample is obtained is provided, as well as protecting against any potential
20 processing errors (for instance a completely wrong imaging to pathology correlation may indicate the wrong sample, or a sample taken from the wrong area of interest).

As described below, many of the shortcomings associated with existing solutions can be addressed through deeper integration of imaging and tissue
25 biopsy. With this more integrated combination of regional and localized

imaging, biopsy of samples, and localized, personalized treatment, the following problems with existing solutions may be addressed in the present disclosure: the inability of existing solutions to track locations of individual biopsy samples, and in-vivo imaging of the regions where those samples were
5 selected from; the lack of an existing method to locate virtual “sticky” points or “geo locations” in the subject in-vivo that correspond to biopsy sample locations, critical structures, or tumor margin locations; the lack of an existing method to link together preoperative, intraoperative, biopsy locations that are common; the lack of an existing method to perform intraoperative imaging of
10 tissue using the same modality that was used to diagnose the tissue (for instance an MRI DWI system that performed imaging on the excised surgical sample); the lack of an existing method to locate small regions of interest in the intraoperative system for local sampling or imaging; the lack of an existing method to search through databases of information linking common
15 preoperative imaging, intraoperative imaging, and pathology reports to better inform decision making at all levels; the lack of an existing method to link from radiology to location specific intraoperative imaging information (in this way, common preoperative imaging information can be linked to a set of intraoperative imaging sets that are representative of that information); the
20 inability for a radiologist to link location specific pathology information back to imaging in a way that can better inform current and future clinical diagnosis and conversely; the inability for the pathologist to access prior, or intraoperative imaging to better inform decision-making; the inability, based on existing solutions, to use common imaging taken in-vivo and ex-vivo to ensure
25 the pathology specimen is properly tracked through the clinical chain; the

inability, based on existing solutions, to use the biopsy specific information, such as antibody status, or genetic status, to link to better intraoperative imaging or therapy options either within the same procedure, or done on another occasion; and the inability, based on existing solutions, to build up
5 such a comprehensive database of pathology, in-vivo and ex-vivo (preoperative, intraoperative and postoperative), and link it in a system that can be used for a subject at either the preoperative, the planning, surgery or treatment.

The specific embodiments described above have been shown by way
10 of example, and it should be understood that these embodiments may be susceptible to various modifications and alternative forms. It should be further understood that the claims are not intended to be limited to the particular forms disclosed, but rather to cover all modifications, equivalents, and alternatives falling within the spirit and scope of this disclosure.

WHAT IS CLAIMED IS:

1. A computer implemented method of correlating a local tissue diagnostic measurement with archival tissue analysis data, the method comprising:
 - obtaining local tissue diagnostic data associated with one or more local tissue diagnostic measurements performed on a subject;
 - accessing archival local tissue diagnostic data and tissue analysis data associated with one or more prior local tissue analyses;
 - comparing, according to pre-selected similarity criteria, the local tissue diagnostic data associated with the one or more local tissue diagnostic measurements and the archival local tissue diagnostic data associated with the one or more prior local tissue analyses;
 - identifying one or more similar prior local tissue analyses having archival local tissue diagnostic data satisfying the pre-selected similarity criteria; and
 - providing tissue analysis data associated with the one or more similar prior local tissue analyses.
2. The method according to claim 1 wherein the tissue analysis data comprises pathology data.
3. The method according to claim 1 further comprising accessing outcome data associated with the prior local tissue analyses, and providing outcome data associated with the one or more similar prior local tissue analyses.
4. The method according to claim 1 wherein the outcome data comprises outcome information associated with defects or impairments resulting from a

time-dependent medical procedure data.

5. The method according to any one of claims 1 to 4 wherein two or more similar prior local tissue analyses are identified, the method further comprising:

ranking the tissue analysis data associated with the similar prior local tissue analyses according to pre-selected ranking criteria.

6. The method according to claim 5 further comprising:

accessing outcome data associated with the prior local tissue analyses;
and

wherein the ranking criteria is based on outcome.

7. The method according to claim 5 wherein the pre-selected ranking criteria are determined according to input from an operator.

8. The method according to claim 1 wherein the tissue analysis data associated with the one or more similar prior local tissue analyses are ranked according to the medical institutions at which the prior local tissue analyses were performed.

9. The method according to claim 1 further comprising providing archival local tissue diagnostic data associated with one or more similar prior local tissue analyses.

10. The method according to any one of claims 1 to 9 wherein one or more of the local tissue analyses is associated with a local diagnostic measurement.

11. The method according to claim 10 wherein the diagnostic measurement is performed in-vivo.

12. The method according to claim 10 wherein the diagnostic measurement is performed en-vivo on a tissue sample.

13. The method according to any one of claims 10 to 12 wherein the diagnostic modality associated with the diagnostic measurement is an optical modality.

14. The method according to claim 13 wherein the optical modality associated with the diagnostic measurement is an optical imaging modality.

15. The method according to claim 13 wherein the optical modality associated with the diagnostic measurement comprises Raman spectroscopy.

16. The method according to claim 13 wherein the optical modality associated with the diagnostic measurement comprises hyperspectral analysis.

17. The method according to any one of claims 1 to 16 further comprising:
obtaining additional information pertaining to the subject, and accessing

corresponding additional information associated with subjects associated with the one or more prior local tissue analyses; and

wherein the pre-selected similarity criteria further comprise criteria associated with the additional information.

18. The method according to claim 17 wherein the additional information comprises demographic information.

19. The method according to claim 17 wherein the additional information comprises genetic information.

20. The method according to claim 17 wherein the additional information comprises medical history information.

21. The method according to any one of claims 1 to 20 wherein one or more of the prior local tissue analyses is associated with the subject.

22. The method according to any one of claims 1 to 20 wherein the archival local tissue diagnostic data and tissue analysis data are obtained from a database.

23. The method according to any one of claims 1 to 22 wherein the database further comprises prior location data associated with one or more of the similar prior local tissue analyses, wherein the prior location data is spatially registered to a patient reference frame having a prescribed orientation;

the method further comprising:

obtaining a medical image of at least a portion of the subject and
displaying the medical image on a user interface; and
for each similar prior local tissue analysis having prior location data
associated therewith,
spatially registering the prior location data to the medical image; and
displaying a reference marker associated with the similar prior local
tissue analysis.

24. The method according to claim 23 wherein at least one prior local tissue analysis having prior location data associated therewith pertains to the subject.

25. The method according to claim 22 wherein the database further comprises, for at least one similar prior local tissue analysis, time-dependent medical procedure data recorded during a medical procedure in which the similar prior local tissue analysis was performed.

26. The method according to claim 25 wherein the time-dependent medical procedure data comprises time-dependent positional information associated with the position and the orientation of one or more medical instruments employed during the medical procedure, the method further comprising processing the positional data to render and display a time-dependent simulation of one or more of the medical instruments during at least a portion of the medical procedure.

27. The method according to claim 26 further comprising receiving input from the operator specifying a viewpoint for rendering and displaying the time-dependent simulation is selected.

28. The method according to claim 27 wherein at least one of the medical instruments is employed for performing the similar prior local tissue analysis.

29. The method according to any one of claims 25 to 28 wherein the time-dependent medical procedure data comprises one or more video streams and/or audio streams recorded during the medical procedure.

30. The method according to any one of claims 25 to 28 wherein the time-dependent medical procedure data comprises a recorded state of one or more devices employed during the medical procedure.

31. The method according to any one of claims 1 to 30 further comprising pre-loading the archival local tissue diagnostic data and tissue analysis data associated with one or more prior local tissue analyses prior to evaluating the similarity criteria.

32. The method according to any one of claims 1 to 30 wherein the one or more local tissue analyses are a plurality of local tissue analyses, and wherein one or more weighting factors are applied to the local tissue analyses when evaluating the pre-selected similarity criteria.

33. The method according to claim 32 wherein at least one of the weighting factors is determined based on a confirmed or suspected pathology.

34. The method according to claim 33 wherein the confirmed or suspected pathology is associated with a tumor type and/or tumor stage.

35. The method according to claim 33 wherein the confirmed or suspected pathology is associated with a tumor size or tumor volume.

36. The method according to claim 32 wherein at least one of the weighting factors is determined or modified based on operator input.

37. The method according to claim 32 wherein at least one of the weighting factors is contextually determined based on the medical procedure associated with the local tissue analyses.

38. The method according to any one of claims 1 to 37 further comprising displaying an archival medical image associated with one or more similar prior local tissue analyses.

39. A system for correlating a local tissue diagnostic measurement with archival tissue analysis data, comprising:

 a control and processing system comprising one or more processors and memory coupled to said one or more processors, said memory storing

instructions, which, when executed by said one or more processors, causes said one or more processors to perform operations comprising:

- obtaining local tissue diagnostic data associated with one or more local tissue diagnostic measurements performed on a subject;

- accessing archival local tissue diagnostic data and tissue analysis data associated with one or more prior local tissue analyses;

- comparing, according to pre-selected similarity criteria, the local tissue diagnostic data associated with the one or more local tissue diagnostic measurements and the archival local tissue diagnostic data associated with the one or more prior local tissue analyses;

- identifying one or more similar prior local tissue analyses having archival local tissue diagnostic data satisfying the pre-selected similarity criteria; and

- providing tissue analysis data associated with the one or more similar prior local tissue analyses.

40. A computer implemented method of displaying tissue analysis information on a user interface, the method comprising:

- obtaining a medical image of at least a portion of a subject and displaying the medical image on the user interface;

- obtaining local tissue information corresponding to one or more local tissue analyses performed on the subject;

- obtaining location data identifying a location corresponding to each local tissue analysis, wherein the location data is spatially registered to the medical image;

- displaying one or more reference markers in the medical image, wherein:

each reference marker is associated with one of the local tissue analyses; and

each reference marker is displayed, in the medical image, at the location at which its associated local tissue analysis was performed;

receiving input from an operator identifying a selected reference marker associated with a selected local tissue analysis, thereby identifying selected local tissue information; and

presenting at least a portion of the selected local tissue information associated with the selected local tissue analysis.

41. The method according to claim 40 wherein the selected local tissue information comprises tissue analysis data.

42. The method according to claim 40 or 41 wherein at least one of the local tissue analyses is associated with a tissue biopsy.

43. The method according to any one of claims 40 to 42 wherein the selected local tissue information comprises local tissue diagnostic data obtained via at least one local diagnostic measurement.

44. The method according to claim 43 wherein the local diagnostic measurement is performed in-vivo.

45. The method according to claim 43 wherein the local diagnostic measurement is performed ex-vivo on a tissue sample.

46. The method according to any one of claims 43 to 45 wherein the diagnostic modality associated with the local diagnostic measurement is an imaging modality.

47. The method according to any one of claims 43 to 46 wherein the diagnostic modality associated with the local diagnostic measurement is an optical modality.

48. The method according to claim 47 wherein the optical modality associated with the local diagnostic measurement is an optical imaging modality.

49. The method according to claim 47 wherein the optical modality associated with the local diagnostic measurement comprises Raman spectroscopy.

50. The method according to claim 47 wherein the optical modality associated with the local diagnostic measurement comprises hyperspectral analysis.

51. The method according to any one of claims 40 to 50 further comprising providing a visual representation of an estimated error associated with the accuracy of the location corresponding to one or more tissue analyses.

52. The method according to any one of claims 40 to 51 wherein the selected local tissue information comprises a plurality of types of local tissue information, and wherein displaying at least a portion of the selected local tissue information comprises:

- displaying a list of the types of the selected local tissue information;
- receiving additional input from the operator identifying one or more types of the selected local tissue information to display; and
- presenting the selected types of the selected local tissue information.

53. The method according to claim 52 wherein the types of the selected local tissue diagnostic data comprise diagnostic data from two or more diagnostic modalities.

54. The method according to any one of claims 40 to 53 wherein the selected local tissue information is overlaid on the medical image.

55. The method according to any one of claims 40 to 53 wherein the selected local tissue information is displayed in a separate window of the user interface.

56. The method according to any one of claims 40 to 55 wherein the medical image is obtained preoperativelyoperatively prior to performing a medical procedure involving at least one of the local tissue analyses.

57. The method according to any one of claims 40 to 56 wherein the medical

image, and the local tissue information associated with at least one of the local tissue analyses, are intraoperatively obtained during a common medical procedure.

58. The method according to any one of claims 40 to 56 wherein the least a portion of the selected local tissue information associated with the selected reference marker is displayed intraoperatively during a medical procedure, and wherein at least one said one or more local tissue analyses are performed during the medical procedure.

59. The method according to any one of claims 40 to 57 wherein at least one of the local tissue analyses pertains to a previously medical procedure performed on the subject.

60. The method according to any one of claims 40 to 58 wherein the local tissue information associated with at least one local tissue analysis further comprises additional tissue analysis information associated with a previous local tissue analysis at approximately the same location.

61. The method according to any one of claims 40 to 60 wherein the local tissue information comprises local tissue diagnostic information, the method further comprising:

- accessing archival local tissue diagnostic data associated with one or more prior local tissue analyses;

- comparing, according to pre-selected similarity criteria, the selected local

tissue diagnostic data and archival local tissue diagnostic data associated with one or more prior local tissue analyses;

identifying one or more similar prior local tissue analyses having archival local tissue diagnostic data satisfying the pre-selected similarity criteria; and

displaying archival local tissue diagnostic data associated with one or more similar prior local tissue analyses.

62. The method according to claim 61 further comprising accessing archival tissue analysis data associated with one or more prior local tissue analyses, the method further comprising displaying the archival tissue analysis data.

63. The method according to claim 62 wherein two or more similar prior local tissue analyses are identified, the method further comprising:

calculating one or more pathology measures associated with the similar prior local tissue analyses based on the tissue analysis data; and

displaying the one or more pathology measures.

64. The method according to any one of claims 61 to 63 wherein one or more of the prior local tissue analyses is associated with the subject.

65. The method according to any one of claims 61 to 63 wherein the archival local tissue diagnostic data is obtained from a database.

66. The method according to any one of claims 61 to 65 wherein the reference markers are primary reference markers;

wherein the database further comprises prior location data associated with one or more of the similar prior local tissue analyses, wherein the prior location data is spatially registered to a patient reference frame having a prescribed orientation;

the method further comprising, for each similar prior local tissue analysis having prior location data associated therewith:

spatially registering the prior location data to the medical image; and

displaying a secondary reference marker associated with the similar prior local tissue analysis.

67. The method according to claim 66 wherein each secondary reference marker is displayed such that is visually differentiable from the one or more primary reference markers.

68. The method according to claim 66 or 67 wherein at least one prior local tissue analysis having prior location data associated therewith pertains to the subject.

69. The method according to claim 65 wherein the database further comprises, for at least one similar prior local tissue analysis, time-dependent medical procedure data recorded during a medical procedure in which the similar prior local tissue analysis was performed.

70. The method according to claim 69 wherein the time-dependent medical procedure data comprises time-dependent positional information associated

with the position and the orientation of one or more medical instruments employed during the medical procedure, the method further comprising processing the positional data to render and display a time-dependent simulation of one or more of the medical instruments during at least a portion of the medical procedure.

71. The method according to claim 70 further comprising receiving input from the operator specifying a viewpoint for rendering and displaying the time-dependent simulation is selected.

72. The method according to claim 71 wherein at least one of the medical instruments is employed for performing the similar prior local tissue analysis.

73. The method according to any one of claims 69 to 72 wherein the time-dependent medical procedure data comprises one or more video streams and/or audio streams recorded during the medical procedure.

74. The method according to any one of claims 69 to 72 wherein the time-dependent medical procedure data comprises a recorded state of one or more devices employed during the medical procedure.

75. The method according to any one of claims 61 to 74 further comprising pre-loading the archival local tissue diagnostic data and tissue analysis data associated with one or more prior local tissue analyses prior to evaluating the similarity criteria.

76. The method according to any one of claims 61 to 75 further comprising displaying an archival medical image associated with one or more similar prior local tissue analyses.

77. The method according to claim 76 wherein the archival medical image is processed to display a region approximately equal to the region shown in the medical image.

78. A system for displaying tissue analysis information on a user interface, comprising:

- a control and processing system interfaced with a display device, said control and processing system comprising one or more processors and memory coupled to said one or more processors, said memory storing instructions, which, when executed by said one or more processors, causes said one or more processors to perform operations comprising:

- obtaining a medical image of at least a portion of a subject and displaying the medical image on the user interface;

- obtaining local tissue information corresponding to one or more local tissue analyses performed on the subject;

- obtaining location data identifying a location corresponding to each local tissue analysis, wherein the location data is spatially registered to the medical image;

- displaying one or more reference markers in the medical image, wherein:

- each reference marker is associated with one of the local tissue

analyses; and

each reference marker is displayed, in the medical image, at the location at which its associated local tissue analysis was performed;

receiving input from an operator identifying a selected reference marker associated with a selected local tissue analysis, thereby identifying selected local tissue information; and

presenting at least a portion of the selected local tissue information associated with the selected local tissue analysis.

79. A computer implemented method of correlating preoperative tissue analysis data with archival tissue analysis data from one or more prior medical procedures, the method comprising:

obtaining preoperative tissue analysis data associated with a subject;

accessing archival tissue analysis data associated with one or more prior medical procedures;

accessing time-dependent medical procedure data recorded during the one or more prior medical procedures;

comparing, according to pre-selected similarity criteria, the preoperative tissue analysis data and the archival tissue analysis data associated with the one or more prior medical procedures;

identifying one or more similar prior medical procedures having archival tissue analysis data satisfying the pre-selected similarity criteria; and

processing the time-dependent medical procedure data associated with the one or more similar prior medical procedures to replay at least a portion of the medical procedure.

80. The method according to claim 79 wherein the time-dependent medical procedure data comprises time-dependent positional information associated with the position and the orientation of one or more medical instruments employed during the medical procedure, the method further comprising processing the positional data to render and display a time-dependent simulation of one or more of the medical instruments during at least a portion of the medical procedure.

81. The method according to claim 80 further comprising receiving input from the operator specifying a viewpoint for rendering and displaying the time-dependent simulation is selected.

82. The method according to any one of claims 79 to 81 wherein the time-dependent medical procedure data comprises one or more video streams and/or audio streams recorded during the medical procedure.

83. The method according to any one of claims 79 to 81 wherein the time-dependent medical procedure data comprises a recorded state of one or more devices employed during the medical procedure.

84. The method according to any one of claims 79 to 83 wherein the preoperative tissue analysis data comprises one or more tumor types.

85. The method according to any one of claims 79 to 84 wherein the

preoperative tissue analysis data comprises a suspected stage of a tumor.

86. The method according to any one of claims 79 to 85 wherein the preoperative tissue analysis data comprises tumor location data.

87. The method according to any one of claims 79 to 86 wherein the preoperative tissue analysis data comprises tumor size data.

88. The method according to any one of claims 79 to 87 wherein the preoperative tissue analysis data comprises tumor stiffness data.

89. A system for correlating preoperative tissue analysis data with archival tissue analysis data from one or more prior medical procedures, comprising:

a control and processing system comprising one or more processors and memory coupled to said one or more processors, said memory storing instructions, which, when executed by said one or more processors, causes said one or more processors to perform operations comprising:

obtaining preoperative tissue analysis data associated with a subject;

accessing archival tissue analysis data associated with one or more prior medical procedures;

accessing time-dependent medical procedure data recorded during the one or more prior medical procedures;

comparing, according to pre-selected similarity criteria, the preoperative tissue analysis data and the archival tissue analysis data associated with the one or more prior medical procedures;

identifying one or more similar prior medical procedures having archival tissue analysis data satisfying the pre-selected similarity criteria; and
processing the time-dependent medical procedure data associated with the one or more similar prior medical procedures to replay at least a portion of the medical procedure.

90. A computer implemented method of suggesting one or more steps of a surgical plan based on archival surgical plan data from one or more prior medical procedures, the method comprising:

obtaining tissue analysis data associated with a subject;
accessing archival tissue analysis data associated with one or more prior medical procedures;
accessing surgical plan data associated with the one or more prior medical procedures;
comparing, according to pre-selected similarity criteria, the tissue identification data and the archival tissue analysis data associated with the one or more prior medical procedures;
identifying one or more similar prior medical procedures having archival tissue analysis data satisfying the pre-selected similarity criteria; and
processing the surgical plan data associated with the one or more similar prior medical procedures to generate one or more steps of a suggested surgical plan; and
communicating the one or more steps of the suggested surgical plan.

91. The method according to claim 90 wherein the tissue analysis data

associated with the subject comprises one or more tumor types.

92. The method according to claim 90 or 91 wherein the tissue analysis data associated with the subject comprises a suspected stage of a tumor.

93. The method according to any one of claims 90 to 92 wherein the pathology data associated with the subject comprises tumor location data.

94. The method according to any one of claims 90 to 93 wherein the pathology data associated with the subject comprises tumor size data.

95. The method according to any one of claims 90 to 94 wherein the pathology data associated with the subject comprises tumor stiffness data.

96. The method according to any one of claims 90 to 95 wherein the pathology data associated with the subject comprises the proximity between a tumor and one or more anatomical structures.

97. The method according to any one of claims 90 to 96 wherein the method is performed prior to a medical procedure.

98. The method according to any one of claims 90 to 96 wherein the method is performed prior during a medical procedure.

99. The method according to claim 97 or 98 wherein the medical procedure is

a simulated medical procedure.

100. A system for suggesting one or more steps of a surgical plan based on archival surgical plan data from one or more prior medical procedures, comprising:

a control and processing system comprising one or more processors and memory coupled to said one or more processors, said memory storing instructions, which, when executed by said one or more processors, causes said one or more processors to perform operations comprising:

obtaining tissue analysis data associated with a subject;

accessing archival tissue analysis data associated with one or more prior medical procedures;

accessing surgical plan data associated with the one or more prior medical procedures;

comparing, according to pre-selected similarity criteria, the tissue identification data and the archival tissue analysis data associated with the one or more prior medical procedures;

identifying one or more similar prior medical procedures having archival tissue analysis data satisfying the pre-selected similarity criteria; and

processing the surgical plan data associated with the one or more similar prior medical procedures to generate one or more steps of a suggested surgical plan; and

communicating the one or more steps of the suggested surgical plan.

101. A computer implemented method of correlating a preoperative surgical

plan with archival surgical plan data from one or more prior medical procedures, the method comprising:

- obtaining preoperative surgical plan data associated with a medical procedure to be performed on a subject;

- accessing outcome data associated with one or more prior medical procedures;

- accessing archival surgical plan data employed during the one or more prior medical procedures;

- comparing, according to pre-selected similarity criteria, the preoperative surgical plan data and the archival surgical plan data associated with the one or more prior medical procedures;

- identifying one or more similar prior medical procedures having archival surgical plan data satisfying the pre-selected similarity criteria; and

- providing outcome data associated with the one or more similar prior medical procedures.

102. A system for correlating a preoperative surgical plan with archival surgical plan data from one or more prior medical procedures, comprising:

- a control and processing system comprising one or more processors and memory coupled to said one or more processors, said memory storing instructions, which, when executed by said one or more processors, causes said one or more processors to perform operations comprising:

- obtaining preoperative surgical plan data associated with a medical procedure to be performed on a subject;

- accessing outcome data associated with one or more prior medical

procedures;

accessing archival surgical plan data employed during the one or more prior medical procedures;

comparing, according to pre-selected similarity criteria, the preoperative surgical plan data and the archival surgical plan data associated with the one or more prior medical procedures;

identifying one or more similar prior medical procedures having archival surgical plan data satisfying the pre-selected similarity criteria; and

providing outcome data associated with the one or more similar prior medical procedures.

103. A method of performing tissue analyses while performing a tissue resection procedure on a subject, the method comprising:

during a tissue resection procedure, performing, with a spatially tracked local tissue analysis device, a plurality of local tissue analyses, such that different local tissue analyses correspond to different tissue locations that are exposed during the resection procedure;

employing tracking data associated with the spatially tracked local tissue analysis device to determine, in a reference frame spatially registered to a medical image of the subject, the location data corresponding to each local tissue analysis;

recording local tissue diagnostic data from each local tissue analysis in association with its corresponding location data;

constructing a spatial profile of the resected tissue by correlating the local tissue diagnostic data with the location data.

104. The method according to claim 103 wherein one or more of the plurality of local tissue analyses involves obtaining a biopsy sample that is analyzed postoperatively.

105. The method according to claim 103 or 104 wherein one or more of the plurality of local tissue analyses involves obtaining an in-vivo diagnostic measurement of exposed tissue.

106. The method according to claim 105 wherein the diagnostic modality associated with the diagnostic measurement is an optical modality.

107. The method according to claim 106 wherein the optical modality associated with the diagnostic measurement is an optical imaging modality.

108. The method according to claim 106 wherein the optical modality associated with the diagnostic measurement comprises Raman spectroscopy.

109. The method according to claim 106 wherein the optical modality associated with the diagnostic measurement comprises hyperspectral analysis.

110. The method according to any one of claims 103 to 109 further comprising:

processing the spatial profile of the resected tissue to determine the spatial

profile of a residual tissue margin.

111. A method of performing intraoperative tissue analysis while performing a tissue resection procedure on a subject, the method comprising:

 during a tissue resection procedure:

 performing a local ex-vivo diagnostic measurement on a biopsy sample of a tumor, thereby obtaining a reference measurement associated with tumor tissue; and

 during subsequent tissue resection:

 intermittently performing local in-vivo diagnostic measurements on exposed tissue; and

 comparing the reference measurement to each in-vivo measurement to identify the presence or absence of tumor tissue in the exposed tissue.

112. The method according to claim 111 wherein the diagnostic modality associated with the diagnostic measurement is an optical modality.

113. The method according to claim 112 wherein the optical modality associated with the diagnostic measurement is an optical imaging modality.

114. The method according to claim 112 wherein the optical modality associated with the diagnostic measurement comprises Raman spectroscopy.

115. The method according to claim 112 wherein the optical modality associated with the diagnostic measurement comprises hyperspectral

analysis.

116. The method according to any one of claims 111 to 115 further comprising:

 alerting an operator upon determining that the exposed tissue no longer contains tumor tissue.