



- (51) **International Patent Classification:**
H01L 31/18 (2006.01) H01L 31/0216 (2014.01)
- (21) **International Application Number:**
PCT/NO2014/050215
- (22) **International Filing Date:**
19 November 2014 (19.11.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
20131549 19 November 2013 (19.11.2013) NO
- (71) **Applicant:** INSTITUTT FOR ENERGITEKNIKK
[NO/NO]; Instituttveien 18, N-2007 Kjeller (NO).
- (72) **Inventors:** ZHU, Junjie; Gunnar Schjelderups vei 11 D,
N-0485 Oslo (NO). ZHOU, Su; Building 5, 2# 602 Guoyuan
South Miyun, Beijing, 101500 (CN). HAUG, Halvard;
Sandakerveien 22G, N-0473 Oslo (NO). STENS-
RUD MARSTEIN, Erik; Tærdustien 10, N-2020 Skedsmo-
korset (NO). FOSS, Sean Erik; Tærdustien 21, N-2020
Skedsmokorset (NO). WANG, Wenjing; A1, Building 1
1407, Yue Tan Bei Jie, Beijing West City District, 100037
(CN). ZHOU, Chunlan; No. 6 Beiertiao Zhongguancun,
Beijing 100190 (CN).
- (74) **Agents:** HÅMSØ PATENTBYRÅ ANS et al.; P.O. Box
171, N-4302 Sandnes (NO).
- (81) **Designated States** (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States** (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,

[Continued on next page]


(54) **Title:** PASSIVATION STACK ON A CRYSTALLINE SILICON SOLAR CELL

Fig. 6a

(57) **Abstract:** There is described a method for manufacturing a passivation stack on a crystalline silicon solar cell (1) device, the method comprising the steps of: - providing a substrate comprising a crystalline silicon layer (2), such as a crystalline silicon wafer or chip; - cleaning a surface (21, 23) of the crystalline silicon layer (2) by removing an oxide layer at least from a portion of one side of the crystalline silicon layer (2); - depositing, on at least a part of the cleaned surface (21, 23), a layer of silicon oxynitride (3); and - depositing a capping layer (5) comprising a hydrogenated dielectric material on top of the layer of silicon oxynitride (3), wherein the layer of silicon oxynitride (3) is deposited at a temperature between 100 °C and 200 °C, preferably between 100 °C and 150 °C, and even more preferably between 100 °C and 130 °C, wherein the step of depositing the layer of silicon oxynitride (3) includes the sub-steps of: - using N₂O and SiH₄ as precursor gases in an N₂ ambient atmosphere; and - depositing silicon oxynitride with a gas flow ratio of N₂O to SiH₄ below 2, preferably below 1, and even more preferably around 0.5. There is also described a crystalline silicon solar cell device obtainable by means of a method according to the invention.



SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, —
GW, KM, ML, MR, NE, SN, TD, TG).

*before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))*

Published:

— *with international search report (Art. 21(3))*