



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : E05D 5/02		A1	(11) International Publication Number: WO 97/23699
			(43) International Publication Date: 3 July 1997 (03.07.97)
(21) International Application Number: ✓ PCT/EP96/05655		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(22) International Filing Date: ✓ 16 December 1996 (16.12.96)			
(30) Priority Data: 295 20 472.9 22 December 1995 (22.12.95) DE 295 20 471.0 22 December 1995 (22.12.95) DE			
(71) Applicant (for all designated States except US): SOCIETA' ITALIANA PROGETTI S.R.L. [IT/IT]; Via Pacinotti, 26/28, I-20013 Magenta (IT).			
(72) Inventor; and (75) Inventor/Applicant (for US only): MARINONI, Mario [IT/IT]; Piazza Vittorio Veneto, 12, I-20013 Magenta (IT).			
(74) Agent: VIERING, JENTSCHURA & PARTNER; Steinsdorfs- trasse 6, D-80538 München (DE).			

(54) Title: MOUNTING FOR A DOOR LEAF

(57) Abstract

A mounting for a door leaf, a fanlight leaf or the like, particularly for an all-glass leaf, has a plane clamping plate (1) and a plane counter clamping plate (2). The mounting can be attached, in the region of an edge recess (3) in a leaf edge (5) of the leaf, to the two opposite surfaces, and the leaf can be pinched between the clamping plate (1) and the counter clamping plate (2) by means of fastening screws (7) joining the clamping plate and the counter clamping plate. At the clamping plate (1) a web plate (9) is formed extending perpendicular to the clamping plate, which web plate, in the assembled condition, spans over the distance between the clamping plate (1) and the counter clamping plate (2) extending through the edge recess (3). The counter clamping plate is provided with a rectangular recess (17, 41) being adapted to the shape of the free end of the web plate (9), the web plate in the assembled condition engaging by means of its free end with the rectangular recess (17, 41). The clamping plate (1) inclusive of the web plate (9) and the counter clamping plate (2) are formed as extruded profile rails or rolled profile rails.

