

DEVICE FOR DELIVERY OF MEDICAL DEVICES TO A CARDIAC VALVE

Field of the Invention

This invention pertains in general to the field of medical devices. In particular the invention
5 relates to the positioning of catheters for the delivery of medical devices and the procedures, and more specifically to the transvascular delivery of a medical device to a cardiac valve.

Background of the Invention

The human heart is a hollow muscular organ, responsible for pumping a large volume of
10 blood around the human body every day. The ability to pump the blood is facilitated by several heart valves which open and close appropriately to allow blood passage through the heart. Heart valve dysfunction through natural defects or through the increasing incidence of heart disease, often requires the dysfunctional valve to be treated, with the main treatment modalities being mechanical adjustment of the valve or replacing the valve altogether. Current medical techniques are aimed at
15 moving away from the major open heart surgery procedure, which is very traumatic for the patient, to more minimally invasive catheter based procedures, which are less traumatic, although more complicated procedures.

Catheter based procedures require precise positioning of the catheter, used to deliver for example the replacement valve, in an optimal position in relation to the cardiac valve to be treated.
20 This is especially important as misalignment has the potential to damage adjacent cardiac structures leading to severe coronary complications. Placement of the catheter adjacent to a heart valve is hampered by the fact that the heart continues to pump throughout the procedure, giving rise to significant levels of turbulence which the catheter has to overcome to maintain its position. Furthermore, clotting of the blood leading to emboli is a continuous threat, as potentially they can
25 lead to serious complications such as stroke.

In the US application 2009/0030510A1, it is disclosed that a significant obstacle to replacement of an aortic valve is the accurate placement of the medical device to replace the aortic valve. The solution taught to this problem is a temporary aortic valve (TAV) device. This is a catheter which has at the distal end a plurality of balloons, which can be inflated to stabilize the position of the
30 TAV by applying pressure directly to the aortic walls of the patient. Further valve modulating tools can be passed through the lumen of the TAV. Between the balloons, blood is allowed to pass, simulating aortic valve function. This device is devised for the ablation and replacement of the aortic valve, with

the balloons of the TAV fully inflated throughout the procedure to facilitate lodgment against the arterial walls.

The balloons are inflated throughout the entire medical procedure. As the balloons hamper bloodflow by restricting the available cross section for blood flow of the aortic lumen, potentially leading to leading a number of undesired issues. For instance, deliverable blood volume during the procedure may be reduced having potential dire consequences for the patient. Blood pressure may increase upstream the restriction created by the inflated balloons. The balloons may dislocate the longer time they are inflated in the aortic lumen, e.g. due to the increased blood pressure upstream thereof.

WO 2006/029370 and US 2009/0287182 discloses expandable transluminal sheaths. The distal end of the sheath is maintained in the first, low cross-sectional configuration during advancement through the atrial septum into the left atrium. The distal end of the sheath is expanded using a radial dilator, a balloon, to dilate the hole in the tissue of the atrial septum. A problem is that the device is not sufficiently stabilized for secure positioning. The radial expansion is purely for allowing the hole to heal more completely as opposed to cutting a large hole from the start.

US2005/0085842 discloses an expandable guide sheath. The sheath is advanced into a blood vessel in a contracted condition, expanded to an enlarged condition to define a lumen. The expanded lumen is for delivering fluids or instruments. Also in this prior art, a problem is that the device is not sufficiently stabilized for secure positioning.

Hence, improved or alternative medical devices and procedures for stabilizing the introducer sheath during cardiac valve replacement would be advantageous, in particular allowing for increased cost-effectiveness, and/or patient safety.

Summary of the Invention

Accordingly, embodiments of the present invention preferably seek to mitigate, alleviate or eliminate one or more deficiencies, disadvantages or issues in the art, such as the above-identified, singly or in any combination by providing a medical device and a method according to the appended patent claims.

The present invention is an introducer sheath that overcomes the positional problems that current catheters face, by using a locking system which locks the catheter to maintain it at the desired anatomical position. In addition to maintaining the position, the invention is so devised so that interference with the blood flow is minimal and deployment of an embolic capture device is provided

for, to decrease the risk for embolism, from for example debris emanating from the treatment of a stenotic valve.

According to a first aspect, a catheter device is provided for transvascular delivery of a medical device to a cardiac valve region of a patient. The catheter device comprises an elongate sheath with a lumen and a distal end, and an elongate member with a distal end portion comprising a plurality of radially expandable units, wherein said elongate member is retractably insertable into said lumen, said expandable units being arranged for temporarily positioning said elongate sheath in relation to said cardiac valve. Said elongate sheath comprises releasable locking members for controllably locking said elongate sheath in a shape at least partly along its length from a relaxed state to a locked state when positioned in relation to said cardiac valve by said expandable units.

In a second aspect, a method of transvascularly delivering a medical device to a cardiac valve of a patient is provided. The comprises providing and minimally invasively introducing a catheter comprising an elongate sheath with a lumen in a relaxed state into said vascular system; navigating a distal end of said elongate sheath through said vascular system to said cardiac valve; inserting said elongate member with a distal end portion comprising a plurality of radially expandable units, into said lumen of said elongate sheath; advancing said elongate member through said elongate sheath to said distal end of said elongate sheath; radially expanding said expandable units to temporarily position in relation to said valve said elongate sheath; releasing locking members of said catheter to maintain said elongate sheath in a locked state; retracting said expandable units and withdrawing said elongate member from the lumen of the elongate sheath; delivering a medical device through the lumen of said locked elongate sheath to said heart valve; releasing said locking members to return said elongate sheath to said relaxed state; and withdrawing said elongate sheath in said relaxed state from the vasculature of said patient.

Further embodiments of the invention are defined in the dependent claims, wherein features for the second and subsequent aspects of the invention are as for the first aspect mutatis mutandis.

It should be emphasized that the term "comprises/comprising" when used in this specification is taken to specify the presence of stated features, integers, steps or components but does not preclude the presence or addition of one or more other features, integers, steps, components or groups thereof.

Brief Description of the Drawings

These and other aspects, features and advantages of which embodiments of the invention are capable of will be apparent and elucidated from the following description of embodiments of the present invention, reference being made to the accompanying drawings, in which

5 Fig 1A is a schematic illustration of an elongate sheath connected to a hemostatic valve;

Fig 1B is a schematic illustration of an elongate member, with the radially expandable units in the collapsed configuration;

Fig 2A is a schematic illustration of the distal end portion of the elongate member with the radially expandable units in the collapsed configuration;

10 Fig 2B is a schematic illustration of the distal end portion of the elongate member with the radially expandable units in the expanded configuration;

Fig 2C is a schematic illustration frontal view of the distal end portion of the elongate member with the radially expandable units in the collapsed configuration;

15 Fig 2D is a schematic illustration frontal view of the distal end portion of the elongate member with the radially expandable units in the expanded configuration;

Fig 3A, 3B, 3C, 3D are schematic illustrations of embodiments of the elongate sheath in the flexible, unlocked configuration;

Fig 3E is a schematic illustration of the cross sectional view of the elongate sheath in the unlocked state;

20 Fig 3F is a schematic illustration of one embodiment of the cross sectional view of the elongate sheath in a locked state;

Fig 3G is a schematic illustration of another embodiment of the cross sectional view of the elongate sheath in the locked state;

25 Fig 4A is a schematic illustration of the elongate sheath delivered transaxillary to a cardiac valve, where an embolic protection filter is deployed, and the sheath is in a relaxed state;

Fig 4B is a schematic illustration where the relaxed sheath is positioned in relation to the cardiac valve by expandable units of an elongate member extending outside the distal end of the sheath;

30 Fig 4C is a schematic illustration of the cross sectional view of the elongate sheath incorporating a second channel for delivering the embolic protection filter;

Fig 4D is a schematic illustration of the elongate sheath delivered transaxillary to a cardiac valve, and the sheath is in the locked configuration arranged relative to an aortic cardiac valve, and the expandable units being withdrawn after positioning the sheath;

Fig 4E is a schematic illustration of the elongate sheath delivered transfemorally to a cardiac valve, where an embolic protection filter is deployed and the sheath in the locked configuration;

Fig 4F is a schematic illustration of the elongate sheath delivered transaxillary to a cardiac valve, and where the relaxed sheath is positioned in relation to the cardiac valve by expandable units of the sheath;

Fig 4G is a schematic illustration of the elongate sheath delivered transaxillary to a cardiac valve, and where an embolic protection filter is deployed over the vessels in the aortic arch via a second channel of the sheath;

Fig 4H is a schematic illustration of the elongate sheath delivered transfemorally to a cardiac valve, and where an embolic protection filter is deployed over the vessels in the aortic arch via a second channel of the sheath; and

Fig 5 is a flowchart for a method of implanting a medical device.

Description of embodiments

Specific embodiments of the invention will now be described with reference to the accompanying drawings. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. The terminology used in the detailed description of the embodiments illustrated in the accompanying drawings is not intended to be limiting of the invention. In the drawings, like numbers refer to like elements.

In an embodiment of the invention according to Fig 1A, a catheter device 1 for transvascular delivery of a medical device to a cardiac valve region 6 (see e.g. Fig. 4D) of a patient is shown. The catheter device comprises an elongate sheath 2 with a lumen and a distal end 3. In addition in Fig 1B an elongate member 4 is provided with a distal end portion 9 comprising a plurality of radially expandable units 5. The end portion 9 may include an obturator. The expandable units 5 are arranged for temporarily positioning the elongate sheath 2 in relation to the cardiac valve 6, Fig. 4B and 4F. The elongate member 4 is retractably insertable into the lumen of the elongate sheath 2 and the elongate sheath 2 comprises releasable locking members for controllably locking the elongate sheath 2 in a shape at least partly along its length from a relaxed state (See Fig 3B, and Fig. 4A-B, 4F) to a locked state (See Fig 3C-D, and Fig. 4D-E, 4G-H) when positioned in relation to the cardiac valve 6 by the expandable units 5.

The elongate sheath 2 depicted in Fig 1A is designed to be deliverable transvascularily in the relaxed state which facilitates optimal flexibility when transiting through the vasculature. When at the desired anatomical location the elongate sheath 2 is able to transit from the relaxed state to the locked state by activation of the locking members, when positioned in relation to the cardiac valve 6, as seen in Fig 4D-E, by said expandable units 5, which facilitates optimal stabilization of the catheter 1 for subsequently affixing the medical device to the heart valve 6.

Fig. 4A shows the elongate sheath inserted in its relaxed shape. Fig. 4B shows the radially expandable units 5 in their expanded configuration, i.e. outside the elongate sheath 2, which positions the elongate sheath 2 centrally over the valve 6. The expandable units 5 expand out of the elongate member 4, which extends beyond the distal end of the sheath 2. Thereafter the elongate sheath 2 is brought to its locked state by locking members, and the elongate member 4 is retractable from the lumen of the elongate sheath 2 together with the plurality of radially expandable units 5 when collapsed, as seen in Figs. 4D-E. The sheath 2 is now positioned and stabilized over the valve 6. This overcomes the problems in prior art with insufficient stabilization and lack of accurate positioning. Merely providing an expandable catheter could not provide stabilization as with the locking members of the sheath 2. Expandable catheters have another purpose, which is providing an accessible lumen or dilating septum punctures. Further, expandable members of previous catheters are merely for providing aforementioned expansion and not for positioning the catheter centrally over a valve as provided by catheter 1. When the elongate sheath 2 is locked and, when the elongate member 4 is retracted, the lumen of the elongate sheath 2 is accessible for delivery of a medical device to the cardiac valve 6 region.

Alternatively, or in addition, expandable units, such as balloons may be arranged on the outside of the sheath 2. The expandable unit may be integrally formed with the sheath, as seen in Fig. 4F. Thus, the expandable units do not affect the cross section of the lumen of sheath 2. Upon returning to the unexpanded state, e.g. by deflating balloons of the expandable units 5, a delivery of a medical device through the catheter lumen may be made without the need to retract the expandable units 5.

The expandable units provide for a defined positioning of the distal end of the catheter sheath 2 in an anatomical structure, like a blood vessel, an atrium or cardiac chamber, relative a cardiac valve. This allows for a precision delivery of a medical device through the catheter device. Movements of certain anatomical structures are very limited over the cardiac cycle. For instance the aortic arch is relatively stable and the locked catheter will stay substantially in the same spatial

orientation, direction, and distance to the cardiac valve as during the final positioning provided by the expanded expandable units 5.

The catheter may thus be positioned relative a cardiac valve in an anatomical structure.

5 The catheter may be locked in the locked configuration along its entire length. Alternatively, it may only be locked along a distal portion thereof. A distal portion may for instance be the portion arranged in the ascending aorta, the aortic arch and the descending aorta, as shown in Fig. 4E. The catheter may comprise an embolic protection unit 8, such as a embolic protection filter 8. The embolic protection unit 8, when protruding out of the second lumen 7 and being in apposition against the surrounding vessel wall, may further contribute to stabilizing the distal end of the locked catheter in
10 place relative to the cardiac valve. Hence, when the embolic protection unit 8 is expanded it will function as an anchor to the sheath because it prevents movement of the sheath 2 in the aortic arch due to the second channel 7, from which the embolic protection unit expands, is fixed to the sheath. The delivery unit 13 for the embolic protection unit 8 has sufficient rigidity to allow an anchoring function for the sheath 2.

15 Fig 4D is a schematic illustration of the elongate sheath delivered transaxillary to a cardiac valve, here the aortic valve 6. The embolic protection filter 8 is deployed, and the sheath 2 is in the locked configuration arranged relative to an aortic cardiac valve 6.

Fig 4E is a schematic illustration of the elongate sheath delivered transfemorally to a cardiac valve, where an embolic protection filter is deployed and the sheath in the locked
20 configuration.

In Figs. 4D and 4E, the expandable units 5 are not shown, as they are either retracted from the sheath, or returned to their low profile unexpanded/collapsed configuration in the sheath.

In Fig. 4G-H the embolic protection filter 8 is positioned over two or three of the vessels in the aortic arch, respectively.

25 In all configurations shown in Figs. 4A-B, 4D-H, the side vessels 22 are effectively protected from embolic particles entering from the aortic arch. Embolic particles are carried with the blood flow past the embolic protection device along the aortic arch to anatomical structures that are less sensitive than e.g. the brain to which some of the side vessels 22 lead the blood flow. Embolic protection units may be filter units in which the embolic particles are caught. Alternatively, or in
30 addition, the embolic protection units may provide for the particles to slide along the protection unit, but not pass it or fasten in it.

In embodiments, such as illustrated in Fig 4A-H a catheter 1 having a second channel 7 that extends parallel on the outer portion or the inner portion of the elongate sheath 2 is depicted.

This channel 7 allows for the delivery of further units for example an embolic protection device 8 or liquids to aid the procedure to place the medical device, when the lumen of the elongate sheath 2 is used for the elongate member 4 or medical device.

The second channel 7 may be an integral part on the inside or outside of the elongate sheath 2. This has the advantage of being relatively cheap to manufacture by an extrusion method.

In Figs 4A-H, an expandable embolic filter 8 embodiment is depicted. The embolic protection or filter device 8 may be extended before extending the aforementioned expandable units 5. This potentially enhances patient safety by capturing any emboli such as plaque debris produced from the treatment of a stenotic valve, and thus reduces the chance for serious complications such as stroke. In these figures at least a portion of the expandable embolic filter 8 extends from the orifice of the side channel 7 through which the embolic filter 8 is passed. The embolic filter may be of the type as disclosed in WO 2010/026240, which is incorporated herein in its entirety for all purposes. The embolic filter unit may be non-tubular, extending substantially planar in the expanded state. This provides for a compact device and efficient blocking of side branch vessels in the aortic arch from embolies. Interaction with the side walls in the aortic arch is therefore also kept at the minimum, avoiding scraping off further debris to be transported with the blood stream. Simultaneously, the aortic arch is kept open for unrestricted navigation of the sheath 2. Hoop shaped baskets in previous devices scrapes against the vessel wall and blocks a substantial portion of the navigational space in the aortic arch.

Extending "planar" in this context means that the thickness of the device is substantially smaller than the longitudinal extension thereof. Moreover, "planar" means such dimensions perpendicular to the longitudinal extension of the protective material, that blood flow through the aortic arch is not hindered by the protective device.

By having a second channel in the sheath 2, the distal end of the sheath can be positioned appropriately at the valve, by the stabilizing and anchoring effect of the protection unit 8 extending from the second channel, while medical device can be delivered through the lumen of the sheath without any hindrance from the protection unit 8 or e.g. expandable units such as balloons, while at the same time the side branch vessels of the aortic arch are protected from embolies that may be transported in the blood stream from the procedure performed at the valve.

The catheter device 1 may comprise a delivery unit 13 connectable to the embolic filter unit 8 at a connection point 14, as illustrated in Figs. 4G-H. The connection point 14 is arranged off-centre at the embolic filter unit such that the delivery unit 13 is connectable off-center to the embolic filter unit 8. The off centre position of the embolic filter unit is advantageous for deploying it

with the sheath 2 via the delivery unit 13, while efficiently protecting the carotid arteries from embolies, when carrying out the intervention. Blood flow is kept open efficiently by such compact device. The term "off centre" used in the context of the present application means eccentric, or not arranged or located in a center. The center is e.g. a center of a circular unit, a focal point of an elliptical unit, a point on a center line, such as a longitudinal center line of an elongated unit, etc. A periphery of a unit is located "off centre" as it is arranged at a distance in relation to a center of the unit.

The elongate member 4 may be comprised of three balloons positioned radially equidistant around the longitudinal axis (See Fig 2C and D). Fewer or more balloons are possible, as well as alternative expansion units such as expandable mechanical levers, or swellable units for example retractable sponges. The expansion units 5 allow for optimal positioning of the elongate sheath 2 in relation to the aforementioned cardiac valve 6. The multiple balloon expansion unit can be expanded (See Fig 2D) using a variety of means for example using a fluid means or where appropriate gaseous means. The balloons can also be individually or simultaneously expanded as well as inflated to differing pressures independently of the other expanding units.

Alternatively, the elongate member 4 is retractably inserted into the elongate sheaths 2 lumen to a length equal to the distance between the distal end 9 and the second proximal marker 10. In this embodiment proximal markers 10 and 11 are used to guide the positional orientation of the distal end portion 9 and thus provide for optimal alignment of the expandable units 5 with the portion of the elongate sheath 2 to be expanded. This facilitates safe positioning at the desired valve region.

In a further embodiment the elongate sheath 2 is comprised of radiopaque material, facilitating visualization of the elongate sheath 2 which provides for optimal positioning of the elongate sheath 2 for delivery of the medical device. Alternatively radiopaque fiducial markers on the elongate sheath 2 can be used for optimal positioning of the sheath 2 within the body of the patient.

The embodiment shown in Fig 2A and B, includes a guide wire 12 which is firstly positioned within the patient which facilitates optimal transit of the elongate sheath 2 and elongate member 4 to the desired anatomical site.

In the embodiments of Figs. 3-4, the locking units may comprise releaseable latches although any one from draw strings, squeezing mechanisms, or the like could be envisaged as being used to lock the elongate sheath 2 in a locked state, i.e. a rigid or semi-rigid state of the sheath that allows the sheath 2 to maintain a specific curvature, i.e. reduction in flexibility, and thereby secure its position relative to the anatomy, as seen in e.g. Fig. 4D-E. Further, thermal, electrical, magnetic or

chemical properties of the material of the locking units or the elongate sheath 2 itself may provide variable flexibility for changing between a locked state and a relaxed state.

In a specific embodiment, the elongate may be expanded when in locked configuration. Releasing of locking units when the elongate sheath 2 is in an expanded state locks the elongate sheath 2 in the expanded state and thus retains the optimal position for medical device positioning through the procedure.

The locked elongate sheath 2 may be used in medical procedures to delivery of a medical device to the cardiac valve 6, which could include an artificial heart valve prosthesis, an annuloplasty device or leaflet clips.

The elongate sheath 2 maybe a constituent of a medical system devised for transvascularly delivering a medical device to a cardiac valve 6 of a patient. The method as depicted in Fig 5 initially comprises 100 minimally invasively either transfemorally (See Fig 4E) or transaxillary (See Fig 4D) introducing a catheter 1 comprising an elongate sheath 2 with a lumen in a relaxed state into the patients vascular system. Step 110 involves the distal end 3 of said elongate sheath 2 being navigated through the vascular system to the desired cardiac valve, Fig. 4A. The next step in the system 120, involves the elongate member 4 with a distal end portion 9 comprising a plurality of radially expandable units 5, being inserted into the lumen of the elongate sheath 2, whereupon it is advanced through the elongate sheath 2 to the distal end of the elongate sheath 2, Fig. 4B. Alternatively, expandable units 5 of the sheath may be expanded at this stage (without introducing an elongate member 4 into the sheath, Fig. 4F. Whereupon step 130 is initiated which involves the plurality of radially expandable units 5, being radially expanded to temporarily position in relation to the cardiac valve 6 the elongate sheath 2, (See Fig 4B and F).

Following positioning, the locking members of the catheter are released to maintain the elongate sheath 2 in a locked state (step 140). Step 150 of the system can then be performed whereby the expandable units 5 are then retracted and the elongate member 4 is withdrawn from the lumen of the elongate sheath 2, Fig. 4D-E. Alternatively, the expandable units 5 of a sheath 2 are brought back to the non-expanded state.

The embolic protection unit as shown in Figs. 4A-H, may then be advanced out of the second channel 7. In this manner, side vessels are protected from embolic material, such as debris.

A medical device can now be delivered through the lumen of the locked elongate sheath 2 to the heart valve 6. This delivery is done with high spatial precision. Blood flow in the lumen around the locked sheath 2 is affected less than with expanded expandible units 5.

The medical device may for instance be a cardiac valve repair or replacement device.

When the medical device is delivered, release of the locking members to return the elongate sheath 2 to the relaxed state can now be performed (step 160) with the subsequent withdrawal of the elongate sheath 2 in the relaxed state from the vasculature of the patient.

5 The embolic protection unit as shown in Figs. 4A-H, may be retracted prior or after the release of the locking members.

Locking of the elongate sheath 2 in the locked state (Fig 3B-D) comprises releasing the locking members for controllably locking the elongate sheath 2 when positioned in relation to the cardiac valve 6 by the expandable units 5. This serves to retain the optimal position for delivery of the medical device during the procedure.

10 To ensure the optimal positioning of the elongate member 4 when it is inserted into the elongate sheath 2, the elongate member 4 is inserted to a length which is equal to the distance between the distal end and the second proximal marker 10 of the elongate member 4. Primarily the elongate sheath 2 will be centrally positioned in relation to the cardiac valve 6, which facilitates optimal delivery of the medical device, although other positions off-center could also be desirable.

15 The medical system is primarily used for the delivery of a medical device to be affixed to the particular cardiac valve 6, which include the aortic and mitral valves of a patient. After delivery of the medical device to the cardiac valve 6, the medical device delivery system is withdrawn through the lumen of the locked elongate sheath 2, which may be aided if the elongate sheath 2 is in an expanded state. After removal of the medical device delivery system, the elongate sheath 2 in said
20 locked state transits to said relaxed state which facilitates enhanced retraction of the elongate sheath 2.

The present invention has been described above with reference to specific embodiments. However, other embodiments than the above described are equally possible within the scope of the invention. Different method steps than those described above, may be provided within the scope of
25 the invention. The different features and steps of the invention may be combined in other combinations than those described. The catheter may be positioned and locked in other cardiac anatomical structures than illustrated. Medical devices delivered through the catheter sheath may be any medical device to be delivered to the cardiac valve tissue. The scope of the invention is only limited by the appended patent claims.

30

CLAIMS

1. A catheter device for transvascular delivery of a medical device to a cardiac valve region of a patient, said catheter device comprising
- 5 an elongate sheath with a lumen and a distal end, and
- an elongate member with a distal end portion comprising a plurality of radially expandable units, wherein said elongate member is retractably insertable into said lumen,
- said expandable units being arranged for temporarily positioning said elongate sheath in relation to said cardiac valve when in an expanded state outside said distal end of said elongate
- 10 sheath; and
- wherein said elongate sheath comprises releasable locking members for controllably locking said elongate sheath in a shape at least partly along its length from a relaxed state to a locked state when positioned in relation to said cardiac valve by said expandable units in order to stabilize said elongate sheath.
- 15
2. The catheter device of claim 1, wherein said elongate sheath is deliverable transvascularly in said relaxed state for transiting from said relaxed state to said locked state when positioned in relation to said cardiac valve by said expandable units, and wherein said elongate member is retractable from said lumen together with said plurality of radially expandable units when
- 20 collapsed, for said elongate sheath being locked and, when said elongate member is retracted, said lumen is accessible for said delivery of said medical device to said cardiac valve region.
3. The catheter device of claim 1 said catheter having a second channel that extends parallel to or in said elongate sheath.
- 25
4. The catheter device of any claims 1 to 3, wherein said side channel is affixed or integral with on the outer portion of said elongate sheath; or wherein said side channel is affixed on or integral with the inside portion of said elongate sheath.
- 30
5. The catheter device of any of claims 1 to 4, wherein at least a portion of an expandable embolic protection unit, such as a filter, is arranged to extend from the orifice of said side channel.

6. The catheter device according to claim 5, wherein said embolic protection unit is non-tubular, extending substantially planar in said expanded state for covering ostia of the side branch vessels in the aortic arch.

5 7. The catheter device according to claim 5 or 6, comprising a delivery unit connectable to said embolic protection unit at a connection point, wherein said connection point is arranged off-centre at the embolic protection unit such that said delivery unit is connectable off-center to said embolic protection unit.

10 8. The catheter device according to any of claims 5-7, wherein said embolic protection unit is arranged to stabilize said distal end of said sheath when said embolic protection unit is expanded out of said second channel.

15 9. The catheter device according to claim 8, wherein said embolic protection unit is an anchor to said sheath when in an expanded state.

20 10. The catheter device of any of claims 1 to 11, wherein said plurality of radially expandable units comprises expandable balloons, preferably three balloons positioned radially equidistant around a longitudinal axis of said elongate sheath.

25 11. The catheter device of any of claims 1 to 10, wherein said plurality of radially expandable units comprises expandable mechanical levers, or swellable units, such as sponges, retractable into said sheath.

12. The catheter device of any of claim 1 to 11 wherein said elongate member is retractably inserted into said elongate sheath's lumen to a length equal to the distance between the distal end and a proximal marker.

30 13. The catheter device of claims 1 to 12 wherein said elongate sheath comprises radiopaque fiducial markers.

14. The catheter device of claims 1 to 13 wherein said locking members are comprised in the list of a draw string, releasable latches, or a squeezing mechanism.

5 15. The catheter device of any of claims 1 to 14, wherein said medical device is an artificial replacement valve or a valve repair device, such as an annuloplasty implant.

16. The catheter device of any of claims 1 to 15, wherein said cardiac valve is an aortic valve of said patient; or a mitral valve of said patient.

10 17. A kit of a catheter device of any of claims 1 to 16 and a medical device for a cardiac valve.

18. A system for transvascularily delivering a medical device to a cardiac valve of a patient, said system comprising

15 a catheter comprising an elongate sheath with a lumen in a relaxed state for minimally invasively introducing into said vascular system;

said sheath having a distal end of said elongate sheath for navigating through said vascular system to said cardiac valve;

a plurality of radially expandable units at least temporarily provideable at said distal end of

20 said elongate sheath;

wherein said radially expandable units are arranged for expanding to temporarily position said distal end in relation to said cardiac valve;

and locking members of said catheter which, when released, maintain said sheath in a structurally locked state to maintain its spatial position relative said cardiac valve;

25 whereby said expandable units are arranged to allow for increased blood flow around said sheath when returned to a non expanded configuration while said locked state is maintained for delivering a medical device through the lumen of said locked elongate sheath to said heart valve;

and wherein said elongate sheath is arranged to return to said relaxed state when said locking members are released for withdrawing said elongate sheath in said relaxed state from the

30 vasculature of said patient.

19. A method of transvascularily delivering a medical device to a cardiac valve of a patient comprising:

introducing a catheter comprising an elongate sheath with a lumen in a relaxed state into said vascular system;

navigating a distal end of said elongate sheath through said vascular system to said cardiac valve;

5 radially expanding expandable units of said catheter or an elongate member positioned beyond a distal end of said sheath, to temporarily position in relation to said valve said elongate sheath;

releasing locking members of said catheter to maintain said elongate sheath in a locked state;

10 delivering a medical device through the lumen of said locked elongate sheath to said heart valve;

releasing said locking members to return said elongate sheath to said relaxed state; and withdrawing said elongate sheath in said relaxed state from the vasculature of said patient.

15 20. A method according to claim 19 comprising,

inserting an elongate member with a distal end portion comprising a plurality of said radially expandable units, into said lumen of said elongate sheath;

advancing said elongate member through said elongate sheath to said distal end of said elongate sheath;

20 retracting said expandable units and withdrawing said elongate member from the lumen of the elongate sheath.