

SPECIFICATION

TITLE OF INVENTION: VERTICAL-SHAFT WINDMILL

FIELD OF THE INVENTION

[0001]

The present invention relates to a vertical shaft wind turbine, particularly relates to a vertical shaft wind turbine comprising a vertical shaft rotor supported by a vertical main shaft of which upper and lower end portions are respectively coupled with rotation shafts of upper and lower generators without using bearings, the generators being respectively arranged in upper and lower horizontal frame bodies of a support frame body for supporting the vertical shaft rotor, such that the vertical main shaft is vertically aligned and is cooperatively movable to reduce torsion.

BACKGROUND OF THE INVENTION

[0002]

Generally, as described in Patent Literature 1 for example, a vertical main shaft of a vertical shaft wind turbine is vertically provided on a generator, and upper and lower and/or intermediate portions of the vertical main shaft are supported by each bearing.

PRIOR ART

PATENT LITERATURES

[0003]

Patent Literature 1: JP 2006-118384 A

SUMMARY OF THE INVENTION

PROBLEMS TO BE SOLVED BY THE INVENTION

[0004]

In the invention described in Patent Literature 1, since the upper and lower portions of

the vertical main shaft are supported by each of the bearings, even though a rotation shaft of the generator and the vertical main shaft of the wind turbine are vertically supported, a deviation is generated. Therefore, the generator is loaded when the wind turbine rotates and accelerates, and torsion is generated on the vertical main shaft, thereby sometimes generating vibration and noise owing to the vibration.

MEANS FOR SOLVING THE PROBLEMS

[0005]

In view of the above disadvantages of the conventional techniques, the following technical means are taken according to the present invention.

[0006]

(1) A vertical shaft wind turbine comprising a plurality of lift-type vertical blades arranged at fixed intervals around a vertical main shaft, wherein each of the lift-type vertical blades has a substantially vertical main portion and upper and lower inward circular arc-shaped portions that are respectively and continuously formed from a top and a bottom of the substantially vertical main portion to respectively elongate toward the vertical main shaft, a tip portion of the upper inward circular arc-shaped portion is fixed to a fixing portion of an upper blade fixture arranged on the vertical main shaft, and a tip portion of the lower inward circular arc-shaped portion is fixed to a fixing portion of a lower blade fixture arranged on the vertical main shaft,

wherein the vertical shaft wind turbine further comprises a support frame body which is framed with horizontal frame bodies horizontally arranged in upper and lower stages and a plurality of support poles, and a generator which is horizontally arranged in each plane central portion surrounded by inner frames respectively provided in the horizontal frame bodies,

wherein the upper generator arranged in the upper horizontal frame body has a rotation shaft of which a lower end portion vertically protrudes downward from a lower surface of the upper generator, the lower generator arranged in the lower horizontal frame body has a rotation shaft vertically protruding upward from an upper surface of the lower generator, upper and lower end surfaces of the vertical main shaft of a vertical shaft rotor are respectively coupled

with a lower end surface of the rotation shaft vertically protruding downward from the lower surface of the upper generator and an upper end surface of the rotation shaft protruding upward from the lower generator such that the vertical main shaft of the vertical shaft rotor is concentrically and directly connected between the upper and lower rotation shafts of the respective upper and lower generators, and an outer peripheral side of each seam of coupling portions formed by said coupling is sheathed with a covering body, and

wherein upper and lower end portions of the vertical main shaft of the vertical shaft rotor are respectively coupled and supported between the upper and lower rotation shafts of the respective upper and lower generators without using bearings so as to be concentrically and vertically aligned and be cooperatively movable to reduce torsion and vibration when rotating.
[0007]

(2) The vertical shaft wind turbine according to the above (1), wherein the horizontal frame bodies of the support frame body are arranged in upper, intermediate, and lower stages, and the generator is horizontally arranged in each of the plane central portions respectively surrounded by the inner frames respectively provided in the horizontal frame bodies,

wherein the upper generator arranged in the upper horizontal frame body has the rotation shaft of which the lower end portion vertically protrudes downward from the lower surface of the upper generator, the intermediate generator arranged in the intermediate horizontal frame body has a rotation shaft which vertically protrudes upward from an upper surface of the intermediate generator, and upper and lower end portions of the vertical main shaft of the upper vertical shaft rotor are respectively and integrally coupled with the rotation shaft vertically protruding downward from the upper generator and the rotation shaft protruding upward from the intermediate generator by each coupling portion such that the vertical main shaft is supported by the rotation shafts of the upper and intermediate generators without using bearings,

wherein a lower end portion of the rotation shaft of the intermediate generator protrudes downward from the intermediate generator, and upper and lower end portions of the vertical main shaft of the lower vertical shaft rotor are respectively and integrally coupled with the rotation shaft vertically protruding downward from the intermediate generator and the rotation

shaft protruding upward from the lower generator by each coupling portion such that the vertical main shaft is supported by the rotation shaft protruding downward from the intermediate generator and the rotation shaft protruding upward from the lower generator without using bearings, and

wherein the rotation shaft of the upper generator, the vertical main shaft of the upper vertical shaft rotor, the rotation shaft of the intermediate generator, and the rotation shaft of the lower generator are connected and supported to be concentrically and vertically aligned and be cooperatively movable.

[0008]

(3) The vertical shaft wind turbine according to the above (2), wherein upper and lower end portions of the rotation shaft of the intermediate generator of the intermediate horizontal frame body vertically protrude upward and downward respectively from the upper and lower surfaces of the generator,

wherein upper and lower end surfaces of the rotation shaft protruding upward and downward are respectively formed with a transverse recessed portion caved in a shaft direction such that the transverse recessed portions are oriented in the same direction,

wherein upper and lower end surfaces of each of the vertical main shafts of the upper and lower vertical shaft rotors are respectively formed with a transverse protruding portion projected in the shaft direction such that the transverse protruding portions are oriented in the same direction to be capable of respectively and concentrically fitting to the recessed portions respectively formed on the end surfaces of the rotation shaft of the intermediate generator,

wherein the covering bodies for preventing decoupling are respectively provided on outer peripheral surfaces of the upper and lower end portions of the vertical main shafts of the upper and lower vertical shaft rotors such that each of the seams of the coupling portions formed when the protruding portions are respectively fit to the corresponding recessed portions of the rotation shafts of the generators is sheathed with the corresponding covering body,

wherein the protruding portions respectively formed on the upper and lower end surfaces of each of the vertical main shafts of the upper and lower vertical shaft rotors are

respectively fit to the corresponding pair of the transverse recessed portions of the rotation shafts vertically facing each other, and

wherein the covering bodies are respectively provided on the peripheral surfaces of the vertical main shafts to sheathe the seams of each of the coupling portions between each pair of the rotation shaft and the vertical main shaft by moving the covering bodies to couple the seams.

ADVANTAGES OF INVENTION

[0009]

According to the present invention, the following effects can be obtained.

[0010]

According to the invention of the above (1), since the upper and lower end portions of the vertical main shaft of the vertical shaft rotor are respectively and integrally coupled and supported with the rotation shafts vertically facing each other of the upper and lower generators without using bearings to cooperatively move, a rotation force of the vertical main shaft can directly rotate the upper and lower generators to generate an electric power.

As a result, it is possible to use small-sized generators each of which has a small cogging torque, the vertical shaft wind turbine of the present invention is excellent in starting performance at low wind speed, and is enhanced in a generation efficiency. Moreover, since the upper and lower end portions of the vertical main shaft are respectively and directly coupled and supported with the generators without using bearings, a power generation load is applied to the upper and lower end portions of the vertical main shaft when accelerating, the present invention has the effects of reducing torsion, and reducing vibration and noise owing to the vibration.

Furthermore, it is possible to apply regenerative brakes by the generators to the upper and lower end portions of the vertical main shaft respectively and simultaneously, thereby enabling the vertical shaft wind turbine to be controlled with an excellent balance even in a strong wind.

Still further, it is possible to omit the bearing devices for supporting the vertical main

shaft, and therefore it is possible to enhance working properties and reduce cost.

[0011]

According to the invention of the above (2), the horizontal frame bodies of the support frame body are arranged in the upper, intermediate, and lower stages in the support frame body, the generators are respectively and horizontally arranged in the central portions of the respective horizontal frame bodies, and the vertical main shaft of the upper vertical shaft rotor is integrally connected and supported between the rotation shafts of the upper and intermediate generators without using bearings and the vertical main shaft of the lower vertical shaft rotor is integrally connected and supported between the rotation shafts of the intermediate and lower generators without using bearings such that the both vertical main shafts are integrally and cooperatively movable. Therefore, even though the vertical main shafts are arranged in multi-stages, it is possible to reduce vibration and noise owing to the vibration when accelerating.

Moreover, the same output can be obtained with small-sized generators each of which has a small cogging torque, thereby improving in starting performance even at low wind speed to enhance the acceleration efficiency and the generation efficiency of the wind turbine. Even though the rotation force is strong owing to a large number of the blades, it is possible to easily obtain an effect of a stable and secure controlling because the regenerative brakes by the three generators can be available even in a strong wind.

[0012]

According to the invention of the above (3), each pair of the rotation shafts of the generators is integrally connected with the corresponding vertical main shaft of each of the vertical shaft rotors by the respective coupling portions, the protruding portions respectively formed on the upper and lower end surfaces of each of the vertical main shafts of the upper and lower vertical shaft rotors are respectively fit to the corresponding pair of the transverse the recessed portions of the respective rotation shafts of the generators in the upper and lower sides, and the covering bodies for preventing decoupling are respectively provided on the outer peripheral sides of the coupling portions formed thereby. Therefore, it is possible to easily obtain a complete connection.

Moreover, since the end surface of each of the rotation shafts of the generators and the facing end surface of the corresponding vertical main shaft of each of the vertical shaft rotors are respectively provided with the recessed portion and the protruding portion such that the recessed and protruding portions are fit between the end surfaces facing each other, each of the rotation shafts can be easily fit to the corresponding vertical main shaft. The covering bodies for preventing decoupling are respectively provided on the outer peripheral surfaces of the upper and lower end portions of the vertical main shafts of the upper and lower vertical shaft rotors such that each of the seams of the coupling portions formed when the protruding portions are respectively fit to the corresponding recessed portions of the rotation shafts of the generators is sheathed with the corresponding covering body, and each pair of the rotation shafts of the generators in the upper and lower sides is concentrically fixed with the corresponding vertical main shaft of each of the vertical shaft rotors. Therefore, each pair of the rotation shafts can be fit to the corresponding vertical main shaft such that linerlity is precisely maintained to reduce vibration.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013]

Figure 1 is a front elevational view showing a vertical shaft wind turbine of the present invention.

Figure 2 is a top plan view showing the vertical shaft wind turbine shown in Fig. 1.

Figure 3 is a sectional view taken along the line III-III in Fig. 1.

Figure 4 is a front view showing each coupling state between a rotation shaft of each generator and a vertical main shaft of a vertical shaft rotor shown in Fig. 1.

Figure 5 is a top plan view showing a blade fixture shown in Fig. 1.

Figure 6 is a front view showing the blade fixture shown in Fig. 5.

Figure 7 is a top plan view showing a middle support arm shown in Fig. 1.

Figure 8 is a front view showing the middle support arm shown in Fig. 7.

Figure 9 is a front elevational view showing a vertical shaft wind turbine of a second

embodiment of the present invention.

Figure 10 is a top plan view showing the vertical shaft wind turbine shown in Fig. 9.

EMBODIMENTS OF THE INVENTION

[0014]

An embodiment according to the present invention is described with the drawings as follows.

[0015]

A vertical shaft wind turbine 1 of the present invention includes a support frame body 4 that is three-dimensionally formed by upper and lower horizontal frame bodies 2, 2 and a plurality of support poles 3 on a support stand g mounted on a base G, and a vertical shaft rotor 16 supported by the support frame body 4. Although three pieces of the support poles 3 are shown in Figs. 2, 3, the number of the support poles 3 may be three or four pieces. Although the support poles 3 respectively in a pipe shape are shown in the drawings, the support poles 3 may be respectively a steel material molded in certain shape such as L-shaped steel material, H-shaped steel material, and so on.

[0016]

As shown in Fig. 2, each of the horizontal frame bodies 2 includes outer frames 2A composed in a triangle shape in a plane view by supported with three pieces of the support poles 3 and a plurality of inner frames 2B by which a generator 5 is horizontally arranged to be in a central portion of the triangle shape. Each of the horizontal frame bodies 2 has the same formation.

[0017]

Upper and lower end portions of a vertical main shaft 7 of the vertical shaft rotor 16 are respectively and integrally coupled with a lower portion of a downward rotation shaft 5A of the upper generator 5 and an upper portion of an upward rotation shaft 6A of the lower generator 6 to be cooperatively movable by each coupling portion 9 formed thereby. Thus, the vertical main shaft 7 of the vertical shaft rotor 16 is supported without using bearings. Pluralities of

lift-type vertical blades 11 are arranged around the vertical main shaft 7.

[0018]

Each formation of the coupling portions 9 which respectively couples the upper and lower rotation shafts 5A, 6A of the upper and lower generators 5, 6 with the vertical main shaft 7 is exemplified in Fig. 4. A protruding portion 9B of the upper portion of the vertical main shaft 7 is fit to a recessed portion 9A of the lower portion of the downward rotation shaft 5A of the upper generator 5, an outer peripheral side of a seam formed thereby is sheathed with a covering body 9C, and the covering body 9C is fixed to the vertical main shaft 7 by a pin 9D, thereby strengthening the coupling.

[0019]

Similarly, a protruding portion 9B of the lower portion of the vertical main shaft 7 is fit to a recessed portion 9A of the upward rotation shaft 6A of the lower generator 6, an outer peripheral side of a seam formed thereby is sheathed with another covering body 9C, and the covering body 9C is fixed to the vertical main shaft 7 by another pin 9D, thereby strengthening the coupling. Thus, it is possible to easily and surely couple the rotation shaft 6A of the generator 6 with the vertical main shaft 7.

A universal joint not shown may be applied to each of the coupling portions 9 to enable canceling a narrow gap between the rotation shaft 6A of the generator 6 and the vertical main shaft 7.

[0020]

Reinforcing pipes 8 that are made of a thick-elastic-synthetic resin are fit to the vertical main shaft 7 except for proximal portions of the upper and lower generators 5, 6 and the upper and lower blade fixtures 10. Thus, the vertical main shaft 7 made of metal is reduced in a diameter, and it is possible to obtain effects of reducing a weight of the vertical main shaft 7 to increase a rotation efficiency, reducing deflection owing to a centrifugal force that is caused when the vertical main shaft 7 rotates at a high speed, reducing vibration owing to the deflection, and reducing noise owing to the vibration. The reinforcing pipe 8 is low in load on the rotation because its weight is small.

[0021]

Two stages of the lift-type vertical blades 11 are fixed to the vertical main shaft 7 to be aligned in upper and lower sides such that the upper and lower blade fixtures 10, 10 are applied to each of the two sets of them. As shown in a top plan view of Fig. 5 and a front view of Fig. 6, the blade fixture 10 has a shaft hole 10C in a central portion and a fitting portion 10D formed on a periphery of the shaft hole 10C on a lower surface. The blade fixture 10 is fixed to the vertical main shaft 7 by fitting a pin into a pin hole 10E formed on a peripheral surface of the fitting portion 10D.

[0022]

As shown in the top plan view of Fig. 5 and the front view of Fig. 6, the blade fixture 10 has a main portion 10A in a disk-like shape and fixing portions 10B formed on a peripheral portion of the main portion 10A to protrude in three directions. The upper and lower end portions of each of the lift-type vertical blades 11 are respectively fixed to the fixing portions 10B by fixing with a screw into each of the screw holes 10F. When using another type of the vertical blade that has an inward inclined portion at the upper and lower end portions respectively, the blade fixture 10 of which the fixing portion 10B is elongated is used.

[0023]

As shown in Fig. 1, an inner surface of a vertically middle portion of each of the lift-type vertical blades 11 is supported by a middle support arm 12 that is horizontally fixed on the reinforcing pipe 8 on the vertical main shaft 7.

As shown in a top plan view of Fig. 7 and a front view of Fig. 8, the middle support arm 12 has a main portion 12A in a disk-like shape, support arm portions 12C horizontally protruded in three directions from a peripheral portion of the main portion 12A, and a downward fixing portion 12D formed at a tip portion of each of the support arm portions 12C. An outer surface of the fixing portion 12D is made to come in contact with an inner surface of the rotating lift-type vertical blade 11 and is fixed with a screw fit into a pin hole 12E.

[0024]

The middle support arm 12 is fixed to the reinforcing pipe 8 by fitting with a screw into

a pin hole (not shown) formed on a fitting portion 12F protruding downward from the main portion 12A. As shown in Fig. 7, a leading edge 11A and a trailing edge 11B of the lift-type vertical blade 11 are set to rotate on the same rotation track T.

[0025]

As shown in Fig. 7, the lift-type vertical blade 11 is thicker on the outer side than on the inner side with respect to the rotation track T of the blade as a boundary. An air stream passing along an outer surface of the lift-type vertical blade 11 passes through inward in a rear direction from the trailing edge 11B by Coanda effect to push the leading edge 11A of the blade in an outer direction by the reaction.

[0026]

The configuration of the lift-type vertical blade 11 is not limited. As shown in Fig. 1, an upper inward circular arc-shaped portion 11D is formed from an upper portion of a substantially vertical main portion 11C to elongate in an arc shape toward the vertical main shaft 7, and a lower inward circular arc-shaped portion 11E is formed from a lower portion of the substantially vertical main portion 11C to elongate in an arc shape toward the vertical main shaft 7. Although each length of these three portions 11C, 11D, 11E is set to approximately one-third of the whole length of the blade 11, it is not limited to this configuration.

[0027]

Figure 9 is a front elevational view showing a vertical shaft wind turbine 1 of a second embodiment of the present invention. The same parts as those in the former embodiment are attached with the respective same reference signs as those in the former embodiment, and are not explained. In this second embodiment, horizontal frame bodies 2 are respectively arranged in three stages of upper, intermediate, and lower portions of a support frame body 4 such that height of the support frame body 4 is increased. Upper, intermediate, and lower generators 13, 14, 15 are respectively and horizontally fixed to the horizontal frame bodies 2.

[0028]

Upper and lower end portions of a vertical main shaft 18 of an upper vertical shaft rotor 17 are respectively and integrally coupled with a downward rotation shaft 13A of the upper

generator 13 and an upward rotation shaft 14A of the intermediate generator 14 to be cooperatively movable by each of upper and lower coupling portions 9, 9 formed thereby and be supported without using bearings. The same coupling portions 9 as described according to Fig. 4 can be used as the coupling portions 9 of this embodiment.

[0029]

Upper and lower end portions of a vertical main shaft 20 of a lower vertical shaft rotor 19 are respectively and integrally coupled with a downward rotation shaft 14B of the intermediate generator 14 and an upward rotation shaft 15A of the lower generator 15 to be cooperatively movable by each of upper and lower coupling portions 9, 9 formed thereby and be supported without using bearings. Incidentally, the same reinforcing pipes 8 as described according to Fig. 1 can be fit to the upper and lower vertical main shafts 18, 20 respectively.

[0030]

The upper vertical shaft rotor 17 is formed such that two sets of lift-type vertical blades 21, 21 are fixed to the upper vertical main shaft 18 to be aligned in upper and lower stages and a phase of the upper lift-type vertical blades 21 is shifted from that of the lower lift-type vertical blades 21 to be equiangularly apart. The configuration of the lift-type vertical blades 21 is optional. Although the two-vanes type, vertical shaft rotor 17 having the semicircular arc-shaped, lift-type vertical blades 21 in the front elevational view is shown in the drawings, the vertical shaft rotor 17 can be formed in a type of more than three vanes.

The lower vertical shaft rotor 19 is formed such that two sets of lift-type vertical blades 21, 21 are fixed to the lower vertical main shaft 20 to be aligned in upper and lower sides and a phase of the upper lift-type vertical blades 21 is shifted from that of the lower lift-type vertical blades 21 to be equiangularly apart.

[0031]

In this manner, the horizontal frame bodies 2 are respectively arranged in the three stages of the upper, intermediate, and lower portions of the support frame body 4, the generators 13, 14, 15 are respectively arranged on the horizontal frame bodies 2, the vertical main shaft 18 of the upper vertical shaft rotor 17 is integrally connected between the downward rotation shaft

13A of the upper generator 13 and the upward rotation shaft 14A of the intermediate generator 14 to be supported without using bearings, and the vertical main shaft 20 of the lower vertical shaft rotor 19 is integrally connected between the downward rotation shaft 14B of the intermediate generator 14 and the upward rotation shaft 15A of the lower generator 15 to be supported without using bearings. Therefore, since the upper and lower end portions of each of the vertical main shafts 18, 20 of the respective vertical shaft rotors 17, 19 different in height are respectively fixed between the rotation shafts of the generators, it is possible to obtain a vibration free effect and an effect of reducing noise owing to the vibration.

[0032]

Moreover, it is possible to use small-sized generators, thereby improving in starting performance even at low wind speed to enhance the rotation efficiency. When it is in a strong wind state, the upper, intermediate, and lower generators 13, 14, 15 can be respectively used as regenerative brakes. Therefore, it is possible to obtain an effect of a stable and secure controlling.

[0033]

Incidentally, regarding the vertical shaft wind turbine shown in Fig. 9, the vertical shaft rotors can be arranged in three stages by arranging the horizontal frame bodies 2 in four stages in the support frame body 4 and the generators are respectively arranged on the horizontal frame bodies 2. In such a case, each of the vertical shaft rotors may have one piece of the vertical blade or three pieces of the vertical blades.

[0034]

As described in detail, since the upper and lower portions of the vertical main shaft of the vertical shaft rotor are respectively and integrally coupled with the rotation shafts of the respective upper and lower generators to be directly supported without using bearings, the present invention has the effects of reducing torsion of the vertical main shaft when rotating, reducing vibration owing to the torsion, and reducing noise owing to the vibration. Moreover, since it is possible to use small-sized generators each of which has a small cogging torque, the vertical shaft wind turbine of the present invention is excellent in starting performance at low

wind speed, is enhanced in the rotation efficiency, and can be widely utilized as a wind-power generation device used in an urban area and so forth.

INDUSTRIAL APPLICABILITY

[0035]

Since the generators are respectively arranged in the upper and lower horizontal frame bodies of the support frame body of the vertical shaft wind turbine, and the vertical main shaft of the vertical shaft rotor is integrally connected between the rotation shafts of the respective upper and lower generators, the vertical shaft wind turbine of the present invention can be enhanced in a starting performance by using small-sized generators, can be enhanced in a rotation efficiency, and can be widely utilized as a wind-power generation device used in an urban area and so forth.

REFERENCE SIGNS LIST

[0036]

1...vertical shaft wind turbine

2...horizontal frame body

2A...outer frame

2B...inner frame

3...support pole

4...support frame body

5, 6...generator

5A, 6A...rotation shaft

7...vertical main shaft

8...reinforcing pipe

9...coupling portion

9A...recessed portion

9B...protruding portion

9C...covering body
9D...pin
10...blade fixture
10A...main portion
10B...fixing portion
10C...shaft hole
10D...fitting portion
10E...pin hole
10F...screw hole
11...lift-type vertical blade
11A...leading edge
11B...trailing edge
11C...substantially vertical main portion
11D...upper inward circular arc-shaped portion
11E...lower inward circular arc-shaped portion
12...middle support arm
12A...main portion
12B...shaft hole
12C...support arm portion
12D...fixing portion
12E...pin hole
12F...fitting portion
13, 14, 15...generator
13A, 14A, 14B, 15A...rotation shaft
16, 17, 19...vertical shaft rotor
18, 20...vertical main shaft
21...lift-type vertical blade
G...base

g...support stand

WHAT IS CLAIMED IS:

1. A vertical shaft wind turbine comprising a plurality of lift-type vertical blades arranged at fixed intervals around a vertical main shaft, wherein each of the lift-type vertical blades has a substantially vertical main portion and upper and lower inward circular arc-shaped portions that are respectively and continuously formed from a top and a bottom of the substantially vertical main portion to respectively elongate toward the vertical main shaft, a tip portion of the upper inward circular arc-shaped portion is fixed to a fixing portion of an upper blade fixture arranged on the vertical main shaft, and a tip portion of the lower inward circular arc-shaped portion is fixed to a fixing portion of a lower blade fixture arranged on the vertical main shaft,

characterized in that the vertical shaft wind turbine further comprises a support frame body which is framed with horizontal frame bodies horizontally arranged in upper and lower stages and a plurality of support poles, and a generator which is horizontally arranged in each plane central portion surrounded by inner frames respectively provided in the horizontal frame bodies,

in that the upper generator arranged in the upper horizontal frame body has a rotation shaft of which a lower end portion vertically protrudes downward from a lower surface of the upper generator, the lower generator arranged in the lower horizontal frame body has a rotation shaft vertically protruding upward from an upper surface of the lower generator, upper and lower end surfaces of the vertical main shaft of a vertical shaft rotor are respectively coupled with a lower end surface of the rotation shaft vertically protruding downward from the lower surface of the upper generator and an upper end surface of the rotation shaft protruding upward from the lower generator such that the vertical main shaft of the vertical shaft rotor is concentrically and directly connected between the upper and lower rotation shafts of the respective upper and lower generators, and an outer peripheral side of each seam of coupling portions formed by said coupling is sheathed with a covering body, and

in that upper and lower end portions of the vertical main shaft of the vertical shaft rotor are respectively coupled and supported between the upper and lower rotation shafts of the respective upper and lower generators without using bearings so as to be concentrically and

vertically aligned and be cooperatively movable to reduce torsion and vibration when rotating.

2. The vertical shaft wind turbine according to claim 1, wherein the horizontal frame bodies of the support frame body are arranged in upper, intermediate, and lower stages, and the generator is horizontally arranged in each of the plane central portions respectively surrounded by the inner frames respectively provided in the horizontal frame bodies,

wherein the upper generator arranged in the upper horizontal frame body has the rotation shaft of which the lower end portion vertically protrudes downward from the lower surface of the upper generator, the intermediate generator arranged in the intermediate horizontal frame body has a rotation shaft which vertically protrudes upward from an upper surface of the intermediate generator, and upper and lower end portions of the vertical main shaft of the upper vertical shaft rotor are respectively and integrally coupled with the rotation shaft vertically protruding downward from the upper generator and the rotation shaft protruding upward from the intermediate generator by each coupling portion such that the vertical main shaft is supported by the rotation shafts of the upper and intermediate generators without using bearings,

wherein a lower end portion of the rotation shaft of the intermediate generator protrudes downward from the intermediate generator, and upper and lower end portions of the vertical main shaft of the lower vertical shaft rotor are respectively and integrally coupled with the rotation shaft vertically protruding downward from the intermediate generator and the rotation shaft protruding upward from the lower generator by each coupling portion such that the vertical main shaft is supported by the rotation shaft protruding downward from the intermediate generator and the rotation shaft protruding upward from the lower generator without using bearings, and

wherein the rotation shaft of the upper generator, the vertical main shaft of the upper vertical shaft rotor, the rotation shaft of the intermediate generator, and the rotation shaft of the lower generator are connected and supported to be concentrically and vertically aligned and be cooperatively movable.

3. The vertical shaft wind turbine according to claim 2, wherein upper and lower end portions of the rotation shaft of the intermediate generator of the intermediate horizontal frame body vertically protrude upward and downward respectively from the upper and lower surfaces of the generator,

wherein upper and lower end surfaces of the rotation shaft protruding upward and downward are respectively formed with a transverse recessed portion caved in a shaft direction such that the transverse recessed portions are oriented in the same direction,

wherein upper and lower end surfaces of each of the vertical main shafts of the upper and lower vertical shaft rotors are respectively formed with a transverse protruding portion projected in the shaft direction such that the transverse protruding portions are oriented in the same direction to be capable of respectively and concentrically fitting to the recessed portions respectively formed on the end surfaces of the rotation shaft of the intermediate generator,

wherein the covering bodies for preventing decoupling are respectively provided on outer peripheral surfaces of the upper and lower end portions of the vertical main shafts of the upper and lower vertical shaft rotors such that each of the seams of the coupling portions formed when the protruding portions are respectively fit to the corresponding recessed portions of the rotation shafts of the generators is sheathed with the corresponding covering body,

wherein the protruding portions respectively formed on the upper and lower end surfaces of each of the vertical main shafts of the upper and lower vertical shaft rotors are respectively fit to the corresponding pair of the transverse recessed portions of the rotation shafts vertically facing each other, and

wherein the covering bodies are respectively provided on the outer peripheral surfaces of the vertical main shafts to sheathe the seams of each of the coupling portions between each pair of the rotation shaft and the vertical main shaft by moving the covering bodies to couple the seams.