

Improved device for the in-situ production of columns of stabilized and compacted soil.

The invention relates to an improved device for the in-situ production of columns of stabilized and compacted soil.

5 EP-B-0,161,974 describes a method for the in-situ production of columns of stabilized and compacted soil. This method includes a first step consisting in forcing into the ground a rotary drilling tool loosening the ground and mixing it with a filler material, and during which step an upward movement, through the drilling tool, is imparted to at least part of the loosened
10 ground, and a second step consisting in withdrawing the drilling tool from the ground, and is characterized in that a device is used, as a drilling tool, which comprises at least two parallel shafts, each shaft rotationally driving an auger, each auger being fitted at its opposite end to the drive shaft with a loosening drill head and the distance between the axes of the augers being less than the
15 diameter of an auger, the shafts and the shanks of the augers including a bore connected to a source of filler material and at least one orifice communicating with the said bore being provided on the shank of each auger in order to discharge the filler material, the augers having opposite hands and being driven in counterrotation, and which furthermore comprises means for reversing the
20 direction of rotation of the augers, in that the first step is carried out by forcing the said device into the ground while discharging a filler material via the said orifice so as to mix it with the loosened ground and in that the second step is carried out, after having reversed the direction of rotation of the augers, by exerting a controlled bearing force on the said device while it is being
25 withdrawn so as to impart a downward movement, through the said device, to the loosened ground mixed with the filler material, tending to compact it.

Although EP-B-0,161,974 also claims a device suitable for the implementation of the said method, comprising at least two augers, it specifically describes only a two-auger device.

30 When employing this specific two-auger device in very soft ground, according to the method described, difficulties have been encountered due to the fact that the path of the device can suffer large deviations with respect to the

one desired. It is apparent, after studying this phenomenon, which is not perceptible in relatively firm ground, that it results from the dissymmetry of the distribution of the forces which are exerted on the device during operation.

5 The main forces, which are applied to the augers or drill heads, namely:

- the forces resulting from the cutting action
- the forces due to lateral friction between the augers and the ground,

and

10 - the forces resulting from the accumulation of materials at the entrance of the imbricated augers, all act in the same direction and tend to impart a movement (translation and/or rotation) to the device with respect to the soil, as well as to exert a torque on the guideway of the drilling machine which serves to guide the multi-auger device.

15 Normal ground, having good or average mechanical characteristics can develop reactions limiting the reactions induced by the said forces, but this is not so in the case of very soft soils, in particular in sensitive clays, in which the deviations become unacceptable since the reaction forces are insufficient.

20 The need therefore arises for an improved device which would be free of the abovementioned drawback.

The subject of the invention is precisely to provide such a device.

25 More specifically, the invention relates to a device for the in-situ production of columns of stabilized and compacted soil, of the kind which comprises at least two parallel shafts, each shaft driving in rotation one auger, each auger being fitted at its opposite end to the drive shaft with a loosening drill head and the distance between the axes of the augers being less than the diameter of an auger, the shafts and the shanks of the augers including a bore and at least one orifice communicating with the said bore being provided on the shank of each auger in order to discharge a filler material, the augers having
30 opposite hands and being driven in counterrotation, and which furthermore comprises means for reversing the direction of rotation of the augers, characterized in that it includes an even number n , at least equal to 4, of augers

and in that, seen in cross-section, the axes of the augers are centred at the vertices of a regular n -sided polygon.

According to preferred embodiments, the device includes 4, 6 or 8 augers and the axes of the augers are respectively arranged at the vertices of a square, a regular hexagon or a regular octagon.

With such a geometry, a symmetrical device is obtained in which the abovementioned forces are compensated for so that deviations in soft ground are no longer observed.

The device preferably includes a single motor driving, via an appropriate gearbox, all the augers, this being for the purpose of synchronizing the augers in terms of rotation, which is essential on account of their mutual imbrication, but it is obviously not excluded to employ several drive motors if desired, as long as, moreover, means are provided for suitably synchronizing the rotation of the augers.

The description which follows, with regard to the appended drawings, given by way of non-limiting example, will make it clear how the invention can be realized.

Figures 1 and 2 are diagrammatic views, in elevation and in cross-section (along the line II-II) respectively, of one embodiment of the device according to the invention.

Figures 3 and 4 are diagrammatic views, in cross-section, in the region of the augers, of other embodiments of the device of the invention.

The device depicted in Figures 1 and 2 includes the following elements:

Four parallel shafts 1, each provided with a bore 1a, drive four counterrotating helical augers 2 of opposite hands. The shafts 1 are arranged so that, in cross-section (Figure 2), their axes are centred at the vertices of an imaginary square C (depicted by the dotted lines). Each auger is fitted at its free end with a loosening drill head 3 adapted to the nature of the ground. This can be, for example, as illustrated, a head in the form of a helix or else a cutter. The distance X between the adjacent axes of the augers is less than the diameter of the augers so that the threads of the adjacent augers are effectively engaged

one in another so as to provide a forced movement or flow of the ground 4 loosened by the augers. The shank 5 of each auger also includes a bore 5a which communicates with the bore of the corresponding driving shaft, thus enabling the filler material or binder, coming from a source (not depicted), by
 5 dry route or by wet route, to be brought right to the orifices 6 provided on the shank of each auger so as to mix it intimately with the loosened ground.

The length of the augers is adapted to the type of ground and it is usually less than the depth of the column to be produced.

It should be noted that the augers, instead of having a continuous
 10 helical profile, could be discontinuous, that is to say be replaced by a plurality of separated helices.

A few double bearings 7, depending on the depth of the column to be produced, are distributed over the length of the driving shafts and of the augers so as to keep them parallel.

15 The four shafts 1 are driven in rotation by means of a geared speed-reducing and reversing device 8, itself connected to a motor 9 which drives them, as well as the augers, in rotation in opposite directions and at the same speed. This gear-motor assembly 8-9 can be carried by a drilling machine (not depicted) installed on the surface in line with the column to be produced or by
 20 means of a guideway on which it can move longitudinally, either freely or by means of a translation device. As a variant, it can be hung from the jib of a lifting contrivance (a crane or other means). In the latter case, the weight of the device can be adapted so that it exerts the desired bearing force.

Figure 3 illustrates diagrammatically a device similar to the one of
 25 Figures 1 and 2 save that it includes six augers 2 instead of four. The shafts 1 of these augers are arranged so that, in cross-section, their axes are centred at the vertices of an imaginary regular hexagon H (shown by the dotted lines).

Figure 4 illustrates diagrammatically a device similar to the one of
 Figures 1 and 2, save that it includes eight augers 2 instead of four. The shafts 1
 30 of these augers are arranged so that, in cross-section, their axes are centred at the vertices of an imaginary regular octagon O (shown by the dotted lines).

The improved device of the invention is used in the same manner as

the device described in EP-B-0,161,974 to which reference should be made for more details.

5 However, because of the symmetrical nature of the device of the invention, it is free, when being used in soft ground, of the drawback exhibited by the device of EP-B-0,161,974, this drawback being recalled in the preamble of the present description.

It goes without saying that the embodiments described are only examples and they could be modified, especially by substituting with technical equivalents, without thereby departing from the scope of the invention.

CLAIMS

1. Device for the in-situ production of columns of stabilized and compacted soil, of the kind which comprises at least two parallel shafts (1), each shaft driving in rotation one auger (2), each auger being fitted at its opposite end to the drive shaft with a loosening drill head (3) and the distance (X) between the axes of the augers being less than the diameter of an auger, the shafts and the shanks (5) of the augers including a bore (1a, 5a) and at least one orifice (6) communicating with the said bore being provided on the shank of each auger in order to discharge a filler material, the augers having opposite hands and being driven in counterrotation, and which furthermore comprises means (8) for reversing the direction of rotation of the augers, characterized in that it includes an even number n , at least equal to 4, of augers and in that, seen in cross-section, the axes of the augers are centred at the vertices of a regular n -sided polygon (C, H, O).
2. Device according to Claim 1, characterized in that it includes four augers, the axes of which, in cross-section, are centred at the vertices of an imaginary square.
3. Device according to Claim 1, characterized in that it includes six augers, the axes of which, in cross-section, are centred at the vertices of an imaginary regular hexagon.
4. Device according to Claim 1, characterized in that it includes eight augers, the axes of which, in cross-section, are centred at the vertices of an imaginary regular octagon.

