

**CIRCUIT INTERRUPTER WITH COVERED ACCESSORY CASE, ADJUSTABLE
UNDER VOLTAGE RELAY, SELF-RETAINING COLLAR AND ONE-PIECE
RAIL ATTACHMENT**

Abstract of the Disclosure

A molded case circuit breaker (10) is taught with a housing base (14) and a primary cover (18) disposed on the housing base. The primary cover has a recess (18X, 18Y) therein for an auxiliary module which is disposed in the recess. A secondary cover (22) is disposed on the primary cover for covering the recess when the auxiliary module is disposed therein. A combination manual trip and secondary cover interlock (23) is provided which is accessible from outside of the secondary cover for manually opening separable main contacts or for automatically opening separable main contacts when the secondary cover is removed. There is also provided on the back plane (400) of the housing a single piece DIN rail attachment (390) for securing the back plane to a DIN rail. There is provided an under voltage release mechanism (92X) for actuating the circuit breaker to trip on the occurrence of an under voltage condition of pre-determined magnitude across the lines served by the circuit interrupter. The under voltage release mechanism has an adjustment spring (348) which is controlled by a nut (344) or thumb screw on a shaft (360) to vary the spring force for calibrating the under voltage release mechanism. There is also provided a self-retaining collar member (400) for the load and line terminals of the circuit interrupter. The collar member comprises a locating protrusion (436) in the bottom thereof which aligns with a hole (71A) in the load or line conductors (71). Side entrapment members (440) which entrap the line or load conductor therebetween and between the bottom of the collar member are also provided.

(Fig. 1)