

Description

The present invention relates to walkers

5 A non reversible walker is disclosed in US Patent No. 2 796 916. Such a walker is adapted to be used in a forward direction and comprises a free standing walker frame having two sides, each side including two legs connected by at least an upper and a lower generally horizontal rail, and a transverse section interconnecting said two sides. The walker also has a patient support attachment.

Walking aids have long been in widespread use in a great variety of designs and configurations. One category of walking aids comprises four legged walkers such as disclosed in U.S. Patents 4, 248, 256 to Thomas, 4, 474, 202 to Blechner, and 3, 945, 389 to Smith. Four legged walkers usually consist of a lightweight framework typically made of aluminum tubing which can be lifted with minimal effort by even a debilitated individual. The walker frame defines a generally rectangular perimeter about the user which is closed along three sides and open on one side to allow a user to step into the walker frame and take hold of hand grips provided thereon. Thus, the frame of a typical conventional walker as referenced to the user has two side sections usually provided with hand grips, one on each side of the user, and a transverse front section which extends between and interconnects the two side sections. The rear of the walker is open and provides no support.

One shortcoming of prior art walkers is the limited flexibility and adaptability of the walker to the great variety of physical disabilities and impairments encountered in medical practice each susceptible of being best treated by a walker configuration fitted to the particular patient's requirements. Such precise fitting of the walker configuration is not easily achieved with prior art walkers having a limited range of adjustment of the hand grips and patient supports such as platforms, and further improvement in the ease and latitude of adjustment and adaptability of walkers is desirable.

In certain cases a reverse walker position, i.e. one where the open side of the walker is oriented towards the front of the patient and the transverse side is behind the patient can be both physical and psychologically advantageous to the patient. The open front of the walker diminishes the portion of the walker frame visible to the user and removes the closed front as a visual barrier in front of the user, more closely approaching the perception of normal, unassisted walking to further promote and speed rehabilitation.

Conventional walkers are ill suited for use in a reverse disposition and are likely to cause the patient to fall forward if so used. In conventional walkers, such as in the aforementioned patent to Smith, the safety zone defined by the walker footprint is too limited to allow the walker to be used in a reverse position because, among other reasons, the length of the side sections is relatively short. The short side sections do not detract significantly from the usefulness of the device so long as the walker stands in front of the patient and the patient steps towards and into the walker with each stride. In normal use the walker stands in plain view before the user who can easily adjust his position and spacing relative to the walker so as to keep his balance and maintain a sure grip on the walker frame. Further, the user cannot step out of the walker's safety zone because the closed front of the walker frame prevents it. If the same walker is turned around such that the open side is directed towards the front of the user, it will be found that the patient must reach back to keep hold of the hand grips because the side sections are too short to be grasped in a reverse walker orientation while the patient's arms extend in a comfortable position. Even if the patient is able to hold on to the side sections at all, he may be forced to do so at a point dangerously near the ends of the hand rails where stable support is not available, risking tipping of the frame with consequent injury to the patient.

Walkers embodying the present invention have a high degree of flexibility and ease of adjustment of the patient support attachments and by its reversibility, that is, it is safely usable in either the conventional leading position where the walker is in front of the patient and the open side of the walker frame faces rearwardly, and a "reversed" behind-the-patient attitude where the open side of the walker frame faces ahead and the walker frame is closed behind the patient. In such reversible walkers hand grips or platform supports are attachable to the rails of each of the two side sections of the walker frame by means of particularly adapted clamps which can be independently fixed at any continuously selected point between the fore and aft ends of the side rails so as to achieve an unprecedented degree of flexibility in the positioning and attitude of the hand grips or other patient support attachments, both in the normal and reverse positions of the walker to give the physical therapist ample professional latitude in configuring the walker to the specific disabilities of each particular patient. The position of the attachments must be shifted depending on the orientation of the walker relative to the patient and the exceptionally flexible mounting of such supports according to this invention therefore contributes to the reversibility of the walker.

The walker frame has two side sections connected by a transverse section, the two side sections and transverse section together forming a four legged free standing walker frame. Each side section includes a

front and rear leg connected by generally horizontal side rails which are of smooth undeformed substantially constant cross-section.

Each such patient support attachment consists of a tube or cane terminating at its upper end in a hand grip which may be either straight or bent and which may also carry a platform for supporting the patient's arm. One such attachment is secured to each side of the walker frame by clamping to an upper and a lower rail so that the attachment tube is held transversely to the side rails on each side section of the walker. The fore to aft position of the attachment is readily adjustable by momentarily loosening and sliding both of the attachment clamps along the rails to displace the attachment along the rails, while its precise uppermost rails of the side sections as projected vertically onto the ground surface.

Walkers embodying the invention is adapted for "reverse" use by extending the length of the side sections to provide a support frame along enough such that the hand grips or other support attachments can be mounted sufficiently far away from the closed rear of the frame to allow the patient adequate and comfortable standing and manoeuvring room within the frame while maintaining an easy hold on the hand grips. When used in the behind-patient position, the closed rear of the present walker allows provision of a bumper pad disposed for contacting the user's gluteal region as the walker is advanced with each step taken, lightly but repeatedly "bumping" the user's backside as a continuing and insistent reminder to maintain an erect posture.

As a result of the extended length of the side sections in combination with the splaying of the front legs, the user's weight is maintained within the walker's safety zone at all times in the reverse position.

A further feature of the walker when used in a reverse, behind the patient position is that a physical therapist is able, through suitable adjustment of the support attachments, to restrict the patient's body between the support attachments mounted to the side and forwardly of the patient and a gluteal bumper pad disposed behind the patient. The spacing of the attachments to the gluteal pad may be adjusted so as to just accommodate the user in a substantially erect attitude in the walker. If the patient stoops forward while supporting by the attachment, his body will curve rearwardly away from the attachment and his backside will make contact the gluteal pad whereby he will be reminded to resume correct posture.

The walker is provided with attachment clamps used in adjustable mounting the various support attachments to the walker's side rails. While such support attachments have been used in the past as illustrated by the platform crutch attachment in U.S. Patent 4, 248, 256 to Thomas, the use of the clamps disclosed herein allow easy and highly flexible positioning of the attachments with only a single manually releasable fastener being used in each clamp, release of which simultaneously releases the clamp from both the walker frame and the support attachment.

The attachment clamps each comprise two generally U-shaped clamp elements each adapted to fit about a tubular element such as a hand rail of the walker and a cane attachment to be mounted to the walker. Each clamp element has a U-shaped outer surface including two mutually parallel, substantially plane outer faces connected by an intermediate surface portion contained between the planes of the parallel outer faces. The two clamp elements are held together by a single fastener, such as a bolt and nut, which applies compressive force simultaneously to both clamp elements along a direction substantially perpendicular to all four plane outer faces, clamping each of the two elements about a corresponding tubular element. The two clamp elements, however, are free to rotate about the single fastener. This allows the inclination of a walker attachment secured by two such clamps to be easily adjusted by loosening only one clamp and sliding the loose clamp along the walker rail to a new position. The loose clamp slides along both the rail and the attachment while the other clamp accommodates to the new attachment inclination only by relative rotation of its two clamp elements. The particular configuration of the two clamp elements disclosed herein allows the two clamp elements to be rotated a full 360 degrees relative to each other about the single fastener.

It must be understood that the clamps as used are not limited to use in a walker. The nearest art pertinent to these clamps of which applicant is aware is disclosed in U.S. Patent 2, 994, 366 to Hoch and forming part of a tray attachment for folding chairs. The Hoch clamps are not rotatable through a full circle about the single bolt joining the two clamp elements because their outer surfaces include nearly cylindrical portions which are not contained between the plane outer surfaces and thus interfere with such rotation.

The solution to the problem posed by the application is given by the features in the characterising portion of claim 1.

A reversible walker embodying the present invention will now be described, by way of example, with reference to the accompanying diagrammatic drawing in which:

Figure 1 is a perspective view showing the reversible walker configured for reverse, behind-patient use;

Figure 2 is a side elevational view of the walker of Figure 1 shown in typical reverse use by a patient;

Figure 3a shows the novel clamps used to secure the patient support attachments to the walker frame;

Figure 3b is a side view of the clamps of Figure 3a;

Figure 4 shows the transverse section of the walker frame and an adjustable gluteal bumper pad arrangement for the same;

Figure 5 is a top plan view of the walker configured for reverse use and seen with the upper ends of the support attachments sectioned away; and

Figure 6 is a perspective view of the reversible walker configured for use in a conventional position relative to the user.

Figure 7 is a side elevational view of the walker of Figure 1 shown in typical forward use by a patient.

The reversible walker 10 shown in Figure 1 has a tubular walker frame 12 consisting of two side sections 14 interconnected by a transverse section 16 to form a three sided, free standing frame supported by four legs and having an open side 18 as best appreciated in Figure 5. Viewed in the reverse position each side section 14 includes a front leg 20a and a rear leg 20b, the front legs terminating in lower extremities 22, and two side rails 24 and 26 connecting the front and rear legs of each side section. The side rails 24, 26 each have a relatively long generally horizontal mutually parallel straight segment, one such straight segment overlying the other. The two segments are of smooth, constant cylindrical cross section at least through the straight, generally horizontal portion of each rail. The transverse section 16 is a generally X or butterfly shaped tubular assembly interconnecting the upper portions of the two rear legs 20b.

The basic walker frame 12 may be adapted to the particular physical requirements of different users by mounting selected support attachments to the frame 12. Most frequently the walker will be equipped with two similar canes 28 such as shown in Figure 6 with curved upper ends to form horizontal hand grips 29, however, other possible attachments include a cane 34 with a vertical hand grip in Figures 1 and 2, and a platform attachment 30 having a forearm rest 31 and a handgrip 33 shown in Figure 1. Each of the attachments is fastened to the frame by means of two clamps 32 secured to the upper and lower rails 26, 24 respectively of a corresponding side section 14. The attachment clamps 32, which will be described in greater detail below, each consist of two pieces or elements pivotably connected together by a single fastener bolt and nut which also operates to simultaneously tighten the two clamp elements around the attachment tube and the walker frame rail. The two clamp elements are free to pivot in relation to one another as required by the desired adjustment of the attachment position, thus allowing great ease and flexibility in positioning and arrangement of the different attachments relative to the walker frame 12 so as to complement the particular physical handicap of any given user, and further permit quick and easy readjustment of the attachment as the patient's requirements change with time.

Each of the various support attachments 28, 30, 34 have a relatively long straight tubular lower shaft portion 25 to which are attached two mounting clamps 32 in spaced apart relationship. Each clamp is also attached to one of the rails 24, 26 on one side 14 to secure the attachment to the walker frame 12. The angular disposition or inclination of the attachment tube relative to the walker frame 12 is readily adjustable by sliding one of the clamps 32 relative to the other clamp along the rails 24, 26. In this manner for example, the cane 28 in Figure 1 can be readily brought from the solid lined to the phantom lined position by merely sliding the upper clamp 32 along rail 26. The cane 28 may also be rotated to adjust the hand grip position as shown. The adjustment range of the support attachments is maximized by allowing for uninterrupted sliding of the attachment clamps along the full length of the upper rail 26 from the transverse section 16 to its forward end at bend 38. The lower rail 24 allows for uninterrupted sliding of the lower clamp along a straight segment 27 of similar length before the lower rail 24 curves upwardly at 29 to meet the splayed leg 20a. The ability to freely slide the attachment clamps along major segments of the rails, in combination with the two piece clamps described below makes for the great flexibility and latitude of adjustment and in particular for the reversibility of the present walker. The height of the attachment relative to the frame is easily adjustable by axial sliding of the attachment tube through the two spaced apart clamps 32. The attitude of the attachment is also readily adjustable by rotation of the attachment tube within the two clamps about the axis of the shaft 25 as illustrated by rotation of the cane 28 with the horizontal hand grip 29 from the solid line to the phantom line position in Figure 1.

With reference to Figure 2, it can be seen that the use of attachments such as the cane 34 terminating in an elevated upper hand grip 36 increases the leverage that can be exercised by the user 100 over the walker frame 12. For example by applying a relatively modest forward force onto the cane handle 36 a substantial amount of forward pivotal leverage can be applied to the walker frame 12. Since the walker is to be used by enfeebled or otherwise handicapped persons such forward force can be accidentally applied and must be guarded against to prevent accidental tipping over of the frame. As has been discussed above use of the walker in a reverse position entails somewhat greater risk of instability and to minimize this, the legs 20a slant or splay forwardly at an angle α such that their lower extremities (in this case provided

with wheels 52) touch the ground 50 a distance "d" forwardly of the ends 38 of the side hand rails 26 as projected onto the ground surface. The effective length "1" of the side rails 26, measured from the transverse section 16 to the bend point 38 of the side rails 26, is sufficient to allow a user 100 to take a stride forward without stepping out of comfortable reach of the attachments, and above all without stepping out of the walker's safety zone. The stride is measured from a beginning position with the transverse section 16 of the frame 12 substantially against the backside of the user 100, bearing in mind that the typical user of the walker will not be able to take long strides. Having taken the stride, the user 100 will find himself near the ends 38 of the side rails 26 and at some distance forwardly of the transverse section 16. In an interrupted gait mode the user may then stand still while the walker 10 is moved forwardly until the transverse section 16 again abuts against the back-side of the user 100. The transverse section 16 will gently "bump" against the backside of the user following each step as a reminder to the patient to maintain an erect attitude while walking. This bumping action is enhanced by provision of a gluteal pad or bumper plate 40. As seen in Figure 4 the gluteal pad 40 may be mounted on a support 44 slideably through a bracket 46 mounted to the transverse section 16. The height of the gluteal pad 40 relative to the frame section 16 can be fixed by means of set screw 48 threaded through the bracket 46 to lock the support 44 against sliding movement therethrough. The adjustable height feature of the gluteal pad 40 further increases the versatility of the walker 10 by allowing adjustment to different patient heights and anatomies.

In cases where a patient is able to and prefers to use the walker in a smooth gait mode the aforementioned repeated gluteal bumping may occur with less regularity. However, the completely flexible positioning of the attachments enables the therapist to configure the walker so that the patient's buttocks are closely spaced from the gluteal pad while the patient is in normally erect posture and holding onto the cane grips or platform supports. If thereafter the patient stoops forward his spacing from the hand grips or platform will tend to remain approximately the same as dictated by natural and comfortable arm extension and position, whereas his buttocks will tend to move rearwardly into contact with the gluteal pad or closed rear of the walker frame due to the curvature of the body associated with stooping or bent posture. This contact is intended as a reminder to resume correct posture.

The forward legs 20a and the upper side rails 26 are formed of a single continuous length of tubing bent at 38 to define the forward termination point of the upper side rails 26 and the commencement of the leg 20a. The bend 38 also marks the forward limit for attachment of the upper clamp 32 used to secure a support attachment such as cane 34. So long as this forward limit is not surpassed, the leverage provided by the upwardly extending attachments will not create a substantial danger of forward tipping of the walker device due to the forward extension of the legs 20a. In other words, the footprint of the walker which has a length of $1 + d$ measured between the lower extremities of the front and rear legs extends substantially forwardly of the front termination points 38 of the upper rails 26 as projected vertically downwardly onto the ground surface.

The front legs 20a of the walker may be provided with casters or wheels 52 for assisting the patient in advancing the walker following each step, while the rear legs 20b terminate in rubber feet which drag over the ground surface in order to prevent the walker from rolling out of control. The use of wheels is particularly desirable to allow the walker to move forward together with the user 100 for a smoother, more continuous joint forward motion but are in any event optional.

The reversible walker 10 is shown in Figures 6 and 7 configured for use in a normal position with the transverse portion 16 in front of the patient and without the gluteal pad. The splayed legs 20a earlier referred to as the forward legs now become the rear legs while the legs 20b are now the front legs. The wheels 52 have been moved from legs 20a to legs 20b and the tip stands 22 placed on legs 20a. The reversal is completed by moving the canes 28 or other attachments along the side rails 24, 26 to a suitable position nearer to the transverse side 16, as in Figure 7.

It is contemplated that the walker may be constructed in different sizes to suit persons of all ages and varying statures as for example, three sizes for use by children, youths and adults respectively. Both the dimensions of the walker frame as well as the splay angle of the front legs may vary. Presently preferred approximate walker dimensions are as follows:

	child	youth	adult
top rail length	20.9cm (8 1/4")	31.4cm (12 3/8")	33.5cm (13 3/16")
front leg splay angle	45°	30°	22°
walker frame width	41.6cm (16 3/8")	48.3cm (19")	48.9cm (19 1/4")
minimum walker height	29.2cm (11.5")	55.9cm (22")	68.6cm (27")
max. extended walker height	53.3cm (21")	94cm (37")	101.6cm (40")

Turning now to Figures 3a and 3b, the clamps 32 earlier referred to are seen to each include two substantially identical U-shaped clamp elements 60, each clamp element having a U-shaped outer surface consisting of two plane side faces 62 which are mutually parallel and are joined by an intermediate semi-cylindrical outer surface portion 64. The interior of each clamp element 60 includes a divergent slot 68 opening into a cylindrical bore 66. The two clamp elements 60 are held in mutually abutting relationship at one of the planar side surfaces 62, as shown in the referenced drawings, by means of a single bolt 70 perpendicular to all four side faces 62 extending through aligned bores 72 in the two clamp elements 60. Clamping force is applied simultaneously to both clamp elements 60 by means of a wing nut 72 threaded onto the bolt 70 as shown in Figure 3b. The nut 72 applies clamping force to urge together the two arms 65 in each of the clamp elements 60 and thus simultaneously close both clamp elements 60 so as to clamp tubular elements extending through each of the two cylindrical bores 66, as seen in the walker of Figures 1, 2 and 5 while also retaining the two elements 66 in face-to-face abutting relationship. The clamp elements 60 are rotatable relative to each other so as to accommodate any angle between an attachment shaft 25 and a side rail 24, 26.

The U-shaped outer surface of the two clamp elements 60 wherein the semi-cylindrical intermediate surface 64 is contained between the mutually parallel planar surfaces 62 allows the two clamp elements 60 to be rotated a full 360 degrees relative to each other about the axis of the bolt 70 so as to accommodate any angle between the attachment and the side rails and thus permit ready and easy mounting and readjustment of attachments such as 28, 30 in Figure 1 by simply loosening the wing nut 72 thereby to simultaneously release both clamp elements 60 from the tubular rails and the attachment, one of the rails 24, 26 passing through one clamp element 60 while the attachment shaft 25 extends through the other clamp element 60 of each mounting clamp 32.

Claims

1. A walker adapted to be used in a forward or reverse direction comprising a free standing walker frame (12) having two sides (14), each side including two legs (20a, 20b) connected by at least an upper (26) and a lower (24) generally horizontal rail, and a transverse section (16) interconnecting said two sides and a patient support attachment (28) characterised in that a patient support attachment (28, 30) is provided on each of the sides (14) of the frame (12), each attachment having a lower shaft (25) and support means (29, 31, 33) at its upper end and clamp means (32) securing said attachment (28, 30) to each of the upper and lower rails (24, 26), each of said clamp means (32) comprising two juxtaposed clamp elements (60) each apertured for receiving a tubular element (24, 25) and held together by a single fastener means (70, 72), the two clamp elements being free to rotate about the fastener means (70, 72) and to slide on the rails (24, 26) to accommodate varying angular as well as height relationships between said lower shaft (25) and said rails (24, 26).
2. A walker as claimed in Claim 1 wherein said clamp elements (60) are U-shaped and are each apertured for receiving a tubular element (25) between two arms (65) and have a U-shaped outer surface including two mutually parallel substantially planar outer faces (62) connected by an intermediate



	child	youth	adult
top rail length	20.9cm (8 1/4")	31.4cm (12 3/8")	33.5cm (13 3/16")
front leg splay angle	45°	30°	22°
walker frame width	41.6cm (16 3/8")	48.3cm (19")	48.9cm (19 1/4")
minimum walker height	29.2cm (11.5")	55.9cm (22")	68.6cm (27")
max. extended walker height	53.3cm (21")	94cm (37")	101.6cm (40")

Turning now to Figures 3a and 3b, the clamps 32 earlier referred to are seen to each include two substantially identical U-shaped clamp elements 60, each clamp element having a U-shaped outer surface consisting of two plane side faces 62 which are mutually parallel and are joined by an intermediate semi-cylindrical outer surface portion 64. The interior of each clamp element 60 includes a divergent slot 68 opening into a cylindrical bore 66. The two clamp elements 60 are held in mutually abutting relationship at one of the planar side surfaces 62, as shown in the referenced drawings, by means of a single bolt 70 perpendicular to all four side faces 62 extending through aligned bores 72 in the two clamp elements 60. Clamping force is applied simultaneously to both clamp elements 60 by means of a wing nut 72 threaded onto the bolt 70 as shown in Figure 3b. The nut 72 applies clamping force to urge together the two arms 65 in each of the clamp elements 60 and thus simultaneously close both clamp elements 60 so as to clamp tubular elements extending through each of the two cylindrical bores 66, as seen in the walker of Figures 1, 2 and 5 while also retaining the two elements 66 in face-to-face abutting relationship. The clamp elements 60 are rotatable relative to each other so as to accommodate any angle between an attachment shaft 25 and a side rail 24, 26.

The U-shaped outer surface of the two clamp elements 60 wherein the semi-cylindrical intermediate surface 64 is contained between the mutually parallel planar surfaces 62 allows the two clamp elements 60 to be rotated a full 360 degrees relative to each other about the axis of the bolt 70 so as to accommodate any angle between the attachment and the side rails and thus permit ready and easy mounting and readjustment of attachments such as 28, 30 in Figure 1 by simply loosening the wing nut 72 thereby to simultaneously release both clamp elements 60 from the tubular rails and the attachment, one of the rails 24, 26 passing through one clamp element 60 while the attachment shaft 25 extends through the other clamp element 60 of each mounting clamp 32.

Claims

1. A walker adapted to be used in a forward or reverse direction comprising a free standing walker frame (12) having two sides (14), each side including two legs (20a, 20b) connected by at least an upper (26) and a lower (24) generally horizontal rail, and a transverse section (16) interconnecting said two sides and a patient support attachment (28) characterised in that a patient support attachment (28, 30) is provided on each of the sides (14) of the frame (12), each attachment having a lower shaft (25) and support means (29, 31, 33) at its upper end and clamp means (32) securing said attachment (28, 30) to each of the upper and lower rails (24, 26), each of said clamp means (32) comprising two juxtaposed clamp elements (60) each apertured for receiving a tubular element (24, 25) and held together by a single fastener means (70, 72), the two clamp elements being free to rotate about the fastener means (70, 72) and to slide on the rails (24, 26) to accommodate varying angular as well as height relationships between said lower shaft (25) and said rails (24, 26).
2. A walker as claimed in Claim 1 wherein said clamp elements (60) are U-shaped and are each apertured for receiving a tubular element (25) between two arms (65) and have a U-shaped outer surface including two mutually parallel substantially planar outer faces (62) connected by an intermediate



- section (64) contained between the planes of said parallel outer faces (62), said two clamp elements (60) being juxtaposed at one of said outer faces of each element, and fastener means (70, 72) for releasably applying compressive force simultaneously to both elements along a direction substantially perpendicular to said planar outer faces thereby to maintain said elements in juxtaposed relationship while clamping each element about a corresponding tubular element, said clamp elements being rotatable through a full circle relative to each other about said fastener to thereby allow unimpeded relative positioning of said tubular element prior to application of said compressive force.
3. A walker as claimed in Claim 1 or Claim 2 wherein said fastener means (70, 72) comprise a single bolt (70) extending through both said clamp elements (60) in said substantially perpendicular direction and a nut (72) threadable onto said bolt (70).
 4. A walker according to any preceding claim wherein said upper and lower rails are of substantially constant cross-section to allow unimpeded sliding of said clamp means therealong.
 5. A walker as claimed in any one of Claims 2 to 4 wherein one of said clamp elements (60) is slidable along a corresponding rail to change the relative angular relationship between said attachment shaft (25) and said rails, said other clamp element (60) accommodating to said changed angular relationship without displacement along either its corresponding rail or said attachment shaft.
 6. A walker as claimed in any one of Claims 1 to 5 wherein said two clamp elements (60) are held pivotably together by said single fastener, said single fastener also being operative for simultaneously tightening said two clamp elements about said lower shaft and said rail respectively.
 7. A walker as claimed in any one of the preceding claims wherein the lower rail (24) of each side (14) is longer than the upper rail (26) so that one of said legs (20a) on each side (14) of said walker slants or splays at an angle to the upper rail (26) so that the distance from the lower extremity of said splayed leg (20a) to the lower extremity of the unsplayed leg (20b) is greater than the length of the upper rail (26).
 8. A walker as claimed in Claim 7 wherein the angle of said splay is between 18 and 50 degrees.
 9. A walker according to any one of the preceding claims further comprising gluteal bumper means (40) attached to said transverse section (16) adapted and positioned for bumping against the backside of a user.
 10. A walker as claimed in Claim 9 wherein said bumper means (40) are adjustable in position relative to said transverse section (16).
 11. A walker as claimed in any one of the preceding claims wherein said patient support attachment comprises a cane terminating in an upper hand grip, each said cane being mounted to a corresponding side section with said grip disposed above said upper rail.
 12. A walker as claimed in any one of claims 7 to 11 wherein said upper rail and said splayed leg of each said side section has been formed by bending a continuous length of tubing, the bend point of said tubing being the termination of said upper rail, said splayed leg forming a forward splay angle with its corresponding upper rail portion of the bent tubing.

Patentansprüche

1. Ein Gehgestell, das zur Benutzung in einer vorwärts gerichteten oder in einer umgekehrten Richtung geeignet ist, bestehend aus einem selbststehenden Gehgestellrahmen (12) mit zwei Seiten (14), wobei jede Seite zwei Beine (20a, 20b) aufweist, die mindestens durch einen oberen (26) und durch einen unteren (24) im wesentlichen horizontalen Holm verbunden sind, und aus einem Querelement (16), welches die beiden Seiten verbindet, und aus einer Patientenabstützbefestigung (28),
dadurch gekennzeichnet,
daß eine Patientenabstützbefestigung (28, 30) an jeder Seite (14) des Rahmens (12) vorgesehen ist, wobei jede Befestigung einen unteren Schaft (25) und Abstützvorrichtungen (29, 31, 33) an seinem



- oberen Ende sowie Klemmvorrichtungen (32) aufweist, welche die Befestigungen (28, 30) mit jedem der oberen und unteren Holme (24, 26) verbinden, wobei jede Klemmvorrichtung (32) zwei aneinander-grenzende Klemmelemente (60) aufweist, die zur Aufnahme eines rohrförmigen Elementes (24, 25) mit einer Öffnung versehen und durch eine einzige Spannvorrichtung (70, 72) zusammengehalten sind, wobei die beiden Klemmelemente frei um die Spannvorrichtung (70, 72) drehbar und auf den Holmen (24, 26) verschiebbar sind, damit unterschiedliche Winkel- sowie Höhenverhältnisse zwischen dem unteren Schaft (25) und den Holmen (24, 26) einstellbar sind.
2. Ein Gehgestell nach Anspruch 1, bei dem die Klemmelemente (60) U-förmig sind und jeweils zur Aufnahme eines rohrförmigen Elementes (25) zwischen zwei Armen (65) eine Öffnung sowie eine U-förmige äußere Oberfläche mit zwei gegenüberliegenden parallelen im wesentlichen ebenen äußeren Flächen (62) aufweisen, die durch einen dazwischenliegende Abschnitt (64) verbunden sind, der zwischen den Ebenen der parallelen äußeren Flächen (62) angeordnet ist, wobei die beiden Klemmelemente (60) an einer der äußeren Flächen von jedem Element aneinandergrenzen, und bei dem Spannvorrichtungen (70, 72) zum ausreichenden Aufbringen einer kompressiven Kraft gleichzeitig auf beide Elemente in einer Richtung vorgesehen sind, die im wesentlichen rechtwinklig zu den ebenen äußeren Flächen ist, so daß die Elemente nebeneinanderliegend gehalten sind, während jedes Element um ein entsprechendes rohrförmiges Element geklemmt ist, wobei die Klemmelemente relativ zueinander um einen vollen Kreis um das Spannelement drehbar sind, so daß eine relative Positionierung des rohrförmigen Elementes vor dem Aufbringen der kompressiven Kraft ungehindert möglich ist.
 3. Ein Gehgestell nach Anspruch 1 oder Anspruch 2, bei dem die Spannvorrichtungen (70, 72) aus einem einzigen Bolzen (70), der sich durch beide Klemmelemente (60) in der im wesentlichen rechtwinkligen Richtung erstreckt, und einer Mutter (72) besteht, die auf den Bolzen (70) aufschraubbar ist.
 4. Ein Gehgestell nach einem der vorstehenden Ansprüche, bei dem die oberen und unteren Holme einen im wesentlichen gleichbleibenden Querschnitt aufweisen, um ein unbehindertes Verschieben der Klemmelemente zu gewährleisten.
 5. Ein Gehgestell nach einem der Ansprüche 2 bis 4, bei dem eines der Klemmelemente (60) entlang einem entsprechenden Holm verschiebbar ist, um den relativen Winkel zwischen dem Befestigungsschaft (25) und den Holmen zu verändern, wobei das andere Klemmelement (60) sich dem geänderten Winkel ohne eine Verschiebung weder entlang dem entsprechenden Holm noch entlang dem Befestigungsschaft anpaßt.
 6. Ein Gehgestell nach einem der Ansprüche 1 bis 5, bei dem die zwei Klemmelemente (60) drehbar durch den einzigen Spanner gehalten sind, wobei der einzige Spanner ebenfalls zum gleichzeitigen Anziehen der beiden Klemmelemente um den unteren Schaft bzw. um den Holm benutzt wird.
 7. Ein Gehgestell nach einem der vorstehenden Ansprüche, bei dem der untere Holm (24) jeder Seite (14) länger als der obere Holm (26) ist, so daß eines der Beine (20a) auf jeder Seite (14) des Gehgestells in einem Winkel bezüglich des oberen Holmes (26) ausschrägt oder ausspreizt ist, so daß der Abstand von dem unteren Ende des ausgespreizten Beins (20a) zu dem unteren Ende des nicht ausgespreizten Beins (20b) größer ist als die Länge des oberen Holmes (26).
 8. Ein Gehgestell nach Anspruch 7, bei dem die Ausspreizung einen Winkel zwischen 18 und 50 Grad aufweist.
 9. Ein Gehgestell nach einem der vorstehenden Ansprüche, das zudem eine Gesäßanstoßvorrichtung (40) aufweist, die an dem Querelement (16) angebracht ist und die zum Anstoßen gegen die Rückseite eines Benutzers geeignet und positioniert ist.
 10. Ein Gehgestell nach Anspruch 9, bei dem die Anstoßvorrichtung (40) bezüglich des Querelementes (16) in seiner Stellung anpaßbar ist.
 11. Ein Gehgestell nach einem der vorstehenden Ansprüche, bei dem die Patientenabstützbefestigung aus einem Rohrstück besteht, welches in einem oberen Handgriff endet, wobei jedes Rohrstück an einem entsprechenden Seitenteil befestigt und der Griff oberhalb des oberen Holms angeordnet ist.



12. Ein Gehgestell nach einem der Ansprüche 7 bis 11, bei der obere Holm und das ausgespreizte Bein von jedem Seitenteil durch Biegen einer durchgehenden Länge eines Rohres hergestellt ist, wobei der Biegepunkt des Rohres das Ende des oberen Holms darstellt und das ausgespreizte Bein einen nach vorne weisenden Spreizwinkel mit seinem entsprechenden oberen Holmanteil des gebogenen Rohres bildet.

Revendications

1. Appareil d'aide à la marche adapté à l'utilisation en direction vers l'avant ou en direction inverse comprenant un bâti (12) d'aide à la marche dressé librement ayant deux côtés (14), chaque côté incluant deux jambes (20a, 20b) reliées par au moins un rail supérieur (26) et un rail inférieur (24) horizontaux dans l'ensemble, et un tronçon transversal (16) interconnectant ces deux côtés et un accessoire de soutien (28) d'un patient, caractérisé en ce qu'un accessoire de soutien (28, 30) d'un patient est prévu sur chacun des côtés (14) du bâti (12), chaque accessoire de soutien ayant une tige inférieure (25) et des moyens de soutien (24, 31, 33) à son extrémité supérieure et des moyens de serrage (32) fixant ledit accessoire (28, 30) à chacun des rails supérieur et inférieur (24, 26), chacun de ces moyens de serrage (32) comprenant deux éléments de serrage (60) juxtaposés, chacun avec une ouverture pour recevoir un élément tubulaire (24, 25), et tenus ensemble par un unique moyen de blocage (70, 72), les deux éléments de serrage étant libres de tourner autour du moyen de blocage (70, 72) et de glisser le long des rails (24, 26) pour permettre la variation de la relation angulaire ainsi que de la relation en hauteur de l'arbre inférieur (25) et des rails (24, 26).
2. Appareil d'aide à la marche selon la revendication 1, dans lequel les éléments de serrage (60) ont un profil en U et ont chacun une ouverture pour la réception d'un élément tubulaire (25) entre deux bras (65) et ont une surface extérieure en U comprenant deux faces extérieures (62) mutuellement parallèles substantiellement dans un même plan réunies par un tronçon intermédiaire (64) contenu entre les plans desdites faces extérieures parallèles (62), ces deux éléments de serrage (60) étant juxtaposés à l'une desdites faces extérieures de chaque élément, et un moyen de blocage (70, 72) pour appliquer de manière libérable une force de compression simultanément aux deux éléments dans une direction substantiellement perpendiculaire aux faces extérieures situées dans un même plan afin de tenir ces éléments dans une relation de juxtaposition tout en bloquant chaque élément autour d'un élément tubulaire correspondant, lesdits moyens de serrage pouvant tourner sur un cercle entier l'un par rapport à l'autre autour du moyen de blocage, autorisant de cette façon un positionnement relatif sans entrave de l'élément tubulaire avant l'application de ladite force de compression.
3. Appareil d'aide à la marche selon la revendication 1 ou la revendication 2, dans lequel les moyens de blocage (70, 72) comprennent une unique vis (70) s'étendant à travers les deux éléments de serrage (60) dans une direction substantiellement perpendiculaire et un écrou (72) se vissant sur ladite vis (70).
4. Appareil d'aide à la marche selon l'une quelconque des revendications précédentes, dans lequel les rails supérieur et inférieur ont une section droite substantiellement constante pour permettre un coulissement longitudinal sans entrave des moyens de serrage.
5. Appareil d'aide à la marche selon l'une quelconque des revendications 2 à 4, dans lequel l'un des éléments de serrage (60) est monté coulissant le long d'un rail correspondant pour le changement de la relation angulaire relative entre la tige (25) de l'accessoire et les rails, l'autre élément de serrage (60) s'accommodant de la relation angulaire modifiée sans déplacement ni le long du rail correspondant, ni le long de la tige de l'accessoire.
6. Appareil d'aide à la marche selon l'une quelconque des revendications 1 à 5, dans lequel les deux éléments de serrage (60) sont tenus ensemble contre le pivotement par l'unique moyen de blocage, cet unique moyen de blocage ayant aussi pour fonction de serrer simultanément les deux moyens de serrage autour de la tige inférieure et du rail respectivement.
7. Appareil d'aide à la marche selon l'une quelconque des revendications précédentes, dans lequel le rail inférieur (24) de chaque côté (14) est plus long que le rail supérieur (26) de sorte que l'une des jambes (20a) sur chacun des côtés (14) de l'appareil s'incline ou s'étend en oblique en faisant un angle avec le rail supérieur (26) si bien que la distance à partir de l'extrémité inférieure de la jambe inclinée (20a)



jusqu'à l'extrémité inférieure de la jambe non inclinée (20b) est supérieure à la longueur du rail supérieur (26).

- 5 8. Appareil d'aide à la marche selon la revendication 7, dans lequel l'inclinaison de la jambe inclinée se trouve entre 18 et 50°.
- 10 9. Appareil d'aide à la marche selon l'une quelconque des revendications précédentes, comprenant en plus un moyen (40) servant de tampon fessier attaché au tronçon transversal (16), adapté et disposé pour s'appliquer contre le dos d'un utilisateur.
- 15 10. Appareil d'aide à la marche selon la revendication 9, dans lequel le moyen (40) servant de tampon est réglable en position par rapport au tronçon transversal (16).
- 20 11. Appareil d'aide à la marche selon l'une quelconque des revendications précédentes, dans lequel l'accessoire de soutien d'un patient comprend une canne se terminant par une poignée supérieure, chaque canne étant montée sur un côté correspondant du bâti avec la poignée disposée au-dessus du rail supérieur.
- 25 12. Appareil d'aide à la marche selon l'une quelconque des revendications 7 à 11, dans lequel le rail supérieur et la jambe inclinée de chaque côté du bâti ont été réalisés par l'incurvation d'une longueur continue d'un tube, la zone d'incurvation de ce tube étant la terminaison du rail supérieur, la jambe inclinée formant un angle d'inclinaison avant avec sa partie correspondante de rail supérieur du tube incurvé.

26

30

35

40

45

50

55