

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
2 August 2001 (02.08.2001)

PCT

(10) International Publication Number
WO 01/56331 A1(51) International Patent Classification⁷: H04R 25/00

(21) International Application Number: PCT/DK01/00048

(22) International Filing Date: 23 January 2001 (23.01.2001)

(25) Filing Language: English

(26) Publication Language: English


(30) Priority Data:
PA 2000 00113 25 January 2000 (25.01.2000) DK(71) Applicant (for all designated States except US):
TØPHOLM & WESTERMANN APS [DK/DK];
Ny Vestergaardsvej 25, DK-3500 Værløse (DK).

(72) Inventor; and

(75) Inventor/Applicant (for US only): LUDVIGSEN, Carl
[DK/DK]; Borghaven 19, DK-2500 Valby (DK).(74) Agents: RAFFNSØE, Knud, Rosenstand et al.; In-
ternationalt Patent-Bureau, Høje Taastrup Boulevard 23,
DK-2630 Taastrup (DK).(81) Designated States (national): AE, AG, AL, AM, AT, AT
(utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA,
CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility
model), DK, DK (utility model), DM, DZ, EE, EE (utility
model), ES, FI, FI (utility model), GB, GD, GE, GH, GM,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,
MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK
(utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZW.(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

[Continued on next page]

(54) Title: A METHOD AND A SYSTEM FOR GENERATION OF A CALIBRATED SOUND FIELD



(57) Abstract: The present invention relates to a method and a system for calibration of a sound field to be used during fine-tuning of an auditory prosthesis. An auditory prosthesis is provided for compensation of hearing loss and for sound pressure determination. During calibration of the sound field to be used during fine-tuning of the auditory prosthesis, the auditory prosthesis is positioned at an observation point in the sound field, and the sound pressure at the auditory prosthesis is adjusted based on determinations of sound pressures performed with the auditory prosthesis. Thus, the need for dedicated calibrated sound pressure determining equipment is eliminated.

WO 01/56331 A1



162162



G00002

WO 01/56331 A1

IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*