[CLAIMS]

[Claim 1]

A sealant when used in a package for transporting of a silicon material, comprising

a sealant base having a first surface and a second surface that faces the first surface,

wherein the sealant base includes a first part including the first surface and a second part positioned closer to the second surface than the first part,

wherein the first part contains low density polyethylene (LDPE) to which substantially no slip agent is added, and

wherein the second part contains linear low density polyethylene (LLDPE), and

the first surface is positioned on an innermost surface of the package.

[Claim 2]

The sealant according to claim 1,

wherein the second part further contains low density polyethylene (LDPE).

[Claim 3]

The sealant according to claim 1 or 2,

wherein the sealant base further includes a third part positioned closer to the second surface than the second part, and

wherein the third part contains low density polyethylene (LDPE).

[Claim 4]

The sealant according to any one of claims 1 to 3,

wherein the sealant base is a laminated structure having at least a first layer including the first part and a second layer including the second part.

[Claim 5]

The sealant according to any one of claims 1 to 3,

wherein the sealant base is a single-layer structure having at least the first part and the second part.

[Claim 6]

The sealant according to claim 5,

wherein the first part is rich in low density polyethylene (LDPE).

[Claim 7]

The sealant according to any one of claims 1 to 6,

wherein the thickness of the second part is thicker than the thickness of the first part.

[Claim 8]

The sealant according to any one of claims 1 to 7,

wherein the linear low density polyethylene (LLDPE) contained in the second part is linear low density polyethylene to which substantially no slip agent is added.

[Claim 9]

A packaging material, comprising:

a base composed of a resin material; and

the sealant according to any one of claims 1 to 8, which

is provided on one side of the base,

wherein the sealant is provided so that the second surface is brought into contact with one side of the base.

[Claim 10]

The packaging material according to claim 9, further comprising

a gas barrier layer that is provided on the other side of the base.

[Claim 11]

A package for transporting of a silicon material, which is composed of the packaging material according to claim 9 or 10.

[Claim 12]

A package of a silicon material, comprising:

the package for transporting of a silicon material according to claim 11; and

a silicon material that is accommodated in the package for transporting of a silicon material.