

RESPONSE MESSAGE TRANSMITTER AND RESPONSE MESSAGE
TRANSMITTING METHOD IN CELLULAR MOBILE
TELEPHONE APPARATUS AND RECORDING
MEDIUM RECORDING PROGRAM FOR EXECUTING THE METHOD

BACKGROUND OF THE INVENTION

The present invention relates generally to a response message transmitter in a portable mobile radio communication apparatus such as a portable telephone apparatus, a cordless telephone apparatus, or the like, and more particularly to a response message transmitter in a cellular mobile telephone apparatus which is operable when the cellular mobile telephone apparatus receives an incoming call but the user cannot immediately answer a calling party, for example, because the user is driving a vehicle or the like, or because the user is in a place where the use of cellular mobile telephones and so on is restricted, or the like, to notify such a situation to the calling party.

With a currently used cellular mobile telephone apparatus, when an incoming call is received, although the user should respond to the call, the user is not always immediately ready to do so. Particularly, when the user is driving a vehicle or the like, the user cannot immediately respond to a call. Conventional cellular mobile telephone apparatus have a function of pending a call for coping with such a situation. This function is invoked by depressing a



pending button, when the user cannot immediately accept a call, to notify a calling party through a base station that the user cannot immediately respond to the call although the telephone line connection has been established

5 therebetween, to reduce the volume of a call indicating alarm, and to permit the user to initiate a communication when the user is ready to do so. Such a cellular mobile telephone apparatus is disclosed in JP-A-8-163208.

However, such a simple response message function
10 is not sufficient to notify a calling party of specific reasons for which the user is pending a call. More specifically, the calling party cannot know whether the user cannot respond to a call because he or she (hereinafter abbreviated as he/she) is now in a place where
15 the use of cellular mobile telephone apparatus is restricted, and is moving from that place; or because the user is now busy with other business; or because the user is driving a vehicle or the like so that he/she cannot respond to a call before he/she stops driving. It can
20 therefore be thought that a pending state extends over a so long time period that the calling party gives up the call, as the case may be.

With the conventional cellular mobile telephone apparatus as described above, the user suffers from an
25 inconvenience when an incoming call is received but the user cannot immediately respond to the call because the conventional cellular mobile telephone apparatus does not have any means for notifying a calling party of the current



situation of the user. In addition, the calling party cannot either know the current situation which the user of the destination cellular mobile telephone apparatus is experiencing.

5 According to certain data, traffic accidents related to the cellular mobile telephone apparatus during the operation of vehicle happen more while drivers are looking for their cellular mobile telephone apparatus for placing a call or for responding to an incoming call than
10 while they are actually communicating. The conventional cellular mobile telephone apparatus have not at all been designed in consideration of improvements, particularly, in the usability addressed to such a situation.

 Furthermore, it has been found from exemplary
15 uses that when the users carry their cellular mobile telephone apparatus with them, most of the users keep it in a bag or the like. Thus, even though the user is in a situation in which he/she cannot immediately respond to an incoming call, the user must once take the cellular mobile
20 telephone apparatus from his/her bag, each time an incoming call is received in such a situation, for invoking the pending operation. It can therefore be seen that the conventional cellular mobile telephone apparatus have not been designed in any consideration of improvements in the
25 usability addressed to such a situation.

SUMMARY OF THE INVENTION

The present invention has been made in view of



the problems mentioned above inherent to the prior art cellular mobile telephone apparatus. It is therefore an object of the present invention to provide a response message transmitter in a cellular mobile telephone
5 apparatus which permits the user of the cellular mobile telephone apparatus to notify, even if he/she cannot immediately respond to a call, a calling party of the current situation of the user through simple manipulations.

According to the present invention, a cellular
10 mobile telephone apparatus comprises incoming call responding means for responding to an incoming call from a calling party, means for storing a plurality of messages to be transmitted to the calling party, means for selecting a message to the calling party, and means for transmitting a
15 selected message to the calling party, wherein a message to the calling party, previously selected by the user and stored in the storing means, can be transmitted to the calling party by the action of the incoming call responding means when the user cannot immediately respond to the call
20 from the calling party.

The cellular mobile telephone apparatus further comprises a plurality of response switches corresponding to the stored messages, as the incoming call responding means, wherein the user may select a message to the calling party
25 with the plurality of response switches, and respond to the calling party by transmitting the selected message.

The cellular mobile telephone apparatus is designed to proviously select one of the plurality of

messages and automatically transmit the selected message in response to the incoming call.

The cellular mobile telephone apparatus further comprises a change-over switch as the means for selecting a
5 message to the calling party, and a response switch as the incoming call responding means, wherein the user may select a message to the calling party with the change-over switch and respond to the calling party with the response switch.

The cellular mobile telephone apparatus further
10 comprises a speech coding encoder/decoder circuit for use in a digital telephone system. The speech coding encoder/decoder circuit may be utilized, when a message to a calling party is generated, to convert an analog voice signal to a digital voice signal so that the digital voice
15 signal can be stored in the cellular mobile telephone apparatus.

The cellular mobile telephone apparatus further comprises means for detecting voice while the reception of an incoming call is being notified, wherein a response can
20 be made to a calling party by detecting voice of the user during the notification of the incoming call reception.

The cellular mobile telephone apparatus further comprises means for recognizing a voice pattern, wherein the recognizing means detects a voice pattern while the
25 reception of an incoming call is being notified, such that the user can respond to a calling party by transmitting a message to the calling party selected on the basis of the detected voice pattern.

The cellular mobile telephone apparatus further comprises a speech coding encoder/decoder circuit for use in a digital telephone system which is utilized to convert an analog voice signal to a digital voice signal so that
5 voice can be detected or a voice pattern can be recognized.

The present invention also provides a cellular mobile telephone apparatus comprising a cellular mobile telephone body and an incoming call communicator for notifying the reception of an incoming call, wherein:
10 the cellular mobile telephone body includes transmitting/receiving means for transmitting and receiving information to and from the incoming call communicator through a radio channel, incoming call responding means for responding to an incoming call from a calling party, means
15 for storing a message to the calling party, and means for transmitting the message to the calling party; and

the incoming call communicator includes incoming call responding means for responding to an incoming call received from a calling party, and transmitting/receiving
20 means for transmitting and receiving information to and from the cellular mobile telephone body through a radio channel,

wherein incoming call information is transmitted from the cellular mobile telephone body to the incoming
25 call communicator when an incoming call is received, and if the incoming call from the calling party cannot be responded immediately, response information is transmitted



from the incoming call communicator to the cellular mobile telephone body by the action of the incoming call responding means, so that the cellular mobile telephone body can transmit the previously stored message to the
5 calling party.

The present invention further provides a cellular mobile telephone apparatus comprising a cellular mobile telephone body and an incoming call communicator for notifying the reception of an incoming call, wherein:
10 the cellular mobile telephone body includes transmitting/receiving means for transmitting and receiving information to and from the incoming call communicator through a radio channel, incoming call responding means for responding to an incoming call from a calling party, means
15 for storing a plurality of messages to the calling party, means for selecting a message to the calling party, and means for transmitting a selected message to the calling party; and

the incoming call communicator includes incoming
20 call responding means for responding to an incoming call from a calling party, means for selecting a message to the calling party, and transmitting/receiving means for transmitting and receiving information to and from the cellular mobile telephone body through a radio channel,

25 wherein incoming call information is transmitted from the cellular mobile telephone body to the incoming call communicator when an incoming call is received, and if the call received from the calling party cannot be



responded immediately, response information is transmitted from the incoming call communicator to the cellular mobile telephone body by the action of the incoming call responding means, so that the cellular mobile telephone body can transmit a previously stored message to the calling party, selected by a user, to the calling party.

The incoming call communicator further includes a plurality of response switches corresponding to the stored messages, as the incoming call responding means, wherein the user may select a message to the calling party with the plurality of response switches and respond to the calling party by transmitting the selected message.

The incoming call communication is designed to previously select one of the plurality of messages and automatically transmit the selected message in response to the incoming call.

The incoming call communicator further includes a change-over switch as the means for selecting a message to the calling party, and a response switch as the incoming call responding means, wherein the user may select a message to the calling party with the change-over switch and respond to the calling party with the response switch.

The incoming call communicator further includes means for detecting voice while the reception of an incoming call is being notified, wherein response information can be sent to the cellular mobile telephone body by detecting voice of the user during the notification of the incoming call reception.

The incoming call communicator further includes means for recognizing a voice pattern, wherein the recognizing means detects a voice pattern while the reception of an incoming call is being notified, such that
5 response information is changed in accordance with the voice pattern to select one of the message to the calling party stored in the cellular mobile telephone body, whereby the calling party can be responded to with the selected message.

10 The incoming call communicator further includes means for displaying time and date, and a holding strap with which the user may hold the incoming call communicator on his/her body such as an arm.

BRIEF DESCRIPTION OF THE DRAWINGS

15 Fig. 1 is a block diagram illustrating an embodiment of a cellular mobile telephone apparatus according to the present invention;

Fig. 2 is a plan view depicting an outer appearance of the cellular mobile telephone apparatus
20 illustrated in Fig. 1;

Fig. 3A is a flow chart illustrating an embodiment of the operation of the cellular mobile telephone apparatus according to the present invention;

Fig. 3B is a flow chart illustrating a partially
25 modified example of the operation illustrated in Fig. 3A;

Fig. 4 is a flow chart illustrating another embodiment of the present invention;

This Sheet Has Been Replaced



Figs. 5A and 5B are flow charts illustrating further embodiments of the present invention, respectively;

Figs. 6A and 6B are block diagrams illustrating other configurations of the cellular mobile telephone apparatus according to the present invention, where Fig. 6A illustrates a cellular mobile telephone body, and Fig. 6B illustrates an incoming call communicator for use with the body;

Figs. 7A and 7B are plan views depicting outer appearances of the cellular mobile telephone body and the incoming call communicator illustrated in Figs. 6A and 6B, respectively;

Fig. 8 is a flow chart illustrating the operation of the cellular mobile telephone body illustrated in Fig. 6A;

Fig. 9 is a flow chart illustrating the operation of the incoming call communicator illustrated in Fig. 6B; and

Fig. 10 is a block diagram illustrating a further embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS


Embodiments of the present invention will hereinafter be described with reference to the accompanying drawings.

Fig. 1 is a block diagram illustrating the configuration of a cellular mobile telephone apparatus according to one embodiment of the present invention. Fig.

2 depicts an outer appearance of the cellular mobile telephone apparatus illustrated in Fig. 1.

As illustrated in Fig. 1, a radio communication signal sent from a base station (not shown) is inputted to
5 a radio transmitter/receiver circuit 4 through an antenna 3 in a cellular mobile telephone apparatus 1. The received radio communication signal is converted to an intermediate frequency signal in the radio transmitter/receiver circuit 4. Then, the received intermediate frequency signal is
10 demodulated to a digital signal by a digital modulator/demodulator circuit 5, and the demodulated digital signal is decoded by an error correcting encoder/decoder circuit 6. Digital signals decoded by and outputted from the error correcting encoder/decoder circuit 6 include a digital
15 communication signal and a digital control signal, and the digital control signal is supplied to and identified by a control circuit 10. The digital communication signal, in turn, is decoded by a speech coding encoder/decoder circuit 7 to restore an analog communication signal which is
20 subsequently outputted from an audio output device 8.

On the other hand, outgoing speech is first transduced to a transmission signal by a transducer 9, and the transmission signal is then converted to a digital transmission signal by the speech coding encoder/decoder
25 circuit 7. The digital transmission signal, after encoded in the error correcting encoder/decoder circuit 6 together with a digital control signal generated in the control



circuit 10, is inputted to a digital modulator/demodulator circuit 5 and modulated to an orthogonally modulated signal therein. The modulated signal is transmitted to the base station from the antenna 3 after being converted to a high frequency signal by the radio transmitter/receiver circuit 4 for transmission through a predetermined radio channel.

The control circuit 10, which employs a microcomputer as a main control unit, has means for generating a message to a calling party, means for storing such messages in a memory, and means for transmitting a message to a calling party, in addition to functions for controlling respective components of the cellular mobile telephone apparatus 1.

Electrical power required by the cellular mobile telephone apparatus 1 is generated by a battery power supply 18 and supplied to respective components through a power supply switch 19.

Next, the operation of the cellular mobile telephone apparatus 1 according to this embodiment of the present invention will be described with reference again to Figs. 1 and 2 as well as to Fig. 3 illustrating an operation flow chart.

When it is assumed that the user cannot immediately respond to an incoming call because the user is driving a vehicle or the like, the cellular mobile telephone apparatus 1 may have previously created a message to cope with such a situation. More specifically, an



analog voice signal from the transducer 9 is converted to serial digital data by the speech coding encoder/decoder circuit 7. The serial digital data is then converted to a parallel signal by the error correcting encoder/decoder circuit 6 and stored in a storage circuit 12 through the control circuit 10.

It should be noted that the storage circuit 12 is not provided exclusively for storing messages but is also shared by the control circuit 10 for its control purposes.

Alternatively, messages stored in the storage circuit 12 may be previously written into a read only memory (ROM) such that the user need not register messages.

The operation flow of the cellular mobile telephone apparatus 1 when responding to an incoming call will be described below with reference to Fig. 3A.

The cellular mobile telephone apparatus 1, when it is powered on (step 30), enters a standby state and remains in this state until it receives a call reception signal destined thereto (step 31). When the cellular mobile telephone apparatus 1 receives the call reception signal (step 32), the control circuit 10 recognizes the reception of an incoming call and generally lets the user know the reception of an incoming call for a predetermined time period with incoming call notification in the form of an alarm generated by a sounder 11 or vibrations generated by a vibrator 15 (step 33). Simultaneously with this operation, the control circuit 10 monitors whether or not the user manipulates a key on the cellular mobile telephone



apparatus 1 in response to the incoming call notification or whether or not of state-holdinh keys has been previously depressed (step 34).

In this event, if the user does not respond to
5 the incoming call notification in spite of the incoming call notification which has been provided to the user for the predetermined time period (step 35), the control circuit 10 transmits an absence message for notifying the calling party that the user is now absent (step 36), and
10 initiates a recording operation when the calling party wants to leave some message (step 37). Then, the communication channel is cut (step 39) and the cellular mobile telephone apparatus 1 again enters the standby state (step 31) when the calling party cuts the call or an
15 available recording time expires (step 38).

The predetermined time period provided at step 35 is actually a time period required for the control circuit 10 to notify the user of the reception of an incoming call a number of times which has been previously registered in
20 the control circuit 10 to generate the alarm from the sounder 11 or vibrations from the vibrator 15 the registered number of times.

If the user responds by manipulating a key while the reception of the incoming call is being notified to the
25 user (step 34) or if one of the state-holding keys has been previously depressed, an operation specified by an associated key is performed (steps 40 - 45). Keys used at

This Sheet Has Been Replaced



the reception of an incoming call are classified into two: function keys 16, according to the present invention, and a pending key within a key input device 13. When an arbitrary key other than the two kinds of keys is
5 depressed, an any-key-answer function is invoked to immediately enter the cellular mobile telephone apparatus 1 into a communication state.

When the pending key is depressed, the cellular mobile telephone apparatus 1 remains in a pending state
10 until the pending key is released (steps 46 - 48). The cellular mobile telephone apparatus 1 enters the communication state when the pending state is released (steps 48, 49). After the cellular mobile telephone apparatus 1 enters the communication state, when the
15 calling party or the user cuts the call, the communication channel is cut and the cellular mobile telephone apparatus 1 again enters the standby state (steps 50, 39, 31).

When the user cannot immediately respond to an incoming call, the user may transmit a message previously
20 stored in the storage circuit 12 (steps 43 - 45) by selectively depressing one of keys in the input device 13 provided on the cellular mobile telephone apparatus 1, particularly, one of the three function keys 16 which are each assigned a function for transmitting a message to a
25 calling party (steps 34, 40 - 42).

Specifically explaining with reference again to Fig. 2, since three function keys 16 are provided, up to three kinds of messages may be registered. For example, a

message "Since I am now driving a car, I will call you later when I stop the car" may be registered in a function key 1 (F1); a message "Since I am now in a cabin of a train, please hold on for a while until I go to the deck" may be registered in a function key 2 (F2); and a message "Since I am now in conference, please call me again in about one hour" may be registered in a function key 3 (F3).

The control circuit 10 determines which of the function keys 16 has been depressed, and reads a message corresponding to the depressed function key from the storage circuit 12 to transmit the read message (steps 43 - 45). After the message is transmitted, the cellular mobile telephone apparatus 1 initiates an operation for recording a message, which is similar to the processing performed after the absence message is transmitted, since the calling party may want to leave a message (step 37). When the calling party cuts the call after he/she has recorded the message or when a recording available time expires, the communication channel is cut and the cellular mobile telephone apparatus 1 again enters the standby state (steps 38, 39, 31).

Next, functional operations performed when a message is transmitted will be described with reference to the blocks illustrated in Fig. 1.

The control circuit 10 of the cellular mobile telephone apparatus 1 reads a message, previously stored by the user, to a calling party from the storage circuit 12,



inputs the read message to the error correcting encoder/
decoder circuit 6, and then transmits the message to the
calling party in accordance with the aforementioned
transmission operation. In this way, an audio path from
5 the transducer 9 to the error correcting encoder/decoder
circuit 6 through the speech coding encoder/decoder circuit
7 may be switched to input a message stored in the storage
circuit 12 to the error correcting encoder/decoder circuit
6 so that the modulator/demodulator circuit 5 and the
10 transmitter/receiver circuit 4 may be used in common.
Thus, a message stored in the storage circuit 12 can be
readily transmitted.

Since one message corresponds to one function key
16, the user may readily attend to an incoming call by
15 selecting the message most appropriate to the situation,
which the user is now experiencing, from the three function
keys and depressing the function key corresponding to the
selected message. In addition, since the calling party can
be immediately notified of the situation which the user is
20 experiencing, it is possible to provide the calling party
with a material for determining whether the calling party
should be waiting without cutting the call, or whether he/
she should once give up the call and place another call
later. In this way, since useless waiting time is
25 eliminated, the calling party can save call fees.
Furthermore, since a channel occupying time is reduced, a
load on an exchanger can be reduced.

Since the contents of an actual message may be an extremely simple sentence as the aforementioned examples and take approximately five seconds at most, three messages will require a storage capacity corresponding to

5 approximately 15 seconds. The storage circuit 12 currently used in the cellular mobile telephone apparatus includes an IC memory for message which generally has a capacity corresponding to approximately 30 seconds in time. Therefore, even if a 15-second portion of the storage

10 circuit 12 is reserved for the messages, the remaining 15-second portion may be used to store a message from a calling party.

While in the foregoing embodiment, the three function keys 16 are illustrated in the same size, they

15 need not necessarily have the same size. Rather, in place of the function keys 16, the cellular mobile telephone apparatus may be provided with such function keys that enable the user to recognize their special functionalities only by touching them, without requiring visual

20 confirmation, or with touch switches, which are capable of immediately functioning in response to a touch thereto. These alternatives eliminating the need of visual confirmation are particularly suitable when the user is driving a vehicle or the like. Furthermore, a voice

25 recognition function as illustrated in Fig. 3B may be added to improve its original usefulness. More specifically, Fig. 3B illustrates a flow chart which has additional steps 51 - 54 other than those in the operation flow of Fig. 3A,



and includes all the steps appearing in Fig. 3A.

Referring specifically to Fig. 3B, voice of the user inputted to the transducer 9 of the cellular mobile telephone apparatus 1 illustrated in Fig. 1 is converted to
5 serial digital data by the speech coding encoder/decoder circuit 7, and the serial digital data is again converted to a parallel signal by the error correcting encoder/decoder circuit 6. The control circuit 10, upon sensing the inputted digital voice signal (step 51), performs
10 Fourier transform on the digital voice signal to extract a spectrum component of the voice (step 52). Then, if the extracted voice signal is larger than a previously detected noise component, the voice signal is recognized as voice (step 53), and a message is transmitted to notify a calling
15 party that the user is driving a car, or the like (step 54).

In the embodiment illustrated in Fig. 3A, when the user is notified of the reception of an incoming call at step 33, the user finds and depresses a function key for
20 generating an appropriate response message or it has been previously depressed to transmit it to a calling party, whereas Fig. 4 shows another embodiment employing state-holding function keys F1 - F3 as the respective function keys 16. Such state-holding function keys may be a slide
25 switch.

According to the embodiment illustrated in Fig. 4, a message to be transmitted when an incoming call is received has been previously set by depressing or sliding a



corresponding function key. Thereafter, when an incoming call is received, the reception of the incoming call is notified (steps 32, 33), and the states of the function keys F1 - F3 are immediately checked (steps 65 - 67). If
5 any of the keys is set ON, the transmission of a message corresponding to the key is started (steps 43 - 45). The step 33 may be deleted. In the case, the previously set message is transmitted without notifying the reception of incoming call. The notification of the incoming call
10 reception is continued even while the message is being transmitted (step 68), and if depression of any key is sensed during this period (step 34), the flow proceeds to step 46. The rest of the operation steps in Fig. 4 are identical to those in Fig. 3A, so that such steps are
15 designated by the same reference numerals, and explanation thereof is omitted.

Fig. 5A is a flow chart illustrating another embodiment of the present invention. In this embodiment, a message is previously selected from among a plurality of
20 messages such that the previously selected message is transmitted in response to depression of a single function key. As is appreciated, only one function key is provided in this embodiment.

Generally, messages required when an incoming
25 call is received may be classified into two: an absence message which may be transmitted when the user is absent, and a message for notifying a calling party of a situation which the user is currently experiencing. While a



plurality of messages must be prepared for notifying a calling party of a situation which the user is currently experiencing because a variety of possible situations may exist, only one message most appropriate for indicating the
5 situation at that time is transmitted to the calling party.

In Fig. 5A, the same functional steps as those in Fig. 3A are designated by the same reference numerals and repetitive explanation thereof is omitted.

Referring specifically to Fig. 5A, when a message
10 must be changed, the user selects a message indicative of a situation which the user himself/herself is currently experiencing, using the key input device 13, while the cellular mobile telephone apparatus 1 remains in the standby state (steps 56, 57). Specifically, a plurality of
15 messages are stored at assigned addresses in the storage circuit 12. The storage circuit 12 also comprises a pointer memory 120 for storing the address of a message to be transmitted when the function key 16 is depressed. As the user specifies a number from the key input device 13
20 for specifying an associated message, the address of the message is stored in the pointer memory 120. Alternatively, a switch for selecting a message may be used in place of the pointer memory 120.

In this way, when the function key 16 is simply
25 depressed (steps 34, 58) at the time an incoming call is received (step 33), a message specified by the address previously stored in the pointer memory 120 at step 57 is transmitted to a calling party (step 59). Thus, the user



is not required to look for the function key 16 associated with a necessary message in a busy situation, at the time an incoming call is received, and moreover, a large sized function key 16 may be provided on the cellular mobile telephone apparatus 1, thus resulting in an improvement in the operability of the cellular mobile telephone apparatus 1.

While in the embodiment illustrated in Fig. 5A, a message is transmitted by depressing the function key 16 when the reception of an incoming call is notified, the operation flow may directly jump to step 59 to transmit a previously selected message after an incoming call is sensed at step 32 without notifying the reception of the incoming call.

Further, the operation functions at steps 51 - 54 as illustrated in Fig. 3B may be added to the operation procedure illustrated in Fig. 5A so that a response message may be transmitted in response to detection or recognition of voice pronounced by the user in place of manipulating the function key 16. The voice recognition may be implemented by determining whether or not detected voice matches a predetermined signal pattern, other than a test for examining whether a signal level of detected voice is equal to or higher than a predetermined value.

Fig. 5B is a flow chart showing an example in which the step 36 in Fig. 5A is incorporated into the step 59 in Fig. 5A. In the case, the step 57 in Fig. 5A can select also the absence message.



Since such voice recognition is performed during the notification of incoming call reception, which is not in a communication state, the speech coding encoder/decoder circuit 7 and the error correcting encoder/decoder circuit 6 may be commonly used for the voice detection or the voice recognition under the control of the control circuit 10.

Next, another embodiment of the present invention will be described with reference to Figs. 6A - 9.

In Figs. 6A, 6B, 7A, and 7B, a cellular mobile telephone apparatus comprises a main body constituting a cellular mobile telephone 1 and an incoming call communicator 2. The cellular mobile telephone 1 comprises an incoming call notification transmitter/receiver circuit 61 for communicating with the incoming call communicator 2 and an incoming call notification transmitting/receiving antenna 62 in addition to the configuration and functions of the cellular mobile telephone apparatus described in the aforementioned embodiment.

The incoming call communicator 2 comprises an incoming call notification transmitter/receiver circuit 71 for communicating with the cellular mobile telephone 1; an incoming call notification transmitting/receiving antenna 72; an incoming call notification control circuit 23 for controlling respective components of the incoming call communicator 2; an incoming call notification storage circuit 24 for storing response information and so on; a key input device 73 for inputting information; a function

This Sheet Has Been Replaced



key 16; a vibrator 25 for notifying the reception of an incoming call; a LED display 26 for displaying information from the cellular mobile telephone 1; and a display unit 74. The incoming call communicator 2 is powered by a battery 28 which supplies electrical power to the respective components through a power supply switch 29.

The cellular mobile telephone 1 and the incoming call communicator 2 mutually transmit and receive information through radio transmission. Signal formats and transmission scheme used for such radio transmission are fully disclosed in Japanese Patent Application No. 147007/1996 filed June 10, 1996 and corresponding U.S. Patent Application Serial No. 08/872,138, the contents of which are hereby incorporated by reference. The contents of the applications will be outlined below. Information for radio transmission is defined in accordance with an information transmission format composed of a sequential bit train including a preamble, synchronization information, identification information, and information to be transmitted. This sequential bit train is FM-modulated at a carrier frequency at 300 MHz and transmitted at a transmission rate of 512 bps.

For information transmission, the information is transmitted in units of 8 bits, 2 bits of which are assigned to synchronization bits set at "1" and "0." The synchronization bits are used to resynchronize the information every 8 bits when it is demodulated. With the synchronization bits, a total of approximately 6% of



transmission rate error can be tolerated on the transmission side and on the reception side. Thus, effective information within each 8-bit transmitted information is 6 bits.

5 Fig. 8 illustrates an operation flow of the main body of the cellular mobile telephone apparatus depicted in Fig. 7A, in which steps having the same functions as those in Fig. 5 are designated by the same reference numerals. In the cellular mobile telephone apparatus of this
10 embodiment, the notification of the reception of an incoming call is not only made in the main body 1 but also simultaneously transmitted to the incoming call communicator 2 through a radio signal (step 33'). Then, it is monitored whether or not any key on the main body 1 is
15 manipulated (step 34) or whether or not a response is transmitted from the incoming call communicator 2 (step 80) while the reception of the incoming call is being notified.

 In this event, if a key on the cellular mobile telephone body 1 is manipulated, similar processing to the
20 operation in the foregoing embodiment illustrated in Fig. 3a, 3B, 4, or 5 is performed (at step 58 and subsequent steps branched from step 34 through a "yes" path). On the other hand, if a response is transmitted from the incoming call communicator 2 (step 80), the contents of the response
25 information is analyzed (step 81) to select a message to be transmitted (step 82). Operations performed subsequently are similar to the processing performed when a function key



on the main body 1 is depressed (at step 59 and subsequent steps). It is noted that the operations at steps 80 - 82 are disclosed in the aforementioned Japanese Patent Application No. 147007/1996 and the corresponding U.S.

5 Patent Application Serial No. 08/872,138.

Fig. 9 illustrates an operation flow of the incoming call communicator 2, where steps having the same functions as those in Fig. 5 are designated by the same reference numerals. The incoming call communicator 2
10 remains in a standby state until it receives an incoming call notifying signal from the main body 1 (step 31).

Here, the user selects a message to be transmitted from the main body 1 in accordance with the situation which the user himself/herself is now
15 experiencing using the key input device 73 while the incoming call communicator 2 remains in the standby state (steps 56, 57). At step 57, selected response information, which is to be sent when the function key 16 is depressed, is generated and stored in the incoming call notification
20 storage circuit 24.

Upon receiving an incoming call notifying signal, the control circuit 10 recognizes this signal, and makes an incoming call notification to the user for a fixed time period normally in the form of vibrations generated by the
25 vibrator 25 (steps 85, 86). Simultaneously with this, the incoming call communicator 2 monitors whether or not the user manipulates a key in response to the incoming call notification (step 34).

If no response is made to the incoming call notification in spite of the incoming call notification performed for the fixed time period, determination is made that the user is absent, and the incoming call communicator 2 again enters the standby state (steps 35, 31). Actually, the fixed time period may be long enough for the user to make a response, so that it is set to approximately 30 seconds to one minute.

On the other hand, if a response is made through a key manipulation to the incoming call notification while the reception of the incoming call is being notified to the user (step 34), the incoming call communicator 2 generates response information based on information on messages stored in the incoming call notification storage circuit 24 at step 57 (step 87), and transmits the response information to the main body 1 from the incoming call notification transmitter/receiver circuit 41 through the incoming call notification transmitting/receiving antenna 42 (step 88).

By thus providing the compact incoming call communicator 2, even if the main body 1 of the cellular mobile telephone apparatus is held in a bag upon receiving an incoming call, the incoming call communicator 2, if placed in a pocket of clothes, permits the user to transmit a message to a calling party without operating the main body 1 each time the reception of an incoming call is notified. In addition, an improvement in operability is also expected.

Additionally, as an alternative form of this embodiment, the incoming call communicator 2 may be incorporated in a wristwatch to further improve the operability. Since the wristwatch or the like can be
5 directly mounted on a human body, vibrations generated by the vibrator can be advantageously sensed without fail when an incoming call is notified through the vibrations. Also, when a response is made to the notification, the user can manipulate the incoming call communicator 2 without looking
10 for it. Thus, even when the user is driving a vehicle or the like, by way of example, the user can manipulate the incoming call communicator without interfering with the driving.

It should be noted that the radio transmission
15 described in the foregoing embodiments is not limited to a transmission through radio waves, but may be realized by utilizing other media such as infrared rays, ultrasonic waves, and so on.

Next, a further embodiment will be described.

20 The aforementioned embodiments are characterized in that possible messages to be transmitted to a calling party are stored in the storage circuit of the cellular mobile telephone apparatus. However, it is not necessary to prepare many kinds of messages for transmitting to a
25 calling party upon receiving an incoming call. Actually, ten kinds of messages having different contents may be considered as sufficient. Thus, it is not rational that

similar messages are stored in each cellular mobile telephone apparatus.

To eliminate this irrationality, a required number of fixed-style messages may be prepared as possible
5 messages to be transmitted to a calling party, and previously stored in a radio base station or in a switching station 90 as a database 91, as illustrated in Fig. 10. The cellular mobile telephone apparatus, in turn, may store an address code for reading a desired message in a pointer
10 memory 120 of a storage circuit 12, such that the user of the cellular mobile telephone apparatus, when he/she wants to transmit a message to a calling party, sends the address code associated with the message stored as the database 91 to the radio base station or to the switching station, in
15 place of a message stored in the storage circuit 12 of the cellular mobile telephone apparatus as shown in the aforementioned embodiments. The radio base station or the switching station analyzes the message code to transmit the specified message from the database 91 to the calling
20 party.

Since the configuration described above eliminates the need to store messages in the storage circuit of each cellular mobile telephone apparatus, the storage circuit of the cellular mobile telephone apparatus
25 can be reduced in size.

While the foregoing embodiments of the present invention have been described in connection with a mobile station of a digital car telephone system, the present



invention should not be necessarily limited to this particular scheme, but encompasses any other configurations conceivable for achieving the object of the present invention. Furthermore, the appearances, configurations,
5 circuits, means, and so on of the apparatus described in the embodiments are not intended to limit the present invention.

The cellular mobile telephone apparatus of the present invention enables the user to immediately notify a
10 calling party of his/her current situation, even if the user cannot immediately answer a call.

Even when the user of the cellular mobile telephone apparatus is driving a vehicle or the like, the user can make an appropriate response by notifying a
15 calling party of the current situation without interfering with the driving.

Also, even in a place where the use of the cellular mobile telephone apparatus is restricted (restrictions not due to the influence of electromagnetic
20 waves but due to manners of using the cellular mobile telephone apparatus), the user can make an appropriate response by notifying a calling party of the use's situation, in combination of the vibration incoming call notifying means using a vibrator, without annoying other
25 people around the user.

This Sheet Has Been Replaced



CLAIMS:

1. A response message transmitter in a cellular mobile telephone apparatus comprising:
 - a memory for storing a plurality of messages for
 - 5 responding to a calling party;
 - means for selecting one from said plurality of messages;
 - means for transmitting a message selected by said selecting means to the calling party; and
 - 10 incoming call responding means operable when an incoming call is received to instruct said transmitting means to transmit the message selected by said selecting means to the calling party.
2. An apparatus according to claim 1, wherein said
- 15 plurality of messages include a message notifying that the user of said apparatus is driving a vehicle.
3. An apparatus according to claim 1, wherein said selecting means includes a plurality of keys provided in correspondence to the respective ones of said plurality of
- 20 messages.
4. An apparatus according to claim 3, wherein a key corresponding to the message for notifying that the user of said apparatus is driving a vehicle is formed to be distinguishable from other keys with a tactile sense on
- 25 said key.
5. An apparatus according to claim 3, wherein said key corresponding to the message for notifying that the

This Sheet Has Been Replaced



user of said apparatus is driving a vehicle comprises a touch switch.

6. An apparatus according to claim 1, wherein said selecting means includes a state-holding switch for
5 selecting one of said plurality of messages.

7. An apparatus according to claim 6, wherein said selecting means previously selects a desired one from among said plurality of messages before said incoming call is received.

10 8. An apparatus according to claim 7, wherein said incoming call responding means includes a key to be operated in response to the incoming call.

9. An apparatus according to claim 1, wherein said selecting means includes means for previously selecting a
15 message before said incoming call is received.

10. An apparatus according to claim 9, wherein said selecting means includes:

means for specifying a desired one from among said plurality of messages; and

20 a pointer memory for storing an address of said memory at which a message specified by said specifying means is stored.

11. An apparatus according to claim 10, wherein said incoming call responding means includes means responsive to
25 said incoming call to read said specified message based on said address stored in said pointer memory and to instruct said transmitting means to transmit said specified message.

This Sheet Has Been Replaced



12. An apparatus according to claim 9, wherein said selecting means includes a switch for selecting one from among said plurality of messages.

13. An apparatus according to claim 1, further
5 comprising means for generating at least one of said plurality of messages.

14. An apparatus according to claim 13, wherein said message generating means includes:

an audio encoder circuit for converting a voice
10 signal inputted from a transducer to a digital signal; and
means for storing the digital signal converted by said audio encoder circuit in said memory.

15. An apparatus according to claim 1, wherein said incoming call responding means includes means for detecting
15 voice of the user.

16. An apparatus according to claim 15, wherein said voice detecting means includes:

means for transducing said voice of the user to an electrical signal;

20 means for extracting a predetermined voice spectrum component from a voice signal fetched by said transducing means; and

means for operating said transmitting means when the component extracted by said extracting means is higher
25 than a predetermined noise level.

17. An apparatus according to claim 15, wherein said voice detecting means includes means for recognizing a pattern of voice of said user.



This Sheet Has Been Replaced



18. An apparatus according to claim 1, further comprising means for cutting a communication channel for said apparatus after said transmitting means transmits said selected message.
- 5 19. A response message transmitter in a cellular mobile telephone apparatus comprising a cellular mobile telephone body and an incoming call communicator which communicates with said cellular mobile telephone body, wherein:
- 10 said cellular mobile telephone body comprises a transmitter/receiver for transmitting and receiving information to and from said incoming call communicator, means responsive to an incoming call received from a calling party for instructing said transmitter/receiver to
- 15 notify said incoming call communicator of the reception of the incoming call, a memory for storing at least one message for responding to said calling party, and means for transmitting said message to said calling party when said transmitter/receiver receives response information from
- 20 said incoming call communicator; and
- said incoming call communicator comprises a transmitter/receiver for transmitting and receiving information to and from said cellular mobile telephone body, means for notifying a user of said cellular mobile
- 25 telephone apparatus of the reception of an incoming call when said transmitter/receiver receives the notification of the reception of the incoming call from said cellular

This Sheet Has Been Replaced



mobile telephone body, and responding means for instructing said transmitter/receiver to transmit said response information to said cellular mobile telephone body when said user responds to said incoming call notifying means.

5 20. An apparatus according to claim 19, wherein said message storing memory stores a plurality of messages.

21. An apparatus according to claim 20, wherein said incoming call communicator further comprises means for selecting one from among a plurality of messages stored in
10 said message storing memory, and said responding means includes means for instructing said transmitter/receiver to transmit response information associated with a message selected by said selecting means to said cellular mobile telephone body.

15 22. An apparatus according to claim 21, wherein said incoming call communicator further comprises means for storing information associated with a message selected by said selecting means, and said responding means includes means for transmitting the information stored in said
20 storing means as said response information.

23. An apparatus according to claim 21, wherein said selecting means includes a plurality of response switches provided in correspondence to said messages manipulated by said user.

25 24. An apparatus according to claim 21, wherein said selecting means includes a plurality of state-holding switches provided in correspondence to said messages manipulated by said user.

This Sheet Has Been Replaced



* C L M S *

25. An apparatus according to claim 21, wherein said selecting means comprises:

means for specifying a desired one within said plurality of messages; and

5 a storage circuit for storing an address of said memory at which a message specified by said specifying means is stored.

26. An apparatus according to claim 25, wherein said responding means includes at least one response switch, and
10 said responding means also comprises means responsive to a manipulation on said response switch for reading said address stored in said storage circuit and for instructing said transmitter/receiver to transmit said address to said cellular mobile telephone body.

15 27. An apparatus according to claim 21, wherein said responding means comprises means for generating said response information, and means for instructing said transmitter/receiver to transmit said response information.

28. An apparatus according to claim 27, wherein said
20 cellular mobile telephone body further comprises means responsive to said transmitter/receiver receiving said response information from said incoming call communicator for analyzing said response information to read a message selected by said selecting means.

25 29. An apparatus according to claim 19, wherein said responding means includes means for detecting voice of said user.



This Sheet Has Been Replaced



30. An apparatus according to claim 19, wherein said incoming call communicator is incorporated in a device for displaying the time, said displaying device being mountable on a human body.

5 31. A response message transmitter in a cellular mobile telephone comprising:

in a radio base station or in a switching station, a memory for storing a plurality of messages for responding to a calling party, and means for transmitting a
10 selected message to the calling party based on address information for specifying a selection message transmitted from a cellular mobile telephone; and

in said cellular mobile telephone, means for selecting one from among said plurality of messages stored
15 in said memory, and means for transmitting said address information associated with a message selected by said selecting means to said radio base station or to said switching station.

32. A method of transmitting a response message in a
20 cellular mobile telephone apparatus, comprising the steps of:

storing a plurality of messages for responding to a calling party in a memory;

selecting a message from among said plurality of
25 messages;

transmitting the message selected at said selecting step to the calling party; and

This Sheet Has Been Replaced



* C L M S *

transmitting the message selected at said selecting step to said calling party in response to reception of an incoming call.

33. A method of transmitting a response message in a cellular mobile telephone apparatus comprising a cellular mobile telephone body and an incoming call communicator for communicating with said cellular mobile telephone body, comprising the steps of:

said cellular mobile telephone body storing at least one message for responding to a calling party in a memory;

said cellular mobile telephone body notifying, in response to an incoming call received from a calling party, said incoming call communicator of the reception of the incoming call

said incoming call communicator notifying a user of said cellular mobile telephone apparatus of the reception of the incoming call when said incoming call communicator receives the notification of the reception of the incoming call from said cellular mobile telephone body;

said incoming call communicator transmitting response information to said cellular mobile telephone body when said user responds to said notification of the reception of the incoming call; and

said cellular mobile telephone body transmitting said message to said calling party when said cellular mobile telephone body receives said response information from said incoming call communicator.

This Sheet Has Been Replaced



34. A method of transmitting a response message in a cellular mobile telephone comprising the steps of:

storing a plurality of messages for responding to a calling party in a memory provided in a radio base

5 station or in a switching station;

selecting, in a cellular mobile telephone, one from among said plurality of messages stored in said memory;

said cellular mobile telephone transmitting
10 address information associated with a message selected at said selecting step to said radio base station or to said switching station; and

said radio base station or said switching station transmitting said selected message to the calling party
15 based on the address information transmitted from said cellular mobile telephone.

35. A recording medium readable by a computer, said recording medium recording a program for executing a method of transmitting a response information in a cellular mobile
20 telephone apparatus, said method comprising the steps of:

storing a plurality of messages for responding to a calling party in a memory;

selecting one from among said plurality of messages;

25 transmitting a message selected by said selecting means to the calling party; and

transmitting the message selected by said selecting step to said calling party in response to an



incoming call.

36. A recording medium readable by a computer, said recording medium recording a program for executing a method of transmitting a response message in a cellular mobile
5 telephone apparatus comprising a cellular mobile telephone body and an incoming call communicator for communicating with said cellular mobile telephone body, comprising the steps of:

said cellular mobile telephone body storing at
10 least one message for responding to a calling party in a memory;

said cellular mobile telephone body notifying, in response to an incoming call received from a calling party, said incoming call communicator of the reception of the
15 incoming call;

said incoming call communicator notifying a user of said cellular mobile telephone apparatus of the reception of the incoming call when said incoming call communicator receives the notification of the reception of
20 the incoming call from said cellular mobile telephone body;

said incoming call communicator transmitting response information to said cellular mobile telephone body when said user responds to said notification of the reception of the incoming call; and

25 said cellular mobile telephone body transmitting said message to said calling party when said cellular mobile telephone body receives said response information from said incoming call communicator.

This Sheet Has Been Replaced



* C L M S *

37. A recording medium readable by a computer, said recording medium recording a program for executing a method of transmitting a response message in a cellular mobile telephone comprising the steps of:

5 storing a plurality of messages for responding to a calling party in a memory provided in a radio base station or in a switching station;

selecting, in a cellular mobile telephone, one from among said plurality of messages stored in said
10 memory;

said cellular mobile telephone transmitting address information associated with a message selected at said selecting step to said radio base station or to said switching station; and

15 said radio base station or said switching station transmitting said selected message to the calling party based on the address information transmitted from said cellular mobile telephone.

This Sheet Has Been Replaced



* C L M S *

THIS SHEET HAS BEEN
REPLACED

ABSTRACT OF THE DISCLOSURE

A cellular mobile telephone apparatus has circuits for generating messages, a storage circuit for storing messages, and transmitter/receiver circuit for transmitting a message. When the user of the cellular mobile telephone apparatus cannot immediately respond to an incoming call, a desired one of a plurality of previously generated and stored messages can be transmitted to a calling party through simple key manipulations or by other means.

This Sheet Has Been Replaced



FIG. 1







FIG. 2




3/11

FIG. 3A



4/11

FIG. 3B



This Sheet Has Been Replaced



This Sheet Has Been Replaced






FIG. 5A




FIG. 5B






FIG. 6A




FIG. 6B





FIG. 7A



This Sheet Has Been Replaced



FIG. 7B





FIG. 8



This Sheet Has Been Replaced



FIG. 9

This Sheet Has Been Replaced





FIG. 10





24 APR 1998

RESPONSE MESSAGE TRANSMITTER AND RESPONSE MESSAGE

TRANSMITTING METHOD IN CELLULAR MOBILE

TELEPHONE APPARATUS AND RECORDING

MEDIUM RECORDING PROGRAM FOR EXECUTING THE METHOD

BACKGROUND OF THE INVENTION

The present invention relates generally to a response message transmitter in a portable mobile radio communication apparatus such as a portable telephone apparatus, a cordless telephone apparatus, or the like, and more particularly to a response message transmitter in a cellular mobile telephone apparatus which is operable when the cellular mobile telephone apparatus receives an incoming call but the user cannot immediately answer a calling party, for example, because the user is driving a vehicle or the like, or because the user is in a place where the use of cellular mobile telephones and so on is restricted, or the like, to notify such a situation to the calling party.

With a currently used cellular mobile telephone apparatus, when an incoming call is received, although the user should respond to the call, the user is not always immediately ready to do so. Particularly, when the user is driving a vehicle or the like, the user cannot immediately respond to a call. Conventional cellular mobile telephone apparatus have a function of pending a call for coping with such a situation. This function is invoked by depressing a

THIS SHEET HAS BEEN
REPLACED

24 APR 1998

- 42 -

RESPONSE MESSAGE TRANSMITTER AND RESPONSE MESSAGE
TRANSMITTING METHOD IN CELLULAR MOBILE
TELEPHONE APPARATUS AND RECORDING
MEDIUM RECORDING PROGRAM FOR EXECUTING THE METHOD

ABSTRACT OF THE DISCLOSURE

A cellular mobile telephone apparatus has circuits for generating messages, a storage circuit for storing messages, and transmitter/receiver circuit for transmitting a message. When the user of the cellular mobile telephone apparatus cannot immediately respond to an incoming call, a desired one of a plurality of previously generated and stored messages can be transmitted to a calling party through simple key manipulations or by other means.

Figure 1

THIS SHEET HAS BEEN
REPLACED


This Sheet Has Been Replaced



24 APR 1998

-1-


FIG. 1



24 APR 1998

- 2 -


FIG. 2



24 APR 1998

- 3 -

FIG. 3A







FIG. 3B



24 APR 1998

- 5 -

FIG. 4




FIG. 5A




FIG. 5B




FIG. 6A





FIG. 6B



24 APR 1998

FIG. 7A






FIG. 7B



24 APR 1998

FIG. 8






FIG. 9





FIG. 10





6661 100 1 0

REPLACEMENT SHEET

mobile telephone body, and responding means for
said transmitter/receiver to transmit said response
information to said cellular mobile telephone body when
said user responds to said incoming call notifying means.

5 20. An apparatus according to claim 19, wherein said
message storing memory stores a plurality of messages.

21. An apparatus according to claim 20, wherein said
incoming call communicator further comprises means for
selecting one from among a plurality of messages stored in
10 said message storing memory, and said responding means
includes means for instructing said transmitter/receiver to
transmit response information associated with a message
selected by said selecting means to said cellular mobile
telephone body.

15 22. An apparatus according to claim 21, wherein said
incoming call communicator further comprises means for
storing information associated with a message selected by
said selecting means, and said responding means includes
means for transmitting the information stored in said
20 storing means as said response information.

23. An apparatus according to claim 21, wherein said
selecting means includes a plurality of response switches,
provided in correspondence to said messages, which are
manipulated by said user.

25 24. An apparatus according to claim 21, wherein said
selecting means includes a plurality of state-holding
switches, provided in correspondence to said messages, which
are manipulated by said user.

THIS SHEET HAS BEEN
REPLACED

9704675-9

1/10/99



0 1 007 1999

- 37 -

30. An apparatus according to claim 19, wherein said incoming call communicator is incorporated in a device for displaying the time, said displaying device being mountable on a human body.

5 31. A response message transmitter in a cellular mobile telephone comprising :

10 in a radio base station or in a switching station, a memory for storing a plurality of messages for responding to a calling party, and means for transmitting a selected message to the calling party based on address information specified by a selection message transmitted from a cellular mobile telephone; and

15 in said cellular mobile telephone, means for selecting one from among said plurality of messages stored in said memory, and means for transmitting said address information associated with a message selected by said selecting means to said radio base station or to said switching station.

20 32. A method of transmitting a response message in a cellular mobile telephone apparatus, comprising the steps of:

storing a plurality of messages for responding to a calling party in a memory;

selecting a message from among said plurality of messages; and

25 transmitting the message selected at said selecting step to said calling party in response to reception of an incoming call.

THIS SHEET HAS BEEN
REPLACED


This Sheet Has Been Replaced



1800

33. A method of transmitting a response message in a
- 5 cellular mobile telephone apparatus comprising a cellular
mobile telephone body and an incoming call communicator for
communicating with said cellular mobile telephone body,
comprising the steps of:
- 10 said cellular mobile telephone body storing at
least one message for responding to a calling party in a
memory;
- said cellular mobile telephone body notifying, in
response to an incoming call received from a calling party,
said incoming call communicator of the reception of the
- 15 incoming call
- said incoming call communicator notifying a user
of said cellular mobile telephone apparatus of the
reception of the incoming call when said incoming call
communicator receives the notification of the reception of
- 20 the incoming call from said cellular mobile telephone body;
- said incoming call communicator transmitting
response information to said cellular mobile telephone body
when said user responds to said notification of the
reception of the incoming call; and
- 25 said cellular mobile telephone body transmitting
said message to said calling party when said cellular
mobile telephone body receives said response information
from said incoming call communicator.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



01 OCT 1999

34. A method of transmitting a response message in a cellular mobile telephone comprising the steps of:

storing a plurality of messages for responding to a calling party in a memory provided in a radio base station or in a switching station;

selecting, in a cellular mobile telephone, one from among said plurality of messages stored in said memory;

said cellular mobile telephone transmitting address information associated with a message selected at said selecting step to said radio base station or to said switching station; and

said radio base station or said switching station transmitting said selected message to the calling party based on the address information transmitted from said cellular mobile telephone.

35. A recording medium readable by a computer, said recording medium recording a program for executing a method of transmitting a response information in a cellular mobile telephone apparatus, said method comprising the steps of :

storing a plurality of messages for responding to a calling party in a memory;

selecting one from among said plurality of messages;

and

transmitting the message selected by said selecting step to said calling party in response to an incoming call.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



0 1 001 003

- 40 -

36. A recording medium readable by a computer, said
recording medium recording a program for executing a method
of transmitting a response message in a cellular mobile
5 telephone apparatus comprising a cellular mobile telephone
body and an incoming call communicator for communicating
with said cellular mobile telephone body, comprising the
steps of:

said cellular mobile telephone body storing at
10 least one message for responding to a calling party in a
memory;

said cellular mobile telephone body notifying, in
response to an incoming call received from a calling party,
said incoming call communicator of the reception of the
15 incoming call;

said incoming call communicator notifying a user
of said cellular mobile telephone apparatus of the
reception of the incoming call when said incoming call
communicator receives the notification of the reception of
20 the incoming call from said cellular mobile telephone body;

said incoming call communicator transmitting
response information to said cellular mobile telephone body
when said user responds to said notification of the
reception of the incoming call; and

25 said cellular mobile telephone body transmitting
said message to said calling party when said cellular
mobile telephone body receives said response information
from said incoming call communicator.

This Sheet Has Been Replaced

THIS SHEET HAS BEEN
REPLACED


27 SEP 2001

CELLULAR MOBILE TELEPHONE APPARATUS

BACKGROUND OF THE INVENTION

The present invention relates generally to a response message transmitter in a portable mobile radio communication apparatus such as a portable telephone apparatus, a cordless telephone apparatus, or the like, and more particularly to a response message transmitter in a cellular mobile telephone apparatus, which is operable to notify the calling party when the cellular mobile telephone apparatus receives an incoming call but the user cannot immediately answer a calling party, for example, because the user is driving a vehicle or the like, or because the user is in a place where the use of cellular mobile telephones and so on is restricted, or the like.

With a currently used a cellular mobile telephone apparatus, when an incoming call is received, although the user should respond to the call, the user is not always immediately ready to do so. Particularly, when the user is driving a vehicle or the like, the user cannot immediately respond to a call. Conventional cellular mobile telephone apparatus have a special function of answering a call so as to cope with such a situation. This function is invoked by depressing a pending button, when the user cannot immediately accept a call, to notify a calling party through a base station that the user



- 2 -

cannot immediately respond to the call although the telephone line connection has been established therebetween, to reduce the volume of the telephone ring, and to permit the user to initiate a communication when the user is ready to do so. Such a cellular mobile telephone apparatus is disclosed in JP-A-8-163208.

However, such a simple response message function is not sufficient to notify a calling party of specific reasons for which the user is answering a call. More specifically, the calling party cannot know whether the user cannot respond to a call because he or she is now in a place where the use of cellular mobile telephone apparatus is restricted, and is moving from that place; or because the user is now busy with other business; or because the user is driving a vehicle or the like so that he/she cannot respond to a call before he/she stops driving. It can therefore be thought that the pending state extends over such long time period that the calling party gives up the call, as the case may be.

With the conventional cellular mobile telephone apparatus as described above, the user suffers from an inconvenience when an incoming call is received but the user cannot immediately respond to the call because the conventional cellular mobile telephone apparatus does not have any means for notifying a calling party of the current situation of the user. In

27 SEP 2001

- 3 -

addition, the calling party cannot know the current situation which the user of the destination cellular mobile telephone apparatus is experiencing.

According to certain data, traffic accidents related to the cellular mobile telephone apparatus during the operation of a vehicle happen more while drivers are looking for their cellular mobile telephone apparatus for placing a call or for responding to an incoming call than while they are actually communicating. The conventional cellular mobile telephone apparatus have not at all been designed in consideration of improvements, particularly, in the usability addressed to such a situation.

Furthermore, it has been found from exemplary usage that when the users carry their cellular mobile telephone apparatus with them, most of the users keep it in a bag or the like. Thus, even though the user is in a situation in which he/she cannot immediately respond to an incoming call, the user must once take the cellular mobile telephone apparatus from his/her bag, each time an incoming call is received in such situation, for invoking the answering operation. It can therefore be seen that the conventional cellular mobile telephone apparatus have not been designed in any consideration of improvements in the usability addressed to such a situation.

SUMMARY OF THE INVENTION

The present invention has been made in view of


The cellular mobile telephone apparatus further comprises a speech coding encoder/decoder circuit for use in a digital telephone system which is utilized to convert an analog voice signal to a digital voice signal so that voice can be detected or a voice pattern can be recognized.

The present invention also provides a cellular mobile telephone apparatus comprising a cellular mobile telephone body and an incoming call communicator for notifying the reception of an incoming call, wherein:

the cellular mobile telephone body includes transmitting/receiving means for transmitting and receiving information to and from the incoming call communicator through a radio channel, incoming call responding means for responding to an incoming call from a calling party, means for storing a message to the calling party, and means for transmitting the message to the calling party; and

the incoming call communicator includes incoming call responding means for responding to an incoming call received from a calling party, and transmitting/receiving means for transmitting and receiving information to and from the cellular mobile telephone body through a radio channel,

wherein incoming call information is transmitted from cellular mobile telephone body to the incoming call communicator when an incoming call is received, and if the user cannot respond immediately to the incoming call from the calling party, response information is transmitted




from the incoming call communicator to the cellular mobile telephone body by the action of the incoming call responding means, so that the cellular mobile telephone body can transmit the previously stored message to the
5 calling party.

The present invention further provides a cellular mobile telephone apparatus comprising a cellular mobile telephone body and an incoming call communicator for notifying the reception of an incoming call, wherein:

10 the cellular mobile telephone body includes transmitting/receiving means for transmitting and receiving information to and from the incoming call communicator through a radio channel, incoming call responding means for responding to an incoming call from a calling party, means
15 for storing a plurality of messages to the calling party, means for selecting a message to the calling party, and means for transmitting a selected message to the calling party; and

the incoming call communicator includes incoming
20 call responding means for responding to an incoming call from a calling party, means for selecting a message to the calling party, and transmitting/receiving means for transmitting and receiving information to and from the cellular mobile telephone body through a radio channel,

25 wherein incoming call information is transmitted from the cellular mobile telephone body to the incoming call communicator when an incoming call is received, and if the user cannot respond immediately to the call received from the calling party,




response information is transmitted from the incoming call communicator to the cellular mobile telephone body by the action of the incoming call responding means, so that the cellular mobile telephone body can transmit a previously stored message to the calling party, selected by a user, to the calling party.

The incoming call communicator further includes a plurality of response switches corresponding to the stored messages, as the incoming call responding means, wherein the user may select a message to the calling party with the plurality of response switches and respond to the calling party by transmitting the selected message.

The incoming call communication is designed to previously select one of the plurality of messages and automatically transmit the selected message in response to the incoming call.

The incoming call communicator further includes a change-over switch as the means for selecting a message to the calling party, and a response switch as the incoming call responding means, wherein the user may select a message to the calling party with the change-over switch and respond to the calling party with the response switch.

The incoming call communicator further includes means for detecting voice while the reception of an incoming call is being notified, wherein response information can be sent to the cellular mobile telephone body by detecting voice of the user during the notification of the incoming call reception.



The incoming call communicator further includes means for recognizing a voice pattern, wherein the recognizing means detects a voice pattern while the reception of an incoming call is being notified, such that response information is changed in accordance with the voice pattern to select one of the messages to be sent to the calling party stored in the cellular mobile telephone body, whereby the calling party can be notified with the selected message.

The incoming call communicator further includes means for displaying time and date, and a holding strap with which the user may hold the incoming call communicator on his/her body such as an arm.

BRIEF DESCRIPTION OF THE DRAWINGS


Fig. 1 is a block diagram illustrating an embodiment of a cellular mobile telephone apparatus according to the present invention;

Fig. 2 is a plan view depicting an outer appearance of the cellular mobile telephone apparatus illustrated in Fig. 1;

Fig. 3A is a flow chart illustrating an embodiment of the operation of the cellular mobile telephone apparatus according to the present invention;

Fig. 3B is a flow chart illustrating a partially modified example of the operation illustrated in Fig. 3A;


Fig. 4 is a flow chart illustrating another embodiment of the present invention;



2 depicts an outer appearance of the cellular mobile telephone apparatus illustrated in Fig. 1.

As illustrated in Fig. 1, a radio communication signal sent from a base station (not shown) is inputted to
5 a radio transmitter/receiver circuit 4 through an antenna 3 in a cellular mobile telephone apparatus 1. The received radio communication signal is converted to an intermediate frequency signal in the radio transmitter/receiver circuit 4. Then, the received intermediate frequency signal is
10 demodulated to a digital signal by a digital modulator/demodulator circuit 5, and the demodulated digital signal is decoded by an error correcting encoder/decoder circuit 6. Digital signals decoded by and outputted from the error
15 correcting encoder/decoder circuit 6 include a digital communication signal and a digital control signal, and the digital control signal is supplied to and identified by a control circuit 10. The digital communication signal, in turn, is decoded by a speech coding encoder/decoder circuit 7 to restore an analog communication signal which is
20 subsequently outputted from an audio output device 8.

On the other hand, outgoing speech is first transduced to a transmission signal by a transducer 9, and the transmission signal is then converted to a digital transmission signal by the speech coding encoder/decoder
25 circuit 7. The digital transmission signal, after being encoded in the error correcting encoder/decoder circuit 6 together with a digital control signal generated in the control



circuit 10, is inputted to the digital modulator/demodulator circuit 5 and modulated to an orthogonally modulated signal therein. The modulated signal is transmitted to the base station from the antenna 3 after being converted to a high frequency signal by the radio transmitter/receiver circuit 4 for transmission through a predetermined radio channel.

The control circuit 10, which employs a microcomputer as a main control unit, has means for generating a message to a calling party, means for storing such messages in a memory, and means for transmitting a message to a calling party, in addition to functions for controlling respective components of the cellular mobile telephone apparatus 1.

Electrical power required by the cellular mobile telephone apparatus 1 is generated by a battery power supply 18 and supplied to respective components through a power supply switch 19.

Next, the operation of the cellular mobile telephone apparatus 1 according to this embodiment of the present invention will be described with reference again to Figs. 1 and 2 as well as to Fig. 3 illustrating an operation flow chart.

When it is assumed that the user cannot immediately respond to an incoming call because the user is driving a vehicle or the like, the cellular mobile telephone apparatus 1 may have previously created a message to cope with such a situation. More specifically, an

REPLACEMENT SHEET

27 SEP 2001


analog voice signal from the transducer 9 is converted to serial digital data by the speech coding encoder/decoder circuit 7. The serial digital data is then converted to a parallel signal by the error correcting encoder/decoder circuit 6 and stored in a storage circuit 12 through the control circuit 10.

It should be noted that the storage circuit 12 is not provided exclusively for storing messages but is also shared by the control circuit 10 for its control purposes.

Alternatively, messages stored in the storage circuit 12 may be previously written into a read only memory (ROM) such that the user need not register messages.

The operation flow of the cellular mobile telephone apparatus 1 when responding to an incoming call will be described below with reference to Fig. 3A.

The cellular mobile telephone apparatus 1, when it is powered on (step 30), enters a standby state and remains in this state until it receives a call reception signal destined thereto (step 31). When the cellular mobile telephone apparatus 1 receives the call reception signal (step 32), the control circuit 10 recognizes the reception of an incoming call and generally lets the user know the reception of an incoming call for a predetermined time period with incoming call notification in the form of an alarm generated by a sound-producing input device 11 or vibrations generated by a vibrator 15 (step 33). Simultaneously with this operation, the control circuit 10 monitors whether or not the user manipulates a key on the cellular mobile telephone



27 SEP 2001

- 14 -

apparatus 1 in response to the incoming call notification or whether or not a state-holding key has been previously depressed (step 34).

In this event, if the user does not respond to the incoming call notification in spite of the incoming call notification which has been provided to the user for the predetermined time period (step 35), the control circuit 10 transmits an absence message for notifying the calling party that the user is now absent (step 36), and initiates a recording operation when the calling party wants to leave some message (step 37). Then, the communication channel is cut (step 39) and the cellular mobile telephone apparatus 1 again enters the standby state (step 31) when the calling party cuts the call or an available recording time expires, so as to terminate the recording (step 38).

The predetermined time period provided at step 35 is actually a time period required for the control circuit 10 to notify the user of the reception of an incoming call a number of times which has been previously registered in the control circuit 10 to generate the alarm from the input device 11 or vibrations from the vibrator 15 the registered number of times.

If the user responds by manipulating a key while the reception of the incoming call is being notified to the user (step 34) or if one of the state-holding keys has been previously depressed, an operation specified by an associated key is performed (steps 40 - 45). Keys used at

message "Since I am now driving a car, I will call you later when I stop the car" may be registered in a function key 1 (F1); a message "Since I am now in a cabin of a train, please hold on for a while until I go to the deck" may be registered in a function key 2 (F2); and a message "Since I am now in conference, please call me again in about one hour" may be registered in a function key 3 (F3).

The control circuit 10 determines which of the function keys 16 has been depressed, and reads a message corresponding to the depressed function key from the storage circuit 12 to transmit the read message (steps 43-45). After the message is transmitted, the cellular mobile telephone apparatus 1 initiates an operation for recording a message, which is similar to the processing performed after the absence message is transmitted, since the calling party may want to leave a message (step 37). When the calling party cuts the call after he/she has recorded the message or when a recording available time expires, the communication channel is cut and the cellular mobile telephone apparatus 1 again enters the standby state (steps 38, 39, 31).

Next, functional operations performed when a message is transmitted will be described with reference to the blocks illustrated in Fig. 1.

The control circuit 10 of the cellular mobile telephone apparatus 1 reads a message to a calling party, previously stored by the user, from the storage circuit 12,

REPLACEMENT SHEET

27 SEP 2001

Since the contents of an actual message may be an extremely simple sentence as the aforementioned examples and take approximately five seconds at most, three messages will require a storage capacity corresponding to

5 approximately 15 seconds. The storage circuit 12 currently used in the cellular mobile telephone apparatus includes an IC memory for message which generally has a capacity corresponding to approximately 30 seconds in time.

Therefore, even if a 15-second portion of the storage

10 circuit 12 is reserved for the messages, the remaining 15-

second portion may be used to store a message from a calling party.

While in the foregoing embodiment, the three function keys 16 are illustrated in the same size, they

15 need not necessarily have the same size. Rather, in place of the function keys 16, the cellular mobile telephone apparatus may be provided with such function keys that enable the user to recognize their special functionalities only by touching them, without requiring visual


20 confirmation, or with touch switches, which are capable of immediately functioning in response to a touch thereto.

These alternatives eliminating the need of visual confirmation are particularly suitable when the user is driving a vehicle or the like. Furthermore, a voice

25 recognition function as illustrated in Fig. 3B may be added to improve its original usefulness. More specifically,

Fig. 3B illustrates a flow chart which has additional steps

51 - 54 other than those in the operation flow of Fig. 3A,



27 SEP 2001

and includes all the steps appearing in Fig. 3A.

Referring specifically to Fig. 3B, voice of the user inputted to the transducer 9 of the cellular mobile telephone apparatus 1 illustrated in Fig. 1 is converted to serial digital data by the speech coding encoder/decoder circuit 7, and the serial digital data is again converted to a parallel signal by the error correcting encoder/decoder circuit 6. The control circuit 10, upon sensing the inputted digital voice signal (step 51), performs a Fourier transform on the digital voice signal to extract a spectrum component of the voice (step 52). Then, if the extracted voice signal is larger than a previously detected noise component, the voice signal is recognized as voice (step 53), and a message is transmitted to notify a calling party that the user is driving a car, or the like (step 54).


In the embodiment illustrated in Fig. 3A, when the user is notified of the reception of an incoming call at step 33, the user finds and depresses a function key for generating an appropriate response message, or it has been previously depressed to transmit it to a calling party, whereas Fig. 4 shows another embodiment employing state-holding function keys F1 - F3 as the respective function keys 16. Such state-holding function keys may be slide switches.

According to the embodiment illustrated in Fig. 4, a message to be transmitted when an incoming call is received has been previously set by depressing or sliding a

corresponding function key. Thereafter, when an incoming call is received, the reception of the incoming call is notified (steps 32, 33), and the states of the function keys F1 - F3 are immediately checked (steps 65 - 67). If
5 any of the keys is set ON, the transmission of a message corresponding to the key is started (steps 43 - 45). The step 33 may be deleted. In that case, the previously set message is transmitted without notifying the reception of the incoming call. The notification of the incoming call
10 reception is continued even while the message is being transmitted (step 68), and if depression of any key is sensed during this period (step 34), the flow proceeds to step 46. The rest of the operation steps in Fig. 4 are identical to those in Fig. 3A, so that such steps are
15 designated by the same reference numerals, and explanation thereof is omitted.

Fig. 5A is a flow chart illustrating another embodiment of the present invention. In this embodiment, a message is previously selected from among a plurality of
20 messages such that the previously selected message is transmitted in response to depression of a single function key. As is appreciated, only one function key is provided in this embodiment.

Generally, messages required when an incoming
25 call is received may be classified into two: an absence message which may be transmitted when the user is absent, and a message for notifying a calling party of a situation which the user is currently experiencing. While a



plurality of messages must be prepared for notifying a calling party of a situation which the user is currently experiencing because a variety of possible situations may exist, only one message most appropriate for indicating the situation at that time is transmitted to the calling party.

In Fig. 5A, the same functional steps as those in Fig. 3A are designated by the same reference numerals and repetitive explanation thereof is omitted.

Referring specifically to Fig. 5A, when a message must be changed, the user selects a message indicative of a situation which the user himself/herself is currently experiencing, using the key input device 13, while the cellular mobile telephone apparatus 1 remains in the standby state (steps 56, 57). Specifically, a plurality of messages are stored at assigned addresses in the storage circuit 12. The storage circuit 12 also comprises a pointer memory 12p for storing the address of a message to be transmitted when the function key 16 is depressed. As the user specifies a number from the key input device 13 for specifying an associated message, the address of the message is stored in the pointer memory 12p. Alternatively, a switch for selecting a message may be used in place of the pointer memory 12p.

In this way, when the function key 16 is simply depressed (steps 34, 58) at the time an incoming call is received (step 33), a message specified by the address previously stored in the pointer memory 12p at step 57 is transmitted to a calling party (step 59). Thus, the user

REPLACEMENT SHEET


27 SEP 2001

is not required to look for the function key 16 associated with a necessary message in a busy situation, at the time an incoming call is received, and moreover, a large sized function key 16 may be provided on the cellular mobile telephone apparatus 1, thus resulting in an improvement in the operability of the cellular mobile telephone apparatus 1.

While in the embodiment illustrated in Fig. 5A, a message is transmitted by depressing the function key 16 when the reception of an incoming call is notified, the operation flow may directly jump to step 59 to transmit a previously selected message after an incoming call is sensed at step 32 without notifying the reception of the incoming call.

Further, the operation functions at steps 51-54 as illustrated in Fig. 3B may be added to the operation procedure illustrated in Fig. 5A so that a response message may be transmitted in response to detection or recognition of voice pronounced by the user in place of manipulating the function key 16. The voice recognition may be implemented by determining whether or not detected voice matches a predetermined signal pattern, other than a test for examining whether a signal level of detected voice is equal to or higher than a predetermined value.

Fig. 5B is a flow chart showing an example in which the step 36 in Fig. 5A is incorporated into the step 59 in Fig. 5A. In that case, the step 57 in Fig. 5A can select also the absence message.



Since such voice recognition is performed during the notification of incoming call reception, which is not in a communication state, the speech coding encoder/decoder circuit 7 and the error correcting encoder/decoder circuit 6 may be commonly used for the voice detection or the voice recognition under the control of the control circuit 10.

Next, another embodiment of the present invention will be described with reference to Figs. 6A - 9.

In Figs. 6A, 6B, 7A, and 7B, a cellular mobile telephone apparatus comprises a main body constituting a cellular mobile telephone 1 and an incoming call communicator 2. The cellular mobile telephone 1 comprises an incoming call notification transmitter/receiver circuit 61 for communicating with the incoming call communicator 2, and an incoming call notification transmitting/receiving antenna 62, in addition to the configuration and functions of the cellular mobile telephone apparatus described in the aforementioned embodiment.

The incoming call communicator 2 comprises an incoming call notification transmitter/receiver circuit 71 for communicating with the cellular mobile telephone 1; an incoming call notification transmitting/receiving antenna 72; an incoming call notification control circuit 23 for controlling respective components of the incoming call communicator 2; an incoming call notification storage circuit 24 for storing response information and so on; a key input device 73 for inputting information; a function

REPLACEMENT SHEET

27 SEP 2001

key 16; a vibrator 25 for notifying the reception of an incoming call; an LED display 26 for displaying information from the cellular mobile telephone 1; and a display unit 74. The incoming call communicator 2 is powered by a battery 28 which supplies electrical power to the respective components through a power supply switch 29.

The cellular mobile telephone 1 and the incoming call communicator 2 mutually transmit and receive information through radio transmission. Signal formats and a transmission scheme used for such radio transmission are fully disclosed in Japanese Patent Application No. 147007/1996 filed June 10, 1996 and corresponding U.S. Patent Application Serial No. 08/872,138, the contents of which are hereby incorporated by reference. The contents of the applications will be outlined below. Information for radio transmission is defined in accordance with an information transmission format composed of a sequential bit train including a preamble, synchronization information, identification information, and information to be transmitted. This sequential bit train is FM-modulated at a carrier frequency of 300 MHz and transmitted at a transmission rate of 512 bps.

For information transmission, the information is transmitted in units of 8 bits, 2 bits of which are assigned to synchronization bits set at "1" and "0." The synchronization bits are used to resynchronize the information every 8 bits when it is demodulated. With the synchronization bits, a total of approximately 6% of

REPLACEMENT SHEET

27 SEP 2001

27 SEP 2001

transmission rate error can be tolerated on the transmission side and on the reception side. Thus, effective information within each 8-bit transmitted information is 6 bits.

5 Fig. 8 illustrates an operation flow of the main body of the cellular mobile telephone apparatus depicted in Fig. 7A; in which steps having the same functions as those in Fig. 5 are designated by the same reference numerals.

In the cellular mobile telephone apparatus of this embodiment, the notification of the reception of an incoming call is not only made in the main body 1 but also simultaneously transmitted to the incoming call communicator 2 through a radio signal (step 33'). Then, it is monitored whether or not any key on the main body 1 is manipulated (step 34) or whether or not a response is transmitted from the incoming call communicator 2 (step 80) while the reception of the incoming call is being notified.

In this event, if a key on the cellular mobile telephone body 1 is manipulated, similar processing to the operation in the foregoing embodiment illustrated in Fig. 3A, 3B, 4, or 5 is performed (at step 58 and subsequent steps branched from step 34 through a "yes" path). On the other hand, if a response is transmitted from the incoming call communicator 2 (step 80), the contents of the response information are analyzed (step 81) to select a message to be transmitted (step 82). Operations performed subsequently are similar to the processing performed when a function key

27 SEP 2001

similar messages are stored in each cellular mobile telephone apparatus.

To eliminate this irrationality, a required number of fixed-style messages may be prepared as possible messages to be transmitted to a calling party, and previously stored in a radio base station or in a switching station 90 as a database 91, as illustrated in Fig. 10. The cellular mobile telephone apparatus, in turn, may store an address code for reading a desired message in a pointer memory 12p of a storage circuit 12, such that the user of the cellular mobile telephone apparatus, when he/she wants to transmit a message to a calling party, sends the address code associated with the message stored as the database 91 to the radio base station or to the switching station, in place of a message stored in the storage circuit 12 of the cellular mobile telephone apparatus as shown in the aforementioned embodiments. The radio base station or the switching station analyzes the message code to transmit the specified message from the database 91 to the calling party.

Since the configuration described above eliminates the need to store messages in the storage circuit of each cellular mobile telephone apparatus, the storage circuit of the cellular mobile telephone apparatus can be reduced in size.

While the foregoing embodiments of the present invention have been described in connection with a mobile station of a digital car telephone system, the present

27 SEP 2001

invention should not be necessarily limited to this particular scheme, but encompasses any other configurations conceivable for achieving the object of the present invention. Furthermore, the appearances, configurations, circuits, means, and so on of the apparatus described in the embodiments are not intended to limit the present invention.

The cellular mobile telephone apparatus of the present invention enables the user to immediately notify a calling party of his/her current situation, even if the user cannot immediately answer a call. Even when the user of the cellular mobile telephone apparatus is driving a vehicle or the like, the user can make an appropriate response by notifying a calling party of the current situation without interfering with the driving.

Also, even in a place where the use of the cellular mobile telephone apparatus is restricted (restrictions not due to the influence of electromagnetic waves but due to manners of using the cellular mobile telephone apparatus), the user can make an appropriate response by notifying a calling party of the user's situation, without annoying other people around the user.

CLAIMS:

1. A cellular mobile telephone apparatus having a response message transmitter, comprising :

a memory for storing a plurality of previously written message data for responding to an incoming call from a calling party;

a selector for selecting one of said plurality of messages according to a responding user's circumstance at the time of receiving the incoming call from the calling party, regardless of the identity of the calling party;

a transmitter for transmitting the message selected by said selector to the calling party; and

a controller for controlling a response to an incoming call connected to said transmitter and operable when an incoming call is received, to instruct said transmitter to transmit the message selected by said selection to the calling party,

wherein said selector has a switch having a plurality of positions corresponding to responses according to the user's circumstances at the time of receiving the incoming call, said plurality of previously written message data include response messages corresponding to said user's circumstances, and each of said positions of said switch is assigned to corresponding one of said response messages included in said written message data.

2. A cellular mobile telephone apparatus according to claim 1, wherein said plurality of messages include a message notifying that the user of said apparatus is driving a vehicle.

3. A cellular mobile telephone apparatus according to claim 1, wherein said selector includes a plurality of keys provided in correspondence to the respective ones of said plurality of messages.

4. A cellular mobile telephone apparatus according to claim 3, wherein said plurality of keys include a key corresponding to a message for notifying that the user of said



27 SEP 2001

apparatus is driving a vehicle, said key being formed to be distinguishable from other keys by a tactile sense on said key.

5. A cellular mobile telephone apparatus according to claim 4, wherein said key corresponding to the message for notifying that the user of said apparatus is driving a vehicle comprises a touch switch.
6. A cellular mobile telephone apparatus according to claim 1, wherein said selector includes a state-holding switch for selecting one of said plurality of messages.
7. A cellular mobile telephone apparatus according to claim 6, wherein said selector previously selects a desired one from among said plurality of messages before said incoming call is received.
8. A cellular mobile telephone apparatus according to claim 7, wherein said controller includes a key to be operated in response to the incoming call.
9. A cellular mobile telephone apparatus according to claim 1, wherein said selector includes previously-selected message selector for previously selecting a message before said incoming call is received.
10. A cellular mobile telephone apparatus according to claim 9, wherein said selector includes :
message specifier for specifying a desired one from among said plurality of messages; and
a pointer memory for storing an address of said memory at which a message specified by said specifier is stored.
11. A cellular mobile telephone apparatus according to claim 10, wherein said controller includes reader being responsive to said incoming call for reading said specified



message based on said address stored in said pointer memory and for instructing said transmitter to transmit said specified message.

12. A cellular mobile telephone apparatus according to claim 9, wherein said selector includes a switch for selecting one from among said plurality of messages.

13. A cellular mobile telephone apparatus according to claim 1, further comprising message generator for generating at least one of said plurality of messages.

14. A cellular mobile telephone apparatus according to claim 13, wherein said message generator includes :

an audio encoder circuit for converting a voice signal inputted from a transducer to a digital signal; and

digital signal memory for storing the digital signal converted by said audio encoder circuit in said memory.

15. A cellular mobile telephone apparatus according to claim 1, wherein said controller includes voice detector for detecting voice of the user.

16. A cellular mobile telephone apparatus having a response message transmitter, comprising :

a memory for storing a plurality of audio messages for responding to an incoming call from a calling party;

means for selecting one of said plurality of messages according to a responding user's circumstance at the time of receiving the incoming call from the calling party, regardless of the identity of the calling party;

means for transmitting the message selected by said selecting means to the calling party; and

incoming call responding means operable when an incoming call is received to instruct said transmitting means to transmit the message selected by said selecting means to the calling party;



27 SEP 2001

wherein said incoming call responding means includes means for detecting voice of the user; and

wherein said voice detecting means includes :

means for transducing said voice of the user to an electrical signal;

means for extracting a predetermined voice spectrum component from a voice signal fetched by said transducing means; and

means for operating said transmitting means when the component extracted by said extracting means is higher than a predetermined noise level.

17. A cellular mobile telephone apparatus according to claim 15, wherein said voice detector includes voice pattern recognizer for recognizing a pattern of voice of said user.

18. A cellular mobile telephone apparatus according to claim 1, further comprising disconnecter for cutting a communication channel for said apparatus after said transmitting means transmits said selected message.

19. A cellular mobile telephone apparatus having a response message transmitter comprising a cellular mobile telephone body and an incoming call communicator which communicates with said cellular mobile telephone body, wherein :

said cellular mobile telephone body comprises a transmitter/receiver for transmitting and receiving information to and from said incoming call communicator, means responsive to an incoming call received from a calling party for instructing said transmitter/receiver to notify said incoming call communicator of the reception of the incoming call, a memory for storing at least one message for responding to said calling party, and means for transmitting said message to said calling party when said transmitter/receiver receives response information designating said message to be transmitted from said incoming call communicator; and

said incoming call communicator comprises a transmitter/receiver for transmitting and receiving information to and from said cellular mobile telephone body, means for notifying a user of said cellular mobile telephone apparatus of the reception of an incoming



* C L H S *

27 11 2001

call when said transmitter/receiver of the incoming call communicator receives the notification of the reception of the incoming call from said cellular mobile telephone body, and responding means for instructing said transmitter/receiver of the incoming call communicator to transmit said response information to said cellular mobile telephone body when said user responds to said incoming call notifying means.

20. A cellular mobile telephone apparatus according to claim 19, wherein said message storing memory stores a plurality of messages.

21. A cellular mobile telephone apparatus according to claim 20, wherein said incoming call communicator further comprises means for selecting one from among a plurality of messages stored in said message storing memory, and said responding means includes means for instructing said transmitter/receiver of the incoming call communicator to transmit response information associated with a message selected by said selecting means to said cellular mobile telephone body.

22. A cellular mobile telephone apparatus having a response message transmitter, comprising :

a cellular mobile telephone body and an incoming call communicator which communicates with said cellular mobile telephone body, wherein :

said cellular mobile telephone body comprises a transmitter/receiver for transmitting and receiving information to and from said incoming call communicator, means responsive to an incoming call received from a calling party for instructing said transmitter/receiver to notify said incoming call communicator of the reception of the incoming call, a memory for storing at least one message for responding to said calling party, and means for transmitting said message to said calling party when said transmitter/receiver receives response information designating said message to be transmitted from said incoming call communicator;

said incoming call communicator comprises a transmitter/receiver for transmitting and receiving information to and from said cellular mobile telephone body,



27 SEP 2001

means for notifying a user of said cellular mobile telephone apparatus of the reception of an incoming call when said transmitter/receiver of the incoming call communicator receives the notification of the reception of the incoming call from said cellular mobile telephone body, and responding means for instructing said transmitter/receiver of the incoming call communicator to transmit said response information to said cellular mobile telephone body when said user responds to said incoming call notifying means;

said message storing memory stores a plurality of messages;

said incoming call communicator further comprises means for selecting one from among the plurality of messages stored in said message storing memory, said responding means includes means for instructing said transmitter/receiver of the incoming call communicator to transmit response information associated with a message selected by said selecting means to said cellular mobile telephone body; and

wherein said incoming call communicator further comprises means for storing information associated with the message selected by said selecting means;

and said responding means includes means for transmitting the information stored in said storing means as said response information.

23. A cellular mobile telephone apparatus according to claim 21, wherein said selecting means includes a plurality of response switches provided in correspondence to said messages manipulated by said user.

24. A cellular mobile telephone apparatus according to claim 21, wherein said selecting means includes a plurality of state-holding switches provided in correspondence to said messages manipulated by said user.

25. A cellular mobile telephone apparatus according to claim 21, wherein said selecting means comprises :

means for specifying a desired one within said plurality of messages; and

a storage circuit for storing an address of said memory at which a message specified by said specifying means is stored.



27 SEP 2001

37

26. A cellular mobile telephone apparatus according to claim 25, wherein said responding means includes at least one response switch, and said responding means also comprises means responsive to a manipulation on said response switch for reading said address stored in said storage circuit and for instructing said transmitter/receiver of the incoming call communicator to transmit said address to said cellular mobile telephone body.

27. A cellular mobile telephone apparatus according to claim 21, wherein said responding means comprises means for generating said response information, and means for instructing said transmitter/receiver of the incoming call communicator to transmit said response information.

28. A cellular mobile telephone apparatus according to claim 27, wherein said cellular mobile telephone body further comprises means responsive to said transmitter/receiver of the cellular mobile telephone body receiving said response information from said incoming call communicator for analyzing said response information to read a message selected by said selecting means.

29. A cellular mobile telephone apparatus according to claim 19, wherein said responding means includes means for detecting voice of said user.

30. A cellular mobile telephone apparatus according to claim 19, wherein said incoming call communicator is incorporated in a device for displaying the time, said displaying device being mountable on a human body.

31. A cellular mobile telephone apparatus having a response message transmitter comprising :

in a radio base station or in a switching station, a memory for storing a plurality of audio messages for responding to an incoming call from a calling party, and means for transmitting a selected message to the calling party based on address information for specifying a selection message transmitted from the cellular mobile telephone; and



27 SEP 2001

in said cellular mobile telephone, means for selecting one from among said plurality of messages stored in said memory according to a responding user's circumstances at the time of receiving the incoming call from the calling party, regardless of the identity of the calling party, and means for transmitting said address information associated with the message selected by said selecting means to said radio base station or to said switching station.

32. A method of transmitting a response message in a cellular mobile telephone apparatus, comprising the steps of :

storing a plurality of audio messages for responding to a call from a calling party in a memory;

selecting a message from among said plurality of messages according to a responding user's circumstances at the time of receiving the incoming call from the calling party, regardless of the identity of the calling party; and

transmitting the message selected at said selecting step to said calling party in response to reception of the incoming call.

33. A cellular mobile telephone apparatus according to claim 1, wherein said response message is audio message, and said read-only memory stores a plurality of previously written audio message data.


34. A method of transmitting a response message in a cellular mobile telephone apparatus, comprising the steps of :

storing a plurality of audio messages for responding to a call from a calling party in a memory;

assigning a message to each position of selector switch so as to correspond responses according to the user's.

35. A recording medium readable by a computer, said recording medium recording a program for executing a method of transmitting a response information in a cellular mobile telephone apparatus, said method comprising the steps of :





storing a plurality of audio messages for responding to an incoming call from a calling party in a memory;

selecting one from among said plurality of messages according to a responding user's circumstance at the time of receiving the incoming call from the calling party, regardless of the identity of the calling party; and

transmitting the message selected by said selecting step to said calling party in response to the incoming call.

36. A recording medium readable by a computer, said recording medium recording a program for executing a method of transmitting a response message in a cellular mobile telephone apparatus comprising a cellular mobile telephone body and an incoming call communicator for communicating with said cellular mobile telephone body, comprising the steps of:


said cellular mobile telephone body storing at least one message for responding to a calling party in a memory;

said cellular mobile telephone body notifying, in response to an incoming call received from a calling party, said incoming call communicator of the reception of the incoming call;

said incoming call communicator notifying a user of said cellular mobile telephone apparatus of the reception of the incoming call when said incoming call communicator receives the notification of the reception of the incoming call from said cellular mobile telephone body;

said incoming call communicator transmitting response information designating said message to be transmitted to said cellular mobile telephone body when said user responds to said notification of the reception of the incoming call; and

said cellular mobile telephone body transmitting said message to said calling party when said cellular mobile telephone body receives said response information from said incoming call communicator.



27 SEP 2001

37. A recording medium readable by a computer, said recording medium recording a program for executing a method of transmitting a response message in a cellular mobile telephone comprising the steps of:

storing a plurality of audio messages for responding to an incoming call from a calling party in a memory provided in a radio base station or in a switching station;

selecting, in a cellular mobile telephone, one from among said plurality of messages stored in said memory according to a responding user's circumstance at the time of receiving the incoming call from the calling party, regardless of the identity of the calling party;

said cellular mobile telephone transmitting address information associated with a message selected at said selecting step to said radio base station or to said switching station; and

said radio base station or said switching station transmitting said selected message to the calling party based on the address information transmitted from said cellular mobile telephone.



38. A cellular mobile telephone apparatus having a response message transmitter, comprising :

a memory for storing a plurality of audio messages for responding to an incoming call from a calling party;

a selector for selecting one of said plurality of messages according to a responding user's circumstance at the time of receiving the incoming call from the calling party, regardless of the identity of the calling party;

a transmitter for transmitting the message selected by said selecting means to the calling party;

a controller operable when an incoming call is received to instruct said transmitter to transmit the message selected by said selector to the calling party;

a message recorder for recording a message from the calling party after said transmitter transmits said selected message; and

a disconnecter for cutting a communication channel for said apparatus after said message recorder records the message from the calling party.

39. A cellular mobile telephone apparatus having a response message transmitter comprising:

a memory for storing a plurality of audio messages for responding to a an incoming call from calling party;

means for automatically selecting one of said plurality of messages in response to the incoming call;

means for transmitting the selected message to the calling party; and

means for instructing said transmitting means to transmit the selected message in response to the selection by said selecting means.



27 SEP 2001

40. A cellular mobile telephone apparatus having a response message transmitter, comprising:

a memory for storing a plurality of audio messages for responding to a an incoming call from calling party;

means for automatically selecting one of said plurality of messages in response to the incoming call;

means for transmitting the selected message to the calling party; and

means for instructing said transmitting means to transmit the selected message in response to the selection by said selecting means;

wherein said instructing means includes means for detecting voice of the user; and

wherein said voice detecting means includes:

means for transducing said voice of the user to an electrical signal;

means for extracting a predetermined voice spectrum component from a voice signal fetched by said transducing means; and

means for operating said transmitting means when the component extracted by said extracting means is higher than a predetermined noise level.



27 SEP 2001

41. A cellular mobile telephone apparatus having a response message transmitter, comprising :

a memory for storing a plurality of audio messages for responding to an incoming call from calling party;

a selector for automatically selecting one of said plurality of messages in response to the incoming call;

a transmitter for transmitting the selected message to the calling party; and

an instruction device for instructing said transmitter to transmit the selected message in response to the selection by said selecting means;

a message recorder for recording a message from the calling party after said transmitter transmits said selected message; and

disconnecting means for cutting a communication channel for said apparatus after said message recorder records the message from the calling party.

42. A cellular mobile telephone apparatus according to claim 19, wherein said incoming call communicator is incorporated in a wristwatch.

43. A cellular mobile telephone apparatus having a response message transmitter, comprising:

a memory for storing a plurality of audio message for responding to an incoming call from a calling party;

a selector for selecting one of said plurality of messages according to a responding user's circumstance at the time of receiving the incoming call from the calling party, regardless of the identity of the calling party;

a transmitter for transmitting the message selected by said selector to the calling party;

a controller operable when an incoming call is received to instruct said transmitter to transmit the message selected by said selector to the calling party;



wherein said controller includes a voice detector for detecting voice of the user; and

wherein said voice detector includes:

a transducer for transducing said voice of the user to an electrical signal;

a spectrum extracting device for extracting a predetermined voice spectrum component from a voice signal fetched by said transducer;

and

a transmitter controller for operating said transmitter when the component extracted by said spectrum extracting device is higher than a predetermined noise level.

44. A cellular mobile telephone apparatus having a response message transmitter, comprising:

a cellular mobile telephone body and an incoming call communicator

which communicates with said cellular mobile telephone body, wherein:

said cellular mobile telephone body comprises a transmitter/receiver for transmitting and receiving information to and from said incoming call communicator, a controller for responsive to an incoming call received from a calling party for instructing said transmitter/receiver to notify said incoming call communicator of the reception of the incoming call, a memory for storing at least one message for responding to said calling party, and a transmitting device for transmitting said message to said calling party when said transmitter/receiver receives response information designating said message to be transmitted from said incoming call communicator;

said incoming call communicator comprises a transmitter/receiver for transmitting and receiving information to and from said cellular mobile telephone body, notifying device for notifying a user of said cellular mobile telephone apparatus of the reception of an incoming call when said transmitter/receiver of the incoming call communicator receives the notification of the reception of the incoming call from said cellular mobile telephone body, and responding device for instructing said transmitter/receiver of the incoming call communicator to transmit said response information to said



27 SEP 2001

cellular mobile telephone body when said incoming call user responds to said notifying device;

said message storing memory stores a plurality of messages;

said incoming call communicator further comprises a selector for selecting one from among the plurality of messages stored in said message storing memory, said responding device includes instructing device for instructing said transmitter/receiver of the incoming call communicator to transmit response information associated with a message selected by said selector to said cellular mobile telephone body; and

wherein said incoming call communicator further comprises an information memory for storing information associated with the message selected by said selector;

and said responding device includes an information transmitter for transmitting the information stored in said information memory as said response information.

45. A cellular mobile telephone apparatus having a response message transmitter, comprising:

a memory for storing a plurality of audio messages for responding to an incoming call from calling party;

a selector for automatically selecting one of said plurality of messages in response to the incoming call;

a transmitter for transmitting the selected message to the calling party; and

an instruction device for instructing said transmitter to transmit the selected message in response to the selection by said selector;

wherein said instruction device includes a voice detector for detecting voice of the user; and

wherein said voice detector includes:

a transducer for transducing said voice of the user to an electrical signal;

a spectrum extracting device for extracting a predetermined voice spectrum component from a voice signal fetched by said transducer; and



* C L M S *

27 SEP 2001

a transmitter controller for operating said transmitter when the component extracted by said spectrum extracting device is higher than a predetermined noise level.



27 SEP 2001

CELLULAR MOBILE TELEPHONE APPARATUS

ABSTRACT OF THE DISCLOSURE

A cellular mobile telephone apparatus has circuits for generating messages, a storage circuit for storing messages, and transmitter/receiver circuit for transmitting a message. When the user of the cellular mobile telephone apparatus cannot immediately respond to an incoming call, a desired one of a plurality of previously generated and stored messages can be transmitted to a calling party through simple key manipulations or by other means.

Figure 1