

TELEPHONE USABLE FOR BOTH TABLEMOUNTED TYPE WALL HANGING

5

The present invention relates to a telephone serving as both table mounted type and wall hung type.

10

A typical conventional telephone usable for both table mounting and hanging on a wall will be described below with reference to Figs. 1 and 2.

15 When it is used for table mounting, it is constructed such that a casing 1 is detachably mounted on a box-shaped holding board 2 in such a manner that its fore end part (right end part in Fig. 1) is raised up above the table surface, as illustrated in Fig. 1. As is
20 best seen from Fig. 3, one side (hereinafter called the upper side) of the holding board 2 is opened. On the other hand, when it is used for hanging on a wall the casing 1 is mounted on the holding board 2 in such a manner that its rear end part (left end part as seen
25 in Fig. 1) assumes the lower position spaced away from the wall surface, as illustrated in Fig. 2. The holding board 2 of which upper side extends at a

certain inclination angle relative to the bottom thereof is molded of synthetic resin in the same manner as the upper and lower covers 1a and 1b of the casing 1. As illustrated in Fig. 3, the

5 holding board 2 is formed with a pair of pawls 3 on the upper end of the rear side wall 2a, a pair of engagement pieces 4 on the upper end of the fore side wall 2b and three fitting holes 2d on the bottom wall 2c thereof. When the telephone is mounted

10 on a wall 6 as a wall hung type, the holding board 2 is first fixed to the wall 6 by means of set screws 5 threadably fitted through the holes 2d and the casing 1 is then firmly fitted onto the holding board 2 by engaging the pawls 3 and the engagement pieces 4 to

15 corresponding holes 7 and 8 on the lower cover 1b.

When the telephone is used as for table mounting as illustrated in Fig. 1, it is often found that the casing 1 is placed at the position remote from a modular jack which is not shown in the drawing, for

20 instance, on the table surface or the like. On the other hand, when it is used as a wall hung type as illustrated in Fig. 2, it is often found that the casing 1 is placed at the position in the vicinity of the modular jack 9. In the last-mentioned case it

25 generally requires a short length of telephone cable 10. However, if a telephone having telephone cable 10 of which length is determined for the purpose of table

mounting is employed for wall hanging for any reason, there is necessity for cutting off an excessive part of the cable 10 and attaching a new modular plug 11 to the foremost end of the shortened cable.

5 Otherwise, there is necessity for replacing the cable initially provided with another shorter one. However, replacing operation is usually complicated and takes long time.

10 Further, when a telephone which has been once mounted as a wall hung type, that is, a telephone having short telephone cable 10 is to be in use for table mounting, there is a necessity for replacing the initially provided cable 10 with another longer one. Particularly, when an user performs replacing operation
15 by himself, he is required to start it with the step of getting a longer cable. However, this is very complicated and takes long time.

20 Hence, the present invention has been made with the foregoing background in mind.

According to the invention in a first aspect, there is provided a telephone serving as both a table mounted type and a wall hung type comprising:

a casing having a bottom portion and a telephone cable extending therefrom;

a holding board having a bottom face, side faces, an open end facing said bottom portion of said casing, and an outlet hole in said bottom face, said telephone cable extending through said open end into said holding board and through said outlet hole to the outside of said holding board;

engaging means for detachably engaging said open end of said holding board with said bottom portion of said casing;

fixing means for mounting said bottom face of said holding board on a vertical surface; and receiving means for receiving an excessive part of said telephone cable in said holding board.

According to the invention in a second aspect, there is provided a telephone serving both as a table mounted type and a wall hung type, comprising:

a casing having a bottom portion and a telephone cable extending therefrom:

a holding board having a bottom face, side faces, an open end facing said bottom portion of said casing, and an outlet hole in said bottom face, said bottom face including a raised portion having cavity opening away

from said open end of said holding board, said telephone cable extending through said open end into said holding board and through said outlet hole to the outside of said holding board;

engaging means for detachably engaging said open end of said holding board with said bottom portion of said casing;

fixing means for mounting said bottom face of said holding board on a vertical surface; and

receiving means for receiving an excessive part of said telephone cable in said holding board.

According to the invention in a third aspect, there is provided a telephone serving as both a table mounted type and a wall hung type, comprising:

a casing having a bottom portion and a telephone cable extending therefrom;

a holding board having a bottom face, a pair of opposed side faces, an open end facing said bottom portion of said casing, and an outlet hole in said bottom face, said telephone cable extending through said open end into said holding board and through said outlet hole to the outside of said holding board, each of said opposed side faces having a bottom edge fixed to said bottom face and a top edge at said open end, said top edges defining an imaginary plane non-parallel to said bottom face;

engaging means for detachably engaging said open end of said holding board with said bottom portion of said casing in a first engaging manner at times when said telephone is used as a table mounted type and in a second engaging manner at times when said telephone is used as a wall hung type, the position of said holding board in said second engaging manner being rotated 180 degrees relative to the position of said holding board in said first engaging manner;

fixing means for mounting said bottom face of said holding board on a vertical surface at times when said telephone is used as a wall hung type; and

receiving means for receiving an excessive part of said telephone cable in the holding board.

It is an advantage of the described embodiment of the present invention that a telephone serving as both a table mounted type and a wall hung type is provided which assures that the length of telephone cable is adjusted as required.

It is another advantage of the described embodiment of the present invention that a telephone serving as both a table mounted type and a wall hung type is provided which assures that there is no occurrence of exposure of any part of telephone cable to the outside when it is in use as a wall hung type.

It is another advantage of the described embodiment of the present invention that a telephone serving as both a table mounted type and a wall hung type is provided which assures that any length of telephone cable is easy to be handled.

It is still another advantage of the described embodiment of the present invention that a telephone serving as both a table mounted type and a wall hung type is provided which assures that an excessive part of telephone cable is easy to be stored and reused as required.

An embodiment of the invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Fig. 1 is a partially sectioned side view of a conventional telephone usable as both table mounted type and wall hung type, wherein it is in use as a table mounted type.

Fig. 2 is a partially sectioned side view of the conventional telephone in figure 1, wherein it is in use as a wall hung type.

Fig. 3 is a perspective view of a holding board for the conventional telephone in figures 1 and 2.

Fig. 4 is a perspective view of a holding board usable for a telephone serving as both a table mounted type and a wall hung type according to an embodiment of the present invention.

Fig. 5 is a perspective view of essential components constituting the embodiment of the telephone of the invention, shown in the disassembled state.

Fig. 6 is a partially sectioned side view of the embodiment of the telephone of the invention, wherein it is in use as a wall hung type, and

Fig. 7 is a perspective view of the base of the embodiment of the telephone of the invention, particularly illustrating how telephone cable is introduced into the holding board and taken out of the same.

Now, an embodiment of the present invention will be described in a greater detail hereunder with reference to figures 4 to 7.

Referring first to figure 4, a holding board 20 of which upper open side extends at a certain inclination angle relative to the bottom thereof is designed in a box-shaped configuration with its upper surface adapted to be fitted to a telephone casing 30 (figure 5). The holding board 20 is formed with raised portion 20b which is opened outwardly as seen from below in the drawing. Further, the holding board 20 is formed with a pair of engagement pawls 21 on the upper end of the one side wall 20c and a pair of engagement pieces 22 on the upper end of the other side wall 20d. Both the engagement pawls 21 and pieces 22 serve as engagement means for allowing the _____

casing 30 to be engaged to the holding board 20. The one side wall 20e constituting the raised portion 20b on the bottom wall 20a of the holding board 20 has a pair of substantially L-shaped tongues 23 projected outwardly of both the ends thereof so that the free ends 23a of the tongues 23 are located substantially flush with the open end face of the holding board 20 to which the lower surface 30a of the casing 30 is to be firmly engaged. It should be noted that the free end parts of the tongues 23 are extended to the position located close to the side wall 20c. On the one side wall 20e of the raised portion 20b and in the boundary area between the bottom wall 20a and the side wall 20c are formed outlet holes 24 and 25 through which a telephone cable 31 is extended. Further, on the bottom wall 20a are formed key hole-shaped slots 26 which constitute a part of securing means for fixedly securing the holding board 20 to a wall 40 (Fig. 6).

On the other hand, the casing 30 is formed with four rectangular holes 32 and 33 on the lower surface 30a which serve as other part of engaging means for firmly engaging the casing 30 to the holding board 20 as illustrated in Fig. 5. When the casing 30 is mounted on the holding board 20, the engagement pawls 21 and the engagement pieces 22 on the latter are fitted into the rectangular holes 32 and 33 on the

former. Further, the casing 30 is formed with a rectangular hole 34 on the lower surface 30a through which the cable 31 is extended outwardly. As is apparent from Fig. 7, the outlet hole 34 is extended across the end face of the side wall 20c on the holding board 20 when the casing 30 is firmly mounted on the holding board 20. Namely, one half of the outlet hole 34 is opened outside the holding board 20 and the other half of the same is opened inside the latter.

Next, operation of this embodiment of the telephone of the invention will be described below.

Description will be first made as to the case where it is used as a wall hung type telephone. A modular plug 35 at the one end of the cable 31 is taken out of the holding board 20 through the outlet hole and it is then plugged in a modular jack 51 on a plate 50 which is previously fixed to the wall 40. Next, the key hole-shaped slots 26 on the holding board 20 are engaged onto the engagement pins 52 on the plate 50 whereby the holding board 20 is fixedly mounted on the wall 40. At this moment the modular jack 51 and the modular plugs 35 are fully housed in the cavity of the raised portion 20b of the holding board 20. The residual part of the cable 31 is folded in the form of a bundle and the latter is then received in the space as defined by the substantially I-shaped tongues 23, the bottom wall 20a and the side walls 20c and 20e.

Thus, the casing 30 is firmly mounted on the holding board 20 by engaging the engagement pawls 21 and the engagement pieces 22 on the latter to the engagement holes 32 and 33 on the former, as illustrated in

5 Fig. 6. It should be noted that in the illustrated embodiment an opening formed on the one side wall of raised portion 23 is used as an outlet hole through which the cable 31 is to be extended from the holding board 20.

10 When the telephone of the invention is firmly hung on the wall 40 in that way, there is no occurrence of exposure of any part of the cable 31 to the outside and therefore aesthetic appearance of the telephone is not degraded any longer. The bundled part of the
15 cable 31 is easy to be received in the holding board 20 and taken therefrom as required.

In case where the embodiment of the telephone of the invention is used as a table mounted type telephone, the cable 31 is not received in the holding board 20 but it
20 is extended outwardly through the outlet hole 34 on the lower surface 30a of the casing 30, as illustrated by real lines in Fig. 7. Alternatively, it may be extended outwardly through the outlet hole 25 on the holding board 20 after it is once introduced into the
25 latter, as illustrated by phantom lines in Fig. 7.

While the present invention has been described above with respect to a single preferred embodiment,

12

it should be of course be understood that it should
not be limited only to this but various changes or
modifications may be made in any acceptable manner
without departure from the scope of the
5 invention as defined by the appended claims.



13

Claims

1. A telephone serving as both a table mounted type and a wall hung type comprising:

a casing having a bottom portion and a telephone cable extending therefrom;

a holding board having a bottom face, side faces, an open end facing said bottom portion of said casing, and an outlet hole in said bottom face, said telephone cable extending through said open end into said holding board and through said outlet hole to the outside of said holding board;

engaging means for detachably engaging said open end of said holding board with said bottom portion of said casing;

fixing means for mounting said bottom face of said holding board on vertical surface;

receiving means for receiving an excessive part of said telephone cable in said holding board.

2. A telephone serving as both a table mounted type and a wall hung type, comprising:

a casing having a bottom portion and a telephone cable extending therefrom:

a holding board having a bottom face, side faces, an open end facing said bottom portion of said casing, and an outlet hole in said bottom face, said bottom face



14

including a raised portion having cavity opening away from said open end of said holding board, said telephone cable extending through said open end into said holding board and through said outlet hole to the outside of said holding board;

engaging means for detachably engaging said open end of said holding board with said bottom portion of said casing;

fixing means for mounting said bottom face of said holding board on a vertical surface; and
receiving means for receiving an excessive part of said telephone cable in said holding board.

3. A telephone as claimed in claim 2, wherein said raised portion includes a side wall extending from said bottom face of said holding board and said outlet hole in said side wall of said raised portion.

4. A telephone as claimed in claim 1 or 2, wherein said bottom portion of said casing includes an outlet hole through which said telephone cable is extended.

5. A telephone as claimed in claim 4, wherein said outlet hole in said bottom portion of said casing includes a first hole portion opening inside said holding board and a second hole portion opening outside said holding board.



15

6. A telephone as claimed in claim 1 or 2, wherein said receiving means includes a pair of L-shaped tongues each having an attached end extending from said bottom face of said holding board and a free end located close to one of said side faces of said holding board.

7. A telephone as claimed in claim 3, wherein said receiving means includes a pair of L-shaped tongues each having an attached end extending from said bottom face of said holding board adjacent said side wall of said raised portion and a free end located close to one of said side faces of said holding board.

8. A telephone serving as both a table mounted type and a wall hung type, comprising:

a casing having a bottom portion and a telephone cable extending therefrom;

a holding board having a bottom face, a pair of opposed side faces, an open end facing said bottom portion of said casing, and an outlet hole in said bottom face, said telephone cable extending through said open end into said holding board and through said outlet hole to the outside of said holding board, each of said opposed side faces having a bottom edge fixed to said bottom face and a top edge at said open end, said top edges defining an imaginary plane non-parallel to said bottom face;



16

engaging means for detachably engaging said open end of said holding board with said bottom portion of said casing in a first engaging manner at times when said telephone is used as a table mounted type and in a second engaging manner at times when said telephone is used as a wall hung type, the position of said holding board in said second engaging manner being rotated 180 degrees relative to the position of said holding board in said first engaging manner;

fixing means for mounting said bottom face of said holding board on a vertical surface at times when said telephone is used as a wall hung type; and

receiving means for receiving an excessive part of said telephone cable in the holding board.



17

9. A telephone as claimed in claim 8, wherein said bottom face of said holding board includes a raised portion having a cavity opening away from said open end of said holding board.

10. A telephone as claimed in claim 9, wherein said raised portion includes a side wall extending from said bottom face of said holding board and said outlet hole is formed in said side wall of said raised portion.

11. A telephone as claimed in claim 8, wherein said bottom portion of said casing includes an outlet hole through which said telephone cable is extended.

12. A telephone as claimed in claim 11, wherein said outlet hole in said bottom portion of said casing includes a first hole portion opening inside said holding board and a second hole portion opening outside said holding board.

13. A telephone as claimed in claim 8, wherein said receiving means includes a pair of L-shaped tongues each having an attached end extending from said bottom face of said holding board and a free end located close to one of said side faces of said holding board.



18

14. A telephone as claimed in claim 10, wherein said receiving means includes a pair of L-shaped tongues each having an attached end extending from said bottom face of said holding board adjacent said side wall of said raised portion and a free end located close to one of said side faces of said holding board.

15. A telephone substantially as hereinbefore described, with reference to figures 4 to 7 of the accompanying drawings.
