

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
28 February 2008 (28.02.2008)

PCT

(10) International Publication Number
WO 2008/022815 A1

(51) International Patent Classification:

B65B 31/04 (2006.01) **G01M 3/32** (2006.01)
B65B 31/08 (2006.01) **G01M 3/36** (2006.01)
B65D 81/20 (2006.01)

(74) Agents: VANDEBERG, Marie-Paule et al.; Avenue
Wolffers, 32, B-1310 La Hulpe (BE).

(21) International Application Number:

PCT/EP2007/053890

(22) International Filing Date: 20 April 2007 (20.04.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

1032367 25 August 2006 (25.08.2006) NL

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH,
CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES,
FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN,
IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR,
LS, LT, LU, LY, MA, MD, MG, MK, MN, MW, MX, MY,
MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS,
RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL,
PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(71) Applicant (for all designated States except US): INTER-
PRISE BRUSSELS S.A. [BE/BE]; Office Park Nysdam,
Avenue Reine Astrid, 92, B-1310 La Hulpe (BE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): AARTS, L. C. Published:
[NL/NL]; Zweerslaan, 7, NL-3723HN Bilthoven (NL).

— with international search report

(54) Title: METHOD AND ASSEMBLY FOR THE CONTROLLED CHANGE OF THE GAS CONTENT INSIDE A PACKAGE



(57) Abstract: Method and assembly for evacuating a package (2), such as a vacuum package filled with a product such as nuts. The package is at least partially made of packaging film (6). The method employs a suction device (4) provided with a suction opening, for evacuating the package through an aperture (12) in the packaging film. The package is provided with a substantially plate-shaped, rigid element (8), one main surface of which substantially lying in contact "with the inner side of the packaging film, wherein the aperture in the packaging film is provided at the location of the substantially rigid element. The method further includes the sealing abutment of the suction opening against an outer side of the package, at a location where the substantially rigid element lies in contact with the inner side of the packaging film, in such a way that the aperture is in fluid connection with the suction opening.

WO 2008/022815 A1