

What is claimed is:

1. A method of transferring liquid using a robotic liquid handler, the method comprising:
aspirating a first volume of liquid out of a reagent reservoir using a multi-channel
pipettor of the robotic liquid handler, the reagent reservoir having a sloped bottom
along a length of the reagent reservoir, the sloped bottom defining a shallow end and
a deep end of the reagent reservoir, wherein the shallow end is proximal to a first
side-wall of the reagent reservoir, wherein the deep end is proximal to a second side-
wall of the reagent reservoir opposite the first side-wall; and
aspirating a second volume of liquid out of the deep end of the reagent reservoir
using a single-channel pipettor or a single channel of a multi-channel pipettor of the
robotic liquid handler,
wherein aspiration of the second volume out of the deep end results in depletion of
liquid in the shallow end of the reagent reservoir
2. The method of claim 1, wherein the single-channel pipettor or single channel of a
multi-channel pipettor is positioned at a deepest portion of reagent reservoir, wherein
the deepest portion is proximal to the second side-wall of the reagent reservoir.
3. The method of claim 1, wherein the reagent reservoir has a decreasing cross-section
along a width of the reagent reservoir from the first side-wall to the second side-wall.
4. The method of claim 3, wherein aspirating the first volume of liquid out of the reagent
reservoir using the multi-channel pipettor of the robotic liquid handler comprises
aspirating the first volume using the multi-channel pipettor along the width of the
reagent reservoir from the first side-wall to the second side-wall.
5. The method of claim 1, wherein the reagent reservoir has multiple chambers, each
with sloped bottom.
6. The method of claim 5, wherein multiple chambers are formed by a dividing wall
running along length of the reservoir.
7. The method of claim 1, further comprising:
depositing particled in the liquid; and
allowing the particles to become suspended in the liquid;
wherein the particles settle evenly along the sloped bottom.

8. The method of claim 1, further comprising:
aligning tabs with slots on the liquid handler to position the reagent reservoir on a
deck of the robotic liquid handler.
- 5
9. The method of claim 1, further comprising:
engaging tabs of the reagent reservoir with a deck of the robotic liquid handler to
elevate the shallow end above the deep end and the first side-wall and the second
side-wall stand vertical on the deck.
- 10
10. A method of transferring liquid using a robotic liquid handler, the method comprising:
filling a reagent reservoir with a liquid such that a sloped bottom of the reagent
reservoir, wherein the sloped bottom forms a deep end and a shallow end;
removing a first portion of the liquid from the reagent reservoir using a multi-channel
pipettor having a first pipettor tip extending into a first position near the shallow end
and a second pipettor tip extending into a second position near the deep end; and
removing a second portion of the liquid from the reagent reservoir using a multi-
channel pipettor having a single pipettor tip extending into a second position near the
deep end or a pipettor tip of a single-channel pipettor extending into the deep end.
- 15
- 20
11. The method of claim 10, wherein removing the first portion of the liquid from the
reagent reservoir using the multi-channel pipettor can result in the liquid emptying
from the shallow end of the reagent reservoir.
- 25
12. The method of claim 10, wherein removing the first portion of the liquid from the
reagent reservoir can further comprise repeating aspiration of liquid from the second
volume with the second pipettor.
- 30
13. The method of claim 10, wherein removing a second portion of the liquid from the
reagent reservoir using the multi-channel pipettor having a single pipettor tip
extending into a second position near the deep end or a pipettor tip of a single-
channel pipettor extending into the deep end can result in removing all of the liquid in
the first volume.
- 35
14. A method of transferring liquid using a robotic liquid handler, the method comprising:
aspirating a first volume of liquid out of a reagent reservoir using a first pipettor of the
robotic liquid handler, the first pipettor having a number of tips including a first tip and

- a second tip, the reagent reservoir having a sloped bottom along a length of the reservoir, the sloped bottom defining a shallow end and a deep end of the reagent reservoir, wherein the first tip is positioned over the shallow end of the reagent reservoir and another tip is positioned over the deep end of the reagent reservoir during the aspiration of the first volume of liquid; and
5 aspirating a second volume of liquid out of the reagent reservoir using a second pipettor of the robotic liquid handler, the second pipettor having a number of tips less than the number of tips of the first pipettor, wherein a tip of the second pipettor is positioned over the deep end of the reagent reservoir during the aspiration of the
10 second volume.
15. A method of transferring liquid from a bulk storage vessel using a robotic liquid handler, the method comprising:
adding liquid to the bulk storage reservoir such that:
15 a first volume of the bulk storage reservoir formed by a sloped bottom of the storage reservoir forming a deep end and a shallow end fills; and
a second volume of the bulk storage vessel above the first volume formed by first and second end-walls of the bulk storage vessel at the deep and shallow above becomes at least partially filled;
20 emptying the second volume using a multi-channel pipettor; and
emptying the first volume using a single-channel pipettor or a single channel of a multi-channel pipettor.