

Privacy-Preserving Image Distribution

RELATED APPLICATIONS

5 [0001] This application claims the benefit of the filing date of U.S. provisional patent application No. 62/705,604, filed on 07/07/2020, entitled "Privacy-Preserving Surveillance Systems and Methods," the entire contents of which are incorporated by reference herein.

BACKGROUND

10 [0002] The present invention relates to image processing, and in particular to employing cryptographic manipulations to distribute an image to multiple users in a manner which preserves the privacy of selected users.

15 [0003] Recent advances in imaging technology and artificial intelligence have led to an explosion of digital surveillance. Video surveillance of public spaces has been traditionally used by police to prevent crime. Surveillance cameras are also increasingly being used on private property, in shops, offices, and schools. Data collected by the cameras is often further processed to extract various features, for instance a vehicle license plate or an identity of a person appearing in a particular image.

20 [0004] Extensive use of such technologies has raised some concerns. Pro-democracy activists have accused some governments of using surveillance to target political opponents, dissidents, specific social and ethnic groups. In recent years, the public at large has also become less accepting of mass surveillance, increasingly seeing it as an invasion of privacy.

[0005] There is therefore a substantial interest in developing privacy-preserving video surveillance systems and methods.

SUMMARY

25 [0006] According to one aspect, a method of distributing customized privacy-preserving images to a plurality of users comprises employing at least one hardware processor of a privacy

management server, in response to receiving an encrypted source image decryptable with an administration key, to perform an encrypted-domain image segmentation of the source image to produce a plurality of user-specific encrypted private images. A selected private image comprises a region of the source image selected to show a private item of a selected user of the plurality of users, and another private image comprises another region of the source image selected to show a private item of another user of the plurality of users. The method further comprises employing at least one hardware processor of the privacy management server, in response to the image segmentation, to perform an encrypted-domain key change procedure to produce a plurality of user-specific re-encrypted images. A selected re-encrypted image comprises a result of transforming the selected private image from being decryptable with the administration key to being decryptable with a private key of the selected user, and another re-encrypted image comprises a result of transforming the other private image from being decryptable with the administration key to being decryptable with a private key of the other user. The method further comprises employing at least one hardware processor of the privacy management server to transmit the plurality of user-specific re-encrypted images to an image distribution server for further distribution to client devices configured to reconstruct user-specific plaintext versions of the source image.

[0007] According to another aspect, a computer system comprises a privacy management server configured, in response to receiving an encrypted source image decryptable with an administration key, to perform an encrypted-domain image segmentation of the source image to produce a plurality of user-specific private images. A selected private image comprises a region of the source image selected to show a private item of a selected user of the plurality of users, and another private image comprises another region of the source image selected to show a private item of another user of the plurality of users. The privacy management server is further configured, in response to the image segmentation, to perform an encrypted-domain key change procedure to produce a plurality of user-specific re-encrypted images. A selected re-encrypted image comprises a result of transforming the selected private image from being decryptable with the administration key to being decryptable with a private key of the selected user, and another re-encrypted image comprises a result of transforming the other private image from being

decryptable with the administration key to being decryptable with a private key of the other user. The privacy management server is further configured to transmit the plurality of user-specific re-encrypted images to an image distribution server for further distribution to client devices configured to reconstruct user-specific plaintext versions of the source image.

5 **[0008]** According to another aspect, a non-transitory computer-readable medium stores instructions which, when executed by at least one hardware processor of a privacy management server, cause the privacy management server, in response to receiving an encrypted source image decryptable with an administration key, to perform an encrypted-domain image segmentation of the source image to produce a plurality of user-specific private images. A selected private image
10 comprises a region of the source image selected to show a private item of a selected user of the plurality of users, and another private image comprises another region of the source image selected to show a private item of another user of the plurality of users. The instructions further cause the privacy management server, in response to the image segmentation, to perform an encrypted-domain key change procedure to produce a set of user-specific re-encrypted images.
15 A selected re-encrypted image comprises a result of transforming the selected private image from being decryptable with the administration key to being decryptable with a private key of the selected user, and another re-encrypted image comprises a result of transforming the other private image from being decryptable with the administration key to being decryptable with a private key of the other user. The instructions further cause the privacy management server to
20 transmit the plurality of user-specific re-encrypted images to an image distribution server for further distribution to client devices configured to reconstruct user-specific plaintext versions of the source image.s

BRIEF DESCRIPTION OF THE DRAWINGS

25 **[0009]** The foregoing aspects and advantages of the present invention will become better understood upon reading the following detailed description and upon reference to the drawings where:

[0010] Fig. 1 shows an exemplary privacy-preserving surveillance system according to some embodiments of the present invention.

[0011] Fig. 2 shows exemplary components of an input sensor according to some embodiments of the present invention.

5 [0012] Fig. 3 shows exemplary components of a client device according to some embodiments of the present invention.

[0013] Fig. 4 shows exemplary components of an image distribution server according to some embodiments of the present invention.

10 [0014] Fig. 5 shows exemplary components of a privacy management server according to some embodiments of the present invention.

[0015] Fig. 6 shows an exemplary source image according to some embodiments of the present invention.

[0016] Fig. 7 illustrates an exemplary public image contained within the source image in Fig. 6, according to some embodiments of the present invention.

15 [0017] Fig. 8 shows an exemplary private image contained within the source image of Fig. 6, according to some embodiments of the present invention.

[0018] Fig. 9 shows an exemplary user mask according to some embodiments of the present invention.

20 [0019] Fig. 10 shows an exemplary data exchange performed to set up a privacy-preserving surveillance system according to some embodiments of the present invention.

[0020] Fig. 11 shows an exemplary data exchange performed during operation of the privacy-preserving surveillance system according to some embodiments of the present invention.

[0021] Fig. 12 shows an exemplary sequence of steps performed by the privacy management server in embodiments as illustrated in Fig. 11.

[0022] Fig. 13 shows an exemplary data exchange performed in an alternative embodiment of the present invention.

5 [0023] Fig. 14 shows an alternative exemplary sequence of steps carried out by the privacy management server in embodiments as illustrated in Fig. 13.

[0024] Fig. 15 illustrates an exemplary sequence of steps performed by the image distribution server according to some embodiments of the present invention.

10 [0025] Fig. 16 shows an exemplary sequence of steps outlining an exchange between a client device and a distribution server according to some embodiments of the present invention.

[0026] Fig. 17-A shows an exemplary reconstructed image available to a selected client device according to some embodiments of the present invention.

[0027] Fig. 17-B shows another exemplary reconstructed image available to another client device according to some embodiments of the present invention.

15 [0028] Fig. 18 shows an exemplary data exchange in an embodiment of the present invention configured to perform a selected task in a privacy-preserving manner.

[0029] Fig. 19 illustrates an exemplary hardware configuration of a computing device configured to carry out operations according to some embodiments of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

20 [0030] In the following description, it is understood that all recited connections between structures can be direct operative connections or indirect operative connections through intermediary structures. A set of elements includes one or more elements. Any recitation of an element is understood to refer to at least one element. A plurality of elements includes at least two elements. Unless otherwise specified, any use of "OR" refers to a non-exclusive or. Unless

otherwise required, any described method steps need not be necessarily performed in a particular illustrated order. A first element (e.g. data) derived from a second element encompasses a first element equal to the second element, as well as a first element generated by processing the second element and optionally other data. Making a determination or decision according to a parameter encompasses making the determination or decision according to the parameter and optionally according to other data. Unless otherwise specified, an indicator of some quantity/data may be the quantity/data itself, or an indicator different from the quantity/data itself. A computer program is a sequence of processor instructions carrying out a task. Computer programs described in some embodiments of the present invention may be stand-alone software entities or sub-entities (e.g., subroutines, libraries) of other computer programs. The term 'database' is herein used to denote any structured collection of data. Carrying out an encrypted-domain procedure/operation herein denote carrying out the respective procedure/operation in the encrypted domain, i.e., directly on an encrypted input to produce an encrypted output in a manner which does not involve decrypting the input. An encrypted domain procedure is distinct from a procedure that decrypts the input and then encrypts the output of the respective procedure. Stated otherwise, an entity carrying out an encrypted-domain procedure/operation on an encrypted item need not be aware of a plaintext version of the respective item. Computer readable media encompass non-transitory media such as magnetic, optic, and semiconductor storage media (e.g. hard drives, optical disks, flash memory, DRAM), as well as communication links such as conductive cables and fiber optic links. According to some embodiments, the present invention provides, *inter alia*, computer systems comprising hardware (e.g., one or more processors) programmed to perform the methods described herein, as well as computer-readable media encoding instructions to perform the methods described herein.

[0031] The following description illustrates embodiments of the invention by way of example and not necessarily by way of limitation.

[0032] Fig. 1 shows an exemplary privacy-preserving surveillance system **10** according to some embodiments of the present invention. The term "surveillance" is used herein only to bring

clarity to the disclosure by focusing on a particular exemplary use case and is not meant to be limiting to typical surveillance activities such as preventing crime. Although the following description will focus on a video surveillance example, the disclosed systems and methods may be adapted to other applications, such as preserving privacy and/or ensuring confidentiality during a collaboration between multiple parties working on the same document, preventing cyber-bullying perpetrated via online messaging, etc.

[0033] System **10** includes, *inter alia*, an input sensor **14**, a distribution server **30**, a privacy management server **40**, and a plurality of client devices **12a-c**, all communicatively coupled by a network **15**, which may include the Internet.

[0034] Sensor **14** (e.g., a camera, a microphone, etc.) is configured to acquire a signal (e.g., an encoding of an image and/or a sound) which is further manipulated and transformed as described below. In a video surveillance example, sensor **14** may comprise a video camera positioned to acquire images of a public space, such as a schoolyard, a market square, etc. As such, sensor **14** may include hardware and/or software means for acquiring a signal (e.g., a charge-coupled device - CCD light sensor), computer-readable media for storing the acquired signal, and means for transmitting the respective signal (e.g., physical layer communication hardware, encoders, antenna, etc.). Fig. 2 shows other exemplary components of input sensor **14**, which may comprise dedicated software modules according to some embodiments of the present invention. A cryptographic engine **16** encrypts acquired images/sound recordings. A communication module **18** further transmits the resulting encrypted signals to privacy management server **40** and/or image distribution server **30** as detailed below.

[0035] In some embodiments, cryptographic engine **16** encrypts data according to a homomorphic encryption scheme. Homomorphic encryption is a particular kind of encryption which allows performing certain calculations such as additions and/or multiplications of encrypted data, wherein decrypting a result of such calculations produces the same output as applying the respective calculations to a plaintext version of the same data. Stated otherwise, if $Enc(p) = c$ denotes a homomorphic encryption operation wherein p represents a plaintext

message and c denotes its corresponding ciphertext, $Dec(c) = p$ denotes a homomorphic decryption operation that recovers the respective plaintext message from its ciphertext, and $Eval(F, \{c_1, \dots, c_k\}) = C$ denotes a homomorphic evaluation procedure producing a ciphertext C by applying a function F to a set of ciphertexts c_i , then:

$$Dec(C) = F(p_1, \dots, p_k), \quad [1]$$

wherein $p_i = Dec(c_i)$, $i=1, \dots, k$. In formal mathematical language, it is said that the encryption and decryption procedures of a homomorphic encryption scheme are homomorphisms between the plaintext space and ciphertext space.

[0036] Several homomorphic encryption schemes/cryptosystems are known in the art. Schemes that preserve the homomorphic property over any combination of additions and multiplications are commonly known as *fully homomorphic*. Examples include the Gentry-Sahai-Waters (GSW) scheme, among others. Other schemes/algorithms are homomorphic only over a certain type of operation, for instance only addition in the case of a Paillier scheme, and only multiplication in the case of a Rivest-Shamir-Adelman (RSA) scheme. Such schemes are known in the art as *partially homomorphic*. In contrast, ciphers that do not have the homomorphic property described above are herein deemed non-homomorphic. Examples of non-homomorphic ciphers include the Advanced Encryption Standard (AES) used in some Transport Layer Security (TLS) communication protocols.

[0037] Client devices **12a-c** generically represent any end-user electronic device such as a personal computer, smartphone, TV, etc., used to access and/or process (e.g., visualize, play back, etc.) data provided by input sensor **14**. In some embodiments as illustrated in Fig. **3**, a client device **12** may execute a surveillance software application **22** configured to perform a user authentication exchange (e.g., login procedure) with distribution server **30** and to subsequently display a reconstructed image to a user. A data reconstruction engine **24** is configured to reconstruct an image from a set of plaintext public images and a set of encrypted private images as described below. A client cryptographic engine **26** is configured to decrypt the received

encrypted private image(s). In some embodiments, engine **26** implements a homomorphic decryption algorithm.

[0038] Each of distribution server **30** and privacy management server **40** generically represents a set of interconnected computer systems, which may or may not be in physical proximity to each other. Exemplary components of servers **30** and **40** are shown in Figs. **4** and **5**, respectively. In some embodiments, such components represent computer programs (software) executing on at least a hardware processor. Not all illustrated components need to execute on the same hardware processor or physical machine. A skilled artisan will understand that in alternative embodiments, some of the illustrated components may be implemented in dedicated hardware such as application-specific integrated circuits (ASIC) and/or field-programmable gate arrays (FPGA), in firmware, on in a combination of the above.

[0039] In some embodiments, distribution server **30** manages a surveillance service including, for instance, communication with client devices **12a-c** for user registration and/or authentication, as well as distribution of selectively-encrypted data to each client device. Without loss of generality, server **30** may be herein referred to as an image distribution server, i.e., a server configured to distribute images (e.g., video) to clients. An artisan will appreciate that depending on the actual embodiment and use case, server **30** may distribute other kinds of data, such as audio, electronic documents, etc. A user manager component **32** may manage a set of user and/or account data (usernames, passwords, various service agreement parameters, etc.) and provide user interfaces for user registration and account management.

[0040] An access manager component **38** may selectively store and/or retrieve data to/from a data repository **20** and selectively forward such data to each client device **12a-c** according to an identity of a user currently authenticated on the respective client device. Access manager **38** may comprise a web server, among others.

[0041] A cryptographic key manager **34** may initiate and/or perform a key generation and exchange procedure with client devices **12a-c** and privacy management server **40**. Key manager **34** may further generate a set of proxy re-encryption tokens and selectively associate

each such token with a registered user of the surveillance service and/or with a client device **12a-c**. More details on such processes are given below.

[0042] An administration cryptographic engine **36** may be configured to perform data encryption and/or decryption operations as described further below. Engine **36** may implement a version of
5 a homomorphic encryption/decryption algorithm.

[0043] In some embodiments, data repository **20** may comprise a computer-readable storage medium configured to store a database of private and public data. Public data may comprise any data that is accessible to all users, for instance a plaintext (i.e., un-encrypted) image. Private data may be accessible and/or decryptable only by selected users. Examples of private data include
10 user-specific and composite proxy re-encrypted images as shown below. Such data may be indexed according to the user to enable selective insertion and retrieval. Indexing may take any form known in the art.

[0044] In some embodiments, privacy management server **40** (Fig. 5) provides services such as cryptography and automatic detection of private/confidential items in data provided by input
15 sensor **14**. A re-encryption engine **46** of server **40** is configured to perform key-swap procedures on encrypted data, as shown in more detail below. A key-swap procedure herein denotes a procedure of transforming a ciphertext from being decipherable using one key to being decipherable using another key. One example of key-swap procedure is known in the art as proxy re-encryption, which allows an entity Z, given some information about another entity Y, to
20 alter a ciphertext encrypted under a public key of an entity X, thereby making it decryptable by entity Y. Stated otherwise, entity Y can decrypt a ciphertext encrypted under X's public key using its own secret key, but only after the respective cyphertext has been proxy re-encrypted by entity Z using a re-encryption key (also known in the art as a re-encryption token) specific to entity Y. Translating this generic scheme to the exemplary actors illustrated in Fig. 1, some
25 embodiments of privacy management server **40** proxy re-encrypt data already encrypted with a public key of distribution server **30**, to make the respective data decryptable by a selected user of a client device **12a-c**. The proxy re-encryption procedure employs a re-encryption token specific

to the respective user and/or device, for instance a token generated according to a public encryption key of the respective use/device.

[0045] In some embodiments, re-encryption engine 46 operates in the encrypted domain, i.e., the respective key-swap procedures are carried out without decrypting the input. To achieve encrypted-domain key-swaps, some embodiments of engine 46 implement proxy re-encryption algorithms that are compatible with homomorphic encryption/decryption algorithms implemented by client devices 12a-c, distribution server 30, and/or input sensor 14. Such algorithms go beyond the scope of the present description; several such examples are known in the art of cryptography, for instance the PALISADE code library available at <https://gitlab.com/palisade/palisade-development>.

[0046] A set of item detectors 42 may be configured to determine whether input data received from sensor 14 (e.g., a frame captured by a surveillance camera) contains a representation of a private/confidential item associated with a selected user. Exemplary private items include a person, a face or some other body part, a logo/trademark, a car license plate, a bank card, a personal ID (e.g., driver's license, passport), a handwritten text, and a person's signature, among others. In embodiments configured to operate with sound, exemplary private items may comprise any item allowing an identification of a person, for instance any voice quality such as timbre, vocal fry, pitch, tempo, inflection, etc. Other exemplary private sound items include utterances of a name and of a selected word (e.g., profanity, racial slur, etc.), a gunshot, a sound of a verbal fight, etc. In embodiments configured to process text documents and/or electronic messages, exemplary private items comprise written names, addresses, financial information such as credit card numbers, etc. Other examples include text written by a selected author, text written on a selected topic, and text written in a selected style or conveying a selected sentiment, among others.

[0047] Private items may be user-specific. For instance, in a schoolyard surveillance use case, each parent may define his/her own child as a private item, so the respective child may be visible only to the respective parent. In some embodiments, multiple users may share a private item

and/or a single user may have multiple private items. In one such example, all members of a particular user group (e.g., parents of 3rd grade children) may be able to see the faces of their child's peers, but other users may not.

[0048] Fig. 6 shows an exemplary source image 70 received from a surveillance camera (input sensor 14), image 70 showing exemplary private/confidential items including a person (e.g., children 72a-b), a face 72c and a particular object 72d. Figs. 7-8 show exemplary public and private images contained in exemplary source image 70. In some embodiments, a private image comprises a representation (e.g., array of numbers) of a private/confidential item. In the example of Fig. 8, a private image 76a comprises a region of the source image showing private item 72a in Fig. 6. In turn, a public image 74 (Fig. 7) may comprise another region of source image 70 that does not show any private item. For instance, public image 74 may show all content of source image 70 which is not private. An exemplary public image includes a background of a scene (landscape, buildings, trees, a courtyard, the sky, etc.) In some embodiments, public image 74 and/or private image(s) 76a are represented as arrays of numbers having the same size as the source image 70.

[0049] Item detectors 42 may be constructed using any method known in the art. For instance, an exemplary item detector 42 may include an artificial intelligence (AI) system 43a such as a set of artificial neural networks pre-trained to identify an instance of the respective private item within a source image. Exemplary AI systems 43a include a facial recognition module and an image segmentation module, among others. The structure and training of such item detectors goes beyond the scope of the present description; several architectures and training strategies are known in the art.

[0050] In an image processing embodiment, an exemplary item detector 42 may receive source image 70 and output a user mask indicative of a region of the source image that shows a representation of a private item (e.g., a region of the source image that shows the face of a specific person). Fig. 9 shows an exemplary user mask 80a associated with private item 72a of Fig. 6. An exemplary user mask is characterized by a subset of pixels belonging to an image of

the respective private item. Another exemplary user mask comprises all pixels located inside a contiguous region of source image **70**, the region showing the private item. For instance, in an embodiment as illustrated in Fig. **9**, such a region may be defined as the inside of a polygon (e.g., convex hull, bounding box, etc.) enclosing the image of the private item. A convenient computer-readable encoding of a user mask comprises a sparse array of numbers, the array having the same size as source image **70** and wherein all elements are zero except elements corresponding to pixels of the mask. Multiple user masks may be associated with a single user (i.e., with a single re-encryption token, see below). Some user masks may overlap.

[0051] In some embodiments, detectors **42** operate in the encrypted domain, i.e., without decrypting the source images. To achieve such encrypted-domain operation, AI system **43a** (e.g., a neural network that implements facial recognition) may be deliberately structured to be compatible with homomorphic encryption schemes. For instance, detector(s) **42** may receive a homomorphically-encrypted source image and in response, output a homomorphically-encrypted user mask, the user mask encrypted using the same encryption key as the one used to encrypt the source image. Several such AI systems have been described in the art. Examples include CryptoNets described in N. Dowlin *et al.*, "CryptoNets: Applying Neural Networks to Encrypted Data with High Throughput and Accuracy", Proceedings of the 33rd International Conference on Machine Learning, New York, NY, 2016, JMLR: W&CP vol. **48**. In one such example, AI system **43a** includes a neural network wherein selected layers are equivalent to polynomials of a pre-determined degree, and wherein typical non-linear activation functions such as rectifier linear units (ReLU) are replaced with polynomial approximations.

[0052] In some embodiments, AI system **43a** is pre-trained by an AI training system **11** (e.g., machine learning algorithms executing on a processor), using training data provided or otherwise indicated by each user. In one such example, upon registering for the service, each user may provide a sample representation of a respective user's confidential item(s), such as an image of a face or a sample of a person's spoken voice. Some embodiments may then train AI system **43a** to identify representations of the respective private items within a data stream received from input sensor **14**. A relevant example is training facial recognition software on target faces

provided by each user. Training produces a set of optimized detector parameter values **45a** which are transmitted to item detector(s) **42**. In a neural network embodiment, exemplary parameters **45a** include a set of synapse weights and neuron biases, among others.

[0053] Fig. **10** shows an exemplary exchange performed to initialize/set up a privacy-preserving surveillance service according to some embodiments of the present invention. In the illustrated example, distribution server **30** carries out a key generation procedure to produce a pair of homomorphic encryption keys specific to distribution server **30** (herein deemed administration keys) and transmits a public key **52** of the pair to input sensor **14** for use in encrypting the acquired signals/image(s). Server **30** further engages in a key generation and/or exchange protocol with a client device **12** (generically representing any of client devices **12a-c** in Fig. **1**), wherein device **12** generates a distinct pair of encryption keys specific for each user accessing the privacy-preserving surveillance service via client device **12** (herein deemed user keys). An alternative embodiment may generate device-specific encryption keys. User and/or device key generation may occur at signup as part of each user's initial service configuration procedures, and may proceed according to a homomorphic encryption key generation algorithm. Client device **12** then sends public user key(s) **54** to distribution server **30**. In response to receiving key(s) **54**, key manager **34** may generate a set of proxy re-encryption token(s) **50** uniquely associated with each user and/or client device. Some embodiments generate each set of user-specific token(s) **50** according to a public key associated with the respective user/device and according to an administration key, via a token generation algorithm which is compatible with the homomorphic encryption algorithm used by client device **12** for generating user/device keys. Such key generation protocols/procedures go beyond the scope of the present description; several examples are known in the art of cryptography. Re-encryption tokens **50** are then transmitted to privacy management server **40** for use in proxy re-encryption of user-specific private images, as detailed below.

[0054] Figs. **11** and **13** illustrate exchanges of data carried out in two exemplary embodiments of a privacy-preserving surveillance system. For clarity, the following description will focus on video surveillance, i.e., the relevant source data comprises image data. A skilled artisan will

understand that the methods described herein may be adapted to other applications wherein the relevant data comprises an encoding of sound (e.g., voice recordings), text, etc.

[0055] Figs. 12 and 14 show alternative sequences of steps carried out by privacy management server 40 in embodiments described by Figs. 11 and 13, respectively. In turn, Fig 15 shows exemplary steps carried out by image distribution server 30.

[0056] In some embodiments, data acquired by input sensor 14 is encoded as a plaintext image I , for instance comprising an array of numbers wherein each number represents an intensity of the respective image at a distinct position/pixel. Some images may have multiple channels (e.g. red, green, and blue); in such embodiments, each channel may be represented by a separate array. Image I is then encrypted by sensor cryptographic engine 16 according to public administration key(s) 52 to produce an encrypted data stream 60 that is transmitted to privacy management server 40. Stream 60 may comprise, for instance, a set of encrypted source images:

$$I^* = Enc(I, k_{admin}^p), \quad [2]$$

wherein $Enc(x, k)$ generically denotes an encryption of a quantity x using key k , and k_{admin}^p denotes public administration key(s) 52. The star symbol (*) is used throughout to indicate encrypted quantities. In a video surveillance embodiment, each encrypted source image I^* may correspond to a distinct frame and may be tagged with an associated timestamp indicative of a moment in time when the respective frame was taken.

[0057] In response to receiving data stream 60, for each encrypted source image I^* , in a step 204 (Fig. 12), server 40 may apply item detector(s) 42 to determine whether the respective image comprises private data (i.e., images of items deemed private by some users). When yes, some embodiments of detector(s) 42 return a set of user masks (see exemplary mask 80a in Fig. 9) identifying regions of the source image that show various private items. Furthermore, such masks are indexed according to the users that have declared the respective items as private. Some embodiments may further determine a set of public masks comprising areas of the current frame that only contain public data. In an exemplary embodiment, a public mask is determined

by inverting all user masks and superposing the results. In another embodiment, item detectors **42** may be trained to return a set of public masks along with user masks.

[0058] However, since privacy management server **40** does not possess the secret administration key(s) and thus cannot decrypt source image(s) I^* , some embodiments of item detector(s) **42** operate in the encrypted domain, i.e., directly on encrypted data and produce an encrypted output (i.e., user masks are also encrypted). Therefore, in some embodiments, although item detectors **42** execute on server **40**, server **40** is oblivious to the content of the source image, as well as to a what region of the source image contains a private item, if any.

[0059] In some embodiments, a set of steps **206-208** (Fig. **12**) performs an encrypted-domain image segmentation procedure to extract a set of encrypted public and private images from the current source image I^* according to an output of item detector(s) **42**. Each private image may comprise an (encrypted) content of the current source image located within a distinct user mask. In some embodiments, the encrypted private image associated with user mask i may be determined according to a pixel-wise multiplication of the encrypted source image and the encrypted mask i :

$$I_i^{*PRIVATE} = I^* \odot M_i^*, \quad [3]$$

wherein M_i^* denotes the encrypted user mask i returned by item detector(s) **42**:

$$M_i^* = Enc(M_i, k_{admin}^p), \quad [4]$$

and wherein M_i denotes the unencrypted/plaintext user mask i .

[0060] The circled dot operator herein denotes pixel-wise multiplication:

$$(I^* \odot M_i^*)_{xy} = (I^*)_{xy} (M_i^*)_{xy}, \quad [5]$$

wherein the pair $\{xy\}$ indexes positions/pixels within the source image and user mask, respectively. Pixel-wise multiplication applies to images/arrays of the same size.

[0061] Meanwhile, an encrypted public image of the current frame (item **62** in Fig. **11**) may be computed according to an element-wise multiplication of the encrypted source image and the encrypted public mask:

$$I^{*PUBLIC} = I^* \odot M^{*PUBLIC}, \quad [6]$$

5 wherein $M^{*PUBLIC}$ denotes the encrypted public mask produced by item detector(s) **42**:

$$M^{*PUBLIC} = Enc(M^{PUBLIC}, k_{admin}^p), \quad [7]$$

wherein M^{PUBLIC} denotes the respective unencrypted/plaintext public mask.

[0062] In some embodiments, in a step **210**, privacy management server **40** may employ re-encryption engine **46** to proxy re-encrypt the private image(s) determined as seen above (e.g.,
10 formula [2]) according to a re-encryption token associated with the respective user/mask i , to produce an individual, user-specific re-encrypted private image **66** (Fig. **11**), which is then transmitted to image distribution server **30**. Such proxy re-encryption ensures that the respective private image is decipherable only by a holder of a decryption key associated with user/mask i . In some embodiments, re-encrypted private image **66** is tagged with an indicator of the
15 respective user, to enable server **30** to selectively insert and/or retrieve image **66** into/from data repository **20**. A further sequence of steps **212-214** transmits encrypted public image **62** and the re-encrypted private image(s) **66** to server **60** for further distribution to client devices **12a-c**.

[0063] In an alternative embodiment illustrated in Figs. **13-14**, in a step **230**, server **40** may transmit encrypted user mask(s) **64** to image distribution server **30** for decryption, and in
20 response, receive decrypted user mask(s) **65** from server **30**. In some embodiments, decrypted mask(s) **65** comprise plaintext versions of the encrypted user masks determined by item detector(s) **42**:

$$M_i = Dec(M_i^*, k_{admin}^s), \quad [8]$$

wherein $Dec(x, k)$ generically denotes a decryption of a quantity x using a key k , and wherein k_{admin}^s denotes a secret cryptographic key held by image distribution server **30**. In such embodiments, even though privacy management server **40** can clearly see whether and which region of the source image shows a private item, privacy is still preserved since server **40** cannot
 5 decrypt any region of the respective source image I^* .

[0064] Next, a step **234** may extract private images by copying pixels of the encrypted frame located within each decrypted user mask **65**. In some embodiments, this may amount to determining an encrypted private image associated with mask i as:

$$I_i^{*PRIVATE} = I^* \odot M_i \quad [9]$$

10 **[0065]** A further step **236** may employ re-encryption engine **46** to proxy re-encrypt each such private image with a re-encryption token of a user associated with the respective mask i , to produce individual re-encrypted private images. Next, in a step **238**, some embodiments may compute a composite re-encrypted private image **67** according to multiple individual re-encrypted private images determined in step **236**. In some embodiments, composite image **67**
 15 comprises a single image assembled from multiple private images in the manner of a mosaic wherein each individual re-encrypted private image occupies a region of the composite image corresponding to the respective user mask M_i . Calculating the composite private image may be facilitated by zero-padding each proxy re-encrypted private image to the size of the source image. Composite re-encrypted private image **67** may then be calculated according to:

$$20 \quad I^{*COMP} = \oplus_i ReEnc(I_i^{*PRIVATE}, t_i), \quad [10]$$

wherein $ReEnc(x, t)$ generically denotes a proxy re-encryption of a ciphertext x using a token t , and t_i denotes a re-encryption token associated with user/mask i . The circled plus operator herein denotes pixel-wise addition:

$$(I_1 \oplus I_2)_{xy} = (I_1)_{xy} + (I_2)_{xy}, \quad [11]$$

wherein the pair $\{xy\}$ indexes positions/pixels within exemplary images I_1 and I_2 , respectively. Pixel-wise addition is applicable to images of the same size.

[0066] The calculated composite re-encrypted private image **67** may then be transmitted to image distribution server in a step **240**. In an alternative embodiment, privacy management server **40** may compute individual proxy re-encrypted private images and transmit the respective images to distribution server **30**. In turn, server **30** may determine composite image **67** from the received individual re-encrypted images, for instance using Eq. [10].

[0067] Meanwhile (step **226** in Fig. **14**), privacy management server **40** may compute encrypted public image **62** as shown above (e.g., Eq. [6]). Alternatively, image **62** may be determined according to a plaintext public mask:

$$I^{*PUBLIC} = I^{*} \odot M^{PUBLIC}, \quad [12]$$

wherein M^{PUBLIC} is received from distribution server **30**. In yet another embodiment, M^{PUBLIC} may be computed by inverting all plaintext user masks M_i received from server **30** and superposing the results. In any of these situations, image **62** is encrypted with an administration key by virtue of the fact that server **40** performs image segmentation in the encrypted domain, i.e., without decrypting the source image. Stated otherwise, server **40** is unaware of the plaintext content of public image **62**. In a step **228**, encrypted public image **62** is transmitted to server **30** for decryption and further distribution to clients.

[0068] Fig. **15** illustrates an exemplary operation of image distribution server **30** according to some embodiments of the present invention. In a sequence of steps **252-254**, server **30** may wait for communications from privacy management server **40**. When such communications comprise encrypted user masks (step **256** returns a yes), image distribution server **30** may employ cryptographic engine **36** to decrypt the respective masks according to its secret administration key (e.g. formula [6] above), and transmit the decrypted mask(s) to privacy management server **40**.

[0069] When the communication comprises encrypted public image 62, server 40 may decrypt it to yield a decrypted public image 63:

$$I^{PUBLIC} = Dec(I^{*PUBLIC}, k_{admin}^s), \quad [13]$$

and save image 63 to data repository 20. Decrypted public image 63 may be tagged with a timestamp, frame number or another indicator associating image 63 to the source image it was extracted from.

[0070] When the communication received from server 40 comprises a re-encrypted private image (either specific to a user/mask i or composite, according to whether server 40 follows flowchart 12 or 14, respectively), image distribution server 30 may insert the respective private image into data repository 20. Re-encrypted private images may also be tagged according to a timestamp and/or a label associating the respective image(s) to a respective source image. Private images may also be tagged to indicate an association with a specific user and/or mask.

[0071] Fig. 16 shows further exemplary steps performed by image distribution server 30 in relation to a client device 12 generically representing any of client devices 12a-c in Fig. 1. In a step 280, client device 12 may carry out a user authentication procedure to identify a current user of device 12 to distribution server 30. Step 280 may implement any user authentication protocol known in the art (e.g., password, two-factor, biometric, etc.). In a step 282, device 12 may then transmit a query to server 30, for instance to indicate a request to view images from a specific surveillance camera and captured within a specific timeframe. In response, in a sequence of steps 284-290, image distribution server 30 may selectively retrieve from data repository 20 a set of public and private images according to the query, and transmit the respective images to client device 12. Depending on whether privacy management server 40 operates according to flowcharts illustrated in Figs. 12 or 14, private image(s) may comprise individual re-encrypted private images 66 or composite re-encrypted private images 67, respectively. Such transactions may be carried out via a web interface, for instance. In an alternative embodiment, image distribution server 30 may open a dedicated connection (e.g., VPN tunnel) with client device 20, and transmit public and private image(s) via the respective connection.

[0072] A skilled artisan will understand that although public images have been decrypted to plaintext prior to distribution, step 288 does not necessarily comprise transmitting the respective public images in plaintext. Instead, step 288 may include re-encrypting the transmitted public image, for instance as part of a transmission over TLS/HTTPS. However, such an encryption
 5 has no effect on image reconstruction at the client device; in a TLS/HTTPS transaction the receiving client device can always decrypt the payload.

[0073] In response to receiving the public and private images, in a step 292, client device 12 may use client cryptographic engine 26 (Fig. 3) to decrypt the respective private images using a secret cryptographic key associated with the respective user of client device 12. Next, in a step 294,
 10 data reconstruction engine 24 may compute a reconstructed image according to the decrypted private image(s) and further according to decrypted public image 63 received from image distribution server 30. For instance, a reconstructed image may be computed via pixel-wise addition of decrypted public image 63 and a decrypted private image:

$$R_i = I^{PUBLIC} \oplus Dec[ReEnc(I_i^{*PRIVATE}, t_i), k_i^s] \quad [14]$$

15 or

$$R_i = I^{PUBLIC} \oplus Dec(I^{*COMP}, k_i^s), \quad [15]$$

wherein R_i denotes the reconstructed image seen by user i , and k_i^s denotes a secret key of user i . When the source image comprises private data of multiple users, formula [14] may not compute an entire reconstructed image, in the sense that regions of the reconstructed image corresponding
 20 to user masks M_j belonging to users distinct from the current user i of client device 12 may be empty. To get a full reconstructed image, some embodiments may fill the missing regions with dummy data, e.g., zeros, random noise, random colors, etc.

[0074] Reconstructing the frame according to formula [14] may be preferable in situations where masks associated with distinct users may be overlapping, for instance when some information
 25 may be relevant to multiple users (e.g., to members of a selected group), while other information

is private to each user. Another example of such a situation may occur in an automatic image segmentation system configured to produce a multi-label classification.

[0075] In an embodiment wherein the reconstructed image is computed from a composite private image, reconstructed image R_i is complete but the secret key k_i^s held by user i can only decrypt
 5 the respective user's private data. Therefore, regions of the reconstructed image corresponding to user masks M_j of other users will show scrambled images. This effect is illustrated in Figs. 17-A-B, which show how two distinct users see reconstructions of the same source image. Fig. 17-A shows a reconstructed image seen by a user A that declared item 72a (Fig. 6) as being private. User A will see images of private item 72a, but will not be able to see images of other users' private items, such as images of items 72b-c-d (see Fig. 6). Fig. 17-B shows a reconstructed
 10 image seen by another user B for whom item 72b is private. User B may see images of item 72b, but may not be able to see images of private items 72a and 72c-d.

[0076] Reconstructing frame R_i according to formula [15], i.e., from composite encrypted private images, may be preferable in embodiments wherein item detectors 42 only produce non-
 15 overlapping user masks and/or wherein distinct users do not share private information. Otherwise, regions of the reconstructed image covered by mask overlaps may not be decipherable by any individual user, and therefore may appear scrambled. Operating with composite private images may further save computational resources, because it allows sending the same encrypted private data (i.e., one composite private image) to all users instead of storing,
 20 indexing, and selectively delivering individual private images to each user. In such embodiments, server 40 may directly insert private and public images into data repository 20, without further involvement of distribution server 30. A downside of embodiments using composite re-encrypted private images is that they ensure a relatively lower level of privacy compared to embodiments using individual private images, since in computing private images
 25 server 40 operates with decrypted/plaintext masks. Stated otherwise, although server 40 is oblivious to the content of the private images, it knows for instance whether a source image comprises a private item, and it also knows an approximate location of the respective private item via the respective plaintext mask.

[0077] Fig. 18 illustrates an enhancement of a privacy-preserving surveillance system according to some embodiments of the present invention. In some embodiments, privacy management server 40 (Fig. 5) is further endowed with an image task module 44 configured to carry out a specific task according to encrypted data stream 60 received from input sensor 14. One example of an image processing task comprises event detection (determining whether an image or sequence of images are indicative of an occurrence of a particular event). For instance, in a school surveillance embodiment, task module 44 may be configured to analyze images captured by a surveillance camera to determine whether the images are indicative of a fight or bullying incident. In a traffic monitoring embodiment, the task module may determine automatically whether a source image is indicative of an accident, traffic jam, etc. Other exemplary tasks include counting people in an image and determining whether said count exceeds a pre-determined threshold. Yet another exemplary task generically includes any image classification/labelling task, such as determining whether an image shows a particular type of object (e.g., weapon, personal ID, bank card, car license plate, etc.). An artisan will understand that although the above examples involve image processing, this aspect is not meant to be limiting and some embodiments may be adapted to processing other types of data such as sound files, text documents, etc. For instance, in a sound-processing embodiment, task module 44 may determine whether a sound captured by input sensor 14 is indicative of a gunshot, of people shouting, of insulting or discriminatory language, etc.

[0078] In some embodiments, task module 44 (Fig. 5) comprises an AI system 43b pre-trained to carry out the respective task. Several such examples are known in the art of computer vision; their architecture and training go beyond the scope of the present disclosure. AI system 43b may be pre-trained by AI training system 11 in the sense that system 11 may determine a set of optimized task module parameter values 45b (e.g., synapse weights, etc.) for instance via a machine learning process, and use values 45b to instantiate the runtime instance of image task module 44.

[0079] Task module 44 may operate in the encrypted domain, i.e., without decrypting source data. In such embodiments, module 44 may input an encrypted image and produce an encrypted

output comprising a result of executing the respective task, the respective output encrypted with the public administrative key k_{admin}^p associated with distribution server **30**. For instance, the output of task module **44** may comprise an encrypted version of a verdict or label (e.g., YES/NO according to whether data stream **60** is indicative of an occurrence of a specific event or not).
 5 Since module **44** executes in the encrypted domain, privacy-management server **40** is not aware of the task result.

[0080] In some embodiments, the output of task module **44** is proxy re-encrypted by engine **46** (Fig. **5**) using a re-encryption token of a selected user, to produce a re-encrypted task result **86** which is sent to distribution server **30** for delivery to a pre-determined notification device **13** (e.g., a smartphone of the selected user). In some embodiments, notification device **13** may also receive decrypted public image **63**, so that the respective user may get to see the publicly available image data in addition to being notified of the occurrence of the respective event or situation. For instance, a school principal (or security personnel) may receive a notification that there is a fight under way on the school premises, but he/she may not be able to see who is
 10 actually involved in the fight when such information is deemed private. Meanwhile, since task result **86** is only decipherable by the selected notification device, all users except the school principal, may be oblivious of the occurrence of the fight. Furthermore, owners/operators of server **40** are also unaware of such events.

[0081] Some embodiments are further enhanced by the addition of a super user which may be allowed to see all private information contained in a source image. Such a super user may represent an authority figure such as a school principal, a representative of a human resources department of a company, etc. Upon setting up the surveillance service, image distribution server **30** may create a pair of cryptographic keys, as well as a set of re-encryption tokens associated with the super user. In one such exemplary embodiment, in response to determining
 20 user masks and extracting private images, privacy management server **40** may proxy re-encrypt extracted private images associated with *all users* with the re-encryption token(s) of the super user, thus creating a composite private image only accessible to the super user. The respective re-encrypted private data is then sent to image distribution server **30** and further made accessible

to the super user together with decrypted public image **63**. The super user may decrypt the respective re-encrypted private image and thus completely reconstruct the source image according to public image **63** and the decrypted composite private image. Meanwhile, a user who is not in possession of the private encryption key of the super user may not see private data
5 belonging to another user.

[0082] Fig. **19** shows an exemplary computer system **90** configured to execute some of the methods described herein. Computer system **90** may represent any of client devices **12a-c**, as well as image distribution server **30** and privacy management server **40**. The illustrated hardware configuration is that of a personal computer; the configuration of other computing
10 appliances such as mobile telephones and servers may differ slightly from the one shown in Fig. **19**. Processor(s) **92** comprise a physical device (e.g. microprocessor, multi-core integrated circuit formed on a semiconductor substrate) configured to execute computational and/or logical operations with a set of signals and/or data. Such signals or data may be encoded and delivered to processor(s) **92** in the form of processor instructions, e.g., machine code. Processor(s) **92** may
15 include a central processing unit (CPU) and/or an array of graphics processing units (GPU).

[0083] Memory unit **93** may comprise volatile computer-readable media (e.g. dynamic random-access memory – DRAM) storing data and/or instruction encodings accessed or generated by processor(s) **92** in the course of carrying out operations. Input devices **94** may include computer keyboards, mice, trackpads, and microphones, among others, including the respective hardware
20 interfaces and/or adapters allowing a user to introduce data and/or instructions into computer system **90**. Output devices **95** may include display devices such as monitors and speakers among others, as well as hardware interfaces/adapters such as graphic cards, enabling the respective computing device to communicate data to a user. In some embodiments, input and output devices **94-95** share a common piece of hardware (e.g., a touch screen). Storage devices **96**
25 include computer-readable media enabling the non-volatile storage, reading, and writing of software instructions and/or data. Exemplary storage devices include magnetic and optical disks and flash memory devices, as well as removable media such as CD and/or DVD disks and drives. Network adapter(s) **97** include mechanical, electrical, and signaling circuitry for communicating

data over physical links coupled to an electronic communication network (e.g, network **15** in Fig. **1**) and/or to other devices/computer systems. Adapter(s) **97** may be further configured to transmit and/or receive data using a variety of communication protocols.

[0084] Controller hub **98** generically represents the plurality of system, peripheral, and/or chipset buses, and/or all other circuitry enabling the communication between processor(s) **92** and the rest of the hardware components of computer system **90**. For instance, controller hub **98** may comprise a memory controller, an input/output (I/O) controller, and an interrupt controller. Depending on hardware manufacturer, some such controllers may be incorporated into a single integrated circuit, and/or may be integrated with processor(s) **92**. In another example, controller hub **98** may comprise a northbridge connecting processor **92** to memory **93**, and/or a southbridge connecting processor **92** to devices **94**, **95**, **96**, and **97**.

[0085] The exemplary systems and methods described herein allow distributing data (e.g., recorded video, photographs, recorded audio, digital documents, etc.) to a plurality of users in a manner which preserves the privacy of the respective users. Some embodiments employ homomorphic encryption and proxy re-encryption techniques to manipulate the respective data so that selected portions of it are revealed according to an identity of the user currently accessing the respective data.

[0086] One exemplary application of some embodiments comprises video surveillance, wherein the distributed data includes a stream of images received from a surveillance camera. Some embodiments employ image recognition techniques to determine whether an image contains an item deemed confidential by a selected user (e.g., a specific person or face, a specific license plate, etc.), and manipulate and selectively encrypt the respective image so that only the respective user may see the confidential item. Meanwhile, other users may be given access to another version of the same image, wherein the confidential item is obscured (e.g., concealed, cut out, scrambled, etc.).

[0087] One exemplary use case comprises monitoring a schoolyard for signs of bullying, fights, and verbal aggression. In some embodiments, selected users (e.g., parents) may designate some

of the children as private items. Images of the schoolyard captured by a video camera may be distributed to multiple users. However, images distributed to the school principal and the parent of a child deemed private will show the face of the respective child, while in images distributed to all other users the face may be obscured or scrambled. Such manipulations may for instance preserve the privacy of a bullied child and/or delay disclosing the identity of an aggressor until an investigation of the incident is carried out.

[0088] Applications of some embodiments are not limited to surveillance. In another example, a camera records a presentation of a product or prototype. The images are then transmitted to multiple remote users, for instance in a videoconference format. However, distinct users may receive distinct versions of the same image. For instance, users that have signed a non-disclosure agreement may be shown the respective product or prototype, while in images distributed to other users the respective item may be obscured/scrambled.

[0089] The nature of the items deemed private/confidential may differ greatly among embodiments. Some examples include, among others, an offensive hand gesture, an item of clothing (headscarf, swimsuit, etc.), an item of jewelry, a specific body part (bare leg, breast, etc.), a weapon, a company logo, a body lying on the ground (potentially a homeless person, or person in need of medical help), and a person in uniform (e.g., police, medical personnel). Artificial intelligence system 43 (Fig. 5) may be trained to recognize any such type of private item within a source image. Subsequently, some users will see an image of the respective items while others will not.

[0090] Many conventional video surveillance systems use encryption to prevent unauthorized access to the acquired images. Some such systems are also augmented with automatic image recognition and/or image segmentation functionality. However, conventional surveillance systems first decrypt the source images in preparation for image recognition. For instance, a conventional computer system performing image analysis typically also possesses the cryptographic keys for decrypting the source images. In contrast, by leveraging homomorphic encryption some embodiments of the present invention perform automatic item detection/mask

construction directly in the encrypted domain, i.e., without first decrypting the source images. In particular, a privacy management server as described herein does not even have the keys for decrypting the source data. Consequently, in embodiments of the present invention, the computer system performing image recognition and/or segmentation is oblivious to the content of the analyzed images, which substantially enhances the privacy of the system's users.

[0091] The use of homomorphic encryption by some embodiments of the present invention also allows decoupling the user management/image distribution activities from the image analysis activities. In an exemplary privacy-preserving video surveillance system as illustrated in Fig. 1, servers 30 and 40 may be owned and operated by separate entities. In one exemplary use-case scenario illustrating the advantages of some embodiments of the present invention, a company A owns and operates input sensor(s) 14 and distribution server 30 and contracts out image processing services, i.e., services provided by server 40, to another company B. Sensors 14 may collect images from an office building, and company A may be interested to automatically detect events such as anomalous office dynamics, a presence of an unknown person, etc., to determine the attendance at certain office events, to determine when certain employees arrive at work or clock out, etc. Company B can provide such services in a privacy-preserving manner, since server 40 does not have access to unencrypted data and further lacks the information to decrypt the incoming source data. Instead, image segmentation and/or other task execution are carried out in the encrypted domain, and the results of such operations are only decryptable by computer systems (e.g., server 30, selected client devices 12a-c) operated by representatives of company A. Privacy is further strengthened by the fact that in embodiments as illustrated in Figs. 11 and 13, distribution server 30 may not have access to the source data *per se*, but only to its "public part", i.e., the part of the source images that does not show private/confidential items.

[0092] Applications of some embodiments are not limited to image processing/video surveillance, and can be adapted to the processing of sound files, documents, and electronic messages, among others. In one such exemplary embodiment, a target person's voice may be selected as a private item. Source data such as a sound recording may be processed as shown herein, i.e., may be split into a private part and a public part, wherein the private part may consist

of a segment of the source recording comprising utterances of the target person. The private part may then be proxy re-encrypted with a token corresponding to a selected subset of users. When reconstructing the respective sound recording, the selected users may hear the target person's speaking, while other users may not. Another exemplary embodiment may distort/scramble
5 utterances of certain words (e.g., swearing, selected names, etc.).

[0093] In an exemplary document- or message-processing embodiment, private items may comprise certain names, addresses, telephone numbers, credit card or bank account numbers, etc. In some embodiments, private items may comprise entire parts of a document, for instance a specific section/chapter, parts having a specific author, parts addressing a specific subject. In yet
10 another exemplary embodiment, private items may comprise parts of a conversation (e.g., electronic message exchange) that indicate a particular sentiment, such as anger, menace, suicidal thoughts, explicit sexual intent, etc. Item detectors 42 may use a set of rules or a pre-trained artificial intelligence system to automatically identify such private items in an encrypted source document. Using selective proxy re-encryption techniques as shown herein, the same
15 document may then be distributed to multiple users in a manner wherein selected users may see the respective private items in plaintext, while other users may not.

[0094] It will be clear to one skilled in the art that the above embodiments may be altered in many ways without departing from the scope of the invention. Accordingly, the scope of the invention should be determined by the following claims and their legal equivalents.

CLAIMS

What is claimed is:

1. A method of distributing customized privacy-preserving images to a plurality of users, the method comprising employing at least one hardware processor of a privacy management server to:
in response to receiving an encrypted source image decryptable with an administration key, perform an encrypted-domain image segmentation of the source image to produce a plurality of user-specific encrypted private images, wherein:
a selected private image comprises a region of the source image selected to show a private item of a selected user of the plurality of users, and
another private image comprises another region of the source image selected to show a private item of another user of the plurality of users;
in response to the image segmentation, perform an encrypted-domain key change procedure to produce a plurality of user-specific re-encrypted images, wherein:
a selected re-encrypted image comprises a result of transforming the selected private image from being decryptable with the administration key to being decryptable with a private key of the selected user, and
another re-encrypted image comprises a result of transforming the other private image from being decryptable with the administration key to being decryptable with a private key of the other user; and
transmit the plurality of user-specific re-encrypted images to an image distribution server for further distribution to client devices configured to reconstruct user-specific plaintext versions of the source image.
2. The method of claim 1, wherein:
performing the encrypted-domain image segmentation of the source image further comprises determining an encrypted public image comprising regions of

4 the source image selected to show neither the private item of the selected
 5 user nor the private item of the other user;
 6 wherein the method further comprises employing at least one hardware processor
 7 of the privacy management server to transmit the encrypted public image
 8 to the image distribution server for decryption and further distribution to
 9 client devices; and
 10 wherein the client devices are configured to reconstruct user-specific plaintext
 11 versions of the source image further according to a decrypted public image
 12 received from the image distribution server.
 13

1 3. The method of claim 1, further comprising employing at least one hardware processor
 2 of the image distribution server to:
 3 in response to receiving the selected re-encrypted image, select a device from a
 4 plurality of client devices according to whether the selected device is
 5 operated by the selected user; and
 6 in response to selecting the client device, transmit the selected re-encrypted image
 7 to the selected device.
 8

1 4. The method of claim 3, further comprising employing at least one hardware
 2 processor of the image distribution server to:
 3 in response to receiving the other re-encrypted image, select another
 4 device from the plurality of client devices according to whether the
 5 other device is operated by the other user; and
 6 in response to selecting the other device, transmit the other re-encrypted
 7 image to the other device.
 8

1 5. The method of claim 1, wherein determining the selected private image comprises:
 2 employing a pre-trained item detector to calculate a mask identifying the region of
 3 the source image showing the private item of the selected user, the mask

4 calculated in the encrypted domain and decryptable with the
5 administration key; and
6 determining the selected private image according to a pixel-wise multiplication of
7 the encrypted source image and the mask.

8

1 6. The method of claim 1, wherein the encrypted source image is encrypted according to
2 a homomorphic encryption scheme.

3

1 7. The method of claim 1, wherein a plaintext version of the source image reconstructed
2 by a client device operated by the selected user shows the private item of the
3 selected user and obscures the private item of the other user.

4

1 8. The method of claim 1, wherein the private item comprises an item selected from a
2 group consisting of a person and a human face.

3

1 9. The method of claim 1, wherein the private item comprises a bank card.

2

1 10. The method of claim 1, wherein the private item comprises a trademark.

2

1 11. A computer system comprising a privacy management server configured to:
2 in response to receiving an encrypted source image decryptable with an administration
3 key, perform an encrypted-domain image segmentation of the source image to
4 produce a plurality of user-specific private images, wherein:
5 a selected private image comprises a region of the source image selected to show
6 a private item of a selected user of the plurality of users, and
7 another private image comprises another region of the source image selected to
8 show a private item of another user of the plurality of users;
9 in response to the image segmentation, perform an encrypted-domain key change
10 procedure to produce a plurality of user-specific re-encrypted images, wherein:

11 a selected re-encrypted image comprises a result of transforming the selected
 12 private image from being decryptable with the administration key to being
 13 decryptable with a private key of the selected user, and
 14 another re-encrypted image comprises a result of transforming the other private
 15 image from being decryptable with the administration key to being
 16 decryptable with a private key of the other user; and
 17 transmit the plurality of user-specific re-encrypted images to an image distribution
 18 server for further distribution to client devices configured to reconstruct
 19 user-specific plaintext versions of the source image.
 20

1 12. The computer system of claim 11, wherein:
 2 performing the encrypted-domain image segmentation of the source image further
 3 comprises determining an encrypted public image comprising regions of
 4 the source image selected to show neither the private item of the selected
 5 user nor the private item of the other user;
 6 wherein the privacy management server is further configured to transmit the
 7 encrypted public image to the image distribution server for decryption and
 8 further distribution to client devices; and
 9 wherein the client devices are configured to reconstruct user-specific plaintext
 10 versions of the source image further according to a decrypted public image
 11 received from the image distribution server.
 12

1 13. The computer system of claim 11, further comprising the image distribution server
 2 and wherein the image distribution server is further configured to:
 3 in response to receiving the selected re-encrypted private image, select a device
 4 from a plurality of client devices according to whether the selected device
 5 is operated by the selected user; and
 6 in response to selecting the client device, transmit the selected re-encrypted
 7 private image to the selected device.

8

1

14. The computer system of claim 13, wherein the image distribution server is further configured to:

2

3

in response to receiving the other re-encrypted private image, select

4

another device from the plurality of client devices according to

5

whether the other device is operated by the other user; and

6

in response to selecting the other device, transmit the other re-encrypted private image to the other device.

7

8

1

15. The computer system of claim 11, wherein determining the selected private image comprises:

2

3

employing a pre-trained item detector to calculate a mask identifying the region of

4

the source image showing the private item of the selected user, the mask

5

calculated in the encrypted domain and decryptable with the

6

administration key; and

7

determining the selected private image according to a pixel-wise multiplication of the encrypted source image and the mask.

8

9

1

16. The computer system of claim 11, wherein the encrypted source image is encrypted according to a homomorphic encryption scheme.

2

3

1

17. The computer system of claim 11, wherein a plaintext version of the source image reconstructed by a client device operated by the selected user shows the private item of the selected user and obscures the private item of the other user.

2

3

4

1

18. The method of claim 1, wherein the private item comprises an item selected from a group consisting of a person and a human face.

2

3

1

19. The computer system of claim 11, wherein the private item comprises a bank card.

2

1

20. The computer system of claim 11, wherein the private item comprises a trademark.

2

1

21. A non-transitory computer-readable medium storing instructions which, when executed by at least one hardware processor of a privacy management server, cause the privacy management server to:

3

4

in response to receiving an encrypted source image decryptable with an administration

5

key, perform an encrypted-domain image segmentation of the source image to

6

produce a plurality of user-specific private images, wherein:

7

a selected private image comprises a region of the source image selected to show

8

a private item of a selected user of the plurality of users, and

9

another private image comprises another region of the source image selected to

10

show a private item of another user of the plurality of users;

11

in response to the image segmentation, perform an encrypted-domain key change

12

procedure to produce a set of user-specific re-encrypted images, wherein:

13

a selected re-encrypted image comprises a result of transforming the selected

14

private image from being decryptable with the administration key to being

15

decryptable with a private key of the selected user, and

16

another re-encrypted image comprises a result of transforming the other private

17

image from being decryptable with the administration key to being

18

decryptable with a private key of the other user; and

19

transmit the plurality of user-specific re-encrypted images to an image distribution server

20

for further distribution to client devices configured to reconstruct user-specific

21

plaintext versions of the source image.

22