

TITLE: SLIDING SHUTTERS

DESCRIPTION

Technical Field

The invention relates to sliding shutters, particularly, but not exclusively, for use as doors for the load carrying compartments of commercial motor vehicles.

Background Art

It is well known to provide a roller or 'up and over' shutter or door for closing a commercial vehicle body such as a van or truck body in the form of a vertically sliding member consisting of a series of planks or laths made, for example, of aluminium or plywood which are hinged together and which are guided at their ends in suitable tracks in the vehicle body. Similar shutters are used for closing commercial premises and to improve the security of domestic premises.

It is an object of the invention to provide an improved sliding or roller shutter or door.

Disclosure of the Invention

According to the invention a sliding shutter comprises a plurality of laths hinged together by elastomeric members attached to adjacent edges of the laths, wherein the mutually adjacent edges of the laths are formed with longitudinally extending key-hole shape slots and the elastomeric members are formed with opposite enlarged portions received in the slots in the laths, characterised in that the slots are positioned such that the elastomeric members are tensioned when the laths are co-planar, such as

when the shutter is closed, by being bent, to cause the mutually adjacent edges of the laths to be pulled together, and that hinging the laths away from the co-planar causes a reduction in the tension of the elastomeric members by unbending the elastomeric members.

The laths or planks are preferably made from a high impact plastics such as UPVC. Suitably the laths or planks may be made by an extrusion process. If desired the laths or planks may be twin-walled and the resulting cavity or cavities may be filled, if desired, with a thermally insulating material.

Where the elastomeric hinges extend along the full length of the laths or planks, an air and watertight door or shutter can be produced.

Brief Description of the Drawings

The invention is diagrammatically illustrated, by way of example, in the accompanying drawings, in which:-

Figure 1 is a perspective view of an 'up and over' shutter door for a commercial motor vehicle body;

Figure 2 is a cross-section through a shutter lath;

Figures 3a and 3b are scrap cross-sectional views of a pair of laths of the kind shown in Figure 2, and showing their manner of interconnection and articulation;

Figure 4 is a scrap plan view of a shutter showing its associated guide members, and

Figure 5 is a scrap end view of a shutter showing how the guide members are received in a guide channel or track.

Best Mode for Carrying Out the Invention

In the drawings, an 'up and over' shutter door for a commercial motor vehicle body is shown which is conventional in its general arrangement and consisting of a sliding shutter 1 formed by a series of generally similar lathes or planks 2 hinged together along their mutually abutting edges 5 and mounted at their respective ends, which form opposite edges of the shutter, in a parallel pair of L-shaped tracks 3, whereby the shutter is movable along the tracks to open and close the door. The tracks 3, which are generally U-shaped in cross section, are mounted in a commercial motor vehicle body (not shown) so that the vertical limbs of the tracks 3 extend down both sides of the door opening and so that the horizontal limbs of the tracks 3 extend along the vehicle body near to its roof. Conventionally the planks or lathes 2 have been made of plywood joined together with metal hinges or have been made from aluminium extrusions formed integrally at their edges with mating hinge portions.

As shown in Figure 1, webbing tapes 12 are fixed to the shutter 1 and in conventional fashion are wound around a spring-urged roller 13 mounted in the vehicle body at the top of the door opening to assist the raising and lowering of the shutter. As can be seen in Figures 4 and 5, guide members are fixed to the ends of the lathes and are guided within the tracks 3 to support the shutter in position during use.

In the present embodiment, the planks or lathes 2 are

extruded from high impact UPVC plastics to form the hollow or twin-walled section best seen in Figure 2. In this embodiment, the laths are generally rectangular in cross-section and have an opposed pair of face webs 9 united by opposite edge webs 5 and internal cross webs 10 which extend between the faces 9. If desired the cavities 11 defined by the hollow section can be filled with a thermally insulating material, not shown, e.g. foam plastics material.

The edges 5 of the lath 2 are formed with oppositely disposed part-cylindrical key-hole slots 4 which extend along the edges 5 and are adapted to receive the correspondingly shaped part-cylindrical opposite edge portions 7 of an elastomeric member or strip 6 which forms a hinge uniting the planks or laths. The elastomeric hinges comprise constant cross-section strips of rubber of the like elastomer having enlarged part-cylindrical opposite edge portions 7 joined by a web portion 8 to resemble a dumb-bell in cross-section.

The hinge members 6 are engaged with the laths 2 by sliding one lengthwise with respect to the other so that the enlarged portions 7 of the member 6 are engaged in the key-hole slots 4. The hinge members 6 and the laths are preferably co-extensive. As shown in Figure 3a the hinge members 6 become bent and are thus slightly tensioned or stretched when the laths 2 are in a planar relationship, such as when the shutter is closed, to improve the rigidity of the shutter.

Although as illustrated, the planks or laths are of

double wall or skin construction they could, of course, be of single wall. Equally they could be extruded from aluminium or fabricated from other materials. Also the cross-sectional shape of the elastomeric member 6 could be different from that shown.

Industrial Applicability

The specific embodiment thus provides a sliding door or shutter which is of light weight, of high strength, of good thermally insulating properties, which is economical to produce, and which requires little or no maintenance.

CLAIMS

1. A sliding shutter (1), comprising a plurality of laths (2) hinged together by elastomeric members (6) attached to adjacent edges (5) of the laths, wherein the mutually adjacent edges (5) of the laths (2) are formed with longitudinally extending key-hole shape slots (4) and the elastomeric members (6) are formed with opposite enlarged portions (7) received in the slots (4) in the laths, characterised in that the slots (4) are positioned such that the elastomeric members (6) are tensioned when the laths (2) are co-planar, such as when the shutter (1) is closed, by being bent, to cause the mutually adjacent edges (5) of the laths (2) to be pulled together, and that hinging the laths (2) away from the co-planar causes a reduction in the tension of the elastomeric members (6) by unbending the elastomeric members.

2. A shutter according to claim 1, characterised in that the elastomeric members (6) are of constant cross-section and in that the opposite enlarged portions (7) are joined by a web (8).

3. A shutter according to claim 2, characterised in that the elastomeric members (6) are dumb-bell shaped in cross-section.

4. A shutter according to any preceding claim, characterised in that the elastomeric members (6) extend



along the full lengths of the laths (2).

5. A shutter according to any preceding claim, characterised in that the laths (2) are formed from a high impact plastics, such as UPVC.

6. A shutter according to any preceding claim, characterised in that the laths (2) have hollow interiors (11).

7. A shutter according to claim 6, characterised in that the hollow interior (11) of the laths (2) is filled with a thermally insulating material.