CLAIMS

WHAT IS CLAIMED IS:

1. A method for switching control of a monitoring state, performed by a network device, comprising:

configuring reception configuration information corresponding to a multicast broadcast service (MBS) for a terminal, wherein the reception configuration information is configured for the terminal to receive the MBS in a discontinuous reception mode; and

sending target control information to the terminal, wherein the target control information is configured to activate or deactivate reception monitoring of the MBS of the terminal;

wherein the target control information comprises indication information of the MBS;

wherein, the indication information of the MBS comprises at least one of: an MBS identifier, or an MBS scheduling identifier;

wherein the MBS scheduling identifier comprises at least one of: a dynamic scheduling identifier, or a semi-persistent scheduling identifier.

2. The method according to claim 1, wherein the target control information is configured to activate the reception monitoring of the MBS of the terminal, and the target control information comprises at least one of:

a wake-up signal, target downlink control information (DCI), or a target media access control layer control element (MAC CE);

wherein the target control information is configured to deactivate the reception monitoring of the MBS of the terminal, and the target control information comprises at least one of:

a go-to-sleep signal, the target DCI, or the target MAC CE.

3. The method according to claim 2, wherein the target DCI is identified by a power saving radio network temporary identification (PS-RNTI).

4. The method according to claim 1, wherein the target control information further comprises an activation state information of the MBS;

wherein, the activation state information of the MBS comprises at least one of: an activated state, or a deactivated state.

5. The method according to any of claims 1 to 4, wherein configuring the reception configuration information corresponding to the MBS for the terminal comprises:

configuring the reception configuration information corresponding to the MBS for the terminal through a radio resource control (RRC) message.

6. The method according to claim 5, wherein the RRC message comprises an initial monitoring state corresponding to the MBS configured for the terminal, the initial monitoring state comprises stopping the reception monitoring of the MBS or starting the reception monitoring of the MBS.

7. The method according to any of claims 1 to 6, wherein a number of MBSs is one or more, and in response to the number of the MBSs is more than one, reception configuration information corresponding to different MBSs are different.

8. The method according to any of claims 1 to 7, wherein the reception configuration information corresponding to the MBS comprises at least one of:

a service monitoring cycle of the MBS;

a first timer configured to indicate a service monitoring duration in each service monitoring cycle;

a service-monitoring start position in each service monitoring cycle;

a second timer configured to indicate that the network device has new data to be scheduled;

a third timer configured to indicate the terminal to perform a hybrid automatic repeat request (HARQ) feedback; or

a fourth timer configured to indicate the terminal to receive data re-transmitted by the network device.

9. A method for switching control of a monitoring state, performed by a terminal, comprising:

starting or stopping reception monitoring of a multicast broadcast service (MBS) based on an indication of received target control information and reception configuration information corresponding to the MBS configured by a network device for the terminal, wherein the target control information is configured to activate or deactivate the reception monitoring of the MBS of the terminal, and the reception configuration information is

configured for the terminal to receive the MBS in a discontinuous reception mode;

wherein the target control information comprises indication information of the MBS;

wherein, the indication information of the MBS comprises at least one of: an MBS identifier, or an MBS scheduling identifier;

wherein the MBS scheduling identifier comprises at least one of: a dynamic scheduling identifier, or a semi-persistent scheduling identifier.

10. The method according to claim 9, wherein the target control information further comprises an activation state information of the MBS;

wherein, the activation state information of the MBS comprises at least one of: an activated state, or a deactivated state.

11. The method according to claim 9 or 10, wherein starting or stopping the reception monitoring of the MBS based on the indication of the received target control information and the reception configuration information corresponding to the MBS configured for the terminal by the network device comprises:

in response to determining that the target control information is configured to activate the reception monitoring of the MBS of the terminal, starting the reception monitoring of the MBS based on the indication of the target control information and the reception configuration information; or

in response to determining that the target control information is configured to deactivate the reception monitoring of the MBS of the terminal, stopping the reception monitoring of the MBS based on the indication of the target control information and the reception configuration information.

12. The method according to any of claims 9 to 11, further comprising one of:

in response to determining that the terminal is in a state of the reception monitoring of the MBS being stopped, monitoring the target control information configured to activate the reception monitoring of the MBS of the terminal;

in response to determining that the terminal is in a state of the reception monitoring of the MBS being started, monitoring the target control information configured to deactivate the reception monitoring of the MBS of the terminal;

determining an initial monitoring state corresponding to the MBS based on an indication

of a radio resource control (RRC) message sent by the network device; or

determining an initial monitoring state corresponding to the MBS based on a protocol agreement;

wherein the initial monitoring state comprises stopping the reception monitoring of the MBS, or starting the reception monitoring of the MBS.

13. The method according to any of claims 9 to 12, further comprising:

monitoring the target control information at a target time domain position configured for monitoring the target control information.

14. The method according to claim 13, further comprising one of:

in response to the target control information being monitored at the target time domain position, and in response to a bit value of the target control information being a first predefined value, determining that the target control information configured to indicate to activate the reception monitoring of the MBS of the terminal is monitored;

in response to the target control information being monitored at the target time domain position, and in response to a bit value of the target control information being a second predefined value, determining that the target control information configured to indicate to deactivate the reception monitoring of the MBS of the terminal is monitored;

in response to the target control information being not monitored at the target time domain position, and in response to determining that the terminal is in a state of the reception monitoring of the MBS being stopped, starting the reception monitoring of the MBS based on the reception configuration information; or,

in response to the target control information being not monitored at the target time domain position, and in response to determining that the terminal is in a state of the reception monitoring of the MBS being started, stopping the reception monitoring of the MBS based on the reception configuration information.

15. The method according to claim 13, wherein an offset value of the target time domain position relative to a specified time domain position in each target cycle is a predetermined offset value.

16. The method according to claim 15, wherein a cycle duration of the target cycle is a positive integer multiple of a service monitoring cycle of the MBS or a positive integer

multiple of a duration of a paging cycle, or

wherein the specified time domain position comprises at least one of:

a service-monitoring start position of the MBS, a paging-monitoring start position, or a change-starting indication position of a multicast control channel.

17. The method according to any of claims 9 to 16, wherein a number of MBSs is one or more, and in response to the number of the MBSs is more than one, reception configuration information corresponding to different MBSs are different.

18. The method according to any of claims 9 to 17, wherein the reception configuration information corresponding to the MBS comprises at least one of:

a service monitoring cycle of the MBS;

a first timer configured to indicate a service monitoring duration in each service monitoring cycle;

a service-monitoring start position in each service monitoring cycle;

a second timer configured to indicate that the network device has new data to be scheduled;

a third timer configured to indicate the terminal to perform a hybrid automatic repeat request (HARQ) feedback; or

a fourth timer configured to indicate the terminal to receive data re-transmitted by the network device.

19. The method according to claim 18, wherein starting the reception monitoring of the MBS comprises at least one of:

starting at least one of the first timer, the second timer, the third timer or the fourth timer;

starting monitoring of a control channel corresponding to the MBS; or

starting monitoring of a data channel corresponding to the MBS; or

wherein stopping the reception monitoring of the MBS comprises at least one of:

stopping or not starting at least one of the first timer, the second timer, the third timer or the fourth timer;

stopping monitoring of a control channel corresponding to the MBS; or

stopping monitoring of a data channel corresponding to the MBS.

20. A device for switching control of a monitoring state, comprising:

a processor; and

a memory for storing instructions executable by the processor;

wherein the processor is configured to perform the method for switching control of a monitoring state according to any of claims 1 to 8, or perform the method for switching control of a monitoring state according to any of claims 9 to 19.