

DESCRIPTION

TITLE OF INVENTION: INFORMATION PROCESSING
APPARATUS, INFORMATION PROCESSING METHOD AND
5 PROGRAM, INFORMATION PROCESSING APPARATUS, VACANT
SPACE GUIDANCE SYSTEM, VACANT SPACE GUIDANCE
METHOD AND PROGRAM, IMAGE DISPLAY SYSTEM, IMAGE
DISPLAY METHOD AND PROGRAM

10 TECHNICAL FIELD

[0001] The present invention relates to an
information processing apparatus, an information
processing method and a program, an information
processing apparatus, a vacant space guidance
15 system, a vacant space guidance method and a
program, an image display system, an image
display method and a program.

BACKGROUND ART

[0002] Navigation technologies are utilized in
20 various fields such as guiding to a destination
and presenting an operating procedure during an
operation. The navigation technologies are to
provide support for facilitating a certain
action, and hence systems which allow
25 understanding as intuitive as possible have been
demanded hitherto. As one of such systems, there
exists a navigation technology utilizing what is
called an augmented reality which displays data
of texts, images, and so on managed in a computer

in a manner overlaid on a real environment, so as to give supplementary information to the real environment.

[0003] For example, as a navigation technology
5 for shopping, there has been disclosed a technology utilizing augmented reality (hereinafter abbreviated AR) to perform three-dimensional navigation on a route to a target attraction or on display information of products
10 recommended by a shop side in a theme park or a shopping mall (see, for example, Patent Literature 1). More specifically, it is a technology to calculate the position and posture of a mobile information terminal at a time of
15 imaging, and use a marker shown on the image imaged by the mobile information terminal to display predetermined information, which is related to the marker in advance, in a manner overlaid on the imaged image. Note that the AR
20 is a technology to display data of texts, figures, still images, moving images, and so on managed in a computer (hereinafter referred to as computer-graphics image data) in a manner overlaid on a real environment, so as to give
25 supplementary information.

[0004] Further, there is known a technology such that products to buy are registered in a list in a mobile terminal in advance, and when the user walks near a product registered in the list,

product information of this product is displayed on the mobile terminal (see, for example, Patent Literature 2).

[0005] Similarly, there have been developed
5 several technologies for navigating to a vacant space in a parking lot. In a shopping center, amusement park, or large public parking lot, it is difficult for the driver of a car to comprehend where there is a vacant space, and
10 hence guidance information is necessary. Accordingly, in certain parking lots, for example, sensors are provided in respective parking spaces for detecting parking statuses. Then, the parking lot is divided into plural
15 blocks, and guidance of vacant space is given to the driver by displaying "full", "vacant", or the like in each block on an electric sign or the like.

However, even when "full", "vacant" or the
20 like is displayed at the entrance of each block, the driver is not able to comprehend the status of "full" or "vacant" unless he or she actually gets close to this block. Alternatively, there are also parking lots employing an electric sign
25 listing information of the parking lot, but it is difficult for a driver to reach his/her target space by looking at the electric sign while driving. Further, one-way passages are often set in the parking lot, where there is a problem that

even when the driver finds "vacant", it is still difficult for the driver to reach a vacant parking space.

To solve such problems, for example, Patent Literature 3 disclosed a system to reflect vacant statuses of a parking lot on a car navigation system. The method of Prior Art Literature 1 detects a car which is about to leave a vacant space, and this situation is transmitted to a car navigation system of another car, thereby guiding a vacant space existing in the vicinity.

[0006] Similarly, in the field of ships, various navigation technologies have been developed. In operation of a ship, there is performed navigation with marine charts particularly in old days, or navigation utilizing a radar device, GPS, and/or the like nowadays. Incidentally, in the case of a ship cruising in a coastal area, the above-described equipment is fully used for avoiding any trouble related to obstacles below sea level, such as stranding on a reef. Also, not limited in coastal areas, not only visual observation but also information from equipment is utilized on the sea in order to avoid contacting with another ship due to dense fog or the like.

Although it is possible to increase avoidance of stranding or contacting with another ship by utilizing these devices, there is

demanded a system which is capable of detecting and avoiding hazards more intuitively. For example, Non-Patent Literature 1 disclosed a system which three-dimensionally displays an automatic identification system (AIS) and an electronic marine chart in combination. However, eventually, a shipman is required to understand a graph display as shown in Fig. 35 of Non-Patent Literature 1, and judge collision or the like.

10 CITATION LIST

PATENT LITERATURE

[0007] Patent Literature 1: Japanese Laid-open Patent Publication No. 2004-48674

Patent Literature 2: Japanese Laid-open Patent Publication No. 10-198731

Patent Literature 3: Japanese Laid-open Patent Publication No. 2006-209429

NON PATENT LITERATURE

[0008] Non-Patent Literature 1: "Intermediate report of study on collision and strand avoiding system as fail safe", Junji Hukuto and three others, [online], [searched on February 10, 2010], Internet
<<http://www.nmri.go.jp/main/publications/paper/pdf/f/2A/03/00/PNM2A030043-00.pdf>>

SUMMARY OF INVENTION

TECHNICAL PROBLEM

[0009] However, in order to allow intuitive understanding in an environment where the status

changes constantly, it is demanded to present information in a state as close as possible to the reality and instantly perceivable with respect to the timing of obtaining information, the type of information, and so on.

[0010] The present invention is made in view of such a problem, and it is an object thereof to provide strengthened perception for allowing intuitive understanding by displaying information in real time in an overlaid manner at arbitrary timing by utilizing an augmented reality technology considering the current status of a navigation target in a constantly variable situation.

[0011] In the technology disclosed in Patent Literature 1, for example, it is possible that the navigation information may include information which is recommended by the shop side but is unnecessary for a user. On the other hand, the technology disclosed in Patent Literature 2 can display product information of a product to buy which is registered in the list in advance on the mobile terminal. However, it is not always the case that the user goes shopping at a time when a product is registered in the list, and thus it is possible that the product to buy is out of stock or the price of the product to buy is changed when the user goes shopping.

Moreover, in order to allow intuitive

understanding in an environment where the status changes constantly, such as the price of product or inventory status, it is demanded to present information in a state as close as possible to
5 the reality and instantly perceivable with respect to the timing of obtaining information, the type of information, and so on.

[0012] The present invention is made in view of such a problem, and it is a first object thereof
10 to provide a support for facilitating obtaining product information or guidance information of a product to buy at arbitrary timing.

[0013] Besides that, for example, in the structure as in Patent Literature 3, the car
15 navigation system or the like needs to store map information of parking lots, which poses a problem that the map information of the car navigation system needs to be updated every time the parking lot is renovated, or the like.

[0014] Furthermore, in order to allow intuitive
20 understanding in an environment where the status changes constantly, such as the status of a vacant space in a parking lot, it is demanded to present information in a state as close as
25 possible to the reality and instantly perceivable with respect to the timing of obtaining information, the type of information, and so on.

[0015] The present invention is made in view of such a problem, and it is a second object thereof

to provide a technology which allows a driver to find and reach a target vacant space, without updating map information of the car navigation system provided in a car, or even when the car navigation system is not provided in the car.

[0016] Besides that, in order to allow intuitive understanding in an environment where the status changes constantly, such as operation of a ship for example, it is demanded to present

information in a state as close as possible to the reality and instantly perceivable with respect to the timing of obtaining information, the type of information, and so on.

[0017] The present invention is made in view of such a problem, and it is a third object thereof to provide information which is beneficial while a ship is cruising in a manner that a shipman or the like can intuitively comprehend the situation.

SOLUTION TO PROBLEM

[0018] Accordingly, an information processing system of the present invention is an information processing system having an augmented reality presenting device capable of combining an image in real space with computer-graphics image data and displaying the combined image and a managing device managing at least one of inventory information and sales information of respective products posted on a flier, wherein the augmented

reality presenting device has: an imaging unit obtaining image data related to a product posted on the flier by imaging; and a first transmitting unit transmitting the image data related to the product obtained by the imaging unit to the managing device, wherein the managing device has: a first obtaining unit determining, upon reception of the image data related to the product from the augmented reality presenting device, the product by analyzing the image data related to the product, and obtaining at least one of the inventory information and the sales information of the product; and a second transmitting unit transmitting at least one of the inventory information and the sales information of the product obtained by the first obtaining unit to the augmented reality presenting device, and wherein the augmented reality presenting device further has a presenting unit combining computer-graphics image data indicating at least one of the inventory information and the sales information of the product transmitted from the managing device with an image of the flier in real space and presenting the combined image.

[0019] Accordingly, an information processing apparatus of the present invention has: a vacant space information obtaining unit obtaining vacant space information of a parking lot; a vehicle

information obtaining unit obtaining a position
and a direction of a car in the parking lot; a
vacant space determining unit determining a
vacant space existing in a traveling direction of
5 the car based on the vacant space information
obtained in the vacant space information
obtaining unit, the position and the direction of
the car in the parking lot obtained in the
vehicle information obtaining unit, and
10 information related to position information of
respective vacant spaces of a parking lot map
stored in a storage device; an image generating
unit generating a virtual space image in the
parking lot which includes a vacant space object
15 indicating the vacant space determined in the
vacant space determining unit and indicates a
position of the vacant space; and a transmitting
unit transmitting the virtual space image
generated in the image generating unit to the
20 car.

[0020] Further, an information processing
apparatus of the present invention has: a vacant
space information obtaining unit obtaining vacant
space information of a parking lot; a vehicle
25 information obtaining unit obtaining a position
and a direction of a car in the parking lot; a
vacant space determining unit determining a
vacant space existing in a traveling direction of
the car based on the vacant space information

obtained in the vacant space information
obtaining unit, the position and the direction of
the car in the parking lot obtained in the
vehicle information obtaining unit, and
5 information related to position information of
respective vacant spaces of a parking lot map
stored in a storage device; and a transmitting
unit transmitting to the car a vacant space
object indicating the vacant space determined in
10 the vacant space determining unit and position
information representing a position of the vacant
space.

[0021] Accordingly, the present invention is an
image display system including a position
15 information obtaining device obtaining position
information of a ship, an information storage
device storing an electronic marine chart
including seafloor shapes and a tide table, an
image display device, and an image providing
20 device providing an image to the image display
device, wherein the image providing device
obtains a depth below sea level at a position of
the ship based on the position information of the
ship obtained in the position information
25 obtaining device, the tide table, and information
related to depths indicated on the electronic
marine chart, creates a virtual space image of a
seafloor shape below sea level at the depth at
the position of the ship based on the position

information, the depth below sea level, and
seafloor topography image data indicated on the
electronic marine chart, and provides the virtual
space image to the image display device, and
5 wherein the image display device displays the
virtual space image of the seafloor shape
provided by the image providing device in a
manner overlaid on a view from the image display
device.

10

ADVANTAGEOUS EFFECTS OF INVENTION

[0022] According to the present invention, in
order to allow intuitive understanding in a
navigation technology in an environment where the
15 status changes constantly, it becomes possible to
present information in a state as close as
possible to the reality and instantly perceivable
with respect to the timing of obtaining
information, the type of information, and so on.

20 For example, according to the present
invention, it is possible to provide a support
for facilitating obtaining product information or
guidance information of a product to buy at
arbitrary timing.

25 [0023] Besides that, for example, according to
the present invention, it is possible to provide
a technology which allows a driver to easily find
and reach a target vacant space, without updating
map information of the car navigation system

provided in a car, or even when the car navigation system is not provided in the car.

[0024] Besides that, for example, according to the present invention, it is possible to provide
5 information which is beneficial while a ship is cruising in a manner that a shipman or the like can intuitively comprehend the situation.

BRIEF DESCRIPTION OF DRAWINGS

10 [0025] [Fig. 1] Fig. 1 is a diagram schematically illustrating a structure of a shopping navigation system of Embodiment 1.

[Fig. 2A] Fig. 2A is a diagram illustrating a hardware structure of a shopping management
15 server.

[Fig. 2B] Fig. 2B is a diagram illustrating a hardware structure of a mobile terminal.

[Fig. 3A] Fig. 3A is a flowchart illustrating the flow of registration processing
20 of product to buy in the shopping navigation system of Embodiment 1.

[Fig. 3B] Fig. 3B is a flowchart illustrating presentation processing of product information of a product to buy and navigation
25 processing from a current location to a shop in the shopping navigation system of Embodiment 1.

[Fig. 4] Fig. 4 is a diagram illustrating a state that a user points at a product to buy posted on a flier and this state is captured in

the angle of view of an imaging unit of the mobile terminal.

[Fig. 5] Fig. 5 is a diagram illustrating a display example combining computer-graphics image data of product information with an image in real space.

[Fig. 6] Fig. 6 is a diagram illustrating an example of AR display when product information of an apple, which is a product to buy of the user, of three shops is obtained.

[Fig. 7] Fig. 7 is a diagram schematically illustrating an example of a database structure of a flier information DB.

[Fig. 8] Fig. 8 is a diagram schematically illustrating an example of a database structure of a user information DB.

[Fig. 9] Fig. 9 is a diagram schematically illustrating an example of a database structure of a product information DB.

[Fig. 10] Fig. 10 is a diagram schematically illustrating a structure of a shopping navigation system of Embodiment 2.

[Fig. 11A] Fig. 11A is a flowchart illustrating the flow of registration processing of a product to buy in the shopping navigation system of Embodiment 2.

[Fig. 11B] Fig. 11B is a flowchart illustrating presentation processing of product information of a product to buy and navigation

processing from a current location to a shop in the shopping navigation system of Embodiment 2.

[Fig. 12] Fig. 12 is a diagram illustrating an example of a shopping list.

5 [Fig. 13] Fig. 13 is a diagram illustrating an example of a system structure of a vacant space guidance system.

[Fig. 14] Fig. 14 is a diagram illustrating an example of a hardware structure of an
10 information processing apparatus.

[Fig. 15] Fig. 15 is a diagram illustrating an example of a hardware structure of a car.

[Fig. 16] Fig. 16 is a diagram illustrating an example of a software structure of the
15 information processing apparatus of Embodiment 3.

[Fig. 17] Fig. 17 is a diagram illustrating an example of a software structure of the car of Embodiment 3.

[Fig. 18] Fig. 18 is a sequence diagram
20 illustrating an example of processing in the vacant space guidance system of Embodiment 3.

[Fig. 19] Fig. 19 is a diagram illustrating an example of overlay display on a display of Embodiment 3.

25 [Fig. 20] Fig. 20 is a diagram illustrating an example of a software structure of an information processing apparatus of Embodiment 4.

[Fig. 21] Fig. 21 is a sequence diagram illustrating an example of processing in a vacant

space guidance system of Embodiment 4.

[Fig. 22] Fig. 22 is a diagram illustrating an example of overlay display on a display of Embodiment 4.

5 [Fig. 23] Fig. 23 is a diagram illustrating an example of a software structure of an information processing apparatus of Embodiment 5.

[Fig. 24] Fig. 24 is a sequence diagram illustrating an example of processing in a vacant
10 space guidance system of Embodiment 5.

[Fig. 25] Fig. 25 is a diagram illustrating an example of overlay display on a display of Embodiment 5.

[Fig. 26] Fig. 26 is a diagram illustrating
15 an example of a software structure of an information processing apparatus of Embodiment 6.

[Fig. 27] Fig. 27 is a diagram illustrating an example of a software structure of a car of Embodiment 6.

20 [Fig. 28] Fig. 28 is a sequence diagram illustrating an example of processing in a vacant space guidance system of Embodiment 6.

[Fig. 29] Fig. 29 is a diagram illustrating an example of a system structure of an image
25 display system of Embodiment 7.

[Fig. 30] Fig. 30 is a diagram illustrating an example of a hardware structure of an image providing device.

[Fig. 31] Fig. 31 is a diagram illustrating

an example of a hardware structure of an image display device.

[Fig. 32] Fig. 32 is a diagram illustrating an example of a software structure of an image
5 providing device.

[Fig. 33] Fig. 33 is a diagram illustrating an example of a software structure of the image display device.

[Fig. 34] Fig. 34 is a diagram illustrating
10 an example of displaying a virtual space image of a seafloor shape in an overlaid manner below sea level on a view from a display device.

[Fig. 35] Fig. 35 is a diagram illustrating an example of a system structure of an image
15 display system of an embodiment.

[Fig. 36] Fig. 36 is a diagram illustrating an example of a system structure of an image display system of Embodiment 9.

[Fig. 37] Fig. 37 is a diagram illustrating
20 an example of a system structure of an image display system of Embodiment 10.

[Fig. 38] Fig. 38 is a diagram illustrating a system structure of an image display system of Embodiment 11.

25

DESCRIPTION OF EMBODIMENTS

[0026] Hereinafter, embodiments of the present invention will be described based on the drawings.

[0027] <Embodiment 1>

Fig. 1 is a diagram schematically illustrating a structure of a shopping navigation system of Embodiment 1. As illustrated in Fig.

5 1, the shopping navigation system according to this embodiment includes a shopping management server 100 and a mobile terminal 200, which are connected communicably via a wireless communication line.

10 [0028] The user browses a flier 300 and chooses a product to buy from products posted on the flier 300. The user then points at the chosen product to buy and captures this state in the angle of view of an imaging unit of the mobile
15 terminal 200, and then the imaging unit generates image data of the state pointing at the product to buy. The mobile terminal 200 detects image data of the product to buy from the image data generated by the imaging unit. As a method for
20 detecting image data of the product to buy, it is conceivable that, for example, several finger shape patterns of a finger in a pointing state are prepared, and when image data which match or similar to these shape patterns of the finger are
25 detected in the image data, the image data are recognized as the finger, and an object existing within a certain distance from the finger in the direction of the finger is detected as a product to buy.

[0029] Upon detection of the image data of the product to buy, the mobile terminal 200 transmits the image data of the product to buy to the shopping management server 100. Upon reception
5 of the image data of the product to buy from the mobile terminal 200, the shopping management server 100 judges in a product matching unit 106 conformity between the image data of the respective products posted on the flier 300,
10 which are stored in a flier information DB 102, and the image data of the product to buy received from the mobile terminal 200, and judges whether or not the product to buy is a product posted on the flier 300. When the product to buy is a
15 product posted on the flier 300, a registration/inquiry unit 105 correlates the product to buy and the user and stores them in a user information DB 101. Thus, the product to buy of the user is registered in the shopping
20 management server 100.

[0030] After the product to buy is registered in the shopping management server 100, if the user wants to know transition of price information and inventory information of the product to buy, the
25 user holds the mobile terminal 200 over the flier 300 again, and captures the product to buy in the angle of view of the imaging unit of the mobile terminal 200. Thus, the image data of the product to buy are transmitted from the mobile

terminal 200 to the shopping management server 100. By analyzing the image data received from the mobile terminal 200, the product matching unit 106 of the shopping management server 100
5 detects that the image data are image data of the product posted on the flier 300. Then, the registration/inquiry unit 105 judges that this product is the product to buy of the user. Then, a product information retrieving unit 107 obtains
10 the latest (current) product information such as selling price and inventory information of the product to buy, and transmits the information to the mobile terminal 200. The mobile terminal 200 combines the computer-graphics image data
15 indicating the latest product information of the product to buy and an image in real space, and displays the combined image on a display. At this time, the computer-graphics image data indicating the product information are combined
20 with the image in real space so that the image data are displayed in the vicinity of the product to buy, so as to make it easy to comprehend that the product information is related to the product to buy.

25 [0031] A map information retrieving unit 108 obtains current location information of the mobile terminal 200, obtains address information of a shop which sells the product to buy, and obtains map information including the position

indicated by the current location information and the position indicated by the address information from a map information DB 104. Then, by using the obtained map information, the map information
5 retrieving unit 108 generates guidance information for guidance on a route from the current location of the mobile terminal 200 to the shop selling the product to buy, and transmits the information to the mobile terminal
10 200. By using the guidance information, the mobile terminal 200 combines computer-graphics image data for guidance on the route from the current location to the shop selling the product to buy with an image in real space, and displays
15 the combined image. Thus, by capturing a street in the angle of view of the imaging unit of the mobile terminal 200, the user can move to the shop while confirming on the display of the mobile terminal 200 the image in which the route
20 guidance by computer-graphics image data is combined with the image in real space of the street.

[0032] In this embodiment, augmented reality is presented by displaying the computer-graphics
25 image data at a position which matches with an image in real space on the display of the mobile terminal 200. Hereinafter, display of computer-graphics image data which gives such augmented reality may also be referred to as AR (Augmented

Reality) display. Note that there are various types of HMDs such as non-transmissive type, video transmission type and optical transmission type. Combination display (AR display) refers to
5 overlay display of computer-graphics image data at a matching position on an image in real space projected on a lens part of the HMD of any type. For example, for the optical transmission type, overlay display on a see-through image in real
10 space is performed, and for the video transmission type, overlay display on an image in real space imaged by a video camera is performed.

[0033] Further, the above-described mobile terminal 200 assumes an AR display device of
15 mobile terminal type which displays an image in real space imaged by an imaging unit on a display and displays computer-graphics image data in a combined manner on the displayed image in real space, but the AR display device applicable to
20 this embodiment is not limited thereto. For example, it may be an AR display device (HMD) of eyeglass type worn on the head of the user, which displays computer-graphics image data at a position matching with the image in real space
25 projected on a lens part in an optically transmitted manner, or it may be a head-up display type AR display device which is disposed in a line of sight from a driver's seat of a mobile vehicle, and displays computer-graphics

image data in a combined manner on an image in real space which is projected in an optically transmitted manner.

[0034] Further, when computer-graphics image
5 data are displayed in a manner matched with an image in real space, coordinate matching is performed between an object in the image in real space and the computer-graphics image data. A method for coordinate matching may be such that
10 where the user possessing the mobile terminal 200 sees in real space through the imaging unit is estimated based on the position (latitude, longitude) and posture (direction, elevation angle) of the mobile terminal 200, and computer-
15 graphics image data are combined so as to match with the estimated position. Another method is such that a marker is added to an object in real space, this marker is imaged by the imaging unit, the position of the marker is detected from the
20 imaged image data, and computer-graphics image data are combined so as to match with the detected position. Moreover, the position of an object in real space may be detected by analyzing image data in real space captured by the imaging
25 unit, and computer-graphics image data may be combined so as to match with the detected position.

[0035] Fig. 2A is a diagram illustrating a hardware structure of the shopping management

server 100 according to this embodiment. A CPU 1001 performs overall control of respective devices and controllers connected to a system bus. In the ROM 1003 and the HD (hard disk) 1009, BIOS (Basic Input/Output System) which is a control program of the CPU 1001, an operating system program, for example a program of processing executed by the shopping management server 100 among processing illustrated in Fig. 3A and Fig. 3B, and so on are stored.

[0036] Note that although the HD 1009 is disposed inside the shopping management server 100 in the structure of the example illustrated in Fig. 2A, a structure equivalent to the HD 1009 may be disposed outside the shopping management server 100 as another embodiment. Further, a program for performing, for example, the processing illustrated in Fig. 3A and Fig. 3B according to this embodiment may be recorded in a computer readable recording medium such as a flexible disk (FD) or a CD-ROM and supplied from this recording medium, or may be supplied via a communication medium such as the Internet.

[0037] The RAM 1002 functions as a main memory, a work area, or the like for the CPU 1001. The CPU 1001 loads on the RAM 1002 a necessary program or the like when executing processing and executes the program to thereby realize various operations.

[0038] The HD 1009 and FD 1008 functions as an external memory. The CPU 1001 loads on the RAM 1002 a necessary program or the like when executing processing and executes the program to
5 thereby realize various operations.

[0039] A disk controller 1007 controls access to the external memory such as the HD 1007 or the FD 1008. A communication I/F controller 1006 connects to the Internet, LAN, and the like and
10 controls communication with an external unit by TCP/IP for example.

[0040] A display controller 1010 controls image display in a display 1011.

[0041] A KB controller 1004 accepts an operating
15 input from a KB (keyboard) 1005, and transmits the operating input to the CPU 1001. Note that although not illustrated, besides the KB 1005, a pointing device such as a mouse is applicable to the shopping management server 100 according to
20 this embodiment as an operating unit for a user.

[0042] The registration/inquiry unit 105, product matching unit 106, product information retrieving unit 107, and map information retrieving unit 108 illustrated in Fig. 1 are
25 realized by, for example, a program which is stored in the HD 1009 and loaded on the RAM 1002 as necessary and by the CPU 1001 executing the program. Further, the user information DB 101, flier information DB 102, product information DB

103, and map information DB 104 are structures equivalent to a partial storage area in the HD 1009.

[0043] Fig. 2B is a diagram illustrating a
5 hardware structure of the mobile terminal 200 according to this embodiment. A CPU 2001 performs overall control of respective devices and controllers connected to a system bus. In a ROM 2003, for example, a program of processing
10 executed by the mobile terminal 200 among processing illustrated in Fig. 3A and Fig. 3B, and so on are stored. Note that a program for performing the processing illustrated in Fig. 3A and Fig. 3B may be supplied via a communication
15 medium such as the Internet.

[0044] A RAM 2002 functions as a main memory, a work memory, or the like for the CPU 2001. The CPU 2001 loads on the RAM 2002 a necessary program or the like when executing processing and
20 executes the program to thereby realize various operations. A communication I/F controller 2005 connects to the Internet, LAN, and the like and controls communication with an external unit by TCP/IP for example.

25 [0045] An imaging unit 2004 converts a subject image incident via an optical lens and formed on an imaging element into an electric signal, and outputs moving image data or still image data. A display controller 2006 controls image display on

a display 2007. In this embodiment, a liquid crystal display is employed as the display 2007.

[0046] Fig. 3A is a flowchart illustrating the flow of registration processing of product to buy in the shopping navigation system according to this embodiment. The user first points at a product to buy posted on the flier 300, and captures this state in the angle of view of the imaging unit 2007 of the mobile terminal 200. Thus, in step S101 the imaging unit 2007 generates image data captured in the angle of view, and by analyzing the image data, the mobile terminal 200 detects image data of the product to buy specified by pointing. In step S102, the mobile terminal 200 transmits the image data of the product to buy detected in step S101 to the shopping management server 100.

[0047] Fig. 4 is a diagram illustrating a state that the user points at a product to buy posted on the flier 300, and this state is captured in the angle of view of the imaging unit 2007 of the mobile terminal 200. The user chooses and points at an apple as a product to buy out of the products posted on the flier 300. In the example of Fig. 4, the imaging unit of the mobile terminal 200 captures this state in the angle of view, and an image of the state that the user points at the product to buy (apple) on the flier 300 is displayed on the display 2007. Therefore,

in the example of Fig. 4, image data of the apple is detected as image data of the product to buy. Note that besides the above-described method, for example, a product to buy may be specified such

5 that the user moves his or her finger so as to surround the apple on the flier, and captures this movement in the angle of view of the imaging unit 2007. In this case, the mobile terminal 200 detects the trace of the user's finger, and

10 judges that a product fitting in this trace is a product to buy. By employing the method of specifying a product to buy as described above, it is possible to simply specify a product to buy.

15 [0048] In step S201, the shopping management server 100 receives the image data of the product to buy from the mobile terminal 200. In step S202, the product matching unit 106 obtains the image data of the respective products posted on

20 the flier 300 from the flier information DB 102, and compares them with the image data of the product to buy received from the mobile terminal 200. In step S203, the product matching unit 106 judges whether or not the product to buy is a

25 product posted on the flier 300 by judging conformity between the image data of the product to buy and the image data of the products posted on the flier 300. This judgment of conformity is made such that pattern matching is performed

between the image data of the product to buy and the image data of the products posted on the flier 300, and when it is judged that there is conformity or similarity therebetween, the product to buy is judged as a product posted on the flier 300. When it is judged that the product to buy is a product posted on the flier 300, the processing proceeds to step S204. On the other hand, when it is judged that the product to buy is not a product posted on the flier 300, the processing returns to step S201 and waits for reception of image data of a new product to buy.

[0049] Fig. 7 is a diagram schematically illustrating an example of a database structure of the flier information DB 102. In Fig. 7, the flier information DB 102 manages IDs of the respective products (product IDs) posted on the flier 300 and image data in correlation. When the shopping management server 100 receives the image data of the apple for example from the mobile terminal 200 in step S201, the product matching unit 106 judges in step S203 that, as a result of comparing the image data of the product to buy and the image data of the respective products posted on the flier 300, the image data of the product to buy matches or is similar to the image data of the apple of 701, and judges that the product to buy is the apple.

[0050] In step S204, the registration/inquiry unit 105 obtains the product ID correlated with the image data of the product judged as the product to buy from the flier information DB 102 via the product matching unit 106. Further, the registration/inquiry unit 105 obtains the user ID of the sender from header information of the image data of the product to buy received in step S201. Then, the registration/inquiry unit 105 registers the user ID and the product ID of the product to buy in correlation in the user information DB 101.

[0051] Fig. 8 is a diagram schematically illustrating an example of a database structure of the user information DB 101. In Fig. 8, the user information DB 101 manages user IDs and product to buy IDs in correlation. For example, when the product ID of a product to buy is "1011", and a user ID "aaa" is obtained from the header information of image data of the product to buy, the user ID "aaa" and the product to buy ID "1011" are managed in correlation as illustrated in the record of 801.

[0052] Fig. 3B is a flowchart illustrating presentation processing of product information of a product to buy and navigation processing from a current location to a shop in the shopping navigation system according to this embodiment. For example, when the user wants to comprehend

the latest price information, inventory information, and the like of a product to buy which is already registered in the shopping management server 100, the user holds the mobile terminal 200 again over the product to buy posted on the flier 300, and captures the product to buy in the angle of view of the imaging unit 2007. Thus, in step S103, the imaging unit 2007 of the mobile terminal 200 generates image data of the product to buy. In step S104, the mobile terminal 200 transmits the image data of the product to buy to the shopping management server 100.

[0053] In step S205, the shopping management server 100 receives the image data of the product to buy from the mobile terminal 200. In step S206, the product matching unit 106 obtains the image data of the respective products posted on the flier 300 from the flier information DB 102, and compares them with the image data of the product to buy obtained from the mobile terminal 200. In step S207, the product matching unit 106 judges whether or not the product to buy is a product posted on the flier 300 by judging conformity between the image data of the product to buy and the image data of the products posted on the flier 300. When it is judged that the product to buy is a product posted on the flier 300, the processing proceeds to step S213. On

the other hand, when it is not judged that the product to buy is a product posted on the flier 300, the processing returns to step S205.

[0054] In step S213, the registration/inquiry
5 unit 105 obtains the product ID correlated with the image data of the product judged as the product to buy from the flier information DB 102 via the product matching unit 106. Further, the registration/inquiry unit 105 obtains the user ID
10 of the sender from header information of the image data received in step S205. In step S208, the registration/inquiry unit 105 judges whether or not the product ID obtained in step S213 is managed in the user information DB 101 in
15 correlation with the aforementioned user ID. When the product ID and the user ID are correlated, the processing proceeds to step S209. On the other hand, when the product ID and the user ID are not correlated, the processing
20 returns to step S205.

[0055] In step S209, the product information retrieving unit 107 retrieves product information corresponding to the product ID obtained in step S213 from the product information DB 103, and
25 transmits the information to the mobile terminal 200.

[0056] Fig. 9 is a diagram schematically illustrating an example of a database structure of the product information DB 103. In Fig. 9,

the product information DB 103 manages product IDs, product names, prices (price 1, price 2, ...), shops, stock quantities, and product attributes in correlation. As the product
5 attributes, when the product is food, place of production, production date, and so on are managed, and when the product is clothes, color, size, and so on are managed. Further, data managed in the product information DB 103 may be
10 updated at arbitrary timing in cooperation with a POS system (Point Of Sales system) which is not illustrated in Fig. 1. For example, when the product ID obtained in step S213 is "1011", a record of 901 is retrieved in step S209 from the product information DB 103 illustrated in Fig. 9,
15 and the product information registered in the record 901 is transmitted to the mobile terminal 200. Note that regarding the price and stock quantity included in the product information,
20 latest information is transmitted to the mobile terminal 200. In the product information DB 103, the price of the product posted on the flier 300 is registered as an initial price (price 1), and a price is registered in addition every time the
25 price is updated (price 2, price 3, ...). In step S209, from histories of prices recorded in this manner, the price registered at last is transmitted to the mobile terminal 200. Thus, in the mobile terminal 200, the latest (current)

price of the product to buy is displayed. Note that the product information DB 103 may be of the type in which price histories are managed, and the price itself is overwritten and only the latest price is managed. Further, in the product information DB 103, the stock quantity is overwritten at predetermined timing, and only the latest stock quantity is managed. Therefore, in step S209, the latest stock quantity is transmitted to the mobile terminal 200. Thus, in the mobile terminal 200, the latest stock quantity of the product to buy is displayed.

[0057] In step S105, the mobile terminal 200 receives the product information from the shopping management server 100. In step S106, the mobile terminal 200 combines computer-graphics image data of the received product information with an image in real space and displays the combined image. Fig. 5 is a diagram illustrating a display example combining computer-graphics image data of product information with an image in real space. In the example of Fig. 5, in the vicinity of the product to buy, computer-graphics image data illustrating product information 501 and computer-graphics image data illustrating a tag 502 which is an operating switch for requesting route guidance are displayed.

[0058] In step S110, the mobile terminal 200

judges whether there is a request for route guidance (navigation) or not. That is, the mobile terminal 200 judges whether the tag 502 is operated or not. When the tag 502 is operated, the processing proceeds to step S107. On the other hand, when the tag 502 is not operated, the processing is finished. In step S107, the mobile terminal 200 issues a request for route guidance to the shopping management server 100.

10 [0059] In step S210, the shopping management server 100 accepts the request for route guidance from the mobile terminal 200. In step S211, the map information retrieving unit 108 obtains current location information of the mobile terminal 200, and obtains shop information of a shop selling the product to buy from the product information retrieving unit 107. Note that the current location of the mobile terminal 200 can be obtained using GPS (Global Positioning

20 System). Further, although not illustrated in Fig. 9, the product information DB 103 includes address information of the shop selling the product, and the map information retrieving unit 108 obtains the address information of the shop selling the product to buy from the product information DB 103 via the product information retrieving unit 107. In step S211, the map information retrieving unit 108 retrieves map information including the position indicated by

25

the current location information of the mobile terminal 200 and the position indicated by the address information of the shop selling the product to buy. In step S212, the map
5 information retrieving unit 108 generates guidance information for guiding a route from the current location of the mobile terminal 200 to the shop selling the product to buy using the retrieved map information, and transmits the
10 information to the mobile terminal 200.

[0060] In step S108, the mobile terminal 200 receives the guidance information from the shopping management server 100. In step S109, the mobile terminal 200 uses the received
15 guidance information, and combines computer-graphics image data guiding the route from the current location of the mobile terminal 200 to the shop selling the product to buy with the image in real space, and displays the combined
20 image on the display 2007.

[0061] In the above-described embodiment, when the user wants to know product information of a product to buy which is registered in advance, the user can easily obtain the latest product
25 information such as stock quantity, price, and so on of the product to buy by performing a predetermined specifying operation on the product to buy on the flier, and capturing this in the angle of view of the imaging unit 2004. Further,

in order to enable notification of product information of the product to buy to the mobile terminal 200 when the correlation between the user ID and the product ID of the product to buy is registered in the user information DB 801, step S209 of Fig. 3B may be executed after step S204 of Fig. 3A. That is, when the shopping management server 100 registers the correlation between the user ID and the product ID of the product to buy in the user information DB 801 in step S204, the server retrieves the product information corresponding to the product ID from the product information DB 103 in subsequent step S209, and transmits this information to the mobile terminal 200. In this manner, it becomes possible to notify the product information of the product to buy to the mobile terminal 200 when the correlation between the user ID and the product ID of the product to buy is registered.

[0062] Note that in the above-described embodiment, it is necessary for the user to hold the mobile terminal 200 over the flier 300 again in the presentation processing of the product information of the product to buy, but it is not limited thus. Another embodiment in which it is not necessary to hold the mobile terminal 200 over the flier 300 again will be described with respect mainly to differences from the above-described embodiment.

[0063] <Embodiment 2>

Fig. 10 is a diagram schematically illustrating a structure of a shopping navigation system of Embodiment 2. As illustrated in Fig. 10, the system of this embodiment does not include the user information DB 101 in the shopping management server 100, and instead a shopping list 201 is included in the mobile terminal 200, as compared to the system of the above-described embodiment. Note that the shopping list 201 is a file recording product IDs of products to buy, and is managed in correlation with a product image, a product name, and so on as illustrated in Fig. 12 for example.

[0064] Fig. 11A is a flowchart illustrating the flow of registration processing of a product to buy in the shopping navigation system according to this embodiment. As compared to Fig. 3A, step S1101 is added, and step S1201 is added as an alternative to step S204 being deleted.

[0065] In step S1201, the registration/inquiry unit 105 obtains a product ID correlated with image data of a product judged as a product to buy from the flier information DB 102 via the product matching unit 106. Then, the obtained product ID is transmitted to the mobile terminal 200.

[0066] In step S1101, the product ID is received from the mobile terminal 200. Then, the obtained

product ID is stored in the ROM 2003.

[0067] Next, Fig. 11B is a flowchart illustrating presentation processing of product information of a product to buy and navigation processing from a current location to a shop in the shopping navigation system according to this embodiment. As compared to Fig. 3B, step S1102 is added as an alternative to step S103 and step S104 of Fig. 3B being deleted. Further, step S1202 is added as an alternative of step S205 to step S208 of Fig. 3B being deleted. Hereinafter, this embodiment will be described mainly focusing on differences from the above-described embodiment.

[0068] For example, when the user wants to comprehend the latest price information, inventory information, and the like of a product to buy which is already registered in the mobile terminal 200 in step S1101 of Fig. 11A, the mobile terminal 200 transmits the product ID of the product to the shopping management server 100 in step S1102 of Fig. 11B. A method of determining the product ID of this product is such that, for example, a shopping list is displayed on the mobile terminal 200 as illustrated in Fig. 12, and when a product name displayed on the shopping list is tapped, the product ID registered in the mobile terminal 200 corresponding to this product name is chosen and

transmitted to the shopping management server
100.

[0069] In step S1202, the shopping management
server 100 obtains the product ID. After this,
5 the server proceeds to the processing of step
S209 similarly to Fig. 3B. With the structure of
this embodiment, the user does not need the flier
30 when obtaining inventory information or price
information of a product to buy, and hence easier
10 obtainment is possible.

[0070] Note that in the above-described
embodiment, when the user chooses a product to
buy from the products posted on the flier 300,
product information of the product to buy in a
15 shop selling this product to buy is AR displayed,
but it is not limited thus. For example, it is
possible that the product to buy of the user is
sold in plural shops. In such a case, it is
possible that in above-described step S209
20 product information in the plural shops selling
the product is retrieved, and the product
information is AR displayed. Specifically, the
correlation of image data of products of plural
shops and product IDs is managed in the flier
25 information DB 102. When plural sets of image
data of the product matching with or similar to
the image data of a product to buy exist, and a
combination of any one of the product IDs
correlated with all sets of image data and the

user ID recorded in the header of image data of the product to buy exists in the user information DB 101, all the product information corresponding to the product IDs may be obtained from the product information DB 103. Alternatively, another possible method is to determine all product IDs corresponding to the image data matching with or similar to the image data of the product to buy from the flier information DB 102. Alternatively, although not illustrated in Fig. 7, another possible method is such that a row for managing product names is added in the flier information DB 102, and a product name which is the same or similar to the product name of the product matching with or similar to the image data of the product to buy determines all the product IDs of the products managed in the row "product name". Alternatively, another possible method is to determine, rather than the image data of the product to buy, all the product IDs of products matching with or similar to the product name or the image data of the product which are managed in correlation with the product ID received from the mobile terminal 200. Then, all the pieces of obtained product information are transmitted from the shopping management server 100 to the mobile terminal 200, and in the mobile terminal 200, the product information of the plural shops can be AR displayed with respect

to the product to buy.

[0071] Fig. 6 is a diagram illustrating an example of AR display when product information of an apple, which is a product to buy of the user, of three shops is obtained. In Fig. 6, numerals 601, 602, 603 denote product information related to apples in shop A, shop B, shop C, respectively, which indicate the current prices, stock quantities, and so on of the apples in the respective shops. Thus, the user can refer to the product information of the apples other than that of shop A which issued the flier. For example, if an apple is sold at a lower price than that of the shop A in a shop other than the shop A, or the apple is out of stock in the shop A but is in stock in another shop, the shopping destination may be changed to buy the apple in the other shop. In this case, in step S110, the mobile terminal 200 judges whether a tag 604 regarding the product is operated or not and which shop it is operated for among the plural shops for which the product information is AR displayed, and then in step S107 the mobile terminal 200 issues a request for route guidance to the relevant shop to the shopping management server 100. Note that in Fig. 6, the mode of choosing a shop in the tag 604 which is an operating switch for requesting route guidance is displayed as a pull-down menu, but any other mode

is possible. For example, respective tags of the plural shops may be provided, or voice recognition recognizing a shop name vocalized by the user may be used.

5 [0072] Further, in the case where the user initially planned to buy the apple in the shop A but the apple is sold at a lower price in another shop than in the shop A, or the case where the apple is out of stock in the shop A but is in
10 stock in another shop, the shopping management server 100 may detect this automatically, generate guidance information for navigating to the other shop for the mobile terminal 200, and transmit the information to the mobile terminal
15 200. At this time, the shopping management server 100 makes a comparison of product information in plural shops retrieved in above-described step S209 in step S211 and step S212, and generates guidance information based on a
20 predetermined rule. This rule is stored in the ROM 1003 or HD (hard disk) 1009, and a conceivable example is to guide a route to the shop at the closest distance from the current location among the plural shops retrieved in step
25 S209, or guide a route to the shop having the largest stock quantity among the plural shops retrieved in step S209, or separately obtain information indicating the congestion status of people in respective routes to the plural shops

retrieved in step S209, and guide a route which allows smoothest passing. Note that rather than applying one rule fixedly, plural rules may be applied in combination, or a combination may be
5 changed dynamically and applied. For example, when guidance information to the shop A is generated first by applying a rule "to guide a route to the shop at the closest distance", and then the shopping management server 100 refers to
10 the product information DB 103 and comprehends that the product is out of stock while the user is on the way to the shop A based on the information AR displayed on the mobile terminal 200, the shopping management server 100 generates
15 new guidance information based on another rule "to guide a route to the shop having the largest stock quantity", and AR displays this on the mobile terminal 200. Further, rather than guiding from the current location to a shop, it
20 is also possible to guide the user to a location where the target product is displayed in a shop. Moreover, when the user has reached the vicinity of the target product but cannot find the product, the posture of the mobile terminal may
25 be detected by the posture detection function of the mobile terminal 200, and where the user should look at may be guided.

[0073] Further, other examples of information which is AR displayed on the mobile terminal 200

include an alarm notifying that a product registered in the past is posted on a flier which the user is looking at, a discount price and a discount period of this product, and the like.

5 Specifically, if the user registers a consumable product, for example a powder milk or a tissue paper, which is needed periodically by the method described in Fig. 3A, when the user holds the mobile terminal 200 over a flier which is issued
10 thereafter and the registered product is posted on the flier, this product may be detected by the method described in Fig. 3B (steps S205 to S208), and the alarm and the discount price, discount period, and so on of the product may be
15 transmitted to the mobile terminal 200 by the processing similar to step S209. Thus, information of alarm or the like is AR displayed in a state that the user looks at the flier through the mobile terminal 200.

20 [0074] Further, as another embodiment, the shopping management server 100 may automatically select a product corresponding to the user's taste from the flier, and guide the selected product or a shop selling this product to the
25 user. More specifically, master information of the user is registered in the shopping management server 100. Information registered as the master information includes personal preferences (whether or not to focus on quality, whether or

not to focus on seasonal products, whether or not having allergies, target weekly food cost, target daily calories, whether or not to desire increase in number of items with the same material and in the same cooking procedure to the middle, whether or not to desire shopping in nearby places), family preferences (father: less oil, child: meat-centered, adult: hot curry, child: mild curry), cooking histories (whether cooking is succeeded or failed, history of leftover, reaction of family), and so on. Further, the shopping management server 100 obtains flier information of respective shops. As a method for obtaining the flier information, there is a method to obtain images, prices, and so on of products from electronic flier data of the sites of the respective shops, or to image a flier inserted in a newspaper by a camera, and obtain images, prices, and so on of products from image data obtained by imaging. Note that the flier information may be obtained from flier information of plural shops. For example, it is conceivable that flier information related to ingredients of curry is obtained from a shop A which is a supermarket, and flier information related to seasonings is obtained from a shop B which is a discount liquor shop. On the other hand, when the user observes a cooking program, a restaurant introducing program, a blog of a

cuisine researcher, or a recommended cooking recipe on the mobile terminal 200 and operates a button labeled "looks delicious" for example on the screen, the mobile terminal 200 performs

5 image recognition, voice recognition, text recognition, or the like to match the analysis result thereof and the master information and the flier information to select cooking ingredients and a selling shop.

10 [0075] The shopping management server 100 generates guidance information for guiding a route from the current location of the mobile terminal 200 to the selling shop based on the cooking ingredients and the selling shop selected

15 in this manner, and transmits the information to the mobile terminal 200. The mobile terminal 200 combines, using the guidance information, computer-graphics image data guiding from the current location to the selling shop with an

20 image in real space, and displays the combined image. Thus, the route to the shop where the cooking ingredients matching with preferences of the user can be purchased is guided automatically. Further, when the user moves into

25 the selling shop and holds up the mobile terminal 200 in the shop, computer-graphics image data indicating product information such as prices, stock quantities, places of production, and so on of the cooking ingredients may be combined and

displayed with an image in real space in which a shelf where the ingredients are displayed is shown, or computer-graphics image data of an arrow pointing at the position of the shelf may
5 be combined and displayed with an image in real space.

[0076] Further, histories of cooking ingredients which the user has actually purchased may be registered in the master information, and may be
10 used when cooking ingredients are selected next time. Moreover, histories of purchased cooking ingredients may be outputted as part of information of a housekeeping book.

[0077] In the above-described embodiment,
15 although image data of a product to buy is imaged by the imaging unit 2004 when the product to buy is registered or product information of the product to buy is obtained, and the image data are transmitted from the mobile terminal 200 to
20 the shopping management server 100, it is not limited thus. Specifically, when a marker corresponding to a product is posted on a flier, the marker may be imaged by the imaging unit 2004, and image data of the marker may be
25 transmitted from the mobile terminal 200 to the shopping management server 100. The shopping management server 100 manages the correlation between markers and products, and identifies the product to buy corresponding to the marker by

analyzing the received image data of the marker.
Then, the shopping management server 100 compares
IDs of respective products posted on the flier
300 stored in the flier information DB 102 with
5 the ID of the product to buy, and when there is a
matching product, the server judges that the
product to buy is a product posted on the flier,
and manages the user and the product to buy in
correlation in the user information DB 101.

10 [0078] Further, when it is desired to obtain
product information of this product to buy, the
user likewise images the marker corresponding to
the product to buy by the imaging unit 2004, and
transmits image data of the marker from the
15 mobile terminal 200 to the shopping management
server 100. The shopping management server 100
identifies the product to buy corresponding to
the marker by analyzing the received image data
of the marker. Then, the shopping management
20 server 100 compares IDs of respective products
posted on the flier 300 stored in the flier
information DB 102 with the ID of the product to
buy. When there is a matching product, the
shopping management server 100 judges whether or
25 not the correlation between the ID of the product
to buy and a user is registered in the user
information DB 101. When the correlation between
the ID of the product to buy and a user is
registered in the user information DB 101, the

product to buy is judged as one specified by this user in the past. Therefore, the shopping management server 100 transmits the product information of the product to buy to the mobile terminal 200 of this user. As described above, by using the markers corresponding to the products posted on the flier, product information of a product to buy can be obtained easily at arbitrary timing similarly.

10 [0079] Note that in the above-described embodiments, a flier is taken as an example and described, but the embodiments can be implemented similarly for any advertisement medium such as a poster posted in the street or a TV advertisement.

15 [0080] <Embodiment 3>

Hereinafter, Embodiment 3 will be described.

Fig. 13 is a diagram illustrating an example of a system structure of a vacant space guidance system. As illustrated in Fig. 13, in the vacant space guidance system, plural sensors 3 disposed in respective spaces (car spaces) in a parking lot, plural antennas for wireless communication provided in the parking lot, plural parking lot cameras 5 provided in the parking lot, an information processing apparatus 1, and a car 2 in the parking lot are connected via a network.

25 The information processing apparatus 1 receives vacant space information in the parking

lot from the plural sensors 3 wirelessly or via wire. Note that the sensors 3 may transmit to the information processing apparatus 1 a notification of a vacant space when a space
5 becomes vacant, or may transmit to the information processing apparatus 1 information on whether a space is vacant or not at predetermined time intervals.

Further, the information processing
10 apparatus 1 constantly receives images imaged by the parking lot cameras 5 wirelessly or via wire from the plural parking lot cameras 5. The information processing apparatus 1 obtains the position and direction of the car 2 based on the
15 images received from the cameras 5. Describing more specifically, the information processing apparatus 1 has information correlating the parking lot cameras 5 and location information where the parking lot cameras 5 are disposed,
20 determines location information where a parking lot camera 5 is disposed by an image from this parking lot camera 5, and determines the location of the car 2 shown on the image. Further, the information processing apparatus 1 obtains the
25 direction of the car 2 by analyzing the image. Note that in the vacant space guidance system of this embodiment, a parking lot camera 5 is disposed at an entrance of the parking lot, and this parking lot camera 5 images the number plate

of a car 2 which enters the parking lot. The information processing apparatus 1 can identify the car 2 based on this number plate, and extract the number plate from images of the car 2 sent from the plural parking lot cameras 5 so as to trace the car 2. That is, the information processing apparatus 1 constantly comprehends the current position and direction of the car 2 in the parking lot based on the images sent from the plural parking lot cameras 5.

[0081] The information processing apparatus 1 determines a vacant space existing in the traveling direction of the car 2 based on the vacant space information received from the plural sensors 3, the position and direction of the car 2 in the parking lot, and a parking lot map stored in a storage device 12 or the like, which will be described later. Note that the parking lot map is map data which manage at least a space ID identifying each car space in the parking lot, position information of a space identified based on the space ID, information related to standards such as the area, height, and so on of each space, and route information related to traveling directions in the parking lot. Further, the vacant space information indicates position information of a car space which became vacant, and may be information by which the position of a vacant space can be determined by verifying with

the parking lot map, such as a space ID of a car space which became vacant or position information of the sensor provided in this vacant space for example. Then, the information processing apparatus 1 generates a virtual space image in the parking lot which includes a vacant space object indicating the vacant space and indicates the position of the vacant space according to the location (or position) of the determined space.

10 The information processing apparatus 1 transmits the generated virtual space image to the car 2 via the plural antennas 4 for wireless communication provided in the parking lot.

When the car 2 receives the virtual space image, control is performed to project the virtual space image on a display of the car, and display the virtual space image in a manner overlaid on a view in the parking lot from the display.

20 [0082] Fig. 14 is a diagram illustrating an example of a hardware structure of the information processing apparatus 1.

As illustrated in Fig. 14, the information processing apparatus 1 has, as a hardware structure, a structure in which a control device 11, a storage device 12, and a communication device 13 are connected via a bus 14. The control device 11 is a CPU or the like, and realizes functions of the information processing

25

apparatus 1 by executing processing based on a program stored in the storage device 12 or the like. The storage device 12 is a storage device such as RAM, ROM, or HDD which stores a program as well as data and the like used by the control device 11 when executing processing based on the program. The communication device 13 is in charge of control of wired or wireless communication between the information processing apparatus 1 and the plural sensors 3 and control of wireless communication with the plural antennas 4. The following embodiments including this embodiment will be described assuming that the communication device 13 is in charge of control of wireless communication with the plural sensors 3 and the plural antennas 4. However, the information processing apparatus 1 may employ a structure having two communication devices, a communication device in charge of control of wireless communication between the information processing apparatus 1 and the plural sensors 3, and a communication device in charge of control of wireless communication between the information processing apparatus 1 and the plural antennas 4.

[0083] Fig. 15 is a diagram illustrating an example of a hardware structure of the car 2. Note that in Fig. 15, among hardware structures of the car, a hardware structure related to this embodiment is illustrated, and what are called

hardware structures of the car such as an engine are omitted.

As illustrated in Fig. 15, the car 2 has, as a hardware structure, a structure in which a control device 21, a storage device 22, a communication device 23, and a projector 24 are connected via a bus 25. The control device 21 is a CPU or the like, and realizes functions related to this embodiment of the car 2 by executing processing based on a program stored in the storage device 22 or the like. The storage device 22 is a storage device such as RAM, ROM, or HDD which stores a program as well as data and the like used by the control device 21 when executing processing based on the program. The communication device 23 is in charge of control of wireless communication between the car 2 and the plural antennas 4. The projector 24 projects a virtual space image transmitted (or distributed) from the information processing apparatus 1 on a display of the car 2. This display is a system called Head-Up Display (HUD), on which an image projected from the projector 24 is reflected on the windshield or the like of the car and can be seen by the driver. Thus, the driver simultaneously sees a normal view seen from the driver's seat through the windshield, and a virtual space image projected by the projector 24 and reflected to be seen, which can

be seen as an overlaid image.

[0084] Fig. 16 is a diagram illustrating an example of a software structure of the information processing apparatus 1 of Embodiment 3. As illustrated in Fig. 16, the information processing apparatus 1 includes, as a software structure (functional structure), a vacant space information obtaining unit 31, a vehicle information obtaining unit 32, a vacant space determining unit 33, an image generating unit 34, and a transmitting unit 35.

The vacant space information obtaining unit 31 obtains vacant space information of the parking lot. More specifically, the vacant space information obtaining unit 31 receives vacant space information of the parking lot from the plural sensors 3 wirelessly or via wire. The vehicle information obtaining unit 32 obtains the position and the direction of the car in the parking lot. Describing more specifically, the vehicle information obtaining unit 32 receives an image of the car 2 imaged by a parking lot camera 5. Then, the vehicle information obtaining unit 32 determines location information on where this parking lot camera 5 is disposed by recognizing which parking lot camera 5 sent this image from the information correlating the parking lot cameras 5 and the location information on where the parking lot cameras 5 are disposed, which is

stored in the storage device 12 or the like, and determines the location of the car 2 shown in the image. Further, the vehicle information obtaining unit 32 obtains the direction of the car 2 by analyzing the image.

The vacant space determining unit 33 determines a vacant space existing in the traveling direction of the car 2 based on the vacant space information obtained in the vacant space information obtaining unit 31, the position and direction of the car 2 obtained in the vehicle information obtaining unit 32, and the parking lot map which is map information in the parking lot stored in the storage device 12 or the like. More specifically, for example, a space ID or position information of the vacant space obtained from the vacant space information obtained from the vacant space information obtaining unit 31 is verified with the parking lot map, so as to determine the position information of the vacant space. Then, the vacant space determining unit 33 determines the vacant space existing in the traveling direction of the car 2 out of the position information of the determined one or more vacant spaces from the position and direction of the car 2 obtained in the vehicle information obtaining unit 32 and the route information of the parking lot map. The image generating unit 34 generates a virtual

space image in the parking lot which includes a vacant space object indicating the vacant space and indicates the position of the vacant space, according to the position of the vacant space in the parking lot existing in the traveling direction of the car 2 which is determined in the vacant space determining unit 33. Here, the image generating unit 34 may determine the visual field of the driver from the car 2 based on the position and direction of the car 2 obtained in the vehicle information obtaining unit 32, and generate a virtual space image in the parking lot which includes a vacant space object indicating the vacant space and indicates the position of the vacant space, according to the position of the vacant space in the parking lot existing in the traveling direction of the car 2 in the visual field.

The transmitting unit 35 transmits the virtual space image generated in the image generating unit 34 to the car 2 via an antenna 4 near the position of the car 2.

[0085] Fig. 17 is a diagram illustrating an example of a software structure of the car 2 of Embodiment 3. In Fig. 17, among software structures of the car, a software structure related to this embodiment is illustrated, and software structures related to control of an engine and so on of the car are omitted. As

illustrated in Fig. 17, the car 2 includes, as a software structure (functional structure), a receiving unit 41 and a display control unit 42.

The receiving unit 41 receives a virtual
5 space image from the information processing
apparatus via the antenna 4. The display control
unit 42 controls the projector 24 to project the
virtual space image received in the receiving
unit 41 on the display of the car, to thereby
10 display the virtual space image in a manner
overlaid on a view in the parking lot from the
display.

[0086] Fig. 18 is a sequence diagram
illustrating an example of processing in the
15 vacant space guidance system of Embodiment 3.

In sequence SQ1, the sensors 3 disposed
respectively in spaces (car spaces) in the
parking lot transmit, for example, information on
whether a space is vacant or not to the
20 information processing apparatus 1 at
predetermined time intervals. The information
processing apparatus 1 receives the information
and comprehend and manage the vacant space
information in the parking lot.

25 In sequence SQ2, the parking lot cameras 5
constantly transmit an imaged image wirelessly or
via wire to the information processing apparatus
1. Note that the order of the sequence SQ1 and
the sequence SQ2 is not in question. The order

may be reverse of the order illustrated in Fig. 18, or may be simultaneous. The information processing apparatus 1 receives the image, and comprehend and manage the position and direction
5 of the car in the parking lot.

In sequence SQ3, the information processing apparatus 1 determines a vacant space existing in the traveling direction of the car 2 based on the vacant space information and the position and
10 direction of the car comprehended and managed, and the parking lot map stored in the storage device 12 or the like.

In sequence SQ4, the information processing apparatus 1 generates a virtual space image in
15 the parking lot which includes a vacant space object indicating the vacant space and indicates the position of the vacant space, according to the position of the vacant space in the parking lot existing in the traveling direction of the
20 car comprehended and managed.

In sequence SQ5 and sequence SQ6, the information processing apparatus 1 transmits the virtual space image to the car 2 via an antenna 4 near the position of the car.

25 In sequence SQ7, the car 2 performs control so that a virtual space image received from the information processing apparatus 1 is projected on the display of the car, to thereby display the virtual space image in a manner overlaid on a

view in the parking lot from the display.

The processing illustrated in Fig. 18 is executed constantly or at predetermined intervals (for example, at 0.1-second intervals) until the
5 car enters the parking lot and is parked in a parking space.

[0087] Fig. 19 is a diagram illustrating an example of overlay display on the display of Embodiment 3. As illustrated in Fig. 19, a
10 virtual space image including a "vacant" object indicating a vacant space is displayed on the display in a manner overlaid on a view in the parking lot from the display. Here, when plural vacant spaces existing in the traveling direction
15 of the car 2 are determined, the information processing apparatus 1 generates the virtual space image including vacant space objects with different shapes or colors according to distances from the car 2 to the respective vacant spaces.
20 In the example of Fig. 19, the information processing apparatus 1 makes sizes of the vacant space objects different according to the distances. Describing more specifically, the information processing apparatus 1 generates a
25 virtual space image in which a vacant space closer in distance to the car 2 is given a larger vacant space object among the plural determined vacant spaces. In this manner, the driver of the car 2 can intuitively recognize nearby vacant

spaces.

Here, it is conceivable that when there are many vacant spaces, many "vacant" objects indicating a vacant space as illustrated in Fig. 19 are displayed on the display, and the visual field worsens for the driver of the car 2. Accordingly, for example, when the distance from a vacant space to the car 2 is more than or equal to a predetermined distance, the information processing apparatus 1 generates a virtual space image which includes a vacant space ratio object representing by a color or the like for example the ratio of a vacant space to the space inside a block in each of plural blocks dividing the parking lot, and indicates the position of the block. On the other hand, when the distance is less than the predetermined distance, the information processing apparatus 1 may generate a virtual space image which includes a vacant space object representing a vacant space existing in the traveling direction of the car 2 and indicates the position of the vacant space. In such a structure, when the car 2 is located away from vacant spaces, an object distinguished by a different color and indicating the vacant space ratio in each block is displayed on the display. Then, when the car 2 gets close to the vacant spaces, vacant space objects each indicating one vacant space as illustrated in Fig. 19 are spread

and displayed.

[0088] As described above, according to this embodiment, it is possible to provide a technology allowing the driver to find and reach
5 a target vacant space without updating the map information of the car navigation system mounted in each car or even when no car navigation system is mounted in each car.

[0089] <Embodiment 4>

10 Hereinafter, Embodiment 4 will be described. In Embodiment 4, differences from Embodiment 3 will be described.

Fig. 20 is a diagram illustrating an example of a software structure of an information
15 processing apparatus 1 of Embodiment 4. As illustrated in Fig. 20, the software structure of the information processing apparatus 1 of Embodiment 4 further includes a route determining unit 51 as compared to the software structure of
20 the information processing apparatus 1 of Embodiment 3. Based on a vacant space determined in the vacant space determining unit 33, the position and direction of the car in the parking lot obtained in the vehicle information obtaining
25 unit 32, and the parking lot map stored in the storage device 12, the route determining unit 51 determines a route from the car to the vacant space. The image generating unit 34 of this embodiment generates the virtual space image

which includes a vacant space object indicating the vacant space, indicates the position of the vacant space, and includes a guidance object indicating the route determined in the route determining unit 51, according to the position of the vacant space in the parking lot existing in the traveling direction of the car 2 which is determined in the vacant space determining unit 33.

10 Further, for example, when plural vacant spaces existing in the traveling direction of the car are determined in the vacant space determining unit 33, the route determining unit 51 determines a route from the car to the vacant space which is closest to the car among the plural vacant spaces.

[0090] Fig. 21 is a sequence diagram illustrating an example of processing in a vacant space guidance system of Embodiment 4.

20 In the sequence diagram of Embodiment 4 illustrated in Fig. 21, sequence SQ11 is newly added as compared to the sequence diagram of Embodiment 3 illustrated in Fig. 18.

In the sequence SQ11, the information processing apparatus 1 determines a route from the car to the vacant space determined in the sequence SQ3 based on the vacant space information and the position and direction of the car comprehended and managed, and the parking lot

map stored in the storage device 12 or the like.

In the sequence SQ4, the information processing apparatus 1 generates the virtual space image which includes a vacant space object indicating the vacant space, indicates the position of the vacant space, and includes a guidance object indicating the determined route, according to the position of the vacant space in the parking lot existing in the traveling direction of the car comprehended and managed.

[0091] Fig. 22 is a diagram illustrating an example of overlay display on the display of Embodiment 4. In the overlay display of Embodiment 4 illustrated in Fig. 22, as compared to the overlay display of Embodiment 3 illustrated in Fig. 19, an arrow object is added as an example of the guidance object indicating a route to a vacant space close to the car.

As described above, according to this embodiment, it is possible to provide a technology allowing the driver to find and reach a target vacant space more quickly without updating the map information of the car navigation system mounted in each car or even when no car navigation system is mounted in each car.

[0092] <Embodiment 5>

Hereinafter, Embodiment 5 will be described. In Embodiment 5, differences from above-described

embodiments will be described.

Fig. 23 is a diagram illustrating an example of a software structure of an information processing apparatus 1 of Embodiment 5. As illustrated in Fig. 23, the software structure of the information processing apparatus 1 of Embodiment 5 further includes a fixture determining unit 61 as compared to the software structure of the information processing apparatus 1 of Embodiment 4. Further, in the parking lot map, in addition to the above-described information, fixtures in the parking lot (for example, an entrance of a shop, a restroom, an emergency exit, and so on) and position information and so on related to locations of the fixtures are managed. The fixture determining unit 61 determines a fixture (for example, an entrance of a shop, a restroom, an emergency exit, and so on) existing in the traveling direction of the car based on the position and direction of the car in the parking lot obtained in the vehicle information obtaining unit 32 and the parking lot map stored in the storage device 12. The image generating unit 34 of this embodiment generates a virtual space image which includes a vacant space object indicating the vacant space, a guidance object indicating the route determined in the route determining unit 51, and a fixture object indicating the fixture

existing in the traveling direction of the car 2
determined in the fixture determining unit 61,
and indicates the position of the vacant space
and the position of the fixture, according to the
5 positions of the vacant space and the fixture in
the parking lot existing in the traveling
direction of the car 2 determined in the vacant
space determining unit 33.

[0093] Fig. 24 is a sequence diagram
10 illustrating an example of processing in a vacant
space guidance system of Embodiment 5.

In the sequence diagram of Embodiment 5
illustrated in Fig. 24, sequence SQ21 is newly
added as compared to the sequence diagram of
15 Embodiment 4 illustrated in Fig. 21.

In the sequence SQ21, the information
processing apparatus 1 determines a fixture of
the parking lot existing in the traveling
direction of the car based on the position and
20 direction comprehended and managed and the
parking lot map stored in the storage device 12
or the like. Note that the order of the sequence
SQ11 and the sequence SQ21 is not in question.
The order may be reverse of the order illustrated
25 in Fig. 24, or may be simultaneous.

In the sequence SQ4, the information
processing apparatus 1 generates the virtual
space image which includes the vacant space
object, the guidance object, and the fixture

object, and indicates the position of the vacant space and the position of the fixture, according to the positions of the vacant space and the fixture in the parking lot existing in the traveling direction of the car comprehended and managed.

[0094] Fig. 25 is a diagram illustrating an example of overlay display on the display of Embodiment 5. In the overlay display of Embodiment 5 illustrated in Fig. 25, as compared to the overlay display of Embodiment 4 illustrated in Fig. 22, an object indicating an entrance of a shop and an object indicating a restroom are added as examples of the fixture object.

As described above, according to this embodiment, it is possible to provide a technology allowing the driver to find and reach a target vacant space more appropriately without updating the map information of the car navigation system mounted in each car or even when no car navigation system is mounted in each car. For example, the driver can park in a parking space near the entrance of the shop.

[0095] <Embodiment 6>

Hereinafter, Embodiment 6 will be described. In Embodiment 6, differences from the above-described embodiments will be described.

Fig. 26 is a diagram illustrating an example

of a software structure of an information processing apparatus 1 of Embodiment 6. Further, Fig. 27 is a diagram illustrating an example of a software structure of a car 2 of Embodiment 6.

5 The software structure of the information processing apparatus 1 of Embodiment 6 does not include the image generating unit 34 as compared to the software structure of the information processing apparatus 1 of Embodiment 3. Instead,
10 the software structure of the car 2 of Embodiment 6 newly includes an image generating unit 34 as compared to the software structure of the car 2 of Embodiment 3. In the structure of this embodiment, the information processing apparatus
15 1 transmits a vacant space object and so on to the car 2. The car 2 performs control to generate an image including the received vacant space object and so on and project the image on a display or the like.

20 The transmitting unit 35 of this embodiment transmits a vacant space object indicating a vacant space determined in the vacant space determining unit 33 and position information representing the position of the vacant space to
25 the car 2. Then, the receiving unit 41 of this embodiment receives the vacant space object and the position information from the information processing apparatus 1. Then, the image generating unit 34 of this embodiment generates a

virtual space image in the parking lot in which the vacant space object received in the receiving unit 41 is displayed at the position indicated by the position information received in the
5 receiving unit 41. Then, the display control unit 42 of this embodiment performs control to project the virtual space image generated in the image generating unit 34 on the display of the car, to thereby display the virtual space image
10 in a manner overlaid on a view in the parking lot from the display.

[0096] Fig. 28 is a sequence diagram illustrating an example of processing in a vacant space guidance system of Embodiment 6.

15 Processing from sequence SQ1 to sequence SQ3 of Embodiment 6 illustrated in Fig. 28 is similar to the processing from the sequence SQ1 to the sequence SQ3 of Fig. 18, and thus description thereof is omitted.

20 In sequence SQ31 and sequence SQ32, according to the position in the parking lot of a vacant space existing in the traveling direction of the car comprehended and managed, the information processing apparatus 1 transmits a
25 vacant space object indicating the vacant space and position information of the vacant space to the car 2 via an antenna 4 close to the position of the car.

In sequence SQ33, the car 2 generates a

virtual space image in the parking lot in which the vacant space object received from the information processing apparatus 1 is displayed at the position indicated by the position
5 information.

In sequence SQ34, the car 2 performs control to project the generated virtual space image on the display of the car, to thereby display the virtual space image in a manner overlaid on a
10 view in the parking lot from the display.

[0097] In the structure as in this embodiment, it is possible to provide a technology allowing the driver to find and reach a target vacant space without updating the map information of the
15 car navigation system mounted in each car or even when no car navigation system is mounted in each car.

[0098] <Other embodiments>

Hereinafter, other embodiments will be
20 described.

When there exist plural cars in the parking lot, the information processing apparatus 1 may be configured to predict a parking status after a predetermined time (for example, after one
25 minute) based on contents of guidance to a certain car (for example, information related to a route to a vacant space, or the like), and change a destination of guidance to a vacant space for another car.

Further, when there exists a vehicle not complying with guidance based on images from the parking lot cameras 5 and the like, the information processing apparatus 1 may be
5 configured to switch the guidance to a next-best destination of guidance. Note that at this time, the information processing apparatus 1 may be configured to change the prediction of parking status.

10 Further, when a blind corner or the like exists in the parking lot cameras 5, the information processing apparatus 1 may be configured to predict the parking status and compensate the blind corner based on entrance
15 information, exit information, and/or guidance histories or the like of the parking lot.

Further, the information processing apparatus 1 may be configured to determine the size (height, light car, large car) and so on of
20 a car based on the image of the car (for example, a number plate or the like) imaged at the entrance and verify them with information related to standards of the vacant space managed in the parking lot map, and determine vacant space
25 information corresponding to the size of the vehicle.

[0099] Further, in the above-described embodiments, the information processing apparatus 1 determines the position and direction of the

car based on images from the parking lot cameras
5 or the like. However, the information
processing apparatus 1 may be configured to
determine the position and movement (direction)
10 of the car from wireless communication between
the antenna 4, which is an example of wireless
access point, and the car 2. Further, when the
car 2 is equipped with a camera, the information
processing apparatus 1 may be configured to
15 receive an image imaged by the camera of the car
2 via wireless communication or the like, and
determine the position and direction of the car
based on the image. Further, when the car 2 has
a GPS compass (or GPS receiver) obtaining
20 position information of the car (longitude,
latitude) or a gyro compass obtaining the
direction of the car, the information processing
apparatus 1 may be configured to obtain the
position information and direction of the car
25 from the car 2 via wireless communication to
determine them. Further, the information
processing apparatus 1 may be configured to
determine the position and direction of the car
by combining these plural methods.

[0100] Further, although the information
processing apparatus 1 is described to perform
wireless communication with the car 2 via the
antennas 4 in the above-described embodiments,
the information processing apparatus 1 may be

configured to perform wireless communication directly with the car 2 without intervention of the antennas 4.

Further, the car 2 may be configured to
5 transmit speed information of itself to the information processing apparatus 1. In such a structure, the information processing apparatus 1 determines a vacant space existing in the traveling direction of the car 2 according to the
10 speed information of the car 2. Note that the information processing apparatus 1 may be configured to obtain the speed information of the car 2 based on images of the car 2 from the parking lot cameras 5.

15 Further, when the car 2 has an imaging device such as a camera, the car 2 may be configured to overlay an image in the parking lot imaged by the imaging device and a virtual space image received from the information processing
20 apparatus 1 and display the overlaid images on the display or the like, or display the image and the virtual space image on a display device of a car navigation system (that is, a non-transmissive display or the like).

25 Further, for example, in the above-described embodiments, the projector 24 of HUD type is described as an example, but it may be a transmissive display. For example, it may be a human body wearable type such as a Head Mounted

Display, or a non-human body wearable type such as a windshield on which a transmissive liquid crystal film is attached. For example, the car 2 displays the virtual space image on the

5 transmissive liquid crystal film, allowing seeing the virtual space image and a view in the parking lot from the windshield of the car as overlaid images.

Note that alignment of the virtual space

10 image and the view in the parking lot may be performed in the information processing apparatus 1 or in the car 2.

[0101] Note that the above-described embodiments may be combined arbitrarily and implemented.

15 Note that the above-described information processing apparatus 1 is an example of a computer.

[0102] <Embodiment 7>

Hereinafter, Embodiment 7 will be described.

20 Fig. 29 is a diagram illustrating an example of a system structure of an image display system of Embodiment 7. As illustrated in Fig. 29, in the image display system of Embodiment 7, a GPS compass (or GPS receiver) 2000 obtaining position

25 information of a ship, an information storage device 5000 storing an electronic marine chart including seafloor shapes and a tide table, an image display device 4000, an image providing device 1000 providing an image to the image

display device 4000, a gyro compass 7000000
obtaining the direction of the ship, and a cruise
control device 6000 controlling cruising of the
ship are connected via a network.

5 The GPS compass (or GPS receiver) 2000 as an
example of a position information obtaining
device obtains position information (longitude,
latitude) of the ship. Note that an example of
the position information obtaining device may be
10 a GPS compass or a GPS receiver, but for
simplicity of description, the GPS compass is
described below for example.

 The gyro compass 7000 as an example of a
direction obtaining device obtains the direction
15 of a ship.

 The image providing device 1000 obtains the
depth below sea level at the position of the ship
based on position information of the ship
obtained in the GPS compass 2000 and the tide
20 table and the electronic marine chart stored in
the information storage device 5000. Note that
the tide table shows data representing times and
heights of the sea level measured with reference
to a hydrographic datum or the like in
25 correlation in certain position information, and
is published by the Japan Coast Guard or the
like. Further, the electronic marine chart is,
for example, computerized map data of the sea
published by the Japan Coast Guard or the like,

and is categorized in various types depending on purposes, such as nautical charts, special charts, basic maps of the sea, topographic maps of coastal areas, land condition maps of coastal areas, marine geology maps, and so on. The electronic marine chart describes, for example, information related to depths measured with reference to a hydrographic datum or the like, statuses of channels, ocean currents and tidal currents, signs, coastal conditions, and so on, and for example, the basic maps of the sea include bathymetric charts representing seafloor topographies with depth contours, three-dimensional overhead view maps of the seafloor topographies, and so on. The image providing device 1000 may obtain the depth by calculation based on the position information, the tide table, and the information related to depths indicated on the electronic marine chart, or may obtain the depth from a table or the like in which the position information, the tide table, and the information related to depths indicated on the electronic marine chart are managed. Further, the image providing device 1000 creates a virtual space image of a seafloor shape below sea level at the depth at the position of the ship based on the position information, the obtained depth below sea level, and the electronic marine chart stored in the information

storage device 5000, and provides the virtual space image to the image display device 4000. For example, three-dimensional overhead view maps illustrating seafloor topographies are stored in the information storage device 5000, and a three-dimensional map of a seafloor topography at the relevant position and depth is extracted from marine charts of the three-dimensional overhead view maps or calculated based on the position information and the obtained depth below sea level, so as to create the virtual space image of the seafloor shape below sea level at the depth at the position of the ship. Note that the image providing device 1000 performs coordinate conversion of the image into an image of the view point from a windshield or the like of the ship, which will be described later, and provides the converted image to the image display device 4000. The image providing device 1000 is also an example of a computer.

The image display device 4000 is, as will be described later, a display device of transmissive liquid crystal film or the like attached to a windshield or the like of the ship, and displays the virtual space image of the seafloor shape provided from the image providing device 1000 in an overlaid manner below sea level on a view from the windshield or the like.

Note that besides the above-described

information, the information storage device 5000 stores own ship information obtained from a predetermined device or the like or calculated based on predetermined information as disclosed in the above-described prior art literatures. As examples of the own ship information, there are stored position information, movement information including a course, speed, and so on, draft information, cargo information, number of passengers, time information, and so on.

[0103] Fig. 30 is a diagram illustrating an example of a hardware structure of the image providing device 1000.

As illustrated in Fig. 30, the image providing device 1000 has, as a hardware structure, a structure in which a control device 1100, a storage device 1200, and a communication device 1300 are connected via a bus 1400. The control device 1100 is a CPU or the like, and realizes functions of the image providing device 1000 by executing processing based on a program stored in the storage device 1200 or the like. The storage device 1200 is a storage device such as RAM, ROM, or HDD which stores a program as well as data and the like used by the control device 1100 when executing processing based on the program. The communication device 1300 is in charge of control of communication between the image providing device 1000 and other devices in

the image display system.

[0104] Fig. 31 is a diagram illustrating an example of a hardware structure of the image display device 4000.

5 As illustrated in Fig. 31, the image display device 4000 has, as a hardware structure, a structure in which a control device 2100, a storage device 2200, a communication device 2300, and a display device 2400 are connected via a bus
10 250000. The control device 2100 is a CPU or the like, and realizes functions of the image display device 4000 by executing processing based on a program stored in the storage device 2200 or the like. The storage device 2200 is a storage
15 device such as RAM, ROM, or HDD which stores a program as well as data and the like used by the control device 2100 when executing processing based on the program. The communication device 2300 is in charge of control of communication
20 between the image display device 4000 and other devices in the image display system. The display device 2400 is a transmissive liquid crystal film or the like attached on a windshield or the like of the ship, and displays an image and so on
25 provided by the image providing device 1000 under control of the control device 2100.

[0105] Fig. 32 is a diagram illustrating an example of a software structure of the image providing device 1000.

As illustrated in Fig. 32, the image providing device 1000 includes an image provision control unit 3100 as a software structure (functional structure). The image provision control unit 3100 obtains the depth below sea level at the position of the ship based on the position information of the ship obtained in the GPS compass 2000, and the tide table and the electronic marine chart stored in the information storage device 5000. Generally, for example, information related to a depth measured with reference to a hydrographic datum or the like on the electronic marine chart is compensated with information related to the tide level at the relevant time and position managed in the tide table, so as to obtain the depth below sea level at the position of the ship. Then, the image provision control unit 3100 extracts seafloor topography image data at the position information and depth from the bathymetric charts of the electronic marine chart based on the position information, the obtained depth below sea level, and the electronic marine chart stored in the information storage device 5000 so as to create a virtual space image of the seafloor shape below sea level at the depth at the position of the ship, and provides the virtual space image to the image display device 4000. Note that the image provision control unit 3100 performs coordinate

conversion of the image into an image of the view point from a windshield of the ship which will be described later, and provides the image to the image display device 4000.

5 The image provision control unit 3100 determines the visual field from the display device 2400 based on the position of the image display device 4000 (more specifically, the display device 2400 of the image display device
10 4000) determined by a relative positional relation from the position information as a reference point of the ship obtained in the GPS compass 2000, the direction of the ship obtained in the gyro compass 7000, the size of the display
15 device 2400, and so on. Then, based on the determined visual field, the depth below sea level, and the electronic marine chart, the image provision control unit 3100 may extract seafloor topography image data at the position information
20 and the depth in the determined visual field from the electronic marine chart such as the three-dimensional overhead view maps illustrating bathymetric charts, to thereby create a virtual space image of a seafloor shape below sea level
25 at the depth in the visual field. Note that the image provision control unit 3100 may create a virtual space image of a seafloor shape below sea level at the depth in the visual field, or may create a virtual space image of a seafloor shape

below sea level at the depth at the position of the ship, perform the coordinate conversion, and then extract an image in the visual field from the image on which the coordinate conversion is performed.

Further, the image provision control unit 3100 obtains a draft of the ship according to the cargo and/or the number of passengers of the ship. For example, the draft information stored in the information storage device 5000 is compensated with the weight of cargo, and so on to obtain the draft of the ship. Then, the image provision control unit 3100 may calculate the difference between the depth below sea level and the draft, that is, the distance from the lowest part of the ship to the seafloor shape based on the draft, the position information, the depth below sea level, and the electronic marine chart, create a virtual space image of a seafloor shape below sea level in which a seafloor shape below sea level at the depth at the position of the ship where a distance from a lowest part of the ship to the seafloor shape is within a predetermined distance is emphasized and displayed, and provide the virtual space image to the image display device. Such a structure can easily notify a shipman or the like of a seafloor shape having a hazard of collision.

[0106] Fig. 33 is a diagram illustrating an

example of a software structure of the image display device 4000.

As illustrated in Fig. 33, the image display device 4000 includes an image display control unit 4100 as a software structure (functional structure). The image display control unit 4100 displays the virtual space image of the seafloor shape provided by the image providing device 1000 in an overlaid manner below sea level on a view from the display device 2400. Fig. 34 is a diagram illustrating an example of displaying the virtual space image of the seafloor shape in an overlaid manner below sea level on the view from the display device 2400. For example, in Fig. 34, 5100 and 5200 are displayed as rocks on the seafloor on a windshield at the stem in a manner overlaid on a view from the windshield. In the case of the structure to perform emphasizing display as described above, when the rock 5100 on the seafloor exists within a predetermined distance from the lowest part of the ship, the rock 5100 on the seafloor is emphasized as compared to the rock 5200 on the seafloor. Note that as an example of the emphasizing display, a character string such as "collision hazard!" may be displayed near the rock 5200, or the rock 5200 may be outlined with red.

[0107] As described above, according to this embodiment, information which is beneficial while

the ship is cruising can be provided in a manner that a shipman or the like can intuitively comprehend the situation.

[0108] <Embodiment 8>

5 Hereinafter, Embodiment 8 will be described. In Embodiment 8, mainly differences from Embodiment 7 will be described.

Fig. 35 is a diagram illustrating an example of a system structure of an image display system of Embodiment 8. As illustrated in Fig. 35, the
10 image display system of Embodiment 8 newly includes a radar 8000 as an example of a radar device as compared to the image display system of Embodiment 7.

15 The image providing device 1000 of Embodiment 8 compares an image below sea level based on echoes of the radar 8000 with the electronic marine chart, and creates, when any obstacle not indicated on the electronic marine
20 chart is detected below sea level, a virtual space image of the seafloor shape including the obstacle and provides this image to the image display device 4000.

With the structure of Embodiment 8, an
25 obstacle such as sunken ship, caisson, or the like which is not indicated on the electronic marine chart can be detected, and the obstacle can be displayed in an overlaid manner below sea level on a view from the display device 2400.

Note that the radar 8000 of Fig. 35 may be a fish finder. With such a structure, a virtual space image of a seafloor shape including a marine life, such as a whale which can be an obstacle to a cruising ship, can be created and displayed in an overlaid manner below sea level on a view from the display device 2400.

[0109] <Embodiment 9>

Hereinafter, Embodiment 9 of the present invention will be described. In Embodiment 9, mainly differences from the above-described embodiment will be described.

Fig. 36 is a diagram illustrating an example of a system structure of an image display system of Embodiment 9. As illustrated in Fig. 36, in the image display system of Embodiment 9, a gyro sensor 9000 detecting a posture of the ship is newly included in the image display system as an example of a detecting device as compared to the image display system of Embodiment 7.

The image providing device 1000 of Embodiment 9 performs coordinate conversion so that the sea level of a created virtual space image of a seafloor shape and the sea level of a view from the image display device become horizontal based on the posture of the ship detected by the gyro sensor 9000, and provides the converted image to the image display device 4000.

With the structure of Embodiment 9, when the ship is in a swinging state, the actual sea level and the sea level of the virtual space image of the seafloor shape are matched and displayed on a windshield.

[0110] <Embodiment 10>

Hereinafter, Embodiment 10 will be described. In Embodiment 10, mainly differences from the above-described embodiments will be described.

Fig. 37 is a diagram illustrating an example of a system structure of an image display system of Embodiment 10. As illustrated in Fig. 37, in the image display system of Embodiment 10, a receiving device 10000 receiving information is newly included in the image display system as compared to the image display system of Embodiment 7.

The receiving device 10000 receives information related to other ships in the sea area where the ship is present from a marine traffic center or the like for example.

The image providing device 1000 of Embodiment 10 creates a virtual space image including information related to other ships received in the receiving device 10000, and provides the virtual space image to the image display device 4000.

The image display device 4000 displays the

virtual space image of the seafloor shape and the virtual space image including the information related to other ships which are provided by the image providing device 1000 in a manner overlaid
5 on a view from the display device 2400.

The structure of Embodiment 10 allows a shipmen or the like to intuitively recognize information related to other ships such as sizes and movements of other ships even in a dense fog
10 or the like.

[0111] <Embodiment 11>

Hereinafter, Embodiment 11 will be described. In Embodiment 11, mainly differences from the above-described embodiments will be
15 described.

Fig. 38 is a diagram illustrating an example of a system structure of an image display system of Embodiment 11. As illustrated in Fig. 38, in the image display system of Embodiment 11, as
20 compared to the image display system of Embodiment 7, a radar 8000 and a receiving device 10000 receiving information are newly included in the image display system.

The receiving device 10000 of Embodiment 11
25 receives from another ship an echo of a radar of the other ship obtained by the other ship and position information where this ship detected the echo.

Then, the image providing device 1000 of

Embodiment 11 compares an image based on an echo of the radar 8000 with an image based on the echo of the radar of the other ship received in the receiving device 10000 so as to create a virtual
5 space image including an obstacle detected by the echo of the radar 8000 and an obstacle which is not detected by the echo of the radar 8000, and provides the created virtual space image to the image display device 4000. At this time, since
10 the echo image of the radar of the other ship is generated based on the position where this ship detected the echo, this image is aligned with the image detected by the radar 8000 of the own ship using the received position information and then
15 compared.

The image display device 4000 displays the virtual space image of the seafloor shape provided by the image providing device 1000 and the virtual space image including the obstacle
20 detected by the echo of the radar 8000 and the obstacle which is not detected by the echo of the radar 8000 in a manner overlaid on a view from the display device 2400.

With the structure of Embodiment 11, by
25 receiving an echo of a radar captured by another ship and overlaying this echo with the echo of the radar of the own ship to take the difference therebetween, an obstacle (a ship, a reef, a marine life such as a whale, or the like) which

is not captured in the own ship can be identified, and a virtual space image including the obstacle can be created and displayed.

[0112] According to the above-described
5 embodiments, information which is beneficial while the ship is cruising can be provided in a manner that a shipman or the like can intuitively comprehend the situation.

[0113] In the foregoing, the preferred
10 embodiments of the present invention have been described in detail. However, the invention is not limited to such embodiments and can be modified or changed in various ways within the scope of the spirit of the present invention
15 which is described in the claims.

For example, in the above-described embodiments, what is called a transmissive display of non-human body wearable type, such as a window or the like on which a transmissive
20 liquid crystal film is attached, is described as an example, but a human body wearable type transmissive display such as a Head Mounted Display may be employed. Further, the image display device 4000 may be a mobile transmissive
25 or non-transmissive display which is held by a shipman or the like. In the case of the non-transmissive display, the non-transmissive display displays an image imaged by an imaging device and a virtual space image in an overlaid

manner.

Further, in the above-described embodiments,
the image display device 4000 is described as an
example, but a projector projecting a virtual
5 space image to a window or the like on which a
low-reflecting film is attached may be employed
for example.

Note that the above-described embodiments
may be combined arbitrarily and implemented.

10

INDUSTRIAL APPLICABILITY

[0114] The present invention is used for a
technology called augmented reality.

CLAIMS

[Claim 1] An information processing apparatus comprising an augmented reality presenting device capable of combining an image in real space with
5 computer-graphics image data and displaying the combined image and a managing device managing at least one of inventory information and sales information of respective products posted on a flier,

10 wherein the augmented reality presenting device comprises:

an imaging unit obtaining image data related to a product posted on the flier by imaging; and

15 a first transmitting unit transmitting the image data related to the product obtained by the imaging unit to the managing device,

wherein the managing device comprises:

20 a first obtaining unit determining, upon reception of the image data related to the product from the augmented reality presenting device, the product by analyzing the image data related to the product, and obtaining at least one of the inventory information and the sales information of the product; and

25 a second transmitting unit transmitting at least one of the inventory information and the sales information of the product obtained by the first obtaining unit to the augmented reality presenting device, and

wherein the augmented reality presenting device further comprises a presenting unit combining computer-graphics image data indicating at least one of the inventory information and the sales information of the product transmitted from the managing device with an image of the flier in real space and presenting the combined image.

[Claim 2] The information processing apparatus according to claim 1,

wherein the managing device obtains by the first obtaining unit at least one of inventory information and sales information which are registered at last, and transmits by the second transmitting unit at least one of the inventory information and the sales information which are registered at last to the augmented reality presenting device.

[Claim 3] The information processing apparatus according to claim 1,

wherein the augmented reality presenting device transmits to the managing device a guidance information request from a user on a product illustrated in the computer-graphics image presented by the presenting unit, and

wherein the managing device further comprises a third transmitting unit transmitting information related to a selling shop of the

product to the augmented reality presenting device in response to the obtained guidance information request, and the presenting unit of the augmented reality presenting device combines
5 computer-graphics image data indicating the information related to the selling shop which is obtained from the managing device with an image in real space and presents the combined image.

10 [Claim 4] The information processing apparatus according to claim 1,

wherein the augmented reality presenting device transmits by the first transmitting unit the image data related to the product to the
15 managing device in response to a specifying operation on the product by a user,

wherein the managing device further comprises a registering unit registering the product as a product to buy based on the image
20 data related to the product which are received from the augmented reality presenting device, and

wherein when a result of analyzing the image data related to the product which are received subsequently from the augmented reality
25 presenting device indicates that the product corresponding to the image data is registered in the registering unit, the first obtaining unit obtains at least one of the inventory information and the sales information of the product.

[Claim 5] The information processing apparatus according to claim 4,

wherein the augmented reality presenting
5 device further comprises:

a detecting unit detecting a specifying operation on the product by a user on the flier captured in an angle of view of an imaging device; and

10 a second obtaining unit obtaining image data related to the product which is the target of the specifying operation detected by the detecting unit,

wherein the first operating unit transmits
15 the image data related to the product obtained by the second obtaining unit to the managing device.

[Claim 6] An information processing method in an information processing system which comprises an
20 augmented reality presenting device capable of combining an image in real space with computer-graphics image data and displaying the combined image and a managing device managing at least one of inventory information and sales information of
25 respective products posted on a flier, the information processing method comprising:

an imaging step of obtaining by the augmented reality presenting device image data related to a product posted on the flier by

imaging;

a first transmitting step of transmitting by the augmented reality presenting device the image data related to the product obtained in the

5 imaging step to the managing device;

an obtaining step of determining by the managing device, upon reception of the image data related to the product from the augmented reality presenting device, the product by analyzing the
10 image data related to the product, and obtaining at least one of the inventory information and the sales information of the product;

a second transmitting step of transmitting by the managing device at least one of the
15 inventory information and the sales information of the product obtained in the obtaining step to the augmented reality presenting device; and

a presenting step of combining by the augmented reality presenting device computer-
20 graphics image data indicating at least one of the inventory information and the sales information of the product transmitted from the managing device with an image of the flier in real space and presenting the combined image.

25

[Claim 7] A program causing a computer to execute:

an imaging step of obtaining image data related to a product posted on a flier by

imaging;

5 a transmitting step of transmitting the image data related to the product obtained in the imaging step to a managing device managing at least one of inventory information and sales information of respective products posted on the flier; and

10 a presenting step of combining computer-graphics image data indicating at least one of the inventory information and the sales information of the product transmitted from the managing device with an image of the flier in real space and presenting the combined image.

15 [Claim 8] An information processing apparatus, comprising:

a vacant space information obtaining unit obtaining vacant space information of a parking lot;

20 a vehicle information obtaining unit obtaining a position and a direction of a car in the parking lot;

a vacant space determining unit determining a vacant space existing in a traveling direction of the car based on the vacant space information obtained in the vacant space information obtaining unit, the position and the direction of the car in the parking lot obtained in the vehicle information obtaining unit, and

information related to position information of respective vacant spaces of a parking lot map stored in a storage device;

an image generating unit generating a
5 virtual space image in the parking lot which includes a vacant space object indicating the vacant space determined in the vacant space determining unit and indicates a position of the vacant space; and
10 a transmitting unit transmitting the virtual space image generated in the image generating unit to the car.

[Claim 9] The information processing apparatus
15 according to claim 8, further comprising a route determining unit determining a route from the car to the vacant space based on the vacant space determined in the vacant space determining unit, the position and the direction of the car in the
20 parking lot obtained in the vehicle information obtaining unit, and the information related to the position information of respective vacant spaces of the parking lot map stored in the storage device,

25 wherein the image generating unit generates the virtual space image further including a guidance object indicating the route determined in the route determining unit.

[Claim 10] The information processing apparatus according to claim 9,

wherein when plural vacant spaces existing in the traveling direction of the car are
5 determined in the vacant space determining unit, the route determining unit determines a route from the car to the vacant space which is closest to the car out of the plural vacant spaces.

10 [Claim 11] The information processing apparatus according to claim 8, further comprising a fixture determining unit determining a fixture in the parking lot existing in the traveling
direction of the car based on the position and
15 the direction of the car in the parking lot which are obtained in the vehicle information obtaining unit and the parking lot map stored in the storage device,

wherein the image generating unit generates
20 the virtual space image which further includes a fixture object indicating the fixture existing in the traveling direction of the car determined in the fixture determining unit and indicates the position of the vacant space and a position of
25 the fixture.

[Claim 12] The information processing apparatus according to claim 8,

wherein when plural vacant spaces existing

in the traveling direction of the car are determined in the vacant space determining unit, the image generating unit generates the virtual space image including the vacant space object
5 which differs in shape or color corresponding to distances from the car to the vacant spaces.

[Claim 13] The information processing apparatus according to claim 8,
10 wherein the image generating unit generates, when a distance between the vacant space existing in the traveling direction of the car determined in the determining unit and the car is more than or equal to a predetermined distance, a virtual
15 space image which includes a vacant space ratio object representing a ratio of vacant space in one of predetermined blocks dividing the parking lot and indicates a position of the one block, and generates, when the distance is less than the
20 predetermined distance, a virtual space image which includes a vacant space object representing the vacant space existing in the traveling direction of the car determined in the determining unit and indicates the position of
25 the vacant space.

[Claim 14] An information processing apparatus, comprising:

a vacant space information obtaining unit

obtaining vacant space information of a parking lot;

a vehicle information obtaining unit obtaining a position and a direction of a car in
5 the parking lot;

a vacant space determining unit determining a vacant space existing in a traveling direction of the car based on the vacant space information obtained in the vacant space information
10 obtaining unit, the position and the direction of the car in the parking lot obtained in the vehicle information obtaining unit, and information related to position information of respective vacant spaces of a parking lot map
15 stored in a storage device; and

a transmitting unit transmitting to the car a vacant space object indicating the vacant space determined in the vacant space determining unit and position information representing a position
20 of the vacant space.

[Claim 15] A system comprising an information processing apparatus and a car,

wherein the information processing apparatus
25 comprises:

a vacant space information obtaining unit obtaining vacant space information of a parking lot;

a vehicle information obtaining unit

obtaining a position and a direction of a car in the parking lot;

a vacant space determining unit determining a vacant space existing in a traveling direction
5 of the car based on the vacant space information obtained in the vacant space information obtaining unit, the position and the direction of the car in the parking lot obtained in the vehicle information obtaining unit, and
10 information related to position information of respective vacant spaces of a parking lot map stored in a storage device;

an image generating unit generating a virtual space image in the parking lot which
15 includes a vacant space object indicating the vacant space determined in the vacant space determining unit and indicates a position of the vacant space; and

a transmitting unit transmitting the virtual
20 space image generated in the image generating unit to the car, and

wherein the car comprises:

a receiving unit receiving a virtual space image from the information processing apparatus;
25 and

a display control unit performing control to project the virtual space image received in the receiving unit on a display of the car so as to display the virtual space image in a manner

overlaid on a view in the parking lot from the display.

[Claim 16] A system comprising an information
5 processing apparatus and a car,
wherein the information processing apparatus
comprises:

a vacant space information obtaining unit
obtaining vacant space information of a parking
10 lot;

a vehicle information obtaining unit
obtaining a position and a direction of a car in
the parking lot;

a vacant space determining unit determining
15 a vacant space existing in a traveling direction
of the car based on the vacant space information
obtained in the vacant space information
obtaining unit, the position and the direction of
the car in the parking lot obtained in the
20 vehicle information obtaining unit, and
information related to position information of
respective vacant spaces of a parking lot map
stored in a storage device; and

a transmitting unit transmitting to the car
25 a vacant space object indicating the vacant space
determined in the vacant space determining unit
and position information representing a position
of the vacant space, and

wherein the car comprises:

a receiving unit receiving the vacant space object from the information processing apparatus and the position information;

an image generating unit generating a
5 virtual space image in the parking lot in which the vacant space object received in the receiving unit is displayed at a position indicated by the position information received in the receiving unit; and

10 a display control unit performing control to project the virtual space image generated in the image generating unit on a display of the car so as to display the virtual space image in a manner overlaid on a view in the parking lot from the
15 display.

[Claim 17] An information processing method executed by an information processing apparatus, the information processing method comprising:

20 a vacant space information obtaining step of obtaining vacant space information of a parking lot;

a vehicle information obtaining step of obtaining a position and a direction of a car in
25 the parking lot;

a vacant space determining step of determining a vacant space existing in a traveling direction of the car based on the vacant space information obtained in the vacant

space information obtaining step, the position and the direction of the car in the parking lot obtained in the vehicle information obtaining step, and information related to position
5 information of respective vacant spaces of a parking lot map stored in a storage device;

an image generating step of generating a virtual space image in the parking lot which includes a vacant space object indicating the
10 vacant space determined in the vacant space determining step and indicates a position of the vacant space; and

a transmitting step of transmitting the virtual space image generated in the image
15 generating step to the car.

[Claim 18] An information processing method executed by an information processing apparatus, the information processing method comprising:

20 a vacant space information obtaining step of obtaining vacant space information of a parking lot;

a vehicle information obtaining step of obtaining a position and a direction of a car in
25 the parking lot;

a vacant space determining step of determining a vacant space existing in a traveling direction of the car based on the vacant space information obtained in the vacant

space information obtaining step, the position and the direction of the car in the parking lot obtained in the vehicle information obtaining step, and information related to position
5 information of respective vacant spaces of a parking lot map stored in a storage device; and
a transmitting step of transmitting to the car a vacant space object indicating the vacant space determined in the vacant space determining
10 step and position information representing a position of the vacant space.

[Claim 19] A vacant space guidance method in a system comprising an information processing
15 apparatus and a car, the vacant space guidance method comprising:

a vacant space information obtaining step of obtaining by the information processing apparatus vacant space information of a parking lot;

20 a vehicle information obtaining step of obtaining by the information processing apparatus a position and a direction of a car in the parking lot;

a vacant space determining step of
25 determining by the information processing apparatus a vacant space existing in a traveling direction of the car based on the vacant space information obtained in the vacant space information obtaining step, the position and the

direction of the car in the parking lot obtained
in the vehicle information obtaining step, and
information related to position information of
respective vacant spaces of a parking lot map
5 stored in a storage device;

an image generating step of generating by
the information processing apparatus a virtual
space image in the parking lot which includes a
vacant space object indicating the vacant space
10 determined in the vacant space determining step
and indicates a position of the vacant space;

a transmitting step of transmitting by the
information processing apparatus the virtual
space image generated in the image generating
15 step to the car;

a receiving step of receiving by the car a
virtual space image from the information
processing apparatus; and

a display control step of performing control
20 by the car to project the virtual space image
received in the receiving step on a display of
the car so as to display the virtual space image
in a manner overlaid on a view in the parking lot
from the display.

25

[Claim 20] A vacant space guidance method in a
system comprising an information processing
apparatus and a car, the vacant space guidance
method comprising:

a vacant space information obtaining step of obtaining by the information processing apparatus vacant space information of a parking lot;

5 a vehicle information obtaining step of obtaining by the information processing apparatus a position and a direction of a car in the parking lot;

a vacant space determining step of determining by the information processing
10 apparatus a vacant space existing in a traveling direction of the car based on the vacant space information obtained in the vacant space information obtaining step, the position and the direction of the car in the parking lot obtained
15 in the vehicle information obtaining step, and information related to position information of respective vacant spaces of a parking lot map stored in a storage device;

a transmitting step of transmitting by the
20 information processing apparatus to the car a vacant space object indicating the vacant space determined in the vacant space determining step and position information representing a position of the vacant space;

25 a receiving step of receiving by the car the vacant space object from the information processing apparatus and the position information;

an image generating step of generating by

the car a virtual space image in the parking lot in which the vacant space object received in the receiving step is displayed at a position indicated by the position information received in
5 the receiving step; and

a display control step of performing by the car control to project the virtual space image generated in the image generating step on a display of the car so as to display the virtual
10 space image in a manner overlaid on a view in the parking lot from the display.

[Claim 21] A program causing a computer to execute: a vacant space information obtaining
15 step of obtaining vacant space information of a parking lot;

a vehicle information obtaining step of obtaining a position and a direction of a car in the parking lot;

20 a vacant space determining step of determining a vacant space existing in a traveling direction of the car based on the vacant space information obtained in the vacant space information obtaining step, the position
25 and the direction of the car in the parking lot obtained in the vehicle information obtaining step, and information related to position information of respective vacant spaces of a parking lot map stored in a storage device;

an image generating step of generating a virtual space image in the parking lot which includes a vacant space object indicating the vacant space determined in the vacant space
5 determining step and indicates a position of the vacant space; and

a transmitting step of transmitting the virtual space image generated in the image generating step to the car.
10

[Claim 22] A program causing a computer to execute:

a vacant space information obtaining step of obtaining vacant space information of a parking
15 lot;

a vehicle information obtaining step of obtaining a position and a direction of a car in the parking lot;

a vacant space determining step of
20 determining a vacant space existing in a traveling direction of the car based on the vacant space information obtained in the vacant space information obtaining step, the position and the direction of the car in the parking lot
25 obtained in the vehicle information obtaining step, and information related to position information of respective vacant spaces of a parking lot map stored in a storage device; and
a transmitting step of transmitting to the

car a vacant space object indicating the vacant space determined in the vacant space determining step and position information representing a position of the vacant space.

5

[Claim 23] An image display system comprising a position information obtaining device obtaining position information of a ship, an information storage device storing an electronic marine chart including seafloor shapes and a tide table, an image display device, and an image providing device providing an image to the image display device,

wherein the image providing device obtains a depth below sea level at a position of the ship based on the position information of the ship obtained in the position information obtaining device, the tide table, and information related to depths indicated on the electronic marine chart, creates a virtual space image of a seafloor shape below sea level at the depth at the position of the ship based on the position information, the depth below sea level, and seafloor topography image data indicated on the electronic marine chart, and provides the virtual space image to the image display device, and

wherein the image display device displays the virtual space image of the seafloor shape provided by the image providing device in a

manner overlaid on a view from the image display device.

[Claim 24] The image display system according to
5 claim 23,

wherein the image providing device obtains a draft of the ship according to at least one of information related to cargo and information related to number of passengers of the ship which
10 are stored in the information storage device, creates a virtual space image of a seafloor shape below sea level in which a seafloor shape below sea level at the depth at the position of the ship where a distance from a lowest part of the
15 ship to the seafloor shape is within a predetermined distance is emphasized and displayed based on the draft, the position information, the depth below sea level, and the electronic marine chart, and provides the virtual
20 space image to the image display device.

[Claim 25] The image display system according to claim 23, further comprising a direction obtaining device obtaining the direction of the
25 ship,

wherein the image providing device determines a visual field from the image display device based on the position information of the ship obtained in the position information

obtaining device and the direction obtained in the direction obtaining device, creates a virtual space image of a seafloor shape below sea level at the depth within the visual field based on the
5 determined visual field, the depth below sea level, and seafloor topography image data indicated on the electronic marine chart, and provides the virtual space image to the image display device.

10

[Claim 26] The image display system according to claim 23, further comprising a radar device,

wherein the image providing device compares an image below sea level based on an echo of the
15 radar device with seafloor topography image data indicated on the electronic marine chart, and creates, when any obstacle not indicated on the electronic marine chart is detected below sea level, a virtual space image of the seafloor
20 shape below sea level including the obstacle, and provides the virtual space image to the image display device.

[Claim 27] The image display system according to
25 claim 23, further comprising a detecting device detecting a posture of the ship,

wherein the image providing device performs coordinate conversion so that a sea level of the created virtual space image of the seafloor shape

becomes horizontal with a sea level of the view from the image display device based on the posture of the ship detected in the detecting device, and provides the converted image to the
5 image display device.

[Claim 28] The image display system according to claim 23, further comprising a receiving device receiving information,

10 wherein the receiving device receives information of other ships in a sea area where the ship is present from a marine traffic center,

wherein the image providing device creates a virtual space image including the information of
15 other ships received in the receiving device and provides the virtual space image to the image display device, and

wherein the image display device displays the virtual space image of the seafloor shape
20 provided by the image providing device and the virtual space image including the information of other ships in a manner overlaid on a view from the image display device.

25 [Claim 29] The image display system according to claim 23, further comprising:

a radar device; and

a receiving device receiving information,

wherein the receiving device receives from

another ship an echo of a radar device of the other ship which is obtained by the other ship,

wherein the image providing device compares an image based on the echo of the radar device
5 with an image based on the echo of the radar device of the other ship received by the receiving device to thereby create a virtual space image including an obstacle which is detected with the echo of the radar device and an
10 obstacle which is not detected with the echo of the radar device and provides the created virtual space image to the image display device, and

wherein the image display device displays the virtual space image of the seafloor shape
15 provided by the image providing device and the virtual space image including the obstacle which is detected with the echo of the radar device and the obstacle which is not detected with the echo of the radar device, in a manner overlaid on a
20 view from the image display device.

[Claim 30] An image display method in an image display system comprising a position information obtaining device obtaining position information
25 of a ship, an information storage device storing an electronic marine chart including seafloor shapes and a tide table, an image display device, and an image providing device providing an image to the image display device, the image display

method comprising:

5 a step of obtaining a depth below sea level at a position of the ship based on the position information of the ship obtained in the position information obtaining device, the tide table, and information related to depths indicated on the electronic marine chart, creating a virtual space image of a seafloor shape below sea level at the depth at the position of the ship based on the position information, the depth below sea level, and seafloor topography image data indicated on the electronic marine chart, and providing the virtual space image to the image display device by the image providing device; and

10 a step of displaying the virtual space image of the seafloor shape provided by the image providing device in a manner overlaid on a view from the image display device by the image display device.

20

[Claim 31] A program causing a computer to execute:

a measuring step of obtaining a depth below sea level at a position of a ship based on position information of the ship, a tide table, and information related to depths indicated on an electronic marine chart; and

25

a step of creating a virtual space image of a seafloor shape below sea level at the depth at

the position of the ship based on the position
information, the depth below sea level calculated
in the measuring step, and seafloor topography
image data indicated on the electronic marine
5 chart, and providing the virtual space image to
an image display device.