COMMUNICATIONS SYSTEM PROVIDING EXTENSIBLE PROTOCOL TRANSLATION AND CONFIGURATION FEATURES AND RELATED METHODS

Field of the Invention

[0001] The present invention relates to the field of communications systems, and, more particularly, to communications systems using multiple operating protocols for data access operations and related methods.

Background of the Invention

[0002] Software clients operating on or in conjunction with a computer system are often used to access data stored at a server with which the computer system can establish communications, such as through a local area network (LAN). In many instances, the data on the server is accessible only through a particular protocol, which in turn tends to limit a user to a particular client. Similarly, a particular type of client is typically configurable to operate with only certain types of servers or protocols. In an e-mail system, for example, in which users have associated mailboxes on a mail server, a particular protocol and often a particular messaging client is required for e-

mail access. There is no single standard method for accessing e-mail stored on a server. Instead, there are several incompatible protocols defined by various vendors and standards bodies.

[0003] Each category of client accessing an application may have different capabilities and needs. For example, a POP client accessing a mail service may require a list of unique identifiers (UIDs) from the server, whereas a WAP client may require not only the UIDs, but also a subject. A desktop browser client may require not only UID and subject, but also information regarding message origination, date, importance, etc. When developing a service that can handle all of these needs, it would a more efficient use of bandwidth and processing power, both on the server and on a target data system such as a mail store, if only the necessary attributes were requested and returned whenever possible.

[0004] Another problem is that each of these clients may require slightly different behavior in response to a request. For example, a POP client might request that a message on the server be deleted, however, instead of removing it at the time of the request, the service has to wait until the POP client issues the QUIT command. For a WAP client, on the other hand, the message should be deleted immediately in response to a delete request.

[0005] A further problem that frequently occurs when building an application has to do with memory consumption and application performance. To improve performance, it often makes sense to cache results from a data store to more quickly respond to a follow-on request from the client. If data is stored in memory, the application can quickly use up all available

memory. Even caching the data on disk can lead to disk space problems.

[0006] It is also possible to access multiple data sources that have different capabilities or support different mechanisms for querying information. In this case, code can quickly become convoluted when attempting to manage multiple and different request types.

[0007] Various prior art approaches have been developed for providing communications between systems and devices using different operating protocols. One such approach is set forth in U.S. Patent No. 6,615,212 to Dutta et al., in which a transcoding proxy server receives a request for content from a client machine. The transcoding proxy server retrieves the content from an originating server. The retrieved content is provided in a first format type. In response to a determination that an increase in efficiency would be obtained by allowing the client to process the content in the first format type prior to transcoding the content into a second format type, the transcoding proxy server sends the content to the client in the first format type.

[0008] Furthermore, in response to a determination that the client does not have content processing software for processing the content in the first format, the transcoding proxy server sends content processing software for the first format type along with the content in the first format type to the client. The transcoding proxy server then transcodes the content from the first format type into the second format type and sends the content in the second format to the client.

[0009] Despite such prior art approaches, further protocol translation and/or conversion functionality may be desirable in certain applications.

Summary of the Invention

[0010] In view of the foregoing background, it is therefore an object of the present invention to provide a communications system providing enhanced operating protocol conversion features and related methods.

[0011] This and other objects, features, and advantages in accordance with the present invention are provided by a communications system which may include a plurality of data storage devices each using at least one of a plurality of different operating protocols, and a plurality of mobile wireless communications devices for accessing the plurality of data storage devices. Each mobile wireless communications device may also use at least one of the plurality of different operating protocols. The system may further include a protocol interface device. In particular, the protocol interface device may include a protocol engine module for communicating with the plurality of data storage devices using respective operating protocols, and a front-end proxy module coupled to the protocol engine. The protocol interface device may further include a respective proxy module for communicating with the plurality of mobile wireless communications devices using each different operating protocol, and at least one common core service module coupled to the proxy modules.

[0012] Additionally, the front-end proxy module may also include a configuration file module coupled to the front-end proxy module for storing a plurality of different sets of configuration files relating to

different allocations of resources of the at least one common core service module. The plurality of different sets of configuration files may include a primary set of configuration files corresponding to core resource allocation operations, and a secondary set of configuration files for customizing the core resource allocation operations. Thus, for example, if a secondary file is specified, resources defined in the secondary file may override those specified in the corresponding primary configuration file(s). This allows a user to specify a core set of resources yet still modify these core resources as desired for a particular application.

[0013] More particularly, the at least one common core service module may be for routing traffic between the proxy modules and the protocol engine module, for accessing data from the plurality of data storage devices, and/or rendering data for the plurality of mobile wireless communications devices. In other words, the front-end proxy module advantageously may be used with numerous types of operating protocols, yet still use common core services to route traffic, access data, and/or render data. This provides greater efficiencies, as well as reduced complexity.

[0014] The at least one common core service module may include a plurality of handlers for interfacing the proxy modules with the protocol engine module. More specifically, the plurality of proxy modules may convert access requests from the plurality of mobile wireless communications devices to common access parameters. In addition, the front-end proxy module may also include a flow controller module for receiving the common access parameters from the plurality of proxy

modules and selecting desired handlers for processing thereof. Moreover, the plurality of handlers and the protocol engine module may communicate using a common interface protocol.

[0015] Furthermore, the at least one common core service module may include a renderer module for cooperating with the proxy modules to format data for the plurality of mobile wireless communications devices. Additionally, the at least one common core service module may also include an extensible mark-up language (XML) engine module coupled to the renderer module, such as an extensible stylesheet language transformations (XSLT) engine module, for example. Also, the at least one common core service module may further include a memory coupled to the XML engine module for storing a plurality of templates corresponding to respective operating protocols.

[0016] A method aspect of the invention is for interfacing a plurality of mobile wireless communications devices with a plurality of data storage devices. The mobile wireless communications devices and the data storage devices may each use at least one of a plurality of different operating protocols. The method may include providing a protocol engine module for communicating with the plurality of data storage devices using respective operating protocols, and coupling a front-end proxy module to the protocol engine module. More particularly, the front-end proxy module may include a respective proxy module for communicating with the plurality of mobile wireless communications devices using each different operating protocol, and at least one common core service module coupled to the proxy modules. The method may further

include providing a configuration file module for the front-end proxy module for storing a plurality of different sets of configuration files relating to different allocations of resources of the at least one common core service module.

[0017] A protocol interface device in accordance with the invention may include a front-end proxy module and a protocol engine module, and a configuration file module, such as those described briefly above, for example. Moreover, a computer-readable medium in accordance with the present invention may similarly include a front-end proxy module, a protocol engine module, and a configuration file module.

Brief Description of the Drawings

[0018] FIG. 1 is a schematic block diagram of a communications system in accordance with the present invention.

[0019] FIG. 2 is a schematic block diagram illustrating the protocol interface device of the communications system of FIG. 1 in greater detail.

[0020] FIG. 3 is a schematic block diagram illustrating the extensible front-end proxy module of the protocol interface device of FIG. 2 in greater detail.

[0021] FIGS. 4 and 5 are schematic block diagrams illustrating an alternate embodiment of a communications system in accordance with the invention implementing an extensible proxy architecture similar to that of FIG. 3.

[0022] FIG. 6 is a schematic block diagram of an alternate embodiment of the protocol interface device of FIG. 2.

[0023] FIG. 7 is a schematic block diagram further illustrating the protocol engine module of the protocol interface device of FIG. 3 and interface connector modules therefor.

[0024] FIG. 8 is a schematic block diagram of an alternate embodiment of the protocol engine module and interface connector modules of FIG. 7.

[0025] FIG. 9 is a schematic block diagram of still another alternate embodiment of the protocol interface device of FIG. 2.

[0026] FIG. 10 is a schematic block diagram of yet another alternate embodiment of the protocol interface device of FIG. 2.

[0027] FIG. 11 is a flow diagram illustrating operation of the protocol interface device of FIG. 2.

[0028] FIG. 12 is a flow diagram illustrating operation of the front-end proxy module of FIG. 3.

[0029] FIG. 13 is a flow diagram illustrating operation of the communications system of FIG. 5.

[0030] FIG. 14 is a flow diagram illustrating operation of the protocol interface module of FIG. 6.

[0031] FIG. 15 is a flow diagram illustrating operation of the protocol engine and interface connector modules of FIG. 7.

[0032] FIG. 16 is a flow diagram illustrating operation of the protocol interface device of FIG. 9.

[0033] FIG. 17 is a flow diagram illustrating operation of the protocol interface device of FIG. 10.

[0034] FIG. 18 is a schematic block diagram of an exemplary mobile wireless communications device for use with the present invention.

Detailed Description of the Preferred Embodiments

[0035] The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout, and prime notation and multiple prime notation are used to indicate similar elements in alternate embodiments.

Turning now to FIG. 1, a communications system **10** includes a protocol interface device **14** that provides access to a plurality of data storage devices or systems **16, 18, 20.** The communications system **10** illustratively includes a plurality of communications devices, namely a mobile wireless communications device **11** and a communications device **12** connected to the system via a wired connection. By way of example, various mobile wireless communications devices may be used in accordance with the invention, such as personal data assistants (PDAs), cellular telephones, etc. An exemplary mobile wireless communications device **11** suitable for use with the present invention is described in the example provided below with reference to FIG. 18. Moreover, examples of wired communications devices include personal computers, telephones, fax machines, etc. Of course, numerous wired and wireless devices may be used, although only two are shown in the exemplary embodiment for clarity of illustration.

[0036] The communications devices **11, 12** typically include software clients, which are software modules or applications that operate on or in conjunction with their respective communications device to provide access to data stored at one or more of the data storage devices **16, 18,** and **20** through the protocol interface device **14.** Those skilled in the art will appreciate that such communications devices also include further components and/or software modules, which have not been explicitly shown in FIG. 1 for clarity of illustration. With respect to the mobile wireless communications device **11,** its software client communicates with the protocol interface device **14** via a wireless communication network **13,** and perhaps other networks as well (e.g., a public switched telephone network (PSTN) or the Internet), as will be appreciated by those skilled in the art.

[0037] The various functions and operations of the protocol interface device **14** are preferably implemented in software operating thereon, or in conjunction therewith. The protocol interface device **14** illustratively bridges the software clients of the communications devices **11, 12** and the data storage devices **16, 18, 20.** Communications between the protocol interface device **14,** the communications devices **11, 12,** and the data storage devices **16, 18, 20** are preferably via a wide area network (WAN) such as the Internet. That is, the communications devices **11, 12** may communicate with the protocol interface device **14** via the Internet, as noted above, and so too may the protocol interface device communicate with the data storage devices **16, 18, 20.**

[0038] Of course, other implementations are also contemplated. For example, the protocol interface device **14** may be implemented in a private network that also includes the data storage devices **16, 18, 20,** the communications devices **11, 12,** or both the data storage devices and the communications devices (e.g., in a WAN). It should be noted that the present invention is in no way limited to any particular connection or communication scheme.

[0039] The data storage devices **16, 18, 20** store data to be accessed by the software clients of the communications devices **11, 12.** Although some software clients are configurable to directly access certain types of data storage devices, they are often data system specific or protocol specific, as described briefly above. More particularly, on constrained electronic devices such as the mobile wireless communication device **11,** processor power, memory resources, and communication channel characteristics may preclude the installation and operation of software clients having the same capabilities as those commonly used on desktop and laptop computer systems, for example. In addition, while the installation of multiple software clients for accessing data storage devices associated with different protocols is feasible for desktop and laptop computer systems, providing multiple-protocol support on such constrained devices may not be possible.

[0040] The data storage devices **16, 18, 20** are accessible using different operating protocols or access schemes. As such, the protocol interface device **14** accesses the data storage devices **16, 18, 20** via an operating protocol supported by respective data storage

devices, and provides data to the communications device **11, 12** via a respective client-supported operating protocol. The protocol conversion functionality of the protocol interface device **14** provides a unified approach to support access to multiple types of data system. As described in further detail below, the protocol interface device **14** provides an "any-to-any" bridge between different protocols or access schemes.

[0041] The protocol interface device **14** is illustrated in further detail in FIG. 2. As noted above, the protocol interface device **14** bridges different types of communications devices with different types of data storage devices. In the illustrated embodiment, data storage devices **24, 26, 28** are systems/servers for storing electronic mail (e-mail). However, it should be noted that the present invention is not limited to mail system access. Each of the mail systems **24, 26, 28** supports a different operating protocol or access scheme. More particularly, the mail system **24** supports Outlook Web Access (OWA), the mail system **26** supports Microsoft Messaging Application Programming Interface (MAPI), and the mail system **28** supports a proprietary protocol, such as that used by America Online (AOL), for example.

[0042] The protocol interface system **14** illustratively includes a front-end proxy module **30**. The front-end proxy module illustratively includes proxy modules **34, 36, 38, 40** which respectively support the Wireless Application Protocol (WAP), the Post Office Protocol (POP), the Internet Message Access Protocol (IMAP), and the Hypertext Transfer Protocol (HTTP) for communication with clients.

[0043] The front-end proxy **30** also communicates with a protocol engine module **32**. The protocol engine module **32** translates OWA, MAPI, the proprietary protocol of the mail system **28** (and other protocols, if desired) into a format compatible with the front-end proxy module **30**. To this end, a respective interface connector module may **70-77** (FIG. 7) be coupled to the protocol engine module **32** for each of the operating protocols used by the mail systems **24, 26, 28**, as will be discussed further below. In a preferred embodiment, the front-end proxy module **30** and the protocol engine module **32** are extensible or expandable to accommodate additional operating protocols as they become available, as will also be discussed further below.

[0044] In operation, a user accesses a mailbox on one of the mail systems **24, 26, 28** through client software on his communications device. For example, a WAP browser on a mobile wireless communication device communicates with the WAP proxy module **34** to access the mail system **24**. Access commands or instructions received by the WAP proxy **34** are converted into a format compatible with the protocol engine module **32**. Communications between the front-end proxy module **30** and the protocol engine module **32** are preferably achieved via a common interface protocol, which may be a proprietary protocol or an established public protocol.

[0045] The protocol engine module **32** then translates the access commands or instructions received from the front-end proxy module **30** into a protocol associated with the mail system to be accessed (e.g., OWA for the mail system **24**). Data received from the mail system (e.g., e-mail messages, a list of new messages,

calendar appointments, tasks, etc., depending on the particular mail system), the features that its access protocol supports, and the nature of the access command are translated into the common interface protocol and transferred to the front-end proxy.

[0046] The active proxy module (i.e., the WAP proxy module **34** in the present example) then formats the received data, or at least portions thereof, for the requesting client. Further commands from the client are also translated by the protocol interface device **14**. Access commands from other types of clients are similarly processed. It should be noted that several mail systems may be accessed in response to a single access command, where a user has enabled multiple mailbox access through the protocol interface device **14**.

[0047] The protocol interface device **14** thus allows clients using different operating protocols to access the mail systems **24, 26, 28**, which also use different operating protocols. Access commands such as move, delete, create, send, fetch, and view, for example, that are generated at a client affect the data stored at the mail systems **24, 26, 28** instead of copies of the data. Through the protocol interface device **14**, a client compatible with any one of the proxy modules **34, 36, 38, 40** is provided access to one or more of the mail systems **24, 26, 28**. The client itself advantageously need not support the access protocol or scheme associated with the mail system(s) to be accessed.

[0048] Since the mail system protocol and the client protocol need not be compatible, feature support between the protocols may be different. For example, a

POP client does not support the same features as OWA. The interface protocol used between the protocol engine module **32** and the front-end proxy module **30** is preferably designed to be able to represent a desired number of protocol-supported elements or features for a desired operating protocol. More specifically, the common interface protocol is preferably able to represent all protocol-supported elements for the most "capable" protocol (OWA in the present example), to provide the broadest possible feature support. Further still, the common interface protocol may support a full feature set across all supported protocols, if desired.

[0049] By way of example, the common interface protocol may be a proprietary protocol based on the Web-based Distributed Authoring and Versioning (WebDAV) protocol. An example of an authentication request using such a common interface protocol is provided as program listing #1, below. This exemplary authentication request routine allows the protocol interface device **14** to be authenticated by a mail system using a user identifier and password provided by a user, and it also retrieves a root folder and basic capabilities of a target mailbox on the mail system.

[0050] An exemplary inbox request in accordance with a WebDAV-based common interface protocol is set forth below as program listing #2. In accordance with this routine, responsive to an inbox request, the capabilities of the inbox in a target mailbox are queried, and then its contents are queried. Another example is provided below as program listing #3, which is for a folder search request in accordance with the aforementioned WebDAV-based common interface protocol. Here, a list of subfolders for a given folder is

returned in response to this request. It will be appreciated by those skilled in the art that numerous other requests and operations may be used as well.

[0051] It should be noted that the software clients need not initiate data access requests in all embodiments. For example, in some embodiments the protocol interface device **14** may include (or communicate with) a polling or aggregation engine module (not shown) that prompts the protocol engine module **32** to aggregate messages for respective users from the mail systems **24, 26, 28** at predetermined intervals, as will be appreciated by those skilled in the art. The protocol engine module **14** would then cooperate with the front-end proxy module **30** to provide the aggregated messages to the respective software clients, as described above. Additionally, the front-end proxy module **30** need not communicate directly with the communications devices **11, 12** in all embodiments, but it may instead communicate therewith via an intervening mail system or server, for example. Thus, in the case where an aggregation engine module is used, the aggregated messages may be first transferred by the front-end proxy module **30** to an intervening mail server, which in turn provides the messages to the appropriate communications device, as will also be appreciated by those skilled in the art. Here again, the front-end proxy module **30** would use the appropriate protocol(s) supported by such intervening mail server for communicating therewith.

[0052] A method for providing access to a plurality of data storage devices, such as the mail systems **24, 26, 28**, using the protocol interface system **14** is illustrated in FIG. 11. Beginning at Block **110**, an

access command or data is first received, at Block **111**. The access command or data is translated into the common interface protocol, at Block **112**. An access command is then translated (Block **113**) into a data system protocol associated with the data system to be accessed, such as OWA for the mail system **24**, for example.

[0053] On the other hand, data is translated into the client protocol, at Block **113**. Depending upon the particular features supported by the client protocol, only those portions of the data corresponding to elements of the interface protocol that are supported by the client protocol are translated during this step. The protocol interface device **14** may generate an error responsive to a non-supported operating protocol. More particularly, non-supported interface protocol elements are preferably ignored or processed according to a default or error-processing scheme. Translated access commands or data are then transferred to a data system or a client, at Block **114**, thus concluding the illustrated method (Block **115**).

[0054] Turning now additionally to FIG. 3, an exemplary embodiment of the front-end proxy module **30** is now described. The front-end proxy module **30** illustratively includes the proxy modules **34**, **36**, **38**, **40**, a renderer module **44**, an extensible stylesheet language transformations (XSLT) engine module **46**, a memory or template store **48**, a flow controller module **50**, and handlers **52a-52n**.

[0055] As noted above, each proxy module **34**, **36**, **38**, **40** effectively "fronts" the protocol engine module **32** and translates respective operating protocols for different client types. For example, a WAP proxy module

provides information retrieved from one or more of the handlers **52a-52n** in the form of WML documents targeted for display on devices such as cell phones and PDAs. A POP proxy makes use of at least some of the same proxy components, including the flow controller module **50** and the renderer module **44** to render data in the form required by the POP protocol.

[0056] One particularly advantageous benefit of the illustrated front-end proxy module **30** is that each proxy module **34, 36, 38, 40** makes use of the same core services to route traffic, access data, and render data. In other words, the renderer module **44**, XSLT engine module **46**, template memory **48**, flow controller module **50**, and handlers **52a-52n** provide a common core service module for the proxy modules **34, 36, 38, 40.** The only differences between translations by the different proxy modules **34, 36, 38, 40** would be in the configuration of the flow controller **50**, the handlers **52a-52n**, and the XSL templates used to translate the data into its final form. It many cases, the same handlers **52a-52n** will be re-used between by the various proxy modules **34, 36, 38, 40**, as will be appreciated by those skilled in the art.

[0057] During operation, a data access request from a client is passed to the appropriate proxy module **34, 36, 38, 40** using standard mechanisms for the client protocol. For a WAP client, for example, parameters are passed via a query string and/or form variables. The WAP proxy module **34** determines a component identifier (which identifies a target item such as a mail folder), an action identifier (which identifies an action to be performed), and any parameters based on data in the request. In the case of WAP, the component and action

identifiers are passed in the query string or form. Other parameters in the query string or form are packaged into a parameter list.

[0058] The active proxy module then calls the flow controller **50**, passing along the identifiers and parameter list. The flow controller looks up the appropriate handler via the component and action identifiers and constructs the handler, passing the parameters as arguments to a constructor (not shown). Using the handler **52a** as an example, this handler would processes the request, using a data layer (FIG. 5) to gather information needed for a response.

[0059] For mail system access, for instance, the data layer communicates with the protocol engine module **32** for any information related to the contents of the user's mailbox, calendar, or address book, for example. Communications with other components may be established for different types of information, such as information related to authentication services and a user's e-mail account. The handler **52a** then decides whether the request should be forwarded to another handler, or if its results should be rendered.

[0060] All information passed back by the handlers **52a-52n** is preferably in a common format, such as org.xml.sax.InputSource, for example, a provider of extensible mark-up language (XML) data. The active proxy module then calls the renderer module **44**, passing along the InputSource, locale information, the name of the template to be rendered, and an OutputStream. The renderer module **44**, making use of the XSLT engine **46**, renders the page into the OutputStream. The OutputStream is then provided to the client by the active proxy module using the client protocol.

[0061] The above system provides a generic application framework following the classic model/view/controller (MVC) architecture that implements most of the application infrastructure. One important feature is that a base set of functionality may be defined for similar services and then extended to provide the service-specific functionality required to fully implement a given service. Within a given implementation, the flow controller **50**, the handlers **52a-52n**, and/or the data access layer are fully extensible or replaceable.

[0062] With this in mind, supporting a brand new service simply involves defining and implementing the data layer, defining the control flow and discrete actions within the system (i.e., the flow controller module **50**), and defining and implementing the interface with the service (i.e., the renderer module **44**). On the other hand, supporting a new type of client with an existing service involves making minor changes to, and extending actions within, the flow controller module **50** and handlers **52a-52n** to support additional client-required functionality, and defining and implementing the interface between the client and the system (i.e., the renderer module **44**).

[0063] Operation of the front-end proxy module **30** to perform protocol translation is further described with respect to the block diagram of FIG. 12. Certain of the illustrated operations have been described in detail above, and thus will be described only briefly below to avoid undue repetition. Beginning at Block **120**, an access request or command is received at a proxy module **34, 36, 38, 40**, at Block **121**. The access request is

translated into the common interface protocol by one or more of the handlers **52a-52n**, at Block **122**.

[0064] Data is received from a given mail system **24, 26, 28** in response to the request, at Block **123**. This data, which has already been translated into the common interface protocol by the protocol engine module **32**, is rendered (Block **124**) and returned to the client, at Block **125**, thus concluding the illustrated method (Block **126**). Depending upon the particular features supported by the client protocol, only portions of the data corresponding to elements of the common interface protocol that are supported by the client protocol are rendered or translated. Non-supported interface protocol elements may be ignored or processed according to a default or error processing scheme, as noted above.

[0065] It should be noted that the extensible, common core service architecture of the front-end proxy module **30** may also be used for a variety of applications. One such application is to address various shortcomings of the disparate methods used to respond to HTTP requests from a Web application. Referring now to FIGS. 4 and 5, a Web data access system **100** having an extensible architecture in accordance with the present invention is now described. The components of the Web data access system **100** communicate bi-directionally, and they illustratively include a user request **101**, a Web server **102**, a proxy server **104**, and an extensible controller system **106**.

[0066] More particularly, the user request **101** refers to a user using a web browser or web application to request a web page (e.g., from a PDA or personal computer). Once the request is made, the Web server **102**

processes the request. The proxy server **104** assists the Web server **102** in processing the request. For comparison purposes, the proxy server **104** here functions similar to the protocol interface device **14** discussed above, and the extensible controller system **106** would be implemented as a software module that is run on or in conjunction with the proxy server, as will be appreciated by those skilled in the art. Of course, in some embodiments the proxy server **104** and extensible controller system **106** could be implemented in different physical devices or servers, for example.

[0067] The proxy server **104** provides a process of providing cached or storage items available on other servers which are slower or more resource intensive to access. The proxy server **104** accepts URLs with a special prefix. When it receives a request for such a URL, it strips off the prefix and looks for the resulting URL in its local cache. If found, it returns the document immediately, otherwise it fetches it from the remote server, saves a copy in the cache, and returns it to the requester. The pages returned by the proxy server **104** can be either static or dynamic in nature. The proxy server **104** may communicate with application servers or data servers, and in this specific embodiment, the extensible controller system **106**.

[0068] More particularly, the components of the proxy server **104** illustratively include an aggregate server **202**, a renderer module **212**, an XSLT engine module **214**, and a memory **216** for storing a series of templates, similar to those described above. The components of the extensible controller system **106**

include an action map **204**, and a series of handlers **206**, also similar to those discussed above.

[0069] The aggregate server **202** performs the processing of incoming information and passes it onto other components for assistance. The renderer module **212** renders the resultant data into a viewable format. The renderer module **212** makes use of the XSLT engine module **214** and any necessary templates from the memory **216** to render the page.

[0070] The aggregate server **202** sends data to the action map **204**, which maintains the control flow and handles the business logic in the system. The action map **204** interacts with a series of handlers **206**. The handler **206** utilizes the data layer **208** to retrieve information from other data sources **210**. The other data sources **210** may include, for example, XML for web data, a universal proxy for any information related to the contents of user applications (e.g., e-mail, calendar or contact), or a provisioning API for authentication services and data relating to a user account.

[0071] The system functions by having a user send in a URL as a user request **101**. This request is received at the Web server **102**, which passes on to the proxy server **104** for processing using standard mechanisms for the protocol. For example, a WML request would pass a WAP parameter query string and/or form variables. The aggregate server **202** component of the proxy server **104** determines the component ID, action ID and any parameters based on data in the request. Using the same WAP example, the component and action IDs are passed in the query string or form. All other parameters in the query string or form are packaged up into a parameter list.

[0072] The aggregate server **202** then calls the action map **204** of the extensible controller system **106** and passes along the IDs and parameter list. The action map **204** looks up the appropriate handler **206** via the component and action IDs and constructs the handler, passing the parameters as arguments to the constructor. The handler **206** processes the request, using the data layer **208** to gather information needed for a response. The data layer **208** will retrieve information from other data sources **210** located within the network or external to the network. The handler **206** then decides whether the request should be forwarded to another handler **206**, or if its results should be rendered.

[0073] If the system decides to render the data, the data is passed from the handler **206**, back to the action map **204**, and back to aggregate server **202** of the proxy server **104**. The aggregate server **202** then calls the renderer module **212**, which invokes the XSLT engine module **214** and any necessary templates to render the data into a viewable output. This output is then returned to the Web server **102** to serve the data as a viewable web page as a result of the user request **101**.

[0074] The various steps involved in processing Web data using the extensible controller system **106** will now be further described with reference to FIG. 13. More particularly, this diagram illustrates in greater detail the processing and interaction of the proxy server **104** and the extensible controller system **106**. The system flow begins with a user request **101**. This request is sent to the Web server **102**, which passes the information to the proxy server **104** for processing. The proxy server **104** invokes the aggregate server **202** for processing.

[0075] The aggregate server **202** determines whether a context is available, at Block **302**. If it is available, the system will move to the next step to mine the IDs (Block **306**). If it is not available, the system will first create the context, at Block **304**, and then continue onto the step to mine the IDs, at Block **306**. The action ID and component ID are also mined out of the system. These IDs, along with the request parameters and any form data, are packaged into an envelope and gathered together, at Block **308**.

[0076] An invoke procedure is called to pass the data from the aggregate server **202** to the action map **204** of the extensible controller system **106**. This invoke procedure will pass information pertaining to the envelope, an action code, the component ID and context info to the action map **204**. The action map **204** looks up the action, at Block **310**, and determines whether the action exists, at Block **312**. If it does, then it moves to the next step to determine whether the action requires authentication, at Block **316**. If the action does not exist, the system retrieves the default action, at Block **314**, and then determines whether the action requires authentication, at Block **316**.

[0077] At this point, if the action does not require authentication, the system determines if any requests are pending, at Block **320**. If the action does require authentication, the system then determines whether the context is in an authenticated state, at Block **318**. If the context is in an authenticated state, the system then determines whether a request is pending, at Block **320**. However, if the context is not in an authenticated state, the system returns the request to the retrieve

default action, at Block **314**, until authentication is accepted.

[0078] At Block **320**, the system determines if a request is pending. If a request is pending, the system executes on the pending request and jumps to next stage, determining whether a process is in queue, at Block **346**. If no request is pending, the system executes on the action and validates on the envelope data, at Block **322**, and passes control to the handler **206** to create the action handler, at Block **324**. Once the action handler is created, it is initialized, at Block **326**.

[0079] The system then determines whether background processing is allowed, at Block **328**. If so, a background handler is created, at Block **344**, and the system determines whether a process is in queue, at Block **346**. However, if background processing is not allowed, the system then processes the action handler, at Block **330**, and then returns the result, at Block **332**. Revisiting the system, at Block **346** the system determines whether a process is in the queue. If the process is in the queue, it then determines whether the action is complete, at Block **350**. If the process is not in the queue, then it submits it to the queue, at Block **348**, and then determines whether the action handler is complete, at Block **350**.

[0080] If the action handler is complete, the system returns the action handler result, at Block **352**. If the action handler is not complete, the system returns the pending render result, at Block **354**. The output of the steps illustrated at Blocks **352** and **354** (returning either an action handler result or pending renderer

result) will be used to determine whether to render the result, at Block **334**.

[0081] More particularly, the results of the steps illustrated at Blocks **332** (return result), **352** (return action handler result) and **354** (return pending render result) are used to determine whether to render the result (Block **334**). If the system decides to render the result, the system sends the data from the extensible controller system **106** to the proxy server **404** and renders the data, at Block **340**, at the renderer module **212**. The data is then passed onto the Web server **102** to display the result, at Block **342**, as a response to the user request **101**. However, if the system decides not to render the result and has instead decided to forward the request to another action handler for processing, the system retrieves the ID keys, at Block **336**, retrieves the envelope data, at Block **338**, and then looks up the appropriate action, at Block **310**. The system will loop around at this point until a decision to render a result is ultimately accepted, at Block **334**.

[0082] The above-described method involves using a single source for defining the components within the system. In this particular embodiment, the source is an XML file, but other formats could be used as well, as will be appreciated by those skilled in the art. This source would define the code that handles the request, the URL syntax and parameters, templates or code used to generate the response for the request, and the routing information for the request, for example.

[0083] The code that handles the request, along with the parameter definition, is used by the system to create the action handler, pass the correctly typed

parameters, and pass control to it for processing. The parameters include type information allowing for strongly typed data. The parameters may also be defined as optional or required. The template or templates are used to generate the response for the request. If an attempt is made to generate a response other than to what was defined an error is generated.

[0084] The source would also define the routing information for the request. Often times, it is desirable for a handler to perform work within its scope and then hand off control to another handler to allow it to perform its work. However, if the handler attempts to hand control to something not defined in the source, an error is generated.

[0085] Other variations are also possible. For example, the source may be used whenever generating URL's for use within the system. Moreover, request routing may be separated from the actual processing of those requests. Control flow is then handled by one component of the system, not by each handler. The handler would then simply ask the controller to forward a request to another handler. Thus, incoming data may be kept in a known state for the life of a particular request.

[0086] Yet another approach involves enforcing control flow through the system where one handler does not call another handler directly to do its work. Still another approach involves keeping the handlers relatively small and simple. That is, this will limit the handler's purpose and scope to receiving requests and calling the appropriate business logic to gather the desired results. Another variation involves keeping each handler focused on one task, and upon completion

of the task, allowing the results to be rendered or forwarded on to the next handler.

[0087] A further variation involves providing an extensible mechanism for handling requests that can handle immediate needs, as well as grow over time without becoming overly complex. When loading the system, the user is able to specify a primary and secondary action map. In this way, generic business logic and control flow may be specified by the primary action map while still providing the user with a method of adding or modifying the functionality. Another approach is to provide the developer with a generic mechanism for responding quickly to long running requests to avoid generating a timeout. This enables the developer to specify background processing at either a handler level, or at the entire system.

[0088] The above-described extensible controller is particularly advantageous for addressing shortcomings in Web or HTTP-based applications. Of course, it will be also appreciated by those skilled in the art that this same architecture may be extended to support other types of non-HTTP based applications as well.

[0089] Turning now to FIG. 6, an alternate embodiment of the protocol interface device **14'** is now described. In the illustrated embodiment, all requests to a data storage device, such as the mail systems **24'**, **26'**, **28'**, are defined in configuration files stored in a configuration file store or memory **31'**. In this way, for a given client category, an application developer can easily request only those properties required to support the client for which it was written.

[0090] A resource manager, which may be part of the front-end proxy module **30'** or a separate component of

the protocol interface device **14'**, advantageously allows a user to specify a primary and secondary set of configuration files. If a secondary configuration file is specified, any resources defined in it will override those specified in the primary configuration file. This allows the user to specify a core set of resources and then tweak them to fit a particular implementation.

[0091] Moreover, configuration files may be stored for processing operations at different network layers. For example, configuration files for data layer operations for interfacing the front-end proxy module **30'** and protocol engine module **32'** may be stored in the memory **31'**, as well for upper network layer operations performed by the flow controller module **50**, for example. Other types of configurations files may be used as well, as will be appreciated by those skilled in the art.

[0092] A configuration file also preferably specifies the implementation class that is created to handle the response to a given request. This makes it a simple matter to slightly change the behavior of an object in a data model, or even completely replace it. Caching behavior and strength for each request may also be specified in a configuration file. With a combination of these two properties, a developer can have much greater control over memory consumption and response/request performance.

[0093] In addition, configuration files also allow a user to specify multiple requests for a given resource. This makes it possible to support data systems with different request/response formats. An exemplary configuration file is provided below as program listing #4. This configuration file is suitable for a data

store that supports a WebDAV interface, as discussed above, or in the case of the protocol interface device **14'**, a protocol engine that supports a WebDAV interface. However, it could be used for other types interfaces/data stores as well.

[0094] It should also be noted that, in addition to the content class specified for the resource, a user may also specify a command to further identify a given resource. This allows the user to perform multiple different operations on a given resource type, as will be appreciated by those skilled in the art.

[0095] Operation of the protocol interface device **14'** using configuration files will now be described further with reference to FIG. 14. Beginning at Block **140**, an access request or command is received at a proxy module, at Block **141**. The access request is translated into the common interface protocol by a handler **52a-52n**, at Block **142**, with reference to one or more configuration files. Data that is received from the data system (Block **143**) in response to the request, and which has already been translated into the common interface protocol by the protocol engine module **32'**, is formatted into a response and rendered, at Block **144**. Again, this is done with reference to one or more configuration files. The rendered response is then returned to the client (Block **145**), thus concluding the illustrated methods, at Block **146**.

[0096] Referring now additionally to FIG. 7, the protocol engine module **32** will now be described in further detail. The protocol engine module **32** provides a framework to incorporate various interface connector modules **70-77** that communicate with various mail systems using different protocols. The protocol engine

module **32** also provides a common interface XML and WebDAV, for example, that the clients, through the front-end proxy module **30**, use to access various mail accounts. Common operations like retrieving only the essential headers of new mail and determining the presence and size of attachments without downloading them are highly efficient. All operations are performed directly on the source, and only the essential data is retrieved.

[0097] The protocol engine module **32** uses an appropriate one of a plurality of interface connector modules **70-77** to access a mail account. All of the connector modules **70-77** preferably support a common application programming interface (API), such that adapting the protocol engine module **32** to support a new protocol amounts to simply adding a new interface connector module. The connector modules **70-77** may be written in Java, for example, although other suitable languages or protocols may also be used. Overall system performance and availability may be improved, for example, by providing multiple dynamically load-balanced protocol engine machines.

[0098] Results received by the protocol engine module **32** from the mail systems **24, 26, 28** are similarly translated into the common interface protocol for translation into a client-supported protocol, if necessary, and transmission to a client. The results communicated back to a client preferably include only data that was requested by the client. Data corresponding to features that are supported by a mail system protocol but not by a client protocol may be translated into the common interface protocol, but it

may also be ignored or handled according to a default or error processing scheme, as noted above.

[0100] A method of protocol translation using the protocol engine module **32** and interface connector modules **71-77** is now described with reference to FIG. 15. Beginning at Block **150**, an access request or command is received, at Block **151**. The access request is translated into a protocol supported by the target data system, at Block **152**. Data is received from the data system in response to the request, at Block **153**, and it is translated into the common interface protocol, at Block **154**. Further translation of the data into a client protocol may be performed, if necessary, at Block **155**, and the data transmitted to the client at Block **156**, thus concluding the illustrated method, at Block **157**.

[0101] Again, depending upon the particular features supported by the client protocol, only portions of the data corresponding to elements of the common interface protocol that are supported by the client protocol are translated. As described above, non-supported interface protocol elements may be ignored or processed according to a default or error processing scheme.

[0102] Turning now to FIG. 8, an alternate embodiment of the above-described protocol conversion module architecture is now described. Here, the protocol engine module **32** takes the form of a universal proxy (UP) servlet module **80**, and each interface connector module **81**, **82**, **83** and a respective provider module **84**, **85**, **86** are associated with different operating protocols. In the illustrated example, the different protocols are OWA, IMAP, and POP. Further or different protocols may be supported by corresponding

provider/connection pairs, as will be appreciated by those skilled in the art.

[0103] For a common interface protocol, such as the proprietary interface protocol described above, the UP servlet module **80** takes incoming common format requests and translates them into calls, using the defined interfaces, to the interface connector modules **81-83**. The UP servlet module **80** also takes the results of these calls and formats them into common format requests. Each common format request includes a method request and a path in the form of a URL. It may also include an XML document that provides additional parameters for the request.

[0104] Conceptually, below the UP servlet module **80** there is a provider module **84-86** for each supported mail system protocol. The providers take care of handling the calls made by the UP servlet module **80**. As shown, each provider has a connection, which takes care of communicating with the source mailbox/account on a target mail system. Initially, the connection will also be the provider.

[0105] The interfaces used by the UP servlet **80** and implemented by the provider modules **84-86** define a loose folder hierarchy. In fact, it may be conceptualized as a collection of collections of items. An item can be a message, a folder, or a contact, for example, or any other data item to be represented. Each item has a defined type (e.g., mail, contact, appointment). An interface for each type of item defines the properties and actions that are available for that type of item. A folder item includes a collection of items, and provides methods to enumerate the items within a folder.

[0106] The connector interface modules **81-83** provide a common way for the UP servlet module **80** to communicate with different provider modules/interface connector modules. Some connector modules may only implement a subset of the protocol and/or may only support a single folder (collection) of items, as in the case of POP.

[0107] The basic flow for an exemplary common format request proceeds as follows. The UP servlet module **80** receives the request, and it either retrieves or creates the appropriate provider/connection. The UP servlet module **80** then calls an appropriate "get folder" or similar function associated with the interface connector module, passing a target mail system identifier, such as a URL that was included in the common format request. The interface connection module returns a reference to some object that implements the folder interface and represents the requested folder. In its simplest implementation (e.g., POP), a single object could be the interface connector module and also represent the mailbox folder.

[0108] The UP servlet module **80** uses the returned folder reference to make additional calls to satisfy the common format request. For example, if the UP servlet module **80** needs to retrieve a specific item, it may first call a "get folder" function, passing the requested URL, and after it has the folder, it will then call a "get item" function, again passing the URL. The results of the call(s) are then formatted into an appropriate format, such as XML, and returned in an HTTP response.

[0109] It will be up to the provider module/interface connection module to interpret a URL

passed in and return the appropriate reference. This will not be complicated because the provider module/interface connection module provides the URLs in the first place. The only URL that any interface connection module will be required to know about is "\". All other URLs are generated by the provider/connection. As long as the URLs within the hierarchy/collections are unique, the provider will be able to resolve to the correct item when a "get" function is called.

[0110] The provider modules **84-86** and interface connection modules **81-83** preferably support a root folder. If only a root folder is supported, then inbox, calendar, and contact items (as appropriate) should be items within that folder if they are to be accessible through a protocol engine.

[0111] In accordance with one aspect of the invention, a single, advantageous mechanism to access various types of protocols is provided. This mechanism supports the full functionality of each data system protocol for similarly capable client protocols, and degrades when a specific data system protocol feature is not supported by a client protocol. Requests received in a common format are translated into a provider/protocol specific format before forwarding the request on to the destination server. Responses from the destination server, which are in provider/protocol specific format, are translated back into the common format.

[0112] A mechanism for a client to query supported functionality for a specific provider module, giving the client greater control over how it generates requests to the provider, is also provided. Any client

written to support the common protocol format, directly or through a proxy, can easily provide access to any mail store without concerning itself with the details of the mail store provider module/protocol.

[0113] Referring now additionally to FIG. 9, another embodiment of the protocol interface device **14''** is now described. Here, user e-mail account information associated with e-mail accounts to be accessed through the protocol interface device **14''** is stored in a data store **90''**. The per-account information preferably includes an indication of the access protocols supported for each e-mail account.

[0114] Records in the data store **90''** may be arranged by an account identifier, such as an e-mail address, or by a user name associated with the protocol interface device **14''** such that all e-mail account information for particular users is grouped in the data store **90''**, for example. Where access protocol support is the same for all e-mail accounts on each of the mail systems **24''**, **26''**, the per-account information may include mail system information indicating the operating protocols supported by each mail system.

[0115] A data store **91''** stores a list of all operating protocols supported by the protocol engine module **32''**, and corresponding metrics (i.e., ranking) representing protocol preferences. These metrics are calculated based on capability criteria, such as the degree to which features of each mail system **24''**, **26''** are supported by a protocol and the security level of a protocol, for example. Other criteria may also be used and will be apparent to those skilled in the art. In the data store **91''**, OWA would typically have a higher metric or ranking than MAPI, and IMAP would generally

be ranked higher than POP. Each of the data stores **90''**, **91''** may be implemented, for example, in a database on a local hard disk or other memory at the protocol interface device **14''**, or on a file server with which the protocol interface device communicates.

[0116] The protocol engine module **32''** determines to which mailbox(es) or account(s) the command or instruction relates, and then accesses the per-account information in the data store **90''** to determine whether more than one access protocol is supported for each account to be accessed. If only one access protocol is supported, then that protocol is selected. Where more than one access protocol is supported for the account, then the protocol engine module **32''** accesses the data store **91''** to determine which supported protocol is preferred or desired, and the supported protocol with the highest metric or ranking is selected. For the mail system **24''**, OWA is preferably selected over MAPI, and for the mail system **26''**, IMAP is preferably selected over POP.

[0117] The protocol interface device **14''** thus allows access to the mail systems **24''**, **26''** using a most capable supported protocol. Through the protocol interface device **14''**, a client compatible with any of the proxy modules **34''**, **36''**, **38''**, **40''** is provided access to one or more of the mail systems **24''**, **26''**. The client itself need not support the access protocol or scheme associated with the mail system(s) to be accessed.

[0118] A method of data system access protocol selection using the protocol interface device **14''** is now described with reference to FIG. 9. Beginning at Block **160**, an access command is received from a client

at Block **161**. A determination is made (Block **162**) as to whether each data system to be accessed in response to the command supports more than one access protocol. If so, then the most capable supported protocol is selected, at Block **164**. Otherwise, the one supported protocol is selected, at Block **163**. Each data system is accessed using the selected protocol, at Block **165**, thus concluding the illustrated method, at Block **166**. Where more than one data system is to be accessed, the protocol selection steps illustrated at Blocks **162-164** are preferably repeated for each data system.

[0119] It should be noted that the protocol and metric data store **91''** is but one example exemplary of a protocol preference ranking technique that may be used in accordance with the present invention. Protocol preferences may be inherent in the ordering of a list of supported protocols, for example.

[0120] Further criteria than metrics or overall preferences may also be considered when selecting a protocol. The type of client from which the access command is received may also affect protocol selection. Where the access command is received from a POP client, for example, many of the enhanced features supported by OWA cannot be represented in POP for transfer to the device. If a user has only one type of client for accessing the protocol interface device **14''**, then the per-account information may be adapted to reflect the type of client or to limit the list of supported protocol based on the type of client. Otherwise, a further step in protocol selection may be to determine the type of client from which an access request is received.

[0121] Alternatively, a most capable protocol supported by a data system to be accessed may always be selected, and any incompatibility between the selected access protocol and the protocol supported by the client is handled during translation of data to the client protocol. Portions of data corresponding to elements of the interface protocol that are supported by the client protocol are translated, whereas non-supported interface protocol elements are ignored or processed according to a default or error processing scheme.

[0122] Generally speaking, clients often access servers through proxies. Also, the latency is often positively correlated to the cardinality of the collection being accessed (e.g., number of email messages in the mailbox being accessed). As will be evident from the following description, the present invention provides an apparatus and technique that may be used by the proxy to give the client the illusion that the collection being accessed is smaller than it really is. For example, a proxy may show only the 100 most recent messages in a mailbox, while the mailbox itself has 2000+ messages. The present invention advantageously allows this proxy to select a small subset of the collection that can be presented to the client in lieu of the entire collection without a significant impact to the user experience.

[0123] More particularly, turning now to FIG. 10, another advantageous embodiment of the protocol interface device **14'''** is now described. Generally speaking, when a data access request is received from a client, the protocol interface device **14'''** accesses one or more of the data systems **24'''**, **26'''**. However,

in some cases accessing the data systems and providing a response to the client might otherwise cause timeouts for certain client protocols, and longer than desired wait times for a user of a client after a request has been sent. Yet, in accordance with the present aspect of the invention, certain data may be stored at the protocol interface device **14'''** which may be used to reduce response times.

[0124] More particularly, the protocol engine module **32'''** polls the data systems **24'''**, **26'''** to determine whether they currently store data items associated with users that have been configured for access thereof. Users are configured in the protocol interface device **14'''** by establishing a user account associated therewith, for example. Polling is preferably performed in accordance with a polling interval. The polling interface may be a static predetermined polling interval, or an adaptive polling interval that can be adjusted based on operating conditions or the occurrence of particular events, as will be appreciated by those skilled in the art.

[0125] In response to a poll from the protocol engine module **32'''**, a given data system **24'''**, **26'''** returns data items, or at least data item identifiers that can be used to retrieve the data items, to the protocol interface device **14'''**. These data items or identifiers are then stored by the protocol engine module **32'''** in the data store or memory **92'''**.

[0126] In particular, the protocol engine module **32'''** may determine whether new data items for a user are stored in any of the data systems **24'''**, **26'''**. Where the data systems **24'''**, **26'''** are e-mail systems, for example, the protocol engine module **32'''** queries

mailboxes associated with each user configured for e-mail access through the protocol interface device **14'''**. For each mailbox query, a mail system returns, at a minimum, a list of unique identifiers (UIDs) associated with e-mail messages stored in the mailbox.

[0127] A current UID list is then compared with a previous UID list for the mailbox in the UID store **92'''** to determine whether new messages have been stored in the mailbox at the mail system. If new messages are detected, an alert is preferably sent to a user's client by the protocol engine module **32'''** in cooperation with the front-end proxy module **30'''** (or another component of the protocol interface device **14'''**), and the current UID list including the new messages is stored to the UID store **92'''**.

[0128] One of the most common data access operations is viewing a listing of data items currently stored at data systems, especially where the data items are messages stored on mail systems. As described above, the protocol engine module **32'''** polls one or more of the data systems **24'''**, **26'''** to detect new data items based on a list of UIDs stored in the UID store **92'''**. Therefore, the protocol interface device **14'''** has a local listing of UIDs of data items that were stored at the data systems **24'''**, **26'''** the last time the data systems were polled.

[0129] In accordance with the present aspect of the invention, the protocol engine module **32'''** retrieves the stored UID list from the UID store **92'''** when a "view items" or similar access request is received. This stored UID list, which is accurate to within the current polling interval, is then returned to the requesting client. This provides a much faster response

time than accessing the data systems **24'''**, **26'''** when the request is received, as will be appreciated by those skilled in the art.

[0130] In the case of a POP client, for example, the client times out if no response to a request is received within 30 seconds. Where the POP client is operating on a mobile wireless communications device, latency within the wireless communications network can cause delays that are significant relative to this limited response time. The faster response time associated with providing a stored UID list in response to a data access request is particularly advantageous in these types of scenarios. Even in the absence of such time constraints, a faster response time enhances the user experience at a client by reducing the wait time between sending a data access request and receiving a response.

[0131] As described above, the stored UID list is accurate to within the polling interval. When the stored UID list is provided to a client in response to a data access request, the protocol engine module **32'''** preferably polls the data system(s) **24'''**, **26'''** to determine whether the stored UID list is still accurate. If new items have been stored at the data system(s) **24'''**, **26'''** since the last poll, then a new UID list is sent to the client. This further polling of the data systems **24'''**, **26'''** is performed either according to the polling interval or initiated by the data access request.

[0132] It will be appreciated that the preceding description relates to "view items" or similar data access requests. Other types of data access requests may be processed by other components or modules of the

protocol interface device **14'''**. For example, such data access requests are translated, if necessary, by the front-end proxy module **30'''**, as described above.

[0133] The protocol interface device **14'''** thereby allows access to the data systems **24'''**, **26'''**, and provides for reduced response times for various types of data access requests. Through the protocol interface device **14'''**, a client compatible with any of the protocols handled by the front-end proxy module **30'''** is provided access to one or more of the data systems **24'''**, **26'''**. The client itself need not support the access protocol or scheme associated with the data system(s) **24'''**, **26'''** to be accessed, as noted above.

[0134] A method of reducing response times for data system access requests using the protocol interface device **14'''** is now described with respect to FIG. 17. Beginning at Block **170**, a data access request is received at Block **171**. A determination is then made, at Block **172**, as to whether data pertinent to the data access request (i.e., a UID list) is locally stored. Where such data is in a local store **92'''**, then the stored data is provided to the requesting client, at Block **173**. After the stored data has been transmitted to the client, or if no such data has been stored, the data system(s) **24'''**, **26'''** to which the data access request relates is polled, at Block **174**.

[0135] An optional step of determining whether the polled data received in response to a poll is different from the stored data may then be performed at Block **175**. If so, this means that there is new data stored on the data system(s) **24'''**, **26'''**, and the data received in response to the poll is provided to the client, at Block **176**. It is also locally stored in the data store

92''', at Block **177**, thus concluding the illustrated method (Block **178**).

[0136] By way of example, data access systems and methods according to aspects of the invention may be applied to other types of data storage devices than mail systems, and other protocols and access schemes than those specifically described above and shown in the drawings.

[0137] Additional features of the invention may be found in co-pending applications entitled COMMUNICATIONS SYSTEM PROVIDING REDUCED ACCESS LATENCY AND RELATED METHODS, attorney docket number ID-494; COMMUNICATIONS SYSTEM INCLUDING PROTOCOL INTERFACE FOR MULTIPLE OPERATING PROTOCOLS AND RELATED METHODS, attorney docket number ID-493; COMMUNICATIONS SYSTEM PROVIDING EXTENSIBLE PROTOCOL TRANSLATION FEATURES AND RELATED METHODS, attorney docket number ID-507; COMMUNICATIONS SYSTEM WITH DATA STORAGE DEVICE INTERFACE PROTOCOL CONNECTORS AND RELATED METHODS, attorney docket number ID-506; COMMUNICATIONS SYSTEM PROVIDING MULTI-LAYERED EXTENSIBLE PROTOCOL INTERFACE AND RELATED METHODS, attorney docket number ID-503; and COMMUNICATIONS SYSTEM INCLUDING PROTOCOL INTERFACE DEVICE PROVIDING ENHANCED OPERATING PROTOCOL SELECTION FEATURES AND RELATED METHODS, attorney docket number ID-495, the entire disclosures of which are hereby incorporated herein by reference.

EXAMPLE

[0138] An exemplary hand-held mobile wireless communications device **1000** that can be used in the present invention is further described in the example below with reference to FIG. 18. The device **1000**

includes a housing **1200**, a keyboard **1400** and an output device **1600**. The output device shown is a display **1600**, which is preferably a full graphic LCD. Other types of output devices may alternatively be utilized. A processing device **1800** is contained within the housing **1200** and is coupled between the keyboard **1400** and the display **1600**. The processing device **1800** controls the operation of the display **1600**, as well as the overall operation of the mobile device **1000**, in response to actuation of keys on the keyboard **1400** by the user.

[0139] The housing **1200** may be elongated vertically, or may take on other sizes and shapes (including clamshell housing structures). The keyboard may include a mode selection key, or other hardware or software for switching between text entry and telephony entry.

[0140] In addition to the processing device **1800**, other parts of the mobile device **1000** are shown schematically in FIG. 18. These include a communications subsystem **1001**; a short-range communications subsystem **1020**; the keyboard **1400** and the display **1600**, along with other input/output devices **1060**, **1080**, **1100** and **1120**; as well as memory devices **1160**, **1180** and various other device subsystems **1201**. The mobile device **1000** is preferably a two-way RF communications device having voice and data communications capabilities. In addition, the mobile device **1000** preferably has the capability to communicate with other computer systems via the Internet.

[0141] Operating system software executed by the processing device **1800** is preferably stored in a persistent store, such as the flash memory **1160**, but may be stored in other types of memory devices, such as

a read only memory (ROM) or similar storage element. In addition, system software, specific device applications, or parts thereof, may be temporarily loaded into a volatile store, such as the random access memory (RAM) **1180**. Communications signals received by the mobile device may also be stored in the RAM **1180**.

[0142] The processing device **1800**, in addition to its operating system functions, enables execution of software applications **1300A-1300N** on the device **1000**. A predetermined set of applications that control basic device operations, such as data and voice communications **1300A** and **1300B**, may be installed on the device **1000** during manufacture. In addition, a personal information manager (PIM) application may be installed during manufacture. The PIM is preferably capable of organizing and managing data items, such as e-mail, calendar events, voice mails, appointments, and task items. The PIM application is also preferably capable of sending and receiving data items via a wireless network **1401**. Preferably, the PIM data items are seamlessly integrated, synchronized and updated via the wireless network **1401** with the device user's corresponding data items stored or associated with a host computer system.

[0143] Communication functions, including data and voice communications, are performed through the communications subsystem **1001**, and possibly through the short-range communications subsystem. The communications subsystem **1001** includes a receiver **1500**, a transmitter **1520**, and one or more antennas **1540** and **1560**. In addition, the communications subsystem **1001** also includes a processing module, such as a digital signal processor (DSP) **1580**, and local oscillators

(LOs) **1601**. The specific design and implementation of the communications subsystem **1001** is dependent upon the communications network in which the mobile device **1000** is intended to operate. For example, a mobile device **1000** may include a communications subsystem **1001** designed to operate with the Mobitex™, Data TAC™ or General Packet Radio Service (GPRS) mobile data communications networks, and also designed to operate with any of a variety of voice communications networks, such as AMPS, TDMA, CDMA, PCS, GSM, etc. Other types of data and voice networks, both separate and integrated, may also be utilized with the mobile device **1000**.

[0144] Network access requirements vary depending upon the type of communication system. For example, in the Mobitex and DataTAC networks, mobile devices are registered on the network using a unique personal identification number or PIN associated with each device. In GPRS networks, however, network access is associated with a subscriber or user of a device. A GPRS device therefore requires a subscriber identity module, commonly referred to as a SIM card, in order to operate on a GPRS network.

[0145] When required network registration or activation procedures have been completed, the mobile device **1000** may send and receive communications signals over the communication network **1401**. Signals received from the communications network **1401** by the antenna **1540** are routed to the receiver **1500**, which provides for signal amplification, frequency down conversion, filtering, channel selection, etc., and may also provide analog to digital conversion. Analog-to-digital conversion of the received signal allows the DSP **1580** to perform more complex communications functions, such

as demodulation and decoding. In a similar manner, signals to be transmitted to the network **1401** are processed (e.g. modulated and encoded) by the DSP **1580** and are then provided to the transmitter **1520** for digital to analog conversion, frequency up conversion, filtering, amplification and transmission to the communication network **1401** (or networks) via the antenna **1560**.

[0146] In addition to processing communications signals, the DSP **1580** provides for control of the receiver **1500** and the transmitter **1520**. For example, gains applied to communications signals in the receiver **1500** and transmitter **1520** may be adaptively controlled through automatic gain control algorithms implemented in the DSP **1580**.

[0147] In a data communications mode, a received signal, such as a text message or web page download, is processed by the communications subsystem **1001** and is input to the processing device **1800**. The received signal is then further processed by the processing device **1800** for an output to the display **1600**, or alternatively to some other auxiliary I/O device **1060**. A device user may also compose data items, such as e-mail messages, using the keyboard **1400** and/or some other auxiliary I/O device **1060**, such as a touchpad, a rocker switch, a thumb-wheel, or some other type of input device. The composed data items may then be transmitted over the communications network **1401** via the communications subsystem **1001**.

[0148] In a voice communications mode, overall operation of the device is substantially similar to the data communications mode, except that received signals are output to a speaker **1100**, and signals for

transmission are generated by a microphone **1120**. Alternative voice or audio I/O subsystems, such as a voice message recording subsystem, may also be implemented on the device **1000**. In addition, the display **1600** may also be utilized in voice communications mode, for example to display the identity of a calling party, the duration of a voice call, or other voice call related information. The short-range communications subsystem enables communication between the mobile device **1000** and other proximate systems or devices, which need not necessarily be similar devices. For example, the short-range communications subsystem may include an infrared device and associated circuits and components, or a Bluetooth™ communications module to provide for communication with similarly-enabled systems and devices.

[0149] Many modifications and other embodiments of the invention will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is understood that the invention is not to be limited to the specific embodiments disclosed, and that modifications and embodiments are intended to be included within the scope of the appended claims.

Computer Program Listings

Program Listing #1 - Exemplary Authentication Request

```
PROPFIND /ups HTTP/1.1
Depth: 0
Brief: t
Pragma: no-cache
Content-Type: text/xml
```

```
        X_UP_LOGIN:
svr=login.oscar.aol.com&prt=5190&ssl=0&pcol=aol&uid=******&pwd=******&pwp=
        X_UP_SYNC: false
        X_UP_REFRESH_CACHE: force
        X_UP_NEWCON: 1
        User-Agent: Mozilla/4.0 (compatible; MSIE 5.5; Windows NT 5.0)
        Connection: Keep-Alive
        Host: localhost:9080
        Content-Length: 664

        <?xml version="1.0"?>
        <D:propfind xmlns:D="DAV:" xmlns:h="http://schemas.microsoft.com/hotmail/"
xmlns:hm="urn:schemas:httpmail:" xmlns:up="urn:schemas:corp:universalproxy" >
          <D:prop>
            <hm:contacts/>
            <hm:calendar/>
            <hm:journal/>
            <hm:notes/>
            <hm:inbox/>
            <hm:outbox/>
            <hm:sendmsg/>
            <hm:sentitems/>
            <hm:deleteditems/>
            <hm:drafts/>
            <hm:msgfolderroot/>
            <up:corporatecontacts/>
            <h:maxpoll/>
            <h:sig/>
          </D:prop>
        </D:propfind>

        HTTP/1.1 207 Multi-Status
        Set-Cookie: JSESSIONID=C70CD1AED7D2BE210B34D93F7ACD6935; Path=/ups
        Content-Type: text/xml
        Transfer-Encoding: chunked
        Date: Wed, 06 Aug 2003 18:20:28 GMT
        Server: Apache Coyote/1.0

        <?xml version="1.0" encoding="UTF-8"?>
        <D:multistatus xmlns:D="DAV:" xmlns:up="urn:schemas:corp:universalproxy"
        xmlns:c="urn:schemas:calendar:" xmlns:a="urn:schemas:contacts:"
        xmlns:hm="urn:schemas:httpmail:" xmlns:m="urn:schemas:mailheader:">
          <D:response>
            <D:href>http://localhost:9080/ups/</D:href>
            <D:propstat>
              <D:status>HTTP/1.1 200 OK</D:status>
              <D:prop>
                <hm:inbox>http://localhost:9080/ups/INBOX/</hm:inbox>

        <hm:sendmsg>http://localhost:9080/ups/AOL_MAIL_SUBMISSION_URL/</hm:sendmsg>
                <hm:sentitems>http://localhost:9080/ups/Sent Items/</hm:sentitems>
                <hm:msgfolderroot>http://localhost:9080/ups/</hm:msgfolderroot>
              </D:prop>
            </D:propstat>
          </D:response>
        </D:multistatus>
```

Program Listing #2 - Exemplary Inbox Request

Query Folder Capabilities:

REQUEST:
OPTIONS /ups/INBOX/ HTTP/1.1
User-Agent: Mozilla/4.0 (compatible; MSIE 5.5; Windows NT 5.0)
Connection: Keep-Alive
Host: localhost:9080
Cookie: JSESSIONID=C70CD1AED7D2BE210B34D93F7ACD6935
Content-Length: 0

RESPONSE:
HTTP/1.1 200 OK
allow: OPTIONS, PROPFIND, MOVE, DELETE, BDELETE, BMOVE, SEARCH
dasl: <urn:schemas:corp:universalproxy:basicsearch>
Content-Type: text/plain
Content-Length: 0
Date: Wed, 06 Aug 2003 18:20:28 GMT
Server: Apache Coyote/1.0

List messages in INBOX:

REQUEST:
PROPFIND /ups/INBOX/ HTTP/1.1
Range: rows=0-24
Depth: 1,noroot
Brief: t
Pragma: no-cache
Content-Type: text/xml
X_UP_REFRESH_CACHE: force
User-Agent: Mozilla/4.0 (compatible; MSIE 5.5; Windows NT 5.0)
Connection: Keep-Alive
Host: localhost:9080
Cookie: JSESSIONID=C70CD1AED7D2BE210B34D93F7ACD6935
Content-Length: 586

```
<?xml version="1.0"?>
<D:propfind xmlns:D="DAV:" xmlns:hm="urn:schemas:httpmail:" xmlns:m="urn:schemas:mailheader:"
xmlns:up="urn:schemas:corp:universalproxy">
  <D:prop>
    <D:uid/>
    <D:isfolder/>
    <D:ishidden/>
    <hm:read/>
    <hm:hasattachment/>
    <hm:importance/>
    <m:from/>
    <m:subject/>
    <m:date/>
    <up:isdeleted/>
    <D:getcontentlength/>
    <D:contentclass/>
  </D:prop>
</D:propfind>
```

RESPONSE:
HTTP/1.1 207 Multi-Status
Content-Range: rows 0-8; total=9
Content-Type: text/xml
Transfer-Encoding: chunked
Date: Wed, 06 Aug 2003 18:20:28 GMT
Server: Apache Coyote/1.0

<?xml version="1.0" encoding="UTF-8"?>
<D:multistatus xmlns:D="DAV:" xmlns:up="urn:schemas:corp:universalproxy" xmlns:c="urn:schemas:calendar:" xmlns:a="urn:schemas:contacts:" xmlns:hm="urn:schemas:httpmail:" xmlns:m="urn:schemas:mailheader:">
<D:contentrange>0-8</D:contentrange>
<D:response>
<D:href>http://localhost:9080/ups/INBOX/6623963;1</D:href>
<D:propstat>
<D:status>HTTP/1.1 200 OK</D:status>
<D:prop>
<D:uid>3ac59b38c08ad3356435efea144660e3</D:uid>
<D:isfolder>0</D:isfolder>
<D:ishidden>0</D:ishidden>
<hm:read>0</hm:read>
<hm:hasattachment>0</hm:hasattachment>
<hm:importance>1</hm:importance>
<m:from>Mail Delivery Subsystem <MAILER-DAEMON@aol.com></m:from>
<m:subject>Returned mail: User unknown</m:subject>
<m:date>2003-08-05T23:12:48Z</m:date>
<up:isdeleted>0</up:isdeleted>
<D:getcontentlength>3247</D:getcontentlength>
<D:contentclass>urn:content-classes:message</D:contentclass>
</D:prop>
</D:propstat>
</D:response>
<D:response>
<D:href>http://localhost:9080/ups/INBOX/6623954;1</D:href>
<D:propstat>
<D:status>HTTP/1.1 200 OK</D:status>
<D:prop>
<D:uid>51073b22a28c2820115bc80d42e8c6ec</D:uid>
<D:isfolder>0</D:isfolder>
<D:ishidden>0</D:ishidden>
<hm:read>1</hm:read>
<hm:hasattachment>0</hm:hasattachment>
<hm:importance>1</hm:importance>
<m:from>johnsmith@demo.com</m:from>
<m:subject>Re: Test #1-All -French template</m:subject>
<m:date>2003-08-05T23:10:30Z</m:date>
<up:isdeleted>0</up:isdeleted>
<D:getcontentlength>1577</D:getcontentlength>
<D:contentclass>urn:content-classes:message</D:contentclass>
</D:prop>
</D:propstat>
</D:response>
<D:response>
<D:href>http://localhost:9080/ups/INBOX/6623926;1</D:href>
<D:propstat>
<D:status>HTTP/1.1 200 OK</D:status>
<D:prop>
<D:uid>b072c3748ceff1320f9fa746f797e64b</D:uid>

```
        <D:isfolder>0</D:isfolder>
        <D:ishidden>0</D:ishidden>
        <hm:read>1</hm:read>
        <hm:hasattachment>0</hm:hasattachment>
        <hm:importance>1</hm:importance>
        <m:from>johnsmith@demo.com</m:from>
        <m:subject>Re: xxxFWD: Re: Test #1</m:subject>
        <m:date>2003-08-05T23:07:18Z</m:date>
        <up:isdeleted>0</up:isdeleted>
        <D:getcontentlength>1927</D:getcontentlength>
        <D:contentclass>urn:content-classes:message</D:contentclass>
      </D:prop>
    </D:propstat>
  </D:response>
  <D:response>
    <D:href>http://localhost:9080/ups/INBOX/6623922;1</D:href>
    <D:propstat>
      <D:status>HTTP/1.1 200 OK</D:status>
      <D:prop>
        <D:uid>11f1c8e69555d33971aea12c09be5021</D:uid>
        <D:isfolder>0</D:isfolder>
        <D:ishidden>0</D:ishidden>
        <hm:read>1</hm:read>
        <hm:hasattachment>0</hm:hasattachment>
        <hm:importance>1</hm:importance>
        <m:from>johnsmith@demo.com</m:from>
        <m:subject>Re: xxxFWD: Re: Test #1</m:subject>
        <m:date>2003-08-05T23:06:45Z</m:date>
        <up:isdeleted>0</up:isdeleted>
        <D:getcontentlength>1930</D:getcontentlength>
        <D:contentclass>urn:content-classes:message</D:contentclass>
      </D:prop>
    </D:propstat>
  </D:response>
  <D:response>
    <D:href>http://localhost:9080/ups/INBOX/6623915;1</D:href>
    <D:propstat>
      <D:status>HTTP/1.1 200 OK</D:status>
      <D:prop>
        <D:uid>55bc30adfb4fb66f3d11b0416c82b701</D:uid>
        <D:isfolder>0</D:isfolder>
        <D:ishidden>0</D:ishidden>
        <hm:read>1</hm:read>
        <hm:hasattachment>1</hm:hasattachment>
        <hm:importance>1</hm:importance>
        <m:from>johnsmith@demo.com</m:from>
        <m:subject>xxxFWD: Re: Test #1</m:subject>
        <m:date>2003-08-05T23:05:27Z</m:date>
        <up:isdeleted>0</up:isdeleted>
        <D:getcontentlength>3254</D:getcontentlength>
        <D:contentclass>urn:content-classes:message</D:contentclass>
      </D:prop>
    </D:propstat>
  </D:response>
  <D:response>
    <D:href>http://localhost:9080/ups/INBOX/6623910;1</D:href>
    <D:propstat>
      <D:status>HTTP/1.1 200 OK</D:status>
      <D:prop>
```

```
        <D:uid>07cdf24a06f8e849754f90fe6dc8bf4f</D:uid>
        <D:isfolder>0</D:isfolder>
        <D:ishidden>0</D:ishidden>
        <hm:read>1</hm:read>
        <hm:hasattachment>0</hm:hasattachment>
        <hm:importance>1</hm:importance>
        <m:from>johnsmith@demo.com</m:from>
        <m:subject>Re: Test #1-All</m:subject>
        <m:date>2003-08-05T23:04:31Z</m:date>
        <up:isdeleted>0</up:isdeleted>
        <D:getcontentlength>1258</D:getcontentlength>
        <D:contentclass>urn:content-classes:message</D:contentclass>
      </D:prop>
    </D:propstat>
  </D:response>
  <D:response>
    <D:href>http://localhost:9080/ups/INBOX/6623909;1</D:href>
    <D:propstat>
      <D:status>HTTP/1.1 200 OK</D:status>
      <D:prop>
        <D:uid>0e79a3593253ffb9596bf9d86873f498</D:uid>
        <D:isfolder>0</D:isfolder>
        <D:ishidden>0</D:ishidden>
        <hm:read>1</hm:read>
        <hm:hasattachment>0</hm:hasattachment>
        <hm:importance>1</hm:importance>
        <m:from>johnsmith@demo.com</m:from>
        <m:subject>Re: Test #1</m:subject>
        <m:date>2003-08-05T23:04:13Z</m:date>
        <up:isdeleted>0</up:isdeleted>
        <D:getcontentlength>1241</D:getcontentlength>
        <D:contentclass>urn:content-classes:message</D:contentclass>
      </D:prop>
    </D:propstat>
  </D:response>
  <D:response>
    <D:href>http://localhost:9080/ups/INBOX/6605332;1</D:href>
    <D:propstat>
      <D:status>HTTP/1.1 200 OK</D:status>
      <D:prop>
        <D:uid>6060b944e60256c814498af29e5f0e47</D:uid>
        <D:isfolder>0</D:isfolder>
        <D:ishidden>0</D:ishidden>
        <hm:read>0</hm:read>
        <hm:hasattachment>0</hm:hasattachment>
        <hm:importance>1</hm:importance>
        <m:from>aolmbrsecurity@aol.com</m:from>
        <m:subject>Security Notice to AOL Members</m:subject>
        <m:date>2003-08-01T23:00:58Z</m:date>
        <up:isdeleted>0</up:isdeleted>
        <D:getcontentlength>5137</D:getcontentlength>
        <D:contentclass>urn:content-classes:message</D:contentclass>
      </D:prop>
    </D:propstat>
  </D:response>
  <D:response>
    <D:href>http://localhost:9080/ups/INBOX/6567082;1</D:href>
    <D:propstat>
      <D:status>HTTP/1.1 200 OK</D:status>
```

```
      <D:prop>
        <D:uid>f47b72c8c1aa91458f40f81fce3b5e05</D:uid>
        <D:isfolder>0</D:isfolder>
        <D:ishidden>0</D:ishidden>
        <hm:read>0</hm:read>
        <hm:hasattachment>0</hm:hasattachment>
        <hm:importance>1</hm:importance>
        <m:from>aolmemberinfo@aol.com</m:from>
        <m:subject>Coming Soon - AOL 9.0 Optimized</m:subject>
        <m:date>2003-07-25T21:15:22Z</m:date>
        <up:isdeleted>0</up:isdeleted>
        <D:getcontentlength>10012</D:getcontentlength>
        <D:contentclass>urn:content-classes:message</D:contentclass>
      </D:prop>
    </D:propstat>
  </D:response>
</D:multistatus>
```

Program Listing #3 - Exemplary Folder Search Request

Capabilities of folder:

```
REQUEST:
OPTIONS /ups HTTP/1.1
User-Agent: Mozilla/4.0 (compatible; MSIE 5.5; Windows NT 5.0)
Connection: Keep-Alive
Host: localhost:9080
Cookie: JSESSIONID=C70CD1AED7D2BE210B34D93F7ACD6935
Content-Length: 0

RESPONSE:
HTTP/1.1 200 OK
allow: OPTIONS, PROPFIND, MOVE, DELETE, BDELETE, BMOVE, SEARCH
dasl: <urn:schemas:corp:universalproxy:basicsearch>
Content-Type: text/plain
Content-Length: 0
Date: Wed, 06 Aug 2003 18:20:28 GMT
Server: Apache Coyote/1.0
```

Search for folders:

```
REQUEST:
SEARCH /ups HTTP/1.1
Depth: 1,noroot
Brief: t
Pragma: no-cache
Content-Type: text/xml
User-Agent: Mozilla/4.0 (compatible; MSIE 5.5; Windows NT 5.0)
Connection: Keep-Alive
Host: localhost:9080
Cookie: JSESSIONID=C70CD1AED7D2BE210B34D93F7ACD6935
Content-Length: 922

<?xml version="1.0"?>
<D:searchrequest xmlns:D="DAV:" xmlns:t="urn:schemas:corp:universalproxy">
  <t:basicsearch>
    <D:select>
```

```
            <D:prop><D:uid/></D:prop>
            <D:prop><D:contentclass/></D:prop>
            <D:prop><D:displayname/></D:prop>
          </D:select>
          <D:from>
            <D:scope>
              <D:href>url</D:href>
              <D:depth>1</D:depth>
            </D:scope>
          </D:from>
          <D:where>
            <D:eq>
              <D:prop><D:contentclass/></D:prop>
              <D:literal>urn:content-classes:mailfolder</D:literal>
            </D:eq>
          </D:where>
        </t:basicsearch>
      </D:searchrequest>

      RESPONSE:
      HTTP/1.1 207 Multi-Status
      Content-Type: text/xml
      Transfer-Encoding: chunked
      Date: Wed, 06 Aug 2003 18:20:28 GMT
      Server: Apache Coyote/1.0

      <?xml version="1.0" encoding="UTF-8"?>
      <D:multistatus xmlns:D="DAV:" xmlns:up="urn:schemas:corp:universalproxy"
xmlns:c="urn:schemas:calendar:" xmlns:a="urn:schemas:contacts:" xmlns:hm="urn:schemas:httpmail:"
xmlns:m="urn:schemas:mailheader:">
        <D:response>
          <D:href>http://localhost:9080/ups/INBOX/</D:href>
          <D:propstat>
            <D:status>HTTP/1.1 200 OK</D:status>
            <D:prop>
              <D:uid>c90d66b2362a1a0bc3df1852021a6f63</D:uid>
              <D:contentclass>urn:content-classes:mailfolder</D:contentclass>
              <D:displayname>INBOX/</D:displayname>
            </D:prop>
          </D:propstat>
        </D:response>
        <D:response>
          <D:href>http://localhost:9080/ups/VOICE-MAIL/</D:href>
          <D:propstat>
            <D:status>HTTP/1.1 200 OK</D:status>
            <D:prop>
              <D:uid>cabbce34709ab79d2ad2d5334d998272</D:uid>
              <D:contentclass>urn:content-classes:mailfolder</D:contentclass>
              <D:displayname>VOICE-MAIL/</D:displayname>
            </D:prop>
          </D:propstat>
        </D:response>
      </D:multistatus>
```

Program Listing #4 - Exemplary Configuration File

```
      <resource
```

```
    contentclass="urn:content-classes:mailfolder"
    javaclass="com.teamon.proxy.data.impl.MailFolderImpl"
    responsecacheduration="0"
    cachestrength="0">

  <request method="PROPFIND">
    <header name="Brief"          value="t"       />
    <header name="Content-Type"   value="text/xml"/>
    <header name="Depth"          value="1,noroot"/>
    <header name="Range"          value="rows=$rangeStart$-$rangeEnd$"/>
    <header name="Pragma"         value="no-cache"/>
    <header name="X_UP_REFRESH_CACHE" value="force" />
    <body><![CDATA[
      <?xml version="1.0"?>
      <D:propfind
          xmlns:D="DAV:"
          xmlns:hm="urn:schemas:httpmail:"
          xmlns:m="urn:schemas:mailheader:"
          xmlns:up="urn:schemas:teamon:universalproxy">
        <D:prop>
          <D:uid/>
          <D:isfolder/>
          <D:ishidden/>
          <hm:read/>
          <hm:hasattachment/>
          <hm:importance/>
          <m:from/>
          <m:subject/>
          <m:date/>
          <up:isdeleted/>
          <D:getcontentlength/>
          <D:contentclass/>
        </D:prop>
      </D:propfind>
      ]]>
    </body>
  </request>
</resource>
```

THAT WHICH IS CLAIMED IS:

1. A communications system comprising:

a plurality of data storage devices each using at least one of a plurality of different operating protocols;

a plurality of mobile wireless communications devices for accessing said plurality of data storage devices and each using at least one of the plurality of different operating protocols; and

a protocol interface device comprising

a protocol engine module for communicating with said plurality of data storage devices using respective operating protocols,

a front-end proxy module coupled to said protocol engine module and comprising

a respective proxy module for communicating with said plurality of mobile wireless communications devices using each different operating protocol, and

at least one common core service module coupled to said proxy modules, and

a configuration file module coupled to said front-end proxy module for storing a plurality of different sets of configuration files relating to different allocations of resources of the at least one common core service module.

2. The communications system of Claim 1 wherein said plurality of different sets of configuration files comprises a primary set of

configuration files corresponding to core resource allocation operations, and a secondary set of configuration files for customizing the core resource allocation operations.

3. The communications system of Claim 1 wherein said at least one common core service module is for routing traffic between said proxy modules and said protocol engine module.

4. The communications system of Claim 1 wherein said at least one common core service module is for accessing data from said plurality of data storage devices.

5. The communications system of Claim 1 wherein said at least one common core service module is for rendering data for said plurality of mobile wireless communications devices.

6. The communications system of Claim 1 wherein said at least one common core service module comprises a plurality of handlers for interfacing said proxy modules with said protocol engine module.

7. The communications system of Claim 6 wherein said plurality of proxy modules convert access requests from said plurality of mobile wireless communications devices to common access parameters; and wherein said front-end proxy module further comprises a flow controller module for receiving the common access parameters from said plurality of proxy modules and selecting desired handlers for processing thereof.

8. The communications system of Claim 6 wherein said plurality of handlers and said protocol engine module communicate using a common interface protocol.

9. The communications system of Claim 1 further comprising a renderer module for cooperating with said proxy modules to format data for said plurality of mobile wireless communications devices.

10. The communications system of Claim 9 further comprising an extensible mark-up language (XML) engine module coupled to said renderer module.

11. A protocol interface device for interfacing a plurality of mobile wireless communications devices with a plurality of data storage devices, the mobile wireless communications devices and the data storage devices each using at least one of a plurality of different operating protocols, the protocol interface device comprising:

a protocol engine module for communicating with the plurality of data storage devices using respective operating protocols;

a front-end proxy module coupled to said protocol engine and comprising

a respective proxy module for communicating with the plurality of mobile wireless communications devices using each different operating protocol, and

at least one common core service module coupled to said proxy modules; and

a configuration file module coupled to said front-end proxy module for storing a plurality of different sets of configuration files relating to different allocations of resources of the at least one common core service module.

12. The protocol interface device of Claim 11 wherein said plurality of different sets of configuration files comprises a primary set of

configuration files corresponding to core resource allocation operations, and a secondary set of configuration files for customizing the core resource allocation operations.

13. The protocol interface device of Claim 11 wherein said at least one common core service module is for at least one of routing traffic between said proxy modules and said protocol engine module, accessing data from the plurality of data storage devices, and rendering data for the plurality of mobile wireless communications devices.

14. The protocol interface device of Claim 11 wherein said at least one common core service module comprises a plurality of handlers for interfacing said proxy modules with said protocol engine module.

15. The protocol interface device of Claim 14 wherein said plurality of proxy modules convert access requests from the plurality of mobile wireless communications devices to common access parameters; and wherein said front-end proxy module further comprises a flow controller module for receiving the common access parameters from said plurality of proxy modules and selecting desired handlers for processing thereof.

16. A method for interfacing a plurality of mobile wireless communications devices with a plurality of data storage devices, the mobile wireless communications devices and the data storage devices each using at least one of a plurality of different operating protocols, the method comprising:

providing a protocol engine module for communicating with the plurality of data storage devices using respective operating protocols;

coupling a front-end proxy module to the protocol engine comprising

a respective proxy module for communicating with the plurality of mobile wireless communications devices using each different operating protocol, and

at least one common core service module coupled to the proxy modules; and

providing a configuration file module for the front-end proxy module for storing a plurality of different sets of configuration files relating to different allocations of resources of the at least one common core service module.

17. The method of Claim 16 wherein the plurality of different sets of configuration files comprises a primary set of configuration files corresponding to core resource allocation operations, and a secondary set of configuration files for customizing the core resource allocation operations.

18. The method of Claim 16 wherein the at least one common core service module is for at least one of routing traffic between the proxy modules and the protocol engine module, accessing data from the plurality of data storage devices, and rendering data for the plurality of mobile wireless communications devices.

19. The method of Claim 16 wherein the at least one common core service module comprises a plurality of handlers for interfacing the proxy modules with the protocol engine module.

20. The method of Claim 19 wherein the plurality of proxy modules convert access requests from the plurality of mobile wireless communications devices

to common access parameters; and wherein the front-end proxy module further comprises a flow controller module for receiving the common access parameters from the plurality of proxy modules and selecting desired handlers for processing thereof.

21. A computer-readable medium having computer executable modules for interfacing a plurality of mobile wireless communications devices with a plurality of data storage devices, the mobile wireless communications devices and the data storage devices each using at least one of a plurality of different operating protocols, the computer-readable medium comprising:

a protocol engine module for communicating with the plurality of data storage devices using respective operating protocols;

a front-end proxy module coupled to the protocol engine and comprising

a respective proxy module for communicating with the plurality of mobile wireless communications devices using each different operating protocol, and

at least one common core service module coupled to the proxy modules; and

a configuration file module coupled to the front-end proxy module for storing a plurality of different sets of configuration files relating to different allocations of resources of the at least one common core service module.

22. The computer-readable medium of Claim 21 wherein the plurality of different sets of configuration files comprises a primary set of configuration files corresponding to core resource

allocation operations, and a secondary set of configuration files for customizing the core resource allocation operations.

23. The computer-readable medium of Claim 21 wherein the at least one common core service module is for at least one of routing traffic between the proxy modules and the protocol engine module, accessing data from the plurality of data storage devices, and rendering data for the plurality of mobile wireless communications devices.