

DRY POLYMER HYDRATION APPARATUS AND METHODS OF USE

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] The present invention relates to the preparation of subterranean formation treatment fluids, and more particularly, but not by way of limitation, apparatus and methods for preparing viscous treatment gels with dry polymer and water.

Description of the Related Art

[0002] In the oil drilling and production industry, viscous aqueous fluids are commonly used in treating subterranean wells, and as carrier fluids. Such fluids may be used as fracturing fluids, acidizing fluids, and high-density completion fluids. In an operation known as well fracturing, such fluids are used to initiate and propagate underground fractures for increasing oilwell productivity.

[0003] Viscous fluids, such as gels, are typically an aqueous solution of a polymer material. A common continuous method used to prepare viscous fluids at an oilwell site, involves the use of initial slurry of the polymer material in a hydrocarbon carrier fluid (i.e. diesel fluid) which facilitates the polymer dispersion and slurry mixing. Although this process achieves the required gel quality, the presence of hydrocarbon fluids is often objected to in particular fields, even though the hydrocarbon represents a relatively small

amount of the total fracturing gel once mixed with water. Also, there are environmental problems associated with the clean-up and disposal of both hydrocarbon-based concentrates and well treatment gels containing hydrocarbons; as well as with the clean-up of the tanks, piping, and other handling equipment which have been contaminated by the hydrocarbon-based gel.

[0004] Other applications used for the continuous mixing of viscous treatment gels include gelling the polymer in a hydrocarbon carrier that is mixed with water to produce the fracturing gel which is then flowed through baffled tanks providing first-in / first-out (FIFO) flow pattern, and allowing for the hydration time of the gel. Yet, another technique for mixing of dry polymer directly to produce viscous treatment gels is described in Allen, U.S. Patent No. 5,426,137, Allen, U.S. Patent No. 5,382,411, and Harms et al., U.S. Patent No. 5,190,374. These techniques, while potentially effective, require several complicated steps to prepare the gel, which presents drawbacks in an oilwell setting. Further, U.S. Patent Application 2004/0256106 A1 discloses an apparatus without an eductor, for substantially hydrating a gel particulate using a mixer in conjunction with an impeller located within the mixer housing, which prevents formation of gel balls.

[0005] Therefore, there is a need for apparatus and methods useful for hydrating a dry polymer constituents directly for preparing viscous treatment gels in a continuous mode without the use of the hydrocarbon carrier fluid, and such need is met, at least in part, by the following invention.

SUMMARY OF THE INVENTION

[0006] Preparation of a viscous treatment gel from dry polymer is achieved by first dispersing the polymer in water utilizing a constant volume commercial eductor. A premixing device may also be placed in parallel with the eductor to help dispersion and reduce air introduction into the mixture. The eductor operates at a constant water rate and pressure thus producing a concentrated polymer slurry. The resulting concentrated polymer slurry is discharged into a specifically designed dilution and remixing chamber, referred to herein as a "mixing chimney." In the input section of the mixing chimney, a jet of metered dilution water is applied at high pressure to the incoming concentrated polymer slurry stream, to form a diluted polymer slurry. The dilution stream accelerates the concentrated polymer slurry in a circular, and preferably upward, motion where it is sheared against the high drag wall of the chimney, thus fully mixing both streams producing a homogenous diluted gel. The diluted polymer slurry is further sheared as it exits the mixing chimney through circumferentially located perforations or slots which are located upon the output section of the mixing chimney. The exiting viscous treatment gel may then be contained by an external splashguard, or outer chamber, that arrests the radial velocity of the exiting gel while maintaining some of the rotational motion of the fluid into a storage compartment of a hydration tank. The above apparatus provides a simple to operate and robust field technique for continuously producing quality viscous treatment gel at any rate, as required by any specific oilwell application.

[0007] The present invention may be used for continuously mixing and dispersing quality gel from polymer powder, without the need for pretreating the polymer with or spraying

by chemicals that function, for instance, as pH buffers or even hydration retarders. Hence, the invention enables effective use of untreated polymers to prepare a viscous treatment gel at a wellsite.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Fig. 1 shows a general overview of an embodiment of a mixing chimney according to the invention.

[0009] Fig. 2A is a top cross-sectional illustration representing an input section of a mixing chimney embodiment according to the invention.

[0010] Fig. 2B is a first side view of an input section of a mixing chimney embodiment according to the invention.

[0011] Fig. 2C is a second side view of an input section of a mixing chimney embodiment according to the invention.

[0012] Fig. 3 shows an isometric illustration of a mixing chimney middle section according to an embodiment of the present invention.

[0013] Fig. 4 illustrates a process scheme and apparatus that provides the means for continuous mixing and hydration of well viscous treatment gels from dry polymer.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0014] Illustrative embodiments of the invention are described below. In the interest of clarity, not all features of an actual implementation are described in this specification. It will of course be appreciated that in the development of any such actual embodiment,

numerous implementation- specific decisions must be made to achieve the developer's specific goals, such as compliance with system-related and business-related constraints, which will vary from one implementation to another. Moreover, it will be appreciated that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking for those of ordinary skill in the art having the benefit of this disclosure. Preferred embodiments of the invention will now be described with reference to the drawings, wherein like reference characters refer to like or corresponding parts throughout the drawings and description.

[0015] The present invention relates to the preparation of subterranean formation treatment fluids, and more particularly, but not by way of limitation, an apparatus and methods for preparing a viscous treatment gel from dry polymer constituents and water in a continuous mode. The apparatus and methods are particularly useful for preparing a viscous treatment gel from dry polymer at a wellbore site for fracturing a subterranean formation. As used herein: the term "gel" means any liquid material in a viscous state suitable for treating a wellbore; "dry polymer" means any form of polymer which is commercially available, transferred, or supplied, in a solid form (crystalline, amorphous, or otherwise), and not in an aqueous or non-aqueous solvated, slurried, or suspended form, and may be any polymer type useful for well treatments, including, but not limited to biopolymers such as xanthan and diutan, cellulose and its derivatives (i.e. carboxymethylhydroxyethyl cellulose, hydroxypropyl cellulose, etc.), guar and its derivatives (i.e. carboxymethylhydroxypropyl guar, hydroxypropyl guar, carboxymethyl guar, carboxymethylhydroxyethyl guar, etc.), polylactic acid, polyglycolic acid, polyvinyl

alcohol, polyacrylamide, other synthetic polymers, and the like. Any dry polymer may contain commercially acceptable moisture levels.

[0016] Referring to **Fig. 1**, in one embodiment of the invention, the apparatus generally is a mixing chimney (housing) **100** without the need for an impeller inside the chimney, that serves to dilute and mix a concentrated polymer slurry. The mixing chimney **100** also assists in removing air from (de-aerates) the mixture. The mixing chimney **100** comprises a lower input section **110** wherein concentrated polymer slurry and water are separately introduced under pressure, a central section **120** through which the slurry and water are mixed and sheared, and a top section **130** wherein the mixture is further sheared as well as exits. To enable adequate mixing and shear, along the inner wall of mixing chimney **100**, mechanical structures **140** may be disposed thereon in order to impart mixing friction and increase mixing surface area. Suitable examples of the mechanical structures include, but are not necessarily limited to, metallic protrusions, expanded metal mesh, and the like.

[0017] Referring to **Figs. 2A – 2C**, top and side representations of lower input section **110** of a mixing chimney **100** according to an embodiment of the invention, the lower input section **110** has a mixing and dilution chamber **210**, and is ported with inlets in such way as to connect to input tubes **220**, **230**. Input tubes **220** and **230** facilitate the transport of dilution water and concentrated polymer slurry into the mixing chimney **100**. Input tube **230** includes a butterfly type valve **240** placed directly at the entrance of the mixing and dilution chamber to control the dilution rate and produce a high velocity water jet across the range of desired flow rates. The concentrated polymer slurry is

initially prepared by forming a dispersion of dry polymer in water in an eductor. The concentrated polymer slurry is supplied from the eductor through input tube **220**.

[0018] In an embodiment of the present invention, input tube **230** is used to inject dilution water for mixture with the concentrated polymer slurry. The water stream is injected tangentially under pressure along the inner wall of the lower input section **110** of the mixing chimney **100**. Along the inner wall of the lower input section **110**, the water sweeps and accelerates the concentrated polymer slurry stream into a circular motion as the slurry is injected through input tube **220**. The unrestricted flow path in the vertical upwards direction in the mixing chimney **100** allows the incoming slurry and dilution water to move upwards with the resultant flow of the diluted mixture being spirally upwards along the inner wall of the chimney **100**. The rotating motion and the upwards flow induced by the motive force of the dilution water stream from input tube **230**, and not merely the passive energy of the slurry stream from input tube **220**, aids in the elimination of air from the mixture.

[0019] Fig. 3, is an isometric illustration of a mixing chimney central section **120** according to an embodiment of the present invention. The central section **120** of the mixing chimney, illustrated in Fig. 1, which is positioned adjacent the input section **110**. As described above, to enable adequate mixing and shear, mechanical structures **140** may be disposed about the inner wall of the central section **110** to provide higher shear energy. The inner wall may also be smooth. The velocity of the fluid mixture induced by the concentrated polymer slurry and water input streams, as well as the high centrifugal force from the rotation produce a high level of shear against the wall of the central section to

effectively homogenize the mixture and further disperse the polymer. This effectively prevents the formation of undesirable gel balls (commonly referred to as fish-eyes).

[0020] Referring again to **Fig. 1**, in this embodiment, the diluted polymer slurry then passes from the central section **120** upwards into the top section **130**. The top section **130** has a hollow cylindrical outer chamber **150** which surrounds upper chamber **160**, at least in part. The upper chamber **160** of the top section **130**, wherein the diluted polymer slurry transports to from the central section **120**, may have mechanical structures **140** disposed about the inner wall. The diluted polymer slurry then passes from upper chamber **160** and into outer chamber **150**. As the diluted polymer slurry passes from upper chamber **160** and into the space within outer chamber **150**, the slurry passes through a plurality holes or slots **170** circumferentially located upon the periphery of the chamber **160** which may further shear the diluted polymer slurry as it exits the chamber **160**. As the diluted polymer slurry exits the mixing chimney **100**, it is considered formed into a gel which is essentially fully mixed and de-aerated, and at least partially hydrated.

[0021] Upon exiting the mixing chimney **100**, the gel may pass into a first compartment of the hydration tank. In one process, the treatment gel is delivered on a first-in / first-out flow path of the hydration tank, as the treatment gel exits the chimney. Such processes are known in the art and or generally described in Constien et al., U.S. Patent No. 4,828,034, and McIntire, U.S. Patent No. 5,046,865.

[0022] In one embodiment the mixing chimney **100** comprises a lower input section **110** a central section **120**, and a top section **130** wherein each section is connected to form a chamber for mixing. The sections may be connected by any means know in the art, such

as, by non-limiting example, welding or connectable flanges. In other embodiments of the present invention, the chamber may also be formed from one or two cylinders.

[0023] Some mixing chimneys according to the invention may have the input section placed other than the lower portion. For instance, the input section may be at the top of the chimney, while the section through which the diluted polymer slurry exits is positioned at the bottom of the chimney. Hence, the chimney could be comprised of: a top input section comprising a mixing and dilution chamber and inlets connected to input tubes; a central section wherein polymer slurry and water are mixed and sheared; and, a bottom section comprising a plurality holes circumferentially located upon the periphery thereof through which gel exits the chimney.

[0024] In another embodiment of the invention, a method for hydrating a dry polymer to prepare a viscous treatment gel is provided. The process generally includes the steps of dispersing dry polymer in water in an eductor to form a concentrated polymer slurry, and simultaneously injecting the concentrated polymer slurry with water into the input portion of the mixing chimney. The concentrated polymer slurry and dilution water are mixed inside the mixing chimney to form a diluted polymer slurry. The diluted polymer slurry exits through plurality holes or slots positioned at the output section of the mixing chimney to provide a viscous treatment gel. The viscous treatment gel may then be contained and delivered from a hydration tank.

[0025] In further embodiments of the invention, the viscous treatment gel may also be held and flowed through vertically baffled compartments of a first-in / first-out hydration tank which ensures residence time to accommodate further, or full hydration of the gel. Bar turbine agitators in each of the compartments may be further used to shear the gel

enhancing the hydration process, and improving the first-in / first-out flow pattern. The fluid is discharged by gravity from the last compartment of the hydration tank. Process control with feedback from level sensors in each compartment, or the last compartment, controls the mixing rate by altering the opening of the dilution valve.

[0026] Fig. 4 illustrates another embodiment of the invention, which is a method and apparatus that provides the means for continuous mixing and hydration of well viscous treatment gels from dry polymer at a wellbore site. This process and apparatus may however be used for mixing other types of powder material with liquids as well.

[0027] Fig. 4 shows the general process scheme which includes a centrifugal pump 416 that produces motive energy, a mixing eductor 406 that disperses the dry polymer forming a concentrated polymer slurry, a feeder 404 for dispensing the dry polymer from storage/supply bin 402 into the mixing eductor 406, a dilution and mixing chamber (chimney) 410 that receives the concentrated polymer slurry, mixes with dilution water, and discharges a diluted polymer slurry with the required polymer concentration into tank 418. Tank 418 is a multi compartment, 1, 2, 3, 4, 5, first-in/first-out holding and hydration tank equipped with shearing agitators 420. Tank 418 stores and further hydrates the diluted polymer slurry to form a viscous treatment gel.

[0028] In the embodiment represented by Fig. 4, the dry polymer is stored in a storage bin 402 attached to a volumetric feeder 404. The feeder 404 discharges the dry polymer into a mixing eductor 406, where it is dispersed in water, provided from a supply of water, to form a slurry. The supply of water may be introduced into the system via suction connections attached to any suitable available water source. The bin 402 and the feeder 404 are mounted on load cell that continuously records the weight of the bin 402.

Metering of the polymer load rate may be achieved by an initial approximate volumetric rate given by the metering the volumetric feeder 404 screw speed. Accurate gravimetric proportioning is achieved by continuously monitoring the loss in weight of the storage bin 402. Either of these two metering methods may be used individually or in combination. A radial premixer 408, for premixing dry polymer in an aqueous medium, may optionally be placed between the feeder 404 and mixing eductor 406.

[0029] Referring again the Fig. 4, and the embodiment represented thereby, the mixer is a fixed nozzle size eductor 406 which flows a fixed volume of fluid when operated at a constant pressure. The eductor 406 disperses the dry polymer in water and produces a concentrated polymer slurry at a constant flow rate. The resulting concentrated polymer slurry is directed to mixing chimney 410 where the dilution water jet sweeps the concentrated stream and accelerates it into a circular upwards-spiraling motion. The resulting diluted polymer slurry is sheared against the inner wall of the central section of mixing chimney 410 as well as when it exists from top of mixing chimney 410 through the circumferentially located holes or slots to complete the mixing and prevent formation of gel balls. Dilution stream is controlled by a butterfly type valve equipped with an automatic controller 412 which sets the valve position to achieve the required mixing rate. The butterfly valve is located directly at the entry of the chimney and is oriented in a way to produce a jet with a tangential flow into the chimney. A flow meter 414 upstream of both eductor and dilution flow measures the total rate and sends a signal to the controller for setting the position of the control valve. The speed of the feeder 404 is set by the controller to maintain the required ratio between the volume of the mixing water as measured by the flowmeter 414 and the amount of dry polymer dispensed by the

storage bin **402**. As mixing water moves from flowmeter **414** to eductor **406**, the water may optionally pass through a filter **422** to trap any undesirable particles.

[0030] The amount of dry polymer dispensed from bin **402** may be determined by any suitable means, including gravimetrically by measuring the loss in mass of the bin **402**, or volumetrically by controlling the speed of the metering screw **404**. To further formation of the viscous treatment gel, diluted polymer slurry exits the mixing chimney **410** into the first compartment of the hydration tank **418**. Then it may be directed from one compartment to the next flowing downwards from the first compartment **1** to the second **2**, upwards from the second **2** to the third **3**, downwards from the third **3** to the fourth **4**, and upwards from the fourth **4** to the fifth **5**. This maintains a predominantly first-in /first-out flow pattern and ensuring the gel spends at least the required residence time at maximum rate to complete its hydration. Agitators **420** (only one indicated) in each of the compartments may be used to add energy and enhance hydration, as well as to maintain the first-in /first-out flow pattern by minimizing channeling. Ultimately, the viscous treatment gel is supply to a wellbore from the hydration tank via discharge connections.

[0031] The following example illustrates the operation of an embodiment of the invention. The target output rate of a wellbore viscous treatment gel for at a wellbore site is about 20 barrels per minute (840 gal per min., 3180 liters per minute), and the desired concentration of dry polymer in the treatment gel is 40 lb/1000 gallons (4.8 kg/1000 liters). Referring again to Fig. 4, to achieve this rate, chimney **410** would deliver 20 barrels/min (840 gal/min, 3180 liters/min) of diluted polymer slurry to hydration tank **418**. If eductor **406** has a fixed output of 160 gal/min (606 liters/min) to supply concentrated polymer slurry stream to chimney **410**, then the dilution stream water

supply rate to chimney 410 will be 680 gal/min (2574 liters/min). In order to provide the dry polymer concentration (40 lb/1000 gallons) at a viscous treatment gel output rate (20 barrels per minute), 33.6 lb/min (15.3 kg/min) of dry polymer should be supplied from bin 402 to eductor 406, and mixed with water supplied thereto to form a concentrated slurry with dry polymer concentration of about 210 lb/1000 gallons (25.2 kg/1000 liters).

[0032] Also, in other embodiments of the invention, a method and apparatus that provides the means for continuous mixing and hydration of well viscous treatment gels from dry polymer may incorporate the use of a plurality of mixing chimneys. The mixing chimneys may be connected in series, parallel, or any combination thereof.

[0033] While presently preferred embodiments of the invention have been described herein for the purpose of disclosure, numerous changes in the construction and arrangement of parts and the performance of steps will suggest themselves to those skilled in the art in view of the disclosure contained herein, which changes are encompassed within the spirit of this invention, as defined by the following claims.

CLAIMS

We Claim:

1. An apparatus for preparing a viscous treatment gel comprising an eductor connected to a water supply; a plurality of input tubes, wherein at least one input tube is connected with the eductor; and a mixing chimney connected to the input tubes, wherein the mixing chimney comprises:

- a lower input section comprising a mixing and dilution chamber and inlets connected to the input tubes;
- a central section wherein polymer slurry and water are mixed and sheared; and,
- a top section comprising an upper chamber and plurality holes circumferentially located periphery of the upper chamber.

2. The apparatus of claim 1 wherein the central section further comprises mechanical structures adjacent the inner wall of the central section.

3. The apparatus according to any of the preceding claims wherein the top section further comprises a cylindrical outer chamber at least partially disposed about the upper chamber.

4. The apparatus according to any of the preceding claims further comprising a tank for containing and delivering a viscous treatment gel.

5. The apparatus according to any of the preceding claims wherein a first input tubes provides a water dilution stream to the lower section, wherein a second input stream is connected to the eductor and supplies concentrated polymer slurry to the lower section, and wherein the water stream sweeps and accelerates the concentrated polymer slurry stream into a circular motion within the dilution chamber, as the slurry is introduced into the lower section.

6. The apparatus according to any of the preceding claims further comprising a bin connected to the eductor, for storing and supplying dry polymer to the eductor, and further comprising gravimetric load cells upon which the bin is mounted, a volumetric feeder connect to the bin, or combination of both.

7. The apparatus according to any of the preceding claims further comprising premixer positioned between the bin and the eductor.

8. The apparatus according to any of the preceding claims further comprising a filter positioned between the eductor and the water supply.

9. The apparatus according to any of the preceding claims wherein viscous treatment gel is formed from dry polymer and water, and wherein the apparatus operates in a continuous mode.

10. The apparatus according to any of the preceding claims wherein the eductor has a fixed nozzle size.

11. The use of apparatus according to any of the preceding claims to prepare a viscous treatment gel for fracturing a subterranean formation.

12. An apparatus for preparing a viscous treatment gel comprising an eductor connected to a water supply; a plurality of input tubes, wherein at least one input tube is connected with the eductor; and a mixing chimney connected to the input tubes, wherein the mixing chimney comprises:

- an input section comprising a mixing and dilution chamber and inlets connected to the input tubes;
- a central section wherein polymer slurry and water are mixed and sheared; and
- an output section a bottom section comprising a plurality holes circumferentially located upon the periphery thereof through which gel exits the chimney.

13. An apparatus according to claim 12 wherein a first input tubes provides a water dilution stream to the input section, wherein a second input stream is connected to the eductor and supplies concentrated polymer slurry to the input section, and wherein the water stream sweeps and accelerates the concentrated polymer slurry stream into a circular motion within the dilution chamber, as the slurry is introduced into the input section.