

Description

This invention relates to an anti-spin brake system which allows the operator to control each wheel of a vehicle having hydraulic fluid operated brakes in order to limit wheel spin.

Having an automatic differential lock on a vehicle causes the differential gears, axles, wheel spindles, etc., of one wheel to be subjected to high torque loads when the other wheel is experiencing a loss of traction resulting in full torque being applied to the wheel with full traction. This may result in early failure of these components due to the higher torque loads.

Some have overcome this problem by using a standard differential and providing a hydraulic pump coupled to each wheel to automatically sense a change in speed of the two wheels and act on a differential valve which in turn delivers a fluid to apply the brake on the wheel that is spinning, thus causing the spinning wheel to turn substantially at the same rate as the non-spinning wheel. Even though this arrangement allows the torque to be split between the wheels, it is a rather expensive and complex system.

Another attempt at solving this problem was to use a standard differential and spring applied, pressure released brakes and selectively vent the pressure from each brake thus fully applying the brake of the wheel that is spinning. This caused a harsh braking action and could also result in the vehicle veering quickly if the brake of one wheel was accidentally applied by the operator (see for example US-A-3,603,424).

According to the present invention, a vehicle fluid brake system having right and left spring applied, fluid pressure released wheel brakes, a source of fluid pressure, and a brake valve for modulating the pressure applied to the brakes, is characterized in that valve means are provided, disposed between the brake valve and the right and left brakes, and having respective separate outputs to the brakes, for selectively varying the fluid pressure applied to the brakes to separately control the degree of engagement of each brake.

The drawing is a partial schematic and diagrammatic representation of an embodiment of the present invention.

With reference to the drawing, a hydraulic fluid brake system 10 has a main brake control valve 12 for controllably directing pressurized air from an air source 14 to a modulation valve 16. The modulation valve 16 receives pressurized hydraulic fluid from a source of fluid pressure 18, controllably modulates the pressure in response to manual operation of main valve 12, and produces a resultant modulated source of fluid pressure 20. This resultant controlled fluid pressure 20 is passed from modulation valve 16, through conduit 22 and to valve means 24.

For a more thorough understanding of the

modulation valve 16 and its operation and main valve 12, reference is made to U.S. Patent 4,006,939 to Lawrence Francis Schexnayder, issued February 8, 1977.

The valve means 24 is connected to the conduit 22 and receives the modulatable source 20. The valve means 24 can include, for example, a valve 26 of the infinitely variable type having three positions and a selector valve 28 for selective remote control of the valve 26 by receiving pressurized air from a source 29 and directing the air through valve 28 and conduits 31 and 33 to the valve 26 for shifting valve 26 from its first centered position 35 to either its second or third positions 37 and 39. Even though valve 26 is shown to be remotely controlled, it is to be understood that the valve can be directly controlled. A relief valve 30 is associated with valve 26 and a reservoir 34.

A conduit 36 is connected to valve 26 and a right brake 38 and a conduit 40 is connected to valve 26 and a left brake 42. Right brake 38 and left brake 42 are both spring applied and pressure released brakes which are well known in the art and shown in the above noted U.S. Patent 4,006,939.

Right and left wheels 44, 46 are each driven by a pair of respective axles 48 and 50 by an engine 52 through differential 54. Differential 54 is of the standard type that does not allow all of the torque from the engine to be transmitted to the non-spinning wheel such as is the case with ones having differential lock.

The brake system 10 is particularly suitable for use in a vehicle and allows the operator to selectively apply the brake on a wheel that is spinning but prevents the brake from being fully applied.

During normal braking conditions main valve 12 is actuated by the operator and positions modulation valve 16 to provide a controlled pressure signal to both brakes 38 and 42 through the first position 35 of valve 26. By lowering the fluid pressure signal, the braking force is increased. During normal run conditions the modulatable source pressure is, for example, approximately 3860 kPa (560 psi).

When the vehicle encounters a condition that allows one wheel to spin, the operator moves valve 26 to one of its second or third position 37, 39 in response to controllably moving selector valve 28 and supplying pressurized air to either conduit 31 or 33, depending on which wheel is spinning.

If, for example, wheel 46 is spinning, then valve 26 would be moved towards its second position 37 as shown in the drawing. At this position of the valve 26, fully pressurized fluid would be continually delivered to brake 38 while modulating the fluid pressure at brake 42. The controlled fluid pressure may be accomplished at valve 26 or by relief valve 30. Relief valve 30 ensures that the pressure at the brake of the spinning wheel does not go below a preselected pressure, for example, approximately

1050 kPa (152 psi). Consequently, the braking of the spinning wheel is not fully applied.

If, for example, wheel 44 is spinning, then the operator moves valve 26 towards its third position 39 with resultant control of the pressure on the spinning wheel 44, as described above for spinning wheel 46.

By partially applying the brake of the spinning wheel, torque equal to the applied brake torque is transmitted to the ground by the non-spinning wheel. If the selector valve 28 were inadvertently moved during normal roading of the vehicle, the partial braking of one wheel would not create major control problems with the vehicle.

Other aspects, objects and advantages of this invention can be obtained from a study of the drawing, the disclosure, and the appended claims.

Claims

1. A vehicle fluid brake system (10) having right and left spring applied, fluid pressure released wheel brakes (38, 42) a source of fluid pressure (18), and a brake valve (16) for modulating the pressure applied to the brakes (38, 42), characterized in that valve means (24) are provided, disposed between the brake valve (16) and the right and left brakes (38, 42), and having respective separate outputs to the brakes, for selectively varying the fluid pressure applied to the brakes (38, 42) to separately control the degree of engagement of each brake.

2. A system according to claim 1, wherein the valve means (24) includes means (30) for maintaining one of the brakes (38, 42) at a pre-selected minimum fluid pressure.

3. A system according to claim 1 or claim 2, wherein the valve means (24) includes a valve (26) connected to the brake valve (16) and the brakes (38, 42) the valve (26) being movable between a first position (35) at which fluid pressure is supplied evenly to both of the brakes, a second position (37) in which pressure to one of the brakes is independently controllably reduced and a third position (39) in which pressure to the other brake is independently controllably reduced.

4. A system according to claim 3, wherein the valve means (24) includes a manually shiftable selector valve (28) connected to control pilot operation of the valve (26).

5. A system according to claim 3 or claim 4, wherein the valve (26) connects the one or other brake (38, 42) to a reservoir (34) to reduce pressure therein in its second or third positions.

Revendications

1. Système de freinage à commande par fluide (10) pour véhicules, comportant des freins de roue droit et gauche (38, 42) chargés par ressort et libérés par la pression d'un fluide,

une source de fluide sous pression (18), et une valve de freinage (16) destinée à moduler la pression appliquée sur les freins (38, 42), caractérisé en ce qu'il est prévu des moyens formant valve (24) qui sont disposées entre la valve de freinage (16) et les freins droit et gauche (38, 42) et qui possèdent des sorties distinctes aboutissant respectivement aux freins, pour faire varier sélectivement la pression de fluide appliquée sur les freins (38, 42) en vue de régler séparément la force de contact de chaque frein.

2. Système selon la revendication 1, dans lequel les moyens formant valve (24) comprennent des moyens (30) pour maintenir l'un des freins (38, 42) sous une pression minimum pré-sélectionnée de fluide.

3. Système selon la revendication 1 ou la revendication 2, dans lequel les moyens formant valve (24) comprennent une valve (26) raccordée à la valve de freinage (16) et aux freins (38, 42), la valve (26) étant déplaçable entre une première position (35) dans laquelle du fluide sous pression est fourni dans les mêmes proportions aux deux freins, une deuxième position (37) dans laquelle la pression appliquée sur l'un des freins peut être réduite par un réglage indépendant et une troisième position (39) dans laquelle la pression appliquée sur l'autre frein peut être réduite par un réglage indépendant.

4. Système selon la revendication 3, dans lequel les moyens formant valve (24) comprennent une valve sélectrice manoeuvrable manuellement (28) et connectée de telle façon à piloter le fonctionnement de la valve (26).

5. Système selon la revendication 3 ou la revendication 4, dans lequel la valve (26) raccorde l'un ou l'autre des freins (38, 42) à un réservoir (34) afin de réduire la pression à l'intérieur de ceux-ci, dans sa deuxième et sa troisième positions.

Patentansprüche

1. Fahrzeugströmungsmittel-Bremssystem (10) mit rechts und links Feder-angelegten Durchströmungsmitteldruck freigegebenen Radbremsen (38, 42), einer Strömungsmitteldruckquelle (18) und einem Bremsventil (16) zum Modulieren des an die Bremsen (38, 42) angelegten Drucks, dadurch gekennzeichnet, daß Ventilmittel (24) vorgesehen sind, und zwar angeordnet zwischen dem Bremsventil (16) und den rechten und linken Bremsen (38, 42) und mit entsprechenden gesonderten Ausgängen zu den Bremsen, um selektiv den an die Bremsen (38, 42) angelegten Strömungsmitteldruck zu verändern zum gesonderten Steuern des Eingriffsmaßes jeder Bremse.

2. System nach Anspruch 1, wobei die Ventilmittel (24) Mittel (30) aufweisen, um eine der Bremsen (38, 42) auf einem vorgewählten Minimum- Strömungsmitteldruck zu halten.

3. System nach Anspruch 1 oder 2, wobei die Ventilmittel (24) ein Ventil (26) aufweisen, welches mit dem Bremsventil (16) und den

1050 kPa (152 psi). Consequently, the braking of the spinning wheel is not fully applied.

If, for example, wheel 44 is spinning, then the operator moves valve 26 towards its third position 39 with resultant control of the pressure on the spinning wheel 44, as described above for spinning wheel 46.

By partially applying the brake of the spinning wheel, torque equal to the applied brake torque is transmitted to the ground by the non-spinning wheel. If the selector valve 28 were inadvertently moved during normal roading of the vehicle, the partial braking of one wheel would not create major control problems with the vehicle.

Other aspects, objects and advantages of this invention can be obtained from a study of the drawing, the disclosure, and the appended claims.

Claims

1. A vehicle fluid brake system (10) having right and left spring applied, fluid pressure released wheel brakes (38, 42) a source of fluid pressure (18), and a brake valve (16) for modulating the pressure applied to the brakes (38, 42), characterized in that valve means (24) are provided, disposed between the brake valve (16) and the right and left brakes (38, 42), and having respective separate outputs to the brakes, for selectively varying the fluid pressure applied to the brakes (38, 42) to separately control the degree of engagement of each brake.

2. A system according to claim 1, wherein the valve means (24) includes means (30) for maintaining one of the brakes (38, 42) at a pre-selected minimum fluid pressure.

3. A system according to claim 1 or claim 2, wherein the valve means (24) includes a valve (26) connected to the brake valve (16) and the brakes (38, 42) the valve (26) being movable between a first position (35) at which fluid pressure is supplied evenly to both of the brakes, a second position (37) in which pressure to one of the brakes is independently controllably reduced and a third position (39) in which pressure to the other brake is independently controllably reduced.

4. A system according to claim 3, wherein the valve means (24) includes a manually shiftable selector valve (28) connected to control pilot operation of the valve (26).

5. A system according to claim 3 or claim 4, wherein the valve (26) connects the one or other brake (38, 42) to a reservoir (34) to reduce pressure therein in its second or third positions.

Revendications

1. Système de freinage à commande par fluide (10) pour véhicules, comportant des freins de roue droit et gauche (38, 42) chargés par ressort et libérés par la pression d'un fluide,

une source de fluide sous pression (18), et une valve de freinage (16) destinée à moduler la pression appliquée sur les freins (38, 42), caractérisé en ce qu'il est prévu des moyens formant valve (24) qui sont disposées entre la valve de freinage (16) et les freins droit et gauche (38, 42) et qui possèdent des sorties distinctes aboutissant respectivement aux freins, pour faire varier sélectivement la pression de fluide appliquée sur les freins (38, 42) en vue de régler séparément la force de contact de chaque frein.

2. Système selon la revendication 1, dans lequel les moyens formant valve (24) comprennent des moyens (30) pour maintenir l'un des freins (38, 42) sous une pression minimum pré-sélectionnée de fluide.

3. Système selon la revendication 1 ou la revendication 2, dans lequel les moyens formant valve (24) comprennent une valve (26) raccordée à la valve de freinage (16) et aux freins (38, 42), la valve (26) étant déplaçable entre une première position (35) dans laquelle du fluide sous pression est fourni dans les mêmes proportions aux deux freins, une deuxième position (37) dans laquelle la pression appliquée sur l'un des freins peut être réduite par un réglage indépendant et une troisième position (39) dans laquelle la pression appliquée sur l'autre frein peut être réduite par un réglage indépendant.

4. Système selon la revendication 3, dans lequel les moyens formant valve (24) comprennent une valve sélectrice manoeuvrable manuellement (28) et connectée de telle façon à piloter le fonctionnement de la valve (26).

5. Système selon la revendication 3 ou la revendication 4, dans lequel la valve (26) raccorde l'un ou l'autre des freins (38, 42) à un réservoir (34) afin de réduire la pression à l'intérieur de ceux-ci, dans sa deuxième et sa troisième positions.

Patentansprüche

1. Fahrzeugströmungsmittel-Bremssystem (10) mit rechts und links Feder-angelegten Durchströmungsmitteldruck freigegebenen Radbremsen (38, 42), einer Strömungsmitteldruckquelle (18) und einem Bremsventil (16) zum Modulieren des an die Bremsen (38, 42) angelegten Drucks, dadurch gekennzeichnet, daß Ventilmittel (24) vorgesehen sind, und zwar angeordnet zwischen dem Bremsventil (16) und den rechten und linken Bremsen (38, 42) und mit entsprechenden gesonderten Ausgängen zu den Bremsen, um selektiv den an die Bremsen (38, 42) angelegten Strömungsmitteldruck zu verändern zum gesonderten Steuern des Eingriffsmaßes jeder Bremse.

2. System nach Anspruch 1, wobei die Ventilmittel (24) Mittel (30) aufweisen, um eine der Bremsen (38, 42) auf einem vorgewählten Minimum- Strömungsmitteldruck zu halten.

3. System nach Anspruch 1 oder 2, wobei die Ventilmittel (24) ein Ventil (26) aufweisen, welches mit dem Bremsventil (16) und den



Bremsen (38, 42) verbunden ist, wobei das Ventil (26) zwischen einer ersten Position (35) und einer zweiten Position (37) bewegbar ist, wobei in der ersten Position Strömungsmittel-
druck gleichmäßig an beide Bremsen geliefert wird, während in der zweiten Position der an eine der Bremsen angelegte Druck unabhängig steuerbar vermindert wird wobei schließlich in einer dritten Position (39) der Druck an der anderen Bremse unabhängig steuerbar vermindert wird.

4. System nach Anspruch 3, wobei die Ventilmittel (24) ein von Hand schaltbares Wählventil (28) aufweisen, und zwar geschaltet zur Steuerung des Pilotbetriebs des Ventils (26).

5. System nach Anspruch 3 oder 4, wobei das Ventil (26) die eine oder die andere Bremse (38, 42) mit einem Reservoir (34) verbindet, um den Druck darinnen in seinen zweiten oder dritten Positionen zu vermindern.

15

20

25

30

35

40

45

50

55

60

65

4

