

Description

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a screw compressor provided with a built-in volume ratio adjusting valve and a volume control slide valve.

Description of the Related Art

Fig. 3 shows a conventional screw compressor provided with a built-in volume ratio adjusting valve 11 and a volume control slide valve 12. This screw compressor comprises: a casing 15 provided with a suction port 13 and a discharge port 14; a pair of intermeshing, counterrotating screw rotors 16 disposed within and journaled on the casing 15; a cylinder 22 feed to the casing, 15, provided with a partition wall 17 held in place with snap rings and partitioning the interior of the cylinder 22 into a first chamber 18 on the near side with respect to the rotors 16, provided with an inlet port 20X and an outlet port 20Y for the working fluid, and a second chamber 19 on the far side with respect to the rotors 16, provided with an inlet port 21X and an outlet port 21Y for the working fluid; a first piston 24 fitted in the first chamber 18 for axial sliding motion; a second piston 25 fitted in the second chamber 19 for axial sliding motion; a first piston rod 26 having one end joined to the first piston 24 and the other end operatively connected to the built-in volume ratio adjusting valve 11 to move the inner volume adjusting valve 11 in a space between the rotors 16 and the inner surface of the casing 15; a second piston rod 27 having one end joined to the second piston 25 and the other end operatively connected to the volume control slide valve 12 to move the volume control slide valve 12 in a space between the rotors 16 and the inner surface of the casing; a stopper 28 formed integrally with the casing 15 to limit the backward movement of the built-in volume ratio adjusting valve 11. The second piston rod 27 is extended through the first piston rod 26 for sliding movement relative to the first piston rod 26. The volume control slide valve 12 is able to move in the operating range of the built-in volume ratio adjusting valve 11 or in the extension of the operating range of the built-in volume ratio adjusting valve 11. The backward movement of the volume control slide valve 12 is limited by the built-in volume ratio adjusting valve 11. In a state shown in Fig. 3, the first piston 24 is held immovable by spacers 29. The spacers 29 are removed when built-in volume ratio adjustment is necessary.

The adiabatic efficiency of the screw compressor reaches a maximum when

$$V_1^k = P_d/P_s$$

where $V_1 = V_1/V_0$, V_1 is theoretical maximum thread volume, V_0 is theoretical minimum thread volume at the opening of the outlet port, P_d/P_s is external pressure ratio, P_d is discharge pressure, P_s is suction pressure and k is the ratio of specific heat.

When the built-in volume ratio of the compressor needs to be increased to achieve the maximum adiabatic efficiency, the built-in volume ratio adjusting valve 11 is moved to the right, as viewed in Fig. 3, and, when the built-in volume ratio needs to be decreased for the same purpose, the built-in volume ratio adjusting valve 11 is moved to the left. For full load operation; the volume control slide valve 12 is placed contiguously with the built-in volume ratio adjusting valve 11 as shown in Fig. 3 to compress all the sucked gas and to discharge the same through the discharge port 14. For partial load operation or no-load operation, only the volume control slide valve 12 is moved to the right so that a gap is formed between the built-in volume ratio adjusting valve 11 and the volume control slide valve 12 to return part of or all the gas sucked through the suction port 13 to the suction port 13 without compressing the gas.

When the screw compressor is operated under a condition where the suction pressure and the discharge pressure do not vary very much, the built-in volume ratio need not be adjusted by the built-in volume ratio adjusting valve 11. Accordingly, the spacers 29 are placed on both sides of the first piston 24 in the first chamber 18 to hold the first piston 24 immovable and to hold the built-in volume ratio adjusting valve 11 at a fixed-position. This conventional screw compressor, however, has a problem that a large force acting on the built-in volume ratio adjusting valve 11 from the side of the rotors 16 is transmitted through the first piston rod 26, the first piston 24, the spacer 29 and the partition wall 17 and acts on the snap ring 23, and hence the snap ring 23 is liable to be damaged.

US-A-4516914, which provides the preamble of claim 1, describes a screw compressor with a built-in volume control slide valve and stopper means of the casing for limiting the backward movement of the built-in volume ratio adjusting valve. However this stopper means limits the movement of the valve only in one direction and does not provide a means for immobilising the valve under operating conditions where the adjustment of the built-in volume ratio adjusting valve is not required.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a screw compressor provided with a built-in volume ratio adjusting valve and incorporating improvements for securely fixing the built-in volume ratio adjusting valve.

The present invention provides, a screw compressor in accordance with claim 1

In this configuration, all the forces applied by the fixed built-in volume ratio adjusting valve to the spacers is sustained by the casing, and hence the rest of the components are not exposed to excessive forces.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and advantages of the present invention will become more apparent from the following description taken in connection with the accompanying drawings, in which:

Figure 1 is a sectional view of a screw compressor in a first embodiment according to the present invention;

Figure 2 is a sectional view of a screw compressor in a second embodiment according to the present invention; and

Figure 3 is a sectional view of a conventional screw compressor.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

A screw compressor in a first embodiment according to the present invention shown in Fig. 1 is substantially the same in construction as the conventional screw compressor shown in Fig. 3, except that the screw compressor embodying the present invention is provided with a spacer 1a instead of the spacers 29 of the conventional screw compressor, and has a shape conforming to the employment of the spacer 1a. Therefore, parts shown in Fig. 1 like or corresponding to those described, with reference to Fig. 3 are denoted by the same reference characters and the description thereof will be omitted.

Referring to Fig. 1, the spacer 1a is disposed between a built-in volume ratio adjusting valve 11 and a stopper 28 and is fastened to the built-in volume ratio adjusting valve 11 with a bolt with its surface on the far side with respect to the stopper 28 in contact with the side surface of a spacer inserting hole 2. Thus, a force acting on the built-in volume ratio adjusting valve 11 to the left, as viewed in Fig. 1, is sustained by the stopper 28, and a force acting on the built-in volume ratio adjusting valve 11 to the right, as viewed in Fig. 1,

is sustained by the side surface of the spacer inserting hole 2. The spacer inserting hole 2 is closed with a cover plate 3.

A screw compressor in a second embodiment according to the present invention shown in Fig. 2 is substantially the same in construction as the screw compressor shown in Fig. 1, except that the screw compressor in the second embodiment employs a spacer 1b fastened to a built-in volume ratio adjusting valve 11 and a stopper 28 with bolts instead of the spacer 1a, and hence parts like of corresponding to those shown in Fig. 1 are denoted by the same reference characters and the description thereof will be omitted.

In this screw compressor both forces acting in opposite directions on the built-in volume ratio adjusting valve 11 are sustained by the stopper 28.

As is apparent from the foregoing description; according to the present invention, the spacer is fastened at least to either the built-in volume ratio adjusting valve or the first piston rod, and to the casing so as to be immovable in the operating direction of the built-in volume ratio adjusting valve relative to the built-in volume ratio adjusting valve and the casing, so that force acting on the fixed built-in volume ratio adjusting valve is sustained directly by the casing. Accordingly, the rest of the components are not exposed to excessive forces and the built-in volume ratio adjusting valve can be securely fixed.

Although the invention has been described in its preferred forms with a certain degree of particularity, obviously many changes and variations are possible therein. It is therefore to be understood that the present invention may be practiced otherwise than as specifically described herein without departing from the scope and spirit thereof.

A screw compressor comprises a pair of screw rotors provided in a casing, a cylinder fixed to the casing and having a first chamber and a second chamber, a first piston fitted in the first chamber, a second piston fitted in the second chamber, a built-in volume ratio adjusting valve operated by the first piston; a volume control slide valve operated by the second piston, a stopper fixed to the casing to limit the backward movement of the built-in volume ratio adjusting valve, and a volume control slide valve. When built-in volume ratio adjustment is unnecessary, the built-in volume ratio adjusting valve is held immovable between the stopper and a spacer fixed to the built-in volume ratio adjusting valve and resting on a fixed surface of the casing. All the forces acting on the immovable built-in volume ratio adjusting valve are sustained by the casing, so that the rest of the components of the screw compressor are not exposed to excessive forces.



Claims

1. A screw compressor comprising:

a casing (15);
a pair of intermeshing, counterrotating screw rotors (16) disposed within and journaled on said casing (15);

a cylinder (22) fixed to said casing (15) and provided with a fixed partition wall (17) partitioning the interior of said cylinder into a first chamber (18) on the near side with respect to said screw rotors (16), provided with a first inlet port (20x) and a first outlet port (20x) for the working fluid, and a second chamber (19) on the far side with respect to said screw rotors, provided with a second inlet port (21x) and a second outlet port (21x) for the working fluid;

a first piston (24) fitted in said first chamber (18) for an axial sliding movement;

a second piston (25) fitted in said second chamber (19) for an axial sliding movement;

a first piston rod (26) joined to said first piston (24);

a built-in volume ratio adjusting valve (11) operated through said first piston rod (26) by said first piston (24) for movement in a space between said screw rotors (16) and an inner surface of said casing (15);

a stopper (28) formed integrally with said casing or fixed to said casing to limit the backward movement of said built-in volume ratio adjusting valve;

a second piston rod (27) joined to said second piston (25) and extended through said first piston rod (26) for an axial sliding movement relative to said first piston rod; and

a volume control slide valve (12) operated through said second piston rod (27) by said second piston (25) for movement in a space between said screw rotors (16) and said inner surface of said casing (15) in the operating range of said built-in volume ratio adjusting valve (11) or in the extension of the operating range of said built-in volume ratio adjusting valve, the backward movement of said volume control slide valve (12) being limited by said built-in volume ratio adjusting valve (11);

characterized in that a spacer (1a; 1b) is fastenable at least to either said built-in volume ratio adjusting valve (11) or said first piston rod (26), and to said casing (15) so that a force acting on said built-in volume ratio adjusting valve (11) is sustained directly by said casing (15).

Patentansprüche

1. Schraubenverdichter, der aufweist:

ein Gehäuse (15),

ein Paar von ineinandergreifenden, sich gegenläufig drehenden Schraubenrotoren (16), die im Gehäuse (15) angeordnet und an diesem gelagert sind,

einen Zylinder (22), der am Gehäuse (15) befestigt ist und mit einer feststehenden Trennwand (17) versehen ist, die das Innere des Zylinders in eine erste Kammer (18) an der in bezug auf die Schraubenrotoren (16) nahe liegenden Seite, die mit einer ersten Einlaßöffnung (20x) und einer ersten Auslaßöffnung (20x) für das Arbeitsfluid versehen ist, und eine zweite Kammer (19) an der in bezug auf die Schraubenrotoren entfernt liegenden Seite unterteilt, die mit einer zweiten Einlaßöffnung (21x) und einer zweiten Auslaßöffnung (21x) für das Arbeitsfluid versehen ist,

einen ersten Kolben (24), der in die erste Kammer (18) für eine axiale Gleitbewegung eingepaßt ist,

einen zweiten Kolben (25), der in die zweite Kammer (19) für eine axiale Gleitbewegung eingepaßt ist,

eine erste Kolbenstange (26), die mit dem ersten Kolben (24) verbunden ist,

ein Einbau-Volumenverhältnis-Einstellventil (11), das über die erste Kolbenstange (26) durch den ersten Kolben (24) zur Bewegung in einem Raum zwischen den Schraubenrotoren (16) und einer Innenfläche des Gehäuses (15) betätigt wird,

einen Anschlag (28), der mit dem Gehäuse einstückig ausgebildet ist oder am Gehäuse befestigt ist, um die Rückwärtsbewegung des Einbau-Volumenverhältnis-Einstellventils zu beschränken,

eine zweiten Kolbenstange (27), die mit dem zweiten Kolben (25) verbunden ist und sich durch die erste Kolbenstange (26) hindurch zur axialen Gleitbewegung in bezug auf die erste Kolbenstange erstreckt, und

einen Volumensteuerschieber (12), der im Arbeitsbereich des Einbau-Volumenverhältnis-Einstellventils (11) oder in der Erweiterung des Arbeitsbereiches des Einbau-Volumenverhältnis-Einstellventils über die zweite Kolbenstange (27) durch den zweiten Kolben (25) zur Bewegung in einem Raum zwischen den Schraubenrotoren (16) und der Innenfläche des Gehäuses (15) betätigt wird, wobei die Rückwärtsbewegung des Volumensteuerschiebers (12) durch das Einbau-Volumenverhältnis-Einstellventil (11) beschränkt wird,

dadurch gekennzeichnet, daß ein Abstand-



halter (1a; 1b) an zumindest dem Einbau-Volumenverhältnis-Einstellventil (11) oder der ersten Kolbenstange (26), und dem Gehäuse (15) befestigbar ist, so daß eine auf das Einbau-Volumenverhältnis-Einstellventil (11) wirkende Kraft durch das Gehäuse (15) direkt abgefangen wird.

Revendications

1. Compresseur à vis comprenant :

- un boîtier (15);
- une paire de rotors de vis en opposition et en engrènement (16) placés dans et tourillonnant sur ledit boîtier (15);
- un cylindre (22) fixé audit boîtier (15) et muni d'une paroi de séparation fixe (17) séparant l'intérieur dudit cylindre en une première chambre (18) sur le côté proche desdits rotors de vis (16), munie d'un premier orifice d'entrée (20x) et d'un premier orifice de sortie (20y) pour le fluide de travail, et en une seconde chambre (19) sur le côté éloigné desdits rotors de vis (16), munie d'un second orifice d'entrée (21x) et d'un second orifice de sortie (21y) pour le fluide de travail;
- un premier piston (24) logé dans ladite première chambre (18) pour un coulisement axial;
- un second piston (25) logé dans ladite seconde chambre (19) pour un coulisement axial;
- une première tige de piston (26) liée audit premier piston (24);
- une soupape intégrée de réglage du rapport volumique (11) actionnée via ladite première tige de piston (26) par ledit premier piston (24) pour se déplacer dans un espace séparant lesdits rotors de vis (16) et une surface interne dudit boîtier (15);
- une butée (28) formée de façon intégrale audit boîtier ou fixée audit boîtier pour limiter le déplacement vers l'arrière de ladite soupape intégrée de réglage du rapport volumique (11);
- une seconde tige de piston (27) liée audit second piston (25) et s'étendant à travers ladite première tige de piston (26) pour un coulisement axial par rapport à ladite première tige de piston (26); et
- une soupape à coulisseau de commande du volume (12) actionnée via ladite seconde tige de piston (27) par ledit second piston (25) pour se déplacer dans un espace séparant lesdits rotors de vis

(16) et ladite surface interne dudit boîtier (15) dans l'intervalle de fonctionnement de ladite soupape intégrée de réglage du rapport volumique (11) ou dans une extension de l'intervalle de fonctionnement de ladite soupape intégrée de réglage du rapport volumique (11), le déplacement vers l'arrière de ladite soupape à coulisseau de commande du volume (12) étant limité par ladite soupape intégrée de réglage du rapport volumique (11);

compresseur caractérisé en ce qu'une entretoise (1a; 1b) peut être fixée au moins soit à ladite soupape intégrée de réglage du rapport volumique (11), soit à ladite première tige de piston (26) et audit boîtier (15) de telle façon qu'un effort agissant sur ladite soupape intégrée de réglage du rapport volumique (11) soit directement repris par ledit boîtier (15).