CLAIMS

1. A circuit card configuration (I) comprising a card element (10) being arranged to be attached via assembly points and to support connection points for signal connection and ground connection, ~~**characterized in that**~~ wherein the respective assembly points as well as the respective connection points comprise a metallic bushing (21, 22, 23, 24, 25, 26) arranged to be attached at the card element (10), **characterized in that** the card element (10) with its bushings (21, 22, 23, 24, 25, 26) is arranged to be embedded in a case compound (G), wherein a portion (21b, 22b, 23b, 24b) of bushings (21, 22, 23, 24) is arranged to protrude from said cast compound (G) for assembly and connection to ground.

2. A circuit card configuration according to claim 1, wherein said metallic bushing (21, 22, 23, 24, 25, 26) is essentially made of brass.

~~3. A circuit card configuration according to claim 1 or 2, wherein the card element (10) with its bushings (21, 22, 23, 24, 25, 26) is arranged to be embedded in a cast compound (G).~~

~~4.~~3. A circuit card configuration according to ~~any of claims 1-3~~claims 1 or 2, wherein said metallic bushing (21, 22, 23, 24, 25, 26) comprises an internal thread.

~~5.~~4. A circuit card configuration according to any of claims ~~1-4~~1-3, wherein said metallic bushing (21, 22, 23, 24, 25, 26) comprises a portion (21a, 22a, 23a, 24a, 25a, 26a) with a polygonal cross section.

~~6.~~5. A circuit card configuration according to any of claims ~~1-5~~1-4, wherein said polygon is a regular hexagon.

~~7.~~6. A circuit card configuration according to any of claims ~~1-6~~1-5, wherein said bushing (21, 22, 23, 24, 25, 26) is arranged to be attached to the card element with soldered joints and or screw joints.

~~8.~~7. A circuit card configuration according to any of claims ~~1-7~~1-6, wherein said metallic bushing (21, 22, 23, 24, 26) comprises a through hole (21d, 22d, 23d, 24d, 26d) for said assembly and/or signal connection.

~~9.~~8. A circuit card configuration according to any of claims ~~1-8~~1-7, wherein said card element (10) and at least parts of said bushings (21, 22, 23, 24, 25, 26) are housed in a box (50).

~~10.~~9. A circuit card configuration according to any of claims 1-8, wherein the card element (10) is arranged to support an electric filter configuration.