

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65H 37/00		A1	(11) International Publication Number: WO 96/15060
			(43) International Publication Date: 23 May 1996 (23.05.96)
(21) International Application Number: PCT/US95/14539		(81) Designated States: AL, AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, LS, MW, SD, SZ, UG).	
(22) International Filing Date: 8 November 1995 (08.11.95)			
(30) Priority Data: 9422905/1 14 November 1994 (14.11.94) GB			
(71) Applicant (for all designated States except US): THE GILLETTE COMPANY [US/US]; Prudential Tower Building, Boston, MA 02199 (US).			
(72) Inventors; and			
(75) Inventors/Applicants (for US only): STEVENS, Christopher, John [GB/GB]; 8 The Willows, Caversham, Reading, Berkshire RG4 8BD (GB). WHITE, Robert [GB/GB]; 69 Ilges Lane, Cholsey, Oxford OX10 9PA (GB).			
(74) Agents: GALLOWAY, Peter, D.; Ladas & Parry, 26 West 61st Street, New York, NY 10023 (US) et al.			

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

86 9701991-3

(54) Title: TAPE DISPENSER

(57) Abstract

A tape dispenser, e.g. a correction tape dispenser, has a tip element (4) defining an edge (5) around which passes the tape (1) including the correction composition carried on a carrier ribbon, the tip edge being used to press the tape against a surface onto which the correction composition is to be transferred as a strip or band, and the tip element (4) being mounted, such as by plastic hinge (10), to allow pivotal movement of the tip about an axis Y substantially perpendicular to the surface and spaced in front of the tip edge (5).

