

ELECTRIC MOTOR FOR CLOTHES WASHING MACHINE DRIVE

5 This invention relates to clothes washing machines of the type having a cabinet in which an agitator is mounted on a vertical axis and is oscillated back and forth within a perforated spin tub which, in turn, is mounted within a watertight container, the spin tub and the agitator rotating continuously in one direction to give a spin action, the cabinet containing an electric motor and driving means for the agitator and spin tub and/or clothes washing machines incorporating such drives.

10 A clothes washing machine of the general type described above is disclosed in USA 2,665,576. In the washing machine of USA 2,665,576 the agitator is fixed to the spin tub. When an agitating action is required the spin tub is rotated back and forth independently of the water tight container. When a spin action is required the spin tub and the water tight container are rotated together in one direction. The washing machine of USA 2,665,576 has a float chamber for effecting engagement and/or
15 disengagement of a clutch mechanism which engages a spin tub with the water tight container. The engagement and/or disengagement of the clutch mechanism is dependant on the quantity of water present in the water tight container. The arrangement disclosed in USA 2,665,576 has the disadvantage that the agitator, spin tub and water tight container must all be rotated during the spin action. Also, since the
20 agitator and spin tub are connected together, agitation is not as effective as it would be if the agitator was moving while the spin tub was kept stationary. Another disadvantage with the washing machine disclosed in USA 2,665,576 is that during a spin cycle there must be a hydraulic connection between the water tight container and the spin tub which is less efficient than a direct mechanical connection between the
25 motor and the spin tub.

It is, therefore, an object of the present invention to provide a clothes washing machine of the type described which goes some way towards overcoming the above disadvantages or which will at least provide the public with a useful choice.

Accordingly, in one aspect, the invention consists in an electric motor for a
30 clothes washing machine having a stator carrying energisable windings on poles thereof and a rotor,

characterised in that

a motor frame has a single pair of spaced apart bearings mounted in said frame

in a central disposition relative to said frame, said frame has stator locating means arranged to hold an outer cylindrical surface of said stator concentric with said bearings; and

5 a single shaft is rotatably mounted directly in said bearings and carries said rotor, and at least one bearing of said pair of bearings is spaced at a remote position relative to said stator wherein said rotor comprises:

a backing ring of a magnetic material,

a series of permanent magnets spaced apart on an inner surface of said backing ring, said backing ring and magnets being rotatable exteriorly of said stator windings,

10 a hub mounted on said shaft, and

a backing ring support holding inner faces of said permanent magnets concentric with said shaft.

In a second aspect, the invention consists in an electric motor for a clothes washing machine having a stator formed as an annular helical yoke edgewise wound
15 from a strip of magnetic material and having an inner face and an outer face, said strip having pole pieces formed integrally therewith, the pole pieces extending from one edge of said strip and said strip being edgewise wound whereby said pole pieces coincide in stacked groups to form a plurality of poles arranged at equally spaced intervals extending radially outwardly from the outer face of the yoke;

20 energisable stator windings wound directly on said pole pieces of said stator and adapted to be energized through an electronic commutation circuit;

a rotor mounted for rotation exteriorly of and relative to said stator, said rotor comprising a backing ring of magnetic material and a series of permanent magnets held at spaced-apart intervals on an inner surface of said backing ring and opposing
25 the pole pieces of said stator;

characterised in that

a motor frame having a single pair of spaced apart bearings mounted is in said frame in a central disposition relative to said frame, said frame having stator locating means arranged to hold an outer cylindrical surface of said stator concentric with said
30 bearings; and

a single shaft is rotatably mounted directly in said bearings and carrying said rotor, and at least one bearing of said pair of bearings being spaced at a remote position relative to said stator.

In a further aspect, the invention consists in a drive for a clothes washing machine of the type having a cabinet in which an agitator is mounted on a vertical shaft so as to rotate therewith and to be oscillated back and forth within a coaxially mounted perforated spin tub for washing action, the spin tub and the agitator being
5 rotatable continuously in one direction for providing a spin action, and the perforated spin tub and agitator in turn being mounted within a stationary watertight container, said cabinet containing driving means acting through said shaft for selectively oscillating said agitator back and forth or rotating said spin tub continuously in one direction, characterised in that

10 said shaft is rotatably mounted on a single pair of water-sealed bearings and said spin tub is rotatably mounted on said shaft by an unsealed bearing, said shaft rotatably carrying said spin tub and driving said spin tub when desired through interconnecting means,

interconnection actuating means are provided to actuate said interconnecting
15 means to interconnect said spin tub and said agitator for conjoint rotation in one direction for spinning and to disconnect said agitator from said spin tub for said washing action to take place.

To those skilled in the art to which the invention relates, many changes in construction and widely differing embodiments and applications of the invention will
20 suggest themselves without departing from the scope of the invention as defined in the appended claims. The disclosures and the descriptions herein are purely illustrative and are not intended to be in any sense limiting.

The invention consists in the foregoing and also envisages constructions of which the following gives examples.

25 One preferred form of the invention will now be described with reference to the accompanying drawings, in which;

Figure 1 is a cross-sectional elevation of a clothes washing machine constructed according to the invention, with some parts shown at 45° in plan to other parts,

Figure 2 is an enlarged view part in cross-section of a water container, spin tub,
30 agitator, drive and electric motor, and

Figures 3 and 4 are respectively a plan view and cross-section of preferred motor frames incorporated in the invention in the preferred form,

Figure 5 is a further enlarged view of a seal shaft and bearings being part of

Figure 2,

Figure 6 is a part cross-section of an alternative embodiment of the invention,

Figure 7 is a part cross-section of a further alternative embodiment of the invention,

5 Figure 8 is a scrap elevation at 45° to the view in Figure 1, and

Figure 9 is a rear view of a motor agitator forming part of the invention.

Referring to the drawings a clothes washing machine comprises a cabinet 1 of square cross section which has mounted in it an electric motor 2 constructed according to the present invention as will be described further later. A water container 3 is
10 suspended within the cabinet 1 by suspension rods 4 and springs 5 and for example four springs and rods are provided, and the motor and other mechanism are attached to the container 3. The springs are provided in the corners of the square cross-section cabinet 1 accordingly parts of the rod are shown in sectional view in Figure 8 which is at 45° to the other sectional view of Figure 1. By water is meant washing liquid, for
15 example water and detergent. Contained within the water container 3 there is a perforated spin tub 6 and within the spin tub is an agitator 7. An opening lid 9, shown only partially is provided through which clothes may be inserted into the container and within the spin tub 6. The spin tub is partly balanced by upper balancing ring 40 shown only in the rear one side in Figure 1. The springs terminate in hooks 12 which engage
20 in apertures 13 in the container base moulding 29. The agitator 7 is mounted on a hollow drive shaft 11 so as to rotate therewith but is slidable axially thereon. The spin tub 6 is coaxially mounted on the shaft 11 so as to be rotatably and also slidable axially thereon.

The motor 2 is constructed as follows. A rotor 15 has a backing ring 16 (Figure
25 2) and the backing ring is formed from a strip of magnetic material for example a silicon steel alloy and the strip of steel is coiled on edge with adjacent surfaces lightly insulated and touching each other to provide a short hollow cylinder or annular helix. Inside the helix there is provided a series of magnets 17, the backing ring 16 being expanded slightly before being placed over the magnets placed in a mould. The
30 magnets are permanent magnets of a material capable of being magnetised to a high flux value, for example, Neodinium iron made by Magnaquench Inc. and the annulus and the magnets are held in place by a plastics member 18 which has a hub 19, a disc or spoked connector portion 20, and substantially cylindrical element 21, the member

being moulded over the backing ring and magnets so as to maintain the inner faces of the magnets 17 concentric with the axis of the hub 16.

The stator 25 of the motor has a magnetic core which comprises a strip of magnetic material again preferably a silicon steel alloy or other low hysteresis steel which is preformed to provide spaced apart pole pieces and again this strip is formed by bending on edge to form an annular helix in the form of a hollow cylinder with the poles 8 formed by the stacked pole pieces pointing outwardly. As may be seen in Figure 9 the poles 8 are connected together by a narrow band 14 so that bending on edge is relatively easily effected. To provide insulation for windings on the poles of the core a top insulating moulding 22 is placed on one side of the poles and a bottom insulating moulding 23 placed on the opposite side, meeting at a joint line 24. Windings are placed on the mouldings wound around each pole and such windings 26 are effected on the poles directly.

It is preferable that the stator be wound in a three phase star connected mode and the windings are made and connected using known techniques.

The stator 25 and the rotor 15 are mounted as will shortly be described.

The water container 3 is preferably an injection moulding and the base 29 has motor support columns 30 preferably braced with stiffening webs 31. These webs extend to the outer perimeter of the container 3 and are moulded integrally with the container.

The motor 2 includes two bearing frames 32 and 33 which comprise injection mouldings of a die cast metal or plastics material or preferably steel pressings or plastic material. Preferably the frames 32 and 33 are produced from the same mould or set of dies, thus ensuring equality of dimensions between the two frames. The frames are carefully designed and made so that the bearing mouldings 27 and 28 are concentric with locating pins or dimples 34 and corresponding holes 35 at the periphery of the frames and with the external angle 36 in which the inner corner 3 of the stator 25 fits with an interference fit.

Stiffening depressions 49 are provided to stiffen the frames and on assembly one frame is assembled rotated 45° relative to the other frame to provide correct matching of holes and dimples.

Bearings 38 and 39 fit in the bearing mountings 27 and 28 and the bearings are spaced apart by a spacing tube 40 which encircles the drive shaft 11. The hub 19 is

fixed to the shaft 11 by a bolt 41 engaging a nut 41a held in the hollow of the shaft 11 by the shaft 11 being swaged down to provide splines which engage corresponding spline spaces 42 in the hub 19. For transport purposes a further nut 43 holds the assembly supported by suspension rods and fixed to a cabinet member 44.

5 The spin tub 6 comprises a stainless steel perforated hollow cylinder 45 fixed to a plastics extruded base 46, for example, by spinning the lower edge of the cylinder 45 on to the periphery of the plastics base 46. If desired a lower balancing ring 47 is provided and the upper and lower balancing rings each comprise a hollow ring with baffles and liquid container therein and the rings are each closed by an annular disc
10 48 and 48a respectively. One balancing ring preferably the ring 10 have been found to give reasonable balance while spinning.

A plurality of bridges 50 are provided at spaced intervals with gaps between them and the bridges connect the balancing ring 47 (if fitted) to an air chamber in the form of a bell having an open mouth directed downwardly and a tube 52 integral
15 therewith which surrounds the shaft 11. A low friction plastics bearing 53 enables the plastics base 29 and consequently the spin tub 6 to rotate and slide axially on the drive shaft 11.

A series of downwardly directed dog clutch teeth 55 (Figure 2) of a high impact duty material, for example a high impact duty plastics material, are carried by a carrier
20 56 riveted screwed or otherwise fixed to the air chamber 51, for example by screws 57. A ring 60 carries coacting dog clutch teeth 61 also of a high impact duty material and the ring 60 is rotatable by and axially slidable on the drive shaft 11, for example by engagement of splines on the ring 60 with splines on the drive shaft 11. The agitator
25 7 has a boss 62 with inner splines 63 engaging outer splines 64 on the ring 60 so that rotation of shaft 11 results in rotation of the teeth 61 and the agitator 7, and the boss 62 slides axially on the drive shaft 11 as may be seen by comparing the "up" position of elements on the left hand side of Figures 1 and 2 with the "down" position on the right hand side.

The air chamber 51 is designed to provide a flotation or buoyancy force
30 resulting from the entrapment of air in the air tight air chamber 51 when water closes the perimeter of the lower edge of the air chamber 51. In the event that water enters the air chamber 51, for example because of turbulence during agitation, the lower face could be closed off with a disc 54.

The buoyancy force is at least sufficient to lift the spin tub 6, and the agitator 7 when a substantially predetermined volume of water is provided in the container 3, and the spin tub and agitator 7 is shown in the "up" position on the left hand side of Figures 1 and 3 and in the "down" position on the right hand side. When the spin tub 6 is in the up position, that is, supported by floatation of the air chamber 51 the teeth 55 and the teeth 61 are disengaged from each other and the agitator may be rotated freely over any desired rotational movement independent of the spin tub 6. When water is absent or substantially absent from the container 3 the spin tub 6 sinks until the teeth 55 and 61 are engaged. The spin tub 6 and agitator will then be rotated as one unit and this rotation will be effected continuously in one direction to spin clothes in the spin tub to a drier condition in the known way. To assist in freeing frictional contact between the axially sliding parts during up and down movement of the spin tub during filling with, and emptying of water, control means are provided controlling motor 2 to give a slow agitating action, that is, forward and reverse rotation over a small arc of movement. At each reversal the dogs will reverse contact and be free of each other for a short time due to clearances as between the dogs and spaces between the dogs.

To assist in fixing the spin tub against rotation during agitation, that is, when the agitator is in the up position, the upper edge 67 of the spin tub may contact a frictional surface 68 on the underside of a top member 69 of the container 3.

The agitator 7 has external blades 81 thereon which extend from the surface of both column 82 and the upper surface of an upper coned disc 83. There is a space 84 between the disc 83 and the upper surface 85 of the air chamber 51 this space may be divided with radial vanes (not shown) since the purpose of the space arrangement is to provide a centrifugal impeller. Such an impeller may be otherwise provided, for example an independent centrifugal pump could be provided.

Outlet openings 86 are provided from the space 84 at or near the outer edge of the disc 83 the outer edge 87 of which is turned downwardly and operates in close proximity to the inner edge of the balance ring 47. As a result of this construction a pumping action is given, pumping water from the centre of column 82, from apertures 88 through space 84 below balance ring 47 to space 86 between the spin tub 6 and the container 3 and lint is restrained in this space before the water re-enters the spin tub through the holes 90. If desired a container may be mounted on the column 82 such

container holding a clothes conditioner in the known way.

Electronic commutation equipment 65 is provided on an annular printed circuit board in an annular container 66 mounted below the stator 25 and the electronic commutation equipment is preferably enclosed in a compound for protection and heat
5 sinking, and is such as to enable the electric motor 2 to move in a backward and forward motion thus causing the shaft 11 to be oscillated backward and forth resulting in the agitator 7 being also rotated in a back and forth motion to give the well known washing motion. Such electronic commutation equipment is described in New Zealand
10 Patent No 213489/213490 and corresponding UK Patent No 82180672 and US Patent No 4857814 which are incorporated herein by reference. The electronic commutation equipment 65 is also arranged to drive the motor continuously to give a spin action, and to drive the spin tub with the agitator, the absence of water from the container 3 results in engagement of teeth 55 and 61 as above described.

However, when the agitator is preferably given a slow agitation motion and the
15 container 3 has water in it at least to a predetermined level the flotation force of air in air chamber 51 causes the air chamber spin tub and agitator to rise. The teeth 55 are then raised out of contact with the teeth 61 and the agitator may now move independently of the spin tub and thus may be oscillated back and forth at a desired rate and over any desired angle of rotation to give a washing action without material
20 movement of the spin tub.

To provide seals between the drive shaft 11 and the base 29 of the water container, a short cylinder 70 of steel for example (Figure 5) is fixed to the upper frame 32 by a screw 71 and a flange 72 holds the bearing 38 in place. The short cylinder 70 supports a seal 72 against the wall 73 of an aperture in the water container
25 base 29 and a disc 74 holds a further seal 75 against the shaft 11, being reinforced by a backing ring 76. A played disc 77 holds a further seal 78 against the shaft 11 reinforced also by a spring 79, the flange 80 sitting within a short cylinder 81 integral with disc.

The seal 72, short cylinder 81 disc 74 and seal 75 are integral with each other
30 and the played disc 77 seal 78 and flange 80 are integral with each other. Both units are made of Neoprene or other known flexible sealing material.

A pump 95 is provided for the purpose of draining the container 3 and the pump 95 is mounted directly about an opening 96 in a lower part of the container 3

and thus a single flexible tube can run from the pump outlet through the back of the cabinet to the user drain connection point.

It is to be noted that the bearings 38 and 39 are a slip fit on the drive tube 11 and tightening of the bolt 41 and a cap 91 by a screw 92 clamps both bearings into position. Removal of the rotor securement screw 92 and the bolt 41 can result in the drive tube 11 being removed from above and the motor rotor 16 being removed from below. The motor 2 is removable as a unit after removing also the screws 93 holding the frames 32 and 33 in position. Thus for maintenance purposes this removal can be readily be effected. Furthermore following removal of the securement screw 92, the agitator and agitator hub can be removed and the spin tub assembly then lifted off from above. Thus maintenance is very simple.

It is also to be noted that because the spin tub and its contents float during the agitation phase no thrust bearing is required. Also the bearing 53 operates under water and only under low speed condition, that is, the agitator speed relative to the substantially stationary spin tub and therefore the bearing need only be a light duty bearing.

An alternative form of interconnection means is provided as follows with reference to Figure 6.

The agitator 7 has associated with it a bell 100 both being fixed to the shaft 101 by a bolt 102. The shaft 101 corresponds to the shaft 11 and is driven by an electric motor as above described.

Within the bell 100 is a rise and fall member 103 which is a plastics moulding sealably attached by a flexible bellows 105 eg. of neoprene to the outer edge 106 of the plastic member 103 and to the edge of the bell 100. A further flexible bellows 107a is sealably attached to the member 103 and to the hub of the bell 100. The member 103 has prongs or dogs 108 spaced at intervals thereon and such prongs or dogs 108 engage in the spaces between castellations 109 in the bottom of the spin tub 6. A spring (not shown) is provided which exerts a downward force from the hub 108 on the member 103 and the cavity 110 is open to atmosphere through a cross hole or notch 111 in the hub 108 and a series of holes in the shaft or drive tube 101. This arrangement is such that when the container 3 is emptying, the spring moves the member 103 downwardly so that the prongs or dogs 108 engage in the spaces between the castellations and thus the spin tub will move with the agitator and be rotated with

that agitator continuously for the purpose of spinning. However, when the container 3 has water in it to a predetermined level the hydrostatic water pressure on the undersurface of the member 103 causes that member to rise against the pressure of the spring air venting through the air holes abovementioned and the prongs or dogs 5 108 are then raised out of contact with the spin tub and the agitator may now move independently of the spin tub and thus may be oscillated back and forth to give a washing action.

In a further alternative arrangement of spin tub to agitator interconnecting means shown in Figure 7 the agitator 7 is combined with a hub 110 fixed by a bolt 111 10 to a solid splined shaft 112. An air chamber in the form of a bell member 115 is a slidable fit on the shaft 112 and has air entrapment spaces 116 in which air is trapped by rising water in the container 3 when the latter is being filled preparatory to agitation occurring. The bell 115 then acts as a float raising detents or dogs 113 from engagement with castellations 107 as shown on the right hand side of Figure 7 to a 15 disengaged position as shown on the left hand side of Figure 7.

At least in the preferred forms the invention provides the following advantages:

1. The electric motor assembly and construction is integrated with the drive system in that a simple shaft and pair of bearings supports the rotor at one end of the agitator and spin tub at the other end advocating the need for separate shafts and bearings for the motor and for the agitator and spin tub drive. 20
2. The mounting of the stator and the rotor outboard of the lower motor frame enable ready replacement of the stator and/or rotor.
3. The mounting of the electronics in an annular disk associated with the stator of the motor reduces the length of interconnecting wiring and enables a 25 compact factory wired unit to be provided.
4. The floating spin tub concept eliminates the need for springs bearings and enables ready maintenance to be carried out.
5. The complete freedom of the agitator to rotate through an unlimited angle of rotation during agitation enables any desired angle of rotation.

CLAIMS:

1. An electric motor (2) for a clothes washing machine having a stator (25) carrying energisable windings (26) on poles (8) thereof and a rotor (21),
5 characterised in that
a motor frame (32, 33) has a single pair of spaced apart bearings (38, 39) mounted in said frame (32, 33) in a central disposition relative to said frame (32, 33), said frame (32, 33) has stator locating means (34, 35, 36) arranged to hold an outer cylindrical surface of said stator concentric with said bearings (38, 39); and
10 a single shaft (11) is rotatably mounted directly in said bearings (38, 39) and carries said rotor (21), and at least one bearing of said pair of bearings (38, 39) is spaced at a remote position relative to said stator (25) wherein said rotor (21) comprises:
a backing ring (16) of a magnetic material,
15 a series of permanent magnets (17) spaced apart on an inner surface of said backing ring (16), said backing ring (16) and magnets (17) being rotatable exteriorly of said stator (25) windings,
a hub (19) mounted on said shaft (11), and
a backing ring support (18) holding inner faces of said permanent magnets (19)
20 concentric with said shaft (11).
2. An electric motor as claimed in claim 1, wherein said stator (25) is disposed outboard of said frame (32, 33) and with said rotor (21) has a connecting portion (20) between a hub (16) and a rim (21) and said connecting portion (20) being outboard
25 of said stator (25).
3. An electric motor as claimed in claim 1 wherein said stator (25) comprises an annular helix of a magnetic material, said helix having said poles (8) extending outwardly from the circumferential surface of an annulus, said annular helix being
30 mounted on said stator locating means (34, 35, 36).
4. An electric motor as claimed in claim 1, wherein insulation to insulate said windings from said poles is provided and comprises a pair of mouldings (22, 23), each



said moulding being in the form of an annulus with insulation covering one part of each pole (8), there being a division (24) intermediate of the thickness of each pole (8) between the two mouldings (22, 23).

- 5 5. An electric motor for a clothes washing machine having a stator (25) formed as an annular helical yoke edgewise wound from a strip of magnetic material and having an inner face and an outer face, said strip having pole pieces formed integrally therewith, the pole pieces extending from one edge of said strip and said strip being edgewise wound whereby said pole pieces coincide in stacked groups to form a
10 plurality of poles (8) arranged at equally spaced intervals extending radially outwardly from the outer face of the yoke;

energisable stator windings (26) wound directly on said pole pieces of said stator (25) and adapted to be energized through an electronic commutation circuit (65, 66);

- a rotor (21) mounted for rotation exteriorly of and relative to said stator (25),
15 said rotor (21) comprising a backing ring (16) of magnetic material and a series of permanent magnets (17) held at spaced-apart intervals on an inner surface of said backing ring (16) and opposing the pole pieces of said stator (25);

characterised in that

- a motor frame (32, 33) having a single pair of spaced apart bearings (38, 39)
20 mounted is in said frame (32, 33) in a central disposition relative to said frame (32, 33), said frame having stator locating means (34, 35, 36) arranged to hold an outer cylindrical surface of said stator (25) concentric with said bearings (38, 39); and

- a single shaft (11) is rotatably mounted directly in said bearings (38, 39) and carrying said rotor (21), and at least one bearing of said pair of bearings (38, 39) being
25 spaced at a remote position relative to said stator (25).

6. An electric motor as claimed in claim 5, wherein the inner face edge of said stator strip opposite the edge thereof from which said pole pieces extend is notched between each adjacent pole (8) so as to reduce the width of said stator strip whereby
30 adjacent poles (8) are connected by a narrow band of strip material (14).

7. An electric motor as claimed in claim 5 or claim 6, and further comprising insulated mouldings (22, 23) on said poles (8), said stator windings being wound on



said insulated mouldings (22, 23).

8. A drive for a clothes washing machine of the type having a cabinet (1) in which an agitator (7) is mounted on a vertical shaft (11) so as to rotate therewith and to be
5 oscillated back and forth within a coaxially mounted perforated spin tub (6) for washing action, the spin tub (6) and the agitator (7) being rotatable continuously in one direction for providing a spin action, and the perforated spin tub (6) and agitator (7) in turn being mounted within a stationary watertight container (3), said cabinet (1) containing driving means (2) acting through said shaft (11) for selectively oscillating
10 said agitator (7) back and forth or rotating said spin tub (6) continuously in one direction,

characterised in that

said shaft (11) is rotatably mounted on a single pair of water-sealed bearings (38, 39) and said spin tub (6) is rotatably mounted on said shaft (11) by an unsealed
15 bearing 53), said shaft (11) rotatably carrying said spin tub (6) and driving said spin tub (6) when desired through interconnecting means (55, 56, 108, 109),

interconnection actuating means (51, 16) are provided to actuate said interconnecting means (55, 56, 108, 109) to interconnect said spin tub (6) and said agitator (7) for conjoint rotation in one direction for spinning and to disconnect said
20 agitator (7) from said spin tub (6) for said washing action to take place.

9. A drive for a clothes washing machine as claimed in claim 8, wherein said spin tub (6) is slidably and rotatably mounted on said shaft (11) by an unsealed bearing (53).
25

10. A drive for a clothes washing machine as claimed in claim 8, wherein said agitator (7) and said spin tub (6) are removable from said container (3) upwardly through an upper opening in said container merely by freeing said agitator (7) from said drive shaft (11).
30

11. A drive for a clothes washing machine as claimed in claim 8 wherein said shaft is driven by a salient pole electric motor (2) having a stator (25) carrying energisable windings on salient pole pieces (8) thereof, a rotor (21) and a stator support frame (32,



33) mounted on said stationary water-tight container (3) and supporting said stator (25), said shaft (11) carrying said rotor (21) at one end thereof and said agitator (7) at another opposite end thereof, said shaft (11) being mounted on said single pair of water-sealed bearings (38, 39) spaced intermediately of said electric motor (2) and said
5 agitator (7).



ELECTRIC MOTOR FOR CLOTHES WASHING MACHINE DRIVE
ABSTRACT

An electric motor (2) for a clothes washing machine including the motor and
5 a drive, the motor having a stator (25) held outboard of a frame carrying bearings (38,
39) in which a shaft (11) rotates, the shaft carrying the rotor (21) outboard of the
stator (25), and permanent magnets (17) on an inner face of the rotor. The stator (25)
is formed as an annular helical yoke edgewise wound from a strip of magnetic material
and having an inner face and an outer face, the strip having pole pieces (8) formed
10 integrally therewith extending from one edge of the strip and the strip being edgewise
wound whereby the pole pieces coincide in stacked groups to form a plurality of poles
arrange at equally spaced intervals extending radially outwardly from the outer face of
the yoke. Energisable stator windings (26) are wound directly on the poles (8) of the
stator and are adapted to be energised through an electronic commutation circuit (65,
15 66) and the rotor (21) is mounted for rotation exteriorly of and relative to the stator,
the rotor comprising a backing ring (16) of magnetic material and a series of
permanent magnets (17) held at spaced apart intervals on an inner surface of the
backing ring (16) and opposing the poles (8) of the stator (25).

[Figure 1 is suggested for publication]

Fig. 1.





Fig. 2.








Fig. 6.




Fig. 7.




Fig. 8.




Fig. 9.

