

METHOD FOR DISPENSING MILK PORTIONS IN DRINK
PREPARATION MACHINES

The invention relates to a method for dispensing milk
5 portions in drink preparation machines having a milk
fill level monitoring unit for a milk container
according to claim 1, in particular for coffee machines
with milk container provided for preparing Capuccino.
The invention further relates to a milk fill level
10 monitoring unit for a milk container according to claim
2 for carrying out the method.

In coffee machines, producing the milk froth for the
Capuccino and the heating of milk is carried out in
15 many cases in a frothing device using the Venturi
principle. A negative pressure is generated with a
suitable steam jet, which sucks the milk from the
supply container (milk container) via a hose system and
guides it into the nozzle of the frothing device. In
20 the nozzle, the milk is brought together with the steam
and the milk-steam-air mixture leaves the frothing
device and runs into the cup through a steady outlet
jet. If air is added to the cold milk during the
extraction, warm milk with a milk froth located
25 thereover is produced in the cup. Without air being
added, the milk can only be heated.

If too little or no milk is present in the milk
container and the sequence of the milk product
30 deliveries, in particular the Capuccino delivery in the
coffee machine controller is fixedly programmed, the
consumer only receives a coffee without milk or with
too little milk and milk froth. For the user this is
irksome since he must repeat the entire process once
35 again to obtain a perfect Capuccino (milk product) and
throw away the coffee that has possibly already been
withdrawn. This means a waste of resources and also has

financial implications, particularly if the consumer must pay a fixed amount for the Capuccino withdrawal, whether this be in the office area or in the restaurant area.

5

If the milk supply is interrupted, whether this be because no or too little milk is available, this does not form a homogeneous milk outlet jet from the nozzle during withdrawal. In addition to the first annoyance, 10 there is the added factor that the front side of the coffee machine can be contaminated by milk, water and steam splashes.

In addition, since in most cases the milk container is 15 not transparent, it is difficult for the consumer to monitor the fill level of the milk. The supplied milk should be stored in a cooled manner as far as possible. This is achieved in many cases with an insulating container (double-walled structure with an evacuated 20 intermediate space) or with a small refrigerator using a Peltier element. In these devices, it is not possible to monitor the milk fill level without opening the container. In addition, this is also impractical in most cases and is frequently forgotten.

25

There are indeed drink preparation machines such as, for example, the "Thermoplan Tiger" from Thermoplan which have an integrated milk system with a cooled milk tank in the substructure. The device additionally has a 30 capacitively operating milk fill level monitoring unit. Naturally however, the milk fill level in the milk tank is not readily apparent to the user of the drink preparation machine even in this case. It has additionally been found that in the event of the milk 35 fill level monitoring unit being tripped, i.e. in the event of the capacitively operating sensor being tripped in this device, a milk dispensing process which

is possibly just being executed, is not carried out completely but is prematurely interrupted.

It is thus the object of the invention to provide an improved and more user-friendly method for preparing drinks with milk or milk constituents in drink preparation machines such as coffee machines. Furthermore, a suitable milk fill level monitoring unit will be provided for carrying out the method.

10

This object is achieved by the features of claims 1 and 2.

15

The solution starts from the fact that a delivery of a milk portion from the milk container, controlled by the electronic device control system, is carried out completely and with a sufficient quantity of milk even when, during a delivery of the milk portion, the milk fill level monitoring unit signals a drop in the fill level of the milk below a threshold value.

20

At the same time, in order to further increase the user friendliness of the drink preparation machine, when the fill level of the milk drops below the threshold value, the user is given an indication on a display that the milk container is empty and further deliveries of milk portions are blocked until the milk container is sufficiently filled again or at least until the milk fill level monitoring unit releases this function again.

30

By ensuring that a milk delivery process, once initiated, is always completed, it is achieved that the milk outlet jet always remains homogeneous and as a result jet irregularities and splashes are reliably avoided.

35

Naturally, the necessary conditions for this must also be provided on the hardware side. Thus, it must be ensured by constructive measures that in the event of the threshold value sensor being tripped, there is
5 still sufficient milk in the milk container to actually complete the initiated process. However, since such measures are substantially questions of dimensioning in most cases, e.g. by specifying the height of the suction opening of a suction tube and the level of
10 triggering of a threshold value signal, in the exemplary embodiment shown, reference is merely made to one possible embodiment.

Various principles of action can be used in the
15 threshold value sensors. Thus, for example, sensors using the capacitive or resistive principles can be used. Capacitive monitoring has the advantage that this is simpler to achieve electronically. However, such circuits are fundamentally known to the person skilled
20 in the art which is why they are not explained in detail in the following.

Due to the possibility that either an internally or an externally disposed milk container can be used, the
25 user friendliness can be further improved, in particular if a modular extension concept is provided (i.e. a suitable milk container can be made available to the drink preparation machine).

30 In the case of an externally disposed milk container, an external electronic evaluation system attached to the milk container can also be provided. However, this is usually only used for fill level information and with the exception of signal relaying functions, has no
35 further functions on the electronic device control system of the drink preparation machine. However, it can nevertheless be very practical and conducive to

clarity to display the fill level directly on the
'affected' device.

The fill level monitoring according to the invention in
5 a coffee machine will be explained in detail
hereinafter for two examples using the resistively
acting sensor principle with reference to drawings.

In the drawings:

10

Fig. 1 shows a schematic diagram of a coffee machine
with a milk container provided,

15

Fig. 2 shows a sectional drawing of the milk
container with an external electronic
evaluation system in a first embodiment and

20

Fig. 3 shows a simplified sectional drawing of the
arrangement of the elements of the milk fill
level monitoring unit in the milk container
according to the first embodiment.

25

Fig. 4 shows a sectional drawing of the milk
container with an external electronic
evaluation system in a second embodiment.

Figure 1 shows a schematic diagram of a coffee machine
with a milk container 1 provided.

30

In this case, milk is poured into the milk container 1
which is located in a coffee machine 11 or preferably
outside said coffee machine. This liquid container 1 is
preferably an insulating container and can be made of
metal, glass or plastic. As a result, the milk can be
35 stored for some time in this container. The milk is
sucked by a suction tube 3 with a flexible hose 7 to a
milk frother 12 with a milk outlet 13. On one side the

hose 7 is plugged onto a hose connection 6 of a container lid 2 of the milk container 1 and on the other side it is plugged onto a docking point 8 of the milk frother 12. Both connections can be removed by the user for cleaning.

The suction tube 3 and a measuring rod 4 are fastened on the container lid 2 at a suitable distance with respect to one another. The suction tube 3 is required for extracting the milk and is made of an electrically conductive material, preferably metal. The shorter, likewise electrically conductive measuring rod 4, which can also be implemented as a tube closed at the bottom, is fixed parallel to the suction tube 3 on the container lid 2. A temperature measurement can also be integrated in the measuring rod 4 by which means the milk temperature can be measured or monitored. If the temperature is too high, this can be notified to the consumer directly via a display 10 on the coffee machine 11. The two elements suction tube 3 and measuring rod 4 are connected electrically to an electronic device control system 9 of the coffee machine 11 by means of a signal line 5. The fill level of the milk can be monitored by means of variation in conductance between the suction tube 3 and the measuring rod 4. The conductivity of the milk is higher than that of air. The principle can also be applied to other liquids such as water, tea, etc. If the milk level falls below the (shorter) measuring rod 4, there is a marked jump in the measurement signal. This signal is evaluated directly in the electronic device control system 9 or evaluated with an external display 16. When the signal evaluation is made directly by the electronic device control system 9, the delivery of milk products can be interrupted or blocked until sufficient milk has been topped up again. This ensures

that the outlet jet from the milk outlet 13 of the milk frother 12 always remains homogeneous.

The electronic device control system 9 can also release
5 a certain follow-up quantity 14 so that the actuated delivery is not interrupted if the set milk delivery quantity does not exceed a residual quantity 15 in the milk container 1. The request for topping up the milk is only made at the end of the milk delivery. The fill
10 level minimum (alarm) can be notified to the consumer with various possibilities for display; it can be accomplished visually by means of a display indication, a luminous LED or pictogram or the like or it can be effected audibly by means of a beeper, buzzer, vibrator
15 or the like.

The applied measurement principle also functions when the suction tube 3 and the measuring rod 4 are arranged coaxially.

20

If the milk container 1 is made of metal, the fill level monitoring can also be made between the container wall and the measuring rod 4 and the suction tube 3 could then be made of a non-conducting material. The
25 corresponding signal line 5 must then naturally not be secured to the suction tube 3 but to the container wall of the milk container 1.

Figure 2 shows a sectional drawing of the milk
30 container 1 with an external electronic evaluation system 16 in a first embodiment. In this case, the measurement signal from the threshold value sensor is not connected directly to the electronic device control system 9 of the drink preparation machine but is fed to
35 the external electronic evaluation system 16. When the signal evaluation is made with an external electronic evaluation system 16, the product delivery is not

prevented but merely indicated when the fill level is fallen below or the liquid container 1 is empty. If the display 10 on the external electronic evaluation system 16 is not noted by the consumer and a Capuccino delivery is triggered nevertheless, the jet from the milk outlet 13 is not homogeneous when the fill level is fallen below. The fill level minimum can be displayed to the consumer with similar means as on the drink preparation machine.

10

Figure 3 shows another simplified sectional drawing of the arrangement of the elements of the milk fill level monitoring unit in the milk container according to the first embodiment. The suction tube 3 projects deeper into the milk container 1 than the shorter measuring rod 4. If the fill level falls below the level A, the lower end of the measuring rod 4 no longer touches the milk and the measured conductance between the suction tube 3 and the measuring rod 4 is then much lower. In this exemplary embodiment, the level A therefore designates the mentioned threshold value. Nevertheless, milk can be further extracted via the suction tube 3 until the suction opening 17 of the suction tube is exposed (indicated as level B) and only a residual quantity 15 remains in the milk container. The amount of milk which can be extracted between level A and B is designated as the follow-up quantity 14 and is determined in such a manner that when the method according to the invention is being used to deliver milk portions, the delivery of milk portions can always be completed. The follow-up quantity 14 is therefore the same as or greater than the largest amount of milk required per drink selection.

35

Figure 4 finally shows a sectional drawing of the milk container with an external electronic evaluation system in a second embodiment. In this case, the milk

container 1 is made of metal (or an electrically conductive material). Thus, the fill level monitoring can also be made directly between the milk container 1 and the suction tube 3. This is a more cost-effective
5 solution. In this case, the suction tube 3 must be constructed of two materials. The upper part of the suction tube 3 is here made of an electrically conductive material (preferably metal tube), the lower part, in this case a suction part 19, is made of a non-
10 conductive material (preferably plastic or rubber). Both parts must be tightly connected to one another. The signal lines 5 are connected by means of a contact spring 18 and a conducting connecting piece.

15 The evaluation signal is generated by measuring the conductivity between the suction tube 3 and the milk container 1. For this purpose, the upper end of the suction tube 3 and the milk container 1 are electrically connected to the external electronic
20 evaluation system 16. If the milk level drops below the electrically conducting part of the suction tube, a marked jump in the measurement signal takes place. However, the suction part 19 can still extract milk from the milk container 1. The length of the non-
25 conducting suction part 19 determines the residual quantity 15 and the follow-up quantity 14 in the milk container 1.

REFERENCE LIST

- 1) Milk container
- 2) Container lid
- 5 3) Suction tube
- 4) Measuring rod
- 5) Signal line
- 6) Hose connection
- 7) Hose
- 10 8) Docking point for milk frother
- 9) Electronic device control system
- 10) Display
- 11) Coffee machine
- 12) Milk frother
- 15 13) Milk outlet
- 14) Follow-up quantity
- 15) Residual quantity
- 16) Electronic external evaluation system
- 17) Suction opening
- 20 18) Contact spring
- 19) Suction part
- 20) Conducting connecting piece
- A,B (Fill level) level

25

30

35

CLAIMS

1. A method for dispensing milk portions in drink
preparation machines having a milk fill level
5 monitoring unit for a milk container (1), wherein
according to the method
 - a delivery of a milk portion from the milk
container (1) controlled by an electronic
device control system (9) is carried out
10 completely and with sufficient quantity of
milk even when the milk fill level monitoring
unit signals a drop in the fill level of the
milk below a threshold value during the
delivery of the milk portion,
 - 15 - when the fill level of the milk drops below
the threshold value, the user of the drink
preparation machine is given an indication on
a display (10) that the milk container (1) is
empty and
 - 20 - further deliveries of milk portions to the
drink preparation machine are blocked until
the milk container (1) is sufficiently
refilled or at least until the milk fill
level monitoring unit releases this function
25 again.
2. A milk fill level monitoring unit for carrying out
the method according to claim 1 for a drink
preparation machine having a milk container (1),
30 wherein the drink preparation machine has an
electronic device control system (9), a display
(10) and a milk frother (12) and wherein a suction
tube (3) of the milk container (1) is connected
via a tube or hose (7) to the milk frother (12)
35 and wherein the suction tube (3) dipping into the
milk container (1) has a suction opening (17) and
a measuring rod (4) likewise dipping into the milk

container (1) to form the threshold value and a capacitively or resistively operating threshold value sensor is provided, characterised in that the suction opening (17) is disposed at the lower end of the suction tube (3) closer to the bottom of the milk container (1) than a lower end of the measuring rod (4) and a vertical distance between the suction opening (17) on the suction tube (3) and the lower end of the measuring rod (4) is arranged in such a manner that, when the fill level of the milk drops below the threshold value, a minimal predetermined residual volume of milk can still be extracted.

3. The milk fill level monitoring unit for carrying out the method according to claim 1 for a drink preparation machine having a milk container (1), wherein the drink preparation machine has an electronic device control system (9), a display (10) and a milk frother (12) and wherein a suction tube (3) of the milk container (1) is connected via a tube or hose (7) to the milk frother (12) and wherein the suction tube (3) dipping into the milk container (1) has a suction opening (17) and at the same time serves as a measuring rod dipping into the milk container (1) to form the threshold value and a capacitively or resistively operating threshold value sensor is further provided, characterised in that the suction tube (3) and the milk container (1) are electrically conducting and an electrically non-conducting suction part (19) is placed at the lower end of the suction tube (3) and the height of the non-conducting suction part (19) is dimensioned so that when the fill level of the milk drops below the threshold value, a minimal predetermined residual volume of milk can still be extracted.

4. The milk fill level monitoring unit according to
claim 2 or 3, characterised in that when a milk
container (1) is located externally with respect
5 to the drink preparation machine, an external
electronic evaluation system (16) attached to the
milk container (1) is provided.

10

15

20

25

30

35