



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B28C 5/38, 5/46, 5/48, B01F 7/20, 13/06		A1	(11) International Publication Number: WO 96/00640
			(43) International Publication Date: 11 January 1996 (11.01.96)
(21) International Application Number: PCT/AU95/00383		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, <u>SG</u> , SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).	
(22) International Filing Date: 28 June 1995 (28.06.95)			
(30) Priority Data: PM 6578 30 June 1994 (30.06.94) AU			
(71)(72) Applicant and Inventor: HOOD, Max, George [AU/AU]; 17 Serpentine Road, Erina Heights, NSW 2260 (AU).			
(74) Agent: SHELSTON WATERS; 60 Margaret Street, Sydney, NSW 2000 (AU).		Published With international search report.	

(54) Title: APPARATUS FOR CEMENT BLENDING

(57) Abstract

An apparatus (10) for mixing and discharging a slurry consisting primarily of water and cement, said apparatus comprising a pressure vessel (12) adapted to contain slurry and agitating means (13) disposed to mix the slurry within the pressure vessel (12). The pressure vessel (12) includes a first inlet (14) adapted for connection to a source of pressurised driving fluid and a first outlet (16) for discharge of the slurry upon pressurisation of the vessel (12) by the driving fluid.

