



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : C08G 65/48		A1	(11) International Publication Number: WO 00/46275
			(43) International Publication Date: 10 August 2000 (10.08.00)
(21) International Application Number: PCT/US99/29068 (22) International Filing Date: 7 December 1999 (07.12.99) (30) Priority Data: 09/245,255 5 February 1999 (05.02.99) US (71) Applicant: GENERAL ELECTRIC COMPANY [US/US]; 1 River Road, Schenectady, NY 12345 (US). (72) Inventors: BRAAT, Adrianus, J., F., M.; Krekeberg 17, NL-4708 KR Roosendaal (NL). LANDA, Adrie; Pater Dehonlaan 144, NL-4615 DB Bergen op Zoom (NL). LISKA, Juraj; De Boulevard 136, NL-4617 LZ Bergen op Zoom (NL). (74) Agents: SNYDER, Bernard et al.; General Electric Company, 3135 Easton Turnpike W3C, Fairfield, CT 06431 (US).		(81) Designated States: AU, BR, CA, CN, CZ, IN, JP, KR, MX, RU, SG, ZA, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.	
 *G00001*			
(54) Title: CAPPING OF POLYPHENYLENE ETHER RESIN			
(57) Abstract			
The invention relates to methods of capping poly(phenylene ether) resin having an intrinsic viscosity between 0.05 and 0.35 dl/g. More particularly, the methods comprise capping a poly(phenylene ether) resin having an intrinsic viscosity between 0.05 and 0.35 dl/g in a solvent to produce a capped poly(phenylene ether) resin having an intrinsic viscosity between 0.05 and 0.35 dl/g and isolating the capped poly(phenylene ether) resin by removal of the solvent, preferably in a process other than precipitation. The invention also relates to the capped poly(phenylene ether) resin having an intrinsic viscosity between 0.05 and 0.35 dl/g.			
 *162162*			