



- (51) International Patent Classification:
C10M 129/06 (2006.01)
- (21) International Application Number:
PCT/US2015/034628
- (22) International Filing Date:
8 June 2015 (08.06.2015)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
62/009,377 9 June 2014 (09.06.2014) US
- (71) Applicant: **THE LUBRIZOL CORPORATION**
[US/US]; 29400 Lakeland Blvd., Wickliffe, Ohio 44092-2298 (US).
- (72) Inventors: **HOBSON, David M.**; P.O. Box 88, Belper, Derby Derbyshire DE56 1QN (GB). **KOHUT, Michael R.**; P.O. Box 88, Belper, Derby Derbyshire DE56 1QN (GB). **GOTHERIDGE, Stephen J.**; P.O. Box 88, Belper, Derby Derbyshire DE56 1QN (GB).
- (74) Agents: **TYRPAK, Michele M.** et al.; The Lubrizol Corporation, 29400 Lakeland Blvd., Wickliffe, Ohio 44092-2298 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: SYNTHETIC INDUSTRIAL LUBRICANTS WITH IMPROVED COMPATIBILITY

(57) Abstract: The invention relates to industrial gear oil compositions that have been specially designed to have improved storage stability and/or paint compatibility and/or seal compatibility. This improvement is achieved while maintaining good performance in other areas. These improvements are particularly relevant to synthetic lubricants, such as those made with polyalphaolefin (PAO) base oils. This balance of properties has been difficult to achieve in synthetic compositions where problems in the areas of storage stability, paint compatibility and/or seal compatibility of become more pronounced. The invention also relates to processes of making such compositions and methods of using the same.

