

HIGH-DENSITY, ROBUST CONNECTOR WITH CASTELLATIONS

Background of the Invention

The present invention pertains generally to electrical connectors, and more particularly to an improved connector suitable for use in backplane applications, of robust structure and improved electrical performance.

Backplanes are large circuit boards that contain various electrical circuits and components. They are commonly used in servers and routers in the information and technology areas. Backplanes are typically connected to other backplanes or to other circuit boards, known as daughter boards, which contain circuitry and components. Data transfer speeds for backplanes have increased as backplane technology has advanced. A few years ago, data transfer speeds of 1 Gigabit per second (Gb/s) were considered fast. These speeds have increased to 3Gb/s to 6Gb/s and now the industry is expecting speeds of 12Gb/s and the like to be implemented in the next few years.

At high data transfer speeds, differential signaling is used and it is desirable to reduce the crosstalk and skew in such test signal applications to as low as possible in order to ensure correct data transfer. As data transfer speeds have increased, so has the desire of the industry to reduce costs. High speed signal transfer has in the past required the differential signal terminals to be shielded and this shielding increased the size and cost of backplane connectors because of the need to separately form individual shields that were assembled into the backplane connector.

These shields also increased the robustness of the connectors so that if the shields were to be eliminated, the robustness of the connector needed to be preserved. The use of shields also added additional cost in the manufacture and assembly of the connectors and because of the width of the separate shield elements, the overall relative size of a shielded backplane connector was large.

The present invention is directed to an improved backplane connector that is capable of high data transfer speeds, that eliminates the use of individual shields and that is economical to produce and which is robust to permit numerous cycles of engagement and disengagement.

Summary of the Invention

It is therefore a general object of the present invention to provide a new backplane connector for use in next generation backplane applications.

Another object of the present invention is to provide a connector for use in connecting circuits in two circuit boards together that has a high terminal density, high speed with low crosstalk and which is robust.

A further object of the present invention is to provide a connector for use in backplane applications in which the connector includes a plurality of conductive terminals arranged in rows and in which the rows comprise either signal or ground terminals and which are held in a support structure that permits the connector to be used in right angle and orthogonal mating applications.

Yet another object of the present invention is to provide a backplane connector assembly that includes a backplane header component and a wafer connector component that is matable with the backplane header component, the backplane header component having a base that sits on a surface of a backplane and two sidewalls extending therefrom on opposite ends defining a channel into which the wafer connector component fits, the backplane header component including a plurality of conductive terminals, each of the terminals including a flat contact blade portion, a compliant tail portion and a body portion interconnecting the contact and tail portions together so that they are offset from each other, the backplane header component including slots associated with terminal-receiving cavities thereof, the slots providing air gaps, or channels, between the terminals through the backplane header component.

A still further object of the present invention is to provide a wafer connector component that includes a plurality of conductive terminals arranged in two symmetric columns, each of the terminals including contact portion at one end thereof and tail portion at another end thereof, the terminals being held in insulative support halves that are combined together to form a single wafer connector component.

An additional object of the present invention is to provide a wafer connector component in which two columns of conductive terminals are supported in an insulative support body, the body including an internal cavity disposed between the two columns of conductive terminals, the terminal being arranged in horizontal pairs of terminal, the cavity defining an air channel between each horizontal pair of terminals arranged in the two columns of terminals, and the terminals being further aligned with each other in each row so that horizontal faces of the terminals in the two rows face each other to thereby promote broadside coupling between horizontal pairs of terminals.

Another object of the present invention is to provide a backplane connector that is assembled from a plurality of wafers, with each wafer supporting a plurality of rows of

conductive terminals and with each of the wafers including an internal cavity interposed between the terminals of each row, the cavity receiving an insert having a selected dielectric to affect the broadside capacitive coupling between the terminals of each row.

Yet still a further object of the present invention is to provide a high density backplane connector that utilizes a plurality of connector elements, each of the connector elements supporting two rows of conductive terminals, the two rows of terminals defining a plurality of pairs of associated terminals which are aligned side to side with each other to promote broadside capacitive coupling between the terminal pairs, the two rows of terminals being held within the connector elements in a predetermined spacing devoid of grounding shields, each row of terminals being held by an insulative framework that includes a plurality of castellations between adjacent terminals in the row, the castellations serving to focus the coupling energy of the terminals of each terminal pair into broadside coupling while deterring edge coupling between adjacent pairs or terminal.

The present invention accomplishes these and other objects by way of its structure. In one principal aspect, the present invention includes a backplane connector component that takes the form of a pin header having a base and at least a pair with sidewalls that cooperatively define a series of slots, or channels, each of which receives the mating portion of a wafer connector component. The base has a plurality of terminal receiving cavities, each of which receives a conductive terminal. The terminals have flat contact blades and compliant tails formed at opposite ends. These contact blades and tails are offset from each other and the cavities are configured to receive them. In the preferred embodiment, the cavities are shown as having an H-shape with each of the legs of the H-shaped cavities receiving one of the terminals and the interconnecting arm of the H-shaped cavity remaining open to define an air channel between the two terminals. Such an air channel is present between pairs of terminals in each row of terminals in the horizontal direction to effect broadside coupling between the pairs of terminals.

In another principal aspect of the present invention, a plurality of wafer connector components are provided that mate with the backplane header. Each such wafer connector component includes a plurality of conductive terminals that are arranged in two vertical columns (when viewed from the mating end thereof), and the two columns defining a plurality of horizontal rows of terminals, each row including a pair of terminals, and preferably a pair of differential signal terminals. The terminals in each of the wafer connector component rows are aligned broadside together so that capacitive coupling may occur between the pairs in a

broadside manner. In order to regulate the impedance of each pair of terminals, each wafer connector component includes a structure that defines an internal cavity, and this internal cavity is interposed between the columns of terminals so that an air channel is present between each of the pairs of terminals in each wafer connector component.

In another principal aspect of the present invention, the contact portions of the wafer connector component terminals extend forwardly of the wafer and are formed as bifurcated contacts that have a cantilevered contact beam structure. An insulative housing, or cover member, may be provided for each wafer connector component and in such an instance, the housing engages the mating end of each wafer connector component in order to house and protect the contact beams. Alternatively, the cover member may be formed as a large cover member that accommodates a plurality of wafer connector elements.

In the preferred embodiment of the invention, these housings or cover members have a U-shape with the legs of the U-shape engaging opposing top and bottom edges of the wafer connector component and the base of the U-shape providing a protective shroud to the contact beams. The base (of face, depending on the point of view) of the U has a series of I or H-shaped openings formed therein that are aligned with the contact portions of the terminals and these openings define individual air channels between the contact beams so that the dielectric constant of air may be used for broadside coupling between the terminal pairs through substantially the entire path of the terminals through the wafer connector component.

In yet another embodiment of the present invention, each of the halves that form a connector wafer element include a plurality of what we call "castellations," which take the form of channels, or recesses, that are disposed between the edges of terminal in each row of terminals. These castellations have been found to focus the intensity of the differential pair coupling energy in the are between pairs of terminals in each of the facing rows of terminals. This is done by providing an air spacing between the edges of the terminals, which thereby minimizes edge coupling in the connector.

These and other objects, features and advantages of the present invention will be clearly understood through a consideration of the following detailed description.

Brief Description of the Drawings

In the course of this detailed description, the reference will be frequently made to the attached drawings in which:

FIG. 1 is a perspective view of a backplane connector assembly constructed in

accordance with the principles of the present invention and shown in a conventional right-angle orientation to join the electrical circuits on two circuit boards together;

FIG. 2 is a perspective view of two backplane connectors of the present invention used in an orthogonal orientation to join circuits on two circuit boards together;

FIG. 3 is a perspective view of the backplane connector component of the backplane connector assembly of FIG. 1;

FIG. 4 is an end view of FIG. 3 taken along the line 4-4;

FIG. 4A is a perspective view of a series of terminals used in the backplane connector member of FIG. 4 and shown attached to a carrier strip to illustrate a manner in which they are formed;

FIG. 4B is a an end view of one of the terminals of FIG. 4A, illustrating the offset configuration of the terminal;

FIG. 5 is a top plan view of the backplane connector component in place on a circuit board and illustrating the tail via pattern used for such a component;

FIG. 5A is an enlarged plan view of a portion of the backplane member of FIG. 5, illustrating the terminals in place within the terminal-receiving cavities thereof;

FIG. 5B is the same plan view of the backplane member of FIG. 5, but with the terminal-receiving cavities thereof empty;

FIG. 5C is an enlarged plan view of a portion of FIG. 5B, illustrating the empty terminal-receiving cavities in greater detail;

FIG. 5D is a an enlarged detail sectional view of a portion of the backplane member illustrating two terminals of the type shown in FIG 4A in place therein;

FIG. 6 is a perspective view of a stamped lead frame illustrating the two arrays of terminals that will be housed in a single wafer connector component;

FIG. 7 is an elevational view of the lead frame of FIG. 6, taken from the opposite side thereof and showing the wafer halves formed over the terminals;

FIG. 7A is the same view of FIG. 7, but in a perspective view;

FIG. 8 is a perspective view of FIG. 7 but taken from the opposite side thereof;

FIG. 9 is a perspective view of the two wafer halves of FIG. 8, assembled together to form a single wafer connector;

FIG. 10 is a perspective view of a cover member used with the wafer connector of FIG. 9;

FIG. 10A is the same view as FIG. 9, but taken from the opposite side and illustrating

the interior of the cover member;

FIG. 10B is a front elevational view of the cover member of FIG. 10, illustrating the I-shaped channels of the mating face thereof;

FIG. 11 is the same view as FIG. 9, but with the cover member in place to form a completed wafer connector component;

FIG. 11A is a sectional view of the wafer connector component FIG. 11, taken from the opposite side and along lines A-A of FIG. 11, with a portion of the cover member removed for clarity;

FIG. 11B is the same perspective view as FIG. 11, taken from the opposite side and sectioned along lines B-B of FIG. 11, illustrating how the terminal contact portions are contained within the interior cavities of the cover member;;

FIG. 12 is a sectional view of the wafer connector component of FIG. 11, taken along the vertical line 12-12 thereof;

FIG. 13A is a partial sectional view of the wafer connector component of FIG. 11, taken along the angled line 13-13 thereof;

FIG. 13B is the same view as FIG. 13A, but taken directly from the front of the section shown in FIG. 13A;

FIG. 14 is a sectional view of the wafer connector component of FIG. 11, taken along vertical line 14-14 thereof;

FIG. 15 is a perspective view, partly in section of a wafer connector component and backplane member mated together;

FIG. 16 is an end diagrammatic view of the wafer connector component and backplane member mated together with the cover member removed for clarity to illustrate the manner of mating with connectors of the present invention;

FIG. 17 is a similar view to FIG. 16, but with the wafer connector component terminals being supported by their respective connector component supports;

FIG. 18A is an enlarged sectional detail view of the mating interface between the wafer connector component and the backplane member, and showing the component and member;

FIG. 18B is the same view as FIG. 18A, but with the wafer connector component removed from clarity;

FIG. 19 is an angled end sectional view of three wafer connector components in place upon a circuit board, illustrating the air gaps between adjacent signal pairs and the air gap between adjacent wafer connector components;

FIG. 20 is a perspective view of an alternate embodiment of a connector element constructed in accordance with the principles of the present invention;

FIG. 21 is the same view as FIG. 20, but with the connector element split apart into its component halves to illustrate one interior face thereof;

FIG. 22 is the same view as FIG. 20, but vertically sectioned to illustrate the structure of the castellations of the connector element halves; and,

FIG. 23 is an elevational end view of the sectioned front end of the connector element of FIG. 22.

Detailed Description of the Preferred Embodiments

FIG. 1 illustrates a backplane connector assembly 50 constructed in accordance with the principles of the present invention. The assembly 50 is used to join together two circuit boards 52, 54 with the circuit board 52 representing a backplane and the circuit board 54 representing an ancillary, or daughter board.

The assembly 50 can be seen to include two interengaging, or mating, components 100 and 200. One component 100 is mounted to the backplane board 52 and is a backplane member that takes the form of a pin header. In this regard, the backplane member 100, as illustrated best in FIGS. 1 and 3, includes a base portion 102 with two sidewalls 104, 106 rising up from the base portion 102. These two sidewalls 104, 106 serve to define a series of channels, or slots 108, each slot of which receives a single wafer connector component 202. In order to facilitate the proper orientation of the wafer connector components 202 within the backplane connector component, the sidewalls 104, 106 are preferably formed with interior grooves 110 that are vertically oriented and each such groove 110 is aligned with two rows **R1**, **R2** of conductive terminals 120. (FIG. 3.)

As shown in FIG. 4B, the header terminals 120 are formed in an offset manner so that their contact portions 121, which take the form of long, flat blades 122 extend in one plane **P1**, while thin tail portions 123, shown as compliant pin-style tails 124 extend in another plane **P2**, that is spaced apart from the first plane **P1**. The terminals 120 each include a body portion 126 that is received within a corresponding terminal-recovery cavity 111 that is formed in the base portion 102 of the backplane member 100. FIG. 4A illustrates the terminals 120 in one stage as they are stamped and formed along a carrier strip 127, and it can be seen that each terminal is interconnected together not only by the carrier strip 127, but also secondary pieces 128 that hold the terminals 120 in line during their forming process. These secondary pieces 128 are removed

later in the forming process as the terminals 120 are removed, or singulated and then are inserted into the base 102 of the backplane member 100, such as by stitching.

The contact blade portions 122 of the terminals 120 and their associated body portions 126 may include ribs 130 that are stamped therein and which preferably extend through the offset bends of the terminals 120. These ribs 130 serve to strengthen the terminals 120 by providing a cross-section to the terminals in this area which is better resistant to bending during insertion of the terminals 120 as well as mating with the terminals 206 of an opposing wafer connector component 202. Dimples 131 may also be formed in the terminal body portion 126 and in a manner such they project out to one side of each terminal 120 (FIG. 4B) and form a projection that will preferably interferingly contact one of the sidewalls of the terminal-receiving cavities 111 in the backplane member base portion 102. As illustrated in FIG. 5D, the backplane member base portion 102 may include a series of slots 132 formed which extend vertically and which will receive the terminal dimples 131 therein. The terminal-receiving cavities 111 are also preferably formed with interior shoulders, or ledges 134, which are best shown in FIG. 5D and which provide a surface against which the terminal body portions 126 rest.

As shown in FIG. 4A, the header terminals 120 preferably have their tail portions 123 offset as well. As shown, this offset occurs laterally of the terminals 120, so that the centerlines of the tail portions 123 are offset from the centerlines of the contact portions 121 by a distance P4. This offset permits, as clearly shown in FIG. 5, pairs of header terminal 120 to face each other and utilize the 45-degree orientation of vias shown in the right half of FIG. 5. As can be determined from FIG. 5, the compliant pin tail of one of the two rows R1 can use the bottom left via, while the compliant pin tail of the facing terminal can take the next via in the right row, and then with the pattern repeated for each pair, the vias of the header terminals, within each two rows are at 45 degree angles to each other, as shown diagrammatically to the right of FIG. 5. This facilitates the route out for such connectors on the circuit boards to which they are mounted.

As seen best in FIGS. 5A & 5C, the terminal-receiving cavities 111 of the backplane member 100 of the connectors of the invention are unique in that they are generally H-shaped, with each H-shape having two leg portions 112 that are interconnected by an arm portion 113. While the leg portions 112 of the H-shaped cavities 111 are filled with the body portions 126 of the terminals 120, the arm portions 113 of each cavity 111 remain open so that an air channel "AC" is defined in the arm portion 113 (FIG. 5A), the purpose of which will be explained in

greater detail below. The spacing that results between the two terminal contact portions 122 is selected to match the approximate spacing between the two contact portions 216 of the wafer connector component terminals 206 that are received within the backplane member channels 110.

The H-shaped cavities 111 also preferably include angled edges 140, that define lead-in surfaces of the cavities 111 that facilitate the insertion of the terminals 120 therein, especially from the top side of the connector base 102. The cavities 111 include tail holes 114 that, as shown in FIG. 5A, are located at angled, opposite corners of each H-shaped opening 111. The contact blade portions 122 of the terminals 120, are located above and slightly outboard of the leg portions 112 of the H-shaped cavities 111. This is due to the offset form present in their body portions 126, and this is best shown in a comparison between FIGS. 5A and 5B. FIG. 5B illustrates in an enlarged detail plan view, the backplane member base portion 102 without any terminals 120 present in the terminal-receiving cavities 111, while FIG. 5A illustrates, also in an enlarged top plan view, the terminal-receiving cavities 111 being filled with the terminals 120. In FIG. 5A, one can see that the contact blade portions extend outwardly into the areas between the rows of terminals so that the outer surfaces 124 thereof are offset from the outermost inner edges 141 of the base member terminal-receiving cavities 111..

FIG. 6 illustrates a metal lead frame 204 which supports a plurality of conductive terminals 206 that have been stamped and formed in preparation for subsequent molding and singulation. The lead frame 204 shown supports two sets of terminals 206, each set of which is incorporated into an insulative support half 220a, 220b, which are subsequently combined to form a single wafer connector component 202. The terminals 206 are formed as part of the lead frame 204 and are held in place within an outer carrier strip 207 and the terminals are supported as a set within the lead frame 204 by first support pieces, shown as bars 205, that interconnect the terminals to the lead frame 204 and also by second support pieces 208 that interconnect the terminals together. These support pieces are removed, or singulated, from the terminal sets during assembly of the wafer connector components 202.

FIG. 7 illustrates the lead frame 204 with the support, or wafer halves 220a, 220b molded over portions of the set of eleven individual terminals 206. In this stage, the terminals 206 are still maintained in a spacing within the support halves by the support halve material and by the second interconnecting pieces 208, 209 that are later removed so that each terminal stands 206 by itself within the completed wafer connector component 202 and is not connected to any other terminal. These pieces 208, 209 are arranged outside of the edges of the body

portions of the wafer connector component halves 220a, 220b. The support halves 220a, 220b are symmetric and are aptly described as mirror images of each other.

FIG. 7A illustrates best the structure which is used to connect the two wafer halves 220a, 220b together, which are shown as complimentary relatively large-shaped posts 222 and openings, or holes 224. One large post 222 and large opening 224 are shown in FIG. 7A and they are positioned within the body portion 238 of the connector component halves 220a, 220b. Three such posts 220 & 226 are shown as formed in the body portions of the wafer connector halves 220a, 220b and the other posts 230, as shown, are much smaller in size, and are positioned between selected terminals and are shown extending out of the plane of the body portion 220b. These posts 230 extend from what may be considered as standoff portions 232 that are formed during the insert molding process, and the standoff portions 232 serve to assist in the spacing between terminals within each wafer half and also serve to space the terminals apart in their respective rows when the halves are assembled together.

These smaller posts are respectively received within corresponding openings 231, which similar, to the posts 230, are preferably formed as part of selected ones of the standoff portions 232. In an important aspect of the present invention, no housing material is provided to cover the inner faces of the terminal sets so that when the wafer connector components are assembled together, the inner vertical sides, or surfaces 247 of each pair of terminals 206 are exposed to each other. The posts and openings 230, 231 and the standoff portions 232 are cooperate in defining an internal cavity within each wafer connector component 202, and this cavity 237 is best seen in the sectional views of FIGS. 12 & 14.

FIG. 8 shows the opposite, or outer sides, of the wafer connector components and it can be seen that the wafer connector components halves 220a, 220b form what may be aptly described as a skeletal framework that utilizes structure in the form of cross braces 240 and interstitial filler pieces, or ribs 242, that extend between adjacent terminals in the vertical direction, and which preferably contact only the top and bottom edges of adjacent terminals. In this manner, the exterior surfaces 248 of the terminals (FIG. 9) are also exposed to air, as are the inner surfaces 247 of the terminals 206. These filler ribs 242 are typically formed from the same material from which the wafer connector component body portions 238 are made and this material is a preferably a dielectric material. The use of a dielectric material will deter significant capacitive coupling from occurring between the top and bottom edges 280, 281 of the terminals (FIG. 14), while driving the coupling that does occur, to occur in a broadside manner between pairs of terminals arranged horizontally.

FIG. 9 illustrates a completed wafer connector component that has been assembled from two halves. The terminals of this wafer connector component have contact and tail portions arranged along two edges and in the embodiment shown, the edges may be considered as intersecting or perpendicular to each other. It will be understood that the edges could be parallel or spaced apart from each other as might be used in an interposer-style application. The first set of contact portions 216 are the dual beam contact portions 217a, 217b that are received in the central portion of the backplane member 100 of the assembly, while the second set of contact portions 214 serve as tail portions and as such, utilize compliant pin structures 215 so that they may be removably inserted into openings, or vias, of circuit boards. The contact portions 216 of the wafer connector component 202 are formed as dual beams 217 and they extend forwardly of a body portion of each terminal. The ends of the terminal contact portions 216 are formed into curved contact ends 219 that are at the ends of the bodies 218 of the contact beams. These curved ends 219 face outwardly so that they will ride upon and contact the flat blade contacts 122 of the backplane member terminals 120. (FIG. 18A.)

When assembled together as a unit of wafers, there is present not only the air channel 133 between the terminals 206 within each wafer connector component 202, but also an air spacing 300 between adjacent wafer connector components, as shown in FIG. 19. The terminals are preferably spaced apart a first preselected distance ST uniformly through out the connector assembly, which defines the dimension of the air channel . This spacing is between designated pairs of terminals in each of the connector elements and this spacing is the same on an edge-to-edge basis within each connector element. Preferably, the spacing SC between connector elements, is greater than the spacing ST. (FIGS. 19 & 20.) This spacing helps create isolation between wafer connector elements.

A cover member 250 is utilized to protect the dual beam contacts 217a, 217b and such a cover member 250 is shown in FIGS. 10 through 11 as one of a construction that covers the front end of only a single wafer connector element. The cover member 250 is shown in place upon the wafer connector component 202 in FIG. 11, and it serves as a protective shroud for the dual beam contacts 217a, 217b. The cover member 250 is preferably molded from an insulative material, such as a plastic that also may be chosen for a specific dielectric property. The cover member 250 has an elongated body portion 251 that extends vertically when applied to the wafer connector component 202 and the body portion 251 includes spaced-apart top and bottom engagement arms 252, 253. In this manner, the cover member 250 has a general U-shape when viewed from the side, and as illustrated in FIG. 10, it generally fits over the contact portions 216

of the terminals 206 of the wafer connector components 202, while the arms 252, 253 engage the wafer connector component 202 and serve to hold it in place.

The cover member 250 is formed with a plurality of cavities, or openings 254, and these are shown best in FIGS. 10 and 10B. The cavities 254 are aligned which each other in side-by-side order so that they accommodate a horizontal pair of terminal contact portions 216 of the wafer connector component 202. The cover member 250 may also include various angled surfaces 258 that serve as lead ins for the terminals 120 of the backplane member 100. As shown best in FIG. 10B, each such cavity 254 has a general H-shape, with the dual beam contacts 216 being received in the leg portions 256 of the H-shape. The leg portion openings 256 are interconnected together by intervening arm portions 257 of the H-shape, and these arm portions 257 are free of any terminal or wafer material so that each one acts as an air channel AC that extends between opposing surfaces of the dual beam contacts 217. As is the case with the backplane member H-shaped cavities 111, the cavities 254 of the cover member 250 also permit broadside coupling between the terminal contact portions 216 of the wafer connector component. FIG. 10C illustrates a cover member 2050 that is wider than just a single connector wafer element as in FIGS. 10-10B. This cover member 2050 includes internal channels 2620 formed in the interior surfaces of the end walls 2520, 2530 which extend between the side walls 2510 thereof. The cover member 2050 includes the H-shaped openings 2540 and angled lead-in surfaces in the same fashion as those shown and described for the cover member 250 to follow.

In this manner, the air channel AC that is present between horizontal pair of terminals 206 (and which is shown in FIG. 12) of the wafer connector component 202 is maintained through the entire mating interface from the connector element tail portions mounted to the circuit board, through the wafer connector component, and into and through the backplane or header connector. It will be appreciated that the air channels 257 of the cover member cavities 254 are preferably aligned with the air channels 113 of the backplane member cavities 111.

As shown in FIG. 10, the cover member 250 may include a pair of channels 262, 263 that are disposed on opposite sides of a central rib 264 and which run for the length of the cover member 250. These channels 262, 263 engage and receive lugs 264 that are disposed along the top edge of the wafer connector component 202. The cover member arms 252, 253 also may contain a central slot 275 into which extends a retaining hook 276 that rises up from the top and bottom edges 234, 235 of the wafer connector component. The manner of engagement is illustrated in FIG. 11B and the cover member arms 252, 253 may be snapped into engagement or easily pried free of their engagement with the wafer connector component 202.

FIG. 12 illustrates the mating interface between the two connector components and it can be seen that the forward portion of the cover members 250 fit into the channels 110 of the backplane member 100. In doing so, the blade contact portions 122 of the backplane member terminals 120 will enter the cover member cavities 254 and the distal tips, i.e. the curved ends 219, of the dual beam contacts 217 will engage the inner surfaces 125 of the pairs of backplane member terminals 120. The backplane member terminal blade contact portions will then flex slightly outwardly against the inner walls of the cover member 250 and this contact ensures that the contact blades 122 will not deflect excessively. Additionally, the cover member 250 includes central walls 259 that flank the center air channel slots 257 and these walls 259 are angled and their angled surfaces meet with and contact the offset which is present in the backplane member terminal body portions 126. The ribs 130 of the terminal body portions 126 of the backplane member terminals 120 may be aligned with the air channel slots 257.

FIG. 13 illustrates how the compliant portions 215 of the wafer connector component connector terminal tail portions 214 are spaced further apart in the tail area than in the body of the wafer connector component 202. The tail portions 214 are offset and the space between adjacent pairs of tails is left empty and is therefore filled with air. No wafer material extends between the pairs of terminal tails 214 so that the air gap that is present in the body of the wafer connector components is maintained at the mounting interface to the circuit board.

The terminal tails 214 are also offset in their alignment and this offset only encompasses the compliant tail portions 215. The legs of the H-shaped cavities 111 can be seen in FIG. 5A as including a slight offset. This is so that the terminals 120 need be only of one shape and size, and one row may be turned 180 degrees from the other row of terminals and inserted into the cavities 111. The body portions 126 and the blade contact portions 122 are not offset so the offset of the leg portions 126 of the terminal-receiving cavities 111 ensures that the flat contact blade and the (offset parts of the) body portions are aligned with each other to maintain coupling. Secondly, the tails are then offset from each other by about 45 degrees. This permits the use of a favorable via pattern on the mounting circuit board and permits the connector assembly to be used in orthogonal midplane applications, such as is shown in FIG. 2. [0079] FIGS. 20-23 illustrate another embodiment 400 of the present invention. The connector element 400 is shown assembled together in FIG. 20 from two interengaging half portions 401, 402. As with the previous connector elements, the connector element 400 supports a plurality of conductive terminals 420 and the element 400 herein has a plurality of edges, and two of these edges 404, 405 can be seen to extend at an angle to each other, and preferably intersect each

other. The terminals 420 have contact portions 421 and tail portions 422, and these are arranged in order, respectively along the edges 405, 404. As seen best in FIG. 21, the contact and tail portions 421, 422 are interconnected by extending body portions 423.

The terminals 420 of each connector element 400 are supported in single rows by each of the connector element halves 401, 402. That is, one row of terminals is arranged on and supported by the right connector half 402, while the other row of terminals is arranged on and supported by the left connector half 401. A plurality of standoff portions 425 are formed in the connector element halves, and these standoff portions serve to space the two rows of terminals apart from each other in a predetermined spacing, ST between the broadsides of the two terminals in each row. This spacing ST is shown best in FIG. 23 and the same spacing is preferably used to space the terminals in each row apart from each other in an edge spacing. As shown in FIG. 23, the broadside spacing ST between pairs of terminals of each row is a horizontal spacing and the edge spacing ST between terminals within a single row is a vertical spacing. Some of the standoff portions 425 include posts (not shown) and holes 426 that receive the posts in order to hold the two halves together as a single connector element 400.

A series of slots 430 are formed in the sidewalls 431 of the connector element halves 401, 402. These slots expose the outer sides of the terminals to air and the open to the spacing between terminals of adjacent connector elements. The standoff portions 425 ensure that in the interior of the connector elements 400, the terminals of each row are spaced apart from each other in horizontal pairs as shown by the exposed sectional face of FIG. 23. This provides the aforementioned air channels between pairs of associated terminals as discussed with the earlier embodiments of the invention. These air channels permit broadside capacitive coupling to occur between the pairs of terminals, and the larger spacing between connector elements tends to isolate the two rows of terminal supported by each connector element.

The connector element halves 401, 402 of this embodiment also include what we call "castellations" 440, which are recesses that are formed in the sidewalls 431 of the connector elements 400 along the inner faces thereof. They can be seen best in FIGS. 22 and 23. These castellations occur between the edges of adjacent terminals in each row (or vertically as shown in FIGS. 22 & 23) and they can be considered as having the form of channels, or recesses, that are disposed between the edges of terminal in each row of terminals. The ones shown in the Figures are generally semi-circular in configuration, but they can also be rectangular, square or angled in configuration. These castellations have been found to focus the intensity of the differential pair coupling energy in the are between pairs of terminals in each of the facing rows

of terminals. This is done by providing an air spacing between the edges of the terminals, which thereby minimizes edge coupling in the connector. In this embodiment, not only is there an air channel between the broadsides of pairs of associated terminals, such as a pair of terminals which are intended to carry differential signals, but there is also an air channel that extends between edges of the terminals in each single row. This has been found to isolate the intended pairs of terminals in the two rows of each connector element and focuses the intensity of the broadside coupling while decreasing the strength of any edge coupling which may occur.

While the preferred embodiment of the invention have been shown and described, it will be apparent to those skilled in the art that changes and modifications may be made therein without departing from the spirit of the invention, the scope of which is defined by the appended claims.

CLAIMS :

1. A connector comprising: a plurality of wafer-style components, each such component including an insulative support body, each support body supporting two columns of conductive terminals, each of said support bodies further including an internal cavity disposed between the two columns of conductive terminals to define air channels between pairs of associated terminals of the two terminal columns, the pairs of terminals being aligned with each other so that side surfaces of the terminals of each pair face each other to thereby promote broadside capacitive coupling therebetween, said support bodies further including castellations formed therein and arranged between edges of adjacent terminals in order to provide electrical isolation of adjacent pairs of terminals.

2. The connector of claim 1, wherein said support body includes a pair of body halves that are joined together, each of the body halves including a plurality of standoff portions disposed between said terminals.

3. The connector of claim 2, wherein some of said standoff portions include post members projecting therefrom and opposing standoff portions include openings extending inwardly thereof, the openings receiving the post members when said the support body halves are joined together.

4. The connector of claim 1, wherein said terminal include tail portions extending out from said support body along a first edge thereof and contact portions extending out from said support body along a second edge thereof.

5. The connector of claim 4, wherein said air channels extend through said support body between pairs of associated terminals from said first edge to said second edge.

6. The connector of claim 1, further including a cover member that receives front faces of said support bodies therein.

7. The connector of claim 6, wherein said terminals include contact portions that are received within said cover member, the terminal contact portions each including a pair of contact arms extending out from said support bodies, said cover member further

including a plurality of H-shaped openings, two pairs contact arms being aligned with each of the H-shaped openings such that a contact arm is disposed in each of four corners of said H-shaped openings.

8. A connector, comprising:

a plurality of connector elements arranged in side by side order;
each of the connector elements supporting two columns of conductive terminals, the two columns of terminals cooperatively defining a plurality of pairs of the associated terminals, the terminals of each pair being spaced apart from each other within said connector elements by respective air channels extending through said connector elements, interior surfaces of said connector elements including a plurality of castellations disposed between said terminals in said columns.

9. The connector of claim 8, wherein said castellations have a partial semi-circular configuration.

10. The connector of claim 8, wherein said castellations extend between edges of said connector elements along which contact and tail portions of said terminal extend.

11. The connector of claim 8, wherein each of said terminals includes a contact portion and a tail portion that are interconnected together by a body portion.

12. The connector of claim 11, wherein said castellations are disposed in said connector elements alongside said terminal body portions.

13. The connector of claim 11, wherein said contact portions include pairs of contact arms.

14. The connector of claim 8, further including a plurality of standoff portions that are interposed between the terminals in each column.

15. The connector of claim 14, wherein said standoff portions space terminals of one column apart from associated terminals in a second column of each of said connector elements.

16. The connector of claim 15, wherein some of said standoff portions include projecting posts which are received in openings disposed in opposing standoff portions.

17. The connector of claim 11, wherein said terminal tail portions include compliant pin portions.

18. The connector of claim 17, wherein said compliant pin portions are offset from said terminal body portions along an edge of said connector element.