[CLAIMS]

1. ~~(Amended)~~ A laminated core comprising a plurality of electrical steel sheets stacked in a thickness direction,

wherein the electrical steel sheet includes an annular core back part and a plurality of tooth parts that protrude from the core back part in a radial direction and are disposed at intervals in a circumferential direction of the core back part,

wherein a fastening part is provided in a portion of the core back part corresponding to the tooth part,

wherein an adhesion part is provided in the tooth part; and

wherein the tooth parts have first tooth part in which the adhesion part is provided and second tooth part in which the adhesion part is not provided.

~~2. (Deleted)~~

~~3~~2. ~~(Amended)~~ The laminated core according to claim 1, wherein the first tooth parts and the second tooth parts are disposed alternately in the circumferential direction.

~~4~~3. ~~(Amended)~~ The laminated core according to claim ~~3~~2, wherein the fastening part is provided in the core back part corresponding to the first tooth part.

~~5~~4. ~~(Amended)~~ The laminated core according to claim ~~3~~2, wherein the fastening part is provided in the core back part corresponding to the second tooth part.

~~6~~5. ~~(Amended)~~ The laminated core according to any one of claims 1 to 4~~and 3 to 5~~,

wherein an average thickness of the adhesion parts is 1.0 μm to 3.0 μm.

~~7~~6. ~~(Amended)~~ The laminated core according to any one of claims 1 to 5~~and 3 to 6~~, wherein an average tensile modulus of elasticity E of the adhesion parts is 1500 MPa to 4500 MPa.

~~8~~7. ~~(Amended)~~ The laminated core according to any one of claims 1 to 6~~and 3 to 7~~, wherein the adhesion part is a room temperature adhesion type acrylic-based adhesive including SGA made of an elastomer-containing acrylic-based adhesive.

~~9~~8. ~~(Amended)~~ An electric motor comprising the laminated core according to any one of claims 1 to 7~~and 3 to 8~~.