FIRE SUPPRESSION SYSTEM AND EMERGENCY ANNUNCIATION SYSTEM

REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of U.S. Provisional Application No. 60/904,551, filed March 2, 2007, the entirety of which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Technical Field.

[0002] The present invention relates to a fire suppression system activated manually (such as by a pull knob or electronically) or activated automatically (such as by the detection links in the detection line).

2. Related Art.

[0003] Fire suppression systems may be activated using a pull knob. The pull knob may be located in the path of egress or near an operator of a machine, such as an oven, popcorn machine, etc., and may be used to activate the fire suppression system. In the event of a fire, the operator may pull the pull knob, thereby activating a release mechanism of the fire suppression system.

[0004] The release mechanism may indirectly or directly cause the fire suppression agent to be dispensed, thereby reducing or eliminate the fire. For example, Fig. 1 illustrates a fire suppression system **100** that using a pull handle **116** to activate a release mechanism **160**. Specifically, the wire rope **140** may be connected between pull handle **116** and an oval sleeve **170** of the cable lever **190** of release mechanism **160**. The oval sleeve **170** may be used to make a loop in the rope so that the connection is between the pull handle **116** and cable lever **190** of the release mechanism **160**. The pull handle **116** may be part of a pull station **110**, that includes a faceplate **114** and pull knob body **118**, and is located in an area remote from hot oil kitchen apparatuses, such as oil fryer ovens. The color of the faceplate **114** is a brushed stainless color in order to blend with the kitchen apparatuses, etc. In the event of a flash fire on the hot oil surface, the operator may pull the pull handle **116**, thereby activating the release mechanism **160** located within the system pressurizing control cabinet **162**. The release mechanism **160** thereafter indirectly causes release of the fire suppression agent by creating a pressure surge into a container of fire suppression agent, such as foam or flame retardant material, which in turn causes a release of the fire suppression agent onto the flaming oil through permanently placed spray nozzles, and thus reducing or extinguishing the fire. Alternatively, the release mechanism may directly cause release of the fire suppression agent, such as the pull handle **116** activating a triggering release mechanism coupled directly to a fire suppression agent container such as a water container or such as a CO_2 fire extinguisher. Upon activation, water may be dispensed. Or, the CO_2 fire extinguisher (or other extinguishing agent) may discharge CO_2 (or nitrogen cartridges) to cause the pressurization of the agent, thereby expelling the agent through a fixed piping system into the containment area to eliminate the fire supporting O_2 and thus minimizing or extinguishing the fire. Alternatively, CO_2 may be used as the extinguishing agent

[0005] The pull handle in the fire suppression system is coupled to the release mechanism. One way to couple the pull handle **116** to the release mechanism **160** is by using a rigid conduit mechanical system,

such as shown in Fig. 1. A wire rope **140** is routed from the system pressurizing control cabinet **162** to the pull station **110** through rigid electrical mechanical tubing (EMT) **130** and making 90 degree turns through pulley elbows **150**. Further, the rigid EMT **130** is connected to a junction box **120** via a conduit-to-junction box coupling **131** to the pull station **110**. However, using rigid EMT tubing **130** and 90 degree elbows **150** is very labor intensive, expensive and not preferable to some building wall geometries and accesses.

[0006] Another way to couple the pull handle to the release mechanism is to route the wire rope **140** through an outer diameter (OD) (such as a ¼" diameter) pre-shaped rigid conduit tubing. The pre-shaped rigid conduit tubing is commonly used in situations like the popcorn machine because designs and component dimensions are known and fixed. The pre-shaped rigid tubing may be constructed using aluminum or stainless steel for example, to ensure that in the event of a fire, the wire rope **140** routing conduit is non-flammable and will function as designed under high heat conditions. Because the pre-shaped rigid conduit tubing does not include pulley elbows **150**, the wire rope **140** encounters high friction, making pulling of the pull handle difficult.

[0007] Still another way to couple the pull handle to the release mechanism is to route the wire rope along a predetermined path (length and direction) defined by specific pulley systems located at each change in wire rope direction. Disadvantages to this method include the excess cost associated with the pulley system along with the lack of controlled routing. A simple loss of wire rope tension might result in the wire rope "jumping its pulley" and thus a complete failure of the wire rope system.

[0008] Yet another way to couple the pull handle to the release mechanism is by using a pneumatic system. The pull handle may trigger a change is gas pressure, thereby activating the release mechanism. While the pneumatic system may be easier to configure than the systems using the electrical EMT tubing **130** and the 90 degree pulley elbows **150** shown in Fig. 1 or the pre-shaped rigid conduit tubing, it is typically less reliable. Therefore, what is needed is an easily configurable and reliable system for activating a release mechanism of a fire suppression using a pull handle.

[0009] As discussed above, the pull handle **116** is part of a pull station **110**. An example of a pull station **110** is illustrated in Figs. 2, 3 and 4A-C. Configuration of the pull station **110** may include installing a break rod **112**, as shown in Figs. 4A-C. The break rod **112** is slid through break rod end bushings **113** until a set-screw end bushing **119** is screwed into break rod end bushing **113**. However, sliding the break rod **112** into the break rod end bushings **113** may prove difficult. Further, pulling the pull handle **116** from the pull knob bushing **125** after installation of the break rod **112** may also prove difficult. The pull station **110** is illustrated in cross-section with the pull handle **116** connected (Fig. 2) and disconnected (Fig. 3). Due to the design, excess force is required when pulling in direction **134** to overcome the friction forces resulting from cable friction at friction points such as **132** and **133** shown in Fig. 2 and 3. What is therefore needed is a pull station that is easier to configure and to activate.

SUMMARY OF THE INVENTION

[0010] A fire suppression system and/or an emergency annunciation system using a flexible conduit and a wire rope is provided. The flexible conduit and wire rope may be used in a fire suppression system, an emergency annunciation system, or a combination of a fire suppression and emergency annunciation system. The wire rope may be connected to a lever or handle at a pull station and to a release mechanism of the fire suppression system. An operator may pull the lever at the pull station, thereby activating the release mechanism to release, either directly or indirectly, fire suppression agent. A flexible conduit may be used to house the wire rope along at least a part of the connection from the pull station to the release mechanism. The flexible conduit may be used to route the wire rope in non-standard configurations between the remote pull station and the release mechanism, such as a local system pressurizing control cabinet. Alternatively, the wire rope may be connected to a lever or handle at a pull station and to a switch for a fire annunciator system. The operator may pull the lever at the pull station, thereby controlling the switch for the annunciator system to visually or aurally indicate a chemical leak or the like (such as by activating strobes, horns, speakers, or the like with a predetermined output).

[0011] A material on the interior of the flexible conduit and/or on the wire rope may be used to reduce the coefficient of friction of wire rope in the flexible conduit. The material may comprise a liner of the flexible conduit whereby the wire rope is disposed to slide axially within the liner of the flexible conduit. The liner may be composed of a flexible material, such as plastic, with a low coefficient of friction. The material may also comprise a lubricant, such as a liquid lubricant. The lubricant may be applied to the interior of the flexible conduit, such as the interior of the liner, and/or applied to the wire rope. With the lower coefficient of friction, a lower level of force may be necessary to pull the lever at the pull station in order to activate the release mechanism of the fire suppression system.

[0012] The fire suppression system may include a pull station that is configured to allow for easier installation, such as break rod installation without the use of tools and break rod installation in wall areas where there is space limitations. One of, or both, of the faceplate and the pull knob assembly (which may include a pull knob and/ pull handle) may be rotated, such as up to rotated 90 degrees (either clockwise or counterclockwise) or rotated greater than 90 degrees, to facilitation break rod installation. In particular, installation of the break rod may occur when the pull knob is inserted into the faceplate and rotated approximately 90 degrees clockwise from its normal position (with the faceplate stationary). Rotation of the pull knob/break rod assembly in a rotational direction 90 degrees counter clockwise back into its normal position may then cause the break rod ends to engage into and then become fully seated in the corresponding slots contained within each sidewall protective barrier. Further, the break rod installation may be accomplished without the use of tools.

[0013] The faceplate may contain one or more mounting screw bosses, each with integral containment boundary diaphragms to prevent grease, dirt or grime from entering behind the pull station. These screw bosses may be located to correspond with the associated screw bosses found on electrical junction boxes

(such as shallow or deep electrical junction boxes). The containment boundary diaphragm holes aligned with the electrical junction box mounting screw bosses may be punched out to enable the faceplate to be screw mounted to the electrical junction box. Removal of the containment boundary diaphragms thus may enable an assembly screw to be inserted through the hole and momentarily captured in that hole to enable positioning of the faceplate over the electrical junction box without the screws falling from the holes. The faceplate may further include one or more indicia that is a color or texture that is different from another portion of the faceplate (such as a contrasting color indicia). For example, one or more of the words that are on the faceplate may be red, fluorescent, or glow in the dark in order to differentiate the words (and the faceplate) from the surroundings (such as an aluminum background).

[0014] The pull station faceplate may also include functional standing protective barriers that may protect the pull knob and pull handle from side impact and may provide a protective and functional means to capture the ends of the break rod when the pull knob is installed and ready to be activated. Further, the faceplate may include storage for maintenance components. The maintenance components may include maintenance parts such as spare break rods or copper compression fittings.

[0015] The faceplate of the pull station may be integrated with a pulley block system. The pulley block system may securely engage into and with corresponding features of the faceplate. For example, the pulley block system may be press fitted into the faceplate of the pull station. The combination may create an assembly that routes the wire rope in the direction of and on centerline to the flexible conduit or to rigid conduit as it enters the electrical junction box. The faceplate and pulley block each may contain multiple and corresponding inter-engaging features to enable numerous wire rope direction routing capabilities. Specifically, the pulley block and pulley may be configured in various ways to enable the faceplate/pulley block assembly to be used on multiple electrical junction box designs such as shallow or deep boxes without a need for other assembly components. The pulley block assembly may contain cable quick-connect capturing features to enable rapid flexible conduit installation/engagement into the pull station assembly. This flexible conduit installation may be performed rapidly without tools, thereby minimizing the manpower required to field install this system.

[0016] The pull knob assembly of the pull station may be coupled to the wire rope using one or more set screws that may be directed perpendicular to the wire rope axis or may be coupled with the wire rope using a compression fitting secured at one end, both while allowing at least part of the pull knob assembly (such as the pull handle) rotational freedom to enable break rod installation all while the pull knob assembly is fully inserted into the faceplate's corresponding center boss. The pull knob assembly of the pull station may further include a snap-fit uniform cap for ease of pull knob assembly installation and ease of providing market specific labeling or culture specific language alterations without excess cost. The cap system may be labeled or colored in any fashion specific to the end user needs, all while using the standardized pull knob assembly base element.

[0017] As discussed above, a wire rope may be used to connect the pull knob assembly to the release mechanism. An auto wire rope tensioning mechanism may be used to maintain tension on some or all excess wire rope after installation. The tensioning mechanism may also maintain the pull knob assembly to be seated flush to the faceplate while it is in a ready-to-activate stance. Slight tension on the excess wire rope may enable the installation personnel the ability to test pull the wire rope through the rigid or flexible conduit without activating the system pressurizing control mechanism (provided the cartridge is not installed). The wire rope testing methodology may provide a single person the ability to validate that the field run conduit system (either using a rigid or flexible conduit) allowing free, unobstructed, movement of the wire rope without activating the system. Further, the tension of the wire rope may be maintained with a predetermined amount of force, thereby standardizing the amount of force required to pull the pull knob assembly.

[0018] Other systems, methods, features and advantages will be, or will become, apparent to one with skill in the art upon examination of the following figures and detailed description. It is intended that all such additional systems, methods, features and advantages be included within this description, be within the scope of the invention, and be protected by the following claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] The system may be better understood with reference to the following drawings and description. The components in the figures are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention. Moreover, in the figures, like referenced numerals designate corresponding parts throughout the different views.

[0020] Fig. 1 is a representation of a prior art fire suppression system using rigid conduit routing.

[0021] Fig. 2 is a cross-section of a prior art pull handle with wire rope connection.

[0022] Fig. 3 is a cross-section of a prior art pull handle with wire rope connection that has been activated.

[0023] Figs. 4A-C illustrate a prior art sequence for installing a break rod.

[0024] Fig. 5A illustrates a Bowden conduit.

[0025] Fig. 5B illustrates a braided conduit with bends.

[0026] Fig. 5C illustrates a braided conduit with exploded construction view from Fig. 5B.

[0027] Fig. 6 is a representation of the pull station and flexible cable routing.

[0028] Fig. 7A is a first cross section of the pull station with integral pulley block and cable compression connection (such as a crimp stop) in a shallow junction box.

[0029] Fig. 7B is a second cross section of the pull station with integral pulley block and cable compression connection in a shallow junction box.

[0030] Fig. 7C is a first cross section of the pull station with integral pulley block and cable compression connection in a deep junction box.

[0031] Fig. 7D is a second cross section of the pull station with integral pulley block and cable compression connection in a deep junction box.

[0032] Fig. 8A is a first cross section of the pull station with integral pulley block and cable set screw connection in a shallow junction box.

[0033] Fig. 8B is a second cross section of the pull station with integral pulley block and cable set screw connection in a shallow junction box.

[0034] Fig. 8C is a first cross section of the pull station with integral pulley block and cable set screw connection in a deep junction box.

[0035] Fig. 8D is a second cross section of the pull station with integral pulley block and cable set screw connection in a deep junction box.

[0036] Fig. 9A is an exploded view of the pull station with pulley block snap-fit.

[0037] Fig. 9B is an exploded view of the pull station with pulley block set screw fit.

[0038] Fig. 10A is an exploded view of the pulley block with groove fit features.

[0039] Fig. 10B is a front view and side view of the retaining clip and flexible conduit.

[0040] Fig. 10C is an exploded view of the pulley block with snap-fit features.

[0041] Fig. 10D is a front view of the pull station pull knob rotated relative to the faceplate.

[0042] Fig. 10E is a cross-section (E-E) from Fig. 10D.

[0043] Fig. 10F is an exploded portion (detail F) from Fig. 10E.

[0044] Fig. 10G is a front view of the pull station pull knob of the faceplate assembly not rotated.

[0045] Fig. 10H is a cross-section (G-G) from Fig. 10G.

[0046] Fig. 10I is an exploded portion (detail H) from Fig. 10H.

[0047] Fig. 10J is a perspective view of the pulley block pulley.

[0048] Fig. 10K is a front view of the pulley block pulley shown in Fig. 10J.

[0049] Fig. 10L is a cross-section (A-A) from Fig. 10K.

[0050] Fig. 11A is a front view of the faceplate of the pull station with the pull knob rotated.

[0051] Fig. 11B is a front perspective view of the faceplate of the pull station and junction box with the pull knob rotated as depicted Fig. 11A.

[0052] Fig. 11C is a front view of the faceplate of the pull station with the pull knob not rotated.

[0053] Fig. 11D is a front perspective view of the faceplate of the pull station and junction box with the pull knob not rotated as depicted Fig. 11C.

[0054] Fig. 12A is a front view of the faceplate of the pull station with the pull knob rotated and with walls proximate to the pull station.

[0055] Fig. 12B is a front view of the faceplate of the pull station with the pull knob not rotated and with walls proximate to the pull station.

[0056] Fig. 12C is a front perspective view of the faceplate of the pull station and junction box with the pull knob not rotated as depicted Fig. 12B.

[0057] Fig. 13A is a perspective cross-section of the pull knob, wire rope, and the set screws holding the wire rope.

[0058] Fig. 13B is a cross-section of the pull knob, wire rope, and the set screws holding the wire rope as depicted in Fig. 13A.

[0059] Fig. 13C is an exploded view of the pull knob, wire rope, and the set screws holding the wire rope as depicted in Fig. 13A.

[0060] Fig. 13D is a top perspective exploded view of the pull knob, wire rope, and compression fitting capturing the wire rope.

[0061] Fig. 13E is a bottom perspective exploded view of the pull knob, and wire rope capturing the wire rope as depicted in Fig. 13D.

[0062] Fig. 13F is a cross-section of the pull knob, wire rope, and compression fitting capturing the wire rope as depicted in Fig. 13D.

[0063] Fig. 14 is a representation of the pull station, flexible cable routing, and auto wire rope tensioning mechanism.

[0064] Fig. 15A is an exploded view of the auto wire rope tensioning mechanism illustrated in Fig. 14.

[0065] Fig. 15B is an illustration of the auto wire rope tensioning mechanism compressed.

[0066] Fig. 15C is an illustration of the auto wire rope tensioning mechanism extended fully.

[0067] Fig. 15D is an illustration of the auto wire rope tensioning mechanism with partial movement pull testing from the pull station.

[0068] Fig. 16A is an exploded bottom perspective view of the junction box and faceplate with break rod storage mechanism.

[0069] Fig. 16B is a top perspective view of the faceplate.

[0070] Fig. 16C is a bottom perspective view of the faceplate illustrating storage of the additional break rods.

[0071] Fig. 16D is a front perspective view of a portion of the faceplate.

[0072] Fig. 16E is a front perspective view of a portion of the faceplate illustrating the snap cleat.

[0073] Fig. 17A is a side cross-section of the pull station with rigid conduit wire rope connection.

[0074] Fig. 17B is a side cross-section of the pull station with flexible conduit wire rope connection.

[0075] Fig. 17C is a front view of the pull station with wire rope routing on-center to the junction box interface hole.

[0076] Fig. 17D is a side view of the pull station with wire rope routing on-center to the junction box interface hole.

[0077] Fig. 18A depicts a perspective view of a PG9 cap.

[0078] Fig. 18B depicts a perspective view of the compression fitting.

[0079] Fig. 18C depicts an exploded view of the compression fitting and the PG9 cap depicted in Figs. 18A-B.

[0080] Fig. 18D depicts a perspective view of the strain relief.

[0081] Fig. 18E depicts a side view of the strain relief and the compression fitting prior to attachment of the strain relief.

DETAILED DESCRIPTION OF THE INVENTION

[0082] Fig. 6 is a block diagram illustrating a mechanical system for connecting the pull handle **416** of pull station **400** to the release mechanism **160** of the fire suppression system using a wire rope **140** contained within a flexible conduit **220**. An example of the release mechanism **160** is a panel, such as the Ansul AUTOMAN® panel. Another example of the release mechanism **160** is a valve. Alternatively, flexible conduit **220** may be used to connect pull station **110** (shown in Fig. 1) with the release mechanism **160**.

[0083] The flexible conduit **220** may be composed of a variety of types of conduits, such as a Bowden conduit and a braided conduit, as shown in more detail in Figs. 5A-C. However, the flexible conduit is not limited to these types of conduits. The flexible conduit **220** may include a liner, a liner wrap, and an outer jacket. Though, the flexible conduit **220** does not need to include each of the liner, the liner wrap and the outer jacket. For example, the outer jacket need not be included in the flexible conduit. The flexible conduit **220** and wire rope **140** are coaxial mechanical devices whereby the wire rope **140** is disposed to slide axially within the liner of the flexible conduit **220**. The flexible conduit **220** may be routed in non-standard configurations **221** as shown in Fig. 6. Further, the flexible conduit **220** may be used in combination EMT **130** and/or pulley elbows **150** to couple wire rope **140** between, for example, structures such as the pull station **400** and release mechanism **160**. The wire rope **140** may be composed of a metal, such as an aircraft quality stainless steel braided wire rope with, for example, 7x7 braiding. The braiding of the wire rope may allow for the wire rope to be more bendable. Alternatively, the wire rope may have different braiding or no braiding at all.

[0084] The liner may comprise a material with a low coefficient of friction. For example, the liner may be composed of in part or whole a plastic material such as, for example, an acetal polymer, a polyethylene polymer, a PVC polymer, or a Teflon® fluoropolymer. In this manner, the liner may reduce the coefficient of friction between the liner and the wire rope whereby reducing the force required to slide the wire rope through the flexible conduit.

[0085] The liner wrap may comprise metal or composite, and may be a wire braid (such as a cross-weave), a flat wrap, or a wire wrap. The liner wrap may provide structural support to the flexible conduit **220**,

such as structural support to the liner. The liner wrap may be a mesh-type structure, with a plurality of holes there through. As discussed above, the flexible conduit may include an outer jacket. The outer jacket may comprise a polypropylene material, a PVC material, or other suitable plastics materials. The outer jacket, which may be free of holes, may be used for a variety of purposes. For example, the outer jacket may be used to form an impermeable and ductile outer sheathing for flexible conduit **220**. The outer jacket may also be colored (such as red) thereby serving as a visual warning mechanism to identify this flexible conduit as "SAFETY RELATED". In addition to the red color, indicia (such as printed text) may be printed on the outer jacket. For example, black text may be printed against the red outer jacket indicating the "fire suppression cable – do not disturb".

[0086] One example of flexible conduit may include Bowden lined conduit **500**, illustrated in Fig. 5A. The Bowden lined conduit **500** may include an outer jacket **502** composed of PVC. The outer jacket **502** may be a 0.197" outer diameter, for example. The Bowden lined conduit **500** may also include a wire wrap **506**, acting as a liner wrap. And, the Bowden lined conduit **500** may include a polyethylene liner **504** acting as a liner. The wire rope **140** may be inside of the polyethylene liner **504**. Another example of flexible conduit may include a braided conduit **305**, illustrated in Figs. 5B-5C. The braided conduit **305** may include a polypropylene outer jacket **310**. The polypropylene outer jacket **310** may have a 0.203" outer diameter. The braided conduit **305** may include a wire braid **330**, such as a 12-16 wire braid, acting as a liner wrap. And, the braided conduit **305** may include, an acetal liner **320** acting as a liner. Still another example of flexible conduit may include a long lay conduit with a polyethylene jacket of 0.187" outer diameter, a wire wrap, and a polyethylene liner. The flexible conduits illustrated in Figs. 5A-5C may easily be bent without the need for permanent deformation (or reshaping) of the liner or liner wrap.

[0087] Further, a lubricant may be used to reduce the coefficient of friction between the wire rope **140** and the liner. In particular, a lubricant (such as a Silicone lubricant) may be added to one of, or both, the flexible conduit **220** and the wire rope **140**. For example, the interior surface of the liner and/or the exterior surface of the wire rope **140** may be coated with a lubricant to reduce the coefficient of friction between the wire rope **140** and the liner. Alternatively, the liner may be attached to the wire rope **140**. For example, the wire rope **140** may be coated with a lubricant that subsequently solidifies (or partly solidifies). In this way, the wire rope **140** and/or the flexible conduit **220** may include a liner. As discussed above, the flexible conduit **220** allows the wire rope **140** to be pulled at the pull station **400** in order to activate the release mechanism **160**. The following is an equation of the forces associated with the pull station **400** and the release mechanism **160**:

[0088] $F1 = F2 \times e^{uskB}$

[0089] where F1 is the force at the pull station **400**;

[0090] F2 is the force at the release mechanism **160**;

[0091] usk is the coefficient of friction; and

[0092] B is the radians of total flex where 360 degrees = 2 pi radians for the flexible conduit **220** routing.

[0093] As discussed above, the liner of the flexible conduit **220** may be composed of a Teflon® fluoropolymer, which has a usk (coefficient of friction) of .040. According to the equation above, a flexible conduit **220** with no bends results in a force F1 at the pull station **400** of 1 pound to generate a 1 pound force at the release mechanism **160** (basically, no loss in the force generated from the pull station **400** to the release mechanism **160**). Further, according to the equation shown above, a flexible conduit **220** with a summation of angular curves of 4.7 radians (270 degrees) requires a force F1 at the pull station **400** of 1.21 pounds to generate a 1 pound force at the release mechanism **160**. In this way, even though the flexible conduit **220** has considerable bends in it, the amount of force necessary at the pull station **400** to generate a 1 pound force at the release mechanism **160** is substantially the same and not considerably higher than the flexible conduit **220** with no bends in it. Therefore, comparing the low friction flexible conduit to other conduits of higher friction, the flexible conduit **220** does not cause the operator of the pull station **400** to exert an inordinate amount of force to activate the release mechanism **160**.

[0094] The fire suppression system may also include a pulley block **610** of Fig. 9A or **710** of Fig. 9B. Pulley blocks **610** and **710** may be installed proximate to the pull station **400** such as being connected to the pull station as shown in Figs. 7A-D, 8A-D, 17A-B. Pulley blocks **610** and **710** may be connected to the pull station so that the wire rope **140** exits from the pulley block in any of multiple directions. For example, if the pull station **400** may be mounted flush to a wall, the wire rope **140** may exit from the pulley block **610** or **710** in any upward direction (toward the ceiling), a downward direction (toward the floor), to the right, and to the left.

[0095] The pulley blocks **610** and **710** may allow for installation in a variety of boxes, such as a standard electrical box **440**, a deep electrical box **445**, or no box. For a standard electrical box, the pulley blocks **610** and **710** may be configured in a first orientation (as shown in Figs. 7A-B and 8A-B) for a shallow box. In a first configuration for a standard electrical junction box, portion **615** or **715** may be pressed into the faceplate **410** in receiving location **420** of the pull station (shown in Figs. 9A-B and 16D). The portions **615** or **715** may be multi sided, such as square in shape, and may include a series of grooves **726** or snap fitting features **627** to provide positive engagement of the pulley blocks **610** and **710** into the faceplate **410**. In this manner and with a square configuration, the pulley blocks **610** and **710** may be pushed into the faceplate **410** in any one of four positions, thus allowing the cable exit points to exit the junction boxes **440** and **445** in any one of four holes **430** or **431**. In a second configuration for a deep electrical junction box, pulley box portions **620** or **720** may be pressed into the faceplate **410** of the pull station (shown in Figs. 7C-D and 8C-D). The portions **620** or **720** may be multi sided, such as square in shape, and may include a series of grooves **726** or snap fitting features **627**. In this manner and with a square configuration, pulley blocks **610** and **710** may be pushed into the faceplate **410** in any one of four positions, thus allowing the cable exit point of pulley blocks **610** and **710** to exit the junction box **440** and **445** in any one of four holes **430** or **431** respectively. The junction box **440** and **445** may include a box bottom **436** and a box screw boss **437**. The junction box **440** may interface with EMT **130** using a conduit-to-junction box coupling **131** (as shown in Fig. 17A) or may interface with flexible conduit **220** using a strain relief (not shown in Fig. 17B).

[0096] The pulley blocks **610** and **710** are uniquely configured to ensure that field cable entering the shallow or deep electrical junction boxes may enter on centerline of the junction box access holes **430** or **431** as illustrated in Figs. 17C-D.

[0097] The pulley blocks **610** and **710** shown in Figs. 10A and 10B may include a pulley **640** and **740** with bearings, or a pulley with a low friction bushing, in order to reduce the force necessary to pull the wire rope **140** out of the pull station when activating the pressurizing control cabinet **200,** release mechanism **160**. The pulley **640** or **740** may be connected to pulley block **610** or **710** using pulley axle screw threaded boss and pulley axle retaining clip **147**. An example of the means by which to connect the pulley includes using pulley axle shaft **641** and threaded pulley axle **642** (for pulley **640**), or pulley axle shaft **741** and threaded pulley axle **742** (for pulley **740**). Alternatively, the pulley axle retaining clip **147** need not be used. For example, threaded pulley axle **742** may be turned into the pulley block to secure the pulley **640** or **740**. Fig. 10A further illustrates a pull knob stem receiver **725**, a cleat retaining boss for a flexible cable **745**, and a cleat retaining boss for a pulley axle **747**. Fig. 10C further illustrates a pull knob stem receiver **625**, a snap cleat relief **626**, a snap cleat locking surface **628**, and a cleat retaining boss for a flexible cable **645**.

[0098] The pulley blocks **610** and **710** may connect to the flexible conduit **220** using an integral or assembly assisting retaining clip **145**. The retaining clip **145** may contain teeth or cleats **146** dimensioned such that the inner diameter (ID) of the clip is slightly less than the outer diameter (OD) of the flexible conduit **220** outer jacket **310** to enable positive engagement of the teeth or cleats **146** with the outer jacket **310**. The teeth or cleats **146** may be angled in such a way to allow the flexible conduit to be inserted into the pulley blocks **610** or **710** using reasonable force by hand. Based on the predisposed angle of the teeth or cleats **146** as shown in Figs. 10A and 10B, removal of the flexible conduit **220** from the pulley blocks **610** or **710** is made difficult and thus may require the use of a special tool. Alternatively, a crimp may be used in place of the retaining clip **145** to connect the flexible conduit **220** to the pulley blocks **610** or **710**. The pulley blocks **610** or **710** may also include proper circular interface bosses at each wire rope **140** exit point to enable the pulley blocks **610** or **710** to couple directly to EMT conduit compression fittings or other forms of conduit castings or couplings.

[0099] The fire suppression system may include a faceplate **410** that is coupled to pulley blocks **610** and **710**. The faceplate **410** may include lettering in one or more languages. The faceplate **410** may be coupled to pulley blocks **610** and **710** in several ways, including using one or more set screws **417** or snap lock features **627** (illustrated in Fig. 10C) that may couple the pulley blocks **610** and **710** into engagement with the faceplate **410.** Alternatively, instead of set screws **417**, a crimp connector may be used. The resulting combination is a faceplate **410**/pulley block **610** or **710** coupled as an assembly. When the faceplate **410** is configured with the snap lock feature as shown in Fig. 9A, assembly of the pulley block **610** into the faceplate **410** may be accomplished by hand without tools. The snap lock feature, as described herein and depicted in Fig. 9A, enables a faceplate-to-pull knob snap lock feature **425** to be utilized for locking the pull knob body **418** in a normal rotational orientation as shown in Figs. 11C-D and 16E. The

snap lock feature **425** may be used to engage the pull knob body **418** into place once the pull knob body **418** is rotated into its final position. In this way, the pull knob body **418** may be rotated relative to the faceplate **410**. Alternatively, the pull knob body **418** may remain stationary and the faceplate **410** may be rotated. The faceplate **410** may include one or more faceplate center pulley block receiver walls **421** and a faceplate center pulley block receiver step lock **422**, as shown in Fig. 16E.

[00100] The snap lock feature **425** enables the pull knob body **418** to be rotated, such as rotated sufficiently clockwise to allow the break rod **412** to be inserted into the pull knob body **418** in preparation for setting the pull station to a normal orientation as shown in Figs. 11A-D. Insertion of the break rod **412** may thus be accomplished in areas where there is adequate wall space on each side of the pull station and also within the narrow wall confines. This is illustrated in Figs. 12A-C in which wall **117** is proximate to the faceplate **410**. In order to insert break rod **412**, the pull knob body **418** is rotated clockwise (illustrated in Fig. 12A), and after installation of the break rod, rotated counterclockwise (illustrated in Fig. 12B). While the pull knob body **418** is being rotated counterclockwise towards the snap lock position, the snap lock cleat **425** may remain compressed until it moves into the corresponding relief **409** contained within the pull knob body as shown in Figs. 10D-I and 13E.

[00101] The pull station **400** includes pull handle cap **390**, cap snap fit boss **391**, and cap body snap fit receiving boss **392**, as shown in Fig. 9a. A crimp stop **141** may be used to hold pull handle cap **390**. The crimp stop **141** is one example of a cable compression connection. Another example of a cable compression connection may comprise a compression fitting, which may be used in place of crimp stop **141**. Fig. 9A further shows a cross hole for break rod **401**, a relief hole for wire rope stopper **402**, a ring handle hole **403**, and a tool slot **404**.

[00102] The faceplate **410** may contain one or more protective side walls **411**, such as one on each side of the pull knob body **418** and pull handle **416** assembly as shown in Figs. 16B and 16D. The protective walls **411** may provide a robust barrier to protect the pull knob body **418** and pull handle **416** against inadvertent side impact by foreign objects. These protective side walls **411** may also provide slots **413** for receiving the ends of the break rods **412** when installed, illustrated in Fig. 17A-C. Further, the faceplate **410** may include a pull handle circular race of faceplate **423** and a pull knob set screw threaded boss **424**.

[00103] Activation of the pull station may be accomplished by pulling the pull knob body **418** away from the pull station **400**. This action may cause the break rod **412** to fracture allowing the pull knob body **418** to move away from the faceplate **410** and thus moving the wire rope **140** through the flexible conduit **220**, thereby activating the release mechanism **160**. Coupling of the wire rope **140** to the pull knob body **418** may be accomplished in several ways, such as shown in Fig. 9B. Two methods are provided for illustration purposes only. The first method, as illustrated in Figs. 13A-C, uses one or more set screws **417** to secure the wire rope **140** into fixed or permanent configuration with the pull knob body **418**. In this configuration, the wire rope **140** may be threaded into the wire rope recess **426** of the pull handle cable boss **428**, such as

shown in Fig. 13C. Set screws **417** may be tensioned against the wire rope **140** to cause a sufficient binding on the wire rope to prevent it from being removed, such as shown in Fig. 6. As discussed above, set screws **417** need not be used and alternative methodologies, such as using a crimp connector, may be used. The second method, as illustrated in Figs. 13D-F, uses a compression fitting **141** to create an oversized end of wire rope coupling to inhibit or prevent the wire rope **140** from being removed from the pull knob body **418**. In this configuration, the OD of the compression fitting **141** may be larger than the OD of the wire rope access hole **426** in order that removal of the wire rope **140** from the pull knob body **418** is inhibited or prevented.

[00104] The faceplate **410** may also contain containment boundary diaphragms **415** (illustrated in Fig. 16D) located in each faceplate **410** mounting screw boss **414**, (illustrated in Figs. 9A-B and 16D). The containment boundary diaphragms **415** may be used to reduce or minimize any contaminate such as grease, dirt or grime from penetrating the faceplate **410** outer surface and entering into the working components and/or wire rope conduit **140** or **200** sections of the pull station assembly, such as shown in Fig. 11A.

[00105] The faceplate **410** and/or the pull handle cap **390** may further include various indicia, such as words, as shown in Figs. 9A-B and 10D. The indicia may be of a color that is different from another portion of the faceplate **410** and the pull handle cap **390**.

For example, the color may be red, fluorescent, or glow in the dark in order to differentiate the words (and the faceplate) from the surroundings (such as an aluminum background). The break rod **412** may be composed of plastic or glass and therefore may be transparent or opaque. The color on the faceplate **410** may be highlighted when viewed through the break rod **412**. Moreover, a part (or all) of the pull handle **416**, break rod **412**, screw boss **414**, or containment boundary diaphragms **415** may be of a color that is different from another portion of the pull handle **416**, break rod **412**, screw boss **414**, or containment boundary diaphragms **415**. Or, the pull handle **416**, break rod **412**, screw boss **414**, or containment boundary diaphragms **415** may entirely be red, fluorescent, or glow in the dark in order to differentiate it from an adjacent part. Finally, the colors of two parts that are designed to mate may be selected such that the colors match when installed properly (*e.g.*, continuous color red for screw boss **414** and containment boundary diaphragm **415** if they are installed properly) or such that the colors are different when installed properly (*e.g.*, color red next to color aluminum when screw boss **414** is installed properly with containment boundary diaphragm **415**).

[00106] The faceplate **410** may further be adapted to serve as a storage mechanism for service items, such as extra break rods **412**. One method is shown in Figs. 16A and 16B. In the event that the pull station **400** needs to be reconfigured or reinitialized, such as by inserting a new break rod, the hardware used for the reinitializing may be stored proximate to the pull station **400**, such as storing additional break rods **412** on an underside of the faceplate **410**, as shown in Fig. 16A. The break rods **412** may be stored at a 90° angle to that depicted in Figs. 16A and 16C.

[00107] When the pull station **400** is installed in the field, the technician may often leave extra wire rope **140** inside the pressurizing control cabinet **200**. This extra length of wire rope **140** may have the effect of allowing the pull knob body **418** to move away from the pull station **410** without activation of the release mechanism **160**. A wire rope auto tensioning device may be used to control the "dead band" of wire rope **140** and maintain the wire rope **140** under tension, though this is not required. One example of an auto tensioning device comprises an auto tensioning spring **142**, illustrated in Figs. 15A-D. The auto tensioning spring **142** may be used to reduce the "dead band", as shown in Figs. 15A-B. The auto tensioning spring **142** may allow the technician the ability to field test the conduit **130** or **220** routing without activating the system, as illustrated in Fig. 15D, by partial movement pull testing from the pull station. For example, a single technician located at the pull station **400** may pull the pull handle **416** in order to test the device. If after pulling the pull handle **416**, the handle returns to its position (*i.e.*, springs back), then the technician may determine that the auto tensioning spring **142** is operational and the wire rope is properly configured. The auto tensioning spring **142** may further ensure activation of the system upon deployment of the pull knob body **418**, as illustrated in Fig. 15C, by extended full movement.

[00108] As shown in Fig. 15A, the auto tensioning device (such as the auto tensioning spring **142**) is located proximate to the release mechanism **160**. Alternatively, the auto tensioning device may be located at any point along the path of the wire rope **140** from the pull station **400** to the release mechanism **160**. The auto tensioning device may comprise a variety of shapes, such as a "Z" shaped spring, as shown in Fig. 15A.

[00109] The equation $F_1 = F_2 e^{uskB}$ may be used to describe the characteristics of the flexible conduit system shown in Figs. 6 and 14. F_1 may be the force at one end of the wire rope (such as where the wire rope **140** is connected to the pull station **400**), and F2 may be the force at the other end of the rope (such as where the wire rope **140** is connected to the release mechanism **160** of the pressurizing control station **100** or **200**). The coefficient of static or kinetic friction may be represented by usk. The angle B may be expressed in radians.

[00110] As discussed above, there are a variety of ways by which the flexible conduit **220** (and the wire rope **140** inside the flexible conduit) may be attached to various structures in the fire suppression system. One example is depicted in Figs. 18A-E. Fig. 18A depicts a perspective view of a PG9 cap **800**. As discussed in more detail below, the PG9 cap **800** works in combination with compression fitting **810** and strain relief **820** to connect the flexible conduit **220** and the wire rope **140** to structures within the fire suppression system, such as junction boxes, valves, AUTOMAN® panel, etc.

[00111] The PG9 cap **800** includes a hole **802**. As discussed in more detail below, the hole **802** may have a radius large enough to pass wire rope **140** through and a radius small enough so that the flexible conduit **220** cannot pass through. For example, the hole **802** may be sufficiently small so that the liner of the flexible conduit **220** (such as polyethylene liner **504** and acetal liner **320**) cannot pass through. A further example may be where the hole **802** diameter is equivalent to the outer jacket diameter of the flexible conduit **502** and **310** to create an effective flexible conduit guide into the junction boxes **440** or **445** (as viewed in

Figs. 7B and 7D). Further, the PG9 cap **800** has an interior surface that includes threading **804**. As discussed in more detail below, a portion of the strain relief **820** may connect to the threading **804**.

[00112] Fig. 18B depicts a perspective view of the compression fitting **810**. The compression fitting **810** includes compression fitting cap **812** and compression fitting main body **814**. The compression fitting main body **814** may be connected to a structure within the fire suppression system, such as junction box **120**, using bolt **816**.

[00113] Fig. 18C depicts an exploded view of the compression fitting **810** and the PG9 cap **800**. The PG9 cap **800** may be sandwiched in between the compression fitting cap **812** and the compression fitting main body **814**. The compression fitting cap **812** may then be attached to the compression fitting main body **814**, such as by screwing the compression fitting cap **812** onto the compression fitting main body **814** via threads **817** on the compression fitting main body **814** and threads on an interior surface of the compression fitting cap **812** (not shown). The outer diameter of the PG9 cap **800** may be less than the inner diameter of the compression fitting cap **812** so that the compression fitting cap **812** may slide onto the PG9 cap **800**. Further, the outer diameter of the PG9 cap **800** may be less than or equal to the outer diameter of the compression fitting main body **814**. In this way, when the compression fitting cap **812** is screwed onto the compression fitting main body **814**, the PG9 cap **800** may be securely compressed in between.

[00114] Fig. 18D depicts a perspective view of the strain relief **820**. The strain relief **820** includes strain relief cap **822** and strain relief main body **824**. The strain relief cap **822** includes a hole **826** by which the flexible conduit **220** may be attached. The strain relief main body **824** includes threading **828** for threading with the threads **804** of the PG9 cap **800**. In this way, the strain relief **820** may be attached.

[00115] Fig. 18E depicts a side view of the strain relief **820** and the compression fitting **810** prior to attachment of the strain relief **820**. As shown, the flexible conduit may be attached to the strain relief **820**. And, using PG9 cap **800**, the wire rope **140** may be guided into the junction box **120**.

[00116] Considering Teflon® to steel usk = 0.04 (such as where the liner **320** is composed of Teflon® and the wire rope **140** is composed of steel), F_2 = 6 lbs and F_1 = 40 lbs, then B = 47.4 radians or 2717 degrees. Without a liner and/or lubricant, the coefficient of friction is higher, such as usk = 0.15. Using the same forces of F_2 = 6 lbs and F_1 = 40 lbs, the B = 12.6 radians or 724 degrees. Comparing these two examples illustrate the significant impact that a lower coefficient of friction has on the flexible conduit constraints. In the example using usk = 0.04, the flexible conduit may be bent 30 times at right angles whereas the example using usk = 0.15 (without the liner), the flexible conduit may be bent at the same angle only 8 times.

[00117] The flexible conduit **220** in the fire suppression system may be easier to install than the EMT **130** and the 90 degree pulley elbows **150** shown in Fig. 1. Further, the flexible conduit **220** still provides a reliable system similar to the fire suppression system shown in Fig. 1. The flexible conduit system was cycled more than 8,000 times without signs of degradation. The system passed a 500 cycle test with 150 feet of lined and coated Bowden conduit, eight 90 degree bends with a 3" radius, 15 pulley elbows, a pull

station with a built-in pulley block, and a 6 lb load at one end, the resulting force on the other end being 37.23 lbs on average with a standard deviation of 1.45 lbs. With a similar setup, except with a pull station having an ultrahigh molecular weight polyethylene (UHMW) busing and a three pound load, the resulting force was 30.83 pounds with a standard deviation of 1.25 lbs.

[00118] As discussed above, the flexible conduit may be connected to the Ansul AUTOMAN® panel, gas valve, corner pulleys, electrical box, EMT conduit, etc. For example, the flexible conduit may be connected between the Ansul AUTOMAN® panel and the pull station, up to 140 ft and four 90° bends. When the flexible conduit is used to make 90° bends, these bends may start from the AUTOMAN® panel or gas valve, with some or no mechanical 90° elbows being used in between these bends. If more than four 90° bends are used, then mechanical pulleys may be used. The flexible conduit may also be connected between the Ansul AUTOMAN® panel and the gas valve, up to 75 ft and four 90° bends and four corner pulleys. The flexible conduit may be placed along the same path as the EMT conduit would normally be run. Stainless steel rope may be routed through the flexible conduit. The flexible conduit may be distanced from hood or other high temperature items by more than 6 inches. These examples are provided for illustration purposes only.

[00119] Alternatively, instead of using wire rope **140** to connect the pull handle **416** to the release mechanism **160**, other means may be used. For example, activation of the pull handle **416** may in turn activate a circuit (such as a switch) which could send a signal to a releasing mechanism. The signal may be an electrical signal transmitted via an electrical wire. Or, the signal may be a wireless signal, which may be transmitted via a transceiver and received at the release mechanism (such as the Ansul AUTOMAN® panel, which may include a wireless receiver and/or transmitter).

[00120] Moreover, instead of using wire rope **140**, a fiber optic cable may be used. For example, the pull station may be connected between a first fiber optic cable and a second fiber optic cable. Specifically, a light source may be connected to the first fiber optic cable, sending a beam through the first fiber optic cable. A panel may be connected to the second fiber optic cable. In the event that the pull station is not activated, light traveling through the first fiber optic cable may be interrupted, indicating to the panel that the pull station has not been activated. In the event that the pull station is activated (such as by pulling the pull handle **416**), light traveling through the first fiber optic cable may not be interrupted, indicating to the panel that the pull station has been activated.

[00121] While various embodiments of the invention have been described, it will be apparent to those of ordinary skill in the art that many more embodiments and implementations are possible within the scope of the invention. Accordingly, the invention is not to be restricted except in light of the attached claims and their equivalents.

We claim:

1. In a fire suppression system having a lever at a pull station, a release mechanism for releasing a fire suppression agent, a wire rope connected between the lever and the release mechanism, and a flexible conduit, the wire rope disposed to slide axially within the flexible conduit, wherein the improvement comprises:

a material on at least one of the wire rope or an interior of the flexible conduit in order to reduce a coefficient of friction.

2. The fire suppression system of claim 1, wherein the material comprises a liner for the flexible conduit.

3. The fire suppression system of claim 2, wherein the liner is composed of plastic.

4. The fire suppression system of claim 1, wherein the material comprises a lubricant.

5. The fire suppression system of claim 4, wherein the lubricant is applied to at least one of an interior of the flexible conduit or the wire rope.

6. The fire suppression system of claim 5, wherein the interior of the flexible conduit comprises a plastic liner.

7. The fire suppression system of claim 6, wherein the lubricant is applied to both an interior of the plastic liner and the wire rope.

8. The fire suppression system of claim 4, wherein the lubricant comprises silicone.

9. A fire suppression system comprising:

a pull station comprising a pull lever and a pulley, the pulley proximate to the pull lever;

a release mechanism for causing fire suppression agent to be released when activated; and

a wire rope connected between the pull lever and the release mechanism, with the wire rope abutting at least a part of the pulley so that the pulley reduces an amount of force necessary to pull the pull lever in order to activate the release mechanism.

10. The fire suppression system of claim 9, wherein the pull station further comprises a pulley block and a faceplate, the pulley mounted with the pulley block, the pulley block connected to the faceplate.

11. The fire suppression system of claim 10, wherein a groove on the pulley block is pressed into the faceplate to engage the faceplate.

12. The fire suppression system of claim 10, wherein the pull station further comprises a junction box; and

wherein the pulley block is connectable with the faceplate in at least two configurations depending on the size of the junction box.

13. The fire suppression system of claim 12, wherein a first configuration of the pulley comprises a shallow box configuration for a shallow box; and

wherein a second configuration of the pulley comprises a deep box configuration for a deep box.

14. The fire suppression system of claim 12, wherein the pulley and pulley block are configured to direct the wire rope on a centerline to openings in the junction box.

15. The fire suppression system of claim 10, wherein the pull station further comprises a junction box with a first opening and a second opening; and

wherein the pulley block is connectable with the faceplate in a first configuration and a second configuration so that the wire rope exits the pulley block along a centerline of the first opening in the first configuration and exits the pulley block along a centerline of the second opening in the second configuration.

16. The fire suppression system of claim 9, further comprising a flexible conduit, the wire rope disposed to slide axially within the flexible conduit, wherein a material is on at least one of the wire rope or an interior of the flexible conduit in order to reduce a coefficient of friction.

17. The fire suppression system of claim 16, wherein the flexible conduit comprises a plastic liner; and

wherein a lubricant is applied on at least one of an interior of the plastic liner or the wire rope.

18. The fire suppression system of claim 9, wherein the pull station further comprises a faceplate, the faceplate including contrasting colored indicia.

19. A fire suppression or annunciation system comprising:

a pull station comprising a pull knob assembly and a faceplate, the pull knob assembly adapted to interface with a break rod, wherein at least one of the pull knob assembly and the faceplate are rotatable;

an activation mechanism for causing release of fire suppression agent or causing annunciation when activated; and

a wire rope connected between the pull knob assembly and the release mechanism.

20. The fire suppression or annunciation system of claim 19, wherein the pull knob assembly and the faceplate are rotatable relative to one another.

21. The fire suppression or annunciation system of claim 20, wherein the faceplate is stationary and the pull knob assembly is rotatable.

22. The fire suppression or annunciation system of claim 21, wherein the pull knob assembly comprises a pull handle connected to a pull knob, the pull knob connected to the wire rope, a user pulling the pull handle in order to pull the wire rope and activate the release mechanism;

wherein the pull knob and pull handle are adapted to be rotated in a first direction in order to interface with the break rod;

wherein the faceplate includes at least two sidewalls; and

wherein the pull knob and pull handle are adapted to rotate in a second direction opposite to the first direction in order for the break rod to be received by at least a portion of the two sidewalls of the faceplate.

23. A fire suppression or annunciation system comprising:

a pull station comprising a pull knob assembly;

an activation mechanism for causing release of fire suppression agent or causing annunciation when activated;

a wire rope connected between the pull knob assembly and the release mechanism; and

a wire rope tensioning mechanism to maintain tension on the wire rope, the wire rope tensioning mechanism connected to at least two separate parts of the wire rope.

24. The fire suppression or annunciation system of claim 23, wherein the wire rope tensioning mechanism comprises a spring.

25. The fire suppression or annunciation system of claim 24, wherein the spring is proximate to the activation mechanism.