

TITLE OF THE INVENTION

PRINTED CIRCUIT BOARD WITH ELECTRONIC DEVICES MOUNTED THEREON ✓

BACKGROUND OF THE INVENTION

The present invention relates to a printed circuit board
5 with electronic devices mounted thereon and, more
particularly, to a printed circuit board equipped with a
cooler having a sealed case wherein a liquid coolant is
passed over the printed circuit board having mounted thereon
LSIs or similar semiconductor devices of large calorific
10 power.

Because of the recent increase in the LSI integration
density as well as the recent speeding up of LSI operations,
calorific power that individual high-density LSIs generate
keeps on increasing. Such being the case, there is a demand
15 for the development of a more efficient cooling unit for a
high-density-LSI-mounted, printed circuit board. The LSI-
mounted printed circuit board has a required number of LSIs
mounted on one or both sides of the board. To cool the LSIs,
it is customary in the prior art to cool the entire structure
20 of the LSI-mounted printed circuit board by forced air
cooling or liquid cooling of the type that soaks the printed
circuit board in a liquid coolant.

The forced air cooling does not sufficiently achieve the
intended purpose of cooling LSIs of large calorific power.
25 The liquid cooling involves the immersion of the whole
printed circuit board structure in the coolant, and hence it
has a defect that the cooler therefor is inevitably bulky.

In addition, since the liquid cooling of the printed circuit board substantially relies on convection of the coolant, it is impossible to produce a satisfactory effect of cooling the printed circuit board when electronic devices of large
5 calorific power are mounted thereon.

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide an electronic-devices-mounted, printed circuit board equipped with a highly efficient but small cooler.

10 According to an aspect of the present invention, the electronic-devices-mounted, printed circuit board comprises: a printed circuit board having an electronic device array mounted on at least one side thereof; and a sealed case that houses the electronic device array, has its marginal edges
15 held in liquidtight contact with one side of the printed circuit board all around the electronic device array and has an inlet port for supplying therethrough a coolant into the sealed case from the outside and an outlet port for discharging therethrough the coolant to the outside. The
20 interior of the sealed case forms a cooling chamber in which the electronic devices are soaked in the coolant that is supplied through the inlet port, distributed through the electronic devices and drained through the outlet port to the outside.

25 According to another aspect, the cooling chamber has a plurality of barriers which extend between adjacent electronic devices across their array so that the coolant channel or passage from the inlet to the outlet port meander

through the individual electronic devices.

According to still another aspect, the electronic devices are arranged in a matrix form on the printed circuit board and the sealed case has a box-like configuration which has a bottom panel, a pair of opposed side walls extending in the column direction of the matrix and a pair of opposed end walls joining opposed ends of the above-mentioned two side walls, and a partition wall extending from one of the end walls to a position a little short of the other to define therebetween a clearance and dividing the matrix array of electronic devices in its column direction into two sub-matrix arrays, thereby providing a substantially U-shaped coolant channel from the inlet to the outlet port.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1A is a plan sectional view of an embodiment of the present invention;

Fig. 1B is a sectional view taken on the line 1b-1b' in Fig. 1A;

Fig. 2 is a partially enlarged sectional view of the embodiment shown in Figs. 1A and 1B;

Fig. 3A a plan sectional view of another embodiment of the present invention;

Fig. 3B is a sectional view taken on the line 3b-3b' in Fig. 3A;

Fig. 4 is a partially enlarged sectional view of the embodiment shown in Figs. 3A and 3B;

Fig. 5 is a plan sectional view of an electronic-devices-mounted, printed circuit board used for measurement of the

effect of the present invention;

Fig. 6 is a graph showing measured values obtained with the printed circuit board of Fig. 5;

Fig. 7A is a plan sectional view of another embodiment of
5 the present invention;

Fig. 7B is a sectional view taken on the line 7b-7b' in Fig. 7A;

Fig. 8A is a plan sectional view of another embodiment of the present invention;

10 Fig. 8B is a sectional view taken on the line 8b-8b' in Fig. 8A;

Fig. 9A is a plan sectional view illustrating a modified form of the embodiment shown in Figs. 8A and 8B;

Fig. 9B is a sectional view taken on the line 9b-9b' in
15 Fig. 9A;

Fig. 10 is a plan sectional view of another embodiment of the present invention;

Fig. 11 is a plan sectional view of still another embodiment of the present invention;

20 Fig. 12 is a perspective view of an embodiment in which electronic devices of relatively small calorific power are mounted on the same printed circuit board outside the sealed case and cooled by a forced air-cooling fan motor of test equipment;

25 Fig. 13A is a side view showing an example of an electronic-devices-mounted, printed circuit board mounting structure;

Fig. 13B is a side view showing another example of an

electronic-devices-mounted, printed circuit board mounting structure; and

Fig. 13C is a side view showing still another example of an electronic-devices-mounted, printed circuit board mounting
5 structure.

DESCRIPTION OF THE PREFERRED EMBODIMENT

A description will be given, with reference to Figs. 1A and 1B, of a first embodiment of the cooler-equipped printed circuit board according to the present invention. Fig. 1A is
10 a sectional view taken on the line 1a-1a' in Fig. 1B and Fig. 1B a sectional view taken on the line 1b-1b' in Fig. 1A. As shown in Figs. 1A and 1B, there is mounted on a printed circuit board 10 over the entire area of its either side a matrix array of 32 electronic devices 3 of large calorific
15 power, such as LSIs. Each side of the printed circuit board 10 is covered with a box-like sealed case 20 which has its one side opened and forms a cooling chamber wherein the electronic devices 3 are housed and a coolant 7 is distributed through the electronic devices 3. The sealed
20 case 20 comprises a bottom panel 21, a pair of opposed side panels 22a, 22b and a pair of end panels 22c, 22d. As depicted in Fig. 2, each electronic device 3 comprises an LSI 33 having terminal pins 31 and a radiator 32 having radiation fins and held in intimate contact with the LSI 33. Both
25 sides of the printed circuit board 10 and marginal portions 26 of the sealed case 20 are pressed in liquidtight contact with each other by clamps 12a and 12b through elastic O rings 4 and fixed by screws 13.

The terminal pins 31 of the electronic device 3 connect therethrough the LSI 33 to the printed circuit board 10 electrically and mechanically. The radiator 32, which is fixedly contacted with the surface of the LSI 33 is made of a good thermal conductor such as copper or aluminum and has a plurality of radiation fins formed on the surface thereof. The printed circuit board 10 further has a number of connectors 5 mounted thereon at its marginal edges. The terminal pins 31 of the electronic devices 3 are connected to the connectors 5 through multi-layer interconnections of the printed circuit board 10. Between the sealed case 20 and the printed circuit board 10 there is defined the cooling chamber 25 wherein the electronic devices 3 are housed and cooled by the coolant 7 distributed therethrough in the direction indicated by the arrows 71. Reference numeral 61 denotes an inlet port for injecting the coolant 7 into the cooling chamber and 61' an inlet port made in the end wall 22c. Reference numeral 62 denotes an outlet port for discharging therethrough the coolant 7 from the cooling chamber 25 and 62' an outlet port made in the end wall 22d.

The coolant 7 flows through the inlet ports 61 and 61' into the cooling chamber 25, wherein the electronic devices 3 are immersed in the coolant 7. The coolant 7 flows in the direction of the arrows 71 while cooling the electronic device 3 and is drained through the outlet ports 62 and 62' to the outside of the sealed case 20.

As shown in Fig. 2, a sealing means 27 is used to provide liquidtight joints between the printed circuit board 10 and

the marginal end portion 26 of the sealed case 20. Reference numeral 11 denotes metallic foil predeposited on the surface area of the printed circuit board 10 for liquidtight contact with the marginal end portion 16 of the sealed case 20. The
5 printed circuit board 10 and the sealed case 20 are joined together with the elastic O ring packing 4 interposed between a groove 28 cut in the end face of the marginal end portion 26 and the metallic foil 11 and the sealed case 20 is pressed against and fixed to the printed circuit board 10 by means of
10 clamps 12a and 12b. The metallic foil 11 is formed by depositing a gold-plated pattern on the surface of the printed circuit board 10 or depositing a copper pattern first and then plating it with gold. The elastic packing 4 that is held between the sealed case 20 and the printed circuit board
15 10 is made of a material free from degradation by the coolant 7. Used as the coolant 7 is, for example, FLUORINERT (Trademark: 3M, Inc.) that is an inert liquid. By plating the metallic foil 11 with gold, the sealing property of the sealing means 27 can be retained for a long period of time.
20 The construction of the sealing means 27 described above is also applied to all the embodiments of the invention that will be described later on.

The radiator 32 mounted on each electronic device 3 housed in the cooling chamber 25 is cooled by the coolant 7
25 that is properly temperature controlled and injected into the sealed case 20 under a required pressure from an external refrigerator through the inlet port 61 and a pipe. The coolant 7 injected into the cooling chamber 25 through the

inlet port 61 flows as indicated by the arrows 71 while absorbing heat from the electronic devices 3 and their radiators 32 and is discharged to the outside through the outlet port 62.

5 By injecting the coolant 7 into the cooling chamber 25 through the inlet ports 61 and 61' and discharging it through the outlet ports 62 and 62' as mentioned above, the heat given off by the electronic devices 3 is absorbed by the coolant 7 flowing in contact with them, and hence it can
10 efficiently be dissipated. Additionally, since the sealed case is mounted on the printed circuit board so that it covers the electronic device array, the assembly can be made small.

In the embodiment of Figs. 1A and 1B, the coolant 7 flows
15 substantially in parallel with the direction of arrangement of the electronic devices 3 as indicated by the arrows 71. Hence, a high-temperature cross-sectional region of the coolant flux which flows near the electronic devices 3 and a relatively-low-temperature cross-sectional region of the
20 coolant flux which flows off the electronic devices 3 tend to have a steady distribution. As a result, an appreciable amount of the coolant flux in the relatively-low-temperature cross-sectional region is drained intact from the cooling chamber 25, giving rise to a problem that the coolant is not
25 effectively utilized to dissipate the heat generated by the electronic devices 3. In such a state, the cooling efficiency does not increase even if the flow rate of the coolant 7 is set at a large value. When the coolant flux

flowing in contact with the electronic devices 3 has a low flow rate, it undergoes a large temperature rise. In such an instance, as the coolant 7 flows downstream, its temperature gradually rises and its cooling ability diminishes
5 accordingly, resulting in a marked increase in the temperature of the electronic devices 3 lying downstream.

The flow rate of the coolant 7 could be increased by raising the coolant injection pressure to increase its velocity of flow. With the use of an arrangement for
10 injecting the coolant at high pressure, the reliability of liquidtightness for the coolant 7 would also decrease. Furthermore, such an arrangement would make the liquid cooling unit bulky and raise its manufacturing cost accordingly.

15 To heighten the heat absorbing effect of the coolant 7, it is desirable to make the entire coolant flux contribute to the heat absorption as equally as possible. That is, it is important to give every portion of the coolant 7 an opportunity for flowing in touch with the electron devices 3.
20 This can be achieved by disturbing the coolant flux in its cross-sectional region. Next, a description will be given of another embodiment of the present invention intended for enhanced cooling efficiency by changing the direction of flow of the coolant 7 or disturbing its flow by barriers set up in
25 the cooling chamber 25. Incidentally, although in the following embodiments no reference is made, for brevity, to the clamps 12a, 12b and the screws 13 shown in Figs. 1A and 2, they shall naturally be provided.

The embodiment shown in Figs. 3A and 3B differs from the embodiment of Figs. 1A and 1B in that the electronic devices 3 are arranged in the form of a matrix with 6 rows and 4 columns and that barriers 24 are formed which extend
5 alternately from one of the opposed side walls 22a and 22b toward the other and the latter toward the former every other column. In this embodiment, the coolant inlet port 61 and the outlet port 62 are provided near the opposite ends of the same side wall 22b. Since the direction of flow of the
10 coolant 7 from the inlet port 61 to the outlet port 62 is reversed by the barriers 24 a plurality of times as indicated by the arrows, the coolant flux is stirred or disturbed and a uniform temperature distribution is provided over the entire flux.

15 Fig. 3B is a sectional view taken in the direction of the arrows from the line 3b-3b' in Fig. 3A and Fig. 4 a partly enlarged sectional view taken in the direction of the arrows from the line 4-4' in Fig. 3A.

In Figs. 3A, 3B and 4, the printed circuit board 10 has
20 on its either side the electronic devices 3 arranged in a matrix form as in the case of the Fig. 1 embodiment. The electronic devices 3 are each electrically and mechanically connected by the terminal pins 31 to the printed circuit board 10. Each electronic device 3 has the radiator means 32
25 fixedly secured to its surface and the radiator means 32 has a plurality radiation fins formed on its surface. On either side of the printed circuit board 10 there are mounted the sealed case 20 to define between it and the board 10 the

cooling chamber 25 in which to cool the electronic devices 3 housed therein. That is, the sealed case 10 has the barriers 24 that extend alternately from the bottom panel 21 and one of the opposed side walls 22a and 22b toward the printed circuit board 10 and the other side wall and the latter toward the former. The lower marginal edge of each barrier 24 may be spaced apart from the printed circuit board 10.

Thus, there is formed between the printed circuit board 10 and each sealed case 20 the cooling chamber 25 in which the electronic devices 3 are housed and the coolant 7 meanders in such directions as indicated by the arrows. In this instance, the inlet and outlet ports 61 and 62 for one of the cooling chamber 25 may be dispensed with, but instead holes through which the both cooling chambers 25 communicate with each other are made in the printed circuit board 10 near the inlet and outlet ports 61 and 62 for the other cooling channel 25 so that the coolant 7 flows from one side to the other of the printed circuit board 10. This permits reduction of the number of inlet and outlet ports 61 and 62.

Next, a description will be given of the results of measurements indicating that the efficiency of cooling the electronic devices 3 can be increased by disturbing the coolant flux with the barriers 24 set up in the cooling chamber 25 as described above.

As shown in Fig. 5, the printed circuit board 10 used for the measurement has eight electronic devices 3 aligned in a row at equal intervals and the cooling chamber 25 has the barriers 24 extending between every second and third

electronic devices 3. The sealed case 20 measures 200 by 40 mm². Each electronic device 3 is composed of a ceramic substrate measuring 16 by 16 by 1.0 mm³ and an LSI formed thereon in a size of 7.5 by 7.5 by 0.5 mm³ and has a heating value of 12 W.

Fig. 6 shows measured values of the surface temperatures of electronic devices #1 and #8 in the cases where the flow rate of the coolant was set at 1000 cm³/min, 1500 cm³/min and 2000 cm³/min, respectively. The coolant temperature at the inlet port 61 is 25°C. The black holes indicate the values measured with no barriers and the white holes the values measured with the barriers provided. Fig. 6 clearly demonstrates that the device cooling efficiency can be increased by the provision of the barriers 24.

Other embodiments of the cooler-equipped printed circuit board according to the present invention will be described below.

In the embodiment of Figs. 7A and 7B, there are mounted on either side of the printed circuit board 10 the electronic devices 3 in the form of a matrix with 8 rows and 4 columns. Reference numeral 8 denotes a partition wall, which divides the electronic device matrix into two sub-matrixes each consisting of two rows of electronic devices 3. In the end wall 22c divided by the partition wall 8 there are made the inlet and outlet ports 61 and 62 that communicate with the two regions of the cooling chamber 25, respectively. The partition wall 8 extends from the bottom panel 21 and the end wall 22c integrally therewith and when the upper sealed case

20 is mounted on the printed circuit board 10, the lower marginal edge of the partition wall 8 is pressed into liquidtight contact or engagement with the top of the printed circuit board 10, blocking the flow of the coolant 7 between the two separated regions of the cooling chamber 25. The end edge of the partition wall 8 lengthwise thereof does not extend to the end wall 22d to define therebetween a clearance, forming a substantially U-shaped coolant channel from the inlet port 61 to the outlet port 62 in the cooling chamber 25. In the U-shaped coolant channel, there are provided barriers 9 which extend alternately from the side walls 22a, 22b and the partition wall 8 into adjacent electronic devices 3. The barriers 9 are formed integrally with the bottom panel 21 and the side walls 22a, 22b or the partition wall 8 and have the same height as those of the side walls and the end walls and their lower marginal edges are urged against the printed circuit board 10 in a liquidtight manner when the upper sealed case 20 is mounted thereon. The width of each barrier 9 is about 1/2 the spacing between the side wall 22a or 22b and the partition wall 8. The barriers 9 are extended from the side walls 22a, 22b and the partition wall 8 alternately every other electronic device 3 in the direction of arrangement of the electronic devices 3. With such barriers 9, the coolant 7 flowing down the U-shaped channel from the inlet port 61 to the outlet port 62 repeatedly meander, so that the coolant flux is disturbed.

The cooling chamber 25 is filled with the coolant 7

flowing thereinto through the inlet ports 61 and 61' and the electronic devices 3 are immersed in the coolant 7. In this embodiment, since the cooling chamber 25 is separated into two compartments and since the barriers 9 are provided
5 therein as mentioned above, the cross-sectional area of the coolant channel or passage is small. Hence, the velocity of flow of the coolant 7 is higher than in the embodiment of Figs. 1A and 1B in the case of the same flow rate. The coolant 7 flowing into the cooling channel 25 becomes
10 turbulent while striking against the barriers 9 at high velocity and flows as indicated by the arrows 71, cooling the electronic devices 3. Finally, the coolant 7 flows out of the cooling chamber 25 through the outlet ports 62 and 62'.

By the turbulent flow of the coolant 7, its higher and
15 lower temperature portions are effectively mixed with each other to provide a uniform temperature distribution over the entire coolant flux, further heightening the electronic device cooling effect. While in this embodiment the electronic devices 3 are mounted on either side of the
20 printed circuit board 10, they may be mounted only on one side of the board 10. Moreover, although this embodiment has only one partition wall 8 formed in the cooling chamber 25, it is also possible to adopt a construction wherein such partition walls are extended between adjacent electronic
25 devices 3 in the row direction of their array alternately from the end walls 22c and 22d and the barriers 9 are extended between every second and third electronic devices 3 in the column direction alternately from the two opposed

partition walls (or one partition wall 8 and the side wall 22a or 22b).

Turning next to Figs. 8A and 8B, another embodiment of the present invention will be described. Fig. 8A is a
5 sectional view taken on the line 8a-8a' in Fig. 8B and Fig. 8B a sectional view taken on the line 8b-8b' in Fig. 8A.

In this embodiment, there are mounted on both sides of the printed circuit board 10 the electronic devices 3 in the same fashion as in the embodiment of figs. 7A and 7B. The
10 end wall 22c has only one inlet port 61' bored therethrough for injecting the coolant 7 into the cooling chamber 25 on the top of the printed circuit board 10 and in the vicinity of the inlet port 61' the printed circuit board 10 has an inlet port 14 through which the coolant 7 injected into the
15 upper cooling chamber 25 is also distributed into that defined on the underside of the printed circuit board 10. Similarly, only one outlet port 62' is bored through the end wall 22c for discharging the coolant 7 to the outside. In the vicinity of the outlet port 62' the printed circuit board
20 10 an outlet port 15 bored therethrough, so that the coolant 7 from the lower cooling chamber 25 flows through the outlet port 15 and joins the coolant 7 having flowed through the upper cooling chamber, thereafter being discharged through the outlet port 62'.

25 In this embodiment, the coolant 7 injected through the inlet ports 61 and 61' flows into the cooling chamber 25 formed on the top of the printed circuit board 10 and also into the cooling chamber 25 defined on the underside of the

printed circuit board 10 through the inlet port 14. The coolant 7 flowing into the upper cooling chamber 25 flows as indicated by the arrows 71 and flows out of the sealed case 20 through the outlets 62 and 62'. The coolant 7 flowing
5 into the lower cooling chamber 25 through the inlet port 14 similarly flows through the cooling chamber 25, then flows into the upper cooling chamber 25 through the outlet port 15 and flows out of the sealed case 20 through the outlet ports 61' and 62.

10 According to this embodiment, by forming the inlet and outlet ports 14 and 15 in the printed circuit board 10 near the inlet and outlet ports 61' and 62', respectively, the coolant 7 can be distributed equally through the cooling chambers 25 on both sides of the printed circuit board 10
15 although one inlet port 61 and one outlet port 62 are provided for the two sealed cases 20. In addition, the provision of such ports does not introduce any particular complexity in the liquid cooling arrangement. That is, according to this embodiment, the number of tubes that must
20 be connected to the inlet and outlet ports 61 and 62 is only two in all for each printed circuit board 10, hence the required number of tubes can be markedly decreased in the case of testing the electronic devices 3 on a plurality of such printed circuit boards 10 that are stacked in
25 semiconductor test equipment. This is effective in downsizing the semiconductor test equipment.

Figs. 9A and 9B illustrate a modified form of the embodiment shown in Figs. 8A and 8B. In this embodiment, the

inlet port 14 is omitted and the outlet ports 62' and 62 are made in the end wall 22c of the lower sealed case at positions corresponding to the inlet ports 61' and 61 of the upper sealed case so as to provide only one coolant channel through all the electronic devices 3 in the both upper and lower cooling chambers 25. With such a structure, in the case of cooling the electronic devices 3 by the coolant at the same flow rate as in the Fig. 8 embodiment, the flow velocity is doubled, producing increased cooling efficiency.

10 In the Fig. 8 embodiment the ports 14 and 15, through which the upper and lower cooling chambers 25 communicate with each other, serve as coolant inlet and outlet ports for the lower cooling chamber 25. In the Fig. 9 embodiment the port 15 through which the upper and lower cooling chambers 25

15 communicate with each other serves both as a coolant outlet port for the upper cooling chamber 25 and as a coolant inlet port for the lower cooling chamber 25.

Turning next to Fig. 10, another embodiment of the present invention will be described, which is identical in construction with the Fig. 7 embodiment except the position of placement of each barrier 9. That is, in each compartment of the cooling chamber 25 separated by the partition wall 8, there are provided barriers 9 that stand upright from the bottom panel 21 (not shown) and extend in opposite directions from the side wall 22a (or 22b) and the partition wall 8 alternately every two electronic devices 3 in the row direction of their matrix array. The opposed side surfaces of adjacent barriers 9 define therebetween a central coolant

channel 252. Reference numeral 9' denotes independent barriers each planted on the bottom panel 21 for each quartet of neighboring electronic devices 3 and extended toward the side wall 22a (or 22b) and the partition wall 8 in the column direction across the cross-shaped clearance that separates the four electronic devices. Between the opposed end edges of the independent barriers 9' and the side wall 22a (or 22b) and the partition wall 8 there are defined by-pass channels 251. Thus, the barriers 9 and the independent barriers 9' are placed alternately in the row direction of the matrix array of the electronic devices 3. The independent barriers 9' are also nearly equal in height to the side walls and the end walls. As mentioned above, the independent barriers 9' and the side wall or partition wall define therebetween the by-pass channels 251 and adjacent barriers 9 extended from the side wall and the partition wall toward each other define therebetween the central channel.

The coolant 7 flowing into the cooling chamber 25 through the inlet ports 61 and 61' is first diverted by the independent barrier 9' closest to the inlet port 61' into by-pass channels 251 as indicated by the arrow 71 and the diverted streams of the coolant 7 join downstream of the first independent barrier 9' and are mixed with each other. The coolant 7 thus joined and mixed flows through the central channel 252, then it is split again by the next independent barrier 9' into two streams flowing into the by-pass channels as indicated by the arrow 71 and the two streams join and are mixed downstream of this independent barrier 9'. Thereafter,

the coolant 7 cools the electronic devices 3 while repeatedly flowing through the by-pass and central channels and it ultimately flows out of the cooling chamber 25 through the outlet ports 62' and 62.

5 In this embodiment, the coolant 7 is blocked and split by each independent barrier 9' into two streams flowing through the by-pass channels 251 as indicated by the arrow 71 and the two streams strike against each other downstream of the independent barrier 9', and hence they are sufficiently mixed
10 together. As the result of this, the temperature of the coolant 7 is made uniform throughout it and the coolant 7 does not form high and low temperature laminar flows. Hence, the cooling efficiency increases accordingly.

Turning next to Fig. 11, another embodiment of the
15 present invention will be described. In this embodiment, the barriers 9 in Figs. 7, 8 or 9 each has one or more through holes drilled therethrough. As described above, the coolant 7 injected into the cooling chamber 25 through the inlet ports 61 and 61' is stirred by striking against the barriers
20 9 and cools the electronic devices 3 while meandering therethrough as indicated by the arrows 71. In this instance, however, the coolant 7 tends to stagnate near the back of each barrier 9, especially at the corner between the side wall 22a (22b) and the partition wall--this gives rise
25 to a problem that the electronic device 3 just behind each barrier 9 is less cooled than the electronic device 3 just in front of the barrier 9.

As a solution to this problem, in the Fig. 11 embodiment

one or more through holes 91 are bored through each barrier 9 and the coolant 7 which would otherwise stagnate in the vicinity of the barrier 9 flows directly to its back through the through holes 91, so that no stagnation of the coolant 7
5 does not occur. Also in the Fig. 10 embodiment, the through holes 91 may be formed through the independent barriers 9' to prevent stagnation of the coolant 7 near the center of the back of each barrier 9'. By forming such through holes through the barriers in the other embodiments, too, the same
10 effect as mentioned above can be produced.

In each of the embodiments described above, when it is necessary to mount electronic devices of relatively small calorific power on the same printed circuit board 10 together with electronic devices of large calorific power, the former
15 may be mounted on the printed circuit board 10 outside the sealed case 20 as indicated by reference numeral 3' in Fig. 12 and cooled by a forced cooling fan 150 as shown. In Fig. 12 a plurality of electronic-devices-mounted, printed circuit boards 10 are mounted in parallel on a board mounting frame
20 110 of semiconductor test equipment and the cooling fan motor 150 is fixedly mounted on the board mounting frame 110 below the printed circuit boards 10. The cooling fan motor 150 blows air in parallel to the printed circuit boards 10 to cool the electronic devices 3' mounted thereon. When the
25 electronic devices 3 of large calorific power and the electronic devices 3' of relatively small calorific power are mounted on the same printed circuit board 10, the packing density of the former on the printed circuit board 10 could

be increased up to a value about the same as the packing density of the latter, by forced cooling of the electronic devices 3 by the coolant 7 in the cooling chamber 24 as described above.

5 Finally, a description will be given, with reference to Figs. 13A, 13B and 13C, of structures for mounting the cooler-equipped printed circuit board on semiconductor test equipment.

10 In Fig. 13A, reference numeral 100 denotes guides that form part of the semiconductor test equipment (not shown). The guides 100 each have a guide groove 102 cut therein and guide the cooler-equipped printed circuit board 10 with its two opposed marginal edges slidably received in the grooves 102. The printed circuit board 10 with its marginal edges 13
15 fitted in the guide grooves 102 is guided by the guides 100 into the test equipment and fixed thereto.

20 In Fig. 13B, the opposed side walls 22a and 22b of the sealed case 20 of the cooler have projections 29 that are slidably received in the guide grooves 102 of the guides 100. The printed circuit board 100 with the projections 29 fitted in the guide grooves 102 is guided by the guides 100 into the test equipment.

25 In Fig. 13C, reference numeral 101 denotes guide rails or projections forming part of the semiconductor test equipment. The opposed side walls 22a and 22b of the sealed case 20 each have a groove 29' for receiving one of the guide projections 101. The printed circuit board 10 with the guide projections 101 slidably received in its grooves 29' is guided along the

guide projections 101 into the test equipment.

Thus, the cooler-equipped printed circuit board can be singly mounted on and dismounted from the semiconductor test equipment. While in the above embodiments the partition wall 5 8, the barriers 9 and the independent barriers 9' have been described to be extended from the sealed case 20, they may be planted on the printed circuit board 10. Further, the electronic devices 3 are not limited specifically to LSIs but may be any kinds of heat-generating electronic devices.

10 EFFECT OF THE INVENTION

As described above, according to the present invention, the sealed case 20 is mounted on the printed circuit board 10 in a manner to cover the electronic devices mounted thereon and the coolant 7 is injected into the sealed case 20 wherein 15 it flows through the electronic devices 3 for forced absorption of heat generated by them, so that the electronic devices 3 can be cooled more efficiently than in the case of forced air cooling or cooling by natural convection of a coolant. With the provision of the barriers 9 (9') in the 20 sealed case 20, the coolant 7 is effectively stirred and has a uniform temperature distribution, achieving a particularly high cooling efficiency. By forced circulation of the coolant 7 through the cooling chamber 25 at high pressure, the cooling effect can be further heightened.

25 With the provision of the inlet and outlet ports 14 and 15 bored through the printed circuit board 10 near the inlet and outlet ports 61' and 62', respectively, the coolant 7 can be distributed equally through the cooling chambers 25 on

both sides of the printed circuit board 10 although one inlet port 61 and one outlet port 62 are provided for the two sealed cases 20. In addition, the provision of such ports does not introduce any particular complexity in the liquid cooling arrangement. That is, the number of tubes that must be connected to the inlet and outlet ports 61 and 62 is only two in all for each printed circuit board 10, hence the required number of tubes can be markedly decreased in the case of testing the electronic devices 3 on a plurality of such printed circuit boards 10 that are stacked in semiconductor test equipment. This is effective in downsizing the semiconductor test equipment.

Furthermore, the coolant 7 is blocked and split by each independent barrier 9' into two streams flowing through the by-pass channels 251 as indicated by the arrow 71 and the two streams strike against each other downstream of the independent barrier 9', and hence the coolant 7 is sufficiently stirred. As the result of this, the temperature of the coolant 7 is made uniform throughout it and the coolant 7 does not form high and low temperature laminar flows. Hence, the cooling efficiency increases accordingly.

With the provision of one or more through holes 91 bored through each barrier 9, the coolant 7 which would otherwise stagnate in the vicinity of the barrier 9 flows directly to its back through the through holes 91, so that no stagnation of the coolant 7 does not occur. By forming such through holes 91 through the independent barriers 9', it is possible to prevent the coolant 7 from stagnation near the center of

the back of each barrier 9'.

By fitting the elastic O ring packing 4 into the groove 28 cut in the marginal edge 26 of each sealed case 20 on the printed circuit board 10, excellent sealing means 27 can be
5 obtained. In this case, the liquidtightness is increased by the metallic pattern 14 which is predeposited on the surface area of the printed circuit board 10 for engagement with the marginal edge 26. The metallic pattern 14 is formed by depositing a copper pattern on the surface of the printed
10 circuit board 10 or plating the copper pattern with gold. The plating the metallic pattern 14 with gold ensures long-term liquidtightness of the sealing means 27.

By adopting an arrangement for guiding the printed circuit board into semiconductor test equipment by the guides
15 100 or guide projections 101 that form part of the test equipment, the printed circuit board 10 can be singly mounted on or dismounted from the test equipment.

It will be apparent that many modifications and variations may be effected without departing from the scope
20 of the novel concepts of the present invention.



THIS SHEET HAS BEEN
REPLACED

WHAT IS CLAIMED IS:

1. An electronic-devices-mounted, printed circuit board comprising:

a printed circuit board with an array of electronic devices mounted on at least one side thereof; and

a sealed case that covers said array of electronic devices, has its marginal edge held in liquidtight contact with said one side of said printed circuit board all around said array of electronic devices and has an inlet port for injecting a coolant into said sealed case from the outside and an outlet port for discharging said coolant from said sealed case to the outside;

wherein the interior of said sealed case forms a cooling chamber in which said electronic devices are immersed in said coolant injected through said inlet port and said coolant is distributed through said electronic devices and discharged to the outside through said outlet port.

2. The printed circuit board of claim 1, wherein said cooling chamber has a plurality of barriers each extending into one of spaces between said electronic devices in the direction across their array so that a coolant channel from said inlet port to said outlet port meanders.

3. The printed circuit board of claim 2, wherein: said sealed case has a box-like configuration composed of a bottom panel and a pair of opposed side walls extending in the direction of said electronic device array; said electronic devices are spaced apart; and said barriers are extended between said electronic devices across their array





THIS SHEET HAS BEEN REPLACED

alternately from one and the other of said opposed side walls to define clearances by the extending ends of said barriers and said side walls opposite them, respectively, thereby making said coolant channel from said inlet port to said outlet port meander.

4. The printed circuit board of claim 3, wherein said electronic device array is a 3 by 2 matrix array.

5. The printed circuit board of claim 3 or 4, wherein said barriers are each extended from said bottom panel to said printed circuit board.

6. The printed circuit board of claim 2, wherein said electronic device array is a matrix array and said barriers are staggered so that they do not overlap in the column direction of said matrix array.

7. The printed circuit board of claim 6, wherein said matrix array of electronic devices is a matrix with at least 3 rows and at least 2 columns and said barriers are disposed so that the barriers in two arbitrary adjacent spaces between the electronic devices in the row direction are alternately extended across the spaces between said electronic devices in the column direction.

8. The printed circuit board of claim 1, wherein: said sealed case has a box-like configuration composed of a bottom panel, a pair of opposed side walls extending in the direction of said electronic device array, and a pair of opposed end walls joining opposite ends of said side walls, respectively; and a partition wall is extended from one of said end walls toward the other of them to form a clearance





between the extended end of said partition wall and said other end wall and divide said matrix array of electronic devices in its column direction into two sub-matrix arrays, thereby providing a substantially U-shaped coolant channel from said inlet port to said outlet port in said cooling chamber.

9. The printed circuit board of claim 8, wherein said matrix array is an array with four columns of electronic devices and at least three rows of electronic devices; each of said two sub-matrix arrays is an array of two columns of electronic devices; barriers are extended from said partition wall and each of said side walls and alternately projecting into spaces in the row direction defined by said electronic devices of said two columns of each of said two sub-matrix array; and the extended ends of said barriers are spaced apart from said partition wall and said one side wall to make said U-shaped coolant channel meander.

10. The printed circuit board of claim 9, wherein: said partition wall is extended from said bottom panel and one of said end walls and has the same height as said side walls and said end walls; said barriers are extended from at least one of said bottom panel, said side walls and said partition wall and have the same height as said side walls and said partition wall; and the extended ends of said barriers in the row direction and said side wall and said partition wall in the direction of extension of said barriers define therebetween clearances which permit the passage therethrough of said coolant.





11. The printed circuit board of claim 8, further comprising: independent barriers each inserted in one of alternate spaces between said electronic devices of each sub-matrix array in the row direction thereof and extended across the space between said electronic devices in the column direction of their array, both ends of each of said independent barriers being opposed to and spaced apart from each of said side walls and said partition wall to define therebetween coolant by-pass channels; and two barriers alternately extended from said each side wall and said partition wall toward each other and projecting into said spaces adjacent to said alternate ones between said electronic devices in the row direction of their array, the extended ends of said two barriers being opposed to and spaced apart from each other to define therebetween central channel.

12. The printed circuit board of claim 11, wherein said partition wall, said barriers and said independent barriers are formed integrally with said bottom panel to about the same height as said side walls and said end walls.

13. The printed circuit board of claim 9, wherein said barriers are formed integrally with said bottom panel.

14. The printed circuit board of claim 9, wherein said barriers are fixed to said printed circuit board.

15. The printed circuit board of claim 11, wherein said barriers and said independent barriers are fixed to said printed circuit board.

16. The printed circuit board of claim 9 or 10, wherein





THIS SHEET HAS BEEN
REPLACED

said barriers each have a through hole.

17. The printed circuit board of claim 11, wherein said barriers and said independent barriers each have a through hole.

18. The printed circuit board of any one of claims 1, 2, 3, 8, 8 and 11, further comprising a sealing means composed of a groove cut in the marginal edge of said sealed case all around it and an elastic O ring packing fitted in said groove and pressed against said printed circuit board.

19. The printed circuit board of claim 18, wherein a metallic pattern is predeposited over the surface area of said printed circuit board against which said elastic O ring packing fitted in said groove cut in said marginal edge of said sealed case is pressed to provide liquidtight sealing.

20. The printed circuit board of claim 19, wherein said metallic pattern is a copper pattern.

21. The printed circuit board of claim 19, wherein said metallic pattern is plated with gold.

22. The printed circuit board of any one of claims 1, 2, 3, 8, 9 and 11, further comprising another array of electronic devices mounted on the other side of said printed circuit board, and a second sealed case mounted on said other surface of said printed circuit board in a liquidtight manner for sealing therein said electronic devices.

23. The printed circuit board of claim 22, further comprising a port bored through said printed circuit board in the vicinity of said inlet port to inject therethrough said coolant into said second sealed case and another port bored





through said printed circuit board in the vicinity of said outlet port to discharge therethrough said coolant from said second sealed case.

24. The printed circuit board of any one of claims 1, 2, 3, 8, 9 and 11, further comprising a second electronic device disposed on said printed circuit board but outside said sealed case so that it is subjected to forced cooling.

25. The printed circuit board of any one of claims 1, 2, 3, 8, 9 and 11, wherein projections protrusively provided on two opposed marginal edges of said printed circuit board for engagement with guide grooves of guide means of semiconductor test equipment.

26. The printed circuit board of any one of claims 1, 2, 3, 8, 9 and 11, wherein projections protrusively provided on two opposed side walls of said sealed case for engagement with guide grooves of guide means of semiconductor test equipment.

27. The printed circuit board of any one of claims 1, 2, 3, 8, 9 and 11, wherein grooves are cut in two opposed side walls of said sealed case for engagement with guide projections of semiconductor test equipment.

THIS SHEET HAS BEEN
REPLACED



ABSTRACT OF THE DISCLOSURE

A cooler-equipped printed circuit board, in which electronic devices arranged in a matrix form on the printed circuit board are covered with a sealed case held in liquidtight contact with the board and having a coolant channel from an inlet port and an outlet port made in the case. Barriers are provided in the coolant channel to change the direction of flow of the coolant to stir it and make its temperature uniform throughout it.

THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



FIG. 1A






FIG. 1B



THIS SHEET HAS BEEN REPLACED

FIG. 2




THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced




FIG. 3A



THIS SHEET HAS BEEN REPLACED

FIG. 3B



This Sheet Has Been Replaced



FIG. 4





FIG. 5


THIS SHEET HAS BEEN REPLACED



This Sheet Has Been Replaced



FIG. 6



THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



This Sheet Has Been Replaced



FIG. 8A





FIG. 8



THIS SHEET HAS BEEN REPLACED

FIG. 9A





FIG. 9B




This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

FIG. 10




THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



FIG. 11




THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



FIG. 12



THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



FIG. 13A




FIG. 13B





FIG. 13C



**THIS SHEET HAS BEEN
REPLACED**

This Sheet Has Been Replaced




PRINTED CIRCUIT BOARD WITH ELECTRONIC DEVICES MOUNTED THEREON

ABSTRACT OF THE DISCLOSURE

A cooler-equipped printed circuit board, in which electronic devices arranged in a matrix form on the printed circuit board are covered with a sealed case held in liquidtight contact with the board and having a coolant channel from an inlet port and an outlet port made in the case. Barriers are provided in the coolant channel to change the direction of flow of the coolant to stir it and make its temperature uniform throughout it.

Figure 3A



THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



FIG. 1A





FIG. 1B



REPLACEMENT SHEET

18 SEP 1997




FIG. 2




FIG. 3A





FIG. 3B






FIG. 4




FIG. 5




FIG. 6





FIG. 7A






FIG. 7B



THIS SHEET HAS BEEN
REPLACED

- 7 -

REPLACEMENT SHEET
18 SEP 1997

FIG. 8A






FIG. 8



This Sheet Has Been Replaced



REPLACEMENT SHEET

18 SEP 1997

FIG. 9A






FIG. 9B



18 SEP 1997

FIG. 10







FIG. 11





FIG. 12






FIG. 13A




FIG. 13B





FIG. 13C





WHAT IS CLAIMED IS:

1. An electronic-devices-mounted, printed circuit board comprising:

a printed circuit board (10) with an array of electronic devices (3) mounted on at least one side thereof; and

a sealed case (20) that covers said array of electronic devices, has its marginal edge held in liquidtight contact with said one side of said printed circuit board all around said array of electronic devices and has an inlet port (61) for injecting a coolant (7) into said sealed case from the outside and an outlet port (62) for discharging said coolant from said sealed case to the outside;

wherein the interior of said sealed case (20) forms a cooling chamber in which said electronic devices (3) are immersed in said coolant injected through said inlet port and said coolant is distributed through said electronic devices and discharged to the outside through said outlet port (62); and

wherein: said sealed case (20) has a box-like configuration composed of a bottom panel (21), a pair of opposed side walls (22a, 22b) extending in the direction of said electronic device array, and a pair of opposed end walls (22c, 22d) joining opposite ends of said side walls (22a, 22b), respectively; and a partition wall (8) is extended from one of said end walls toward the other of them to form a clearance between the extended end of said partition wall (8) and said other end wall and divide said matrix array of electronic devices in its column direction into two sub-matrix arrays, thereby providing a substantially U-shaped coolant

REPLACEMENT SHEET

01 NOV 1999

9702732-0
1/11/99



channel from said inlet port (61) to said outlet port (62) in said cooling chamber (25).

2. An electronic-devices-mounted, printed circuit board comprising:

a printed circuit board (10) with an array of electronic devices (3) mounted on at least one side thereof;

a sealed case (20) that covers said array of electronic devices, has its marginal edge held in liquidtight contact with said one side of said printed circuit board all around said array of electronic devices and has an inlet port (61) for injecting a coolant (7) into said sealed case from the outside and an outlet port (62) for discharging said coolant (7) from said sealed case (20) to the outside; and

a sealing means composed of a groove (28) cut in the marginal edge of said sealed case (20) all around it and an elastic O ring packing (4) fitted in said groove (28) and pressed against said printed circuit board (10);

wherein the interior of said sealed case forms a cooling chamber (25) in which said electronic devices (3) are immersed in said coolant injected through said inlet port (61) and said coolant (7) is distributed through said electronic devices and discharged to the outside through said outlet port (62).

3. An electronic-devices-mounted, printed circuit board comprising:

a printed circuit board (10) with an array of electronic devices (3) mounted on at least one side thereof;

a sealed case (20) that covers said array of electronic

REPLACEMENT SHEET

01 NOV 1999



devices, has its marginal edge held in liquidtight contact with said one side of said printed circuit board all around said array of electronic devices and has an inlet port (61) for injecting a coolant (7) into said sealed case from the outside and an outlet port (62) for discharging said coolant (7) from said sealed case (20) to the outside; and

another array of electronic devices (3) mounted on the other side of said printed circuit board (10), and a second sealed case (20) mounted on said other surface of said printed circuit board in a liquidtight manner for sealing therein said electronic devices;

wherein the interior of said sealed case forms a cooling chamber (25) in which said electronic devices (3) are immersed in said coolant injected through said inlet port (61) and said coolant (7) is distributed through said electronic devices and discharged to the outside through said outlet port (62).

4. An electronic-devices-mounted, printed circuit board comprising:

a printed circuit board (10) with an array of electronic devices (3) mounted on at least one side thereof;

a sealed case (20) that covers said array of electronic devices, has its marginal edge held in liquidtight contact with said one side of said printed circuit board all around said array of electronic devices and has an inlet port (61) for injecting a coolant (7) into said sealed case from the outside and an outlet port (62) for discharging said coolant (7) from said sealed case (20) to the outside; and

REPLACEMENT SHEET

01 NOV 1999



a second electronic device (3') disposed on said printed circuit board (10) but outside said sealed case (20) so that it is subjected to forced cooling;

wherein the interior of said sealed case forms a cooling chamber (25) in which said electronic devices (3) are immersed in said coolant injected through said inlet port (61) and said coolant (7) is distributed through said electronic devices and discharged to the outside through said outlet port (62).

5. An electronic-devices-mounted, printed circuit board comprising:

a printed circuit board (10) with an array of electronic devices (3) mounted on at least one side thereof;

a sealed case (20) that covers said array of electronic devices, has its marginal edge held in liquidtight contact with said one side of said printed circuit board all around said array of electronic devices and has an inlet port (61) for injecting a coolant (7) into said sealed case from the outside and an outlet port (62) for discharging said coolant (7) from said sealed case (20) to the outside; and

projections (13) protrusively provided on two opposed marginal edges of said printed circuit board (10) for engagement with guide grooves (102) of guide means (100) of semiconductor test equipment;

wherein the interior of said sealed case forms a cooling chamber (25) in which said electronic devices (3) are immersed in said coolant injected through said inlet port (61) and said coolant (7) is distributed through said electronic devices and

REPLACEMENT SHEET

01 NOV 1999



discharged to the outside through said outlet port (62).

6. An electronic-devices-mounted, printed circuit board comprising:

a printed circuit board (10) with an array of electronic devices (3) mounted on at least one side thereof;

a sealed case (20) that covers said array of electronic devices, has its marginal edge held in liquidtight contact with said one side of said printed circuit board all around said array of electronic devices and has an inlet port (61) for injecting a coolant (7) into said sealed case from the outside and an outlet port (62) for discharging said coolant (7) from said sealed case (20) to the outside; and


projections (29) protrusively provided on two opposed side walls (22a, 22b) of said sealed case for engagement with guide grooves (102) of guide means (100) of semiconductor test equipment;

wherein the interior of said sealed case forms a cooling chamber (25) in which said electronic devices (3) are immersed in said coolant injected through said inlet port (61) and said coolant (7) is distributed through said electronic devices and discharged to the outside through said outlet port (62).

7. An electronic-devices-mounted, printed circuit board comprising:

a printed circuit board (10) with an array of electronic devices (3) mounted on at least one side thereof;

a sealed case (20) that covers said array of electronic devices, has its marginal edge held in liquidtight contact with





said one side of said printed circuit board all around said array of electronic devices and has an inlet port (61) for injecting a coolant (7) into said sealed case from the outside and an outlet port (62) for discharging said coolant (7) from said sealed case (20) to the outside; and

grooves (29') are cut in two opposed side walls (22a, 22b) of said sealed case for engagement with guide projections (101) of semiconductor test equipment;

wherein the interior of said sealed case forms a cooling chamber (25) in which said electronic devices (3) are immersed in said coolant injected through said inlet port (61) and said coolant (7) is distributed through said electronic devices and discharged to the outside through said outlet port (62).

8. The printed circuit board of any one of claims 1 through 7, wherein said cooling chamber (25) has a plurality of barriers (24) each extending into one of spaces between said electronic devices in the direction across their array so that a coolant channel from said inlet port to said outlet port meanders.

9. The printed circuit board of any one of claims 8, wherein: said sealed case (20) has a box-like configuration composed of a bottom panel (21) and a pair of opposed side walls (22a, 22b) extending in the direction of said electronic device array; said electronic devices are spaced apart; and said barriers (24) are extended between said electronic devices across their array alternately from one and the other of said opposed side walls (22a, 22b) to define clearances by the extending ends of said barriers (24) and said side walls opposite them, respectively,

REPLACEMENT SHEET

01 NOV 1999



thereby making said coolant channel from said inlet port to said outlet port meander.

10. The printed circuit board of claim 9, wherein said electronic device array is a 3 by 2 matrix array.

11. The printed circuit board of claim 9 or 10, wherein said barriers (24) are each extended from said bottom panel (21) to said printed circuit board.

12. The printed circuit board of claim 8, wherein said electronic device array is a matrix array and said barriers (24) are staggered so that they do not overlap in the column direction of said matrix array.

13. The printed circuit board of claim 12, wherein said matrix array of electronic devices (3) is a matrix with at least 3 rows and at least 2 columns and said barriers (24) are disposed so that the barriers in two arbitrary adjacent spaces between the electronic devices in the row direction are alternately extended across the spaces between said electronic devices in the column direction.

14. The printed circuit board of claim 1, wherein said matrix array is an array with four columns of electronic devices and at least three rows of electronic devices (3); each of said two sub-matrix arrays is an array of two columns of electronic devices; barriers (9) are extended from said partition wall (8) and each of said side walls (22a, 22b) and alternately projecting into spaces in the row direction defined by said electronic devices (3) of said two columns of each of said two sub-matrix array; and the extended ends of said barriers are spaced apart from said

REPLACEMENT SHEET


01 NOV 1999



partition wall and said one side wall to make said U-shaped coolant channel meander.

15. The printed circuit board of claim 14, wherein: said partition wall (8) is extended from said bottom panel (21) and one of said end walls (22c, 22d) and has the same height as said side walls (22a, 22b) and said end walls (22c, 22d); said barriers (9) are extended from at least one of said bottom panel (21), said side walls and said partition wall and have the same height as said side walls and said partition wall (8); and the extended ends of said barriers in the row direction and said side wall and said partition wall in the direction of extension of said barriers define therebetween clearances which permit the passage therethrough of said coolant.

16. The printed circuit board of claim 14, further comprising: independent barriers (9') each inserted in one of alternate spaces between said electronic devices (3) of each sub-matrix array in the row direction thereof and extended across the space between said electronic devices in the column direction of their array, both ends of each of said independent barriers (9') being opposed to and spaced apart from each of said side walls (22a, 22b) and said partition wall to (8) define therebetween coolant by-pass channels (251); and two barriers alternately extended from said each side wall and said partition wall toward each other and projecting into said spaces adjacent to said alternate ones between said electronic devices in the row direction of their array, the extended ends of said two barriers being opposed to and spaced apart from each other to define therebetween central





channel (252).

17. The printed circuit board of claim 16, wherein said partition wall (8), said barriers (9) and said independent barriers (9') are formed integrally with said bottom panel (21) to about the same height as said side walls and said end walls.

18. The printed circuit board of claim 14, wherein said barriers (9) are formed integrally with said bottom panel (21).

19. The printed circuit board of claim 14, wherein said barriers (9) are fixed to said printed circuit board (10).

20. The printed circuit board of claim 16, wherein said barriers (9) and said independent barriers (9') are fixed to said printed circuit board (10).

21. The printed circuit board of claim 14 or 15, wherein said barriers (9) each have a through hole.

22. The printed circuit board of claim 16, wherein said barriers (9) and said independent barriers (9') each have a through hole (91).

23. The printed circuit board of any one of claims 1, 14 and 16, further comprising a sealing means composed of a groove (28) cut in the marginal edge of said sealed case (20) all around it and an elastic O ring packing (4) fitted in said groove (28) and pressed against said printed circuit board (10).

24. The printed circuit board of claim 23, wherein a metallic pattern (11) is predeposited over the surface area of said printed circuit board against which said elastic O ring packing (4) fitted in said groove (28) cut in said marginal edge of said sealed case (20) is pressed to provide liquidtight sealing.

REPLACEMENT SHEET

01 NOV 1999



25. The printed circuit board of claim 24, wherein said metallic pattern (11) is a copper pattern.

26. The printed circuit board of claim 24, wherein said metallic pattern (11) is plated with gold.


27. The printed circuit board of any one of claims 1, 14 and 16, further comprising another array of electronic devices (3) mounted on the other side of said printed circuit board (10), and a second sealed case (20) mounted on said other surface of said printed circuit board in a liquidtight manner for sealing therein said electronic devices.

28. The printed circuit board of claim 27, further comprising a port (14) bored through said printed circuit board in the vicinity of said inlet port (61) to inject therethrough said coolant into said second sealed case and another port (15) bored through said printed circuit board (10) in the vicinity of said outlet port (62) to discharge therethrough said coolant from said second sealed case.

29. The printed circuit board of any one of claims 1, 14 and 16, further comprising a second electronic device (3') disposed on said printed circuit board (10) but outside said sealed case (20) so that it is subjected to forced cooling.

30. The printed circuit board of any one of claims 1, 14 and 16, wherein projections (13) protrusively provided on two opposed marginal edges of said printed circuit board (10) for engagement with guide grooves (102) of guide means (100) of semiconductor test equipment.


31. The printed circuit board of any one of claims 1, 14 and





16, wherein projections (29) protrusively provided on two opposed side walls (22a, 22b) of said sealed case for engagement with guide grooves (102) of guide means (100) of semiconductor test equipment.

32. The printed circuit board of any one of claims 1, 14 and 16, wherein grooves (29') are cut in two opposed side walls (22a, 22b) of said sealed case for engagement with guide projections (101) of semiconductor test equipment.



PRINTED CIRCUIT BOARD WITH ELECTRONIC DEVICES MOUNTED THEREON

ABSTRACT OF THE DISCLOSURE

A cooler-equipped printed circuit board, in which electronic devices arranged in a matrix form on the printed circuit board are covered with a sealed case held in liquidtight contact with the board and having a coolant channel from an inlet port and an outlet port made in the case. Barriers are provided in the coolant channel to change the direction of flow of the coolant to stir it and make its temperature uniform throughout it.

Figure 3A




FIG. 8A




FIG. 8

