

METHOD, LOADED PALLET AND LOADED VEHICLE FOR MAXIMIZING SHIPPING EFFICIENCY OF
ABSORBENT ARTICLES

FIELD OF THE INVENTION

The present disclosure relates generally to absorbent products, and more particularly, to methods of maximizing product delivery and shipping of absorbent articles having a substantially airfelt free absorbent core.

BACKGROUND OF THE INVENTION

Absorbent articles, such as disposable diapers, pant style diapers, training pants, adult incontinence undergarments, absorbent inserts, and the like absorb and contain body exudates. Such absorbent articles are intended to prevent body exudates from soiling, wetting, or otherwise contaminating clothing or other articles, such as bedding, that come into contact with a wearer of the absorbent articles. Absorbent articles may be worn for several hours in a dry state or in a urine (or other body exudates) loaded state. Efforts are made to constantly improve the fit and comfort of such absorbent articles both in the wet and dry state.

Many current absorbent articles, particularly those with airfelt (or cellulose) absorbent cores are soft and flexible when first placed in an undergarment, but become more stiff when wet. Such flexible-then stiff characteristics are seen in absorbent articles with other types of cores as well. Additionally, such airfelt (or cellulose) absorbent articles are typically bulky. Overall, traditional absorbent articles that utilize airfelt (or cellulose) are bulky and somewhat uncomfortable to wear.

Moreover, such airfelt (or cellulose) absorbent articles are inefficient to ship as the large amount of airspace in such articles (for example, between the cellulose fibers) translates into fewer absorbent articles per package and fewer packages per box. While product compression may increase packing efficiency of airfelt (or cellulose) absorbent articles, over compression reduces the absorbency effectiveness of such absorbent articles. Additionally, over compression can reduce aesthetic appeal of such absorbent articles by making the product stiff and uncomfortable to wear, or by reducing the apparent softness of individual components of the absorbent article, such as the absorbent core. Quite often, when absorbent pads containing cellulose are compressed to achieve a thin form, hard spots develop within the pads, thereby resulting in a stiffer pad and a lack of uniformity in the absorbent material.

Due to the high volume/weight ratio of traditional airfelt absorbent articles, most often shipping and packing of such articles is limited by volume instead of weight. In other words, a maximum container or vehicle volume is reached before a maximum container or vehicle weight capacity is reached when packing and/or shipping the traditional airfelt absorbent articles. This results in a shipping inefficiency due to the fact that the maximum weight bearing capacity of the container or vehicle is not being fully utilized. Essentially, shipping capacity is lost due to the amount of air within the absorbent articles that are being shipped.

Improvements have been made to absorbent articles, such as disposable diapers, by including an absorbent polymer material (sometimes known as superabsorbent polymers), such as an absorbent particulate polymer material. Absorbent particulate polymer material absorbs liquid and swells and may be particularly effective when the absorbent particulate polymer is disposed in a particular pattern, arrangement, or matrix that optimizes absorbency, fit and/or comfort. Combinations of airfelt cores and absorbent polymer materials produce diapers that are thinner, more flexible, and more absorbent than previous diapers. This type of diaper construction is now prevalent and has been in use for some time. However, these diapers are still viewed to some extent as being bulky, stiff when wet, and inefficient to ship to various store locations.

It is therefore desirable to have an even thinner, less bulky diaper that is more comfortable to use, remains flexible when wet, and more cost effective to ship to various store locations. One option to reduce bulk is to reduce or eliminate airfelt from the absorbent core. The difficulty with this approach is that it would also necessitate the absorbent particulate polymer material remaining fixed in its intended location within the absorbent article without the airfelt core to help immobilize the material, regardless of whether the absorbent article is dry or wet. Several recent publications have disclosed diapers with reduced or eliminated airfelt cores combined with immobilized absorbent particulate polymer materials. For example, an absorbent article having a substantially airfelt free absorbent core is disclosed in U.S. Patent Publication No. 2008/0312617, which is hereby incorporated by reference herein.

In addition, typical computerized pallet loading software cannot improve loading of absorbent articles beyond a characteristic volume/weight ratio based on assumed inherent properties of the product being shipped. Such known computerized pallet loading software usually includes assumptions that continuous improvements in size and material reduction of absorbent articles will yield ever increasing shipping efficiency. However, such known

computerized pallet loading software does not account for optimization processes that produce synergistic benefits associated with discontinuous improvements in product performance and physical parameters such as compressibility. As a result, known computerized pallet loading software fails to fully optimize shipping efficiency for most absorbent articles.

While the aforementioned application discloses an absorbent core for an absorbent article having a substantially airfelt free absorbent core, a need still exists for a mechanism to avoid hard, stiff spots in the article upon compressing to fit in a package. There further exists a need for a mechanism to fully optimize product delivery and shipping for such articles (optimization from the point of view of more articles per unit volume and less packaging per number of articles packed). These types of shipping efficiencies reduce the environmental impact of shipping such articles by reducing the number of pallets and the number of trucks needed to ship the articles to various store locations and warehouses.

SUMMARY OF THE INVENTION

In one embodiment, a shipping optimization process for absorbent articles having a substantially airfelt free absorbent core is disclosed. The shipping optimization process includes the steps of: identifying an optimized diaper; identifying an optimized bag for holding two or more optimized diapers; identifying an optimized box for holding two or more optimized bags; identifying an optimized pallet and arranging the optimized boxes thereon; and identifying an optimized load plan for a vehicle and arranging the optimized pallets therein. The vehicle has a calculated Load Factor of from about 0.75 to about 1.0 when the vehicle is loaded with the optimized pallets.

BRIEF DESCRIPTION OF THE DRAWINGS

While the specification concludes with claims which particularly point out and distinctly claim the subject matter that is regarded as the invention, it is believed the various embodiments will be better understood from the following description taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a plan view of an absorbent article having a substantially airfelt free absorbent core;

FIG. 2 is a cross sectional view of the absorbent article of FIG. 1;

FIG. 3 is a partial cross sectional view of an absorbent core layer of the absorbent article of FIGS. 1 and 2;

FIG. 4 is a partial cross sectional view of an absorbent core in accordance with another embodiment;

FIG. 5a is side view of a package of absorbent articles in accordance with one embodiment showing the package width. The outer surface is illustrated as transparent for purposes of clarity;

FIG. 5b is a side view of a package of absorbent articles in accordance with one embodiment showing the package height. The outer surface is illustrated as transparent for purposes of clarity;

FIG. 5c is a perspective view of a package of absorbent articles in accordance with one embodiment showing the package depth;

FIG. 6a is a front plan view showing a stiffness test apparatus with an upper fixture assembly and a lower fixture assembly.

FIG. 6b is a front plan view showing the stiffness test apparatus with the upper fixture assembly engaging a test specimen.

FIG. 7a is a side view of an absorbent article that has been bi-folded;

FIG. 7b is a side view of an absorbent article that has been tri-folded;

FIG. 8 is a logic diagram of a shipping optimization process in accordance with the teachings of the disclosure;

FIG. 9 is a logic diagram of the diaper optimization procedure of the optimization process of FIG. 4;

FIG. 10 is a logic diagram of the bag optimization procedure of the optimization process of FIG. 4;

FIG. 11 is a logic diagram of the box optimization procedure of the optimization process of FIG. 4;

FIGS. 12a to 12f are perspective views of different box and bag orientations that may be considered during the box optimization procedure of FIG. 11;

FIG. 13 is a logic diagram of the pallet optimization procedure of the optimization process of FIG. 8;

FIG. 14 is a logic diagram of the vehicle optimization procedure of the optimization process of FIG. 8; and

FIG. 15 is a schematic diagram of a load optimization system constructed in accordance with the teachings of the disclosure.

The figures herein are not necessarily drawn to scale.

DETAILED DESCRIPTION OF THE INVENTION

“Absorbent article” refers to devices that absorb and contain body exudates, and, more specifically, refers to devices that are placed against or in proximity to the body of the wearer to absorb and contain the various exudates discharged from the body. Absorbent articles may include diapers, training pants, and adult incontinence undergarments.

“Absorbent core” means a structure typically disposed between a topsheet and backsheet of an absorbent article for absorbing and storing liquid received by the absorbent article and may comprise one or more substrates, absorbent polymer material disposed on the one or more substrates, and a thermoplastic composition on the absorbent particulate polymer material and at least a portion of the one or more substrates for immobilizing the absorbent particulate polymer material on the one or more substrates. In a multilayer absorbent core, the absorbent core may also include a cover layer. The one or more substrates and the cover layer may comprise a nonwoven. Further, the absorbent core may be substantially cellulose free. The absorbent core includes the one or more substrates, the absorbent polymer material, the thermoplastic composition, optionally the cover layer and optionally auxiliary glue.

“Absorbent polymer material,” “absorbent gelling material,” “AGM,” “superabsorbent,” and “superabsorbent material” are used herein interchangeably and refer to substantially water-insoluble polymer particles that can absorb at least 5 times their weight of an aqueous 0.9% saline solution by way of an osmotic mechanism.

“Absorbent particulate polymer material” is used herein to refer to an absorbent polymer material which is in particulate form so as to be flowable in the dry state.

“Absorbent particulate polymer material area” as used herein refers to the area of the core wherein the first substrate and second substrate are separated by a multiplicity of superabsorbent particles. A boundary of the absorbent particulate polymer material area is defined by perimeters of overlapping shapes. There may be some extraneous superabsorbent particles outside of the perimeter between the first substrate and second substrate.

“Acquisition system” means a structure serving as a temporary reservoir for body fluids until the absorbent core can absorb the fluids. The acquisition system may be in direct contact

with the absorbent core and resides between topsheet and the backsheet. The acquisition system may comprise a single layer or multiple layers, such as an upper acquisition layer facing towards the wearer's skin and a lower acquisition layer facing the garment of the wearer. The acquisition system may function to receive a surge of liquid, such as a gush of urine.

"Airfelt," or "Cellulose" are used interchangeably herein and refer to comminuted wood pulp, which is a form of cellulosic fiber.

"Disposable" is used in its ordinary sense to mean an article that is disposed or discarded after a limited number of usage events over varying lengths of time, for example, less than about 20 events, less than about 10 events, less than about 5 events, or less than about 2 events.

"Diaper" refers to an absorbent article generally worn by infants and incontinent persons about the lower torso so as to encircle the waist and legs of the wearer and that is specifically adapted to receive and contain urinary and fecal waste. As used herein, term "diaper" also includes "pants" which is defined below.

"Fiber" and "filament" are used interchangeably.

A "nonwoven" is a manufactured sheet, web or batt of directionally or randomly orientated fibers, bonded by friction, and/or cohesion and/or adhesion, excluding paper and products which are woven, knitted, tufted, stitch-bonded incorporating binding yarns or filaments, or felted by wet-milling, whether or not additionally needled. The fibers may be of natural or man-made origin and may be staple or continuous filaments or be formed in situ. Commercially available fibers have diameters ranging from less than about 0.001 mm to more than about 0.2 mm and they come in several different forms: short fibers (known as staple, or chopped), continuous single fibers (filaments or monofilaments), untwisted bundles of continuous filaments (tow), and twisted bundles of continuous filaments (yarn). Nonwoven fabrics can be formed by many processes such as meltblowing, spunbonding, solvent spinning, electrospinning, and carding. The basis weight of nonwoven fabrics is usually expressed in grams per square meter (gsm).

"Infant" diaper refers to an absorbent article generally intended for babies that are from about 0 to 6 months old. Within this group of diapers, 4 sizes are common; premature infants (up to about 6 lbs), newborn infants (up to about 10 lbs), size 1 infants (generally from about 8 to 14 lbs), and size 2 infants (generally from about 12 to 18 lbs). It is common for design features of this type of diaper to focus on benefits such as softness and/or gentleness to skin.

“Baby” diaper refers to an absorbent article generally intended for babies that are from about 6 to 12 months old. Within this group of diapers, 5 sizes are common; size 3 (from about 16 to 28 lbs), size 4 (from about 22 to 37 lbs), size 5 (greater than about 27 lbs), size 6 (greater than about 35 lbs), and size 7 (greater than about 41 lbs). It is common for design features of this type of diaper to focus on benefits such as fit and stretch, thereby allowing the baby more flexibility in crawling or walking.

“Toddler” diaper refers to an absorbent article generally intended for babies that are older than about 12 months, and may be in life stage where they are learning to use a toilet facility. Within this group, there are 3 common sizes; size 4 (from about 16 to 34 lbs), size 5 (from about 30 to 40 lbs), and size 6 (greater than about 37 lbs). It is common for design features of this type of diaper to focus on benefits such as fit and ease of placement/removal, thereby allowing the baby more convenience as they are trained on toilet facility usage. These diapers may be designed as pants or training pants, as defined below, or may simply be larger size diapers. The overlapping weight ranges for the various sizes described above are to accommodate the various size and shapes of babies within each stage of development.

“Pant” or “training pant,” as used herein, refer to disposable garments having a waist opening and leg openings designed for infant or adult wearers. A pant may be placed in position on the wearer by inserting the wearer’s legs into the leg openings and sliding the pant into position about a wearer’s lower torso. A pant may be preformed by any suitable technique including, but not limited to, joining together portions of the article using refastenable and/or non-refastenable bonds (e.g., seam, weld, adhesive, cohesive bond, fastener, etc.). A pant may be preformed anywhere along the circumference of the article (e.g., side fastened, front waist fastened). While the terms “pant” or “pants” are used herein, pants are also commonly referred to as “closed diapers,” “prefastened diapers,” “pull-on diapers,” “training pants,” and “diaper-pants.” Suitable pants are disclosed in U.S. Pat. No. 5,246,433, issued to Hasse, et al. on Sep. 21, 1993; U.S. Pat. No. 5,569,234, issued to Buell et al. on Oct. 29, 1996; U.S. Pat. No. 6,120,487, issued to Ashton on Sep. 19, 2000; U.S. Pat. No. 6,120,489, issued to Johnson et al. on Sep. 19, 2000; U.S. Pat. No. 4,940,464, issued to Van Gompel et al. on Jul. 10, 1990; U.S. Pat. No. 5,092,861, issued to Nomura et al. on Mar. 3, 1992; U.S. Patent Publication No. 2003/0233082 A1, entitled “Highly Flexible And Low Deformation Fastening Device”, filed on Jun. 13, 2002; U.S. Pat. No. 5,897,545, issued to Kline et al. on Apr. 27, 1999; U.S. Pat. No. 5,957,908, issued to Kline et al on Sep. 28, 1999, each of which is hereby incorporated by reference.

“Substantially cellulose free” or “substantially airfelt free” is used herein to describe an article, such as an absorbent core, that contains less than 10% by weight cellulosic fibers, less than 5% cellulosic fibers, less than 1% cellulosic fibers, no cellulosic fibers, or no more than an immaterial amount of cellulosic fibers. An immaterial amount of cellulosic material would not materially affect the thinness, flexibility, or absorbency of an absorbent core. For example, the % by weight cellulose fiber for an absorbent core is calculated based upon using the total weight of absorbent particulate polymer material and cellulose fiber found in the absorbent core.

“Substantially continuously distributed” as used herein indicates that within the absorbent particulate polymer material area, the first substrate and second substrate are separated by a multiplicity of superabsorbent particles. It is recognized that there may be minor incidental contact areas between the first substrate and second substrate within the absorbent particulate polymer material area. Incidental contact areas between the first substrate and second substrate may be intentional or unintentional (e.g. manufacturing artifacts) but do not form geometries such as pillows, pockets, tubes, quilted patterns and the like.

“Thermoplastic adhesive material” as used herein is understood to comprise a polymer composition from which fibers are formed and applied to the superabsorbent material with the intent to immobilize the superabsorbent material in both the dry and wet state. The thermoplastic adhesive material of the present invention forms a fibrous network over the superabsorbent material.

“Thickness” and “caliper” are used herein interchangeably.

“In-Bag Compression” as used herein is one minus the height of a stack of 10 diaper pads in millimeters, measured while under compression within a poly-bag (In-Bag Stack Height), divided by the height of a stack of 10 diaper pads of the same type before compression, multiplied by 100; i.e., $(1 - \text{In-Bag Stack Height} / \text{stack height before compression}) \times 100$, reported as a percentage.

“Weight efficiency” as used herein refers to the net product and package weight of a transportation vehicle, such as a semi-trailer and tractor combination, divided by the maximum legal weight capacity of the vehicle on a percent basis. This weight efficiency is a numerical representation of the loading efficiency of a transportation vehicle in fully utilizing its maximum legally allowed weight capacity.

“Volume efficiency” as used herein refers to the net product and package volume of a transportation vehicle, such as a semi-trailer and tractor combination, divided by the volume

capacity of the vehicle on a percent basis. This volume efficiency is a numerical representation of the loading efficiency of a transportation vehicle in fully utilizing its maximum physical space intended for transporting products.

“Load factor” as used herein refers to the ratio of weight efficiency divided by volume efficiency for a transportation vehicle, such as a semi-trail and tractor combination, and is a numerical representation of how well a load of absorbent articles is optimized for both the weight and volume capacities of a particular transportation vehicle.

An absorbent article having a substantially airfelt free absorbent core is disclosed in U.S. Patent Publication No. 2008/0312617, owned by The Procter and Gamble Company, and hereby incorporated by reference herein. An absorbent article having a substantially airfelt free absorbent core, such as a diaper, is shown in FIG. 1. The diaper 10 is shown in its flat out, uncontracted state (i.e., without elastic induced contraction) and portions of the diaper 10 are cut away to more clearly show the underlying structure of the diaper 10. A portion of the diaper 10 that contacts a wearer is facing the viewer in FIG. 1. The diaper 10 generally may comprise a chassis 12 and an absorbent core 14 disposed in the chassis.

The chassis 12 of the diaper 10 in FIG. 1 may comprise the main body of the diaper 10. The chassis 12 may comprise an outer covering 16 including a topsheet 18, which may be liquid pervious, and/or a backsheet 20, which may be liquid impervious. The absorbent core 14 may be encased between the topsheet 18 and the backsheet 20. The chassis 12 may also include side panels 22, elasticized leg cuffs 24, and an elastic waist feature 26.

The leg cuffs 24 and the elastic waist feature 26 may each typically comprise elastic members 28. One end portion of the diaper 10 may be configured as a first waist region 30 of the diaper 10. An opposite end portion of the diaper 10 may be configured as a second waist region 32 of the diaper 10. An intermediate portion of the diaper 10 may be configured as a crotch region 34, which extends longitudinally between the first and second waist regions 30 and 32. The waist regions 30 and 32 may include elastic elements such that they gather about the waist of the wearer to provide improved fit and containment (elastic waist feature 26). The crotch region 34 is that portion of the diaper 10 which, when the diaper 10 is worn, is generally positioned between the wearer's legs.

The diaper 10 is depicted in FIG. 1 with its longitudinal axis 36 and its transverse axis 38. A periphery 40 of the diaper 10 is defined by the outer edges of the diaper 10 in which the longitudinal edges 42 run generally parallel to the longitudinal axis 36 of the diaper 10 and the

end edges 44 run between the longitudinal edges 42 generally parallel to the transverse axis 38 of the diaper 10. The chassis 12 may also comprise a fastening system, which may include at least one fastening member 46 and at least one stored landing zone 48.

The diaper 10 may also include such other features as are known in the art including front and rear ear panels, waist cap features, elastics and the like to provide better fit, containment and aesthetic characteristics. Such additional features are well known in the art and are e.g., described in U.S. Pat. No. 3,860,003 and U.S. Pat. No. 5,151,092, both of which are hereby incorporated by reference.

In order to keep the diaper 10 in place about the wearer, at least a portion of the first waist region 30 may be attached by the fastening members 46 to at least a portion of the second waist region 32 to form leg opening(s) and an article waist. When fastened, the fastening system carries a tensile load around the article waist. The fastening system may allow an article user to hold one element of the fastening system, such as the fastening member 46, and connect the first waist region 30 to the second waist region 32 in at least two places. This may be achieved through manipulation of bond strengths between the fastening device elements. In one embodiment, fastening member 46 may include tape tab fasteners, hook and loop fasteners, mushroom and loop fasteners, snaps, pins, belts and the like, and combinations thereof. Typically, fastening member 46 is configured to be refastenable or re-closable. In some embodiments, fastening member 46 may be adapted to engage or otherwise join with a fastening element, for example, the outer covering 16. In other embodiments, the fastening element may be a fastener landing zone 48. Fastener landing zone 48 may be a piece of loop material located on the outer covering 16 in the front waist region 30 and is adapted to engage a hook-type fastening member 46. In alternative embodiments, the landing zone 48 may be a film adapted to engage with a tape tab fastening member 46.

The diaper 10 may be provided with a re-closable fastening system or may alternatively be provided in the form of a pant-type diaper. When the absorbent article is a diaper, it may comprise a re-closable fastening system joined to the chassis for securing the diaper to a wearer. When the absorbent article is a pant-type diaper, the article may comprise at least two side panels joined to the chassis and to each other to form a pant. The fastening system and any component thereof may include any material suitable for such a use, including but not limited to plastics, films, foams, nonwoven, woven, paper, laminates, fiber reinforced plastics and the like, or combinations thereof. The materials making up the fastening device may be flexible. The

flexibility may allow the fastening system to conform to the shape of the body and thus, reduce the likelihood that the fastening system will irritate or injure the wearer's skin.

For unitary absorbent articles, the chassis 12 and absorbent core 14 may form the main structure of the diaper 10 with other features added to form the composite diaper structure. While the topsheet 18, the backsheet 20, and the absorbent core 14 may be assembled in a variety of well-known configurations, some diaper configurations are described generally in U.S. Pat. No. 5,554,145 entitled "Absorbent Article With Multiple Zone Structural Elastic-Like Film Web Extensible Waist Feature" issued to Roe et al. on Sep. 10, 1996; U.S. Pat. No. 5,569,234 entitled "Disposable Pull-On Pant" issued to Buell et al. on Oct. 29, 1996; and U.S. Pat. No. 6,004,306 entitled "Absorbent Article With Multi-Directional Extensible Side Panels" issued to Robles et al. on Dec. 21, 1999, each of which is hereby incorporated by reference.

The topsheet 18 in FIG. 1 may be fully or partially elasticized or may be foreshortened to provide a void space between the topsheet 18 and the absorbent core 14. Exemplary structures including elasticized or foreshortened topsheets are described in more detail in U.S. Pat. No. 5,037,416 entitled "Disposable Absorbent Article Having Elastically Extensible Topsheet" issued to Allen et al. on Aug. 6, 1991; and U.S. Pat. No. 5,269,775 entitled "Trisection Topsheets for Disposable Absorbent Articles and Disposable Absorbent Articles Having Such Trisection Topsheets" issued to Freeland et al. on Dec. 14, 1993, each of which is hereby incorporated by reference.

The backsheet 26 may be joined with the topsheet 18. The backsheet 20 may prevent the exudates absorbed by the absorbent core 14 and contained within the diaper 10 from soiling other external articles that may contact the diaper 10, such as bed sheets and undergarments. The backsheet 26 may be substantially impervious to liquids (e.g., urine) and comprise a laminate of a nonwoven and a thin plastic film such as a thermoplastic film having a thickness of about 0.012 mm (0.5 mil) to about 0.051 mm (2.0 mils). Suitable backsheet films include those manufactured by Tredegar Industries Inc. of Terre Haute, Ind. and sold under the trade names X15306, X10962, and X10964. Other suitable backsheet materials may include breathable materials that permit vapors to escape from the diaper 10 while still preventing liquid exudates from passing through the backsheet 10. Exemplary breathable materials may include materials such as woven webs, nonwoven webs, composite materials such as film-coated nonwoven webs, and microporous films such as manufactured by Mitsui Toatsu Co., of Japan under the designation ESPOIR NO and by EXXON Chemical Co., of Bay City, Tex., under the

designation EXXAIRE. Suitable breathable composite materials comprising polymer blends are available from Clopay Corporation, Cincinnati, Ohio under the name HYTREL blend P18-3097. Such breathable composite materials are described in greater detail in PCT Application No. WO 95/16746, published on Jun. 22, 1995 in the name of E.I. DuPont, which is hereby incorporated by reference. Other breathable backsheets including nonwoven webs and apertured formed films are described in U.S. Pat. No. 5,571,096 issued to Dobrin et al. on Nov. 5, 1996, which is hereby incorporated by reference.

The backsheet may have a water vapor transmission rate (WVTR) of greater than about 2000 g/24 h/m², greater than about 3000 g/24 h/m², greater than about 5000 g/24 h/m², greater than about 6000 g/24 h/m², greater than about 7000 g/24 h/m², greater than about 8000 g/24 h/m², greater than about 9000 g/24 h/m², greater than about 10000 g/24 h/m², greater than about 11000 g/24 h/m², greater than about 12000 g/24 h/m², greater than about 15000 g/24 h/m², measured according to WSP 70.5 (08) at 37.8.°C and 60% Relative Humidity.

FIG. 2 shows a cross section of the diaper 10 of FIG. 1 taken along the sectional line 2-2 of FIG. 1. Starting from the wearer facing side, the diaper 10 may comprise the topsheet 18, the components of the absorbent core 14, and the backsheet 20. The diaper 10 may also comprise an acquisition system 50 disposed between the liquid permeable topsheet 18 and the backsheet 20. In one embodiment, the diaper 10 may comprise an acquisition system 50 disposed between the liquid permeable topsheet 18 and a wearer facing side of the absorbent core 14. The acquisition system 50 may be in direct contact with the absorbent core 14. The acquisition system 50 may comprise a single layer or multiple layers (not shown), such as an upper acquisition layer 52 facing towards the wearer's skin and a lower acquisition layer 54 facing the garment of the wearer. The acquisition system 50 may function to receive a surge of liquid, such as a gush of urine. In other words, the acquisition system 50 may serve as a temporary reservoir for liquid until the absorbent core 14 can absorb the liquid.

The lower acquisition layer 54 may have a high fluid uptake capability. Fluid uptake is measured in grams of absorbed fluid per gram of absorbent material and is expressed by the value of "maximum uptake." A high fluid uptake corresponds therefore to a high capacity of the material and is beneficial, because it ensures the complete acquisition of fluids to be absorbed by an acquisition material. The lower acquisition layer 54 may have a maximum uptake of about 10 g/g.

A relevant attribute of the upper acquisition layer 54 is its Median Desorption Pressure, MDP. The MDP is a measure of the capillary pressure that is required to dewater the lower acquisition layer 54 to about 50% of its capacity at 0 cm capillary suction height under an applied mechanical pressure of 0.3 psi. Generally, a relatively lower MDP may be useful. The lower MDP may allow the lower acquisition layer 54 to more efficiently drain the upper acquisition material. The ability of the lower acquisition layer 54 to move liquid vertically via capillary forces will be directly impacted by gravity and the opposing capillary forces associated with desorption of the upper acquisition layer. Minimizing these capillary forces may positively impact the performance of the lower acquisition layer 54. However, the lower acquisition layer 54 may also have adequate capillary absorption suction in order to drain the layers above (upper acquisition layer 52 and topsheet 18, in particular) and to temporarily hold liquid until the liquid can be partitioned away by the absorbent core components. Therefore, the lower acquisition layer 54 may have a minimum MDP of greater than 5 cm. Further, the lower acquisition layer 54 has an MDP value of less than about 20.5 cm H₂O, or less than about 19 cm H₂O, or less than about 18 cm H₂O to provide for fast acquisition.

In one embodiment, the absorbent core 14 as shown in FIGS. 1, 2 and 4 generally is disposed between the topsheet 18 and the backsheet 20 and comprises two layers, a first absorbent layer 60 and a second absorbent layer 62. As best shown in FIG. 3, the first absorbent layer 60 of the absorbent core 14 comprises a substrate 64, an absorbent particulate polymer material 66 on the substrate 64, and a thermoplastic composition 68 on the absorbent particulate polymer material 66 and at least portions of the first substrate 64 as an adhesive for covering and immobilizing the absorbent particulate polymer material 66 on the first substrate 64. The first absorbent layer 60 of the absorbent core 14 may also include a cover layer (not shown) on the thermoplastic composition 68.

Likewise, as best illustrated in FIGS. 2 and 4, the second absorbent layer 62 of the absorbent core 14 may also include a substrate 72, an absorbent particulate polymer material 74 on the second substrate 72, and a thermoplastic composition 76 on the absorbent particulate polymer material 74 and at least a portion of the second substrate 72 for immobilizing the absorbent particulate polymer material 74 on the second substrate 72. Although not illustrated, the second absorbent layer 62 may also include a cover layer.

The substrate 64 of the first absorbent layer 60 may be referred to as a dusting layer and has a first surface 78 (FIG. 3) which faces the backsheet 20 of the diaper 10 and a second surface

80 which faces the absorbent particulate polymer material 66. Likewise, the substrate 72 of the second absorbent layer 62 may be referred to as a core cover and has a first surface facing the topsheet 18 of the diaper 10 and a second surface facing the absorbent particulate polymer material 74. The first and second substrates 64 and 72 may be adhered to one another with adhesive about the periphery to form an envelope about the absorbent particulate polymer materials 66 and 74 to hold the absorbent particulate polymer material 66 and 74 within the absorbent core 14.

The substrates 64 and 72 of the first and second absorbent layers 60 and 62 may be a non-woven material. The non-wovens may be porous and may have a pore size of about 32 microns.

As illustrated in FIGS. 2 and 4, the absorbent particulate polymer material 66 and 74 is deposited on the respective substrates 64 and 72 of the first and second absorbent layers 60 and 62 in clusters 90 of particles to form a grid pattern comprising land areas 94 and junction areas 96 between the land areas 94. As defined herein, land areas 94 are areas where the thermoplastic adhesive material does not contact the nonwoven substrate or the auxiliary adhesive directly; junction areas 96 are areas where the thermoplastic adhesive material does contact the nonwoven substrate or the auxiliary adhesive directly. The junction areas 96 in the grid pattern contain little or no absorbent particulate polymer material 66 and 74. The land areas 94 and junction areas 96 can have a variety of shapes including, but not limited to, circular, oval, square, rectangular, triangular, any polygon shape, and the like.

The size of the land areas 94 may vary. The width of the land areas 94 may range from about 8 mm to about 12 mm. The junction areas 96, on the other hand, may have a width or larger span of less than about 5 mm, less than about 3 mm, less than about 2 mm, less than about 1.5 mm, less than about 1 mm, or less than about 0.5 mm.

The junction areas 96 can be disposed in a regular or irregular pattern. In one embodiment, the arrangement of land areas 94 and junction areas 96 forms an angle which may be 0 degrees, greater than 0 degrees, or 15 to 30 degrees, or from about 5 to about 85 degrees, or from about 10 to about 60 degrees, or from about 15 to about 30 degrees.

The first and second absorbent layers 60 and 62 may be combined together to form the absorbent core 14 such that the layers may be offset such that the absorbent polymer material 66 and 74 is substantially continuously distributed across the absorbent polymer area. In a certain embodiment, absorbent polymer material 66 and 74 is substantially continuously distributed

across the absorbent polymer material area despite absorbent polymer material 66 and 74 discontinuously distributed across the first and second substrates 64 and 72 in clusters 90. In a certain embodiment, the absorbent layers may be offset such that the land areas 94 of the first absorbent layer 60 face the junction areas 96 of the second absorbent layer 62 and the land areas of the second absorbent layer 62 face the junction areas 96 of the first absorbent layer 60. When the land areas 94 and junction areas 96 are appropriately sized and arranged, the resulting combination of absorbent polymer material 66 and 74 is a substantially continuous layer of absorbent polymer material across the absorbent polymer material area of the absorbent core 14 (i.e. first and second substrates 64 and 72 do not form a plurality of pockets, each containing a cluster 90 of absorbent particulate polymer material 66 therebetween).

In a certain embodiment, the amount of absorbent polymer material 66 and 74 may vary along the length of the core. The amount of absorbent polymer material 66 and 74 present in the absorbent core 14 may vary, but in certain embodiments, is present in the absorbent core in an amount greater than about 80% by weight of the absorbent core, or greater than about 85% by weight of the absorbent core, or greater than about 90% by weight of the absorbent core, or greater than about 95% by weight of the core. In a particular embodiment, the absorbent core 14 comprises first and second substrates 64 and 72, the absorbent polymer material 66 and 74, and the thermoplastic composition 68 and 76. In such an embodiment, the absorbent core 14 is substantially cellulose free.

It has been found that, for most absorbent articles such as diapers, the liquid discharge occurs predominately in the front half of the diaper. The front half of the absorbent core 14 should therefore comprise most of the absorbent capacity of the core. Thus, according to certain embodiments, the front half of said absorbent core 14 may comprise more than about 60% of the superabsorbent material, or more than about 65%, 70%, 75%, 80%, 85%, or 90% of the superabsorbent material. The front half is defined as the region between the midpoint on the longitudinal axis 36 and the end edge 44 disposed in the first waist region 30.

In certain embodiments, the absorbent core 14 may further comprise any absorbent material that is generally compressible, conformable, non-irritating to the wearer's skin, and capable of absorbing and retaining liquids such as urine and other certain body exudates. In such embodiments, the absorbent core 14 may comprise a wide variety of liquid-absorbent materials commonly used in disposable diapers and other absorbent articles such as comminuted wood pulp, which is generally referred to as airfelt, creped cellulose wadding, melt blown

polymers, including co-form, chemically stiffened, modified or cross-linked cellulosic fibers, tissue, including tissue wraps and tissue laminates, absorbent foams, absorbent sponges, or any other known absorbent material or combinations of materials. The absorbent core 14 may further comprise minor amounts (typically less than about 10%) of materials, such as adhesives, waxes, oils and the like.

Exemplary absorbent structures for use as the absorbent assemblies are described in U.S. Pat. No. 4,610,678 (Weisman et al.); U.S. Pat. No. 4,834,735 (Alemany et al.); U.S. Pat. No. 4,888,231 (Angstadt); U.S. Pat. No. 5,260,345 (DesMarais et al.); U.S. Pat. No. 5,387,207 (Dyer et al.); U.S. Pat. No. 5,397,316 (LaVon et al.); and U.S. Pat. No. 5,625,222 (DesMarais et al.).

In one embodiment, the thermoplastic adhesive material 68 and 76 may serve to cover and at least partially immobilize the absorbent polymer material 66 and 74. In one embodiment, the thermoplastic adhesive material 68 and 76 can be disposed essentially uniformly within the absorbent polymer material 66 and 74, between the polymers. However, in a certain embodiment, the thermoplastic adhesive material 68 and 76 may be provided as a fibrous layer which is at least partially in contact with the absorbent polymer material 66 and 74 and partially in contact with the substrate layers 64 and 72 of the first and second absorbent layers 60 and 62. Fig 4 shows such a structure, and in that structure, the absorbent polymer material 66 and 74 is provided as a discontinuous layer, and a layer of fibrous thermoplastic adhesive material 68 and 76 is laid down onto the layer of absorbent polymer material 66 and 74, such that the thermoplastic adhesive material 68 and 76 is in direct contact with the absorbent polymer material 66 and 74, but also in direct contact with the second surfaces 80 and 84 of the substrates 64 and 72, where the substrates are not covered by the absorbent polymer material 66 and 74. This imparts an essentially three-dimensional structure to the fibrous layer of thermoplastic adhesive material 68 and 76, which in itself is essentially a two-dimensional structure of relatively small thickness, as compared to the dimension in length and width directions. In other words, the thermoplastic adhesive material 68 and 76 undulates between the absorbent polymer material 68 and 76 and the second surfaces of the substrates 64 and 72.

Thereby, the thermoplastic adhesive material 68 and 76 may provide cavities to cover the absorbent polymer material 66 and 74, and thereby immobilizes this material. In a further aspect, the thermoplastic adhesive material 68 and 76 bonds to the substrates 64 and 72 and thus affixes the absorbent polymer material 66 and 74 to the substrates 64 and 72. Some thermoplastic adhesive materials will also penetrate into both the absorbent polymer material 66

and 74 and the substrates 64 and 72, thus providing for further immobilization and affixation. Of course, while the thermoplastic adhesive materials disclosed herein provide a much improved wet immobilization (i.e., immobilization of absorbent material when the article is wet or at least partially loaded), these thermoplastic adhesive materials may also provide a very good immobilization of absorbent material when the absorbent core 14 is dry. The thermoplastic adhesive material 68 and 76 may also be referred to as a hot melt adhesive.

Without wishing to be bound by theory, it has been found that those thermoplastic adhesive materials which are most useful for immobilizing the absorbent polymer material 66 and 74 combine good cohesion and good adhesion behavior. Good adhesion may promote good contact between the thermoplastic adhesive material 68 and 76 and the absorbent particulate polymer material 66 and 74 and the substrates 64 and 72. Good cohesion reduces the likelihood that the adhesive breaks, in particular in response to external forces, and namely in response to strain. When the absorbent core 14 absorbs liquid, the absorbent polymer material 66 and 74 swells and subjects the thermoplastic adhesive material 68 and 76 to external forces. In certain embodiments, the thermoplastic adhesive material 68 and 76 may allow for such swelling, without breaking and without imparting too many compressive forces, which would restrain the absorbent polymer material 66 and 74 from swelling.

In accordance with certain embodiments, the thermoplastic adhesive material 68 and 76 may comprise, in its entirety, a single thermoplastic polymer or a blend of thermoplastic polymers, having a softening point, as determined by the ASTM Method D-36-95 "Ring and Ball", in the range between 50 °C and 300 °C, or alternatively the thermoplastic adhesive material may be a hot melt adhesive comprising at least one thermoplastic polymer in combination with other diluents such as tackifying resins, plasticizers and additives such as antioxidants. In certain embodiments, the thermoplastic polymer has typically a molecular weight (Mw) of more than 10,000 and a glass transition temperature (Tg) usually below room temperature or $-6^{\circ}\text{C} > T_g < 16^{\circ}\text{C}$. In certain embodiments, typical concentrations of the polymer in a hot melt are in the range of about 20 to about 40% by weight. In certain embodiments, thermoplastic polymers may be water insensitive. Exemplary polymers are (styrenic) block copolymers including A-B-A triblock structures, A-B diblock structures and (A-B)_n radial block copolymer structures wherein the A blocks are non-elastomeric polymer blocks, typically comprising polystyrene, and the B blocks are unsaturated conjugated diene or (partly)

hydrogenated versions of such. The B block is typically isoprene, butadiene, ethylene/butylene (hydrogenated butadiene), ethylene/propylene (hydrogenated isoprene), and mixtures thereof.

Other suitable thermoplastic polymers that may be employed are metallocene polyolefins, which are ethylene polymers prepared using single-site or metallocene catalysts. Therein, at least one comonomer can be polymerized with ethylene to make a copolymer, terpolymer or higher order polymer. Also applicable are amorphous polyolefins or amorphous polyalphaolefins (APAO) which are homopolymers, copolymers or terpolymers of C2 to C8 alpha olefins.

In exemplary embodiments, the tackifying resin typically has a Mw below 5,000 and a Tg usually above room temperature, typical concentrations of the resin in a hot melt are in the range of about 30 to about 60%, and the plasticizer has a low Mw of typically less than 1,000 and a Tg below room temperature, with a typical concentration of about 0 to about 15%.

In certain embodiments, the thermoplastic adhesive material 68 and 76 is present in the form of fibers. In some embodiments, the fibers will have an average thickness of from about 1 to about 50 micrometers or from about 1 to about 35 micrometers and an average length of from about 5 mm to about 50 mm or from about 5mm to about 30 mm. To improve the adhesion of the thermoplastic adhesive material 68 and 76 to the substrates 64 and 72 or to any other layer, in particular any other non-woven layer, such layers may be pre-treated with an auxiliary adhesive.

The absorbent core 14 may also comprise an auxiliary adhesive which is not illustrated in the figures. The auxiliary adhesive may be deposited on the first and second substrates 64 and 72 of the respective first and second absorbent layers 60 and 62 before application of the absorbent particulate polymer material 66 and 74 for enhancing adhesion of the absorbent particulate polymer materials 66 and 74 and the thermoplastic adhesive material 68 and 76 to the respective substrates 64 and 72. The auxiliary glue may also aid in immobilizing the absorbent particulate polymer material 66 and 74 and may comprise the same thermoplastic adhesive material as described hereinabove or may also comprise other adhesives including but not limited to sprayable hot melt adhesives, such as H.B. Fuller Co. (St. Paul, MN) Product No. HL-1620-B. The auxiliary glue may be applied to the substrates 64 and 72 by any suitable means, but according to certain embodiments, may be applied in about 0.5 to about 1mm wide slots spaced about 0.5 to about 2 mm apart.

In addition to being thin, flexible, absorbent, and more comfortable to wear, these types of absorbent articles have an unexpected benefit. These absorbent articles can be compressed to higher levels during production, packing, and storage than previous airfelt core absorbent articles without causing an in-use increase in product stiffness due to over compression. The increase in compressibility provides multiple cost-savings benefits; lower shipping costs lower storage/warehousing costs, reduced packaging costs, reduced shelving/stocking costs, lower disposal costs, etc. The increase in compressibility also provides smaller package sizes by reducing the in-bag stack thickness or in-bag stack height for unopened packages of absorbent articles resulting in more environmentally friendly packaging.

In one embodiment, absorbent products according to the present disclosure may have an in-bag stack height of less than or equal to about 80 mm according to the In-Bag Stack Height Test described herein. In another embodiment, absorbent products according to the present disclosure may have an in-bag stack height of less than about 78 mm and in another embodiment of less than 76 mm according to the In-Bag Stack Height Test described herein. In another embodiment, absorbent products may have an In-Bag Stack Height of from about 72 mm to about 80 mm and in yet another embodiment of from about 74 mm to about 78 mm.

Typically, products such as absorbent articles are not sold individually, but rather are sold in packages containing a plurality of absorbent articles. For example, smaller absorbent articles, such as infant diapers may be sold in packages of thirty or more diapers, while toddler training pants may be sold in packages of twelve to eighteen training pants. In one embodiment, the absorbent articles are packaged in a poly bag. In another embodiment, the package may be a plastic "shrink-wrap" container. As shown in FIG. 5a, package 100 is a poly bag. Package 100 has an interior space 102, an exterior surface 112 and a height, width, and depth dimension. Package 100 may be any shape known in the art. For example, the package may have a polyhedral shape defining or forming a polyhedral enclosure. Interior 102 defines an interior space for containing absorbent articles 104. In one embodiment, the absorbent articles may all be identical to one another.

The absorbent articles 104 are arranged to form a stack 106 within interior 102. The articles may be stacked in any direction. As used herein, the term "stack" means an orderly pile. For example, the articles may be stacked vertically, horizontally, or at any angle inside the interior of the package. As shown in FIG. 5a, package 100 has a package width 108 that is defined as the maximum distance between the two highest bulging points along the same

compression stack axis 110 of the package. Absorbent articles according to the present disclosure can be bi-folded, as shown in FIG. 7a, or tri-folded, as shown in FIG. 7b. Other suitable folding techniques are also contemplated, for example, rolled or double bi-folded. The package 100 may also include a mechanism or means for accessing the interior space, for example, a gusset, a line of perforations, tabs, adhesive openings or any other means known in the art.

Package 100 may be composed of different materials or may be composed of substantially the same type of material. Package 100 may be composed of one layer or a laminate. The material can comprise a blown or cast film in a blend of low density polyethylene and linear low density polyethylene, metallocenes, ethylene vinyl acetate, surlyn, polyethylene terephthalate, biaxially oriented polypropylene, and/or nylon.

The number of absorbent articles placed in a package depends on several factors, including for example, folded dimensions, weight and a target compressibility range. For instance, Infant diapers (0-6 months) are expected to have a very soft backsheet feel for consumers when they hold or cuddle with their baby. To prevent a reduction in backsheet softness, these diapers are normally only compressed to between 30-38% within the product package, also known as in-bag compression, based on the number of pads contained in the package.

Baby diapers (6-12 months) and Toddlers (12-24+ months) do not have the same backsheet softness requirements as mothers are not spending as much time holding and cuddling babies within this age group. Within this age group, the diaper performance requirements (beyond absorbency) primarily relate to stretch, flexibility, and fit, and are associated with babies learning to crawl and walk. Diaper stiffness is an important product attribute for these diapers, and can be negatively affected by over-compression of product within the package. These diapers are normally compressed to between about 50 and 57% within the product package. Compression of these diapers beyond 57% leads to overall diaper stiffness associated with core over-compression.

Pants and training pants (24+ months) are designed with a focus on change-ability. Ease of pulling on and off as well as side-opening features are the two most important elements of these diapers. Absorbency and softness are sacrificed in order to encourage potty training and to minimize product costs. Therefore, diapers in this range are occasionally over-compressed

beyond 57% to reduce material and shipping costs. However, backsheet roughness and overall diaper stiffness are seen as product negatives with the pants category.

Surprisingly, we have found that with Baby and Toddler size substantially airfelt free diapers, the target compressibility range can be increased without adversely affecting key consumer aesthetic attributes of the diaper (stiffness/flexibility, softness, etc.). For example, absorbent products according to the present disclosure may have an in-bag compression of greater than or equal to about 58%. In another embodiment, absorbent products may have an in-bag compression of from about 58% to about 62%, in another embodiment of from about 58.5% to about 61.5% and in yet another embodiment of from about 59% to about 61%. Further, the in-bag compression for absorbent products having substantially airfelt free diapers can be increased, while at the same time reducing stiffness and increasing flexibility. In one embodiment, absorbent products according to the present disclosure may include absorbent articles having a longitudinal bending stiffness of less than or equal to about 355 N/m according to the Stiffness Test described herein. In another embodiment, absorbent products may include absorbent articles having a longitudinal bending stiffness of less than about 325 N/m and in another embodiment of less than about 310 N/m. In another embodiment, absorbent products may include absorbent articles having a longitudinal bending stiffness of from about 285 N/m to about 355 N/m and in another embodiment of from about 295 N/m to about 345 N/m.

The effects of over compression on diapers with airfelt cores, measured in terms of stiffness, is illustrated in Table 1 below:

Table 1
Longitudinal Bending Stiffness Results for Sample Diapers and Pants

Example	Longitudinal Bending Stiffness (N/m)
1	699
2	530
3	619
4	641
5	554
6	470

7	507
	Avg. 574
8	414
9	429
10	474
11	494
12	Not recorded due to instrument malfunction
13	392
14	437
	Avg. 440
15	528
16	579
17	582
18	427
19	539
20	446
21	553
	Avg. 522
22	286
23	325
24	325
25	355
26	299
27	285
28	286
	Avg. 309

Examples 1-7 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES LEARNING DESIGN (size 3/4T; bag count 23; Lot # b1919719F 19.1).

Examples 8-14 are commercially available airfelt diapers sold by The Procter & Gamble Company under the trademark PAMPERS CRUISERS (size 5; bag count 28; Lot # 9200U01766 05:16)

Examples 15-21 are commercially available airfelt diapers sold by The Procter & Gamble Company under the trademark PAMPERS CRUISERS (size 5; bag count 25; Lot # 9242U01764 11:50). 10 of these diapers were removed from the bag and compressed under conditions similar to Examples 22-28, i.e. a height of 40 mm for 2 seconds (intended to simulate the compression during transfer from the manufacturing line to the bagger for absorbent articles in accordance with the present disclosure) and then held at a height of 74 mm for 24 hours (intended to simulate the compression while in-bag for absorbent articles in accordance with the present disclosure). This demonstrates that current airfelt diapers compressed under conditions similar to Examples 22-28, adversely affects product stiffness.

Examples 22-28 are embodiments of absorbent articles in accordance with the present disclosure (size 5; bag count 40; Lot # 9244U01762X1504). These examples were less stiff and thus more flexible than the other comparative diapers and pants having airfelt cores from Examples 1-21 above.

Stiffness is measured by the following test. FIGs. 6a and 6b illustrate a Stiffness Test apparatus 300 used to measure the stiffness. The Stiffness Test apparatus 300 includes a constant rate of extension tensile tester 302 with computer interface (a suitable instrument is a MTS Alliance under Test Works 4 software, as available from MTS Systems Corp., Eden Prairie, Minnesota) fitted with a 25 N load cell. The test apparatus 300 also includes an upper movable test fixture 304 and a lower stationary test fixture 306. A plunger blade 308 is used for the upper movable test fixture 304 and base support platforms 310 are used as the lower stationary test fixture 306. All testing is performed in a conditioned room maintained at $23^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and $50\% \pm 2\%$ relative humidity. As discussed in more detail below, during stiffness testing, the upper fixture assembly 304 moves from a first position, such as shown in FIG. 7a, to a second position, such as shown in FIG. 7b, to engage and bend a test specimen 312 disposed on the lower stationary test fixture 306.

Components of the plunger blade 308 are made of aluminum to maximize the available load cell capacity. A shaft 314 is machined to fit the tensile tester and has a locking collar 316 to stabilize the plunger blade 308 and maintain alignment orthogonal to base support platforms 310. The plunger blade defines a length 318L of 300 mm long, a height 318H of 65 mm, and

thickness 318T of 3.25 mm, and has a material contact edge 320 with a continuous radius 322 of 1.625 mm. A bracket 324 fitted with set screws 326 are used to level the blade and a main set screw 328 to firmly hold the plunger blade 308 in place after adjustment.

As shown in FIGs. 6a and 6b, the lower test fixture 306 is attached to the tensile tester 302 with a shaft 330 and locking collar 332. The two support platforms 310 are movably mounted on a rail 334. The two support platforms each have a test surface 336 having a width 336W of 85 mm and length of 300 mm (perpendicular to the plane of the drawing). The test surfaces 336 are made of polished stainless steel so as to have a minimal coefficient of friction. Each platform 310 has a digital position monitor 338 which reads the individual platform positions (to the nearest 0.01 mm), and set screws 340 to lock the positions of the platforms 310 after adjustment. The two platforms form a gap 342 with an adjustable gap width 344. The two platforms 310 are square at the gap edge and the plate edges must be parallel front to back. The surfaces 364 must be at the same height so as to be disposed within the same plane.

A test specimen 312 may include an absorbent article, shown for example, in FIG. 1. The following provides a description of the steps that are followed to carry out a Stiffness Test to determine the longitudinal bending stiffness of a test specimen 312. To test the longitudinal bending stiffness of a test specimen, the plunger blade is accurately aligned (± 0.02 mm) so that the plunger blade is orthogonal to top surfaces 364 of the support platforms 310 and exhibits no skew relative to gap edges 366. Using the position monitors 338, the width 344 of the gap 342 is accurately set to 50.00 ± 0.02 mm between the two gap edges 366 of the support platforms 310, with the plunger blade 308 accurately (± 0.02 mm) centered in the gap 342. The tensile tester is programmed for a compression test. The gage length is set from the material contact edge 320 of the plunger blade 308 to the top surfaces 364 of the support platforms 310 to 25 mm. The crosshead is set to lower at 500 mm/min for a distance of 50 mm. The data acquisition rate is set to 200 Hz.

Test specimens are preconditioned at $23^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and $50\% \pm 2\%$ relative humidity for 2 hours prior to testing. During preconditioning the specimens should remain compressed and sealed within its package until just before testing. The specimen is tested in the same folded configuration it was in the package and should not be tested more than once.

To test the longitudinal bending stiffness, specimen is placed flat onto the top surfaces 364 of the support platforms 310 over the gap 342 with the top side 358 facing upward. The test specimen is placed with the longitudinal axis 36 parallel to the length dimension of the plunger

blade 308, and centered in the lateral 38 and the longitudinal 346 directions under the shaft 314 of the plunger blade. The load cell is zeroed and the tensile tester and the data acquisition are started.

The software is programmed to calculate the maximum peak force (N) and stiffness (N/m) from the force (N) versus displacement (m) curves. Stiffness is calculated as the slope of the force/displacement curve for the linear region of the curve, using a minimum line segment of at least 25% of the total peak force to calculate the slope. The stiffness is reported to the nearest 0.1 N/m. At least five samples are measured in this manner for a given product and the stiffness values are aggregated to calculate an average and standard deviation.

Consumers generally prefer smaller, more environmentally friendly packaging for products. As mentioned above, the increase in compressibility provides smaller package sizes and thus reduces the amount of packaging materials, for example, film material that is required per package of absorbent articles. One way to compare the amount of packaging materials used for absorbent articles is to calculate a bag or film utilization factor by measuring the package width, height and depth and calculating a surface area of the package utilizing the equation: Surface Area = (width x height x 2) + (width x depth x 2) + (height x depth x 2). This package surface area is then divided by the bag pad count, i.e. the number of absorbent articles in the package, to give an area per pad result. However, such a calculation fails to account for differences associated with the size of diapers. Thus, one way to compare the bag utilization factor for different packages is to normalize for differences in Folded Stack Length of the absorbent articles within the package.

As illustrated in FIG. 5a, package width 108 is defined as the maximum distance between the two highest bulging points along the same compression stack axis 110 of a diaper package. As illustrated in FIG. 5b, package height 120 is defined as the maximum distance between the bottom panel and highest point of the top panel. As illustrated in FIG. 5c, package depth 130 is defined as the maximum distance between the front and back panels of a diaper package.

Therefore, the Bag Utilization Factor can be determined by the following equation:

$$\text{Bag Utilization Factor (m}^2\text{/pad/m)} = \frac{\text{Surface Area of Package (cm}^2\text{) / Bag Count}}{\text{Folded Stack Length (cm)}} \div 100$$

Using the averages of Examples 1-5 from Table 2 below, the Bag Utilization Factor is determined as follows:

$$\begin{aligned} \text{Bag Utilization Factor (m}^2\text{/pad/m)} &= \\ &= \frac{(16.3\text{cm} \times 40.1\text{cm} \times 2) + (16.3\text{cm} \times 11.0\text{cm} \times 2) + (40.1\text{cm} \times 11.0\text{cm} \times 2) / 36}{20.6\text{cm}} \div 100 \\ &= 3.436 / 100 \\ &= 0.034 \text{ m}^2\text{/pad/m} \end{aligned}$$

In one embodiment, absorbent products according to the present disclosure may have a bag utilization factor of less than or equal to 0.030 m²/pad/m. In another embodiment, absorbent products may have a bag utilization factor of less than about 0.029 m²/pad/m. In another embodiment, absorbent products may have a bag utilization factor of from about 0.027 m²/pad/m to about 0.030 m²/pad/m.

In another embodiment, a Box Utilization Factor can also be determined by the following equation:

$$\begin{aligned} \text{Box Utilization Factor (m}^2\text{/pad/m)} &= \\ &= \frac{\text{Surface Area of Box (cm}^2\text{)} / \text{Box Count}}{\text{Folded Stack Length (cm)}} \div 100 \end{aligned}$$

In one embodiment, boxes containing absorbent products according to the present disclosure may have a box utilization factor of less than 0.0119 m²/pad/m. In another embodiment, boxes containing absorbent products according to the present disclosure may have a box utilization factor of from about 0.0090 m²/pad/m to about 0.0119 m²/pad/m.

FIGS. 8-15 describe a shipping optimization process for absorbent articles having a substantially airfelt free absorbent core. The overall shipping optimization process 400 according to the teachings of the disclosure includes five optimization procedures, the diaper optimization procedure 510, the bag optimization procedure 610, the box optimization procedure 710, the pallet optimization procedure 810, and the vehicle optimization procedure 910.

As shown in FIG. 9, the diaper optimization procedure 510 begins with a design input phase 520. The design input phase 520 includes gathering data regarding consumer needs 522, business needs 524, habits and practices 526, and market research 528. For example, consumer needs 522 may include data such as 1) absorbency requirements, 2) physiology of the consumer, 3) fluid absorbency rate, 4) fluid retention duration, 5) customer comfort, 6) weight of the

diaper, etc. Business needs 524 may include data such as 1) capital equipment use, 2) gaps in the existing product line, 3) startup costs, 4) startup time, etc. Habits and practices 526 may include data such as 1) past consumer purchase practices, 2) change habits (including day and night frequencies), when toilet training will start, etc. Market research 528 may include data such as 1) cross category purchases, 2) trade margins, 3) competitive marketing programs, etc. After completing the design inputs phase 520, the data collected is input into a design objective phase 530. After a basic design for the product is determined from the design inputs phase 522, several additional factors are considered to modify and engineer the product. For example, raw material costs 532 and raw material availability 534 may drive certain engineering choices to accomplish the design objectives 530. Moreover, the products sizes and dimensions 536 are determined based on the design inputs 520 data along with performance requirements 538. Ultimately the final optimized diaper 550 may be refined based on product aesthetics 540 and manufacturing capabilities 542. Normally products such as absorbent articles and diapers are not sold individually, but rather such absorbent articles are sold in packages containing a plurality of the absorbent articles. For example, smaller absorbent articles, such as infant diapers may be sold in packages of thirty or more diapers, while toddler training pants may be sold in packages of twelve to eighteen training pants. The number of absorbent articles placed in a package depends on several factors.

As shown in FIG. 10, the optimized diaper 550 has certain characteristics based on the diaper design. For example, the optimized diaper 550 has certain folded dimensions 620, a certain weight 622, and a target compressibility range 624. For instance, new-born diapers (0-6 months) are expected to have a very soft backsheet feel. To prevent a reduction in backsheet softness, these diapers are normally compressed to between 30-38% within the product package, also known as in-bag compression 626, based on the number of pads 628 contained in the package. Baby diapers (6-12 months) and Toddlers (12- 24+ months) do not have the same softness requirements and are normally compressed to between about 50 and 57% within the product package. Over-compression beyond this range will lead to stiffness in the diapers with air-felt cores, another undesired product negative. In order to package absorbent articles with this level of compression, the diapers must be transferred to the polybag or other package under a significant level of compression, known as transfer compression 630. Surprisingly, we have found that with larger size air-felt free diapers, the target compressibility range 624, can be increased to greater than about 58% without adversely affecting key consumer aesthetic

attributes of the diaper (stiffness, softness, etc.). Once all the optimized diaper parameters are gathered at 640, data on the packaging is gathered at 650. Based on the optimized diaper parameters 640, certain materials may be selected for the package. Each material has different inherent physical characteristics, such as material stretch 652, material thickness, material weight, etc. Based on these material properties, a number of optimized diapers 654 may be selected for each individual package based on the packaging material, shipping and display limitations, orientation of the diapers 656, orientation of the pads in the diapers 658, and the height of the stack of diapers 660. Additional packing considerations include whether a handle should be included and if so, what type of handle 662 and whether a window 664 or a wicket slit 668 should be included in the package. The number of diapers and the type of material that comprises the container will determine how much side bulge 666 the completed package will have. Ultimately, an optimized package 670 is determined. The optimized package 670 will have certain physical characteristics and dimensions based on the type and number of diapers contained in the package.

As shown in FIG. 11, the optimized package 670 has certain characteristics based on the package design. For example, the optimized package 670 has certain overall dimensions 672, including height, weight, and depth, a certain weight 674, and a package compressibility 676, which is dependent on, for example, the degree of compression 678 that the pads contained in the package are under. Typically a number of optimized packages 670 are shipped in larger containers or boxes 780. These larger containers or boxes 780 make loading and unloading of shipping vehicles more efficient. Once the optimized package 670 parameters are determined at 720, the larger container or box 780 may initially be sized based on the number of package 670 desired in each container or box 780. Once a general idea as to the number of packages 670 should be in each box 780 is determined at 734, physical data describing each package 670 is gathered. The data may include the package circumference 732, the package width 736, the package length 740, the package side bulge 738, the package edge radius 742, the package height 744, the film thickness or gauge 746, and the stretch of the loaded package 748. Each package 770 will also have a certain amount of in-box compression 750 when loaded and each stack of packages 670 will have an in-box height 754. Some of these factors will depend on package orientation 756.

As shown in FIGs. 12a to 12f, the packages 670 may be loaded in many different orientations within the box 780. The orientations shown in FIGs. 12a to 12f are for illustration

purposes only, other package 670 orientations are possible during the box 780 optimization process. Some exemplary package 670 orientations are a horizontal side oriented width-wise stack, as shown in the top left illustration; a horizontal side oriented length-wise stack, as shown in the top right illustration; a dual upright horizontal depth-wise stack, as shown in the middle left illustration; a flat vertical length-wise stack, as shown in the lower left illustration; an upright horizontal width-wise stack, as shown in the middle right illustration; and a dual flat vertical width-wise stack, as shown in the lower right illustration. Each loading configuration may result in a different shaped or dimensioned box 780. On the other hand, the loading orientation may be adapted to standard box 780 shapes and sizes. Each box 780 may have an ultimate weight capacity, based on the material and construction of the box 780, and a volume capacity. When optimizing loading of the box 480, the number and orientation of packages 670 is optimized based on the weight and volume capacity of the box 780.

Once an optimal box design is determined, peripheral features may be included in the optimized box 480. For example, as shown in FIG. 13, the optimized box 780 may further include a container type 820, a color of a container 822, printing on the container 826, and handles on the container 830. Color and printing on the container may help readily identify each optimized box 780 as containing a certain absorbent product. The type and location of the flaps 828 and the type and location of adhesive 824 may also be determined. Once the optimized box 780 is finalized, the box parameters may be determined at 840. The box 780 parameters are input into a pallet loading optimization process at 850.

A pallet (sometimes called a skid) is a flat transport structure that supports goods in a stable fashion while being lifted by a forklift, pallet jack, or other jacking device. A pallet is the foundation of a unit load design, which can be as simple as placing the goods on a pallet, and securing them with straps or stretch-wrapped plastic film, or as exotic as a ULD mini-container.

Containerization for transport has spurred the use of pallets because the containers have the clean, level surfaces needed for easy pallet movement. Most pallets can easily carry a load of 1,000 kg (about 2,000 lb). Pallets make it easy to move heavy stacks. Loads with pallets under them can be hauled by forklift trucks of different sizes, or even by hand-pumped and hand-drawn pallet jacks. Movement is easy on a wide, strong, flat floor, such as concrete. Organizations using standard pallets for loading and unloading can have much lower costs for handling and storage, with faster material movement than businesses that do not. The lack of a single international standard for pallets causes substantial continuing expense in international

trade. A single standard is difficult because of the wide variety of needs a standard pallet would have to satisfy, such as passing doorways, fitting in standard containers, and bringing low labor costs. For example, organizations already handling large pallets often see no reason to pay the higher handling cost of using smaller pallets that can fit through doors.

The size, shape, and weight capacity of a given pallet may be determined in part by the shipping vehicle into which the pallet will be placed. Moreover, the volume capacity of a pallet is generally undetermined because pallets generally do not have side walls or tops. However, a volume capacity of a pallet can be determined based on a particular shipping vehicle. For example, if a particular shipping vehicle has an interior height of approximately 110 inches (e.g., a typical interior height of a semi trailer), then the combined height of the pallets and products cannot exceed 110 inches. Moreover, the combined height of the pallets must be less than 110 inches so that they can be inserted, stacked, and removed from the trailer using common loading and unloading techniques (e.g. using a forklift). Typical pallets are 5.75 inches high. Thus, if two levels of pallets are desired, each pallet can have a maximum product height of about 4 feet (48 inches). Typically, a semi-trailer is loaded with two rows of pallets, side by side. Semi-trailers are usually 8 ft, or 96 inches wide. Pallets may measure 3.3 by 4 ft (40 x 48 inches). If the rows of pallets are alternated so that the pallets inserted side by side have one 40 inch and one 48 inch side perpendicular to the length of the trailer, there will be a few inches of space between and on each side of the two pallets. This extra space also provides the room necessary for easy insertion and removal of the pallets. This alternating pallet configuration is also staggered from the front to the back of the trailer, thereby minimizing gaps between pallets and minimizing load shifting during transportation. A typical semi-trail can hold up to 60 pallets, 30 per layer, in this type of configuration. In addition, the area of a typical pallet may be approximately 13.2 square feet. By determining the maximum height of the pallet and products to be 4 feet when loaded in the vehicle, the volume capacity of each pallet in this example is approximately 52.8 cubic feet. In reality, each pallet must be designed to have 1-2 inches on underhang on each pallet to minimize product damage during shipment. Too much underhang will lead to unstable pallet loads and any amount of overhang will likely lead to product damage. If the desired underhang is subtracted from the previously calculated volume capacity of the pallet, a more accurate number for a true volume capacity for each pallet is about 52.4 ft³.

As shown in FIG. 13, generally the pallet volume capacity may be determined by the pallet dimensions 852, under or over hang specifications 854, 856, pallet pattern selection 858,

cases per pallet 860, layers per pallet 862, and mixed pallet requirements 864. The pallet weight capacity may be determined by the pallet material and the pallet construction. However, the pallet weight capacity is also dependent on the trailer weight capacity. For instance, if the trailer maximum legal weight capacity is about 50,000 lbs and there are 60 pallets contained within the trailer, each pallet would have a maximum load capacity of about 830 lbs. Each pallet weighs about 65 lbs, so the net load capacity of each pallet is about 765 lbs. Given each pallet has a maximum load capacity of about 765 lbs and a maximum volume capacity of about 52.4 ft³, the maximum density of product and packages on each pallet would be approximately 14.6 lbs/ft³. This number is significant in that it highlights that shipments of traditional air-felt absorbent products, especially diaper products, significantly underutilize the weight capacity of the most common form of product transportation, semi-trailers. Today's traditional air-felt absorbent article products, averaging a little under 9 lbs/ft³ have an average Load Factor of about .62 and a maximum Load Factor of about 0.70, while the substantially air-felt free absorbent article products may have an average Load Factor of about .82 and a minimum Load Factor of about 0.75. In one embodiment, the substantially air-felt free absorbent article products may have a Load Factor between about 0.75 and about 1.0, in another embodiment between about 0.77 and about 1.0, and in another embodiment between about 0.81 and about 0.95.

The Load Factor can be determined by the following equation:

$$\text{Load Factor} = (\text{Weight of Trailer Load} / \text{Legal Trailer Weight Limit}) / (\text{Volume of Trailer Load} / \text{Volume Capacity of Trailer})$$

As a result, a significant savings in terms of logistics costs in getting these products from a manufacturing site through distribution and on to the store shelves is realized.

As shown in FIG. 14 and indicated previously, the optimized pallet 880 will have certain physical characteristics useful in load planning of a transportation vehicle, such as a trailer. The optimized pallet 880 includes a loaded weight 920, a loaded volume 922 and a loaded volume utilization 924. These optimized pallet parameters 940 are used to create a load plan for the transportation vehicle at 950. The transportation vehicle includes certain physical transportation area dimensions, such as a height 952, a length 956, and a width 954 along with staggered load requirements 958. Once all the pallet and vehicle parameters are determined, the vehicle is loaded such that the optimized loaded vehicle 980 has a Load Factor of between 0.7 and 1.0. Again, this load factor assures the user that he/she is maximizing his/her transportation value.

In one embodiment, a pallet of absorbent products comprises a plurality of packages each having a plurality of disposable absorbent articles disposed within the interior space of the package, each of the disposable absorbent articles having a topsheet; a backsheet; a substantially cellulose free absorbent core located between the topsheet and the backsheet; a first waist region; a second waist region; a crotch region extending longitudinally between the first and second waist regions; and a fastening member extending laterally outward from the second waist region and adapted to releasably connect with a landing zone located in the first waist region; wherein the absorbent products arranged on the pallet exhibit a calculated Load Factor less than about 1.0, in another embodiment from about 0.7 to about 1.0.

In one embodiment, a shipping vehicle of absorbent products comprises a transportation area for receiving items to be transported, the vehicle having a maximum weight capacity for transporting items and a maximum volume capacity for transporting items; and a plurality of packages each having a plurality of disposable absorbent articles disposed within the interior space of the package, each of the disposable absorbent articles having a topsheet; a backsheet; a substantially cellulose free absorbent core located between the topsheet and the backsheet; a first waist region; a second waist region; a crotch region extending longitudinally between the first and second waist regions; and a fastening member extending laterally outward from the second waist region and adapted to releasably connect with a landing zone located in the first waist region; wherein the vehicle exhibits a calculated Load Factor of from about 0.7 to about 1.0, in another embodiment from about 0.75 to about 1.0.

FIG. 15 is a schematic diagram of a load planning system constructed in accordance with the teachings of the disclosure. The load planning system 1000 includes a processor 1010 operatively connected to an input device 1012, such as a computer keyboard, a computer mouse, a voice recognition system, a touchscreen, or any other type of input device, and an output device 1014, such as a computer monitor, a computer printer, a speaker, or any other type of output device. The processor 1010 is operatively coupled to a memory 1016. The memory 1016 may include software 1018 having one or more routines operable on the processor 1010. The software routines may perform the processes illustrated in FIGS. 8-15. The processor 1010 may also be connected to a loading device, such as an automatic loading system, or a display to instruct manual loaders. The software routines may run iteratively on the processor 1010 until the load factor is optimized for each of the packaging, the container, the pallet and the vehicle. Examples of container loading and cargo load planning software are MaxLoad Pro,

commercially available from TOPS Engineering Corporation of Richardson, Texas and CubeMaster, commercially available from Logen Solutions, Co. of Belmont, California.

EXAMPLES

The following Examples provide a comparison between diapers that are commercially available in the United States to diapers having optimized parameters according to the present disclosure. Tables 2-6 provide data for various diaper packages (folded stack length, in-bag stack height, and bag utilization factor) measured according to the Folded Stack Length Test and In-Bag Stack Height Test described in detail below.

Table 2

In-Bag Stack Height / Bag Utilization Factor Results for Sample Diaper Packages (Size 3)

Example	Height (mm)	Width (mm)	Depth (mm)	Bag Count	Pad Count Per Stack	Child Wt. Range (kg)	Folded Stack Length (mm)	In- Bag Stack Ht (mm)	Bag Utilization Factor (m ² /pad/m)
1.	400	166	110	36	18	7-13	210	92	0.0340
2.	401	163	110	36	18	7-13	206	91	0.0344
3.	400	162	109	36	18	7-13	206	90	0.0340
4.	402	162	110	36	18	7-13	204	90	0.0346
5.	400	164	109	36	18	7-13	206	91	0.0343
Avg.							206	91	0.034
6.	211	284	217	52	26	7-13	210	109	0.0306
7.	216	289	220	52	26	7-13	209	111	0.0319
8.	213	281	217	52	26	7-13	208	108	0.0309
9.	213	285	218	52	26	7-13	210	110	0.0310
10.	208	274	223	52	26	7-13	208	105	0.0304
Avg.							209	109	0.031
11.	204	295	102	26	26	7-13	211	113	0.0405
12.	203	293	102	26	26	7-13	210	113	0.0403
13.	205	294	101	26	26	7-13	208	113	0.0409

14.	204	294	104	26	26	7-13	208	113	0.0413
15.	203	297	103	26	26	7-13	207	114	0.0415
Avg.							209	113	0.041
16.	198	327	111	38	38	7-13	200	86	0.0324
17.	197	328	111	38	38	7-13	205	86	0.0316
18.	189	327	111	38	38	7-13	196	86	0.0320
19.	187	329	112	38	38	7-13	196	87	0.0320
20.	194	330	113	38	38	7-13	204	87	0.0318
21.	193	334	114	38	38	7-13	205	88	0.0320
Avg.							201	87	0.032
22.	203	229	114	31	31	7-13	205	74	0.0301
23.	202	229	114	31	31	7-13	208	74	0.0296
24.	204	230	112	31	31	7-13	207	74	0.0298
25.	204	226	112	31	31	7-13	205	73	0.0297
26.	204	226	113	31	31	7-13	206	73	0.0297
Avg.							206	74	0.030
27.	393	203	113	52	26	7-13	206	78	0.0275
28.	396	209	111	52	26	7-13	206	80	0.0280
29.	392	207	110	52	26	7-13	204	80	0.0277
30.	391	206	112	52	26	7-13	202	79	0.0281
31.	392	207	110	52	26	7-13	204	80	0.0277
Avg.							204	79	0.028

Examples 1-5 are commercially available airfelt diapers sold by Kimberly-Clark Corporation under the trademark HUGGIES SNUG & DRY (size 3; bag count 36; Lot #'s UT915306F 10:09; UT915306F 09:50; UT916806B 06:17; UT915306F 09:50; and UT916806B 06:17, respectively).

Examples 6-10 are commercially available airfelt diapers sold by Kimberly-Clark Corporation under the trademark HUGGIES LITTLE MOVERS (size 3; bag count 52; Lot #'s UT815001B 22:24; BI913412B 00:20; BI913412B 00:20; BI913412B 00:19; and BI913412B 00:20, respectively).

Examples 11-15 are commercially available airfelt diapers sold by Kimberly-Clark Corporation under the trademark HUGGIES PURE & NATURAL (size 3; bag count 26; Lot # BI914617B 23:58—Ex. 11 and 12; BI920317B 06:00—Ex. 13; and BI920317B 01:19—Ex. 14 and 15).

Examples 16-21 are commercially available airfelt diapers sold by The Procter & Gamble Company under the trademark PAMPERS CRUISERS (size 3; bag count 76; Lot #'s 9154U01142 02:35 15837—Ex. 16 and 17; 9192U01142 09:41 38287—Ex. 18 and 19; and 9095U01142 11:03 25875—Ex. 20 and 21).

Examples 22-26 are embodiments of absorbent products in accordance with the present disclosure (size 3; bag count 31; Lot #'s 9242U01762X1028; 9242U01762X1009—Ex. 23-26).

Examples 27-31 are embodiments of absorbent products in accordance with the present disclosure (size 3; bag count 52; Lot #'s 9242U01762X1251—Ex. 27 and 28 and 9242U011762X1317—Ex. 29-31).

Table 3

In-Bag Stack Height / Bag Utilization Factor Results for Sample Diaper Packages (Size 4)

Example	Height (mm)	Width (mm)	Depth (mm)	Bag Count	Pad Count Per Stack	Child Wt. Range (kg)	Folded Stack Length (mm)	In- Bag Stack Ht (mm)	Bag Utilization Factor (m ² /pad/m)
32.	230	262	116	31	31	10-17	228	85	0.0332
33.	219	254	118	31	31	10-17	226	82	0.0318
34.	222	267	116	31	31	10-17	222	86	0.0337
35.	230	262	118	31	31	10-17	227	85	0.0336
36.	221	261	116	31	31	10-17	219	84	0.0335
Avg.							224	84	0.033
37.	212	340	220	32	32	10-17	218	106	0.0555
38.	220	336	222	32	32	10-17	223	105	0.0553
39.	215	339	224	32	32	10-17	221	106	0.0557
40.	209	337	218	32	32	10-17	215	105	0.0551
41.	211	337	219	32	32	10-17	215	105	0.0556

Avg.							218	106	0.055
42.	218	255	109	23	23	10-17	226	111	0.0412
43.	217	258	108	23	23	10-17	227	112	0.0411
44.	216	255	109	23	23	10-17	222	111	0.0417
45.	217	257	108	23	23	10-17	226	112	0.0411
46.	216	254	108	23	23	10-17	226	110	0.0406
Avg.							225	111	0.041
47.	218	233	110	27	27	10-17	225	86	0.0331
48.	218	233	111	27	27	10-17	222	86	0.0337
49.	218	232	111	27	27	10-17	225	86	0.0337
50.	217	239	111	27	27	10-17	219	89	0.0347
51.	219	233	114	27	27	10-17	221	86	0.0344
Avg.							222	87	0.034
52.	217	211	112	27	27	10-17	220	78	0.0316
53.	216	208	112	27	27	10-17	216	77	0.0317
54.	216	210	112	27	27	10-17	220	78	0.0313
55.	216	209	112	27	27	10-17	220	77	0.0312
56.	212	212	112	27	27	10-17	219	79	0.0313
Avg.							219	78	0.031
57.	212	344	121	46	46	10-17	221	75	0.0276
58.	213	344	117	46	46	10-17	220	75	0.0274
59.	213	345	120	46	46	10-17	220	75	0.0278
60.	214	349	118	46	46	10-17	221	76	0.0278
61.	211	348	119	46	46	10-17	222	76	0.0274
Avg.							221	75	0.028

Examples 32-36 are commercially available airfelt diapers sold by Kimberly-Clark Corporation under the trademark HUGGIES SNUG & DRY (size 4; bag count 31; Lot #'s PA913908B 20:06; BI917716B 22:41; WP 920310 F; PA913908B 20:05; and WP 920310 F, respectively).

Examples 37-41 are commercially available airfelt diapers sold by Kimberly-Clark Corporation under the trademark HUGGIES LITTLE MOVERS (size 4; bag count 64; Lot #'s UT916502B 2049 #9917; BI916812X 10:15 82616; BI919112X 11:16 331403; UT917102F 10:01 4548; and UT917102F 09:57, respectively).

Examples 42-46 are commercially available airfelt diapers sold by Kimberly-Clark Corporation under the trademark HUGGIES PURE & NATURAL (size 4; bag count 23; Lot #'s BI911212B 21:24—Ex. 42-44 and BI911212B 21:18—Ex. 45 and 46).

Examples 47-51 are commercially available airfelt diapers sold by The Procter & Gamble Company under the trademark PAMPERS CRUISERS (size 4; bag count 27; Lot #'s 9200 UO1129 21:15—Ex. 47-49; 9194UO1129 11:46; and 9214 UO1754 19:30, respectively).

Examples 52-56 are embodiments of absorbent products in accordance with the present disclosure (size 4; bag count 27; Lot #'s 924762U01762X1755—Ex. 52, 53 and 55; and 924762U01762X1754—Ex. 54 and 56).

Examples 57-61 are embodiments of absorbent products in accordance with the present disclosure (size 4; bag count 46; Lot # 9247U01762X10:36).

Table 4

In-Bag Stack Height / Bag Utilization Factor Results for Sample Diaper Packages (Size 5)

Example	Height (mm)	Width (mm)	Depth (mm)	Bag Count	Pad Count Per Stack	Child Wt. Range (kg)	Folded Stack Length (mm)	In- Bag Stack Ht (mm)	Bag Utilization Factor (m ² /pad/m)
62.	235	304	120	35	35	12+	232	87	0.0335
63.	234	304	121	35	35	12+	229	87	0.0340
64.	234	295	119	35	35	12+	236	84	0.0320
65.	235	294	118	35	35	12+	230	84	0.0327
66.	234	302	122	35	35	12+	232	86	0.0335
67.	235	305	121	35	35	12+	233	87	0.0336
Avg.							232	86	0.033
68.	224	256	111	23	23	12+	230	111	0.0418

69.	230	258	112	23	23	12+	231	112	0.0429
70.	221	254	111	23	23	12+	223	110	0.0424
71.	223	255	111	23	23	12+	223	111	0.0429
72.	224	253	111	23	23	12+	226	110	0.0422
Avg.							227	111	0.042
73.	215	261	104	20	20	12+	221	131	0.0477
74.	217	264	102	20	20	12+	221	132	0.0483
75.	215	261	102	20	20	12+	224	130	0.0468
76.	222	269	95	20	20	12+	227	134	0.0469
77.	214	262	104	20	20	12+	223	131	0.0473
Avg.							223	132	0.047
78.	212	268	117	28	28	12+	220	96	0.0367
79.	211	269	118	28	28	12+	218	96	0.0372
80.	210	267	118	28	28	12+	220	95	0.0365
81.	212	270	117	28	28	12+	219	96	0.0371
82.	212	271	120	28	28	12+	221	97	0.0373
83.	211	271	121	28	28	12+	220	97	0.0375
Avg.							220	96	0.037
84.	214	302	120	40	40	12+	223	76	0.0284
85.	213	304	118	40	40	12+	226	76	0.0278
86.	216	304	120	40	40	12+	225	76	0.0285
87.	216	302	119	40	40	12+	225	76	0.0282
88.	216	304	118	40	40	12+	222	76	0.0286
Avg.							224	76	0.028

Examples 62-67 are commercially available airfelt diapers sold by Kimberly-Clark Corporation under the trademark HUGGIES SNUG & DRY (size 5; bag count 35; Lot #'s PA919002B 04:11—Ex. 62 and 63; BI907015X 02:03 16118—Ex. 64 and 65; and PA915502F 17:00—Ex. 66 and 67).

Examples 68-72 are commercially available airfelt diapers sold by Kimberly-Clark Corporation under the trademark HUGGIES LITTLE MOVERS (size 5; bag count 23; Lot #'s PA914807X 17:15; PA914907X 02:04; and PA917707B 04:55—Ex. 70-72, respectively).

Examples 73-77 are commercially available airfelt diapers sold by Kimberly-Clark Corporation under the trademark HUGGIES PURE & NATURAL (size 5; bag count 20; Lot #'s UT918102F 16:33—Ex. 73-75; UT907802F 14:11; and UT918102F 14:45, respectively).

Examples 78-83 are commercially available airfelt diapers sold by The Procter & Gamble Company under the trademark PAMPERS CRUISERS (size 5; bag count 56; Lot #'s 9208UO1130 08:07 02501—Ex. 78-81 and 9292UO1130 21:12 46676—Ex. 82 and 83).

Examples 84-88 are embodiments of absorbent products in accordance with the present disclosure (size 5; bag count 40; Lot # 9244U01762X1504).

Table 5

In-Bag Stack Height / Bag Utilization Factor Results for Sample Diaper Packages (Size 6)

Example	Height (mm)	Width (mm)	Depth (mm)	Bag Count	Pad Count Per Stack	Child Wt. Range (kg)	Folded Stack Length (mm)	In- Bag Stack Ht (mm)	Bag Utilization Factor (m ² /pad/m)
89.	233	253	218	40	20	16+	233	127	0.0354
90.	241	252	216	40	20	16+	235	126	0.0356
91.	227	259	223	40	20	16+	233	130	0.0359
92.	232	256	212	40	20	16+	239	128	0.0341
93.	227	261	217	40	20	16+	237	131	0.0348
Avg.							235	128	0.035
94.	237	219	108	20	20	16+	238	110	0.0425
95.	235	220	108	20	20	16+	240	110	0.0420
96.	233	220	110	20	20	16+	235	110	0.0430
97.	237	217	111	20	20	16+	238	109	0.0428
98.	232	219	111	20	20	16+	237	110	0.0426
Avg.							238	110	0.043

99.	188	228	115	20	20	16+	235	114	0.0386
100.	189	232	113	20	20	16+	233	116	0.0392
101.	192	232	114	20	20	16+	235	116	0.0395
102.	192	234	116	20	20	16+	235	117	0.0401
103.	192	231	115	20	20	16+	235	116	0.0396
Avg.							235	116	0.039

Examples 89-93 are commercially available airfelt diapers sold by Kimberly-Clark Corporation under the trademark HUGGIES SNUG & DRY (size 6; bag count 40; Lot #'s PA901405B 03:52; PA901405B 03:54; WP 823109F; PA8142055 15:17; and PA901505F 14:41, respectively).

Examples 94-98 are commercially available airfelt diapers sold by Kimberly-Clark Corporation under the trademark HUGGIES LITTLE MOVERS (size 6; bag count 34; Lot #'s PA913107X 11:39; PA913107X 11:37; PA913207X 01:32; PA919007F 10:19; and PA910207X 23:21, respectively).

Examples 99-103 are commercially available airfelt diapers sold by The Procter & Gamble Company under the trademark PAMPERS CRUISERS (size 6; bag count 20; Lot #'s 9141UO17642235—Ex. 81-84 and 9155UO17641647).

Table 6

In-Bag Stack Height / Bag Utilization Factor Results for Sample Diaper Packages (Training Pants)

Example	Height (mm)	Width (mm)	Depth (mm)	Bag Count	Pad Count Per Stack	Child Wt. Range (kg)	Folded Stack Length (mm)	In- Bag Stack Ht (mm)	Bag Utilization Factor (m ² /pad/m)
104.	272	249	125	27	27	17-29	274	92	0.0359
105.	277	248	123	27	27	17-29	275	92	0.0359
106.	276	258	117	27	27	17-29	274	96	0.0361

107.	275	256	117	27	27	17-29	278	95	0.0353
108.	272	246	125	27	27	17-29	272	91	0.0359
Avg.							272	93	0.036
109.	294	205	130	21	21	27-57+	293	98	0.0407
110.	295	206	129	21	21	27-57+	290	98	0.0412
111.	288	209	129	21	21	27-57+	286	100	0.0414
112.	291	205	129	21	21	27-57+	287	98	0.0410
113.	286	209	130	21	21	27-57+	286	100	0.0413
Avg.							288	98	0.041
114.	266	166	124	15	15	17-29	268	111	0.0486
115.	268	169	121	15	15	17-29	268	113	0.0488
116.	269	170	122	15	15	17-29	270	113	0.0490
117.	269	169	122	15	15	17-29	268	113	0.0492
118.	270	167	122	15	15	17-29	269	111	0.0488
Avg.							269	112	0.049
119.	300	205	121	21	21	27-57+	302	98	0.0387
120.	299	209	121	21	21	27-57+	298	100	0.0396
121.	291	205	126	21	21	27-57+	288	98	0.0404
122.	296	205	127	21	21	27-57+	295	98	0.0401
123.	291	207	127	21	21	27-57+	293	99	0.0401
Avg.							295	98	0.040

124.	216	279	132	44	44	8-15	211	63	0.0271
125.	220	279	132	44	44	8-15	215	63	0.0269
126.	219	277	134	44	44	8-15	215	63	0.0269
127.	219	279	134	44	44	8-15	218	63	0.0267
128.	218	279	132	44	44	8-15	216	63	0.0266
Avg.							215	63	0.027
129.	232	172	134	23	23	15-18	235	75	0.0348
130.	233	176	132	23	23	15-18	235	77	0.0352
131.	233	175	132	23	23	15-18	235	76	0.0350
132.	229	175	134	23	23	15-18	231	76	0.0355
133.	232	176	129	23	23	15-18	231	77	0.0352
Avg.							233	76	0.035
134.	240	156	130	19	19	17-23	240	82	0.0390
135.	241	156	130	19	19	17-23	238	82	0.0395
136.	243	156	130	19	19	17-23	240	82	0.0394
137.	238	152	133	19	19	17-23	239	80	0.0388
138.	243	153	133	19	19	17-23	235	81	0.0402
Avg.							238	81	0.039
139.	209	204	129	26	26	8-15	211	78	0.0350
140.	211	205	129	26	26	8-15	208	79	0.0358
141.	213	201	130	26	26	8-15	212	77	0.0351
142.	213	199	129	26	26	8-15	215	77	0.0342
143.	213	199	130	26	26	8-15	214	77	0.0345
Avg.							212	78	0.035
144.	227	176	131	23	23	15-18	228	77	0.0354
145.	227	174	132	23	23	15-18	228	76	0.0353
146.	231	175	131	23	23	15-18	229	76	0.0355
147.	230	172	132	23	23	15-18	227	75	0.0355
148.	226	178	133	23	23	15-18	230	77	0.0355
Avg.							228	76	0.035
149.	238	158	130	19	19	17-23	238	83	0.0394

150.	237	158	131	19	19	17-23	236	83	0.0398
151.	238	157	131	19	19	17-23	238	83	0.0394
152.	239	158	132	19	19	17-23	238	83	0.0399
153.	240	158	132	19	19	17-23	241	83	0.0395
Avg.							238	83	0.040
154.	214	196	129	26	26	8-15	219	75	0.0333
155.	215	196	128	26	26	8-15	218	75	0.0334
156.	218	195	128	26	26	8-15	218	75	0.0337
157.	215	196	129	26	26	8-15	218	75	0.0336
158.	210	202	126	26	26	8-15	217	78	0.0334
Avg.							218	76	0.033
159.	230	182	124	23	23	15-18	233	79	0.0347
160.	230	182	128	23	23	15-18	232	79	0.0355
161.	231	182	126	23	23	15-18	231	79	0.0354
162.	226	170	131	23	23	15-18	233	74	0.0337
163.	230	171	131	23	23	15-18	233	74	0.0343
Avg.							232	77	0.035
164.	236	160	130	19	19	17-23	237	84	0.0396
165.	235	161	131	19	19	17-23	236	85	0.0400
166.	236	160	131	19	19	17-23	238	84	0.0396
167.	235	160	135	19	19	17-23	240	84	0.0399
168.	236	163	133	19	19	17-23	239	86	0.0403
Avg.							238	85	0.040
169.	212	197	124	26	26	8-15	215	76	0.0311
170.	213	190	123	26	26	8-15	215	73	0.0322
171.	214	190	122	26	26	8-15	215	73	0.0322
172.	211	194	127	26	26	8-15	215	75	0.0330
173.	211	202	125	26	26	8-15	214	78	0.0339
Avg.							215	75	0.033
174.	230	172	131	23	23	15-18	235	75	0.0341
175.	232	173	131	23	23	15-18	233	75	0.0348

176.	228	171	131	23	23	15-18	233	74	0.0341
177.	226	172	132	23	23	15-18	235	75	0.0338
178.	226	171	131	23	23	15-18	234	74	0.0337
Avg.							234	75	0.034
179.	237	160	131	19	19	17-23	239	84	0.0396
180.	235	161	131	19	19	17-23	240	85	0.0393
181.	235	161	131	19	19	17-23	238	85	0.0397
182.	233	154	132	19	19	17-23	239	81	0.0383
183.	234	154	133	19	19	17-23	240	81	0.0384
Avg.							239	83	0.039
184.	219	265	118	26	26	7-15	218	102	0.0406
185.	216	265	120	26	26	7-15	220	102	0.0402
186.	219	267	118	26	26	7-15	220	103	0.0405
187.	220	269	120	26	26	7-15	220	103	0.0412
188.	219	266	118	26	26	7-15	215	102	0.0413
Avg.							219	102	0.041
189.	222	231	122	23	23	14-18	228	100	0.0406
190.	224	229	119	23	23	14-18	225	100	0.0407
191.	225	228	117	23	23	14-18	224	99	0.0405
192.	225	228	117	23	23	14-18	228	99	0.0398
193.	225	226	116	23	23	14-18	227	98	0.0395
Avg.							226	99	0.040
194.	218	263	117	26	26	7-15	222	101	0.0394
195.	219	265	116	26	26	7-15	224	102	0.0392
196.	215	266	118	26	26	7-15	216	102	0.0406
197.	217	267	116	26	26	7-15	220	103	0.0399
198.	218	263	117	26	26	7-15	220	101	0.0397
Avg.							220	102	0.040
199.	222	220	122	23	23	14-18	224	96	0.0399
200.	225	220	122	23	23	14-18	228	96	0.0396
201.	226	224	121	23	23	14-18	225	97	0.0406

202.	228	228	121	23	23	14-18	224	99	0.0416
203.	233	225	124	23	23	14-18	226	98	0.0420
Avg.							225	97	0.041
204.	245	213	119	17	17	17-29	256	125	0.0490
205.	247	212	120	17	17	17-29	255	125	0.0496
206.	245	214	118	17	17	17-29	255	126	0.0492
207.	248	212	119	17	17	17-29	252	125	0.0501
208.	241	215	119	17	17	17-29	247	126	0.0505
Avg.							253	125	0.050
209.	260	171	119	13	13	26-39	265	132	0.0556
210.	258	171	121	13	13	26-39	263	132	0.0562
211.	249	170	120	13	13	26-39	252	131	0.0565
212.	249	171	120	13	13	26-39	255	132	0.0561
213.	249	171	118	13	13	26-39	254	132	0.0558
Avg.							258	131	0.056
214.	248	216	118	17	17	17-29	256	127	0.0498
215.	244	214	119	17	17	17-29	253	126	0.0496
216.	250	212	118	17	17	17-29	255	125	0.0496
217.	245	213	120	17	17	17-29	247	125	0.0510
218.	245	214	121	17	17	17-29	245	126	0.0518
Avg.							251	126	0.050

Examples 104-108 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES GOOD NITES (girl S-M; bag count 27; Lot #'s PA19915B 23:25—Ex. 104, 105 and 108; PA916113X 17:29—Ex. 106; and PA916113X 17:31—Ex. 107).

Examples 109-113 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES GOOD NITES (girl L-XL; bag count 21; Lot #'s PA920414F 17:46—Ex. 109 and 110; PA915614B 01:54; PA915414F 10:38; and PA915614B 01:52).

Examples 114-118 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES GOOD NITES (boy S-M; bag count 15; Lot #'s PA917215F 15:09; PA917915F 16:02; PA917915F 16:04; PA916315F 10:44; and PA917915F 16:04, respectively).

Examples 119-123 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES GOOD NITES (boy L-XL; bag count 21; Lot #'s PA919613F 14:33—Ex. 119 and 120; and PA920914F 18:05—Ex. 121-123).

Examples 124-128 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES LEARNING DESIGN (girl 2T/3T; bag count 44; Lot #'s PA920017F 07:03; PA920910B 03:55; PA919917B 06:28; and PA920910B 04:17—Ex. 127 and 128, respectively). These particular examples do not have a substantially cellulose free absorbent core as defined herein.

Examples 129-133 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES LEARNING DESIGN (girl 3T/4T; bag count 23; Lot #'s BI919619B 20:40; BI917919B 05:35—Ex. 130-132; and PA917009X 19:14, respectively). These particular examples do not have a substantially cellulose free absorbent core as defined herein.

Examples 134-138 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES LEARNING DESIGN (girl 4T/5T; bag count 19; Lot # PA921018F 10:48). These particular examples do not have a substantially cellulose free absorbent core as defined herein.

Examples 139-143 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES LEARNING DESIGN (boy 2T/3T; bag count 26; Lot #'s PA922610F08:48—Ex. 139 and 140; PA921210B23:28; PA92120B23:21; and PA92120B23:20). These particular examples do not have a substantially cellulose free absorbent core as defined herein.

Examples 144-148 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES LEARNING DESIGN (boy 3T/4T; bag count 23; Lot #'s PA92189B02:00—Ex. 144-147 and PA919312B03:07). These particular examples do not have a substantially cellulose free absorbent core as defined herein.

Examples 149-153 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES LEARNING DESIGN (boy 4T/5T; bag count

19; Lot #'s PA920718F 12:39—Ex. 139-142; and PA915818X 03:06). These particular examples do not have a substantially cellulose free absorbent core as defined herein.

Examples 154-158 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES COOL ALERT (girl 2T/3T; bag count 26; Lot #'s PA914610X 01:46—Ex. 154-157; and UT911011F 09:25). These particular examples do not have a substantially cellulose free absorbent core as defined herein.

Examples 159-163 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES COOL ALERT (girl 3T/4T; bag count 23; Lot #'s UT911812B 23:34—Ex. 159 and 160; UT919412F07:36—Ex. 161; and BI917219B 03:11—Ex. 162 and 163). These particular examples do not have a substantially cellulose free absorbent core as defined herein.

Examples 164-168 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES COOL ALERT (girl 4T/5T; bag count 19; Lot #'s UT909610B 23:35—Ex. 164-166; and BI912818F 08:46—Ex. 167 and 168). These particular examples do not have a substantially cellulose free absorbent core as defined herein.

Examples 169-173 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES COOL ALERT (boy 2T/3T; bag count 26; Lot #'s WP919510F—Ex. 169-172; and PA914810X 18:23). These particular examples do not have a substantially cellulose free absorbent core as defined herein.

Examples 174-178 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES COOL ALERT (boy 3T/4T; bag count 23; Lot #'s UT917312B 21:51—Ex. 174 and 175; UT917312B 17:43—Ex. 176 and 177; and UT917312F 17:42). These particular examples do not have a substantially cellulose free absorbent core as defined herein.

Examples 179-183 are commercially available airfelt training pants sold by Kimberly-Clark Corporation under the trademark HUGGIES COOL ALERT (boy 4T/5T; bag count 19; Lot #'s BI910818B 23:42—Ex. 179 and 180; PA911418X 02:48—Ex. 181; and BI919918B 01:34—Ex. 182 and 183). These particular examples do not have a substantially cellulose free absorbent core as defined herein.

Examples 184-188 are commercially available airfelt training pants sold by The Procter & Gamble Company under the trademark PAMPERS EASY UPS (girl size 4; bag count 26; Lot #'s 9215U0175512:45; 9214U0175516:19—Ex. 185-187; and 9214U175512:46).

Examples 189-193 are commercially available airfelt training pants sold by The Procter & Gamble Company under the trademark PAMPERS EASY UPS (girl size 5; bag count 23; Lot #'s 914U0112806:15; 9205U0175520:33; and 918U0175517:44—Ex. 191-193).

Examples 194-198 are commercially available airfelt training pants sold by The Procter & Gamble Company under the trademark PAMPERS EASY UPS (boy size 4; bag count 26; Lot #'s 9109U01701R06:26—Ex. 194 and 195; 9191U0175503:59—Ex. 196 and 197; and 9109U01701R06:25).

Examples 199-203 are commercially available airfelt training pants sold by The Procter & Gamble Company under the trademark PAMPERS EASY UPS (boy size 5; bag count 23; Lot #'s 9227U0175510:51—Ex. 199 and 200; 9123U0175504:27; 9207U0175519:34; and 9207U0175519:30).

Examples 204-208 are commercially available airfelt training pants sold by The Procter & Gamble Company under the trademark PAMPERS UNDERJAMS (girl size S/M; bag count 17; Lot #'s 9213U0112601:47—Ex. 204-207; and 9156U0112600:34).

Examples 209-213 are commercially available airfelt training pants sold by The Procter & Gamble Company under the trademark PAMPERS UNDERJAMS (girl size L/XL; bag count 13; Lot #'s 9030U0112620:06; 9030U0112616:52; and 9136U0112600:40—Ex. 211-213).

Examples 214-218 are commercially available airfelt training pants sold by The Procter & Gamble Company under the trademark PAMPERS UNDERJAMS (boy size S/M; bag count 17; Lot #'s 9091U0112623:43; 9147U0112621:33; 9212U0112618L:54; and 9220U0112603:23—Ex. 217 and 218).

TEST METHODS

The test methods and apparatus described below may be useful in testing embodiments of the present disclosure:

STIFFNESS TEST

The Stiffness Test is described in detail above.

IN-BAG STACK HEIGHT

The In-Bag Stack Height is determined as follows:

Equipment

- Universal Diaper Packaging Tester (UDPT) (Model# M-ROEL; Machine# MK-1071), including a horizontal sliding plate (horizontal plate that moves up and down in a vertical

plane) for adding weights. It is counter-balanced by a suspended weight to assure that no downward force is added from the horizontal sliding plate assembly to the diaper package at all times. The UDPT is available from Matsushita Industry Co. LTD, 7-21-101, Midorigaoka-cho, Ashiya-city, Hyogo JAPAN. Zip code: 659-0014.

- A 850 g (± 5 g) weight.

Definitions

- As illustrated in FIG. 5a, package width 108 is defined as the maximum distance between the two highest bulging points along the same compression stack axis 110 of a diaper package.
- In-Bag Stack Height = (Package Width / Pad Count Per Stack) x 10 pads of diapers.

Apparatus Calibration

- Pull down the horizontal sliding plate until its bottom touches the tester base plate.
- Set the digital meter located at the side of the horizontal sliding scale to zero mark.
- Raise the horizontal sliding plate away from the tester base plate.

Test Procedure

- Put one of the side panel of the diaper package along its width standing at the center of the tester base plate. Make sure the vertical sliding plate (vertical plate that moves left and right in a horizontal plane) is pulled to the right so it does not touch the package being tested.
- Add the 850 g weight onto the vertical sliding plate.
- Allow the horizontal sliding plate to slide down slowly until its bottom lightly touches desired highest point of the package.
- Measure the package width in mm (distance from the top of the base plate to the top of the diaper package). Record the reading that appears on the digital meter.
- Remove the 850 g weight.
- Raise the horizontal sliding plate away from the diaper package.
- Remove the diaper package.

Calculation/Reporting

- Calculate and report the “In-Bag Stack Height” = (Package Width / Pad Count Per Stack) x 10.

- Report Sample Identification, i.e. complete description of product being tested (product brand name/size).
- Report the determined value for each width measurement to the nearest 1 mm.
At least five diaper packages having the same pad count are measured in this manner for a given product and the in-bag stack height values are aggregated to calculate an average and standard deviation.
- Report the Production Date of the measured package (taken from package coding).
- Report the Testing Date and Analytical Method used.

FOLDED STACK LENGTH

The Folded Stack Length is determined as follows:

Equipment

- Universal Diaper Packaging Tester (UDPT) (Model# M-ROEL; Machine# MK-1071), including a horizontal sliding plate (horizontal plate that moves up and down in a vertical plane) for adding weights. It is counter-balanced by a suspended weight to assure that no downward force is added from the horizontal sliding plate assembly to the diaper package at all times. The UDPT is available from Matsushita Industry Co. LTD, 7-21-101, Midorigaoka-cho, Ashiya-city, Hyogo JAPAN. Zip code: 659-0014.
- A 850 g (± 5 g) weight.

Definitions

- As illustrated in FIGs. 7a and 7b, pad nose 142 is the outer pad folding of an absorbent article and pad tail 140 is the outer endflap end of an absorbent article.
- As further illustrated in FIGs. 7a and 7b, stack length is the average folded pad length 144 of 10 pads of diapers.

Apparatus Calibration

- Raise the horizontal sliding plate away from the tester base plate to allow stacks of diapers to be placed on the tester base plate.
- Move the vertical sliding plate (vertical plate that moves left and right in a horizontal plane) to the left until it touches the vertical anchored plate.
- Set the digital meter located on the side of the horizontal sliding plate to the zero mark.
- Move the vertical sliding plate to the right to allow stacks of diapers to be placed on the tester base plate.

Stack Length

Preparation

- Place 10 diapers individually on top of each other on the tester base. For taped diapers, the landing zone side is upwards within the UDPT. For pants, the front-side is upwards within the UDPT.
- Place the stack of 10 diapers along the folded pad length (“nose” facing vertical anchored plate) on the tester base, such that good contact is achieved between the stack and the vertical anchored plate.

Test Procedure

- Add the 850 g weight onto the horizontal sliding plate.
- Allow the horizontal sliding plate to slide down slowly until its bottom lightly touches the stack of diapers. Release the plate such that the plate comes to rest on the diaper stack.
- Condition the stack under the weight for 15 seconds.
- Move the vertical sliding plate towards the anchored vertical plate until the plate touches the tail of the first pad. Stop moving the vertical plate as soon as it gets in contact with the tail of the first pad.
- Record the reading that appears on the digital meter.
- Remove the 850 g weight.
- Raise the horizontal sliding plate away from the stack of diapers.
- Remove the stack of diapers.

Calculation/Reporting

- Report the determined value for stack length. At least five samples (5 diaper packages having the same pad count) are measured in this manner for a given product and the folded stack length values are aggregated to calculate an average and standard deviation.
- Report Sample Identification, i.e. complete description of product being tested (product brand name/size).
- Report the Production Date of the measured package (taken from package coding).
- Report the Testing Date and Analytical Method used.

The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such

dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as “40 mm” is intended to mean “about 40 mm”.

Every document cited herein, including any cross referenced or related patent or application, is hereby incorporated herein by reference in its entirety unless expressly excluded or otherwise limited. The citation of any document is not an admission that it is prior art with respect to any invention disclosed or claimed herein or that it alone, or in any combination with any other reference or references, teaches, suggests or discloses any such invention. Further, to the extent that any meaning or definition of a term in this document conflicts with any meaning or definition of the same term in a document incorporated by reference, the meaning or definition assigned to that term in this document shall govern.

While particular embodiments of the present invention have been illustrated and described, it would be obvious to those skilled in the art that various other changes and modifications can be made without departing from the spirit and scope of the invention. It is therefore intended to cover in the appended claims all such changes and modifications that are within the scope of this invention.

What is claimed is:

1. A shipping optimization process for absorbent articles having a substantially airfelt free absorbent core, characterized in that it comprises the steps of:
 - (a) identifying an optimized diaper;
 - (b) identifying an optimized bag for holding two or more optimized diapers;
 - (c) identifying an optimized box for holding two or more optimized bags;
 - (d) identifying an optimized pallet and arranging the optimized boxes thereon; and
 - (e) identifying an optimized load plan for a vehicle and arranging the optimized pallets therein;wherein the vehicle has a calculated Load Factor of from 0.7 to 1.0 when the vehicle is loaded with the optimized pallets.
2. The process according to Claim 1, characterized in that the step of identifying an optimized diaper includes: a design inputs phase comprising gathering data regarding one or more items selected from the group consisting of consumer needs, business needs, habits and practices, and market research; and a design objective phase comprising inputting the data collected from the design inputs phase and determining a basic design for the diaper, and modifying and engineering the basic design considering additional factors, such factors comprising one or more item selected from the group consisting of raw material costs, raw material availability, sizes and size dimensions, performance requirements, design aesthetics, and manufacturing capabilities.
3. The process according to Claim 1, characterized in that the step of identifying an optimized bag includes: a diaper parameters phase comprising gathering data regarding one or more items selected from the group consisting of folded diaper dimensions, diaper weight, pad count, in-bag compression, diaper compressibility, and transfer compression; and a bag inputs phase comprising inputting the data collected from the diaper parameters phase and determining the materials, physical characteristics, and dimensions of the optimized bag considering additional factors, such factors comprising one or more

items selected from the group consisting of bag stretch, pad orientation, whether to include a wicket slit, stack height, whether to include a window type if any, stack number, stack orientation, handle type if any, and bag side bulge.

4. The process according to Claim 1, characterized in that the step of identifying an optimized box includes: a bag parameters phase comprising gathering data regarding one or more items selected from the group consisting of bag dimensions, filled bag weight, bag compressibility, and pad compression; and a box inputs phase comprising inputting the data collected from the bag parameters phase and determining the design of the optimized box considering additional factors, such factors comprising one or more items selected from the group consisting of flat bag circumference, bag width, front to back bag distance, height of bag, stretch of loaded bag, percent compression at transfer, bag orientation, stacked bag count, bag side bulge, vertical edge radius, film gauge, in-box compression, in-box height, and maximum bag number/orientation.
5. The process according to Claim 1, characterized in that the step of identifying an optimized pallet includes: a box parameters phase comprising gathering data regarding one or more items selected from the group consisting of container type, type and location of glue flaps, length and width of glue flaps, number of colors on the container, type of printing, and container handles; and a pallet inputs phase comprising inputting the data collected from the box parameters phase and determining the unit load design of the optimized pallet considering additional factors, such factors comprising one or more items selected from the group consisting of pallet dimensions, over-hang specifications, cases per layer, mixed pallet requirement, under-hang specifications, pallet pattern selection, and layers per pallet.
6. The process according to Claim 1, characterized in that the step of identifying an optimized vehicle includes: a pallet parameters phase comprising gathering data regarding one or more items selected from the group consisting of pallet load weight, pallet load volume, and pallet load volume utilization; and a trailer inputs phase

comprising inputting the data collected from the pallet parameters phase and determining the load plan of the optimized vehicle considering additional factors, such factors comprising one or more items selected from the group consisting of trailer height, trailer length, trailer width, and staggered load requirements.

7. The process according to any one of the preceding claims, characterized in that the vehicle has a calculated Load Factor of from 0.75 to 1.0 when the vehicle is loaded with the optimized pallets, preferably from 0.81 to 0.95.
8. The process according to any one of the preceding claims, characterized in that the optimized diaper has an In-Bag Stack Height of less than or equal to 80 mm, preferably from 72 mm to 80 mm.
9. The process according to any one of the preceding claims, characterized in that the optimized diaper has an In-Bag Compression of greater than or equal to 58%, preferably from 58% to 62%.
10. The The process according to any one of the preceding claims, characterized in that the optimized diaper has a longitudinal bending stiffness of less than or equal to 355 N/m, preferably from 285 N/m to 355 N/m.
11. The process according to any one of the preceding claims, characterized in that the optimized diaper has a bag utilization factor of less than or equal to 0.030 m²/pad/m, preferably from 0.027 m²/pad/m to 0.030 m²/pad/m.
12. A pallet of absorbent products characterized in that it comprises:

a plurality of packages each having a plurality of disposable absorbent articles disposed within the interior space of the package, each of the disposable absorbent articles having

a topsheet; a backsheet; a substantially cellulose free absorbent core located between the topsheet and the backsheet; a first waist region; a second waist region; a crotch region extending longitudinally between the first and second waist regions; and a fastening member extending laterally outward from the second waist region and adapted to releasably connect with a landing zone located in the first waist region;

wherein the absorbent products arranged on the pallet exhibit a calculated Load Factor of less than or equal to 1.0, preferably from 0.7 to 1.0.

13. A shipping vehicle of absorbent products characterized in that it comprises:

a transportation area for receiving items to be transported, the vehicle having a maximum weight capacity for transporting items and a maximum volume capacity for transporting items; and

a plurality of packages each having a plurality of disposable absorbent articles disposed within the interior space of the package, each of the disposable absorbent articles having a topsheet; a backsheet; a substantially cellulose free absorbent core located between the topsheet and the backsheet; a first waist region; a second waist region; a crotch region extending longitudinally between the first and second waist regions; and a fastening member extending laterally outward from the second waist region and adapted to releasably connect with a landing zone located in the first waist region;

wherein the vehicle exhibits a calculated Load Factor of from 0.7 to 1.0, preferably from 0.75 to 1.0.