

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 April 2002 (18.04.2002)

PCT

(10) International Publication Number
WO 02/31018 A1

(51) International Patent Classification⁷: **C08G 59/32**,
H01L 21/58, 23/495

(21) International Application Number: PCT/JP01/00314

(22) International Filing Date: 19 January 2001 (19.01.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2000/310083 11 October 2000 (11.10.2000) JP

(71) Applicant (for all designated States except US): **SUM-ITOMO BAKELITE COMPANY LIMITED** [JP/JP];
5-8, Higashishinagawa 2-chome, Shinagawa-ku, Tokyo
140-0002 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **TAKEDA, Toshiro**

[JP/JP]; 3-4-8-402, Shukugo, Utsunomiya-shi, Tochigi
321-0945 (JP). **ONAMI, Kazuto** [JP/JP]; 4673-1,
Miyukihoncho, Utsunomiya-shi, Tochigi 321-0983 (JP).
KAGIMOTO, Tomohiro [JP/JP]; 4673-1, Miyukihoncho,
Utsunomiya-shi, Tochigi 321-0983 (JP).

(74) Agents: **ASAMURA, Kiyoshi** et al.; Room 331, New
Ohtemachi Bldg., 2-1, Ohtemachi 2-chome, Chiyoda-ku,
Tokyo 100-0004 (JP).

(81) Designated States (national): CN, KR, SG, US.

(84) Designated States (regional): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE, TR).

Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DIE-ATTACHING PASTE AND SEMICONDUCTOR DEVICE

(57) Abstract: The present invention provides a resin paste which has a sufficient hot adhesion strength and gives a cured product of low elastic modulus, and thereby, causes no chip cracking or warpage and resultantly no property deterioration of IC or the like even when used for bonding of a large chip (e.g. IC) to copper frame or the like, and which is rapidly-curable, and generates no void. That is, the present invention lies in a die-attaching paste comprising, as essential components: (A) a liquid epoxy resin comprising (a1) an epoxy resin containing chlorine in an amount of 500 ppm or less and having a viscosity of 5,000 mPa Es or less at 25 °C and (a2) an epoxy group-containing reactive diluent containing chlorine in an amount of 300 ppm or less and having a viscosity of 1,000 mPa Es or less at 25 °C, the weight ratio of (a1):(a2) being 40:60 to 90:10, (B) a phenol compound having at least two hydroxyl groups in the molecule, (C) a latent curing agent, (D) an imidazole compound, and (E) an inorganic filler. The present invention also lies in a semiconductor device produced by using the above die-attaching paste.

WO 02/31018 A1