

High speed receptacle connector part

FIELD OF THE INVENTION

[0001] The invention relates in general to electrical connectors. More particularly, the invention relates to a high speed receptacle connector part.

5 BACKGROUND OF THE INVENTION

[0002] As the speed of electronics increases, electrical connectors are desired that are capable of high speed communications. Electrical connectors provide signal connections between electronic devices using signal contacts.
10 With electronic device miniaturization and high speed electronic communications becoming more prevalent, the signal contacts will be very closely spaced. Often, the signal contacts are so closely spaced that signal integrity becomes a problem.

15 [0003] One method for improving signal integrity is removing the plastic material in the contact area of the contacts. In this manner air will be the main dielectric in the contact area of the contacts. However reducing plastic material in the contact area of a connector part poses
20 problems regarding positioning and supporting of the contact portions of the signal contacts. Therefore, a need exists for a high speed electrical connector design that reduces the plastic material while maintaining a guaranteed support of the contact portions of the signal contacts.

25 SUMMARY OF THE INVENTION

[0004] The invention satisfies the aforementioned need by providing a high speed receptacle connector part, wherein all plastic material in the contact area of the contact terminals has been removed. According to an aspect of the
30 invention a receptacle connector part is provided, comprising a connector housing and a plurality of rows of receptacle contact terminals disposed within the housing. Each receptacle contact terminal includes two single beam contacts

having contact portions with a preload head, and the connector housing comprises a front wall with a plurality of rows of apertures providing access to the contact portions of the contact terminals. Specifically, the connector housing is provided with a plurality of rows of preload ridges, the preload ridges being located at the inner side of the front wall at opposed sides of the apertures, wherein the preload ridges cooperate with said preload heads to support the contact portions of the single beam contacts of each contact terminal in a predetermined preload position.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] The invention will be further explained by reference to the drawings showing an illustrative embodiment of the receptacle connector part according to the invention.

15 [0006] Fig. 1 is a top view of the back side of the connector housing of an exemplary embodiment of the receptacle connector part in accordance with the invention.

[0007] Fig. 2 is a cross-section of the connector housing according to the line II-II in Fig. 1.

20 [0008] Fig. 3 is a perspective view of the connector housing of Fig. 1.

[0009] Fig. 4A and 4B show a top and side views of a row of receptacle contact terminals to be mounted in the connector housing of Fig.1.

25 [0010] Fig. 5 shows a cross-section of the connector housing of Fig. 1 during the assembly step of inserting a row of receptacle contact terminals.

30 [0011] Fig. 6 shows a cross-section corresponding to Fig. 5, wherein the contact portion of the receptacle contact terminals is meeting the preload ridges.

[0012] Fig. 7 shows a cross-section corresponding to Fig. 5, wherein the row of receptacle contact terminals is further inserted into the housing.

35 [0013] Fig. 8 shows a cross-section corresponding to Fig. 5, wherein the row of receptacle contact terminals is fully inserted into the connector housing.

[0014] Fig. 9 shows a cross-section corresponding to Fig. 8, wherein the contact portions of the contact terminals are shown in a position as if a plug signal or ground contact has been inserted.

5 [0015] Fig. 10 is a perspective view of the connector housing.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

[0016] Referring to the drawings there is shown an embodiment of the receptacle connector part according to the invention, comprising a connector housing 1 shown in Figs. 1-3, and a plurality of rows of receptacle contact terminals 2 shown in Figs. 4A and 4B. Figs. 5-8 show a cross section of the connector housing 1 with one row of contact terminals 2 during an assembly step of inserting the contact terminals 2 into the housing 1. In the drawings the connector housing 1 is shown open at one side for explanation purposes only. Normally, a side wall will be present.

[0017] Each receptacle contact terminal 2 includes two single beam contacts 3 having a contact portion 4 with a preload head 5 at its contact tip. As can be seen in the side view of the row of contact terminals 2 in Fig. 4B the contact portions have a kind of hammer head shape, wherein the preload heads 5 of the single beam contacts of one contact terminal 2 extend in opposite directions along the row direction.

25 [0018] The connector housing 1 comprises a front wall 6 with a plurality of rows of apertures 7, which apertures 7 provide access to the contact portions 4 of the contact terminals 2. Further, the connector housing 1 is provided with a plurality of rows of preload ridges 8 located at the inner side of the front wall 6 at opposed sides of the apertures 7. As will be explained hereinafter the preload ridges 8 cooperate with the preload heads 5 to support the contact portions 4 of the single beam contacts 2 of each contact terminal 2 in a predetermined preload position shown in Fig. 8. In the embodiment shown in the drawings one V-shaped preload ridge 8 is located in between each two adjacent apertures 7. The tip of the V-shaped ridges 8 is directed

away from the apertures 7. In this manner, each V-shaped ridge 8 shows two ramp surfaces 9 and 10 extending in a lateral and downward direction from the centre line of a row of apertures 7 to one side of the row of apertures. It is
5 noted that lateral direction means transverse to the row direction and downwards means from the upper to the lower side of the views as shown in Figs. 2 and 8.

[0019] Although in the embodiment shown one V-shaped preload ridge 8 is located in between each two adjacent
10 apertures 7, it will be clear that different embodiments and shapes of pre-load ridges are possible providing ramp surfaces 9, 10 extending in the same manner in a lateral and downward direction. For example, separated V-shaped ridges could be provided, each having ramp surfaces 9, 10. Such V-shaped
15 ridges 8 can be seen at the upper and lower sides of the top view of Fig. 1. As a further alternative separated preload ridges could be provided, one preload ridge having the ramp surface 9 and the other preload ridge having the ramp surface 10. In the latter case the ramp surfaces 9, 10 could extend
20 along the full transverse dimension of the apertures 7.

[0020] Preferably, the V-shaped preload ridges 8 are provided with four support extensions 11, 12, each two support extensions 11, 12 extending in row direction along opposed sides in an aperture 7. In this manner, each aperture
25 7 is bounded by four support extensions 11, 12 directed towards each other at opposed sides of the aperture.

[0021] In the embodiment shown in the drawings, the ramp surfaces 9, 10 of the V-shaped preload ridges have first and second sections 13, 14, extending downwardly at different
30 angles. As can be seen in the cross-sections of Figs. 2 and 8, for example, the second section 14 extends more steeply downwardly as the first section 13.

[0022] Figs. 5-8 show subsequent phases of the assembly of the receptacle connector part as described, during
35 which assembly the rows of contact terminals 2 are inserted into the connector housing 1. In the cross-section of Fig. 5 a centre row of contact terminals 2 is in a first phase of the insertion process. It is noted that a row of contact

terminals can be provided as an assembly as described in US patent 6,652,318, wherein the terminals are interconnected by a holder 15 of insulating material. The contact portions 4 are slightly open at the contact tip, so that the tip of the V-shaped ridges 8 can be received in between the contact portions 4. In the cross-section of Fig. 6, the preload heads 5 of the contact portions 4 are meeting with the first sections 13 of the ramp surfaces 9, 10 of the V-shaped ridges 8 at both sides of the corresponding apertures 7. During the further insertion of the row of contact terminals 2 into the connector housing 1, the contact portions 4 are further opened as the preload heads 5 move further downwards along the ramp surfaces 9, 10. In the last part of the insertion process, the preload heads 5 of the contact portions 4 will be received on the support extensions 11 of the V-shaped ridges 8 as shown in particular in Fig. 8. Fig. 9 shows a cross section of the connector housing 1 as in Fig. 8, wherein the contact portions 4 are moved outwardly as if a contact pin has been inserted through the corresponding aperture 7. In this contacting position the preload heads 5 are lifted off from the support extensions 11, 12.

[0023] In the final position of the contact terminals 2 as shown in Fig. 8, the contact portions 4 are accurately supported with a guaranteed preload, wherein the contact area of the contact portions 4 is fully free of any plastic material. In this manner the signal integrity performance of the contact terminals 2 is improved. Moreover, the design of the V-shaped preload ridges 8 with the support extensions 11, 12 extending along the sides of the apertures 7 in row direction, guarantees a reliable support of the contact portions 4 in the pre-load position within the full range of manufacturing tolerances of all parts of the receptacle connector part.

[0024] In the embodiment of the receptacle connector part shown, any interference of the contact portions, in particular the contact tip parts thereof, is avoided by providing windows 16 in the sidewall 17 of the connector housing 1. These windows 16 receive the contact portion of

the terminals 2 of the adjacent row of receptacle contact terminals. In the same manner windows 18 are provided in the lateral sidewalls 19 of the connector housing 1, only one of which is shown in the drawings. Fig. 10 illustrates the
5 presence of the windows 16 in the sidewall 17 and the windows 18 in the lateral sidewall 19.

[0025] It is to be understood that the foregoing illustrative embodiments have been provided merely for the purpose of explanation and are in no way to be construed as
10 limiting of the invention. The invention extends to all functionally equivalent structures, such as are within the scope of the appended claims.

CLAIMS

1. Receptacle connector part, comprising a connector housing and a plurality of rows of receptacle contact terminals disposed within the housing, each receptacle contact terminal including two single beam contacts having contact portions with a preload head, the connector housing comprising a front wall with a plurality of rows of apertures providing access to the contact portions of the contact terminals, wherein the connector housing is provided with a plurality of rows of preload ridges, the preload ridges being located at the inner side of the front wall at opposed sides of the apertures, wherein the preload ridges cooperate with said preload heads to support the contact portions of the single beam contacts of each contact terminal in a predetermined preload position.

2. Receptacle connector part according to claim 1, wherein said two single beam contacts of one receptacle contact terminal are provided with preload heads extending in opposite directions, and each preload ridge is provided with a ramp surface extending in a lateral and downward direction from at least the center of a row of apertures to one side of the row of apertures, wherein the ramp surfaces of the preload ridges at opposed sides of an aperture extend laterally in opposite directions, said ramp surfaces cooperating with the oppositely directed preload heads of a contact terminal.

3. Receptacle connector part according to claim 2, wherein the preload ridges each are provided with a support extension extending along one side of a corresponding aperture in row direction, the support extensions of the preload ridges at opposed sides of an aperture being directed towards each other at opposed sides of the corresponding aperture, wherein said support extensions support the preload heads.

4. Receptacle connector part according to claim 3, wherein the preload ridges are generally V-shaped preload ridges, and wherein a tip of the V-shape is directed away from the apertures.

5. Receptacle connector part according to claim 4, wherein the V-shaped preload ridges at adjacent sides of adjacent apertures are made as one V-shaped ridge located in between each two adjacent apertures, wherein the ramp surfaces of one V-shaped ridge cooperate with the preload heads of two adjacent receptacle contact terminals in a row of receptacle contact terminals.

6. Receptacle connector part according to claim 5, wherein each V-shaped ridge located in between two adjacent apertures is provided with four support extensions, each two support extensions extending in row direction along opposed sides of an aperture.

7. Receptacle connector part according to claim 3, wherein the ramp surfaces of the preload ridges have first and second sections extending downwardly at different angles, wherein the second section extends more steeply as the first section.

8. Receptacle connector part according to claim 1, wherein the connector housing comprises side walls extending in row direction, at least one of said side walls having windows for receiving a contact portion of a receptacle contact terminal.

9. Receptacle connector part according to claim 8, wherein the connector housing comprises lateral side walls extending lateral to the row direction, at least one of said lateral side walls having windows for receiving a contact portion of a receptacle contact terminal.

10. A receptacle connector part, comprising:
a connector housing; and
a receptacle contact terminal disposed within the housing, said receptacle contact terminal including two single beam contacts, each said single beam contact having a respective contact portion with a respective preload head, the connector housing comprising a front wall with an aperture providing access to the contact portions,
wherein the connector housing is provided with a pair of preload, the preload ridges being located at the inner side of the front wall at opposed sides of the aperture, wherein the

preload ridges cooperate with said preload heads to support the contact portions of the single beam contacts in a predetermined preload position.

11. The receptacle connector part according to claim 5 10, wherein said two single beam contacts are provided with preload heads extending in opposite directions.

12. The receptacle connector part according to claim 11, wherein each said preload ridge is provided with a ramp surface extending in a lateral and downward direction from at 10 least the center of the aperture to one a side of the aperture.

13. The receptacle connector part according to claim 12, wherein the ramp surfaces of the preload ridges extend laterally in opposite directions, said ramp surfaces 15 cooperating with the oppositely directed preload heads of a the contact terminal.

14. The receptacle connector part according to claim 11, wherein each of the preload ridges is provided with a support extension extending along a side of the aperture, the 20 support extensions being directed towards each other at opposed sides of the aperture, wherein said support extensions support the preload heads.

15. The receptacle connector part according to claim 25 14, wherein each of the preload ridges is generally V-shaped, and wherein a tip of the V-shape is directed away from the aperture.

16. The receptacle connector part according to claim 12, wherein the ramp surfaces of the preload ridges have first 30 and second sections extending downwardly at different angles, wherein the second section extends more steeply than the first section.

17. The receptacle connector part according to claim 10, wherein the connector housing comprises side walls 35 extending in row direction, at least one of said side walls having windows for receiving a contact portion of a receptacle contact terminal.

18. The receptacle connector part according to claim 17, wherein the connector housing comprises lateral side walls extending lateral to the row direction, at least one of said lateral side walls having windows for receiving a contact
5 portion of a receptacle contact terminal.