

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织  
国际局



(10) 国际公布号  
**WO 2024/168906 A1**

(43) 国际公布日  
2024 年 8 月 22 日 (22.08.2024)

(51) 国际专利分类号:  
**H04W 72/30** (2023.01)

海淀区上地三街 9 号嘉华大厦 B 座 409,  
Beijing 100085 (CN)。

(21) 国际申请号: PCT/CN2023/076976

(81) 指定国(除另有指明, 要求每一种可提供的国家  
保护): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG,  
BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU,  
CV, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IQ,  
IR, IS, IT, JM, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ,  
LA, LC, LK, LR, LS, LU, LY, MA, MD, MG, MK, MN,  
MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE,  
PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE,  
SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, WS, ZA, ZM, ZW。

(22) 国际申请日: 2023 年 2 月 17 日 (17.02.2023)

(25) 申请语言: 中文

(26) 公布语言: 中文

(71) 申请人: 北京小米移动软件有限公司 (BEIJING  
XIAOMI MOBILE SOFTWARE CO., LTD.) [CN/CN];  
中国北京市海淀区西二旗中路 33 号院 6 号  
楼 8 层 018 号, Beijing 100085 (CN)。

(72) 发明人: 刘晓菲 (LIU, Xiaofei); 中国北京市海  
淀区西二旗中路 33 号院 6 号楼 8 层 018  
号, Beijing 100085 (CN)。

(84) 指定国(除另有指明, 要求每一种可提供的地区  
保护): ARIPO (BW, CV, GH, GM, KE, LR, LS, MW, MZ,  
NA, RW, SC, SD, SL, ST, SZ, TZ, UG, ZM, ZW), 欧亚  
(AM, AZ, BY, KG, KZ, RU, TJ, TM), 欧洲 (AL, AT, BE,  
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR,

(74) 代理人: 北京博思佳知识产权代理  
有限公司 (BEIJING BESTIPR INTELLECTUAL  
PROPERTY LAW CORPORATION); 中国北京市

(54) Title: CONFIGURATION RECEIVING METHOD AND APPARATUS, AND CONFIGURATION RECEPTION DETERMINING METHOD AND APPARATUS

(54) 发明名称: 配置接收、配置接收确定方法和装置

当从第一小区移动到第二小区, 且没有第二小区中可用的组播业务配置, 确定是否进入连接态获取组播业务配置

S201  
图 2

S201 When moving from a first cell to a second cell and having no available multicast service configuration in the second cell, determine whether to enter a connected state to acquire a multicast service configuration

(57) Abstract: The present disclosure relates to the technical field of communications, and in particular relates to a configuration receiving method and apparatus, and a configuration reception determining method and apparatus. The configuration receiving method comprises: when moving from a first cell to a second cell and having no available multicast service configuration in the second cell, determining whether to enter a connected state to acquire a multicast service configuration. In the present disclosure, when a terminal moves from the first cell to the second cell, but has no available multicast service configuration in the second cell, the terminal can determine whether to enter the connected state to acquire the multicast service configuration. Therefore, when there are multiple acquisition modes for the multicast service configuration, the terminal can determine a selection mode of acquiring the multicast service configuration, thus avoiding the terminal failing to determine a certain acquisition mode for acquiring the multicast service configuration and thus causing problems in multicast service reception.

(57) 摘要: 本公开涉及通信技术领域, 具体涉及配置接收、配置接收确定方法和装置, 其中, 所述配置接收方法包括: 当从第一小区移动到第二小区, 且没有第二小区中可用的组播业务配置, 确定是否进入连接态获取组播业务配置。根据本公开, 终端当从第一小区移动到第二小区, 但是没有在第二小区中可用的组播业务配置时, 可以确定是否进入连接态获取组播业务配置。据此, 在组播业务配置的获取方式有多种的情况下, 终端可以确定获取组播业务配置的选择方式, 避免终端不能确定按照哪种获取方式来获取组播业务配置而导致接收组播业务出现问题。

[见续页]

WO 2024/168906 A1

HU, IE, IS, IT, LT, LU, LV, MC, ME, MK, MT, NL, NO,  
PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF,  
CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN,  
TD, TG)。

本国际公布:

— 包括国际检索报告(条约第21条(3))。