

LINEAR DRIVING UNIT WITH A RESONANT SPRING AND A DEFORMATION CONTROL DEVICEField of the invention

The present invention refers to a device for controlling
5 certain deformations of the resonant spring of a linear
driving unit, such as, for example, the linear motor of a
refrigeration compressor, comprising a motor housing,
which is electrically excited and affixed to a fixed
structure, and a magnetic armature which is displaced, by
10 the electric excitation of the motor housing, in a
reciprocating axial movement. When applied to
refrigeration compressors, the magnetic armature is
coupled, on one side, to a piston to be displaced in the
interior of a cylinder or compression chamber and, on the
15 other side, to an end of a helical resonant spring, whose
opposite end is affixed to said fixed structure.

The present invention can be applied to linear
compressors, or to any other type of construction which
uses a resonant spring, operating in conjunction with an
20 electric linear driving unit, for avoiding the radial
elastic deformations of the resonant spring from
negatively affecting the operation of the element to be
linearly and reciprocally displaced by the driving unit,
generally in the interior of a cooperating element, as it
25 occurs in the operational relationship between the piston
and the cylinder of a refrigeration compressor.

Prior art

Helical springs are commonly used as elements for storing
potential energy in resonant systems used in several
30 applications, such as in linear driving units, for
example the linear motors of refrigeration compressors.

As exemplarily illustrated in figure 1 of the appended
drawings, the compressors which are generally used for
refrigeration and driven by an electric motor of the
35 linear type, comprise a housing 1, generally hermetic and
which houses a non-resonant assembly including a
crankcase 10 which can be mounted in the housing 1 by

means of suspension springs 11, for example, springs of the helical type.

The crankcase 10 incorporates a cylinder 12, in the interior of which is defined a compression chamber 13, having an end 13a generally closed by a valve plate and by a head 25, and an open opposite end 13b through which is mounted a piston 20 reciprocating in the interior of the compression chamber 13. The piston 20 is coupled, through a coupling means, generally in the form of a rod 30, to a magnetic armature A, carrying magnets 40 of a linear motor M which further comprises a motor housing C, affixed to a fixed structure and which is electrically excited so as to displace, axially and reciprocally, the magnetic armature A.

In the construction of the linear driving unit of a refrigeration compressor, the motor housing C can be directly affixed to the housing 1 of said compressor, or to any of the component parts of the non-resonant assembly of said compressor, such as, for example and as illustrated, the crankcase 10 thereof. The housing 1 of the compressor defines, in this case, a fixed structure for the fixation of the motor housing C.

The linear motor M is responsible for generating the necessary drive for displacing the piston 20 in the interior of the compression chamber 13 of the cylinder 12 and, consequently, for the compression of the refrigerant fluid, in the form of gas.

To the movable assembly defined by the piston, rod, and magnetic armature is coupled a resonant spring means, generally comprising at least one helical resonant spring 50, which is mounted so as to exert opposite axial forces on the piston 20, upon its reciprocating axial displacement in the interior of the compression chamber 13. The resonant spring 50 operates as a guide for the axial displacement of the piston 20, and also actuates on the compression movable assembly, jointly with the linear motor M of the compressor. The compression movable

assembly (piston-rod-magnetic armature) and the resonant spring 50 define the resonant assembly of the compressor. In the prior art construction, exemplified in figure 1, the resonant spring 50 has a helical shape, having an end 50a coupled to the fixed structure, and an opposite end 50b coupled to the magnetic armature A, so as to be axially and elastically deformed, jointly with the reciprocating axial movement of the magnetic armature A. In the illustrated construction, the ends 50a and 50b of the resonant spring 50 are respectively affixed to the non-resonant assembly, for example, to the crankcase 10 or to the support structure thereof, and to the compression movable assembly.

The actuation of the resonant spring causes a great deformation in a main vibration mode (axial elastic deformation), which is the mode responsible for the correct coaxial positioning of the piston 20 in the interior of the cylinder 10, during the operation of the compressor. The deformation of the resonant spring 50 in the main vibration mode is proportional to its capacity of storing and restoring the energy for moving the piston 20.

While it is desirable to have a great capacity of deformation of the resonant spring 50 in a determined vibration mode, the other vibration modes are, as a rule, undesirable. Torsional and radial modes may generate great tensions and displacements of the piston 20 in undesirable non-axial directions, leading the compressor to present catastrophic failures.

At present, the control of the presence of undesirable vibration modes resulting from the actuation of the resonant spring 50 is obtained by avoiding, in the project, the existence of such modes, that is, modes close to the frequency harmonic of the compressor operation, and by avoiding such undesirable vibration modes of the resonant spring 50 from being provoked by movement of the magnetic armature A of the electric motor

M, upon operation of the compressor.

Nevertheless, in compressors that work with variable capacity (or variable operating frequency), said control is difficult to implement, due to the fact that the compressor no longer operates in a fixed fundamental frequency, but within a range of frequencies, facilitating the potential of exciting the undesirable modes.

Summary of the invention

10 In view of the above, the present invention has the generic object to provide a deformation control device for a resonant spring in a linear driving unit, which allows, by means of a simple construction, to control the deformation of the resonant spring, limiting said
15 deformation to a determined main vibration mode, minimizing or even eliminating the undesirable other vibration modes, during the whole useful life of the linear driving unit, preserving the energy of the main vibration mode and without requiring alterations in the
20 constructive characteristics of the resonant spring.

The present invention has also the object to provide a control device, such as cited above and which allows controlling and minimizing the lateral and torsional displacements of the resonant spring resulting from said
25 undesirable vibration modes.

It is a further object of the present invention to provide a control device, such as cited above and which, in the case of the refrigeration compressors, can guarantee the spring/piston/cylinder alignment, reducing
30 the tensions on the spring wire during the useful life of the compressor.

In order to comply with the objectives cited above, the present invention proposes a deformation control device for a resonant spring in a linear driving unit, of the
35 type which comprises: a linear electric motor formed by a motor housing, which is electrically excited and affixed to a fixed structure, and by a magnetic armature

displaced by the electric excitation of the motor housing, in a reciprocating axial movement; and a helical resonant spring, having an end coupled to the fixed structure, and an opposite end coupled to the magnetic armature, in order to be displaced by the latter and elastically deformed, in a reciprocating axial movement. According to the invention, the deformation control device for a resonant spring in a linear driving unit is mounted to the resonant spring, in order to maintain contact with a surface extension of the resonant spring, which is elastically and radially deformed upon the reciprocating axial movement of said resonant spring, and to generate at least one of the conditions: of friction with said surface extension of the resonant spring; and of elastic deformation of said deformation control The device, absorbing energy in a value sufficient to at least minimize said radial elastic deformation of the resonant spring.

According to a particular aspect of the present invention, the deformation control device is provided around and along a wire extension of the resonant spring. According to a constructive form of the present invention, the deformation control device is defined by a damping spring in the form of a cylindrical helical spring which is mounted, directly and tightly, around said wire extension of the resonant spring.

According to another constructive form of the present invention, the deformation control device is defined by a tubular coating which surrounds, integrally and circumferentially, said wire extension of the resonant spring, maintaining direct contact with the latter or being provided around the damping spring, when present.

Brief description of the drawings

The invention will be described below, making reference to the appended drawings, given by way of example of embodiments of the invention and in which:

Figure 1 represents a schematic and simplified

longitudinal sectional view of a compressor driven by a linear motor and having the resonant spring mounted to the parts of compression movable assembly and non-resonant assembly, according to a prior art arrangement, deprived of the present control device;

Figure 2 represents, schematically, an enlarged perspective view of a portion of the resonant spring of a linear driving unit, such as that of figure 1, but carrying a deformation control device defined by an tubular coating in elastomer;

Figure 3 represents, schematically, an enlarged perspective view of a portion of the resonant spring of a linear driving unit, such as that of figure 1, but carrying a deformation control device defined by a damping spring made of a strip;

Figure 4 represents, schematically, an enlarged perspective view of a portion of the resonant spring of a linear driving unit, such as that of figure 1, but carrying a deformation control device defined by a damping spring formed by a cylindrical wire;

Figure 5 represents, schematically, a cross-sectional view of a coil of the resonant spring illustrated in figure 4 and carrying the damping spring made of a cylindrical wire and surrounded by a thermo-retractable tubular coating;

Figure 6 represents, schematically, a partial longitudinal sectional view of the resonant spring illustrated in figure 4 and carrying the damping spring made of a cylindrical wire surrounded by a thermo-retractable tubular coating;

Figure 7 illustrates a perspective view of a possible constructive form for the deformation control device, to be applied on a surface extension of the resonant spring; Figures 7A and 7B represent cross-sectional views of the deformation control device of figure 7 and of the resonant spring, illustrating, respectively, a pre-mounting condition and a final mounting condition of the

deformation control device in relation to the resonant spring; and

Figure 8 represents, schematically, a graph illustrating the attenuation of vibration, by unit of frequency, obtained with the control device of the present solution.

Detailed description of the invention

The present invention comprises a deformation control device for a resonant spring, which can be applied to any linear driving unit and of the type comprising: a linear electric motor M formed by a motor housing C, electrically excited and affixed to a fixed structure 1, and by a magnetic armature A displaced by the electric excitation of the motor housing C, in a reciprocating axial movement; and a helical resonant spring 50, having an end 50a of its spring wire coupled to the fixed structure 1, and an opposite end 50b coupled to the magnetic armature A, in order to be, by the latter, axially and reciprocally displaced during the operation of the compressor.

The present invention will be described, considering a particular form of a linear driving unit, such as a refrigeration compressor of the type driven by a linear motor M. It should be understood that, although the linear driving unit, illustrated in figure 1 and described in the introduction of the present specification, is exemplified by a refrigeration compressor, the concept presented herein can be applied to any linear driving unit with the fundamental characteristics defined herein. For the application in a refrigeration compressor, the fixed structure 1 is defined by the housing 1a of said compressor.

The present invention proposes a deformation control device 60, for limiting the deformation of the resonant spring 50, of the type mentioned above.

The construction of the compressor of figure 1 represents the already discussed prior art, which does not provide the damping of the undesirable vibration modes resulting

from the operation of the resonant spring 50.

The deformation control device 60 of the present invention is mounted to the resonant spring 50, in such a way as to contact a surface extension of the wire of the resonant spring 50 subject to radial elastic deformations upon the reciprocating axial movement of the magnetic armature A.

The deformation control device 60 is constructed and mounted to the resonant spring 50 so as to produce, during the axial elastic deformation of the latter, at least one of the following operational conditions: generation of friction force between the deformation control device 60 and the resonant spring 50; and/or generation of elastic deformation force of the deformation control device 60, said operational conditions absorbing energy in a value sufficient to minimize or even eliminate the undesirable radial elastic deformations of the resonant spring 50.

The present invention allows controlling the deformations in determined points of the resonant spring 50 by the addition of structural damping. The points of application should be selected by observing the structural modes considered as undesirable (detrimental), and by preserving the deformation energy of the fundamental mode (elastic axial deformation).

The deformation control device 60 of the present solution controls the lateral and torsional displacements of the resonant spring 50, guaranteeing the spring/piston/cylinder alignment and reducing the tensions on the wire that forms said resonant spring 50.

In a way of carrying out the present invention, the deformation control device 60 is of the type provided around and along a wire extension of the resonant spring 50, said deformation control device 60 being, for example, a tubular coating which surrounds, integrally and circumferentially, the determined wire extension of the resonant spring 50. This solution presents as the

main advantage the facility to mount the tubular coating around the spring wire.

According to this concept, the control device of the resonant spring 60 can be, for example, a tubular coating
5 61 defined by an elastomer (figure 2), for example, rubber vulcanized directly on one or more wire extensions of the resonant spring 50 which are subject to undesirable radial or torsional deformations.

In another constructive option, not illustrated, the
10 tubular coating 61 can be obtained in plastic material, for example, in a thermo-retractable plastic material. In this case, the mounting is also facilitated, with the coating being applied to the desired spring portion and then heated, with the heated material suffering a
15 diameter reduction and remaining firmly mounted on the wire.

According to another way of carrying out the present invention, the deformation control device 60 is provided in helical development along one or more wire extensions
20 of the resonant spring 50, maintaining direct contact with the latter, as illustrated in figures 3, 4, 5 and 6. In a particular form of this construction, the deformation control device 60 is defined by a damping spring 62 provided in helical development along a
25 determined wire extension of the resonant spring 50. The use of such solution brings the advantage of having a low cost.

According to this constructive concept, the deformation control device 60 can take the form of a helical spring
30 made by a strip 62a or by a cylindrical rod 62b, in metal or synthetic material, which is helically mounted, directly and tightly around said wire extension of the resonant spring 50, such as respectively illustrated in figures 3 and 4. This type of helical strip is also easy
35 to be obtained and has a low cost, besides providing a larger area of contact with the wire portion of the resonant spring.

As illustrated in figures 5 and 6, the deformation control device 60 can comprise, simultaneously, a damping spring 62 which is applied, directly and tightly, in helical development, around the wire of the resonant spring 50, and also a tubular coating 61 applied on the damping spring 62 and which can be made of different materials, such as vulcanized rubber, or thermo-retractable plastic, as already mentioned hereinbefore, increasing the effectiveness of the deformation control device.

The tubular coating 61 surrounds not only the wire of the resonant spring 50, but also the entire damping spring 62, forcing even more the contact between the damping spring 62 and the wire of the resonant spring 50, allowing that any undesirable radial or torsional deformations of the resonant spring 50 be transmitted to the deformation control device 60, providing at least one of said friction or deformation conditions, which are necessary to absorb, at least partially, the energy that generates said undesirable deformations of the resonant spring 50.

In said constructive option for the deformation control device 60 comprising the damping spring 62 and a tubular coating 61, in plastic material (thermo-retractable), the latter further allows the damping spring 62 to be more tightly mounted around the resonant spring 50, providing a better absorption of deformation energy of the resonant spring 50 through the deformation control device 60, by mutual friction or by deformation of the latter.

According to the present invention, the preferred constructive form for the deformation control device is the one of the type defined by a tubular coating made of elastomeric material, which is applied on the spring by a vulcanization process, since it is the most practical and allows the resonant spring 50 to be already delivered with the elastomeric material already applied and vulcanized thereon by the supplier of the elastomeric

material.

The deformation control device 60 absorbs the energy from the resonant spring 50, transforming said energy into heat dissipated in the environment in which the deformation control device 60 is mounted. The absorbed energy is the one resulting from the specific vibration modes, other than the fundamental mode, which specific modes work against the desired coaxial operation of the piston 20 in the interior of the cylinder 10.

It should be understood that the deformation control device 60 may be provided in specific regions of the resonant spring 50, which are more prone to present the undesirable displacements, whereas its provision in the whole extension of the resonant spring 50 is prejudicial to the main displacement of said resonant spring 50.

In case the deformation control device 60 is a damping spring 62, this must be affixed against longitudinal displacements along the resonant spring 50. Such fixation can be achieved by applying adhesives to the base of flexible material.

Exemplifying, for a damping spring 62 in steel (in the form of wire or strip) there is, upon the deformation of the resonant spring 50, a rotation of the latter not followed by the material of the damping spring 62 and, in this difference of rotation between one element and the other, there is a relative movement between the confronting and adjacent surfaces of said elements, generating friction and heat between said surfaces and, consequently, taking energy from the system and impeding the undesirable deformations of the resonant spring 50.

In case the deformation control device 60 is in the form of a tubular coating 61, this additional element will absorb energy from the resonant spring 50, by deformation of its own structure.

According to another constructive form of the present invention, illustrated in figure 7, the deformation control device 60 is defined by a semi-tubular coating 63

which surrounds part of the circumferential contour of said surface extension of the resonant spring 50, maintaining direct contact with the latter. The semi-tubular coating 63 is defined, in a single piece, by a plurality of semi-annular segments 63a spaced apart and connected to one another.

In the construction illustrated in figure 7, the semi-annular segments 63a are disposed parallel and spaced from one another and also sequentially and alternately interconnected, at the ends thereof, through small longitudinal segments 63b. It should be understood that the semi-annular segments 63a can be interconnected by median longitudinal segments. Although not illustrated in the appended drawings, it should be understood that the semi-annular segments 63a may be not parallel to each other. Said semi-annular segments 63a may be interconnected by means of alternate end longitudinal segments, or by median longitudinal segments, or also directly by the ends thereof, alternately.

As it can be noted through figures 7A and 7B, the circumferential extension of the semi-annular segments 63a are somewhat superior to the circumferential contour of the wire of the resonant spring 50, so as to allow the semi-tubular coating 63 to be easily mounted on the wire of the resonant spring 50 and, at the same time, to guarantee a reliable retention of the semi-tubular coating 63 on the resonant spring 50.

For any of the solutions above, the semi-tubular coating 63 is preferably formed in plastic material or thermoplastic material, provided directly on the surface extension of the resonant spring 50, and said plastic material can be of the thermoretractable type.

As noted, the semi-tubular coating 63 can be easily mounted to the resonant spring 50, by elastic deformation, with no need of mounting it along the wire of the resonant spring 50, from an open end of the latter. In the case of the semi-tubular coating 63, the

mounting can be made on the surface of the spring by elastic deformation of the semi-annular segments 63a.

It should be also pointed out that the semi-tubular coating 63 can be made of wire or strip in a metallic,
5 plastic or thermoplastic material.

It should be understood that the different constructive variants of the invention described herein can be presented in particular constructions, or also partially or totally combined to one another.

10 While only some constructive variants for the present device have been illustrated herein, it should be understood that modifications of form and arrangement of the component elements of the proposed technical solution can be introduced, without departing from the inventive
15 concept defined in the claims that accompany the present disclosure.

CLAIMS

1- A deformation control device for a resonant spring in a linear driving unit, of the type which comprises:

- a linear electric motor (M) formed by a motor housing (C), which is electrically excited and affixed to a fixed structure (1), and by a magnetic armature (A) displaced by the electric excitation of the motor housing, in a reciprocating axial movement;
- a helical resonant spring (50), having um end coupled to the fixed structure (1) and an opposite end coupled to the magnetic armature (A), in order to be displaced by the latter and elastically deformed, in a reciprocating axial movement, characterized in that said deformation control device (60) is mounted to the resonant spring (50), in order to maintain contact with a surface extension of the resonant spring (50), which is elastically and radially deformed upon the reciprocating axial movement of said resonant spring (50), and to generate at least one of the conditions: of friction with said surface extension of the resonant spring (50); and of elastic deformation of said deformation control device (60), absorbing energy in a value sufficient to at least minimize said radial elastic deformation of the resonant spring (50).

2- The device, according to claim 1, characterized in that it is provided around and along a wire extension of the resonant spring (50).

3- The device, according to claim 2, characterized in that it is defined by a tubular coating (61) which surrounds, integrally and circumferentially, said wire extension of the resonant spring (50), maintaining direct contact with the latter.

4- The device, according to claim 3, characterized in that the tubular coating (61) is formed by a rubber which is vulcanized directly on said wire extension of the resonant spring (50).

5- The device, according to claim 3, characterized in

that the tubular coating (61) is formed in plastic material provided directly on said wire extension of the resonant spring (50).

6- The device, according to claim 5, characterized in that the tubular coating (61) is formed in a thermoretractable plastic material.

7- The device, according to claim 2, characterized in that it is provided in helical development along said wire extension of the resonant spring (50), maintaining direct contact with the latter.

8- The device, according to claim 7, characterized in that it is defined by a damping spring (62) in the form of a helical spring made of a cylindrical rod (62b) and which is helically mounted, directly and tightly, around said wire extension of the resonant spring (50).

9- The device, according to claim 7, characterized in that it is defined by a damping spring (62) in the form of a strip (62a) helically mounted around said wire extension of the resonant spring (50).

10- The device, according to any one of claims 8 or 9, characterized in that it further comprises a tubular coating (61) which surrounds, integrally and circumferentially, the damping spring (62) mounted around said wire extension of the resonant spring (50).

11- The device, according to claim 10, characterized in that the tubular coating (61) is formed by a rubber which is vulcanized around the damping spring (62).

12- The device, according to claim 10, characterized in that the tubular coating (61) is formed in plastic material provided around the damping spring (62).

13- The device, according to claim 12, characterized in that the tubular coating (61) is formed in a thermoretractable plastic material.

14- The device, according to claim 1, characterized in that it is defined by a semi-tubular coating (63) which surrounds part of the circumferential contour of said surface extension of the resonant spring (50),

maintaining direct contact with the latter, said semi-tubular coating (63) being defined, in a single piece, by a plurality of semi-annular segments (63a) which are spaced apart and connected to one another.

5 15- The device, according to claim 14, characterized in that the semi-annular segments (63a) are sequentially and alternately interconnected by their ends.

16- The device, according to claim 15, characterized in that the semi-annular segments (63a) are parallel to each
10 other and interconnected by small longitudinal segments (63b).

17- The device, according to any one of claims 14, 15 or 16, characterized in that the semi-tubular coating (63) is formed by one of the materials defined by metallic
15 strip, metallic wire, plastic material, thermoplastic material and thermoretractable plastic material, provided directly on said surface extension of the resonant spring (50).