

Description

(9)

This invention relates to the upgrading of heavy crude oils, and more particularly to a process for rendering such crudes suitable as feed for conventional refinery processes such as fluid catalytic cracking, hydrotreating and coking.

Oxidation/deasphalting and mild coking/in-situ deasphalting are refinery processes that are individually known to be suitable for demetalizing heavy crude oils. U.S. Patent 4,379,747 for example, describes demetalation/deasphalting in coal liquefaction processes, and U.S. Patents 4,358,361 and 4,089,771 describe processes in which residual oil fractions are coked following conventional demetalation.

The present invention is based on the observation that the combination of oxidation/mild coking/in-situ deasphalting offers several advantages. For example, it is a continuous process that gives higher levels of demetalation than mild coking/in-situ deasphalting while producing less rejected material than oxidation/deasphalting. This is of particular significance since heavy crudes will be a more abundant source of fuel in the future because light crude supplies are decreasing. Therefore, demetalation and upgrading of heavy crudes prior to downstream processing will become more and more a necessity if such materials are to be used in conventional refinery systems.

The present invention therefore provides a process for upgrading heavy crude oil which comprises oxidizing the crude oil in a first stage to produce an oxidized oil containing from 0.5 to 3.0 weight % combined oxygen, subjecting the oxidized oil to mild coking at a temperature of 400 to 480°C, under a pressure of 1800 to 3550 kPa and at a liquid hourly space velocity of 3 to 5, allowing the coked product to settle for a period of time of 0.1 to 3 hours, and recovering a product of reduced metal content.

According to the invention, the removal of metals from heavy crude oils is significantly improved by means of a process comprising oxidation/mild coking/in-situ deasphalting resulting in upgraded crude with high levels of demetalation and low solids rejection.

Heavy crude oils which generally have metals contents of 70 ppm or more are especially suitable as feeds for the process of the invention.

The first stage of the process may be carried out in any suitable oxidizer reactor capable of operating within the conventional parameters, preferably at a temperature of 200 to about 270°C; an air pressure of 750 to 2200 kPa; an air flow rate of 170 to 720 NI/I; and a LHSV of 1 to 5. The oxidizer is usually packed with sand (for good mixing) or an oxidation catalyst such as V_2O_5 . Other suitable catalysts include the oxides and sulfides of cobalt, nickel, iron and molybdenum, and alumina and mixtures thereof.

After oxidation the heavy crude oil contains from 0.5 to 3 weight percent combined oxygen and is then ready for the second stage of the process, the mild coking step.

The coking unit operates at a temperature of 400 to 480°C and preferably 450 to 465°C, a pressure of 1800 to 3550 kPa and preferably about 2850 kPa, and LHSV of 3 to 5, preferably about 4. After the oxidized crude has undergone the mild coking, it passes into the settler where the residence time ranges from 0.1 to 3 hours. The light hydrocarbons present in the crude plus any cracking-generated hydrocarbons provide the in-situ deasphalting in the settler. Approximately 9% of mildly coked product becomes the settler lower phase and is removed as pitch which contains most of the nickel and vanadium impurities.

The upper phase in the settler is demetalized by up to about 90% when the oxidized heavy crude is processed in accordance with the invention, while untreated heavy crude is demetalized only by about 75%.

The following Example illustrates the invention.

EXAMPLE

An Arab Heavy Crude having the following elemental analysis:

C	83.3 %
H	11.8 %
N	0.16 %
O	0.1 %
S	2.89 %
Ni	18.6 ppm
V	57.1

was subjected first to oxidation in a trickle bed reactor over a V_2O_5/Al_2O_3 catalyst at 240°C and LHSV 2 in admixture with flowing air under a pressure of 1480 kPa. The process produced a gas make of 1 %, the material balance was 98 % and then oxidized oil product contained 1.77 % oxygen.

The oxidized oil was then subjected to mild coking and deasphalting under the conditions set out below. For comparison, a sample of the same Arab Heavy Crude that had not been treated to oxidation, was subjected to the same mild coking/deasphalting procedure.

(10)

Mild Coking/Deasphalting

	<u>Arab Heavy Crude</u>	<u>Oxidized Arab Heavy Crude</u>
5 Temperature, °C	465	465
Pressure, kPa	2860	2860
Feed rate, LHSV	4	4
Settler residence time, minutes	30	30
10 products were obtained in the following yields and had the following properties:		

	<u>Arab Heavy Crude</u>	<u>Oxidized Arab Heavy Crude</u>	
15 Upper phase, weight %	87.3	89.8	
Lower phase, weight %	8.7	9.0	
Gas, weight %	4.0	1.2	
Ni content, ppm	4.6	2.5	(before coking)
20 V content, ppm	13.0	6.0	(18.6)
Toluene insolubles, %	-	0.1	(57.1)
Demetalation, %	76.8	88.8	(0.1)

25 As can be seen from the data given above, considerably greater demetalation occurs in the process of the invention compared to a process in which the crude feed is not subjected to initial oxidation treatment.

Claims

30 1. A process for upgrading heavy crude oil which comprises oxidizing the crude oil in a first stage to produce an oxidized oil containing from 0.5 to 3.0 weight % combined oxygen, subjecting the oxidized oil to mild coking at a temperature of 400 to 480°C, under a pressure of 1800 to 3550 kPa and at a liquid hourly space velocity of 3 to 5, allowing the coked product to settle for a period of time of 0.1 to 3 hours, and recovering a product of reduced metal content.

35 2. A process according to claim 1, wherein the crude oil is oxidized at a temperature of 200 to 270°C, under an air pressure of 750 to 2200 kPa, at an air flow rate of 170 to 720 NI/l and a liquid hourly space velocity of 1 to 5.

Patentansprüche

40 1. Verfahren zur Qualitätsverbesserung von schwerem Rohöl, welches das Oxidieren des Rohöles in einer ersten Stufe, um ein oxidiertes Öl zu erzeugen, das von 0,5 bis 3 Gew.-% kombinierten Sauerstoff enthält, das Unterziehen des oxidierten Öls einem milden Kochen bei einer Temperatur von 400 bis 480°C bei einem Druck von 1800 bis 3550 kPa und bei einer stündlichen Flüssigkeits-Raum-Geschwindigkeit von 3 bis 5, das Absetzen des gekochten Produktes während eines Zeitraumes von 0,1 bis 3 Stunden und die Rückgewinnung eines Produktes mit reduziertem Metallgehalt umfaßt.

45 2. Verfahren nach Anspruch 1, worin das Rohöl bei einer Temperatur von 200 bis 270°C, bei einem Luftdruck von 750 bis 2200 kPa, einer Luftströmungsmenge von 170 bis 720 NI/l und einer stündlichen Flüssigkeits-Raum-Geschwindigkeit von 1 bis 5 oxidiert wird.

Revendications

50 1.- Un procédé d'amélioration de la qualité d'une huile brute lourde qui consiste à oxyder l'huile brute dans une première étape pour produire une huile oxydée contenant de 0,5 à 3,0% en poids d'oxygène combiné, à soumettre l'huile oxydée à un cokage modéré à une température de 400 à 480°C, sous une pression de 1 800 à 3 550 kPa et à une vitesse spatiale horaire liquide de 3 à 5, à laisser le produit ayant été soumis au cokage décanter pendant une période de temps de 0,1 à 3 heures et à récupérer un produit à teneur en métal réduite.

55 2.- Un procédé selon la revendication 1, dans lequel l'huile brute est oxydée à une température de 200 à 270°C, sous une pression d'air de 750 à 2 200 kPa, avec un débit d'air de 170 à 720 NI/l et à une vitesse spatiale horaire liquide de 1 à 5.

(10)

Mild Coking/Deasphalting

	<u>Arab Heavy Crude</u>	<u>Oxidized Arab Heavy Crude</u>
5 Temperature, °C	465	465
Pressure, kPa	2860	2860
Feed rate, LHSV	4	4
Settler residence time, minutes	30	30
10 products were obtained in the following yields and had the following properties:		

	<u>Arab Heavy Crude</u>	<u>Oxidized Arab Heavy Crude</u>	
15 Upper phase, weight %	87.3	89.8	
Lower phase, weight %	8.7	9.0	
Gas, weight %	4.0	1.2	
Ni content, ppm	4.6	2.5	(before coking) (18.6)
20 V content, ppm	13.0	6.0	(57.1)
Toluene insolubles, %	-	0.1	(0.1)
Demetalation, %	76.8	88.8	

25 As can be seen from the data given above, considerably greater demetalation occurs in the process of the invention compared to a process in which the crude feed is not subjected to initial oxidation treatment.

Claims

30 1. A process for upgrading heavy crude oil which comprises oxidizing the crude oil in a first stage to produce an oxidized oil containing from 0.5 to 3.0 weight % combined oxygen, subjecting the oxidized oil to mild coking at a temperature of 400 to 480°C, under a pressure of 1800 to 3550 kPa and at a liquid hourly space velocity of 3 to 5, allowing the coked product to settle for a period of time of 0.1 to 3 hours, and recovering a product of reduced metal content.

35 2. A process according to claim 1, wherein the crude oil is oxidized at a temperature of 200 to 270°C, under an air pressure of 750 to 2200 kPa, at an air flow rate of 170 to 720 NI/l and a liquid hourly space velocity of 1 to 5.

Patentansprüche

40 1. Verfahren zur Qualitätsverbesserung von schwerem Rohöl, welches das Oxidieren des Rohöles in einer ersten Stufe, um ein oxidiertes Öl zu erzeugen, das von 0,5 bis 3 Gew.-% kombinierten Sauerstoff enthält, das Unterziehen des oxidierten Öls einem milden Kochen bei einer Temperatur von 400 bis 480°C bei einem Druck von 1800 bis 3550 kPa und bei einer stündlichen Flüssigkeits-Raum-Geschwindigkeit von 3 bis 5, das Absetzen des gekochten Produktes während eines Zeitraumes von 0,1 bis 3 Stunden und die Rückgewinnung eines Produktes mit reduziertem Metallgehalt umfaßt.

45 2. Verfahren nach Anspruch 1, worin das Rohöl bei einer Temperatur von 200 bis 270°C, bei einem Luftdruck von 750 bis 2200 kPa, einer Luftströmungsmenge von 170 bis 720 NI/l und einer stündlichen Flüssigkeits-Raum-Geschwindigkeit von 1 bis 5 oxidiert wird.

Revendications

50 1.- Un procédé d'amélioration de la qualité d'une huile brute lourde qui consiste à oxyder l'huile brute dans une première étape pour produire une huile oxydée contenant de 0,5 à 3,0% en poids d'oxygène combiné, à soumettre l'huile oxydée à un cokage modéré à une température de 400 à 480°C, sous une pression de 1 800 à 3 550 kPa et à une vitesse spatiale horaire liquide de 3 à 5, à laisser le produit ayant été soumis au cokage décanter pendant une période de temps de 0,1 à 3 heures et à récupérer un produit à teneur en métal réduite.

55 2.- Un procédé selon la revendication 1, dans lequel l'huile brute est oxydée à une température de 200 à 270°C, sous une pression d'air de 750 à 2 200 kPa, avec un débit d'air de 170 à 720 NI/l et à une vitesse spatiale horaire liquide de 1 à 5.

