

Description

The present invention relates to a lock which is operated by a magnetic key and to a key for operating such a lock. One such lock is described in EP0024242 and EP,A,0276444 and such a magnetic key is described in US,A,4077242.

Briefly, in such locks a slide member carries a plurality of tumblers in the form of small cylindrical magnets (magnet pins) which are slidably received in bores in the slide member so as to slide transversely of the direction of movement of the member. In the locked position, the pins are attracted towards a magnetic plate so that they extend part way out of the bores and through apertures in a non-magnetic lock plate which is fixed in position and located between the slide member and magnetic plate. Hence the pins lock the slide member in position relative to the non-magnetic lock plate.

To unlock the lock, a magnetic key is slid between the magnetic plate and slide member, and repels the pins so that they are pushed out of the apertures in the lock plate. The slide member is then free to slide relative to the lock plate. The key engages a flange on the slide member so that further movement of the key moves the slide to allow operation of the lock.

The code of the lock is governed by the number, position and polarity of the magnet pins relative to the lock plate. EP0024242 describes a system in which the code of the lock can be changed without dismantling the lock. A rotatable wheel mounted in the slide member carries a magnet pin allowing the pin to be moved between four positions which correspond to four respective apertures in the lock plate. To move the pin, a code changing key is inserted to repel the pins from the lock plate and then move the slide member to a position where the wheel can be rotated by a tool inserted through the outside housing of the lock.

It has been found that if the pin is not moved precisely into one of its four positions it may, when an attempt is made subsequently to operate the lock, be caught in another aperture provided in the lock plate as the slide moves relative to the plate. This can cause further rotation of the wheel but generally results in a spurious code for the lock and a special procedure is sometimes required to repel the pin from the aperture in the lock plate so that the proper code can be set. The system of EP0024242 works well in practice but is time consuming as it requires a special manual operation to change the lock code.

Many hotels now have lock systems in which the lock code is changed automatically for each guest. This is presently done only with electronic locks: by recoding them directly from a central computer at the hotel desk; or by giving the hotel

guest a key which carries a different code to that used by the previous guest. In the latter system, the lock runs independently of the central computer and contains a battery powered microprocessor which is programmed to detect the key code. If the code falls in the appropriate position in a list of codes carried in the lock memory the lock will be operated by the key. This system minimises difficulties caused by power failures but requires that a computer at the hotel desk be kept in synchronism with the code changes of all the independent locks at all times so that the hotel management knows which key to issue to a subsequent guest. Errors occur frequently in this system particularly due to electronic malfunctions, which requires re-setting of locks that get out of sequence.

The present invention aims to provide a magnetic key operated lock having a facility for automatically and mechanically changing the lock code without the need for a central computer with on line door locks, or independent locks with electronics or batteries, thus providing the benefits of the electronic systems at a low cost. The above mentioned problems have been solved by the characterizing clauses stated in the independent claims 1 and 23, whereby dependent claims 41 to 44, describe a key or a set of keys which cooperate with the lock described in the claims 1 to 40.

Other aspects of the invention are set forth in the accompanying independent claims.

Other preferred features and advantages of the invention will be apparent from the following description and the accompanying claims.

The invention will be further described by way of example only with reference to the accompanying drawings, in which:

Figure 1 is a plan view of a magnetic key operated lock and a key;

Figure 2 is a side view of the lock and key of Figure 1;

Figure 3 is a cross-section view of the lock and key of Figure 1 on enlarged scale along the line III-III of Figure 6;

Figure 4 shows a detail view of the lock with part thereof cut away to show a slide member of the lock;

Figure 5 is a cross-section along the line V-V of Figure 4;

Figure 6 is a detail view corresponding to Figure 4 but with wheels of the lock rotated from a first position (Figure 4) to a second position;

Figure 7 is a cross-section along the line VII-VII of Figure 6;

Figure 8 shows schematically the 12 different lock codes of the lock of Figures 1 to 7;

Figure 9 shows a plan of a lock plate for the lock of Figures 1 to 8;

Figure 10 to 14 are schematic illustrations of other embodiments of the invention.

Figure 15 is a plan view of a slide member of a lock forming a particularly preferred embodiment of the invention;

Figure 16 is a plan view of a lock plate of the embodiment of Figure 15;

Figure 17 is a detail of a plan view of the lock plate and slide member of Figures 15 and 16, the lock plate laying over the slide member (cf. Figure 3);

Figure 18a to 18l illustrate the operation of the lock of Figure 15 and;

Figure 19 illustrates lock codes and the corresponding key codes for the lock of Figure 15.

Referring to Figures 1 and 2 a lock in accordance with the invention comprises an elongate lock case 1 which supports a rotatable knob 2. The knob is arranged to be coupled to a spindle 3 when the lock is in the unlocking position so that rotation of the knob 2 will turn the spindle to retract a latch or bolt (not shown). When the lock is in the locked position the knob 2 is freely rotatable on the case 1 so that the lock cannot be forced. To unlock the lock a magnetic key 5 is inserted in a slot 4 in the case 1. This operation will be described in more detail hereinafter. The key 5 comprises a sheet of magnetic material sandwiched between steel plates. The sheet is magnetised with a plurality of discrete north and south poles on one face which form a code matching the code of the lock, as described for example in U.S.4077242.

Referring to Figure 3, the case 1 houses an inner case 7 which carries the lock mechanism. The inner case 7 is fixed in position in the case 1.

A slide member 6 is mounted in the inner case 7 and is slidable by the key 5 in the direction of arrow A. The slide member 6 has a plurality of blind bores 14 which are distributed across the plane of the slide member. Tumblers of the lock are formed by magnet pins 15 (small cylindrical permanent magnets) which are accommodated in some or all of the bores 14. Overlaying the open ends of the bores is a lock plate 12 which is fixed in position in the inner case 7 and has apertures 13 which, in the locked position of the slide 6, are aligned with the open ends of the bores 14. A first guide plate 9 of non-magnetic material, such as brass, overlays the fixed plate 12 and, also, is fixed in position with the plate 12. A second, thicker, guide plate 8 bears on the first guide plate 9 and is biased against the first plate by a leaf spring 10 supported on a wall 11 of the inner case 7. The second guide plate is of magnetizable material such as ferromagnetic steel.

In the locking position, seen in Figure 3, the magnet pins 15 are attracted to the second guide plate 8 so that the ends of the pins project into the

apertures 13 and about the first guide plate 9. Hence the slide 6 cannot be slid relative to the lock plate 12. To unlock the lock, a key 5 is slid between the first and second guide plates, 9, 8, the guide plate 8 moving back against the force of the spring 10. The key 5 has a plurality of magnetic poles imprinted on its operating side 5a, these poles are positioned so that when the key is fully inserted, its tip 5' abutting a toe 23 on the slide member 6, the poles are arranged opposite the magnet pins 15 and are of the same polarity as the adjacent ends of the pins 15. Hence the pins are pushed out of the apertures 13 by magnetic repulsion and sit on the bottom of the blind bores 14. The slide member 6 is thus unlocked and can be slid by pushing further on the key 5 in the direction of arrow A. A wedge shaped heel 19 on the slide member 6 has a cam surface 20 which depresses a fork 21 which in turn moves a coupling sleeve 22 in the direction of arrow X to connect the knob 2 with the spindle 3 so that the bolt or latch etc. can be opened by rotating the spindle 3. Such an arrangement is described in more detail in EP0241323.

As the key 5 is inserted it rides over two cams 41 which causes the slide member to be held in place when it reaches the unlocking position. This allows the user to release the key and turn the knob 2, and hence open the lock with one hand. When the key 5 is removed, the slide member stays in the unlocking position until the key 5 is withdrawn past the cams 41, (see for example EP0241323).

As the key 5 is fully withdrawn the slide member 6 is pulled to its locked position by a coil spring 16 attached between the heel 19 and a stop 17 on the inner casing 7 (the spring having been tensioned during the forward stroke of the slide member), the magnet pins entering the apertures 13 when the slide member returns to its locked position.

Also seen in Figure 3 is a movable magnet pin 28b which forms a particular feature of the invention. The magnet pin 28b is received in a through bore 40 in a carrier in the form of a wheel 24b which is rotatably mounted in a bore 32 in the slide member 6. Four such wheels, 24a, 24b, 24c, 24d of equal size, each carrying a respective magnet pin 28a, 28b, 28c, 28d, and a fifth wheel 25 of larger size carrying a magnet pin 26 are provided in respective bores 32 in the slide member 6. The wheels are cog like and intermesh so that rotation of one wheel causes all five wheels to move. The larger wheel 25 has $1\frac{1}{2}$ times the number of teeth of the smaller wheels 24a, 24b, 24c, 24d. The teeth of the wheels sit on ledges on the inner surface of the bores 32.

In operation of the lock, at any one time one of the magnet pins 28a, 28b, 28c, 28d forms a code-changing pin which is utilised to change the code of the lock, whilst the other pins 28a, 28b, 28c, 28d and 26 are locking pins, that is they form part of the lock code and project into respective apertures 13' in the lock plate 12 and must be repelled therefrom by the key 5 to unlock the lock.

Looking at figure 4, the magnet pin 28a is the code-changing pin. This pin 28a is utilised to rotate the wheel 24a and hence wheels 24b, 24c, and 24d by 90 degrees so that all four pins 28a, 28b, 28c, and 28d are moved through 90 degrees and pin 24 is moved through 60 degrees only due to the greater number of teeth on wheel 25. At this point (Figures 3 and 6) magnet pin 28a becomes a locking pin, magnet pin 28b is a code-changing pin and magnet pins 28c and 28d are locking pins. The disposition of the locking pins has thus been changed and so the code of the lock is changed.

The code-changing operation of the lock will now be described in more detail.

Let Figure 4 show the lock with a first code and hence openable by a first key carrying the first code. The code-changing magnet pin 28a projects into an elongate slot 35a in the lock plate 12. When the first key 5(1) is inserted it repels locking magnet pins 15 and magnet pins 28b, 28c, 28d and 26 from their respective apertures in the lock plate 12. The key 5(1) does not repel code changing pin 28a which thus still projects into the elongate slot 35a. This pin is held in the slot by its attraction towards the guide plate 9, or a magnetic spot may be provided on the key to attract the pin more positively into the slot. The pin 28a slides in the slot 35a as the slide member 6 slides and hence the first key can operate the lock, the locations of the magnet pins 28a, 28b, 28c, 28d and 26 remaining constant as the lock is operated. Engagement of the pin 28a in the elongate slot 35 serves to prevent unwanted rotation of the wheels 24a, 24b, 24c, 24d and 25.

To change the lock code to a second code a second key 5(2) is inserted. This key has encoded on it the first code, the second code and a lock changing code. The first and second codes both include parts corresponding to the pins 15, that is to repel them. The first code repels pins 28b, 28c, 28d and 26 in the Figure 4 position, and the second code repels pins 28a, 28c, 28d and 26 in the Figure 6 position. The first lock changing code is a magnetic spot which, in the Figure 4 position, repels the pin 28a.

As stated previously, pin 28a (and pins 28b, 28c and 28d) are located in bores 40 which are open at both ends. When the second key 5(2) is inserted it repels the pin 28 out the "back" of the respective bore 40 against a back wall 18 of inner

casing 7. Accordingly as the second key is inserted it repels all the locking pins to unlock the slide member 6 using the first code, and it repels the pin 28a. The slide member 6 is free to move as the key 5(2) is pushed in further. As the slide member moves (in the direction of arrow A in Figures 4 and 6) the pin 28a engages an edge 44a of a tang 43 which is pressed from the back wall 18 of the inner casing 7. Thus, further movement of the slide member 6 causes the wheel 24a to be rotated, the pin 28a being allowed to move sideways across the abutting edge 44a of the tang 43a. When the slide member 6 is at the limit of its travel, the pin 28a has been moved through 90 degrees, as have the other pins 28b, 28c, 28d to the Figure 6 position. Whilst the pin 26 in the larger wheel 25 is moved through 60 degrees only because of the ratio in the wheel diameters. Also, of course, coupling member 22 is moved to allow the latch or bolt to be retracted, and the slide member 6 is held in the unlocking position due to the action of cams 41.

As the key 5(2) is withdrawn, the pins 28a, 28b, 28c, 28d are all attracted towards the magnetic plate 8. As the slide moves back to its locked position the second code changing pin 28b engages in a respective elongate aperture 35b in the fixed plate 12, the first code changing pin 28a is attracted into a respective locking aperture 13' and the pins 28c, 28d, 26 engage in respective (new) locking apertures 13', as seen in Figures 3 and 6.

At this time the lock can be opened again by a key bearing the second code, and, in particular, by the key 5(2) which carries the second code. Key 5(2) does not repel pin 28b in the Figure 6 position and key 5(1) will not open the lock because its code does not correspond to the position of pins 28c, 28d, and 26.

Preferably key 5(2) has a magnetic spot to attract pin 28b to ensure that it locates securely in the elongate aperture 35b during movement of the slide 6.

To change the lock code from the second code to a third code, a third key 5(3) is used. Key 5(3) has the second lock code (to release the slide member 6), a lock changing code (to repel pin 28b) and the third lock code to allow it to open the lock after the code has been changed. As key 5(3) is inserted it releases the slide member 6, and repels pin 28b to engage the respective edge 44b of a tang 43b to cause wheel 24b (and wheels 24a, 24c, 24d and 25) to rotate as the slide member 6 is moved. The wheels thus adopt a new position where pins 28a, 28b, 28d and 26 form part of the third lock code and pin 28c is the new code changing pin. Thus keys 5(1) and 5(2) are eliminated.

A fourth key 5(4) changes the code from the third code to a fourth code by means of code

changing pin 28c and a fifth key 5(5) changes the code from the fourth code to a fifth code by means of the code changing pin 28d. This eliminates keys 5(3) and 5(4). At this time it can be seen that the wheels 24a, b, c and d have turned a full circle, but that wheel 26 has turned only 240 degrees. Thus pin 28a once again is a code changing pin, but key 5(1) will not unlock the lock again because the locking pin in wheel 26 is in another position.

Accordingly a further 8 code changes can be made before all the magnet pins 28a, 28b, 28c, 28d and 26 are returned to their original (Figure 4) position, i.e. three revolutions of the wheels 28 and two revolutions of the wheel 25. Figure 8 shows the full twelve positions of the magnet pins. Hence the codes can be cycled through continuously but only in the prescribed sequence.

By forming the abutments or edges 44 from tangs 43, the tangs provide a ramp in the return direction of the slide member 6. Hence if a pin retracts from its elongate aperture during the return of the slide member and protrudes out the rear of the bore 40 it will simply ride up over the ramp, which will bring it back towards the attracting plate 8.

The wheel 24a is arranged to rotate in the opposite direction to the other wheels 24b, 24c, 24d, and in particular to wheel 24b, so that slot 35a which is associated with the abutment 43a can be placed to one side where it will not overlap the path of a magnet pin in the wheel 24b, since otherwise the wheels might inadvertently lock in an incorrect position due to a pin entering an incorrect elongate aperture. Similar considerations apply to the location of the locking apertures 13, 13'.

It will be appreciated that the abutments 44 are positioned to one side of the respective wheel axis, relative to the direction of movement of the slide, to ensure rotation of the wheel as the respective pin engages the abutment.

An abutment may be formed on a slant to provide a slight sideways impetus if the abutment is close to the line of movement of the wheel axis.

If desired, other users can be issued with keys corresponding only to the codes 1 to 12 which do not repel the respective code changing pins.

Management can have special keys which only change the code but need not subsequently open the lock and so need comprise only say, the first code and the code-changing code. Another use of this feature is in facilities requiring a key which is usable once only. The user may be issued a key, having the initial unlocking code and the code changing code, but not having the subsequent unlocking code. Hence, for example, when a key with code 1 is inserted it opens the lock and simultaneously changes the code to code 2, which cannot subsequently be unlocked by that key.

Various modifications may be made to the described embodiment. For example, the number of wheels may be changed and a wheel may carry more than one magnet pin. The ratio between the wheel sizes may be varied to obtain a different number of codes in a complete cycle of codes. Care must be taken however, because some arrangements may result in a key which can unlock more than one code in a complete cycle.

To increase the number of stationary locking pins, such a pin may be provided on the axis of rotation of a wheel, for example, the wheel 26 in the embodiment shown.

Figure 9 shows a plan of a lock plate for the embodiment of Figures 1 to 8.

In addition to the automatic code changing facility, the slide member 6 may include a manually rotatable wheel carrying a magnet pin, as described in EP0024242. If a maids key is lost, then a common code of the locks operated by that key can be changed by manually rotating the wheel.

It is possible to provide a variety of keys suitable for hotel use with the system of Figures 1 to 8. In particular a master or maids key, which will open the lock in any code but not change the code, and a recycle key to reset the lock to a particular code.

A maids key will have a code which will repel all the pins 15 and the pins 28, 26 at any of their locking positions but will attract the pins 28a, 28b, 28c, 28d at their code changing positions and so not cause any code change.

A recycle key will have a code which will attract pin 26 at one position and repel it at all others, and repel the pins 28a, 28b, 28c, 28d at their locking positions and their code changing positions. Repeated insertion of the key will cycle the lock through the codes until the key attracts the pin 26 when it will stop the cycle. Management will then know that the lock has been reset to one of two codes.

It is possible to arrange for a single wheel to provide a code changing function more than once per rotation. Such a wheel may comprise only code changing pins and be used to drive a wheel or wheels which carry locking pins.

By using wheels of different sizes, the number of rotations of the code changing wheel before a code is repeated can be made very large. The main limitation on such systems is the need to provide an adequate number of stationary pins to allow basic codes specific to users, that is buildings, and to floors of buildings, e.g. in hotels, without unduly increasing the lock size and the key size. Also it is necessary to ensure that as the slide moves, the path of a pin crosses only one locking aperture in the lock plate, i.e. the aperture specific

to that pin. If the path of a pin crosses another, incorrect, aperture the pin may be attracted into that aperture when the key is removed, which may result in the slide being held in the unlocked position.

Particularly favourable combinations can be achieved by providing pins of opposing polarity in the wheels, although this can prevent master keying of the system with a single master key.

Further embodiments illustrating the above variations will now be described schematically. It will be appreciated that in all cases the basic code changing operation, by repelling (or attracting) a code changing pin, is the same and that other, stationary, locking pins are present.

Figure 10a shows a system using two wheels 51, 52 of equal size for producing a lock with four different codes. One of the wheels 51, is used to drive the other wheel 52. Wheel 51 carries 4 magnets 53 whose polarity alternates north and south around the wheel. Wheel 52 carries two magnets 54 of opposite polarity. A code changing edge 55 is located behind wheel 51 adjacent one of the bores in the wheel 51 and an elongate slot 57 is positioned in the lock plate (not shown) in front of the wheels 51, 52. The magnets 53 are used only for code changing, whilst the magnets 54 are used only for locking. Four apertures are provided in the lock plate above the stationary positions of the magnets 54 in the wheel 52.

To effect a code change, a key is inserted which releases the slide member, i.e. repels the magnets 15, 54. Movement of the slide in the direction of arrow A will cause the magnet 53a to engage the edge 55 and so rotate the wheel 51 anti-clockwise through 90 degrees as the wheels are moved with the slide. This brings magnet 53b to a position where it will engage in the elongate aperture 57 when the slide member returns and wheel 52 is also rotated through 90 degrees, to give a second locking code, Figure 10b. The key can include the second locking code, i.e. spots corresponding to the new position of the magnets in wheel 52 and so will unlock the lock. However, the code changing code which repelled magnet 53a will now attract magnet 53b, which is of opposite polarity, into the elongate aperture 57 and so the lock code will not change again.

To change the code to the third code a key having the second lock code, i.e. repelling, inter alia, the pins 54 in the Figure 10b position, and a code changing code, i.e. repelling the pin 53b is inserted in the lock. The key will also have a code to repel the pins 54 in the Figure 10c position, which shows the third code.

Figure 10d shows the fourth lock code.

This embodiment illustrates a modification to the elongate slot. The slot is curved at its bottom

end, in the direction of travel of the slide member, so that a magnet pin will come into the area of the slot even if the pin does not move fully through 90 degrees. This may occur, for example, if the slide member is not pushed down fully when opening the lock. If the pin enters the slot at the elbow 58 it will be guided round to its upper position as the slide is moved back. Preferably the magnet is a relatively tight fit in the upper end of the slot to ensure proper alignment of all the locking magnet pins with the lock plate apertures. By using the slot to complete the rotation of wheels in this way a greater degree of rotation can be obtained for a small travel of the slide member.

Figure 11 shows an embodiment in which two code changing positions are provided for a wheel. A wheel 60 carries three magnets 61 spaced at 120 degrees and is stepped through six positions. The magnets are of different polarities (e.g. 1 north and 2 south) and engage in locking apertures in the lock plate when not at a code changing position. Code changing edges 62 are provided behind the wheel 60 at two adjacent stopping positions for the magnets, both positions being to the same side of a line through the centre of the wheel 60 in the direction of movement. Referring to Figure 11a, magnet 61a is at the code changing position and located in the top of the slot 63a in the lock plate. When the code is to be changed to the Figure 11b position, a code changing key repels the magnet 61a and magnets 61b and 61c. Magnet 61a engages the rear edge 62a as the slide is moved in the direction of arrow A. This rotates the wheel through 60 degrees (the amount of rotation is limited by the extent of movement of the slide) so that the magnet 61a will enter the aperture 62b when the slide returns to the locked position. The same code changing key repels magnets 61b, 61c in their new positions but attracts magnet 61a in the Figure 11b position so that it will open the lock in the new code but will not change the lock code when used again.

The next code changing key (2) must repel the magnet 61a in the Figure 11b position, and also repel the magnets 61b and 61c in this position. The code is then changed to the Figure 11c position where the magnet 61b becomes a code change magnet using edge 62a. The key (2) will then repel magnets 61a and 61c in the Figure 11c position and attract magnet 61b to operate the lock but not change the code again.

The six codes can be cycled through as shown in Figures 11a to 11f, and the next change will return to the starting code 11a.

To provide a more complex coding the wheel 60 may drive a second wheel 70 which comprises only a locking magnet or magnets, as seen in Figure 12. This wheel 70 is preferably of different

size, having say $\frac{2}{3}$ the number of teeth so that it steps through 90 degrees. Thus three rotations of the wheel 70 may be required for a complete cycle through 12 different lock codes. At least two magnets are preferred over 1 to prevent wheel 70 rotating in the event that the slide member is moved by a key which does not repel the (single) magnet in wheel 70 but does repel the pins in wheel 60.

A drawback of the system of Figures 11 and 12 is that a single full cycle master key cannot be provided because all locking positions at one time or another during the full cycle contain both north and south polarities and a single location on a key can only be one polarity.

Figure 13 shows another 12 code lock, utilising 3 wheels 81, 82, 83. Wheels 81 and 83 each carry two pins 84, 85 and have one code changing position as illustrated by the elongate apertures 86, 87 and abutments 89. The third wheel 82 has 1-1/2 times as many teeth as wheels 81, 83 and so moves through 60 degrees for each 90 degree rotation of the wheels 81, 82. The wheel 82 preferably carries 1 pin, two diametrically opposed pins of opposite polarity, or three pins spaced by 120 degrees with one pin of different polarity to the other pins. The number of pins and their polarities determining the number of code changes. The code changing positions 89 on the wheels 81, 83 are brought into operation alternately. If for example, at least one of the small wheels 81, 82 carries magnets of opposite polarity and wheel 82 carries a single pin or two diametrically opposed pins of opposite polarity, the small wheel must complete 3 revolutions, i.e. 12 code changes, to return to the position shown in Figure 13.

Figure 14 shows another embodiment of the invention which comprises a single wheel 90 having six positions through which it rotates. The wheel carries three magnets 91a, 91b, 91c. The wheel has two associated abutments 96, 97 for rotating the wheel 90 by means of a magnet pin located at either of two positions No. 4 and 5. A particular feature of this embodiment is that one of the abutments is provided on the lock plate, and the other is provided on the back wall 18 of the inner carrier 7.

Referring to Figure 14a, positions 1, 2 and 3 are used as locking positions, that is a magnetic pin in any one of these positions is a locking magnet pin. A magnet pin in one of the positions 4 and 5 is used to rotate the wheel, and hence change the lock code, specifically the location of a pin in the 1, 2, 3 positions.

A first L-shaped aperture 94 is cut into the lock plate, which is in front of the wheel as viewed in the drawing and a second reversed L-shaped recess 95 is formed in the wall 18.

To change the lock code from the Figure 1 position, a magnet pin 91a is attracted by an area of a code changing key (1) so that it projects into the lower arm 94a of the aperture 94 in the lock plate. The other magnet pins 91b, 91c (and 15) are repelled to release the slide member 6. Movement of the slide member in the direction of arrow A causes the pin 91a to abut the abutment 96 (the bottom edge of the arm 94a) and so the wheel is caused to rotate, the pin 91a moving along the arm until it is at the lower end of the vertical arm 94b. As the slide member 6 is released and returns the pin 91a slides up in the slot 94b (Figure 14b). The wheel has thus rotated 60 degrees, bringing pin 91c into position No. 4. Pin 91b thus forms the only locking pin for the wheel.

To change the code again a key (2) is inserted to repel pins 91b and 15 to release the slide member, to repel pin 91a to allow rotation of the wheel 90, and to repel pin 91c into the lower arm 95b of the slot 95. This time, the pin 91c will abut abutment 97 formed by the bottom edge of the rear slot 95b and so cause the wheel 90 to turn as the slide moves. Pin 91c moves into the No. 5 position and pins 91a and 91b form locking pins, as shown at Figure 14c.

To continue to open the lock, but not change the code, the key (2) must repel the pin 91c so that it slides in the rear slot 95a during movement of the slide member, and also repel pins 91a, 91b at their new positions.

The polarities of the magnetic spots of keys which will change the lock code, and continue to open the lock but not change its code, are shown to the right hand side of Figure 14.

Rotation of the wheel 90 thus provides 6 different lock codes. There is some cross-keying in that key (4) will open the lock in code 14f.

To provide a very large number of lock codes, a plurality of wheels 90 could be provided, the wheels being rotated independently of one another, to give 6x6 codes (2 wheels), 6x6x6 (3 wheels) or even more. Use of this system can eliminate cross-keying by having the key change a second wheel at that code.

A single master key or recycle key is not possible with this system.

In the particularly preferred embodiment of Figures 15 to 18 the abutments, for engagement by the code changing pins, are all formed in the lock plate. This can be particularly advantageous where the rear of the slide member serves another purpose, such as in U.S. 4133194 and it would be less convenient to have pins at a number of positions moving out the rear of the slide member.

The basic structure of the lock is as described for the embodiment of Figure 1.

Figure 15 shows a non-magnetic plastics slide member 100 which has a plurality of fixed-position blind bores 102 for receiving magnet pins 123a. A manually rotatable wheel 103 is provided in the slide member 102 and has a blind bore 102" carrying a magnet pin 123"a. Wheel 103 operates in the manner described in EP 24242.

Two toothed non-magnetic plastics wheels 104, 106 are housed in blind recesses in the slide member 100. The wheels 104, 106 are each provided with two diametrically opposed blind bores 108, 110, 112, 114, and are meshed so that one pair of bores is ninety degrees out of phase with the other. Hence the bores 108, 110 in wheel 104 are aligned with the apices of teeth 116, whilst bores 110, 114 in wheel 106 are aligned with the troughs between the teeth 116. Each wheel 104, 106 has a through bore 109, 111 which receives a stub axle 113, 115 which is integral with the body of the slide member 100, the wheels 104, 106 rotating about the axes 113, 115.

Figure 16 shows a lock plate 118, and Figure 17 shows a detail of the lock plate with the slide member 100 below it. With the slide member 100 in the locked position, code-changing magnet pins 108a, 110a, 112a, 114a carried by the wheels 104, 106 are attracted to the steel shield plate 8 (Figure 3) and so project through the slots 120, 122 and 126. Other, fixed-position, magnet pins 123a project through respective apertures 123.

The lock plate 118 has symmetrically arranged slots 120, 122 which function as the abutments for engagement by code-changing pins. For convenience the bottom end (as pictured in the drawing) of each slot is formed as a locking aperture 123' for receiving a locking pin 123'a in a corresponding bore 102' in the slide member 100. A horizontal elongate aperture 126 serves as a locking aperture for an appropriately positioned magnet pin carried by the wheels 104, 106.

Figures 17 and 18a show the position with the slide member 100 in the locked position and wheels 104, 106 in the position of Figure 15. Each bore 108, 110, 112, 114 carries a respective magnet pin 108a, 110a, 112a, 114a. In this position, the pin 110a projects into the aperture 126 in the lock plate, locking the slide member 100 relative to the lock plate 118. The pin 108a is also attracted into an ear 128 in the slot 120. The pin 108a abuts against a bottom edge 130 of the ear 128 in the event that the slide member 100 is urged downwards (Figure 18b). This serves to balance the forces on the wheel 104, preventing it from tending to rotate whilst the pin 110a is in the slot 126.

The pins in bores 110, 112 of wheel 106 serve no locking function in the position shown, but are attracted into the slot 122, and so serve to prevent rotation of the two meshed wheels 104, 106.

To change the code of the lock, a code change key (1) which repels the pins 110a, 112a and 114 and attracts the pin 108a is inserted in the lock. Once pins 110a, 112a, 114a are repelled the wheels 104, 106 are free to rotate. As with previous examples, the key (1) must also repel all the stationary locking magnet pins, including pin 123"a in wheel 103. As the slide member 100 is moved downwards by the key, arrow A, relative to the lock plate 118, the wheel 104 is caused to rotate due to pin 108a abutting abutment 130 (Figure 18b). Pin 108a slides along the abutment 130, (Figures 18b to 18d) as the wheel 104 is caused to rotate clockwise, until the pin 108a is almost in the 12 o'clock position (Figure 18e, 18f), when it rides over a lip 132 and enters a vertical channel 134, as the slide member 100 has neared the bottom of its travel. As seen in Figures 18e to 18g magnet 110a on clearing knee 134a of the slot 134 is attracted by a magnetic spot on the key 1 (see Figure 19) and as the slide member continues to move downward the pin slides along the edge 134b of the slot 134 to aid in guiding the wheel to full 90 degree rotation. At this position (Figure 18g), pins 108a and 110a are aligned with the vertical length 134 of the slot 130, pin 114a has been rotated around with wheel 106 (which has been rotated due to its geared connection to wheel 104) until it is aligned with but below an ear 136 of slot 122 and pin 114a is aligned with but below the locking aperture 126. The bottom edge region 134c of slot 134 is arcuate and forms a seat for pin 110a to properly position the wheels 104, 106 when the slide member reaches the end of its travel. Slot 122 has a similar arcuate edge region 140c.

As the slide member 100 is released to return to its locked position, the key (1) being withdrawn, the pins 108a, 110a are attracted into vertical portion 134 of slot 120, pin 114a will enter ear 136 and pin 112a enters locking aperture 126 (Figures 18h and 18j), due to the attraction of the steel shield plate 8 (see Figure 1).

At the upper end of the travel of the slide member, (Figure 18j) pin 108a is guided into the apex of the slot 120 to ensure that the wheel 104 remains with its two pins vertically aligned, the apex pressing on the pin 108a at this point.

The slots 120 and 122 are shaped to ensure a code change even if the slide member is not pushed down the full distance. As described previously, when the slide member 100 is depressed by the key, the magnet pin that was immediately previously positioned in locking aperture 126 is rotated downwards and before the core is fully depressed the pin enters a knee portion 134a, 140a of elongate slot portion 134, 140 (Figure 18e) and is attracted to a magnetic spot on the key 1. If the slide member is not depressed further but instead

is allowed to return upwards to the locked position, the pin is urged by the cam action of the edge 134d, 140d of the slot above the knee 134a, 140a, to complete the rotation of the wheels through 90 degrees (Figures 18k, 18l, 18j).

If key 1 is to continue to unlock the lock, but not change the code again, it will have four additional magnetic spots to repel pins 114a and 112a in their new position and attract pins 108a, 110a in their new position. (If the key is not intended not to open the lock, once it has been set to the new code, then the four additional magnetic spots are arranged to attract all the pins 108a, 110a, 112a, 114a in their new positions).

When the code of the lock is to be changed a second time, the second code change key (2) will have magnetic spots to repel pins 108a, 110a and pin 112a, as well as all other locking magnet pins 123a, and 123'a. Pin 114a is attracted so as to stay in the ear 136. As the slide member 100 moves downwards relative to the locking plate 116, the pin 114a abuts edge 138 of ear 136 and so causes the wheel 106 to rotate in the anti-clockwise direction. Pin 114a slides across the edge 138 until it is in the vertical channel 140 of slot 122. At this time pin 114a is aligned with the vertical channel 140, pin 110a is aligned with but below ear 130, and pin 108a is aligned with but below locking aperture 126. As the key is withdrawn and the slide member 100 returns to its locked position, pin 108a enters aperture 126 and pin 112a enters ear 130. If the key is to continue to open the lock (but not change the code), it will have magnetic spots to repel pins 108a, 110a in their (new) positions and attract pins 112a, 114a.

If each wheel has magnet pins of the same polarity, e.g. both pins in wheel 104 have exposed north poles and both pins in wheel 106 have exposed south (or north) poles, the lock will be back at the position of Figure 18a. Thus only two codes are available and will alternate.

To have a four code cycle sequence for the lock, the pairs of pins in each wheel must be of opposite polarity.

Figure 19 shows schematically the position of the pins and the respective coding for keys with a four code system, using opposite polarity magnet pins in each wheel. Key codes are shown for keys which will change the code (once) and continue to unlock the lock, and the reset and maids keys are also shown. As shown, the poles of the magnet pins 108a, 110a, 112a, 114a are as viewed from the lock plate, and the poles on the key are the pattern on the "underside" surface of the key which faces the pins, when viewed from "above".

The slide member 100 shown has also a separate disc 103 of the type described in EP 24242 containing one locking magnet pin 123'a which is

manually movable by rotation of the disc 103 from outside the lock to any of four positions as described in EP 24242. After an automatic code sequence of four codes, manually rotating the disc 103 to another position will change the overall code of the lock and so another cycle of automatic code changes giving four more codes are possible, the lock having overall, a different set of codes to the previous sequence. In this manner a total cycle of 16 codes is possible, a manual change being made after each four automatic changes. The full cycle of 16 codes can be repeated, by rotating the disc pin to original starting position, or changing the position or polarity of any other fixed magnet 123a in the slide member can provide a further series of 16 codes.

With each sequence of four codes, two keys coded as "re-cycle keys" each changing the code once for each of two insertions can cycle the lock through the four codes: the first key will cycle from code 1 to 2, and then from 2 to 3 but it will not operate the lock again in code 3. The second key will cycle from code 3 to 4 and from code 4 to 1 but it will not operate the lock again in code 1. Thus only two recycle keys are necessary to reset the lock to any of the four codes. If these same keys master the four positions of the disc 103 they can be used to set the lock to any of the 16 possible codes, the position of pin 123'a being determined by the manual rotation of disc 103.

This embodiment can also have a single-use key in which the key has a code to open the lock once, changing the code, and will not operate the new code. In this way a system in which keys open the lock only once can be provided. Two master keys which operate codes 1 and 2 and 3 and 4, but will not change the code, can also be provided. If they master the four positions of disc 103 they become grant masters for the system. A single master key is not possible as each location is occupied variously by a north or a south pole of a pin, and of course it is not possible to have different polarity spots at the same position on a key.

A system which is particularly useful for hotels makes use of an eight cycle sequence, i.e. two cycles of four automatically changed codes Nos.1-4 and Nos.5-8 by using two positions of the wheel 103, say the first position for codes Nos.1-4 and the third position for Nos.5-8. The second and fourth positions of wheel 103 would be used in the event that maid master keys, which open the lock in all eight codes of the sequence are lost: the wheel 103 being rotated to the second position to lock out the lost maids keys but allowing continuing use of guest codes Nos.1-4, and rotated to the fourth position to allow continued use of guest codes Nos.5-8. The guest keys Nos.1-4 are coded to repel the pin 123'a in wheel 103 when it is in

the first and second positions, and keys Nos.5-8 are coded to repel the pin when in the third and fourth positions. Hence it is not necessary to issue new guest keys when the maids keys are replaced, two sets of maids keys being possible with this system. When both sets of maids keys are lost, the system can be recoded by changing the position or polarity of one of the fixed position magnet pins.

It will be appreciated that a lock may incorporate two (or more) independently operable automatic code changing mechanisms. Thus if each system provided a cycle of 4 codes, a total of 16 automatically changeable codes could be achieved. The lock may incorporate two (or more) different embodiments of code changing mechanisms or two similar embodiments. A lock using the embodiments of Figures 4 and 13, for example, could have 120 different codes which can be cycled through automatically. The code changing keys would, preferably, operate only one of the code changing mechanisms at a time.

It will be appreciated that the code-changing mechanism need not be positioned in the upper part of the slide member, but may be positioned near the toe 23.

Claims

1. A magnetic key operated lock, comprising a generally planar slide member (6) movable from a locked position to an unlocking position with a magnetically coded key (5), a plurality of magnet pins (15) slidable transversely of the slide member (6) from a first position locking the slide member in said locked position to a second position unlocking said slide member on operation of the lock by a said magnetically coded key (5), the position and polarity of some or all of the magnet pins forming a locking code for the lock, at least one additional magnet pin (28a, 53a, 61a, 91a, 108a) in said lock being a code-changing pin (28a, 53a, 61a, 91a, 108a) movable by the action of a code changing key (5) from a first location to a second location in the principal plane of the slide member (6) to change the code from a first code to a second code, by engaging said code changing pin against an abutment during movement of the slide member (6) between the locked and unlocking positions, characterised by said code changing pin (28a, 53a, 61a, 91a, 108a) remaining relocated when the slide member (6) returns to its said locked position.

2. A lock according to claim 1, characterised in that said abutment is formed by an edge (44a) of a ramp (43a) on a stationary plate (18) in the

lock.

3. A lock according to claim 1, characterised in that said abutment is formed by an edge (130) of a slot (120) in a lock plate (118).

4. A lock as claimed in any one of claims 1 to 3 characterised by having at least two carriers (24a, 24b, 104, 106) said carriers being in the form of wheels mounted in the slide member (6) and coupled together directly or through an intermediate wheel (25), one carrier carrying a magnetic pin (28a, 108a) such that when the pin engages the abutment the carrier (24a, 104) is caused to rotate during movement of the slide member (6) between the locked and unlocking positions.

5. A lock as claimed in claim 4, characterised in that said at least two carriers (24a, 25) are of different diameters.

6. A lock as claimed in claim 5, characterised in that at least two of said carriers (24a, 25) are caused automatically to rotate through different predetermined angles on insertion of said code changing key (5), whereby a said carrier is rotated through more than one complete rotation before a code of the lock is repeated.

7. A lock as claimed in claim 4, characterised by means for rotating one of said carriers (24a, 104) on insertion of a said code changing key (5), said carrier in turn rotating the other carrier or carriers.

8. A lock as claimed in claim 4, characterised in that one of said carriers (24a, 104) carries a magnet pin (28a, 108a) which is acted on by the action of said code changing key (5) to move said carrier.

9. A lock as claimed in claim 8, characterised in that another one of said carriers (25, 52, 70, 82) carries only magnet pins which form part of the locking code for the lock and are not acted on by the code changing code of said code changing key (5) to cause movement of a said carrier.

10. A lock as claimed in claim 4, characterised in that a said carriers (51, 60, 81, 90, 104) carries more than one magnet pin.

11. A lock as claimed in claim 10, characterised in that two of said pins in a said carrier carrying more than one pin are of different polarity with respect to a said magnetically coded key (5).



the first and second positions, and keys Nos.5-8 are coded to repel the pin when in the third and fourth positions. Hence it is not necessary to issue new guest keys when the maids keys are replaced, two sets of maids keys being possible with this system. When both sets of maids keys are lost, the system can be recoded by changing the position or polarity of one of the fixed position magnet pins.

It will be appreciated that a lock may incorporate two (or more) independently operable automatic code changing mechanisms. Thus if each system provided a cycle of 4 codes, a total of 16 automatically changeable codes could be achieved. The lock may incorporate two (or more) different embodiments of code changing mechanisms or two similar embodiments. A lock using the embodiments of Figures 4 and 13, for example, could have 120 different codes which can be cycled through automatically. The code changing keys would, preferably, operate only one of the code changing mechanisms at a time.

It will be appreciated that the code-changing mechanism need not be positioned in the upper part of the slide member, but may be positioned near the toe 23.

Claims

1. A magnetic key operated lock, comprising a generally planar slide member (6) movable from a locked position to an unlocking position with a magnetically coded key (5), a plurality of magnet pins (15) slidable transversely of the slide member (6) from a first position locking the slide member in said locked position to a second position unlocking said slide member on operation of the lock by a said magnetically coded key (5), the position and polarity of some or all of the magnet pins forming a locking code for the lock, at least one additional magnet pin (28a, 53a, 61a, 91a, 108a) in said lock being a code-changing pin (28a, 53a, 61a, 91a, 108a) movable by the action of a code changing key (5) from a first location to a second location in the principal plane of the slide member (6) to change the code from a first code to a second code, by engaging said code changing pin against an abutment during movement of the slide member (6) between the locked and unlocking positions, characterised by said code changing pin (28a, 53a, 61a, 91a, 108a) remaining relocated when the slide member (6) returns to its said locked position.
2. A lock according to claim 1, characterised in that said abutment is formed by an edge (44a) of a ramp (43a) on a stationary plate (18) in the lock.
3. A lock according to claim 1, characterised in that said abutment is formed by an edge (130) of a slot (120) in a lock plate (118).
4. A lock as claimed in any one of claims 1 to 3 characterised by having at least two carriers (24a, 24b, 104, 106) said carriers being in the form of wheels mounted in the slide member (6) and coupled together directly or through an intermediate wheel (25), one carrier carrying a magnetic pin (28a, 108a) such that when the pin engages the abutment the carrier (24a, 104) is caused to rotate during movement of the slide member (6) between the locked and unlocking positions.
5. A lock as claimed in claim 4, characterised in that said at least two carriers (24a, 25) are of different diameters.
6. A lock as claimed in claim 5, characterised in that at least two of said carriers (24a, 25) are caused automatically to rotate through different predetermined angles on insertion of said code changing key (5), whereby a said carrier is rotated through more than one complete rotation before a code of the lock is repeated.
7. A lock as claimed in claim 4, characterised by means for rotating one of said carriers (24a, 104) on insertion of a said code changing key (5), said carrier in turn rotating the other carrier or carriers.
8. A lock as claimed in claim 4, characterised in that one of said carriers (24a, 104) carries a magnet pin (28a, 108a) which is acted on by the action of said code changing key (5) to move said carrier.
9. A lock as claimed in claim 8, characterised in that another one of said carriers (25, 52, 70, 82) carries only magnet pins which form part of the locking code for the lock and are not acted on by the code changing code of said code changing key (5) to cause movement of a said carrier.
10. A lock as claimed in claim 4, characterised in that a said carriers (51, 60, 81, 90, 104) carries more than one magnet pin.
11. A lock as claimed in claim 10, characterised in that two of said pins in a said carrier carrying more than one pin are of different polarity with respect to a said magnetically coded key (5).



12. A lock as claimed in any one of claims 1 to 3, characterised by at least one rotatable carrier (60, 90, 24a, 104) in the form of a wheel mounted in said slide member (6) carrying at least one magnet pin. 5
13. A lock as claimed in claim 12, characterised by a carrier (24a, 104) carrying a first magnet pin (28a, 108a) which is slid in a first direction, transverse to said slide member (6), by said code changing key (5) to engage an abutment during movement of the slide member (6) and so cause rotation of the carrier. 10
14. A lock as claimed in claim 13, characterised in that, when said lock is unlocked by a key which does not change the code of the lock from the existing code, said first magnet pin (28a, 108a) moves in an elongate groove (35a, 120) in the lock plate (12, 118). 15
15. A lock as claimed in claim 13, characterised in that after rotation of the carrier (24a, 104) said first magnet pin (28a) engages in an aperture (13') in the lock plate (12) to lock the slide member (6) in position. 20
16. A lock as claimed in claim 13, characterised in that said abutment is formed by a tang (43a) pressed from a stationary plate (18) in the lock. 25
17. A lock as claimed in claim 13, characterised by the carrier (60, 90) being stepwise rotated to move the magnet pin through a plurality of positions and at least two abutments are provided to enable rotation of said carrier by means of a said pin when it is at any one of at least two respective positions corresponding to said at least two abutments. 30
18. A lock as claimed in claim 17, characterised in that a first abutment is provided adjacent one face of the carrier (90) and a second abutment is provided adjacent the other face of the carrier. 35
19. A lock as claimed in claim 18, characterised in that said abutments are each formed by an arm of an L-shaped slot (96, 97). 40
20. A lock as claimed in claim 18, characterised in that at least two said carriers (90) are provided, said carriers being rotatable independently of each other. 45
21. A lock as claimed in claim 13, characterised in that the movement of the carrier (5, 104) is effected on movement of the slide member from the locked towards the unlocked position and on release of said slide member a carrier magnet pin (110a, 53b) enters an aperture (57, 134a) in the lock plate so as to align said carrier in a predetermined angular position, wherein said aperture extends in the direction of movement of the slide member and laterally thereof so that during the return movement of the slide member, the magnet pin in said aperture will be caused, if required, to complete rotation of said carrier to its predetermined angular position by engagement with an edge of the aperture. 50
22. A lock as claimed in claim 1, characterised by a plurality of carriers mounted in the slide member and each carrying at least one magnet pin, wherein a first of said carriers (24b, 51, 60, 81) carries a magnet pin which is acted on by the action of a code changing key to cause rotation of the carrier for changing the code of the lock from a first code to a second code, and a second of said carriers (25, 52, 70, 82) carries only a magnet pin or pins which form part of the locking code for the lock, said second carrier being caused to rotate by the rotation of the first carrier. 55
23. A magnetic key operated lock, comprising a generally planar slide member (6) movable from a locked position to an unlocking position with a magnetically coded key (5), a plurality of magnet pins (15) slidable transversely of the slide member (6) from a first position locking the slide member in said locked position to a second position unlocking said slide member on operation of the lock by a said magnetically coded key (5), the position and polarity of some or all of the magnet pins forming a locking code for the lock, at least one additional magnet pin (28a, 53a, 61a, 91a, 108a) in said lock being a code-changing pin movable by the action of a code changing key (5) from a first location to a second location in the principal plane of the slide member (6) to change the code from a first code to a second code, the code changing means also including a rotatably mounted wheel-shaped carrier (90, 104, 106) in the slide member (6) having said code changing magnet pin slidably carried therein characterised in that said code changing pin is arranged to engage an abutment (96, 130) which is formed by an edge of an aperture (94, 120) in a lock plate (118) as the slide member is moved with a code-changing key, thereby causing the carrier to rotate. 60



24. A lock as claimed in claim 23, characterised in that the abutment (96, 130) is formed by an edge of the aperture (94, 120), which edge extends generally at right angles to the direction of movement of the slide member (6).

5

25. A lock as claimed in claim 23, characterised in that at least two rotatable carriers (104, 106) are provided, said carriers being meshed together and each carrying at least one magnet pin (108a, 112a).

10

26. A lock as claimed in claim 23, characterised in that a respective abutment (130, 138) is associated with each carrier (104, 106), such that when the lock is in a first code a pin (108a) in a first carrier (104) engages the respective abutment (130) when the lock is operated by a first code changing key to change the code to a second code, and when the lock is in the second code, a pin (114a) in the second carrier (106) engages a respective abutment (138) on operation of the lock by a second code-changing key, to change the code from the second code to a third code (which may be the same as the first code).

15

20

25

27. A lock as claimed in claim 26, wherein two carriers are provided, characterised in that each carrier carries two magnet pins which are positioned on a diameter of the respective carrier.

30

28. A lock as claimed in claim 27 characterised by the pins (108a, 110a) of one carrier being rotationally offset by ninety degrees relative to the pins (112a, 114a) of the other carrier.

35

29. A lock as claimed in claim 28, characterised in that the pins (112a, 114a) in one carrier (106) may be of opposite polarity with respect to the key.

40

30. A lock as claimed in claim 27, characterised in that when the slide member (6) is in the locked position, the diameter joining two pins (108a, 110a) is at an angle to the direction of movement of the slide member and to the perpendicular to that direction in the plane of the slide member.

45

50

31. A lock as claimed in claim 4 or 23, characterised in that the carrier rotates about an axle (113, 115) on the slide member.

55

32. A lock as claimed in claim 1 or 23, further comprising a rotatable carrier (103) carrying at least one magnet pin (123"a), characterised in

that the carrier (103) is manually rotatable from outside of a housing of the lock to set the at least one magnet pin (123"a) in a different locking position.

33. A lock as claimed in claim 23, characterised in that a said rotatable carrier (104) has two magnet pins (108a, 110a) positioned on a diameter, a first of said pins (110a) forming a locking pin and a second of said pins (108a) forming a code changing pin, said first pin engaging in an aperture (126) in said lock plate (118) to prevent movement of said slide member (6) in the locking position for a first lock code, and said second pin engaging an edge (130) of a second aperture (120) in said lock plate so that movement of the slide member with a code-changing key (5) which unlocks the lock in the first code, causes rotation of said carrier to change the lock code from the first code to a second code.

34. A lock as claimed in claim 33, characterised in that said second aperture (120) has a first slot portion (128) having an edge (130) extending transversely of the direction of movement of the slide member (6) for engagement by the code-changing magnet pin, and a second slot portion (134) contiguous with said first portion and elongate in the direction of movement of the slide member, said two magnet pins (108a, 110a) carried by said carrier (104) sliding in said elongate slot portion (134) as said slide member returns to the locked position after a code-changing operation, said elongate slot portion being shaped to align said carrier to a preferred orientation.

35. A lock as claimed in claim 34, characterised in that said second, elongate, slot portion is widened at one end, such that said first pin can enter said widened slot portion (134a) before the slide member (6) reaches the end of its unlocking movement, on operation of the lock by a code-changing key.

36. A lock as claimed in claim 4 or 23, characterised in that more than one code changing means (43a, 130) are provided, actuatable independently of each other.

37. A lock as claimed in claim 1 or 23, characterised in that the code changing pins are cycled through a plurality of positions to provide a cycle of lock codes, and that there is provided a movable carrier (103) carrying a second code changing pin (123"a) forming part of the lock code, said carrier being man-



ually movable to move said second code changing pin between first and second positions to provide, in conjunction with the automatically movable code changing pin (28a, 108a), first and second cycles of lock codes.

38. A lock as claimed in claim 4 or 23, characterised by at least two magnet pins in each carrier (51, 60, 81, 90, 104) carrying more than one magnet pin being of opposite polarity to each other. 10
39. A lock as claimed in claim 32, characterised in that the manually rotatable carrier (103) is arranged to be rotated on insertion of a manual code changing tool so as to move a code changing magnet pin (123"a). 15
40. A lock as claimed in claim 4 or 25, characterised in that one of said carriers (25, 70, 82, 52) carries only magnet pins (26, 71, 88, 54) which form part of a locking code for the lock. 20
41. A key for a lock as claimed in any one of the preceding claims characterised by a body carrying predetermined magnetic codes with a first code arranged for unlocking the lock and a second code for changing the lock from the first code to a second code, whereby on unlocking the lock with the key the code of the lock is changed automatically to the second lock code preventing subsequent use of the key which lacks that code. 25 30
42. A key or set of keys for a lock as claimed in any one of claims 1 to 40, characterised in that the or each key comprises a body of magnetic material having a predetermined code encoded in it, the code or codes comprise one or more unlocking codes for the lock but not including a code changing code. 35 40
43. A key or set of keys for a lock as claimed in any one of claims 1 to 40, characterised in that the or each key comprising a body of magnetic material having a predetermined code encoded in it, the code or codes each comprise a plurality of unlocking codes for the lock together with a plurality of code changing codes for the lock, whereby the or each key can be used to cycle the lock to a predetermined code. 45 50
44. A key for a lock as claimed in any one of claims 1 through 40 characterised by a body carrying predetermined magnetic codes with a first code for unlocking the lock, a second code for changing the lock from a first code to 55

a second code, and a third code which forms the second code of the lock.

Patentansprüche

1. Von einem Magnetschlüssel betätigtes Schloß mit einem im allgemeinen ebenen Schieberelement (6), das mit einem magnetisch kodierten Schlüssel (5) aus einer verriegelten in eine entriegelte Position bewegt werden kann, mit einer Vielzahl von Magnetstiften (15), die beim Schließen des Schloßes durch den magnetisch kodierten Schlüssel (5) aus einer ersten Position, in welcher das Schieberelement in der verriegelten Position arretiert ist, in eine zweite Position, welche das Schieberelement entriegelt, quer zu dem Schieberelement (6) geschoben werden können, wobei die Position und die Polarität einiger der oder aller Magnetstifte einen Sperrcode für das Schloß bilden, mit wenigstens einem zusätzlichen Magnetstift (28a, 53a, 61a, 91a, 108a), der ein Kodewechsel-Stift (28a, 53a, 61a, 91a, 108a) ist, in dem Schloß, welcher durch die Wirkung eines Kodewechsel-Schlüssels (5) aus einer ersten Stellung in eine zweite Stellung in der Hauptebene des Schieberelementes (6) bewegt werden kann, um während der Bewegung des Schieberelementes (6) zwischen der verriegelten und der entriegelten Position durch das Zusammenwirken des Kodewechsel-Stiftes mit einem Anschlag den Code aus einem ersten Code in einen zweiten Code zu verändern, gekennzeichnet dadurch, daß der Kodewechsel-Stift (28a, 53a, 61a, 91a, 108a) in der zweiten Stellung bleibt, wenn das Schieberelement (6) in die verriegelte Position zurück geht.
2. Schloß nach Anspruch 1, gekennzeichnet dadurch, daß der Anschlag durch eine Kante (44a) einer Rampe (43a) auf einer feststehenden Platte (18) in dem Schloß gebildet wird.
3. Schloß nach Anspruch 1, gekennzeichnet dadurch, daß der Anschlag durch eine Kante (130) eines Schlitzes (120) in einer Schloßplatte (118) gebildet wird.
4. Schloß nach einem der Ansprüche 1 bis 3, gekennzeichnet dadurch, daß es wenigstens zwei Mitnehmer (24a, 24b, 104, 106) hat, wobei die Mitnehmer die Form von Rädern haben, die im Schieberelement (6) angebracht und direkt oder durch ein Zwischenrad (25) miteinander gekoppelt sind, wobei einer der Mitnehmer einen Magnetstift (28a, 108a) trägt, so daß während der Bewegung des Schieberelementes (6) zwischen der verriegelten und



der entriegelten Position die Rotation des Mitnehmers (24a, 104) bewirkt wird, wenn der Stift mit dem Anschlag zusammenwirkt.

5. Schloß nach Anspruch 4, gekennzeichnet dadurch, daß die wenigstens zwei Mitnehmer (24a, 25) einen unterschiedlichen Durchmesser haben.

5

6. Schloß nach Anspruch 5, gekennzeichnet dadurch, daß beim Einführen des Kodewechsel-Schlüssels (5) automatisch die Rotation von wenigstens zwei der Mitnehmer (24a, 25) um unterschiedliche, vorgegebene Winkel bewirkt wird, wodurch der Mitnehmer um mehr als eine vollständige Umdrehung gedreht wird, bevor sich ein Code des Schloßes wiederholt.

10

15

7. Schloß nach Anspruch 4, gekennzeichnet durch Mittel zur Rotation eines der Mitnehmer (24a, 104) beim Einführen des Kodewechsel-Schlüssels (5), wobei der Mitnehmer wiederum den oder die anderen Mitnehmer dreht.

20

8. Schloß nach Anspruch 4, gekennzeichnet dadurch, daß einer der Mitnehmer (24a, 104) einen Magnetstift (28a, 108a) trägt, der durch die Wirkung des Kodewechsel-Schlüssels (5) betätigt wird, um den Mitnehmer zu bewegen.

25

9. Schloß nach Anspruch 8, gekennzeichnet dadurch, daß ein anderer der Mitnehmer (25, 52, 70, 82) nur Magnetstifte trägt, die Bestandteil des Sperrkodes für das Schloß sind und nicht durch den Kodewechsel-Code des Kodewechsel-Schlüssels (5) betätigt werden, um die Bewegung des Mitnehmers zu veranlassen.

30

35

10. Schloß nach Anspruch 4, gekennzeichnet dadurch, daß die Mitnehmer (51, 60, 81, 90, 104) mehr als einen Magnetstift tragen.

40

11. Schloß nach Anspruch 10, gekennzeichnet dadurch, daß zwei der Stifte auf dem Mitnehmer, der mehr als einen Stift trägt, unterschiedliche Polarität im Verhältnis zum magnetisch kodierten Schlüssel (5) aufweisen.

45

12. Schloß nach einem der Ansprüche 1 bis 3, gekennzeichnet durch wenigstens einen drehbaren Mitnehmer (60, 90, 24a, 104) in der Form eines Rades, der auf dem Schieberelement (6) angebracht ist und wenigstens einen Magnetstift trägt.

50

13. Schloß nach Anspruch 12, gekennzeichnet durch einen Mitnehmer (24a, 104), der einen ersten Magnetstift (28a, 108a) trägt, der durch

55

den Kodewechsel-Schlüssel (5) in einer ersten Richtung, quer zu dem Schieberelement (6), geschoben wird, um während der Bewegung des Schieberelementes (6) mit einem Anschlag zusammenzuwirken und so die Rotation des Mitnehmers zu bewirken.

14. Schloß nach Anspruch 13, gekennzeichnet dadurch, daß sich der erste Magnetstift (28a, 108a) in einer Längsnut (35a, 120) in der Schloßplatte (12, 118) bewegt, wenn das Schloß durch einen Schlüssel entriegelt wird, der nicht den Code des Schloßes gegenüber dem bestehenden Code verändert.

15. Schloß nach Anspruch 13, gekennzeichnet dadurch, daß der erste Magnetstift (28a) nach der Rotation des Mitnehmers (24a, 104) in eine Öffnung (13') in der Schloßplatte (12) eingreift, um das Schieberelement (6) in der Position zu arretieren.

16. Schloß nach Anspruch 13, gekennzeichnet dadurch, daß der Anschlag durch einen Absatz (43a) gebildet wird, der aus der feststehenden Platte (18) im Schloß vorsteht.

17. Schloß nach Anspruch 13, gekennzeichnet dadurch, daß der Mitnehmer (60, 90) schrittweise gedreht wird, um den Magnetstift durch eine Vielzahl von Positionen zu bewegen, und daß wenigstens zwei Anschläge vorhanden sind, um die Rotation des Mitnehmers mittels des Stifts zu ermöglichen, wenn sich dieser an einer der wenigstens zwei Positionen befindet, die den wenigstens zwei Anschlägen entsprechen.

18. Schloß nach Anspruch 17, gekennzeichnet dadurch, daß ein erster Anschlag im Anschluß an eine Fläche des Mitnehmers (90) vorhanden ist und daß ein zweiter Anschlag im Anschluß an die andere Fläche des Mitnehmers vorhanden ist.

19. Schloß nach Anspruch 18, gekennzeichnet dadurch, daß die Anschläge jeweils durch einen Arm eines L-förmigen Schlitzes (96, 97) gebildet werden.

20. Schloß nach Anspruch 18, gekennzeichnet dadurch, daß wenigstens zwei Mitnehmer (90) vorhanden sind, wobei diese Mitnehmer unabhängig voneinander drehbar sind.

21. Schloß nach Anspruch 13, gekennzeichnet dadurch, daß die Bewegung des Mitnehmers (5, 104) durch die Bewegung des Schieberelementes



menten aus der verriegelten in die entriegelte Position bewirkt wird und daß bei der Freigabe des Schieberelementes ein Mitnehmer-Magnetstift (110a, 53b) in eine Öffnung (57, 134a) in der Schloßplatte eintritt, um so den Mitnehmer in einer festgelegten Winkelstellung auszurichten, wobei diese Öffnung in der Bewegungsrichtung des Schieberelementes und seitlich von dieser verläuft, so daß, wenn das erforderlich ist, der Magnetstift in der Öffnung während der Rückführungsbewegung des Schieberelementes dazu gebracht wird, die Rotation des Mitnehmers in die festgelegte Winkelstellung durch Zusammenwirken mit einer Kante der Öffnung zu bewirken.

22. Schloß nach Anspruch 1, gekennzeichnet durch eine Vielzahl von Mitnehmern, die im Schieberelement angebracht sind und die jeweils wenigstens einen Magnetstift tragen, wobei ein erster der Mitnehmer (24b, 51, 60, 81) einen Magnetstift trägt, der durch die Wirkung des Kodewechsel-Schlüssels betätigt wird, um die Rotation des Mitnehmers zur Veränderung des Codes des Schloßes von einem ersten Code in einen zweiten Code zu bewirken, und wobei ein zweiter der Mitnehmer (25, 52, 70, 82) nur einen Magnetstift oder Magnetstifte trägt, die Bestandteil des Sperrcodes für das Schloß sind, wobei der zweite Mitnehmer durch die Rotation des ersten Mitnehmers zur Rotation gebracht wird.

23. Von einem Magnetschlüssel betätigtes Schloß mit einem im allgemeinen ebenen Schieberelement (6), das mit einem magnetisch kodierten Schlüssel (5) aus einer verriegelten Position in eine entriegelte Position bewegt werden kann, mit einer Vielzahl von Magnetstiften (15), die beim Schließen des Schloßes durch den magnetisch kodierten Schlüssel (5) aus einer ersten Position, in welcher das Schieberelement in der verriegelten Position arretiert ist, in eine zweite Position, in welcher das Schieberelement entriegelt ist, quer zum Schieberelement (6) geschoben werden können, wobei die Position und die Polarität einiger der oder aller Magnetstifte einen Sperrcode für das Schloß bilden, mit wenigstens einem zusätzlichen Magnetstift (28a, 53a, 61a, 91a, 108a), der ein Kodewechsel-Stift ist, in dem Schloß, welcher durch die Wirkung eines Kodewechsel-Schlüssels (5) aus einer ersten Stellung in eine zweite Stellung in der Hauptebene des Schieberelementes (6) bewegt werden kann, um den Code von einem ersten Code in einen zweiten Code zu verändern, wobei das Kodewechsel-Mittel auch einen drehbar angebrachten, rad-

förmigen Mitnehmer (90, 104, 106) in dem Schieberelement (6) hat, welcher verschiebbar den den Code verändernden Magnetstift trägt, gekennzeichnet dadurch, daß der Kodewechsel-Stift so angeordnet ist, daß er mit einem Anschlag (96, 130) zusammenwirkt, der durch eine Kante einer Öffnung (94, 120) in einer Schloßplatte (118) gebildet wird, wenn das Schieberelement mit einem Kodewechsel-Schlüssel bewegt wird, wodurch eine Rotation des Mitnehmers bewirkt wird.

24. Schloß nach Anspruch 23, gekennzeichnet dadurch, daß der Anschlag (96, 130) durch eine Kante der Öffnung (94, 120) gebildet wird, wobei diese Kante im allgemeinen im rechten Winkel zur Bewegungsrichtung des Schieberelementes (6) verläuft.

25. Schloß nach Anspruch 23, gekennzeichnet dadurch, daß wenigstens zwei drehbare Mitnehmer (104, 106) vorhanden sind, wobei die Mitnehmer ineinandergreifen und jeder wenigstens einen Magnetstift (108a, 112a) trägt.

26. Schloß nach Anspruch 23, gekennzeichnet dadurch, daß jedem Mitnehmer (104, 106) ein entsprechender Anschlag (130, 138) zugeordnet ist, so daß, wenn sich das Schloß in einem ersten Code befindet, ein Stift (108a) in einem ersten Mitnehmer (104) mit dem entsprechenden Anschlag (130) zusammenwirkt, wenn das Schloß durch einen ersten Kodewechsel-Schlüssel geschlossen wird, um den Code in einen zweiten Code zu verändern, und, wenn sich das Schloß in dem zweiten Code befindet, ein Stift (114a) in dem zweiten Mitnehmer (106) beim Schließen des Schloßes durch einen zweiten Kodewechsel-Schlüssel mit einem entsprechenden Anschlag (138) zusammenwirkt, um den Code vom zweiten Code in einen dritten Code (welcher derselbe wie der erste Code sein kann) zu verändern.

27. Schloß nach Anspruch 26, in welchem zwei Mitnehmer vorhanden sind, gekennzeichnet dadurch, daß jeder Mitnehmer zwei Magnetstifte trägt, die auf dem Durchmesser des entsprechenden Mitnehmers angeordnet sind.

28. Schloß nach Anspruch 27, gekennzeichnet dadurch, daß die Stifte (108a, 110a) des einen Mitnehmers um neunzig Grad gegenüber den Stiften (112a, 114a) des anderen Mitnehmers rotationsversetzt sind.

29. Schloß nach Anspruch 28, gekennzeichnet dadurch, daß die Stifte (112a, 114a) auf dem



einem Mitnehmer (106) gegenüber dem Schlüssel eine entgegengesetzte Polarität aufweisen können.

30. Schloß nach Anspruch 27, gekennzeichnet dadurch, daß der Durchmesser, welcher zwei Stifte (108a, 110a) verbindet, einen Winkel zur Bewegungsrichtung des Schieberelementes und zur Senkrechten zu dieser Richtung in der Ebene des Schieberelementes bildet, wenn sich das Schieberelement (6) in der verriegelten Position befindet.

31. Schloß nach Anspruch 4 oder 23, gekennzeichnet dadurch, daß der Mitnehmer um eine Achse (113, 115) auf dem Schieberelement rotiert.

32. Schloß nach Anspruch 1 oder 23, das außerdem einen drehbaren Mitnehmer (103) aufweist, der wenigstens einen Magnetstift (123"a) trägt, gekennzeichnet dadurch, daß der Mitnehmer (103) manuell von außerhalb eines Gehäuses des Schloßes gedreht werden kann, um den wenigstens einen Magnetstift (123"a) in eine andere Verriegelungsposition zu bringen.

33. Schloß nach Anspruch 23, gekennzeichnet dadurch, daß der drehbare Mitnehmer (104) zwei Magnetstifte (108a, 110a) hat, die auf dem Durchmesser angeordnet sind, wobei ein erster der Stifte (110a) einen Verriegelungsstift bildet und ein zweiter der Stifte (108a) einen Kodewechsel-Stift bildet, wobei der erste Stift in eine Öffnung (126) in der Schloßplatte (118) eingreift, um die Bewegung des Schieberelementes (6) in der Verriegelungsposition zur Schaffung eines ersten Sperrkodes zu verhindern, und wobei der zweite Stift in eine Kante (130) einer zweiten Öffnung (120) in der Schloßplatte eingreift, so daß die Bewegung des Schieberelementes durch einen Kodewechsel-Schlüssel (5), welcher das Schloß im ersten Kode entriegelt, die Rotation des Mitnehmers bewirkt, um den Sperrkode aus einem ersten Kode in einen zweiten Kode zu verändern.

34. Schloß nach Anspruch 33, gekennzeichnet dadurch, daß die zweite Öffnung (120) einen ersten Schlitzabschnitt (128) hat, der eine Kante (130), die quer zur Bewegungsrichtung des Schieberelementes (6) verläuft, zum Zusammenwirken mit dem Kodewechsel-Magnetstift aufweist, und daß sie einen zweiten Schlitzabschnitt (134) hat, der an den ersten Abschnitt angrenzt und längs der Bewegungsrichtung des Schieberelementes verläuft, wobei zwei

Magnetstifte (108a, 110a), die von dem Mitnehmer (104) getragen werden, in dem Längsschlitzabschnitt (134) bewegt werden, wenn das Schieberelement nach einem Kodewechsel-Vorgang in die verriegelte Position zurück geht, und wobei der Längsschlitzabschnitt so geformt ist, daß er den Mitnehmer in einer bevorzugten Ausrichtung ausrichtet.

35. Schloß nach Anspruch 34, gekennzeichnet dadurch, daß der zweite, längs verlaufende Schlitzabschnitt an einem Ende aufgeweitet ist, so daß beim Schließen des Schloßes durch einen Kodewechsel-Schlüssel der erste Stift in den aufgeweiteten Schlitzabschnitt (134a) eintreten kann, bevor das Schieberelement (6) das Ende der Entriegelungsbewegung erreicht.

36. Schloß nach Anspruch 4 oder 23, gekennzeichnet dadurch, daß mehr als ein Kodewechsel-Mittel (43a, 130) vorhanden sind, die unabhängig voneinander betätigt werden können.

37. Schloß nach Anspruch 1 oder 23, gekennzeichnet dadurch, daß die Kodewechsel-Stifte zyklisch durch eine Vielzahl von Positionen geführt werden, um einen Zyklus an Sperrkodes zu schaffen, und daß ein beweglicher Mitnehmer (103) vorhanden ist, der einen zweiten Kodewechsel-Stift (123"a) trägt, welcher Bestandteil des Sperrkodes ist, wobei der Mitnehmer manuell bewegt werden kann, um den zweiten Kodewechsel-Stift zwischen einer ersten und einer zweiten Position zu bewegen, um in Verbindung mit dem automatisch zu bewegendem Kodewechsel-Stift (28a, 108a) erste und zweite Zyklen von Sperrkodes zu schaffen.

38. Schloß nach Anspruch 4 oder 23, gekennzeichnet dadurch, daß wenigstens zwei Magnetstifte in jedem Mitnehmer (51, 60, 81, 90, 104) mehr als einen Magnetstift von einander entgegengesetzter Polarität tragen.

39. Schloß nach Anspruch 32, gekennzeichnet dadurch, daß der manuell drehbare Mitnehmer (130) so angeordnet ist, daß er bei Einführung eines manuellen Kodewechsel-Instruments gedreht wird, um so einen Kodewechsel-Magnetstift (123"a) zu bewegen.

40. Schloß nach Anspruch 4 oder 25, gekennzeichnet dadurch, daß einer der Mitnehmer (25, 70, 82, 52) nur Magnetstifte (26, 71, 88, 54) trägt, die Bestandteil eines Sperrkodes für das Schloß sind.



41. Schlüssel für ein Schloß nach einem der vorhergehenden Ansprüche, gekennzeichnet durch einen Körper, der festgelegte Magnetkodes trägt, wobei ein erster Kode so aufgebaut ist, daß er das Schloß entriegelt, und ein zweiter Kode so aufgebaut ist, daß er das Schloß aus dem ersten Kode in einen zweiten Kode verändert, wodurch beim Aufschließen des Schloßes mit dem Schlüssel der Kode des Schloßes automatisch in den zweiten Sperrkode verändert wird, womit die nachfolgende Nutzung des Schlüssels, der diesen Kode nicht aufweist, verhindert wird.

42. Schlüssel oder Schlüsselsatz für ein Schloß nach einem der Ansprüche 1 bis 40, gekennzeichnet dadurch, daß der oder jeder der Schlüssel einen Körper aus magnetischem Material aufweist, in den ein festgelegter Kode kodiert ist, wobei der Kode oder die Codes einen oder mehrere Entriegelungskodes für das Schloß aufweisen, aber keinen Kodewechsel-Kode einschließen.

43. Schlüssel oder Schlüsselsatz für ein Schloß nach einem der Ansprüche 1 bis 40, gekennzeichnet dadurch, daß der oder jeder der Schlüssel einen Körper aus magnetischem Material aufweist, in den ein festgelegter Kode kodiert ist, wobei der Kode oder die Codes jeweils eine Vielzahl von Entriegelungskodes für das Schloß in Verbindung mit einer Vielzahl von Kodewechsel-Kodes für das Schloß aufweisen, wodurch der oder jeder der Schlüssel benutzt werden können, um das Schloß zyklisch zu einem vorgegebenen Kode zu führen.

44. Schlüssel für ein Schloß nach einem der Ansprüche 1 bis 40, gekennzeichnet durch einen Körper, der vorgegebene magnetische Codes mit einem ersten Kode zum Entriegeln des Schloßes, einem zweiten Kode zur Umstellung des Schloßes von einem ersten Kode auf einen zweiten Kode und einem dritten Kode, der den zweiten Kode des Schloßes bildet, aufweist.

Revendications

1. Une serrure actionnée par une clé magnétique, comprenant un élément coulissant généralement plan (6), pouvant se déplacer d'une position de verrouillage vers une position de déverrouillage par l'intermédiaire d'une clé à codage magnétique (5), plusieurs broches magnétiques (15) pouvant glisser transversalement par rapport à l'élément coulissant (6), d'une première position verrouillant l'élément coulissant dans ladite position de verrouillage vers une

deuxième position déverrouillant ledit élément coulissant lors de l'actionnement de la serrure par une dite clé à codage magnétique (5), la position et la polarité de quelques-unes ou de toutes les broches magnétiques formant un code de verrouillage de la serrure, au moins une broche magnétique additionnelle (28a, 53a, 61a, 91a, 108a) dans ladite serrure étant une broche de changement de code (28a, 53a, 61a, 91a, 108a), pouvant être déplacée par l'intermédiaire d'une clé de changement de code (5), d'un premier emplacement vers un deuxième emplacement dans le plan principal de l'élément coulissant (6), pour changer le code d'un premier code en un deuxième code, par engagement de ladite broche de changement de code contre une butée pendant le déplacement de l'élément coulissant (6) entre les positions de verrouillage et de déverrouillage, caractérisée par ladite broche de changement de code (28a, 53a, 61a, 91a, 108a), restant déplacée lorsque l'élément coulissant (6) retourne vers sa dite position de verrouillage.

2. Une serrure selon la revendication 1, caractérisée en ce que ladite butée est formée par un bord (44a) d'une rampe (43a) sur une plaque stationnaire (18) dans la serrure.

3. Une serrure selon la revendication 1, caractérisée en ce que ladite butée est formée par un bord (130) d'une fente (120) dans une plaque de la serrure (118).

4. Une serrure selon l'une quelconque des revendications 1 à 3, caractérisée en ce qu'elle comporte au moins deux supports (24a, 24b, 104, 106), lesdits supports ayant la forme de roues, montés dans l'élément coulissant (6) et accouplés directement ou par l'intermédiaire d'une roue intermédiaire (25), un support supportant une broche magnétique (28a, 108a), de sorte que lorsque la broche s'engage dans la butée, le support (24a, 104) est entraîné à tourner pendant le déplacement de l'élément coulissant (6) entre les positions de verrouillage et de déverrouillage.

5. Une serrure selon la revendication 4, caractérisée en ce que lesdits au moins deux supports (24a, 25) ont des diamètres différents.

6. Une serrure selon la revendication 5, caractérisée en ce que au moins deux des dits supports (24a, 25) sont entraînés automatiquement à tourner autour d'angles prédéterminés différents lors de l'insertion de ladite clé de changement de code (5), un des dits supports étant



ainsi entraîné à accomplir plus d'une rotation complète avant la répétition d'un code de la serrure.

7. Une serrure selon la revendication 4, caractérisée par un moyen destiné à faire tourner un des dits supports (24a, 104) lors de l'insertion de ladite clé de changement de code (5), ledit support faisant à son tour tourner l'autre support ou les autres supports.

5

8. Une serrure selon la revendication 4, caractérisée en ce que l'un des dits supports (24a, 104) supporte une broche magnétique (28a, 108a), influencée par l'actionnement de ladite clé de changement de code (5) pour déplacer ledit support.

10

15

9. Une serrure selon la revendication 8, caractérisée en ce qu'un autre des dits supports (25, 52, 70, 82) supporte uniquement des broches magnétiques faisant partie du code de verrouillage de la serrure et non influencées par le code de changement de code de ladite clé de changement de code (5) pour entraîner le déplacement d'un des dits supports.

20

25

10. Une serrure selon la revendication 4, caractérisée en ce que l'un des dits supports (51, 60, 81, 90, 104) supporte plus d'une broche magnétique.

30

11. Une serrure selon la revendication 10, caractérisée en ce que deux des dites broches dans un des dits supports supportant plus d'une broche ont une polarité différente d'une dite clé à codage magnétique (5).

35

12. Une serrure selon l'une quelconque des revendications 1 à 3, caractérisée par au moins un support rotatif (60, 90, 24a, 104), sous forme d'une roue, monté dans ledit élément coulissant (6), supportant au moins une broche magnétique.

40

13. Une serrure selon la revendication 12, caractérisée par un support (24a, 104) supportant une première broche magnétique (28a, 108a), qui est glissée dans une première direction, transversale au dit élément coulissant (6), par ladite clé de changement de code (5), pour s'engager dans une butée pendant le déplacement de l'élément coulissant (6) et entraîner ainsi la rotation du support.

45

50

55

14. Une serrure selon la revendication 13, caractérisée en ce que, lorsque ladite serrure est déverrouillée par une clé ne changeant pas le

code de la serrure par rapport au code existant, ladite première broche magnétique (28a, 108a) se déplace dans une rainure allongée (35a, 120) dans la plaque de la serrure (12, 118).

15. Une serrure selon la revendication 13, caractérisée en ce que, après la rotation du support (24a, 104), ladite première broche magnétique (28a) s'engage dans une ouverture (13') dans la plaque de la serrure (12) pour bloquer l'élément coulissant (6) dans sa position.

16. Une serrure selon la revendication 13, caractérisée en ce que ladite butée est formée par un tenon (43a) pressé à partir d'une plaque stationnaire (18) dans la serrure.

17. Une serrure selon la revendication 13, caractérisée en ce que le support (60, 90) est tourné pas à pas pour déplacer la broche magnétique à travers plusieurs positions et en ce qu'elle comporte au moins deux butées pour permettre la rotation du dit support par l'intermédiaire d'une des dites broches, lorsqu'il se trouve dans une quelconque d'au moins deux positions respectives correspondant aux dites au moins deux butées.

18. Une serrure selon la revendication 17, caractérisée en ce qu'une première butée est agencée près d'une face du support (90) et en ce qu'une deuxième butée est agencée près de l'autre face du support.

19. Une serrure selon la revendication 18, caractérisée en ce que lesdites butées sont chacune formées par un bras d'une fente en forme de L (96, 97).

20. Une serrure selon la revendication 18, caractérisée en ce qu'elle comporte au moins deux des dits supports (90), lesdits supports pouvant tourner indépendamment l'un de l'autre.

21. Une serrure selon la revendication 13, caractérisée en ce que le déplacement du support (5, 104) est effectué lors du déplacement de l'élément coulissant, de la position de verrouillage vers la position de déverrouillage, et que lors du relâchement du dit élément coulissant, une broche magnétique de support (110a, 53b) rentre dans une ouverture (57, 134a) dans la plaque de la serrure, de sorte à aligner ledit support dans une position angulaire prédéterminée, dans laquelle ladite ouverture s'étend dans la direction du déplacement de l'élément coulissant et latéralement par rapport à celui-



ci, de sorte que pendant le déplacement de retour de l'élément coulissant, la broche magnétique dans ladite ouverture sera entraînée, si nécessaire, à achever la rotation du dit support vers sa position angulaire prédéterminée par suite de l'engagement dans un bord de l'ouverture.

22. Une serrure selon la revendication 1, caractérisée par plusieurs supports montés dans l'élément coulissant, chacun supportant au moins une broche magnétique, dans laquelle un premier des dits supports (24b, 51, 60, 81) supporte une broche magnétique influencée par l'actionnement d'une clé de changement de code pour entraîner la rotation du support en vue du changement du code de la serrure, d'un premier code en un deuxième code, un deuxième des dits supports (25, 52, 70, 82) supportant uniquement une broche magnétique ou des broches faisant partie du code de verrouillage de la serrure, ledit deuxième support étant entraîné à tourner par suite de la rotation du premier support.

23. Une serrure actionnée par une clé magnétique, comprenant un élément coulissant généralement plan (6), pouvant se déplacer d'une position de verrouillage vers une position de déverrouillage par l'intermédiaire d'une clé à codage magnétique (5), plusieurs broches magnétiques (15) pouvant glisser transversalement par rapport à l'élément coulissant (6), d'une première position, verrouillant l'élément coulissant dans ladite position de verrouillage, vers une deuxième position, déverrouillant ledit élément coulissant lors de l'actionnement de la serrure par une dite clé à codage magnétique (5), la position et la polarité de quelques-unes ou de toutes les broches magnétiques formant un code de verrouillage de la serrure, au moins une broche magnétique additionnelle (28a, 53a, 61a, 91a, 108a) dans ladite serrure étant une broche de changement de code, pouvant être déplacée par l'intermédiaire d'une clé de changement de code (5), d'un premier emplacement vers un deuxième emplacement dans le plan principal de l'élément coulissant (6), pour changer le code d'un premier code en un deuxième code, le moyen de changement de code englobant également un support en forme de roue, monté par rotation (90, 104, 106) dans l'élément coulissant (6), supportant par glissement ladite broche magnétique de changement de code, caractérisée en ce que ladite broche de changement de code est agencée de sorte à s'engager dans une butée (96, 130), formée par un bord d'une ouverture (94, 120)

dans une plaque de la serrure (118), lorsque l'élément coulissant est déplacé par l'intermédiaire d'une clé de changement de code, entraînant ainsi la rotation du support.

24. Une serrure selon la revendication 23, caractérisée en ce que la butée (96, 130) est formée par un bord de l'ouverture (94, 120), ce bord s'étendant généralement à des angles droits par rapport à la direction du déplacement de l'élément coulissant (6).

25. Une serrure selon la revendication 23, caractérisée en ce qu'elle comporte au moins deux supports rotatifs (104, 106), lesdits supports étant interconnectés et chacun supportant au moins une broche magnétique (108a, 112a).

26. Une serrure selon la revendication 23, caractérisée en ce qu'une butée respective (130, 138) est associée avec chaque support (104, 106), de sorte que lorsque la serrure correspond à un premier code, une broche (108a) dans un premier support (104) s'engage dans la butée respective (130) lorsque la serrure est actionnée par une première clé de changement de code pour changer le code en un deuxième code, et que lorsque la serrure correspond à un deuxième code, une broche (114a) dans le deuxième support (106) s'engage dans une butée respective (138) lors de l'actionnement de la serrure par une deuxième clé de changement de code, pour faire passer le code du deuxième code en un troisième code (pouvant être le même que le premier code).

27. Une serrure selon la revendication 26, comportant deux supports, caractérisée en ce que chaque support supporte deux broches magnétiques positionnées sur un diamètre du support respectif.

28. Une serrure selon la revendication 27, caractérisée en ce que les broches (108a, 110a) d'un support sont décalées par rotation de quatre-vingt-dix degrés par rapport aux broches (112a, 114a) de l'autre support.

29. Une serrure selon la revendication 28, caractérisée en ce que les broches (112a, 114a) dans un support (106) peuvent avoir une polarité opposée à celle de la clé.

30. Une serrure selon la revendication 27, caractérisée en ce que, lorsque l'élément coulissant (6) se trouve dans la position de verrouillage, le diamètre réunissant deux broches (108a, 110a) forme un angle par rapport à la direction



du déplacement de l'élément coulissant et par rapport à la perpendiculaire à cette direction dans le plan de l'élément coulissant.

31. Une serrure selon les revendications 4 et 23, caractérisée en ce que le support tourne autour d'un axe (113, 115) sur l'élément coulissant.

32. Une serrure selon les revendications 1 ou 23, comprenant en outre un support rotatif (103), supportant au moins une broche magnétique (123"a), caractérisée en ce que le support (103) peut être tourné manuellement de l'extérieur d'un boîtier de la serrure pour placer au moins une broche magnétique (123"a) dans une position de verrouillage différente.

33. Une serrure selon la revendication 23, caractérisée en ce que l'un des dits supports rotatifs (104) comporte deux broches magnétiques (108a, 110a) positionnées sur un diamètre, une première des dites broches (110a) constituant une broche de verrouillage et une deuxième des dites broches (108a) constituant une broche de changement de code, ladite première broche s'engageant dans une ouverture (126) dans ladite plaque de la serrure (118) pour empêcher le déplacement du dit élément coulissant (6) dans la position de verrouillage d'un premier code de verrouillage, ladite deuxième broche s'engageant dans un bord (130) d'une deuxième ouverture (120) dans ladite plaque de la serrure, de sorte que le déplacement de l'élément coulissant au moyen d'une clé de changement de code (5), déverrouillant la serrure dans le premier code, entraîne la rotation du dit support pour changer le code de la serrure, d'un premier code en un deuxième code.

34. Une serrure selon la revendication 33, caractérisée en ce que ladite deuxième ouverture (120) comporte une première partie de fente (128) possédant un bord (130), s'étendant transversalement par rapport à la direction du déplacement de l'élément coulissant (6) en vue de l'engagement par la broche magnétique de changement de code, et une deuxième partie de fente (134) contiguë à ladite première partie et allongée dans la direction du déplacement de l'élément coulissant, lesdites deux broches magnétiques (108a, 110a) supportées par ledit support (104) glissant dans ladite partie de fente allongée (134) lorsque ledit élément coulissant retourne vers la position de verrouillage après une opération de changement de code, ladite partie de fente allongée étant formée de

sorte à aligner ledit support en fonction d'une orientation préférée.

35. Une serrure selon la revendication 34, caractérisée en ce que ladite deuxième partie de fente allongée est élargie au niveau d'une extrémité, de sorte que ladite première broche peut entrer dans ladite partie de fente élargie (134a) avant que l'élément coulissant (6) n'atteigne l'extrémité de son déplacement de déverrouillage, lors de l'actionnement de la serrure par une clé de changement de code.

36. Une serrure selon les revendications 4 ou 23, caractérisée en ce qu'elle comporte plus d'un moyen de changement de code (43a, 130) pouvant être actionnés indépendamment les uns des autres.

37. Une serrure selon les revendications 1 ou 23, caractérisée en ce que les broches de changement de code passent cycliquement à travers plusieurs positions pour fournir un cycle de codes de verrouillage et en ce qu'elle comporte un support mobile (103) supportant une deuxième broche de changement de code (123"a) faisant partie du code de verrouillage, ledit support pouvant être déplacé manuellement pour déplacer ladite deuxième broche de changement de code entre des première et deuxième positions pour fournir, en combinaison avec la broche de changement de code à déplacement automatique (28a, 108a), des premier et deuxième cycles de codes de verrouillage.

38. Une serrure selon les revendications 4 ou 23, caractérisée en ce qu'elle comporte au moins deux broches magnétiques dans chaque support (51, 60, 81, 90, 104), supportant plus d'une broche magnétique, ont des polarités opposées.

39. Une serrure selon la revendication 32, caractérisée en ce que le support à rotation manuelle (103) est agencé de sorte à être tourné lors de l'insertion d'un outil de changement de code manuel, de sorte à déplacer une broche magnétique de changement de code (123"a).

40. Une serrure selon les revendications 4 ou 25, caractérisée en ce que l'un des dits supports (25, 70, 82, 52) supporte uniquement des broches magnétiques (26, 71, 88, 54) faisant partie d'un code de verrouillage de la serrure.

41. Une clé pour une serrure selon l'une quelconque des revendications précédentes, caractérisée



sée par un corps supportant des codes magnétiques prédéterminés, avec un premier code destiné à déverrouiller la serrure et un deuxième code destiné à changer la serrure, la faisant passer du premier code à un deuxième code, le déverrouillage de la serrure avec la clé entraînant un changement automatique du code de la serrure et la faisant passer au deuxième code de verrouillage, empêchant ainsi une utilisation ultérieure de la clé ne possédant pas ce code.

42. Une clé ou un jeu de clés pour une serrure selon l'une quelconque des revendications 1 à 40, caractérisés en ce que la clé ou chaque clé comprend un corps composé de matériau magnétique, englobant le codage d'un code prédéterminé, le code ou les codes comprenant un ou plusieurs codes de déverrouillage de la serrure, mais n'englobant pas un code de changement de code.

43. Une clé ou un jeu de clés pour une serrure selon l'une quelconque des revendications 1 à 40, caractérisés en ce que la clé ou chaque clé comprend un corps composé de matériau magnétique, englobant le codage d'un code prédéterminé, le code ou les codes comprenant chacun plusieurs codes de déverrouillage de la serrure ainsi que plusieurs codes de changement de code de la serrure, la clé ou chaque clé pouvant ainsi servir à faire correspondre cycliquement la serrure à un code prédéterminé.

44. Une clé pour une serrure selon l'une quelconque des revendications 1 à 40, caractérisés par un corps supportant des codes magnétiques prédéterminés, avec un premier code destiné à déverrouiller la serrure, un deuxième code pour changer la serrure et la faire passer d'un premier code à un deuxième code et un troisième code constituant le deuxième code de la serrure.