

Slicer

BACKGROUND OF THE INVENTION5 Field of the Invention

[0001]

The present invention relates to a slicer for slicing a material to be sliced, such as a vegetable, fruit or the like, and in particular concerns a slicer capable of desirably adjust a
10 slicing width of the material to be sliced.

Description of the Related Art

[0002]

Conventionally, as a slicer for use in easily slicing
15 various materials to be sliced, such as vegetables, fruits or the like, into sliced pieces having a desired width, such a slicer has been used in which the material to be sliced is reciprocally moved forward and rearward in the slicing direction so as to slice the material to be sliced by using a slicing blade.

20 [0003]

As a conventional slicer, such a slicer has been known which is provided with a frame having a pair of right and left supporting arms, a slicing blade with two ends thereof being secured to the supporting arms, a fixed supporting plate that is
25 placed on the front side of the slicing blade and passed between a pair of right and left frame portions, and a movable supporting plate that is placed on the rear side of the slicing blade, with the slicing width (thickness) of a sliced material width being made adjustable by moving the movable supporting plate in a
30 vertical direction.

[0004]

As the movable supporting plate of this slicer, a structure has been known in which its two ends are journaled to the paired right and left supporting arms so as to be able to rock in
35 vertical directions (for example, see JP-A No. 2004-338069), and another structure has been known in which it is movable

horizontally in vertical directions by a spacer disposed below a movable receiving plate (for example, see JP-A No. 2011-156435).

[0005]

[Patent Document 1] JP-A No. 2004-338069

5 [Patent Document 2] JP-A No. 2011-156435

[0006]

In the case of the above-mentioned former slicer, however, as shown in Figs. 7(a) and 7(b), a movable supporting plate 91 is positioned so as to be tilted downward in a vertical direction H, with a slicing blade 92 being diagonally disposed relative to a
10 slicing direction S, that is, with a distance between the movable supporting plate 91 and the slicing blade 92 being gradually widened from one of the ends in a width direction W toward the other end; therefore, in the case when a material M to be sliced
15 is long in the width direction W, a problem arises in which deviations occur between a thickness ta of its cut portion a on the one of the end sides in the width direction W of a sliced piece C and a thickness tb of its cut portion b on the other end side.

20 [0007]

Moreover, since the slicing blade 92 that is intruded to a material M to be sliced horizontally slices the material to be sliced, a problem arises in which in the case when a material to be sliced is long in a slicing direction S, as shown in Figs.
25 8(a) to 8(d), deviations occur in the thicknesses of a sliced piece C before and after the slicing direction S, that is, a thickness tc on the tip side in the slicing direction S of the sliced piece C and a thickness td on the rear side are different from each other.

30 [0008]

Furthermore, in the case of the above-mentioned latter slicer, since the movable supporting plate assembled onto the frame is not easily removed from the frame, cut chips of the material to be sliced tend to be caught in a gap between the
35 movable supporting plate and the spacer, or waste water containing soil or the like adhering to the surface of a material

to be sliced tends to remain in the gap, with the result that sanitation might become poor as the slicer is used.

[0009]

5 In the case of a slicer in which a movable supporting plate made of resin is used, since upon slicing a material to be sliced, the movable supporting plate is deflected downward in the vertical direction by a pressing force exerted onto the material to be sliced, the gap between the slicing blade and the movable supporting plate is widened beyond a predetermined gap between
10 the slicing blade and the movable supporting plate, the sliced pieces tend to become thicker than the intended thickness.

[0010]

Therefore, in order to slice the material to be sliced with a uniform thickness and also to provide a slicer capable of being
15 used sanitarily, there are some technical problems to be solved, and the object of the present invention is to solve these problems.

SUMMARY OF THE INVENTION

20 [0011]

The present invention, which has been proposed to achieve the above object, includes an invention according to claim 1 that provides a slicer including: a frame, a slicing blade with its two ends being supported by the frame, a movable supporting plate
25 that supports a material to be sliced when the material to be sliced is moved to slide toward the slicing blade, and a slice width adjusting mechanism capable of adjusting the slicing width of the material to be sliced by raising and lowering the movable supporting plate in vertical directions, and in this structure,
30 the slice width adjusting mechanism is provided with: a slice width adjusting dial having a cylindrical shape that has a screw portion formed on an outer peripheral surface, and is capable of supporting the rear surface of the movable supporting plate horizontally, a screw receiving hole that is integrally formed
35 with the frame and capable of being engaged with the screw portion and a rib that is formed to stand on the rear surface of

the movable supporting plate and can be fitted into the slice width adjusting dial.

[0012]

5 In accordance with this structure, since the movable supporting plate is raised and lowered with its horizontal state being maintained by the slice width adjusting dial, the slice width adjusting dial is positioned at a desired position in a height direction in accordance with an engaged state between the screw portion and the screw receiving hole; therefore, since the
10 movable supporting plate is raised and lowered depending on the position of the slice width adjusting dial, with its horizontal state being maintained, it becomes possible to slice a material to be sliced with a uniform thickness regardless of the size of the material to be sliced.

15 [0013]

Moreover, by allowing the slice width adjusting dial to support the rear surface of the movable supporting plate without a gap, it is possible to prevent cut chips and waste water from remaining between the slice width adjusting dial and the movable
20 supporting plate, and consequently to sanitarily use the slicer.

[0014]

Furthermore, since the rib is formed on the rear surface of the movable supporting plate, the rigidity of the movable supporting plate is increased so that it becomes possible to
25 prevent the movable supporting plate from being deflected downward by a pressing force exerted when the movable supporting plate slices a material to be sliced.

[0015]

An invention disclosed in claim 2 provides a slicer in
30 which, in addition to the structure of the slicer of claim 1, the movable supporting plate has an easily deflecting region that is formed on the front side in the slicing direction as a narrowed portion along the slicing directions in which the material to be sliced is allowed to slide upon slicing the material to be sliced,
35 with at least one portion of the slice width adjusting dial being made to support the inside of the easily deflecting region.

[0016]

In accordance with this structure, since the slice width adjusting dial supports the movable supporting plate within the easily deflecting region of the movable supporting plate it becomes possible to further prevent the movable supporting plate from being deflected downward by a pressing force exerted when the movable supporting plate slices a material to be sliced.

[0017]

An invention disclosed in claim 3 provides a slicer in which, in addition to the structure of the slicer of claim 2, the movable supporting plate has an easily deflecting region that is formed on the front side in the slicing direction as a narrowed portion along the slicing directions in which the material to be sliced is allowed to slide upon slicing the material to be sliced, with at least one portion of the rib being disposed inside the easily deflecting region.

[0018]

In accordance with this structure, since the rib is disposed within the easily deflecting region of the movable supporting plate, it becomes possible to further prevent the movable supporting plate from being deflected downward by a pressing force exerted when the movable supporting plate slices a material to be sliced.

[0019]

An invention disclosed in claim 4 provides a slicer in which, in addition to the structure of the slicer of any one of claims 1 to 3, the frame is provided with a guide groove formed as a concave portion in a direction perpendicular to the inner peripheral surface, and the movable supporting plate has guide pins that are attached to two sides thereof in the width direction orthogonal to the slicing direction, and capable of being engaged with the guide groove.

[0020]

In accordance with this structure, since the movable supporting plate is raised and lowered upward and downward, it is

possible to easily position-determine the movable supporting plate.

[0021]

5 An invention disclosed in claim 5 provides a slicer in which, in addition to the structure of the slicer according to claim 4, the guide groove is formed on the rear surface of of the frame in a direction perpendicular thereto so as to be opened therefrom, and the guide pin of the movable supporting plate is attachably detached from the guide groove through the opening of
10 the guide groove.

[0022]

In accordance with this structure, since the movable supporting plate can be detached from the frame, it becomes possible to easily wash the movable supporting plate.

15 [0023]

An invention disclosed in claim 6 provides a slicer in which, in addition to the structure of the slicer of any one of claims 1 to 5, in the case when the movable supporting plate is divided into a tip portion, a center portion and a rear portion
20 from the tip to the rear end in the slicing direction, the rib is disposed in a manner so as to bridge over the tip portion and the center portion of the movable supporting plate.

[0024]

In accordance with this structure, since the rib is formed
25 over a wide range of the movable supporting plate, it is possible to prevent the movable supporting plate from being deflected downward by a pressing force exerted when the movable supporting plate slices a material to be sliced.

[Effects of the Invention]

30 [0025]

Since the slicer in accordance with the present invention raises and lowers the movable supporting plate horizontally while suppressing the deflection of the movable supporting plate, it becomes possible to slice a material to be sliced with a uniform
35 thickness regardless of the size of the material to be sliced,

and also to suppress cut chips and waste water from remaining;
thus, the slicer can be sanitarilly used.

BRIEF DESCRIPTION OF THE DRAWINGS

5 [0026]

Figs. 1(a) and 1(b) are drawings that show a slicer in accordance with one embodiment of the present invention; Fig. 1(a) is a perspective view showing the surface side of the slicer; and Fig. 1(b) is a perspective view showing the rear surface side of the slicer.

10 Figs. 2(a) to 2(c) are drawings that show a frame and a fixed supporting plate; Fig. 2(a) is a plan view showing a surface side of the frame; Fig. 2(b) is a bottom face view showing a rear surface side of the frame; and Fig. 2(c) is a cross-sectional view taken along line IIC-IIC in Fig. 2(a).

15 Figs. 3(a) to 3(d) are drawings that show the movable supporting plate of Fig. 1; Fig. 3(b) is a bottom face view showing a rear surface side of the movable supporting plate; Fig. 3(c) is a side view of the movable supporting plate; and Fig. 3(d) is a cross-sectional view taken along line IIID-IIID in Fig. 3(a).

25 Figs. 4(a) to 4(c) are drawings that show the slice width adjusting dial of Fig. 1; Fig. 4(a) is a perspective view showing the slice width adjusting dial; Fig. 4(b) is a plan view of the slice width adjusting dial; and Fig. 4(c) is a cross-sectional view taken along line IVC-IVC in Fig. 4(b).

Fig. 5 is a schematic view that explains the action of the slice width adjusting dial.

30 Fig. 6 is a schematic view that shows a state in which a material to be sliced is sliced by using the slice width adjusting dial.

Fig. 7 is a schematic view that explains a deviation in the slice width in the width direction in a conventional slicer.

35 Fig. 8 is a schematic view that explains a deviation in the slice width in the slicing direction in the conventional slicer.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0027]

In order to achieve the object for providing a slicer that can slice a material to be sliced with a uniform thickness and is capable of being used sanitarily, the present invention is provided with a slicer including: a frame, a slicing blade with its two ends being supported by the frame, a movable supporting plate that supports a material to be sliced when the material to be sliced is moved to slide toward the slicing blade, a slice width adjusting mechanism capable of adjusting the slicing width of the material to be sliced by raising and lowering the movable supporting plate in vertical directions, and in this structure, the slice width adjusting mechanism is provided with: a slice width adjusting dial having a cylinder shape that has a screw portion formed on an outer peripheral surface, and is capable of supporting the rear surface of the movable supporting plate horizontally, a screw receiving hole that is integrally formed with the frame and capable of being engaged with the screw portion and a rib that is formed to stand on the rear surface of the movable supporting plate and fitted into the slice width adjusting dial; thus, it becomes possible to achieve the object.

[Embodiments]

[0028]

Referring to Figs., the following description will discuss one embodiment relating to a slicer 1 in accordance with the present invention. Additionally, in the following description, terms "front" and "rear" correspond to the front side and the rear side in a slicing direction that is coincident with a feeding direction of a material to be sliced at the time of slicing the material to be sliced. Moreover, terms "up" and "down" correspond to the upper side and the downward side in a perpendicular direction to the slicer.

[0029]

As shown in Fig. 1(a) and Fig. 1(b), the slicer 1 is provided with a frame 10, a slicing blade 20 for slicing a material to be sliced, a fixed supporting plate 30 disposed on

the front side of the slicing blade 20, a movable supporting plate 40 disposed on the rear side of the slicing blade 20, an exchange blade 50 that is exchangeable, and a slicing width adjusting mechanism 100 that position-determines the movable supporting plate 40 at a desired position in the vertical direction by the slicing width adjusting dial 60. The frame 10, the fixed supporting plate 30, the movable supporting plate 40 and the slicing width adjusting dial 60 are respectively made of an ABS resin and produced by an injection molding process. The slicing blade 20 and the exchange blade 50 are made of stainless steel.

[0030]

The slicer 1 is designed such that when a user reciprocally moves a material to be sliced in a slicing direction S while pressing the material to be sliced onto the movable supporting plate 40, the material to be sliced is sliced into sliced pieces having a thickness in accordance with a gap between the slicing blade 20 and the movable supporting plate 40. The sliced pieces are discharged from the rear side of the slicer 1.

[0031]

The slicing blade 20 is extended diagonally to the width direction W of the frame 10. On the right and left sides of the slicing blade 20, holes, not shown, are respectively formed. The slicing blade 20 is fastened to the frame 10 by bolts B1 inserted through securing holes 10a formed on the surface of the frame 10 and the holes of the sliding blade 20. Additionally, the fastening method is not limited by a fastening method by the use of bolts, and any method may be used as long as the slicing blade 20 is secured onto the frame 10.

[0032]

The exchange blade 50 is attached between the slicing blade 20 and the movable supporting plate 40. The exchange blade 50 has its two ends supported by the frame 10. The exchange blade 50 is provided with a plurality of teeth formed in the longitudinal direction of the exchange blade 50 so that notches can be formed in the material to be sliced along the slicing direction S in

accordance with the gap of the respective teeth. The exchange blade 50 is secured by being pressed onto the frame 10 by bolts, not shown, that are inserted in bolt through holes 10c formed on outside surfaces 10b of the frame 10. By using the slicing blade 20 and the exchange blade 50 in combination, the material to be sliced can be sliced into various stick shapes or stripe shapes having large and small sizes.

[0033]

The movable supporting plate 40 and the slice width adjusting dial 60 are detachably attached to the frame 10 so that the respective members can be washed individually.

[0034]

The slicer 1 is provided with an anti-slipping member 70 attached to the tip thereof in the slicing direction S. The anti-slipping member 70 has an anti-slipping layer made of resin on its surface. The anti-slipping member 70 has its ridge-line cross-sectional shape in the slicing direction S formed in a manner so as to be curved into a convex shape, and when the user uses the slicer 1, the anti-slipping member 80 is diagonally pushed onto a chopping board or the like so that it is possible to slice the material to be sliced, without the slicer 1 being slipped.

[0035]

As shown in Figs. 2(a) to 2(c), the frame 10 is provided with a pair of right and left supporting arms 11 attached to the two ends in the width direction of the fixed supporting plate 30, a stay 12 that is passed between the right and left paired supporting arms 11, and a screw receiving hole 13 to be described later, which is formed virtually in the center of the stay 12 and can be engaged with a slicing width adjusting dial.

[0036]

The supporting arm 11 is provided with slits 11a that are formed on the inner surfaces and house two ends of the slicing blade 20. The slicing blade 20 is inserted from the slits 11a and disposed at a predetermined position.

[0037]

The supporting arm 11 is provided with a guide groove 11b formed with a concave shape on the inside surface. The guide groove 11b is formed so as to extend in a perpendicular direction H. The guide groove 11b is designed to be engaged with a guided pin 41 to be described later of the movable supporting plate 40. Additionally, the shape of the guide groove 11b may be set desirably. Since the lower portion in the perpendicular direction H of the guide groove 11b is formed so as to be opened. The movable supporting plate 40 can be detachably detached from the frame 10.

[0038]

The frame 10 is provided with a handle 14 that is held by the user. In the present embodiment, the handle 14 is integrally combined with the rear end of the supporting arm 11; however, the handle 14 may have a structure to be detachably attached and fastened by using bolts, as long as it can be secured to the supporting frame 11.

[0039]

The fixed supporting plate 30 is disposed between the paired supporting arms 11, and integrally attached to the supporting arm 11. On the surface 30a of the fixed supporting plate 30, 8 rows of groove portions 31 are engraved and formed side by side in the width direction W in an extended manner in the slicing direction S. By forming the groove portions 31 on the surface 30a of the fixed supporting plate 30, the fixed supporting plate 30 and the material to be sliced are made in contact with each other with a reduced area so that the material to be sliced can be moved smoothly. The depth dimension of the groove portions 31 may be desirably determined.

[0040]

As shown in Fig. 4(a) to 4(c), the movable supporting plate 40 is provided with pins 41 to be guided, formed on the rear side of the side faces 40a so as to protrude therefrom. The pins 41 to be guided are designed to be engaged with the guide grooves 11b of the supporting arm 11 so that the movable supporting plate 40 is raised and lowered in accordance with the shape of the guide

grooves 11b. For example, in the case when each guide groove 11b is formed from the lower side to the upper side in the perpendicular direction H, as well as diagonally from the rear side toward the front side in the slicing direction S, the movable supporting plate 40 is also diagonally raised and lowered in accordance with the shape of each of the guide grooves 11b. When the movable supporting plate 40 is raised, the guided pin 41 is engaged with the guide groove 11b so that wobbling and twisting of the movable supporting plate 40 are regulated.

10 [0041]

On the surface 40b of the movable supporting plate 40, 8 rows of groove portions 42 are engraved and formed side by side in the width direction W in an extended manner in the slicing direction S. By forming the groove portions 42, the contact area between the movable supporting plate 40 and the material to be sliced is reduced correspondingly so that the sliding resistance upon slicing the material to be sliced is reduced.

[0042]

The tip portion 43 of the movable supporting plate 40 is formed so as to be gradually narrowed from the vicinity of the center of the movable supporting plate 40 toward the front side in the slicing direction S, and at the vicinity of the tip of the movable supporting plate 40, an easily deflecting region R that is easily deflected downward by a pressing force that presses the material to be sliced downward upon slicing the material to be sliced. More specifically, the easily deflecting region R is formed at a tip portion 43 that is formed to have a width narrower than that of the rear end portion 44, with a reduced rigidity. That is, when, upon slicing the material to be sliced, a pressing force that presses the material to be sliced downward is exerted on the movable supporting plate 40, the tip portion 43 having a rigidity lower than that of the rear end portion 44 is easily deflected downward locally. In the present embodiment, the easily deflecting region R is formed over virtually a half portion of the length dimension of the movable supporting plate

40 from the tip of the movable supporting plate 40 toward the rear end.

[0043]

Moreover, on the rear surface 40c of the movable supporting plate 40, a first rib 45, which is disposed so as to include one portion of the easily deflecting region R and improves the rigidity of the easily deflecting region R, is formed. The first rib 45 is formed into a tapered shape that is gradually expanded in its diameter from the lower side in the perpendicular direction H upward so that with this structure, the movable supporting plate 40 is easily removed from a metal mold.

[0044]

In the present embodiment, the first rib 45 is formed into a hollow cylindrical shape; however, any shape may be adopted as long as the rigidity of the movable supporting plate 40 is increased, and for example, a solid cylindrical shape may be used, or an ellipsoidal shape or the like may be used.

[0045]

Supposing that the movable supporting plate 40 is divided into three equal portions, that is, a tip region r1, a center region r2, and a rear end region r3, successively from the tip side in the slicing direction S, the first rib 45 is formed in a manner so as to bridge over the tip region r1 and the center region r2. That is, the first rib 45 is formed within $2/3$ of the length dimension of the movable supporting plate from the tip toward the rear end in the slicing direction S of the movable supporting plate 40. Thus, the rigidity of the movable supporting plate 40 is increased so that the movable supporting plate 40 is suppressed from deflecting downward upon receipt of a pressing force exerted at the time of slicing the material to be sliced.

[0046]

On the rear surface 40c of the movable supporting plate 40, a second rib 46 disposed into a lattice pattern is formed. Thus, the rigidity of the movable supporting plate 40 is further increased.

[0047]

As shown in Fig. 5, the slice width adjusting dial 60 is provided with a main body unit 61 having a hollow cylindrical shape, a screw portion 62 formed on the outer peripheral surface of the main body unit 61 and a handle 63 formed on the base end of the main body unit 61.

[0048]

The inner diameter of the main body unit 61 is formed to have a larger diameter than the outer diameter of the first rib 45.

[0049]

The screw portion 62 is capable of being engaged with the screw receiving hole 13.

[0050]

The handle 63 is held by the user when the user rotates the slice width adjusting dial 60 to vertically raise or lower the movable supporting plate 40.

[0051]

Next, referring to Fig. 5, the following description will discuss the slice width adjusting mechanism 100. Additionally, the slice width is adjustable by raising or lowering the movable supporting plate 40 relative to the slicing blade 20, and the sequence of processes for lowering the movable supporting plate 40 is reversed to the sequence of processes for raising the movable supporting plate 40; therefore, the following description will discuss the function of the slice width adjusting mechanism 100 by exemplifying the process for raising the movable supporting plate 40.

[0052]

The slice width adjusting mechanism 100 is constituted by the screw receiving hole 13 of the frame 10, the first rib 45 of the movable supporting plate 40 and the slice width adjusting dial 60.

[0053]

Fig. 5 is a schematic view that explains the action of the slice width adjusting mechanism 100, with the screw receiving hole 12, the first rib 45 and the slice width adjusting dial 60

being omitted. Fig. 5(a) is a view showing a state before the slice width adjusting screw 60 is engaged with the screw receiving hole 13; Fig. 5(b) is a view showing a state in which the slice width adjusting screw 60 is engaged with the screw receiving hole 13; Fig. 5(c) is a view showing a state in which the slice width adjusting screw 60 is made to screw forward; and Fig. 5(d) is a view showing a state in which slice width adjusting screw 60 is made to further screw forward.

[0054]

- 10 First, as shown in Fig. 5(a), before the slice width adjusting screw 60 is engaged with the screw receiving hole 13, the first rib 45 of the movable supporting plate 40 is inserted through the screw receiving hole 13

[0055]

- 15 Next, as shown in Fig. 5(b), the slice width adjusting screw 60 is engaged with the screw receiving hole 13. At this time, the first rib 45 of the movable supporting plate 40 is housed in a nested state inside the main body unit 61 of the slice width adjusting screw 60.

- 20 [0056]

When the slice width adjusting screw 60 is rotated to screw forward, as shown in Fig. 5(c), the slice width adjusting screw 60 is raised relative to the screw receiving hole 13 so that the top surface 61a of the main body unit 61 is made in contact with the rear surface 40c of the movable supporting plate 40. At this time, the top surface 61a of the main body unit 61 comes into contact with the rear surface 40c of the movable supporting plate 40 between the first rib 45 and the second rib 46.

[0057]

- 30 When the slice width adjusting screw 60 further screws forward, as shown in Fig. 5(d), the slice width adjusting screw 60 raises the movable supporting plate 40. At this time, since the movable supporting plate 40 is supported by the entire surface of the top surface 61a of the slice width adjusting screw 60 so that the movable supporting plate 40 is raised in a stable manner.
- 35

[0058]

After the movable supporting plate 40 has been raised until the gap between the slicing blade 20 and the movable supporting plate 40 has reached a desired slice width, the rotation of the slice width adjusting screw 60 is stopped so that the movable supporting plate 40 is supported by the slice width adjusting screw 60 and also position-adjusted.

[0059]

That is, the movable supporting plate 40 is raised with its horizontal attitude being maintained by the slice width adjusting dial 60, and in accordance with the engaged state between the screw portion 62 and the screw receiving hole 13, the slide width adjusting dial 60 is position-determined at a desired position in the height direction H so that as shown in Figs. 6(a) to 6(d), since the movable supporting plate 40 is raised/lowered, with its horizontal attitude being maintained, depending on the position of the slice width adjusting dial 60, it is possible to slice the material to be sliced with a uniform thickness regardless of the size of the material to be sliced.

[0060]

Moreover, since the slice width adjusting dial 60 is made in contact with the rear surface 40c of the movable supporting plate 40, and supports it without any gap, cut chips and waste water are prevented from remaining between the slice width adjusting dial 60 and the movable supporting plate 40; therefore, the slicer 1 can be used sanitarily.

[0061]

Furthermore, since the first rib 45 is placed on the rear surface 40c of the movable supporting plate 40, the rigidity of the movable supporting plate 40 is increased so that it becomes possible to suppress the movable supporting plate 40 from being deflected downward by receiving a pressing force exerted when the movable supporting plate 40 slices the material to be sliced.

[0062]

In this manner, the slicer 1 in accordance with the present embodiment makes it possible to horizontally raise or lower the

movable supporting plate 40 while the deflection of the movable supporting plate 40 is being suppressed; thus, it becomes possible to slice the material to be sliced with a uniform thickness regardless of the size of the material to be sliced and since it is possible to suppress cut chips and waste water from remaining, it becomes possible to use the slicer sanitarily.
[0063]

Additionally, in the present invention, various modifications may be made within the scope without departing from the gist of the present invention, and those modifications are of course included within the scope of the present invention.

[Explanations of Reference Numerals]

[0064]

1	SLICER
15 10	FRAME
10a	ATTACHING hole
10b	OUTSIDE SURFACE
10c	BOLT COMMUNICATION HOLE
11	SUPPORTING ARM
20 11a	SLIT
11b	GUIDE GROOVE
12	STAY
13	SCREW RECEIVING HOLE
14	HANDLE
25 20	SLICING BLADE
30	FIXED SUPPORTING PLATE
30a	SURFACE (OF FIXED SUPPORTING PLATE)
31	GROOVE PORTION (OF FIXED SUPPORTING PLATE)
40	MOVABLE SUPPORTING PLATE
30 40a	SIDE FACE
40b	SURFACE (OF MOVABLE SUPPORTING PLATE)
40c	REAR SURFACE
41	GUIDED PIN
42	GROOVE PORTION (OF MOVABLE SUPPORTING PLATE)
35 43	Tip PORTION
44	REAR END PORTION

	45	FIRST RIB
	46	SECOND RIB
	50	EXCHANGE BLADE
	60	SLICE WIDTH ADJUSTING DIAL
5	61	MAIN BODY UNIT
	61a	TOP SURFACE
	63	HANDLE
	70	ANTI - SLIPPING MEMBER
	100	SLICE WIDTH ADJUSTING MECHANISM
10	B1	BOLT
	S	SLICING DIRECTION
	W	WIDTH DIRECTION
	H	VERTICAL DIRECTION
	R	EASILY DEFLECTING REGION
15	r1	TIP REGION
	r2	CENTER REGION
	r3	REAR END REGION

WHAT IS CLAIMED IS:

1. A slicer comprising: a frame; a slicing blade with two ends thereof being supported by the frame; a movable supporting plate that supports a material to be sliced when the material to be sliced is moved to slide toward the slicing blade; and a slice width adjusting mechanism capable of adjusting the slicing width of the material to be sliced by raising/ lowering the movable supporting plate relative to the slicing blade,
 - wherein the slice width adjusting mechanism comprises:
 - a slice width adjusting dial that has a cylinder shape having a screw portion formed on an outer peripheral surface, and is capable of supporting the rear surface of the movable supporting plate horizontally;
 - a screw receiving hole that is integrally formed with the frame and capable of being engaged with the screw portion; and
 - a rib that is formed in the movable supporting plate to stand on the rear surface of the movable supporting plate and fitted into the slice width adjusting dial,
 - wherein a top surface of the cylinder shape of the slice width adjusting dial, when moved forward, contacts the rear surface of the movable supporting plate,
 - moving the movable supporting plate,
 - forming a gap between the slicing blade and the movable supporting plate, and
 - a combination of the rib and the top surface increases rigidity of the movable supporting plate adjacent the slicing blade,
 - wherein the movable supporting plate is suppressed from moving downward upon receipt of a pressing force exerted during slicing so as to maintain the gap, providing consistent slices.
2. The slicer according to claim 1, wherein the movable supporting plate comprises: an easily deflecting region in which a front portion thereof in a slicing direction in which the material to be sliced is allowed to slide upon slicing the material to be sliced is formed with a narrowed width along the

slicing direction, with at least one portion of the slicing width adjusting dial being arranged to support the inside of the easily deflecting region.

5 3. The slicer according to claim 1 or 2, wherein the movable supporting plate comprises: an easily deflecting region in which a front portion thereof in a slicing direction in which the material to be sliced is allowed to slide upon slicing the material to be sliced is formed with a narrowed width along the
10 slicing direction, with at least one portion of the rib being disposed inside the easily deflecting region.

4. The slicer according to any one of claims 1 to 3, wherein the frame is provided with a guide groove formed into a concave
15 shape along a direction perpendicular to an inner peripheral surface, and the movable supporting plate has a guide pin that is formed on each of two sides in the width direction orthogonal to the slicing direction and is capable of being engaged with the guide groove.

20

5. The slicer according to claim 4, wherein the guide groove is formed on a rear surface in a direction perpendicular to the frame so as to be opened therefrom, with the guide pin of the movable supporting plate being attachably detached from the guide
25 groove through the opening of the guide groove.

6. The slicer according to any one of claims 1 to 5, wherein the movable supporting plate is divided into three equal portions, that is, a tip region, a center region, and a rear end region,
30 successively from a tip side to a rear end, wherein the rib is formed in a manner so as to bridge over the tip region and the center region.