

Description

The present invention relates to a refrigerant compressor, and more particularly, to a wobble plate type refrigerant compressor for use in an automotive air conditioning system.

As disclosed in Japanese Patent Application Publication No. 64-29678, a slant plate type compressor, such as a wobble plate type compressor, includes a balance weight ring of substantial mass disposed on the nose of the hub or "boss" of the slant plate, in order to balance the slant plate under dynamic operation conditions. The balance weight ring is held in place by means of a retaining ring.

Figure 5 shows a slant plate type compressor as disclosed in the Japanese application. Wobble plate 60 is mounted about boss 54 of slant plate 50 through bearings 61 and 62 so that slant plate 50 is rotatable with respect thereto. Boss 54 includes smaller diameter portion 54a at an axially rearward end (to the right in Figure 5) thereof, resulting in the formation of annular shoulder 541 forward of portion 54a. Wobble plate 60 includes annular projection 601 formed at an inner periphery of the axially rearward surface thereof and terminated so as to be same axial level of annular shoulder 541. Annular balance weight ring 500 is mounted about smaller diameter portion 54a in contact with shoulder 541 and annular projection 601. Balance weight ring 500 includes annular depression 501 formed at an inner periphery of the axially rearward surface, reducing the thickness of ring 500 at the inner periphery. Relatively thin plate portion 502 remains at the inner periphery of balance weight ring 500, forward of depression 501. Annular groove 55 is formed in the radially outer peripheral surface of smaller diameter portion 54a, and annular snap ring 56 is disposed therein. The radially outer portion of snap ring 56 extends exteriorly of groove 55 and contacts thin plate portion 502 of balance weight ring 500. Thin plate portion 502 of balance weight ring 500 is retained between snap ring 56 and annular shoulder 541. Therefore, balance weight ring 500 is affixed to boss 54 and prevents the axial movement of wobble plate 60. Consequently, an axially rearward end surface of annular projection 601 always contacts the axially forward surface of balance weight ring 500 during operation of the compressor causing friction between annular projection 601 and balance weight ring 500. Excessive rotational friction can occur between annular projection 601 and balance weight ring 500 during compressor operation causing considerable defects such as unusual wear or seizure between annular projection 601 and balance weight ring 500.

In view of this problem, some compressors in the commercial market are provided with a bearing disposed between the axially rearward end surface of annular projection 601 and the axially forward surface of balance weight ring 500. However, this increases

the number of component parts and complicates the assembly process.

Accordingly, it is an object of the present invention to provide a wobble plate type refrigerant compressor including an annular balance weight ring which can balance a slant plate and prevent the axial movement of a wobble plate under dynamic operating conditions while smoothly rotating on a wobble plate in a bearingless structure.

According to the present invention, a wobble plate compressor comprising a housing including a cylinder block with a plurality of peripherally disposed cylinders; a respective piston slidably reciprocable within each of the cylinders; a crank chamber enclosed within the housing at a location forward of the cylinders; a drive mechanism within the crank chamber and coupled to the pistons to reciprocate the pistons within the cylinders, the drive mechanism including a drive shaft rotatably supported in the housing and further including coupling means for coupling the drive shaft to the pistons such that the rotary motion of the drive shaft is converted into reciprocating motion of the pistons in the cylinders, the coupling means further including a slant plate disposed on the drive shaft and having a surface disposed at an angle inclined relatively to the drive shaft, the slant plate including a boss; an annular balance weight disposed about the boss and including a central thin plate region defining a recessed portion; means for retaining the thin plate region of the annular balance weight on the boss; the coupling means further comprising a wobble plate disposed about the boss, one end surface of the wobble plate rotatably sliding against the thin plate region of the annular balance weight; the pistons being linked to the wobble plate by connecting rods and the slant plate being rotatable with the drive shaft to enable the wobble plate to nutate to thereby reciprocate the pistons in the cylinders; is characterised in that the annular balance weight includes a plurality of holes formed at the periphery of the thin plate region thereof, adjacent to an annular side wall of the recessed portion and leading to the one end surface of the wobble plate.

In the accompanying drawings:-

Figure 1 is a vertical longitudinal sectional view of a wobble plate type refrigerant compressor in accordance with a first embodiment of the present invention.

Figure 2 is a bottom plan view of the balance weight ring shown in Figure 1.

Figure 3 is a sectional view of the balance weight ring taken along line A-A in Figure 2.

Figure 4 is a view similar to Figure 3 showing a second embodiment of the present invention.

Figure 5 is a vertical longitudinal sectional view of a wobble plate type refrigerant compressor in accordance with the prior art.

In all of Figures 1-4, identical reference numerals

are used to denote elements which are identical to the similarly numbered elements shown in the prior art Figure 5. Additionally, although compressor 10 is shown and is described with respect to Figures 1-4 as a wobble plate type refrigerant compressor with a variable displacement mechanism, the invention is not limited thereto and is applicable to a fixed capacity wobble plate type refrigerant compressor. Furthermore, in the following description, the left side of Figure 1 will be referred to as the front or forward side and the right side will be referred to as the rear side. The term "axial" refers to a direction parallel to the longitudinal axis of the drive shaft, and the term "radial" refers to the perpendicular direction. Of course, all of the reference directions are made for the sake of convenience of description and are not intended to limit the invention in any way.

With reference to Figure 1, the construction of wobble plate refrigerant compressor 10 in accordance with a first embodiment of the present invention is shown. Compressor 10 includes cylindrical housing assembly 20 including cylinder block 21, front end plate 23 disposed at one end of cylinder block 21, crank chamber 22 formed within cylinder block 21, and rear end plate 24 disposed at the opposite end of cylinder block 21. Front end plate 23 is mounted on the open forward end of cylinder block 21 by a plurality of bolts 101 to enclose crank chamber 22 therein. Rear end plate 24 is mounted on cylinder block 21 at its opposite end by a plurality of bolts 102. Valve plate 25 is located between rear end plate 24 and cylinder block 21. Opening 231 is centrally formed in front end plate 23. Drive shaft 26 is supported by bearing 30 disposed in opening 231. Central bore 210 extends through cylinder block 21 to a rearward end surface. The inner (rear) end portion of drive shaft 26 is rotatably supported by bearing 31 disposed within central bore 210 of cylinder block 21. Valve control mechanism 19 is disposed in bore 210 to the rear of drive shaft 26.

Cam rotor 40 is fixed on drive shaft 26 by pin member 261, and rotates with shaft 26. Thrust needle bearing 32 is disposed between the axial inner (rear) end surface of front end plate 23 and the adjacent forward axial end surface of cam rotor 40. Cam rotor 40 includes arm 41 having pin member 42 extending therefrom. Slant plate 50 is disposed about drive shaft 26 and includes opening 51 through which drive shaft 26 passes. Slant plate 50 is disposed adjacent cam rotor 40. Slant plate 50 includes arm 51 having slot 52 and boss 54. Cam rotor 40 and slant plate 50 are connected by pin member 42, which is inserted in slot 52 to create a hinged joint. Pin member 42 is slidable within slot 52 to allow adjustment of the angular position of slant plate 50 with respect to the longitudinal axis of drive shaft 26.

Wobble plate 60 is mounted about boss 54 of slant plate 50 through bearings 61 and 62 so that slant

plate 50 is rotatable with respect thereto. Rotational motion of slant plate 50 causes nutational motion of wobble plate 60. Fork shaped slider 61 is attached to the outer peripheral end of wobble plate 60 and is slidably mounted on sliding rail 64 held between front end plate 21 and cylinder block 21. Fork shaped slider 63 prevents rotation of wobble plate 60 and wobble plate 60 reciprocates along rail 64 when cam rotor 40 and slant plate 50 rotate. Cylinder block 21 includes a plurality of peripherally located cylinder chambers 70 in which pistons 71 reciprocate. Each piston 71 is connected to wobble plate 60 at a peripheral location by a corresponding connecting rod 72. Nutational motion of wobble plate 60 causes pistons 71 to reciprocate in cylinders 70 to compress refrigerant therein.

Rear end plate 24 includes peripherally located annular suction chamber 241 and centrally located discharge chamber 251. Valve plate 25 is located between cylinder block 21 and rear end plate 24 and includes a plurality of valved suction ports 242 linking suction chamber 241 with respective cylinders 70. Valve plate 25 also includes a plurality of valved discharge ports 252 linking discharge chamber 251 with respective cylinders 70. Suction ports 242 and discharge ports 252 are provided with suitable reed valves as described in U.S.-A-4,011,029.

Suction chamber 241 includes inlet portion 241a which is connected to an evaporator of the external cooling circuit (not shown). Discharge chamber 251 is provided with outlet portion 251a connected to a condenser of the cooling circuit (not shown). Gaskets 27 and 28 are located between cylinder block 21 and the inner surface of valve plate 25, and the outer surface of valve plate 25 and rear end plate 24, respectively, to seal the mating surfaces of cylinder block 21, valve plate 25 and rear end plate 24.

Communication path 400 links crank chamber 22 and suction chamber 241 and includes central bore 210 and passageway 150. Valve control mechanism 19 controls the opening and closing of communication path 400 in order to vary the capacity of the compressor, as disclosed in Japanese Patent Application Publication No. 01-142,276.

During operation of compressor 10, drive shaft 26 is rotated by the engine of the vehicle through electromagnetic clutch 300. Cam rotor 40 is rotated with drive shaft 26, rotating slant plate 50 as well, causing wobble plate 60 to nutate. Nutational motion of wobble plate 60 reciprocates pistons 71 in their respective cylinders 70. As pistons 71 are reciprocated, refrigerant gas which is introduced into suction chamber 241 through inlet portion 241a, flows into each cylinder 70 through suction ports 242 and is compressed therein. The compressed refrigerant gas is discharged into discharge chamber 251 from each cylinder 70 through discharge ports 252, and therefrom into the cooling circuit through outlet portion 251a.

The capacity of compressor 10 may be adjusted

to maintain a constant pressure in suction chamber 241 in response to a change in the heat load of the evaporator, or a change in the rotating speed of the compressor. The capacity of the compressor is adjusted by changing the angle of slant plate 50 with respect to a plane perpendicular to the axis of drive shaft 26. This angle is dependent upon the crank chamber pressure. An increase in crank chamber pressure decreases the slant angle of slant plate 50 and wobble plate 60, decreasing the capacity of the compressor. A decrease in the crank chamber pressure increases the angle of slant plate 50 and wobble plate 60 and thus increases the capacity of the compressor. In the compressor shown in Figure 1, valve control mechanism 19 acts in response to the crank chamber pressure, such that the acting point is modified according to the discharge chamber pressure, to control the link between the crank and suction chambers, to adjust the crank chamber pressure and thereby change the slant angle of slant plate 50 and vary the operating capacity of the compressor. Of course other types of valve control mechanisms, or none at all may be used according to the present invention.

Compressor 10 further includes annular groove 55 formed in the radially outer surface of smaller diameter portion 54a of boss 54. Boss 54 includes annular shoulder 541 forward of smaller diameter portion 54a. Balance weight ring 500 includes annular depression 501 formed at a rearward, radially inner peripheral region, resulting in the thin plate portion 502 formed axially forward of depression 501. Thin plate portion 502 fits on annular shoulder 541 of boss 54. Annular member 80 made of soft metal, for example, untempered iron, disposed on thin plate portion 502 is caulked into groove 55 so as to retain balance weight ring 500 on boss 54 of slant plate 50 by sandwiching thin plate portion 502 against annular shoulder 541. Annular projection 601 is formed at an inner periphery of the axially rearward surface of wobble plate 60 and terminated to the radially outermost of the axially forward surface of thin plate portion 502. Consequently, an axially rearward end surface of annular projection 601 always contacts the radially outermost of the axially forward surface of thin plate portion 502 during operation of the compressor. Thereby, while axial movement of wobble plate 60 is prevented during compressor operation, rotational friction is created between annular projection 601 of wobble plate 60 and thin plate portion 502 of balance weight ring 500.

With reference to Figures 2 and 3 additionally, balance weight ring 500 includes annular depression 501 of which annular side wall 501a is radially inwardly slanted. Thin plate portion 502 is provided with a plurality of axial holes 503 aligned with the periphery of the forward end of side wall 501a with an equiangular interval so as to face the rearward end surface of annular projection 601 of wobble plate 60.

With reference to Figure 1 again, when the compressor operates, the refrigerant mixed with the mists of lubricating oil (hereinafter, this mixture is represented by "the refrigerant" for explanation only) is introduced into cylinders 70 from suction chamber 241 by the forward motion of pistons 71 and is compressed by the rearward motion of pistons 71. In this situation, a part of the refrigerant is blown into crank chamber 22 from cylinders 70 through the gap between an outer peripheral surface of pistons 71 and an inner peripheral surface of cylinders 70. Then, a part of the refrigerant in crank chamber 22 flows back to suction chamber 241 through communication path 400.

The separation of lubricating oil from the refrigerant which is adjacent to balance weight ring 500 is enhanced by the collision of the refrigerant with balance weight ring 500 due to the rotation of balance weight ring 500. Consequently, the separated oil sticks to the whole external surface of balance weight ring 500, and then moves radially outward by the centrifugal force generated by the rotation of balance weight ring 500.

In particular, the separated oil sticking to the bottom surface of annular depression 501 of balance weight ring 500 moves radially outward and is gathered at the forward end of side wall 501a of annular depression 501. The separated oil sticking to annular side wall 501a moves forward along a slanted surface of side wall 501a due to the centrifugal force and gathers at the forward end of side wall 501a. The lubricating oil gathered at the forward end of side wall 501a flows into the friction surface between the rearward end surface of annular projection 601 of wobble plate 60 and the forward surface of thin plate portion 502 of balance weight ring 500 through axial holes 503. Accordingly, unusual wear or seizure between annular projection 601 and thin plate portion 502 is prevented without disposing a bearing between the axially rearward end surface of annular projection 601 and the axially forward surface of balance weight ring 500, even under extreme conditions.

Since balance weight ring 500 is located near central bore 210, the refrigerant adjacent to balance weight ring 500 is always replaced with the fresh refrigerant which is returning to suction chamber 241 from crank chamber 22 through communicating path 400. Therefore, lubricating oil is sufficiently supplied to the friction surface between the rearward end surface of annular projection 601 of wobble plate 60 and the forward surface of thin plate portion 502 of balance weight ring 500.

Figure 4 shows a second embodiment of the present invention. In the second embodiment, thin plate portion 502 of balance weight ring 500 is provided with a plurality of inclined holes 503' aligned with the periphery of the forward end of side wall 501a at an equiangular interval. The inclined angle of holes 503' corresponds to the slant angle of annular side wall

501a, that is, the line extending forward from the forward end of side wall 501a corresponds to the radially outermost line of holes 503'. The lubricating oil gathered at the forward end of side wall 501a is effectively conducted into the friction surface between the rearward end surface of annular projection 601 of wobble plate 60 and the forward surface of thin plate portion 502 of balance weight ring 500 through inclined holes 503' due to centrifugal force.

Claims

1. A wobble plate compressor comprising a housing (20) including a cylinder block (21) with a plurality of peripherally disposed cylinders (70); a respective piston (71) slidably reciprocable within each of the cylinders; a crank chamber (22) enclosed within the housing at a location forward of the cylinders; a drive mechanism within the crank chamber and coupled to the pistons to reciprocate the pistons within the cylinders, the drive mechanism including a drive shaft (26) rotatably supported in the housing and further including coupling means for coupling the drive shaft to the pistons such that the rotary motion of the drive shaft is converted into reciprocating motion of the pistons in the cylinders, the coupling means further including a slant plate (50) disposed on the drive shaft and having a surface disposed at an angle inclined relatively to the drive shaft, the slant plate including a boss (54); an annular balance weight (500) disposed about the boss and including a central thin plate region (502) defining a recessed portion; means (80) for retaining the thin plate region of the annular balance weight on the boss; the coupling means further comprising a wobble plate (60) disposed about the boss, one end surface of the wobble plate rotatably sliding against the thin plate region of the annular balance weight; the pistons being linked to the wobble plate by connecting rods (72) and the slant plate being rotatable with the drive shaft to enable the wobble plate to nutate to thereby reciprocate the pistons in the cylinders;

characterised in that the annular balance weight (500) includes a plurality of holes (503) formed at the periphery of the thin plate region thereof, adjacent to an annular side wall (501a) of the recessed portion and leading to the one end surface of the wobble plate.

2. A compressor according to claim 1, wherein the annular side wall (501a) of the recessed portion is tapered to funnel refrigerant to the holes.
3. A compressor according to claim 1 or claim 2, wherein each of the holes has a central axis par-

allel to the axis of the annular balance weight.

4. A compressor according to claim 2, wherein each of the holes has a central axis inclined with respect to an axis of the annular balance weight substantially parallel to the adjacent part of the side wall.
5. A compressor according to any one of the preceding claims, wherein there at least three of the holes.
6. A compressor according to any one of the preceding claims, wherein the holes are located at equi-angular intervals.

Patentansprüche

1. Taumelscheibenkompressor mit einem Gehäuse (20) mit einem Zylinderblock (21) mit einer Mehrzahl von umfangsmäßig vorgesehenen Zylindern (70); einem entsprechenden gleitend in jedem der Zylinder hin- und herbewegbaren Kolben (71); einer in dem Gehäuse an einer Stelle vor den Zylindern eingeschlossenen Kurbelkammer (22); einem Antriebsmechanismus innerhalb der Kurbelkammer, der mit den Kolben zum Hin- und Herbewegen der Kolben innerhalb der Zylinder verbunden ist, wobei der Antriebsmechanismus eine drehbar in dem Gehäuse gelagerte Antriebswelle (26) und weiter ein Verbindungsmittel enthält zum Verbinden der Antriebswelle mit den Kolben derart, daß die Drehbewegung der Antriebswelle in eine Hin- und Herbewegung der Kolben in den Zylindern umgewandelt wird, das Verbindungsmittel weiter eine auf der Antriebswelle vorgesehene Schiefscheibe (50) enthält, die eine in einem Winkel relativ zu der Antriebswelle geeignete Oberfläche aufweist, und die Schiefscheibe einen Vorsprung (54) enthält; einem um den Vorsprung vorgesehenen ringförmigen Ausgleichsgewicht (500), das einen einen ausgeschnittenen beschnitt definierenden zentralen dünnen Plattenabschnitt (502) enthält; Mittel (80) zum Zurückhalten des dünnen Plattenabschnittes des ringförmigen Ausgleichsgewichtes auf den Vorsprung; wobei das Verbindungsmittel weiter eine um den Vorsprung vorgesehene Taumelscheibe (60) aufweist, deren eine Endoberfläche drehbar gegen den dünnen Plattenabschnitt des ringförmigen Ausgleichsgewichtes gleitet; wobei die Kolben mit Taumelscheibe durch Verbindungsstangen (72) verbunden sind und die Schiefscheibe drehbar mit der Antriebswelle gebildet ist, um der Taumelscheibe das Nutieren zu ermöglichen, wodurch die Kolben in den Zylindern hin- und herbewegt werden;



501a, that is, the line extending forward from the forward end of side wall 501a corresponds to the radially outermost line of holes 503'. The lubricating oil gathered at the forward end of side wall 501a is effectively conducted into the friction surface between the rearward end surface of annular projection 601 of wobble plate 60 and the forward surface of thin plate portion 502 of balance weight ring 500 through inclined holes 503' due to centrifugal force.

Claims

1. A wobble plate compressor comprising a housing (20) including a cylinder block (21) with a plurality of peripherally disposed cylinders (70); a respective piston (71) slidably reciprocable within each of the cylinders; a crank chamber (22) enclosed within the housing at a location forward of the cylinders; a drive mechanism within the crank chamber and coupled to the pistons to reciprocate the pistons within the cylinders, the drive mechanism including a drive shaft (26) rotatably supported in the housing and further including coupling means for coupling the drive shaft to the pistons such that the rotary motion of the drive shaft is converted into reciprocating motion of the pistons in the cylinders, the coupling means further including a slant plate (50) disposed on the drive shaft and having a surface disposed at an angle inclined relatively to the drive shaft, the slant plate including a boss (54); an annular balance weight (500) disposed about the boss and including a central thin plate region (502) defining a recessed portion; means (80) for retaining the thin plate region of the annular balance weight on the boss; the coupling means further comprising a wobble plate (60) disposed about the boss, one end surface of the wobble plate rotatably sliding against the thin plate region of the annular balance weight; the pistons being linked to the wobble plate by connecting rods (72) and the slant plate being rotatable with the drive shaft to enable the wobble plate to nutate to thereby reciprocate the pistons in the cylinders;

characterised in that the annular balance weight (500) includes a plurality of holes (503) formed at the periphery of the thin plate region thereof, adjacent to an annular side wall (501a) of the recessed portion and leading to the one end surface of the wobble plate.

2. A compressor according to claim 1, wherein the annular side wall (501a) of the recessed portion is tapered to funnel refrigerant to the holes.
3. A compressor according to claim 1 or claim 2, wherein each of the holes has a central axis par-

allel to the axis of the annular balance weight.

4. A compressor according to claim 2, wherein each of the holes has a central axis inclined with respect to an axis of the annular balance weight substantially parallel to the adjacent part of the side wall.
5. A compressor according to any one of the preceding claims, wherein there at least three of the holes.
6. A compressor according to any one of the preceding claims, wherein the holes are located at equi-angular intervals.

Patentansprüche

1. Taumelscheibenkompressor mit einem Gehäuse (20) mit einem Zylinderblock (21) mit einer Mehrzahl von umfangsmäßig vorgesehenen Zylindern (70); einem entsprechenden gleitend in jedem der Zylinder hin- und herbewegbaren Kolben (71); einer in dem Gehäuse an einer Stelle vor den Zylindern eingeschlossenen Kurbelkammer (22); einem Antriebsmechanismus innerhalb der Kurbelkammer, der mit den Kolben zum Hin- und Herbewegen der Kolben innerhalb der Zylinder verbunden ist, wobei der Antriebsmechanismus eine drehbar in dem Gehäuse gelagerte Antriebswelle (26) und weiter ein Verbindungsmittel enthält zum Verbinden der Antriebswelle mit den Kolben derart, daß die Drehbewegung der Antriebswelle in eine Hin- und Herbewegung der Kolben in den Zylindern umgewandelt wird, das Verbindungsmittel weiter eine auf der Antriebswelle vorgesehene Schiefscheibe (50) enthält, die eine in einem Winkel relativ zu der Antriebswelle geneigte Oberfläche aufweist, und die Schiefscheibe einen Vorsprung (54) enthält; einem um den Vorsprung vorgesehenen ringförmigen Ausgleichsgewicht (500), das einen einen ausgeschnittenen beschnitt definierenden zentralen dünnen Plattenabschnitt (502) enthält; Mittel (80) zum Zurückhalten des dünnen Plattenabschnittes des ringförmigen Ausgleichsgewichtes auf den Vorsprung; wobei das Verbindungsmittel weiter eine um den Vorsprung vorgesehene Taumelscheibe (60) aufweist, deren eine Endoberfläche drehbar gegen den dünnen Plattenabschnitt des ringförmigen Ausgleichsgewichtes gleitet; wobei die Kolben mit Taumelscheibe durch Verbindungsstangen (72) verbunden sind und die Schiefscheibe drehbar mit der Antriebswelle gebildet ist, um der Taumelscheibe das Nutieren zu ermöglichen, wodurch die Kolben in den Zylindern hin- und herbewegt werden;



dadurch gekennzeichnet, daß das ringförmige Ausgleichsgewicht (500) eine Mehrzahl von an dem Umfang dessen dünnen Plattenabschnittes gebildete Löcher (503) benachbart zu einer ringförmigen Seitenwand (501a) des ausgeschnittenen Abschnittes aufweist, die zu einer Endoberfläche der Taumelscheibe führen.

2. Kompressor nach Anspruch 1, bei dem die ringförmige Seitenwand (501a) des ausgeschnittenen Abschnittes angeschragt ist zum Trichtern von Kühlmittel zu den Löchern.
3. Kompressor nach Anspruch 1 oder Anspruch 2, bei dem jedes der Löcher eine Mittenachse zu der Achse des ringförmigen Ausgleichsgewichtes aufweist.
4. Kompressor nach Anspruch 2, bei dem jedes der Löcher eine Mittenachse aufweist, die geneigt in Bezug auf eine Achse des ringförmigen Ausgleichsgewichtes ist, die im wesentlichen parallel zu dem benachbarten Teil der Seitenwand ist.
5. Kompressor nach einem beliebigen der vorhergehenden Ansprüche, bei dem es mindestens drei der Löcher gibt.
6. Kompressor nach einem beliebigen der vorhergehenden Ansprüche, bei dem die Löcher in gleichen Winkelabständen angeordnet sind.

Revendications

1. Compresseur à plateau oscillant comprenant un carter (20) comportant un bloc de cylindres (21) muni d'un certain nombre de cylindres (70) disposés périphériquement ; un piston respectif (71) glissant dans un mouvement de va-et-vient à l'intérieur de chacun des cylindres ; une chambre de manivelle (22) enfermée à l'intérieur du carter en un endroit situé en avant des cylindres ; un mécanisme d'entraînement placé à l'intérieur de la chambre de manivelle et couplé aux pistons pour faire aller et venir ces pistons à l'intérieur des cylindres, le mécanisme d'entraînement comprenant un arbre d'entraînement (26) monté en rotation dans le carter et comprenant en outre des moyens d'accouplement destinés à coupler l'arbre d'entraînement aux pistons de façon que le mouvement de rotation de l'arbre d'entraînement soit transformé en un mouvement de va-et-vient des pistons dans les cylindres, les moyens d'accouplement comprenant en outre un plateau en biais (50) monté sur l'arbre d'entraînement et comportant une surface disposée sous un certain angle d'inclinaison par rapport à l'arbre d'en-

traînement, ce plateau en biais comprenant un bossage (54) ; un contrepoids annulaire (500) disposé autour du bossage et comprenant une zone de plaque mince centrale (502) définissant une partie en creux ; des moyens (80) destinés à retenir la zone de plaque mince du contrepoids annulaire sur le bossage ; les moyens d'accouplement comprenant en outre un plateau oscillant (60) disposé autour du bossage, une surface d'extrémité du plateau oscillant glissant en rotation contre la zone de plaque mince du contrepoids annulaire ; les pistons étant reliés au plateau oscillant par des bielles (72) et le plateau en biais pouvant tourner solidairement de l'arbre d'entraînement pour permettre au plateau oscillant d'effectuer un mouvement de nutation de manière à faire aller et venir les pistons dans les cylindres ;

compresseur caractérisé en ce que le contrepoids annulaire (500) comprend un certain nombre de trous (503) formés à la périphérie de sa zone de plaque mince au voisinage d'une paroi latérale annulaire (501a) de la partie en creux, et conduisant à la surface d'extrémité ci-dessus du plateau oscillant.

2. Compresseur selon la revendication 1, caractérisé en ce que la paroi latérale annulaire (501a) de la partie en creux est conique pour canaliser le réfrigérant vers les trous.
3. Compresseur selon l'une quelconque des revendications 1 et 2, caractérisé en ce que chacun des trous comporte un axe central parallèle à l'axe du contrepoids annulaire.
4. Compresseur selon la revendication 2, caractérisé en ce que chacun des trous comporte un axe central incliné par rapport à un axe du contrepoids annulaire essentiellement parallèle à la partie adjacente de la paroi latérale.
5. Compresseur selon l'une quelconque des revendications précédentes, caractérisé en ce qu'il comporte au moins trois trous.
6. Compresseur selon l'une quelconque des revendications précédentes, caractérisé en ce que les trous sont placés à des intervalles angulaires égaux.