

METHOD AND APPARATUS FOR COMPRESSING A SEQUENCE OF INFORMATION-BEARING FRAMES HAVING AT LEAST TWO MEDIA COMPONENTS

TECHNICAL FIELD

5 This invention relates generally to a method of compressing a sequence of information-bearing frames, and more particularly to a method of compressing a sequence of information-bearing frames having at least two media components such as a video program.

BACKGROUND

10 Multimedia sources of information such as video programs are one form of multimedia data composed of at least two distinct media components. For example, a video program is composed of a full motion video component and an audio component. A number of methods are known for reducing the large storage and transmission requirements of the video
15 component of video programs. For example, certain compression methods (such as JPEG) take advantage of spatial redundancies that exist within an individual video frame to reduce the number of bytes required to represent the frame. Additional compression may be achieved by taking advantage of the temporal redundancy that exists between consecutive frames, which is the basis
20 for known compression methods such as MPEG. These known compression methods generate a fixed number of frames per unit time to preserve the motion information contained in the video program.

 In contrast to the compression methods mentioned above, other methods compress video programs by selecting certain frames from the entire
25 sequence of frames to serve as representative frames. For example, a single frame may be used to represent the visual information contained in any given

scene of the video program. A scene may be defined as a segment of the video program over which the visual contents do not change significantly. Thus, a frame selected from the scene may be used to represent the entire scene without losing a substantially large amount of information. A series of
5 such representative frames from all the scenes in the video program provides a reasonably accurate representation of the entire video program with an acceptable degree of information loss. These compression methods in effect perform a content-based sampling of the video program. Unlike the temporal or spatial compression methods discussed above in which the frames are
10 uniformly spaced in time, a content-based sampling method performs a temporally non-uniform sampling of the video program to generate a set of representative frames. For example, a single representative frame may represent a long segment of the video program (e.g., a long scene in which a person makes a speech without substantially changing position for an
15 extended period) or a very short segment of the video program (e.g., a scene displayed in the video program for only a few seconds).

Methods for automatically generating representative images from video programs are known. These methods may detect the boundaries between consecutive shots and may additionally detect scene changes that
20 occur within the individual shots. An example of a method for locating abrupt and gradual transitions between shots is disclosed in Patent Appl. Serial No. 08/171,136, filed December 21, 1993, and entitled "Method and Apparatus for Detecting Abrupt and Gradual Scene Changes In Image Sequences," the contents of which are hereby incorporated by reference. A
25 method for detecting scene changes that occur within individual shots has been disclosed in Patent Appl. Serial No. 08/191,234, filed February 4, 1994,

entitled "Camera-Motion Induced Scene Change Detection Method and System," the contents of which are also hereby incorporated by reference.

Content-based sampling methods are typically employed for indexing purposes because the representative frames generated by such methods can efficiently convey the visual information contained in a video program. However, these methods fail to convey all the useful information contained in a multimedia format such as video because they only compress one media component, namely, in the case of video, the video component, while excluding the remaining media component (e.g., audio) or components.

10 SUMMARY

The present invention provides an apparatus and method for compressing a sequence of frames having at least first and second information-bearing media components. The sequence of frames may constitute, for example, a video program in which the first information-bearing component is a video component and the second information-bearing component is a closed-caption component. In accordance with the invention, a plurality of representative frames are selected from among the sequence of frames. The representative frames represent information contained in the first information-bearing media component. A correspondence is then formed between each of the representative frames and one of a plurality of segments of the second information-bearing media component. The representative frames, the plurality of segments of the second information-bearing media component and the correspondence between them are recorded for subsequent retrieval.

25 In one embodiment of the invention, the representative frames are selected by sampling the sequence of frames in a content-based manner. For example, if the first information-bearing media component is a video

component composed of a plurality of scenes, a representative frame may be selected from each scene. Additionally, if the second information-bearing media component is a closed-caption component, a printed rendition of the representative frames and the closed-caption component may be provided.

5 The printed rendition constitutes a pictorial transcript in which each representative frame is printed with a caption containing the closed-caption text associated therewith. One advantage provided by this embodiment of the invention is that while the information embodied in the original format (e.g., a video program) typically requires additional equipment (e.g., a video
10 cassette recorder and monitor) to be understood, the information embodied in the printed pictorial transcript is self-contained and can be understood directly without requiring additional processing or equipment.

In an alternative embodiment of the invention, a method is provided for displaying a compressed rendition of a sequence of frames having at
15 least first and second information-bearing media components. In accordance with the method, a plurality of representative frames are received which represent information contained in the first information-bearing media component. Additionally, a signal is received that has information that forms a correspondence between each of the representative frames and a segment of the second information-
20 bearing media component. Finally, the representative frames and the segment of the second information-bearing media component are displayed in a manner determined by the correspondence therebetween.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of one example of an apparatus for
25 compressing multimedia data in accordance with the present invention.

FIG. 2 shows an example of a correspondence table for locating representative frames and closed-caption components of a closed-caption video program.

FIG. 3 is an example of one page of a printed pictorial transcript generated from a television news program in accordance with method of the present invention.

DETAILED DESCRIPTION

Certain video programs such as television broadcasts often include a closed-caption component as part of each frame of video. When decoded, the closed-caption component of each frame contains up to two alphanumeric characters or control characters. The sequence of these characters form words and sentences over several or more frames. This text is typically recovered by a dedicated closed-caption decoder and superimposed on the frames displayed on a video screen. The text contains dialog or other information that corresponds to the audio portion of the program. Details regarding the addition of closed-caption information to a video source are disclosed, for example, in Report No. E-7709-C by the Public Broadcasting Service entitled "Television Captioning For the Deaf: Signal and Display Specifications," by John Lentz et al., May, 1980.

The present invention will be described in terms of a method for compressing a closed-caption video program in which a representative frame from each scene in the program is combined with the text generated by decoding the closed-caption component of the video program. As used herein the term video is not limited to any particular video standard but rather refers to any sequence of frames having at least two information-bearing media components, one of which is a visual information component. The frames may be recorded in any format, including film, conventional video, or various

electronic forms such as a computer memory. The term frame refers to the atomic elements of recorded information for all the media components employed in connection with a particular format.

While the present invention will be described in terms of a
5 method of compressing a video program having a closed-caption component, it will be understood by one of ordinary skill in the art that this method is equally applicable to any source of multimedia information having at least two media components. For example, the method may be employed to compress a video program having a video component and an audio
10 component. The audio component may include speech and other auditory information such as music, for example. If desired, the audio component may undergo a speech-to-text conversion process so that a pictorial transcript as described below may be generated.

FIG. 1 shows a block diagram of an apparatus 2 for compressing
15 multimedia data in accordance with the present invention. For purposes of illustration the apparatus 2 will be described as receiving a video input from a video input source 1 such as a video tuner connected to an antenna or cable television, a video-cassette recorder, or any other source capable of providing video and closed-caption information. The apparatus 2 is composed of a
20 scene change detector 4, a closed-caption decoder 5 and a digital computer 8. The scene change detector 4 operates on the video signal received from the input source 1 to generate a representative frame for each scene in the video signal. Scene change detectors that select representative frames are known and examples of such are provided in the above-mentioned references that are
25 incorporated by reference. The representative frames each contain visual information representing the visual information content of an entire scene. The scene change detector 4 may include an image digitizer for digitizing the

input if an analog input source is employed rather than a digital input source. The representative frames extracted by the scene change detector 4 are transmitted to the digital computer 8. The closed-caption decoder 5, which also receives the video signal from the input source 1, extracts the closed-caption characters from the video signal and transmits them to the digital computer 8 in decoded form. The digital computer 8 stores the representative frames and the closed-caption information in a retrievable format in, for example, the main memory 9 or the hard disk 10. As described in more detail below, the digital computer 8 also establishes a correspondence between each representative frame and a segment of the closed-caption information by constructing a correspondence table. The representative frames and closed-caption component may be subsequently retrieved and directed to a printer 12 or a display 13, or alternatively, transmitted over a communications network 14.

A content-based compression method that generates a single representative frame for each of the N scenes in a video program will retain N representative frames I_1 through I_N . Examples of such compression methods are disclosed in the above-mentioned references that are incorporated by reference. Since each representative frame represents the visual information contained in a single scene, each representative frame has associated with it a time interval equal to the length of the scene from which the frame is selected. For example, the time interval associated with representative frame I_i begins with the detection of the i th scene boundary and ends one frame prior to the detection of the $(i+1)$ th scene boundary. The series of consecutive frames constituting the scene from which the representative frame I_i is selected is denoted VS_i . Accordingly, the set of N representative frames I_1 through I_N divide the video program into N non-overlapping visual segments VS_1

through VS_N and each representative frame I_i is associated with visual segment VS_i .

Since each frame of the video program is associated with a portion of the closed-caption component, each of the series of frames
 5 constituting visual segment VS_i is associated with a closed-caption segment denoted TS_i . Accordingly, when the method of this invention divides the video program into N visual segments VS_1 through VS_N each being characterized by a single representative frame, it will also divide the closed-caption component into N segments. The closed-caption component may be
 10 divided into segments, for example, by time-stamping the closed-caption component as it is received by the computer 8 each time a new visual segment is detected by the scene change detector 4. The N closed-caption segments TS_i correspond in a one-to one-manner with the N visual segments VS_i . This correspondence between the representative frames of each visual segment VS_i
 15 and the N closed-caption segments TS_i may be established by a correspondence table such as shown in FIG. 2.

The correspondence table 21 employs a frame memory 22 and a text memory 23 which are located in the digital computer 8. The frame memory 22 stores the representative frames I_1 through I_N produced by the
 20 scene change detector 4 and the text memory 23 stores the closed-caption segments TS_1 through TS_N . The correspondence table 21 has at least two columns and N rows for the N representative frames. The first column 26 of the table contains information that points to frames I_1 through I_N . This information may be in the form of a pointer (denoted in FIG. 2 as frame
 25 pointers PI_1 through PI_N) that points to the location of the representative frames stored in memory 22. For example, pointer PI_1 points to representative frame I_1 located in row 1. This information is sufficient to

determine the beginning and end locations of the frames in the memory 22 if the frames are of fixed size. In the event the frames are of variable size, the end of frame I_i can be determined with pointer $PI_{(i+1)}$, assuming the frames are stored in sequential order in consecutive memory locations. The second

5 column 27 of the correspondence table contains information that points to the closed-caption segments TS_1 through TS_N . Similar to the first column of the table, information pertaining to frame I_i is contained in row i of the second column 27. This information also may be in the form of a pointer, referred to as closed-caption pointer PT_i , which points to the location of closed-caption

10 segment TS_i . The end of the closed-caption segment TS_i associated with frame I_i can be located with pointer $PT_{(i+1)}$. FIG. 2 shows two additional pointers that may be employed, an image end pointer 26, and text end pointer 27, which indicate the end of the N th representative frame and N th closed-caption segment, respectively.

15 The organization of the correspondence table is not limited to the example described above. One of ordinary skill in the art will recognize that the correspondence table may be implemented in any desired manner to ensure that each representative frame is properly correlated with its associated closed-caption segment so that both components are readily

20 retrievable. For example, the correspondence table may contain additional columns for storing information such as the size of the representative frames and the closed-caption segments, the frame numbers that indicate the beginning and end of each visual segment, the length of each scene, or the number of characters in the closed-caption segments. Alternatively, each

25 representative frame and the closed-caption segments associated therewith may be stored as individual files. In this arrangement the entries in the

columns of the correspondence table will identify the location or name of each file.

Once the representative frames and closed-caption segments constituting the compressed video program have been extracted from the original video program and the correspondence table prepared, the data may
5 be recorded in any convenient manner for subsequent retrieval. Thereafter the data may be printed, displayed or transmitted in any desired format. For example, the data may be printed, displayed, or transmitted in the form of a pictorial transcript in which a series of representative frames are each
10 provided with captions of the closed-caption text. An example of a pictorial transcript format is shown in FIG. 3 for a portion of television news program. The transcript may be printed with a commercial text processing package that is capable of conveniently incorporating pictures into text.

Prior to printing the pictorial transcript, it may be necessary to
15 remove non-printable control characters contained in the closed-caption signal which are used to control display functions. These characters control such features as the color of the displayed characters, the font, and the location of the text line on the display screen, for example. In addition to being non-printable, the control characters may adversely effect the proper division of
20 the closed-caption component based on individual scenes in the manner described above. In particular, the control characters may cause the text contained in the closed-caption component to be divided in the middle of a sentence. This improper division of the closed-caption component may occur for other reasons as well, including improper synchronization between the
25 video component and the closed-caption component, for example. Improper synchronization may occur because of a delay in the detection of a scene boundary or a delay in transmitting the closed-caption component to the

digital computer. Regardless of the reason for the improper division, it may be desirable to process the raw text to remove the control characters and shift the boundary between adjacent closed-caption segments so that word fragments are merged into complete words and sentence fragments are merged into complete sentences. Word fragments may be readily identified by locating characters that fall on opposite sides of a closed-caption pointer which are not separated by an appropriate character such as space. These characters then may be joined to form complete words. Similarly, sentences fragments may be identified by locating words on opposite sides of a closed-caption pointer which are not separated by a character such as a question mark, exclamation mark, or a period. These fragments are then merged into a single sentence. The closed-caption pointer is then adjusted accordingly to include complete words and sentences in the text which are associated with a single representative image.

15 Rather than removing the control characters, the control characters may be replaced with another character or characters that can be properly interpreted in subsequent processing stages such as the text processing stage. For example, a control character that is used to change the font or the color in the closed-caption display window may be replaced with the corresponding font change command used in the text processing package that is employed.

25 The characters transmitted in the closed-caption component of a video program are typically all transmitted in the upper case. Accordingly, in addition to removing or replacing control characters prior to printing the pictorial transcript, it may be desirable to first process the raw text extracted from the closed-caption component to convert some of the upper case characters to lower case in a manner consistent with ordinary printed text.

This processing may be accomplished in a number of ways. For example, the upper case characters may first all be converted to lower case characters. The first character following a punctuation character such as a period or question mark is then capitalized. Finally, many proper nouns that require

- 5 capitalization may be located in an electronically stored dictionary. The text in the example of a pictorial transcript shown in FIG. 3 has been partially processed in this manner. The characters were all converted from upper case to lower case and the first character following a period capitalized. As is apparent from the figure, proper nouns have not been capitalized.



This Sheet Has Been Replaced



CLAIMS:

1. A method of compressing a sequence of frames having at least first and second information-bearing media components, said method comprising the steps of :

5 selecting a plurality of representative frames representing information contained in the first information-bearing media component;

forming a correspondence between each of the representative frames and a segment of the second information-bearing media component; and

recording said representative frames, said segment of the second information-bearing media component and the correspondence therebetween.

10 2. The method of claim 1 wherein the step of selecting representative frames comprises the step of performing a content-based sampling of the sequence of frames to select the representative frames.

3. The method of claim 2 wherein the first information-bearing media component is a video component.

15 4. The method of claim 3 wherein the video component includes a series of scenes and the step of performing a content-based sampling to select the representative frames comprises the step of selecting a representative frame from each scene.

20 5. The method of claim 3 wherein the second information-bearing media component is a closed-caption component.

6. A method of compressing a sequence of visual information-bearing frames having a closed-caption component representing textual information associated therewith, said method comprising the steps of:



dividing the sequence of frames and closed-caption component into a plurality of segments;

retaining a representative frame from each segment;

retaining the closed-caption component of each segment; and

5 recording the representative frame and the closed-caption component for each segment.

7. The method of claim 6 wherein the step of dividing the sequence of frames comprises the step of performing a content-based sampling of the sequence of frames to select the representative frames.

10 8. The method of claim 6 or 7 wherein each segment constitutes a single scene.

9. The method of claim 8 further comprising the step of decoding
15 the closed-caption component.

10. The method of claim 9 further comprising the steps of generating and recording a correspondence table for locating the segment of the closed-caption component associated with each representative frame.

11. The method of claim 10 further comprising the step of generating
20 a printed rendition of the representative frames and closed-caption component for each scene to provide a printed pictorial transcript.



12. The method of claim 10 further comprising
5 the step of displaying the representative frame and closed-
caption component for each scene to provide a pictorial
transcript.

13. An apparatus for compressing a sequence of frames having at
least first and second information-bearing media components, comprising:

means for selecting a plurality of representative frames representing
10 information contained in the first information-bearing media component;


means for forming a correspondence between each of the
representative frames and one of a plurality of segments of the second information-
bearing media component; and

means for recording said representative frames, said plurality of
15 segments of the second information-bearing media component and the
correspondence therebetween.

14. The apparatus of claim 13 wherein the selecting means
comprises means for performing a content-based sampling of the sequence of frames
to select the representative frames.

20 15. The apparatus of claim 14 wherein the selecting means
comprises a scene change detector.

16. The apparatus of claim 14 further comprising means for
decoding the second information-bearing component.

**Abstract****METHOD AND APPARATUS FOR COMPRESSING A SEQUENCE OF
INFORMATION-BEARING FRAMES HAVING AT LEAST TWO MEDIA
COMPONENTS**

5 An apparatus and method for compressing a sequence of frames (from
1) having at least first and second information-bearing media components selects a
plurality of representative frames (by 4) from among the sequence of frames. The
representative frames represent information contained in the first information-
bearing media component. A correspondence is then formed between each of the
10 representative frames and one of a plurality of segments of the second information-
bearing media component. The representative frames, the plurality of segments of
the second information-bearing media component (from 5) and the correspondence
between them are recorded (in 9 or 10) for subsequent retrieval. If the first
information-bearing media component is a video component composed of a plurality
15 of scenes, a representative frame may be selected from each scene. Additionally, if
the second information-bearing media component is a closed-caption component, a
printed rendition of the representative frames and the closed-caption component may
be provided (by 12). The printed rendition constitutes a pictorial transcript in which
each representative frame is printed with a caption containing the closed-caption text
20 associated therewith.

FIG. 1




FIG. 2




FIG. 3




>>UNITED NATIONS
ENVOY ROLF EKEUS SAID
TODAY HE HAD RESOLVED
THE DISPUTE WITH IRAQ
OVER WEAPONS MONITORING
HE GAVE NO DETAILS, BUT
SAID THERE WAS NO LONGER

ANY REASON FOR MILITARY ACTION.
WE HAVE A REPORT FROM
BAGHDAD BY ROBERT MOORE OF
OF INDEPENDENT TELEVISION NEWS



>>IT WAS A FINAL DIPLOMATIC
MISSION, AN ATTEMPT TO MEND
THE FRAYING RELATIONSHIP
BETWEEN IRAQ AND THE UNITED
NATIONS




THIS MORNING, AFTER FOUR
DAYS OF TOUGH TALKING AND
BRINKMANSHIP, IRAQ APPEARS
TO HAVE MADE THE CRUCIAL
CONCESSION, TARIQ AZIZ,

IRAQ'S DEPUTY PRIME MINISTER, AGREEING TO
THE CONCEPT'S OF LONG-TERM MONITORING OF
THE COUNTRY'S WEAPONS SYSTEMS.



FOR ROLF EKEUS, THE
SATISFACTION HE HAS
ALMOST CERTAINLY
AVERTED U.N.-BACKED
MILITARY ACTION
AGAINST IRAQ.



OTHER ISSUES REMAIN IN
DISPUTE, BUT A NEW
FRAMEWORK FOR SETTTLING
THEM IS NOW SAID TO
BE IN PLACE



>> I WOULDN'T SAY
THAT WE HAVE A CLEAR-
CUT SETTLEMENT, BUT
I THINK WE ARE ON THE
WAY TO BREAK OUT OF
THAT ALMOST QUITE
DANGEROUS,DANGEROUS
SITUATION.



>> FOR THE LAST TWO
WEEKS, ORDINARY IRAQIS
HAVE BEEN LIVING IN
FEAR OF A FRESH MISSILE
OR AIR ATTACK, BUT WITH
THE CRISIS DEFUSED AND
COMPLIANCE AGREED ON, THERE IS NOW
GROWING HOPE THE U.N. WILL CONSIDER
LIFTING SANCTIONS.

Abstract**METHOD AND APPARATUS FOR COMPRESSING A SEQUENCE OF
INFORMATION-BEARING FRAMES HAVING AT LEAST TWO MEDIA
COMPONENTS**

An apparatus and method for compressing a sequence of frames (from 1) having at least first and second information-bearing media components selects a plurality of representative frames (by 4) from among the sequence of frames. The representative frames represent information contained in the first information-bearing media component. A correspondence is then formed between each of the representative frames and one of a plurality of segments of the second information-bearing media component. The representative frames, the plurality of segments of the second information-bearing media component (from 5) and the correspondence between them are recorded (in 9 or 10) for subsequent retrieval. If the first information-bearing media component is a video component composed of a plurality of scenes, a representative frame may be selected from each scene. Additionally, if the second information-bearing media component is a closed-caption component, a printed rendition of the representative frames and the closed-caption component may be provided (by 12). The printed rendition constitutes a pictorial transcript in which each representative frame is printed with a caption containing the closed-caption text associated therewith.

(**Figure 1**)

This is the replacement sheet

Date: 14 JUL 1998

**CLAIMS:**

1. A method of compressing a sequence of frames having at least first and second information-bearing media components, said method comprising the steps of :

selecting a plurality of representative frames wherein said representative frames represent information contained in the first information-bearing media component;

forming an association between each of the representative frames and a segment of the second information-bearing media component; and

recording said representative frames, said segment of the second information-bearing media component and the association therebetween.
2. The method of claim 1 wherein the step of selecting representative frames comprises the step of performing a content-based sampling of the sequence of frames to select the representative frames.
3. The method of claim 2 wherein the first information-bearing media component is a video component.
4. The method of claim 3 wherein the video component includes a series of scenes and the step of performing a content-based sampling to select the representative frames comprises the step of selecting a representative frame from each scene.
5. The method of claim 3 wherein the second information-bearing media component is a closed-caption component.
6. A method of compressing a sequence of visual information-bearing frames having a closed-caption component representing textual information associated therewith, said method comprising the steps of:

This is the replacement sheet

Date: 20 JAN 1999