

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
31 December 2008 (31.12.2008)

PCT

(10) International Publication Number
WO 2009/000070 A8

(51) International Patent Classification:

F21V 7/00 (2006.01) *G02B 5/08* (2006.01)*F21S 11/00* (2006.01) *G02B 5/12* (2006.01)

(21) International Application Number:

PCT/CA2008/001144

(22) International Filing Date:

16 June 2008 (16.06.2008)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/945,653 22 June 2007 (22.06.2007) US

(71) Applicant (for all designated States except US): **THE UNIVERSITY OF BRITISH COLUMBIA** [CA/CA]; c/o Industry Liaison Office, 103 - 6190 Agronomy Road, Vancouver, British Columbia V6T 1Z3 (CA).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WHITEHEAD, Lorne, A.** [CA/CA]; 3015 West 12th Avenue, Vancouver, British Columbia V6K 2R4 (CA). **SCOTT, Jon, David, Edward** [CA/CA]; Unit 4, 7 East 6 Avenue, Vancouver, British Columbia V5T 1J3 (CA).(74) Agent: **WIGGS, Blake, R.**; Oyen Wiggs Green & Mutala LLP, Suite 480 - The Station, 601 West Cordova Street, Vancouver, British Columbia V6B 1G1 (CA).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG,

[Continued on next page]

(54) Title: ADAPTIVE SUNLIGHT REDIRECTOR




FIGURE 2B

(57) Abstract: Longitudinally adjacent plane mirrors (106—114) are pivotally interconnected in a columnar array (56) by non-stretching linkages (120) which constrain movement of the mirrors such that their normal vectors (115) remain parallel. Pivotal couplings (122, 124) in two mirrors permit movement of the mirrors with respect to mutually perpendicular axes (x , y) and prevent movement of the mirrors with respect to a third axis (z). Two actuators (117A, 117B) coupled to one of the pivotal couplings controllably move a selected mirror with respect to the mutually perpendicular axes (x , y). A first frame (116) couples the mirror columns together so that movement of the selected mirror moves all the mirrors in unison. The actuators controllably move the mirrors to orient the normal vectors such that the mirrors specularly reflect incident light in a preselected direction.



SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG,
US, UZ, VC, VN, ZA, ZM, ZW.

Published:

— with international search report (Art. 21(3))

- (84) Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

- (48) Date of publication of this corrected version:**

10 December 2009

- (15) Information about Correction:**

see Notice of 10 December 2009