

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
25 October 2018 (25.10.2018)



(10) International Publication Number
WO 2018/194981 A1

- (51) **International Patent Classification:**
H04L 1/16 (2006.01) **H04L 1/18** (2006.01)
- (21) **International Application Number:**
PCT/US2018/027802
- (22) **International Filing Date:**
16 April 2018 (16.04.2018)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
62/486,412 17 April 2017 (17.04.2017) US
62/517,148 08 June 2017 (08.06.2017) US
15/953,115 13 April 2018 (13.04.2018) US
- (71) **Applicant: QUALCOMM INCORPORATED** [US/US];
ATTN: International IP Administration, 5775 Morehouse
Drive, San Diego, CA 92121-1714 (US).
- (72) **Inventors: TRAININ, Solomon**; 5775 Morehouse Drive,
San Diego, CA 92121-1714 (US). **HAY, Ran**; 5775 More-
house Drive, San Diego, CA 92121-1714 (US). **EITAN,**
Alecsander Petru; 5775 Morehouse Drive, San Diego, CA
92121-1714 (US).
- (74) **Agent: WORLEY, Eugene**; Loza & Loza, LLP, 305 North
Second Avenue #127, Upland, CA 91786 (US).
- (81) **Designated States** (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO,

DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP,
KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) **Title:** FLOW CONTROL FOR WIRELESS DEVICES

1100

Element ID	Length	Memory config tag	RBUF_ Unit_Size	Recipient Memory Multiple Buffer Units			TID grouping																		
				Mem_ Unit_ Size	Max MPDU_ per MemUnit	Mult_ Buff MPDU	TID/TSID																		
							0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15			
Octets	1	1	1	2	2	1	1																		

FIG. 11

(57) **Abstract:** Systems and methods are provided for flow control in a wireless communication system. In certain aspects, an apparatus for wireless communications comprises an interface configured to receive, from a wireless node, one or more parameters specifying a memory at the wireless node, and an indication of an amount of free memory space in the memory at the wireless node. The apparatus also comprises a processing system configured to determine a number of data units to be transmitted to the wireless node based on the indication of the amount of free memory space and the one or more parameters, wherein the interface is further configured to output data units for transmission to the wireless node, wherein a number of the data units output for transmission to the wireless node equals the determined number of data units.