

(19) World Intellectual Property Organization
International Bureau



G00002

(43) International Publication Date
18 April 2002 (18.04.2002)

PCT

(10) International Publication Number
WO 02/031611 A3


- (51) International Patent Classification⁷: **G05D 7/01**
- (21) International Application Number: PCT/US01/31727
- (22) International Filing Date: 11 October 2001 (11 10.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/239,716 11 October 2000 (11 10.2000) US
09/805,708 13 March 2001 (13 03.2001) US
- (71) Applicant: **FLOWMATRIX, INC.** [US/US]; 2461 Impala Drive, Carlsbad, CA 92008 (US)
- (72) Inventors: **THORDARSON, Petur**; 2461 Impala Drive, Carlsbad, CA 92008 (US) **LOWERY, Patrick, A.**; 2461 Impala Drive, Carlsbad, CA 92008 (US)
- (74) Agent: **GRAY III, Gordon, E.**, Price and Gess, 2100 S.E. Main Street, Suite 250, Irvine, CA 92614 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

[Continued on next page]

(54) Title: VARIABLE PRESSURE REGULATED FLOW CONTROLLERS

(57) Abstract: A flow controller having a first and second stages of regulation. The first stage is a pressure regulation stage that maintains the pressure within an intermediate chamber (formed by a series of interconnected passageways and cavities) within a predetermined range above the pressure in an outlet port. The second stage maintains the flow rate within a predetermined range about a target flow rate. Both stages sample the pressure in the outlet port and automatically adjust the flow of fluid to ensure that fluctuations in pressure at the inlet and outlet ports do not affect the flow rate. The flow rate is set and controlled by a user determined setpoint. The flow rate is set and controlled by a user determined setpoint. The pressure is regulated by one or more feedback systems. The feedback systems used may be mechanical or electromechanical based on a particular operating environment.

162162



WO 02/031611 A3

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette

(88) Date of publication of the international search report:

1 August 2002