



(51) International Patent Classification:

H04L 12/905 (2013.01)

(21) International Application Number:

PCT/US2014/020440

(22) International Filing Date:

4 March 2014 (04.03.2014)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

13/784,814 4 March 2013 (04.03.2013) US

61/772,530 4 March 2013 (04.03.2013) US

(71) Applicant: THERANOS, INC. [US/US]; 1601 S. California Ave., Palo Alto, CA 94304 (US).

(72) Inventor: BALWANI, Sunny; 1601 S. California Avenue, Palo Alto, CA 94304 (US).

(74) Agent: TUNG, Hao, Y.; 1601 S. California Ave., Palo Alto, CA 94304 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

[Continued on next page]

(54) Title: NETWORK CONNECTIVITY METHODS AND SYSTEMS




FIG. 1

(57) Abstract: Methods and systems are provided for connecting an electronic device to a network. In some situations, the electronic device connects to a first network provider and pings a first server having a static internet protocol address and a second server having a dedicated uniform resource locator. If the electronic device receives a response from the first and second server, the electronic device maintains its connection to the first network provider. Otherwise, the electronic device connects to a second network provider and pings the first and second servers.

(88) Date of publication of the international search report:
30 October 2014