



(43) International Publication Date
22 May 2014 (22.05.2014)

- (51) International Patent Classification:
E21B 17/10 (2006.01)
- (21) International Application Number:
PCT/GB2013/053007
- (22) International Filing Date:
14 November 2013 (14.11.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
1220665.2 16 November 2012 (16.11.2012) GB
1220774.2 19 November 2012 (19.11.2012) GB
- (71) Applicant: NATIONAL OILWELL VARCO UK LIMITED [GB/GB]; Martin Street, Audenshaw, Manchester M34 5JA (GB).
- (72) Inventors: WOOD, Carl; Cattie Farmhouse, Whitehouse, Alford Aberdeenshire AB33 8DR (GB). O'BRIEN, Harry Richard Stanley; 11 Straik Road, Elrick Aberdeenshire AB32 6JN (GB).
- (74) Agent: MURGITROYD & COMPANY; Scotland House, 165-169 Scotland Street, Glasgow Glasgow G5 8PL (GB).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

- (88) Date of publication of the international search report:
27 November 2014

(54) Title: ROLLER DEVICE




FIG. 3

(57) Abstract: A roller device for incorporation into a wireline tool string for use in an oil or gas well has a body with rollers comprising captive bearings arranged on the outer surface of the body to rotate around more than one axis relative to the body, and wherein the rollers are arranged in at least one or more helix around the body. Each helix completes at least one full circumferential turn around the body. The rollers circumferentially overlap one another on the body, so that when the body engages the inner wall of the wellbore, the entire circumference of the body is supported by at least one roller.



WO 2014/076481 A3