(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
6 September 2002 (06.09.2002)

PCT

(10) International Publication Number
WO 02/068722 A2

(51) International Patent Classification[7]: C25B 11/04, 1/26

(21) International Application Number: PCT/EP02/02205

(22) International Filing Date: 28 February 2002 (28.02.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
MI2001A000402 28 February 2001 (28.02.2001) IT

(71) Applicant *(for all designated States except US)*: **DE NORA ELETTRODI S.P.A.** [IT/IT]; Via Dei Canzi, 1, I-20134 Milan (IT).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: **MARTELLI, Gian, Nicola** [IT/IT]; Via Cadorno, 59, I-20090 Vimodrone (IT). **FULVIO, Federico** [IT/IT]; Via Scalabrini, 4, I-29100 Piacenza (IT).

(74) Agents: **KINZEBACH, Werner** et al.; Reitstötter, Kinzebach & Partner, Sternwartstr. 4, 81679 München (DE).


(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: NEW ELECTROCATALYTIC COMPOSITION FOR OXYGEN-DEPOLARISED CATHODE



(57) Abstract: An oxygen-depolarised cathode for aqueous hydrochloric acid electrolysis membrane cells is described, the cathode being in contact with the membrane and capable of preventing the release of hydrogen into oxygen even at the highest current densities. Hydrochloric acid may also be of technical grade with a concentration limited to 15%, whereas the operating temperature must not exceed 60 °C. The cathode contains a mixture of rhodium sulphide and a metal of the platinum group applied in a single layer or alternatively applied separately in two distinct layers.

WO 02/068722 A2